

# INDEX OF SHEETS

SEE SHEET 2

## STATE OF TEXAS DEPARTMENT OF TRANSPORTATION

### PLANS OF PROPOSED STATE HIGHWAY IMPROVEMENT



PROJECT NO. C 1685-5-115  
CSJ: 1685-05-115  
**SH 6**  
**HARRIS COUNTY**

LIMITS: 560.0 FEET NORTH OF BELLAIRE BLVD. TO THE HARRIS / FORT BEND COUNTY LINE  
NET LENGTH OF PROJECT= ROADWAY 7,345.00 FT  
BRIDGE 0.00 FT  
TOTAL 7,345.00 FT=1.391 MI

FOR THE CONSTRUCTION OF AN OVERLAY, CONSISTING OF PLANING, SEAL COAT,  
1" TOM-F, 1" TOM-C OVERLAY, AND PAVEMENT MARKINGS.

FED. ROAD DIV. NO.	STATE	PROJECT NO.			SHEET NO.
6	TEXAS	C 1685-5-115			1
STATE DIST. NO.	COUNTY	CONT.	SECT.	JOB	HIGHWAY NO.
HOU	HARRIS	1685	05	115	SH 6

DESIGN SPEED= 50 MPH  
ADT (2021) = 56,500  
ADT (2041) = 79,700



BEGIN PROJECT  
CSJ 1685-05-115  
STA. 961+00.00  
M. P. = 15.928  
TRM = 678+0.781  
DFO = 496.405

END PROJECT  
CSJ 1685-05-115  
STA. 1034+45.00  
M. P. = 17.319  
TRM = 680+0.299  
DFO = 497.796

EXCEPTIONS: NONE  
EQUATIONS: NONE  
RR CROSSINGS: NONE

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND THE SPECIFICATION ITEM LISTED AS FOLLOWS SHALL GOVERN ON THIS PROJECT: REQUIRED LABOR PROVISION FOR STATE PROJECTS: SP000---008

© 2020 BY Texas Department OF Transportation; ALL RIGHTS RESERVED.

**Texas Department of Transportation**  
© 2020 BY TEXAS DEPARTMENT OF TRANSPORTATION ALL RIGHTS RESERVED

SUBMITTED FOR LETTING: 10/30/2020

P.E.  
AREA ENGINEER

RECOMMENDED FOR LETTING: 11/3/2020

DocuSigned by:  
 P.E.  
For DISTRICT ENGINEER

COUNTY: HARRIS PROJ. NO. \_\_\_\_\_  
HWY. NO. SH 6 LETTING DATE: JAN 2021  
DATE ACCEPTED \_\_\_\_\_


# INDEX OF SHEETS


SHEET NO.	DESCRIPTION	SHEET NO.	DESCRIPTION
I. GENERAL		III. ROADWAY DETAILS	
1	TITLE SHEET	42-47	PLAN LAYOUT SH 6
2	INDEX OF SHEETS	48	INTERSECTION DETAILS
3-4	TYPICAL SECTION	IV. TRAFFIC ITEMS	
5-12, 12A	GENERAL NOTES AND SPECIFICATION DATA	49-54	PAVEMENT MARKINGS LAYOUT SH 6
13-14	ESTIMATE AND QUANTITY SHEET	55	* PM -20 (HOU DIST)
15-17	SUMMARY OF QUANTITIES	56	* PM (2) -20
18	SUMMARY OF QUANTITIES-TRAFFIC SIGNAL	57	* PM (3) -20
19	IRI DATA	58	* PM (CLL) -14 (HOU DIST)
II. TRAFFIC CONTROL PLAN		59	* PM (DOT) -11 (HOU DIST)
20	TCP-ONE & TWO LANE CLOSURE	60	* PM(WAS)-07 (HOU DIST)
21	TCP-CENTER LANE CLOSURE AT INTERSECTION	61	TRAFFIC SIGNAL NOTES SH 6 AT BELLAIRE BLVD/BEECHNUT ST
22	* TCP(3-1) -13	62	TRAFFIC SIGNAL EXISTING LAYOUT SH 6 AT BELLAIRE BLVD
23	* TCP(3-3) -14	63, 63A	TRAFFIC SIGNAL PROPOSED LAYOUT SH 6 AT BELLAIRE BLVD
24	* TCPTC 3050 -96 (HOU DIST)	64	TRAFFIC SIGNAL EXISTING LAYOUT SH 6 AT BEECHNUT ST
25	* BC (1) -14	65, 65A	TRAFFIC SIGNAL PROPOSED LAYOUT SH 6 AT BEECHNUT ST
26	* BC (2) -14	66	* ED(1)-14
27	* BC (3) -14	67	* ED(3)-14
28	* BC (4) -14	V. ENVIRONMENTAL ISSUES	
29	* BC (5) -14	68	EPIC - HOU DIST
30	* BC (6) -14	69	SWP3 - HOU DIST
31	* BC (7) -14	70	EC(1)-16(MOD)
32	* BC (8) -14		
33	* BC (9) -14		
34	* BC (10) -14		
35	* BC (11) -14		
36	* BC (12) -14		
37	* WZ (STPM) -13		
38	* WZ (UL) -13		
39	* WZ (BRK) -13		
40	* WZ (BTS-1) -13		
41	* WZ (BTS-2) -13		

LEVELS DISPLAYED  
 1 3 4 15 16 17 18 19 1 01 11 21 31 41 51 6  
 7 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63

THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ABOVE (\*)  
 HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE  
 SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.


 , PE      11/2/2020  
 DATE




©2020


## INDEX OF SHEETS

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			2
STATE	DIST.	COUNTY	
TEXAS	HOU	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6



**EXISTING TYPICAL SECTION**  
 STA. 961+00.00 TO STA. 1034+45.00 (7,345.00')

DIR: FILE: 1685050731108sec1.dwg  
 LEVELS DISPLAYED:  
 1 13.14 15.16 17.18 19.19 21.21 23.23 25.25 27.27 29.29 31.31 33.33 35.35 37.37 39.39 41.41 43.43 45.45 47.47 49.49 51.51 53.53 55.55 57.57 59.59 61.61 63.63 65.65 67.67 69.69 71.71 73.73 75.75 77.77 79.79 81.81 83.83 85.85 87.87 89.89 91.91 93.93 95.95 97.97 99.99



*B. Kwater, P.E.*  
10/1/20

N. T. S.

**Texas Department of Transportation** ©2020

**SH 6**  
**EXISTING TYPICAL SECTION**  
 SHEET 1 OF 2


FED. RD. DIV. NO.	PROJECT NO.	SHEET NO.
6		3
STATE	DIST.	COUNTY
TEXAS	HOU	HARRIS
CONT.	SECT.	JOB
1685	05	115
		HIGHWAY NO.
		SH 6

EXIST. R.O.W.

EXIST. R.O.W.

CL (SH 6)

180'-0" MAX. - 160'-0" MIN.





\*RAISED MEDIAN VARIES FROM 2'-0" TO 14'-0"

### PROPOSED TYPICAL SECTION

STA. 961+00.00 TO STA. 1034+45.00 (7,345.00')

STA. 1032+00.00.00 TO STA. 1034+45.00 (PAVEMENT MARKING ONLY)

FOR THIS TYPICAL SECTION, PAY SCHEDULE 2 WILL BE USED FOR ITEM, "RIDE QUALITY FOR PAVEMENT SURFACE".



*B. Kwater, P.E.*  
10/1/20

N. T. S.

Texas Department of Transportation ©2020

SH 6  
PROPOSED TYPICAL SECTION

SHEET 2 OF 2

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			4
STATE	DIST.	COUNTY	
TEXAS	HOU.	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6

LEVELS DISPLAYED

DIR: FILE: 1685050731.XDRG(1).DGN

1 131415 617181910111213141516  
 17181920212223242526272829303132  
 3334353637383940414243444546  
 47484950515253545556575859606162  
 63646566676869707172737475767778798081828384858687888990919293949596979899100

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

**General Notes:**

**General:**

Contractor questions on this project are to be addressed to the following individuals:

*Area Engineer: Frank Leong, P.E. e-mail: Frank.Leong@txdot.gov*  
*Assistant Area Engineer :Hamoon Bahrami, P.E. e-mail: Hamoon.Bahrami@txdot.gov*

Contractor questions will be accepted through email, phone, and in person by the above individuals. Contractor questions will be reviewed by the Area Engineer or Assistant Area Engineer. Once a response is developed, it will be posted to TxDOT's Public FTP at the following address:

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting Responses/>

Questions submitted that generate a response will be posted through this site. The site is organized by District, Project Type (Construction or Maintenance), Letting Date, and CCSJ/Project Name.

Unless otherwise shown on the plans, RAP generated by this project will become the property of the Contractor for use in the current construction project or in future projects.

If fixed features require, the governing slopes shown may vary between the limits shown and to the extent determined by the Engineer.

Superelevate the curves to match the existing surface.

The following standard detail sheets are modified:

**Modified Standards**

EC (1) -16 (MOD)

References to manufacturer's trade name or catalog numbers are for the purpose of identification only. Similar materials from other manufacturers are permitted if they are of equal quality, comply with the specifications for this project, and are approved, except for roadway illumination, electrical, and traffic signal items.

The cost for materials, labor, and incidentals to provide for traffic across the roadway and for ingress and egress to private property in accordance with Section 7.2.4 of the standard specifications is subsidiary to the various bid items. Restore access roadways to their original condition upon completing construction.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Tolls incurred by the Contractor are incidental to the various bid items.

Procure permits and licenses, which are to be issued by the City, County, or Municipal Utility District.

**General: Roadway Illumination and Electrical**

For roadway illumination and electrical items, use materials from pre-qualified producers as shown on the Construction Division (CST) of the Department's material producers list. Check the latest link on the Department's website for this list. The category/item is "Roadway Illumination and Electrical Supplies." No substitutions will be allowed for materials found on this list.

Perform electrical work in conformance with the National Electrical Code (NEC) and the Department's standard sheets.

**General: Traffic Signals**

For traffic signal items, use materials from the Pre-Qualified Producers List (located at <http://www.dot.state.tx.us/GSD/purchasing/supps.htm>) and the materials pre-qualified for illumination and electrical items (located at <http://ftp.dot.state.tx.us/pub/txdot-info/cmd/mpl/riaes.pdf>) as shown on the Department's Material Producers List and the Roadway Illumination and Electrical Supplies List. Check the latest links on the Department's website for these lists. No substitutions will be allowed for materials found on these lists.

**General: Site Management**

Mark stations every 100 ft. and maintain the markings for the project duration. Remove the station markings at the completion of the project. This work is subsidiary to the various bid items.

Do not mix or store materials, or store or repair equipment, on top of concrete pavement or bridge decks unless authorized by the Engineer. Permission will be granted to store materials on surfaces if no damage or discoloration will result.

Personal vehicles of employees are not permitted to park within the right of way, including sections closed to public traffic. Employees may park on the right of way at the Contractor's office, equipment, and materials storage yard sites.

Assume ownership of debris and dispose of at an approved location. Do not dispose of debris on private property unless approved in writing by the District Engineer.

Control the dust caused by construction operations. For sweeping the base material in preparation for laying asphalt and for sweeping the finished concrete pavement, use one of the following types of sweepers or approved equal:

County: Harris

Control: 1685-05-115

Highway: SH 6

**Tricycle Type**

Wayne Series 900  
Elgin White Wing  
Elgin Pelican

**Truck Type - 4 Wheel**

M-B Cruiser II  
Wayne Model 945  
Mobile TE-3  
Mobile TE-4  
Murphy 4042

**General: Traffic Control and Construction**

The Seal coat (Item 316) will be covered with the Thin Overlay Mixture (TOM) (Item 347) level-up prior to reopening to traffic each day. The roadway will not be opened to traffic until the TOM and work zone pavement markings are in place.

When design details are not shown on the plans, provide signs and arrows conforming to the latest "Standard Highway Sign Designs for Texas" manual.

In the case of an emergency, the Engineer may allow traffic on the roadway before the asphalt overlay is in place. The roadway surface will be cleaned by removing all loose matter resulting from the construction operations.

Verify that all conditions under Item 502 are met before beginning work every day that work occurs.

**General: Utilities**

Consider the locations of underground utilities and employ responsible care to avoid damaging utility facilities. Depending upon scope and magnitude of planned construction activities, advanced field confirmation by the utility owner or operator may be prudent. Where possible, protect and preserve permanent signs, markers, and designations of underground facilities.

If the Contractor damages or causes damage (breaks, leaks, nicks, dents, gouges, etc.) to the utility, contact the utility facility owner or operator immediately.

Be aware that an operational Computerized Transportation Management System (CTMS) exists within the limits of this project and that the system must remain operational throughout construction. If the Contractor damages or cause damage to this system, repair such damage within 8 hours of occurrence at no cost to the Department. In the event of system damage, notify the Director of Traffic Management Systems at 713-881-3283 within one hour of occurrence. Failure of the Contractor to repair damage to the main fiber optic cable and CCTV cable trunk lines, which convey all corridor information to TranStar, will result in the Contractor being billed for the full cost of emergency repairs.

At least 72 hours before starting work, make arrangements for locating existing Department-owned above ground and underground fiber optic, communications, power, illumination, and

County: Harris

Control: 1685-05-115

Highway: SH 6

traffic signal cabling and conduit. Do this by calling the Department's Houston District Traffic Signal Operations Office at 713-802-5663 to schedule marking of underground lines on the ground. Use caution if working in these areas to avoid damaging or interfering with existing facilities.

If overhead or underground power lines need to be de-energized, contact the electrical service provider to perform this work. Costs associated with de-energizing the power lines or other protective measures required are at no expense to the Department.

If working near power lines, comply with the appropriate sections of Texas State Law and Federal Regulations relating to the type of work involved.

Perform electrical work in conformance with the National Electrical Code (NEC) and Department standard sheets.

Before beginning any underground work, notify the City of Houston's Chief Inspector, Public Works and Engineering, to establish the locations of any existing electrical systems for lighting facilities within the limits of this project.

**Item 5: Control of Work**

Submit shop drawings electronically for the fabrication of items as documented in Table 1 below. Information and requirements for electronic submittals can be viewed in the "Guide to Electronic Shop Drawing Submittal" which can be accessed through the following web link, [ftp://ftp.dot.state.tx.us/pub/txdot-info/library/pubs/bus/bridge/e\\_submit\\_guide.pdf](ftp://ftp.dot.state.tx.us/pub/txdot-info/library/pubs/bus/bridge/e_submit_guide.pdf).

References to 11 in. x 17 in. sheets in individual specifications for structural items imply electronic CAD sheets.

**Table 1**  
**2014 Construction Specification Required Shop/Working Drawing Submittals - TxDOT Generated Plans**

Spec Item No.'s	Product	Submittal Required	Approval Required (Y/N)	Contractor/Fabricator P.E. Seal Required	Reviewing Party	Shop or Working Drawing (Note 1)
7.16.1&2	Construction Load Analyses	Y	Y	Y	B	WD
400	Excavation and Backfill for Structures (cofferdams)	Y	N	Y	A	WD
403	Temporary Special Shoring	Y	N	Y	C	WD
420	Formwork/Falsework	Y	N	Y	A	WD
423	Retaining Walls, (calcs req'd.)	Y	Y	Y	C	SD
425	Optional Design Calculations (Prstrs Bms)	Y	Y	Y	B	SD
425	Prestr Concr Sheet Piling	Y	Y	N	B	SD
425	Prestr Concr Beams	Y	Y	N	B	SD
425	Prestr Concr Bent	Y	Y	N	B	SD
426	Post Tension Details	Y	Y	N	B	SD
434	Elastomeric Bearing Pads (All)	Y	Y	N	B	SD

County: Harris

Control: 1685-05-115

Highway: SH 6

441	Bridge Protective Assembly	Y	Y	N	B	SD
441	Misc Steel (various steel assemblies)	Y	Y	N	B	SD
441	Steel Pedestals (bridge raising)	Y	Y	N	B	SD
441	Steel Bearings	Y	Y	N	B	SD
441	Steel Bent	Y	Y	N	B	SD
441	Steel Diaphragms	Y	Y	N	B	SD
441	Steel Finger Joint	Y	Y	N	B	SD
441	Steel Plate Girder	Y	Y	N	B	SD
441	Steel Tub-Girders	Y	Y	N	B	SD
441	Erection Plans, including Falsework	Y	N	Y	A	WD
449	Sign Structure Anchor Bolts	Y	Y	N	T	SD
450	Railing	Y	Y	N	A	SD
462	Concrete Box Culvert	Y	Y	N	C	SD
462	Concrete Box Culvert (Alternate Designs Only, calcs reqd.)	Y	Y	Y	B	SD
464	Reinforced Concrete Pipe (Jack and Bore only; ONLY when requested)	Y	Y	Y	A	SD
465	Pre-cast Junction Boxes, Grates, and Inlets	Y	Y	N	A	SD
465	Pre-cast Junction Boxes, Grates, and Inlets (Alternate Designs Only, calcs req'd.)	Y	Y	Y	B	SD
466	Pre-cast Headwalls and Wingwalls	Y	Y	N	A	SD
467	Pre-cast Safety End Treatments	Y	Y	N	A	SD
495	Raising Existing Structure (calcs reqd.)	Y	Y	Y	B	SD
610	Roadway Illumination Supports (Non-Standard only, calcs reqd.)	Y	Y	Y	BRG	SD
613	High Mast Illumination Poles (Non-standard only, calcs reqd.)	Y	Y	Y	BRG	SD
627	Treated Timber Poles	Y	Y	N	T	SD
644	Special Non-Standard Supports (Bridge Mounts, Barrier Mounts, Etc.)	Y	Y	Y	T	SD
647	Large Roadside Sign Supports	Y	Y	Y	T	SD
650	Cantilever Sign Structure Supports - Alternate Design Calcs.	Y	Y	Y	T	SD
650	Sign Structures	Y	Y	N	T	SD
680	Installation of Highway Traffic Signals	Y	Y	N	T	SD
682	Vehicle and Pedestrian Signal Heads	Y	Y	N	T	SD
684	Traffic Signal Cables	Y	Y	N	T	SD
685	Roadside Flashing Beacon Assemblies	Y	Y	N	T	SD
686	Traffic Signal Pole Assemblies (Steel) (Non-Standard only)	Y	Y	Y	T	SD
687	Pedestal Pole Assemblies	Y	Y	N	T	SD
688	Detectors	Y	Y	N	A	SD
784	Repairing Steel Bridge Members	Y	Y	Y	B	WD
SS	Prestr Concr Crown Span	Y	Y	N	B	SD
SS	Sound Barrier Walls	Y	Y	Y	A	SD

County: Harris

Control: 1685-05-115

Highway: SH 6

SS	Camera Poles	Y	Y	Y	TMS	SD
SS	Pedestrian Bridge (Calcs req'd.)	Y	Y	Y	B	SD
SS	Screw-In Type Anchor Foundations	Y	Y	N	T	SD
SS	Fiber Optic/Communication Cable	Y	Y	N	TMS	SD
SS	Spread Spectrum Radios for Signals	Y	Y	N	T	SD
SS	VIVDS System for Signals	Y	Y	N	T	SD
SS	CTMS Equipment	Y	Y	N	TMS	SD

Notes:

- Document flow for Working Drawings differs from Shop Drawings in that Working Drawings must be submitted to the Engineer rather than the Engineer of Record and they are for the information of the Engineer only; an approval stamp and distribution to all project offices is not required.

Key to Reviewing Party

A - Area Office	
<b>Area Office</b>	<b>Email Address</b>
Brazoria Area Office	<a href="mailto:HOU-BRZAShpDrwgs@txdot.gov">HOU-BRZAShpDrwgs@txdot.gov</a>
Fort Bend Area Office	<a href="mailto:HOU-FBAShpDrwgs@txdot.gov">HOU-FBAShpDrwgs@txdot.gov</a>
Galveston Area Office	<a href="mailto:HOU-GALVAShpDrwgs@txdot.gov">HOU-GALVAShpDrwgs@txdot.gov</a>
Montgomery Area Office	<a href="mailto:HOU-MONTAShpDrwgs@txdot.gov">HOU-MONTAShpDrwgs@txdot.gov</a>
North Harris Area Office	<a href="mailto:HOU-NHAShpDrwgs@txdot.gov">HOU-NHAShpDrwgs@txdot.gov</a>
Southeast Area Office	<a href="mailto:HOU-SEHAShpDrwgs@txdot.gov">HOU-SEHAShpDrwgs@txdot.gov</a>
Traffic Systems Construction Office	<a href="mailto:HOU-TSCShpDrwgs@txdot.gov">HOU-TSCShpDrwgs@txdot.gov</a>
West/Central Harris Area Office	<a href="mailto:HOU-WWCHAOShpDrwgs@txdot.gov">HOU-WWCHAOShpDrwgs@txdot.gov</a>
B - Houston Bridge Engineer	
Bridge Design (Houston TxDOT)	<a href="mailto:HOU-BrgShpDrwgs@txdot.gov">HOU-BrgShpDrwgs@txdot.gov</a>
BRG - Austin Bridge Division	
Bridge Design (Austin TxDOT)	<a href="mailto:BRG_ShopPlanReview@txdot.gov">BRG_ShopPlanReview@txdot.gov</a>
C - Construction Office	
Construction	<a href="mailto:HOU-ConstrShpDrwgs@txdot.gov">HOU-ConstrShpDrwgs@txdot.gov</a>
Laboratory	<a href="mailto:HOU-LabShpDrwgs@txdot.gov">HOU-LabShpDrwgs@txdot.gov</a>
T - Traffic Engineer	
Traffic Operations	<a href="mailto:HOU-TrfShpDrwgs@txdot.gov">HOU-TrfShpDrwgs@txdot.gov</a>
TMS - Traffic Management System	
Computerized Traffic Management Systems (CTMS)	<a href="mailto:HOU-CTMSShpDrwgs@txdot.gov">HOU-CTMSShpDrwgs@txdot.gov</a>

Item 7: Legal Relations and Responsibilities

This project does not require a U.S. Army Corps of Engineers (USACE) Section 404 Permit before letting, but if a permit is needed during construction, assume responsibility for preparing the permit application. Submit the permit application to the Department's District Environmental Section for approval. Once the permit application is approved, the Department will submit it to the USACE. Assume responsibility for the requested revisions, in coordination with the Department's District Environmental Section.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Maintain the roadway slope stability. Maintaining slope stability is subsidiary to the various bid items.

No significant traffic generator events identified.

**Item 8: Prosecution and Progress**

The Department will supply bidders, upon written request, one electronic copy of the time determination schedule. The time determination schedule provided is for informational use only and is not intended for bidding or construction purposes.

The Department will not adjust the number of days for the project and milestones, if any, due to differences in opinion regarding any assumptions made in the preparation of the schedule or for errors, omissions, or discrepancies found in the time determination schedule.

Working days will be computed and charged based on a 5-day workweek in accordance with Section 8.3.1.6 and Article 8.3.3.1, with nighttime work.

A working day will be charged Monday through Friday, excluding national holidays, regardless of weather conditions or material availability. Nighttime work that extends past midnight will be charged to the following day. Work on national holidays will not be permitted without written permission of the Engineer. If work requiring an Inspector to be present is performed on a national holiday, and weather and other conditions permit the performance of work for 7 hours between 10:00 p.m. and 5:00 a.m., a working day will be charged.

Allowable work times are as follows:

Sunday 10:00 p.m. – Monday 5:00 a.m.

Monday 10:00 p.m. – Tuesday 5:00 a.m.

Tuesday 10:00 p.m. – Wednesday 5:00 a.m.

Wednesday 10:00 p.m. – Thursday 5:00 a.m.

Thursday 10:00 p.m. – Friday 5:00 a.m.

The Lane Closure Assessment Fee for all lanes on SH 6 and all intersecting streets is \$1,000.00. This fee applies to the Contractor for closures or obstructions that overlap into restricted hour traffic for each hour or portion thereof, per lane, regardless of the length of lane closure or obstruction. For Restricted Hours subject to Lane Assessment Fee, refer to the Item, "Barricades, Signs, and Traffic Handling".

**Item 134: Backfilling Pavement Edges**

Quantity by station includes both sides of the roadway.

If using salvaged asphalt concrete pavement, size it so that all the material, passes the 2-in. sieve. Use RAP that does not contain deleterious material such as clay or organic material.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Flex Base must meet the requirements of Item 247, Type A, Grade 2. Department Test Method Tex-117-E will not be required.

Place emulsified asphalt (SS-1, CSS-1, or CSS-1H) at an application rate of 0.25 gal/sq. yard.

**Item 204: Sprinkling**

Perform subsidiary sprinkling as required under various other items in accordance with the Item, "Sprinkling."

Sprinkling for dust control is subsidiary to the various bid items.

**Item 210: Rolling**

Use a medium pneumatic roller meeting the requirements of Item 210 as directed. This work is subsidiary to the various bid items. On every asphalt shot, use a minimum of 3 pneumatic rollers or as directed. Use approved rolling patterns. Successive asphalt shots will not be allowed until acceptable rolling has been accomplished on the preceding asphalt shot.

**Item 292: Asphalt Treatment (Plant-Mixed)**

If using the iron ore topsoil as the primary aggregate, meaning 80 percent or more by weight of the total mixture, the requirements for the water susceptibility test are waived.

Mixtures containing the iron ore topsoil are exempted from test methods TEX-217-F (Part I, separation of deleterious material and Part II, decantation test for coarse aggregate) and TEX-203-F (Sand Equivalent Test).

Assume responsibility for proportioning the materials entering the asphalt mixture, regardless of the type of plant used.

Furnish the mix designs for approval.

**Item 316: Seal Coat**

The asphalt application rate shown on the "Basis of Estimate" is an average rate for calculating asphalt quantities. Vary the rate based on the pavement conditions and other factors such as the type and grade of aggregate used, weather, and traffic.

**Item 340: Dense-Graded Hot Mix Asphalt (Small Quantity)**

Dilution of tack coat is not allowed. Before placing asphalt use hot applied Tack Coat.

Taper the asphalt concrete pavement at the beginning and ending points.

Use a maximum 6H:1V slope for the asphalt concrete pavement edge.



**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Where the 6H:1V ACP edge taper extends over onto the unsurfaced shoulders, blade off the loose existing shoulder material to provide a solid base for the outside taper edge. After placing the ACP overlay, blade this material back against the edge taper. This work is subsidiary to the various bid items.

The stockpile will be the point of sampling of coarse aggregate for test method TEX-217-F (Part II, decantation).

Place the asphalt concrete pavement in courses as shown on the typical sections.

Do not use petroleum-based solvents in the beds of hot mix asphalt delivery vehicles.

Do not use Surface Aggregate Classification (SAC) C for this project.

For determining the Asphalt Content, only ignition ovens will be allowed.

The tack coat rate shown on the "Basis of Estimate" is an average rate for calculating tack coat quantities. Vary the rate based on the pavement conditions and other factors such as manufacturer's recommendations and weather.

**Item 347: Thin Overlay Mixture (TOM)**

Place mixtures only when the air temperature is above 70°F.

Provide an asphalt binder PG 76-22. Substitution of the PG binder is not allowed.

Place mixture as the compacted lift thickness of one (1) inch for TOM-F and one (1) inch for TOM-C.

A hot-applied tack coat will be applied prior to placing TOM-C surface, which is paid under Item 3084.

Provide 100% SAC "A" aggregate. Blending is not allowed.

Do not use RAP or RAS in the mixture.

A Pave-IR system or Thermal camera system is mandatory for this project. The Contractor must demonstrate that the mixture is being placed with minimum thermal segregation.

Provide a mixture which exceeds a minimum of 500 cycles in the Overlay Tester, Tex-248-F.

For breakdown rolling, use two steel wheel rollers working in tandem without excessive breakage of the aggregate and provide a smooth surface and uniform texture. Keep the rollers as close as possible to the lay down machine. Do not use pneumatic tire rollers. Use a steel wheel as the finish roller.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Water flow measurements as per test Method 246 is mandatory for setting rolling patterns. For TOM-C the water flow should be at least 4 minutes, adjust the rolling patterns if less than 4 minutes. The water flow shall not exceed 10 minutes in order to avoid excessive compaction. The Contractor must report the selected patterns to TxDOT and show that it meets the water flow requirements [ftp://ftp.dot.state.tx.us/pub/txdot-info/cst/TMS/200-F\\_series/pdfs/bit246.pdf](ftp://ftp.dot.state.tx.us/pub/txdot-info/cst/TMS/200-F_series/pdfs/bit246.pdf).

WMA (Warm Mix Asphalt) is required when the Plant to job haul distance is greater than 40 miles.

When WMA is required no reduction in temperature for the PG grade of binder will be permitted (the WMA is a compaction aide).

The Contractor can pave at any time when the roadway is dry and ambient surface temperature is 70°F or higher regardless of whether or not the thermal imaging system is used.

The Engineer will determine the final asphalt content to be used for the trial batch and production.

**Item 354: Planing and Texturing Pavement**

The Reclaimed Asphalt Pavement from the project will become the property of the Contractor for use in the current construction project or in future projects.

The 1.5" planing is for intersecting streets. Please see plan sheet "Intersection Details" for details.

**Items 420 and 421: All Concrete Items**

For the Department's concrete cylinder split samples, transport the test cylinders to the Houston District Laboratory located at 7600 Washington Avenue in Houston, or to the appropriate Area Laboratory, when applicable. Transporting the test cylinders is subsidiary to the various bid items.

**Item 502: Barricades, Signs, and Traffic Handling**

Use a traffic control plan for handling traffic through the various phases of construction. Follow the phasing sequence unless otherwise agreed upon by the Area Engineer and the Project Manager. Ensure this plan conforms to the latest "Texas Manual on Uniform Traffic Control Devices" and the latest Barricade and Construction (BC) Standard Sheets.

Submit changes to the traffic control plan to the Area Engineer. Provide a layout showing the construction phasing, signs, striping, and signalizations for changes to the original traffic control plan.

Furnish and maintain the barricades and warning signs, including the necessary temporary and portable traffic control devices, during the various phases of construction. Place and construct

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

these barricades and warning signs in accordance with the latest “Texas Manual on Uniform Traffic Control Devices” for typical construction layouts.

Cover work zone signs when work related to the signs is not in progress, or when any hazard related to the signs no longer exists.

Keep the delineation devices, signs, and pavement markings clean. This work is subsidiary to the Item, “Barricades, Signs, and Traffic Handling.”

If a section is not complete before the end of the workday, pull back the base material to the existing pavement edge on a 6H: 1V slope. Edge drop-offs during the hours of darkness are not permitted.

Do not mount signs on drums or barricades, except those listed in the latest Barricades and Construction standard sheets.

Use traffic cones for daytime work only. Replace the cones with plastic drums during nighttime hours.

Do not reduce the existing number of lanes open to traffic except as shown on the following time schedule:

**One and Two Lane Closures  
SH 6 and all intersecting streets**

Day	Daytime Closure Hours	Nighttime Closure Hours	Restricted Hours Subject to Lane Assessment Fee
Monday	N/A	10:00 PM – 5:00 AM	5:00 AM – 10:00 PM
Tuesday	N/A	10:00 PM – 5:00 AM	5:00 AM – 10:00 PM
Wednesday	N/A	10:00 PM – 5:00 AM	5:00 AM – 10:00 PM
Thursday	N/A	10:00 PM – 5:00 AM	5:00 AM – 10:00 PM
Friday	N/A	N/A	N/A
Saturday	N/A	N/A	N/A
Sunday	N/A	10:00 PM – 5:00 AM	5:00 AM – 10:00 PM

The above times are approved for the traffic control conditions listed. The Area Engineer may approve other closure times if traffic counts warrant. The Area Engineer may reduce the above times for special events.

Law enforcement assistance will be required for this project and is expected to be required for major traffic control changes and lane closures. Coordinate with local law enforcement and arrange for law enforcement as directed or agreed by the Engineer. Before payment will be made, complete the “Daily Report on Law Enforcement Force Account Work” (Form 318),

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

provided by the Department and submit daily invoices that agree with this form for any day during the month in which approved services were provided.

Provide full-time, off-duty, uniformed, certified peace officers, as part of traffic control operations. The peace officers must be able to show proof of certification by the Texas Commission on Law Enforcement Officers Standards. The cost of the officers is paid for on a force account basis.

A minimum of 7 days in advance of any total closure, notify the Houston District Public Information Office of which roadways, ramps, intersections, or lanes will be closed, the dates they will remain closed, and when they will be opened again to traffic.

A minimum of 7 days in advance of any total closure, place a portable changeable message (PCM) sign at the location of each total closure which informs the traveling public of the details of the closure. Alternately, if the Traffic Control Plan provides a positive barrier at the location, a non-trailer mounted static message board sign behind the positive barrier may be used in place of a PCM.

Use Uneven Lane Signs (CW 8-11) during resurfacing operations for elevation differences between adjacent lanes of greater than 1 in.

Before closing any City of Houston sidewalk, one or more city street lanes, or entire city streets during construction, obtain a permit to do so from the City. Obtain the required permit in person at the City of Houston Permit Office, or apply online at <http://www.gims.houstontx.gov>.

The Contractor Force Account “Safety Contingency” that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor’s Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

**Item 506: Temporary Erosion, Sedimentation and Environmental Controls**

The use of hay bales is not permitted as Storm Water Pollution Prevention Plan (SWP3) measures.

The Storm Water Pollution Prevention Plan (SWP3) consists of temporary erosion control measures needed and provided for under this Item. The disturbed area is less than one acre and use of erosion control measures is not anticipated. If physical conditions encountered at the job site require necessary controls, BMP installation, maintenance, and removal will be paid as extra work on a force account basis per Articles 4.4 and 9.7. Since the disturbed area is less than 5 acres, a “Notice of Intent” (NOI) is not required.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Use appropriate measures to prevent, minimize, and control the spill of hazardous materials in the construction staging area. Remove and dispose of materials in compliance with State and Federal laws.

Before starting construction, review with the Engineer the SWP3 used for temporary erosion control as outlined on the plans. Before construction, place the temporary erosion and sedimentation control features as shown on the SWP3.

Implement temporary and permanent erosion control measures to comply with the National Pollution Discharge Elimination System (NPDES) general permit under the Clean Water Act.

**Item 585: Ride Quality for Pavement Surfaces**

To eliminate the need for corrective action due to excessive deviations in the final surface layers, exercise caution to ensure satisfactory profile results in the intermediate paving layers (mixture).

Milling will not be allowed as a corrective action for excessive deviations in the final surface layer of hot-mix asphalt.

For this project, use Surface Test Type B and Pay Adjustment Schedule 2 for all lanes.

**Item 618: Conduit**

**Item 620: Electrical Conductors**

**Item 628: Electrical Services**

If the specifications for electrical items require UL-listed products, this means UL-listed or CSA-listed.

**Item 618: Conduit**

When backfilling bore pits, ensure that the conduit is not damaged during installation or due to settling backfill material. Compact select backfill in three equal lifts to the bottom of the conduit; or if using sand, place it 2 in. above the conduit. Ensure backfill density is equal to that of the existing soil. Prevent material from entering the conduit.

Construct bore pits a minimum of 5 ft. from the edge of the base or pavement. Close the bore pit holes overnight.

Unless otherwise shown on the plans, install the underground conduit a minimum of 24 in. deep. Install the conduit in accordance with the latest National Electrical Code (NEC) and applicable Department standard sheets. Place conduit under driveways or roadways a minimum of 24 in. below the pavement surface.

If using casing to place bored conduit, the casing is subsidiary to the conduit.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

If placing the conduit under existing pavement to reach the service poles, bore the conduit in place and extend it a minimum distance of 5 ft. beyond the edge of shoulder or the back of curb.

Pull conductors in the PVC conduit only with a nonmetallic pull rope.

Remove conductor and conduit to be abandoned to 1 ft. below the ground level. This work is subsidiary to the various bid items

Use materials from the pre-qualified producers as shown on the Department's Construction Division (CST) material producers list. Check the latest links on the TxDOT website for the list. The category is "Roadway Illumination and Electrical Supplies." The polymer concrete barrier box is subsidiary to Item 618, "Conduit."

Furnish rigid metal conduit for underground conduit bends of 45 degrees or greater in all conduit systems, including bends into ground boxes and foundations. Where the rigid metal conduit is exposed at any point and where rigid metal conduit extends into ground boxes, bond the metal conduit to the grounding conductor with grounding type bushings or by other approved, UL-listed grounding connectors approved by the Engineer. Rigid metal bends are subsidiary to the conduit system.

**Item 620: Electrical Conductors**

Test each wire of each cable or conductor after installation. Incomplete circuits or damage to the wire or the cable are cause for immediate rejection of the entire cable being tested. Remove and replace the entire cable at no expense to the Department. Also test the replacement cable after installation.

When pulling cables or conductors through the conduit, do not exceed the manufacturer's recommended pulling tensions. Lubricate the cables or conductors with a lubricant recommended by the cable manufacturer.

For both transformer and shoe-base type illumination poles, provide double-pole breakaway fuse holders as shown on the Department's Construction Division (CST) material producers list. Check the latest link on the Department website for this list. The category is "Roadway Illumination and Electrical Supplies." The fuse holder is shown on the list under Items 610 and 620. Provide 10 Amp time delay fuses.

Ensure that circuits test clear of faults, grounds, and open circuits.

Split bolt connectors are allowed only for splices on the grounding conductors.

For electrical licensing and electrical certification requirements for this project, see Item 7 of the Standard Specifications and any applicable special provisions to Item 7.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

**Item 624: Ground Boxes**

The ground box locations are approximate. Alternate ground box locations may be used as directed, to avoid placing in sidewalks or driveways.

Ground metal ground box covers. Bond the ground box cover and ground conductors to a ground rod located in the ground box and to the system ground.

Ground the existing metal ground box covers as shown on the latest standard sheet ED (4)-14.

During construction and until project completion, provide personnel and equipment necessary to remove ground box lids for inspection. Provide this assistance within 24 hours of notification.

Construct concrete aprons in accordance with the latest standard sheet ED (4)-14. Make the depth of the concrete apron the same as the depth of the ground box, except for Type 1 and Type 2 ground boxes. For Type 1 or Type 2 ground boxes, construct the concrete apron in accordance with details shown on the "Ground Box Details Installations" standard.

**Item 662: Work Zone Pavement Markings**

At the end of each workday, mark roadways that remain open to traffic during construction operations with standard pavement markings, in accordance with the latest "Texas Manual on Uniform Traffic Control Devices."

Do not use raised pavement markers as optional work zone pavement markings on final asphalt surfaces.

**Item 662: Work Zone Pavement Markings**

**Item 666: Reflectorized Pavement Markings**

Use Type III glass beads for thermoplastic pavement markings.

Use a 0.100 in. (100 mil) thickness for thermoplastic pavement markings, measured to the top of the thermoplastic, not including the exposed glass beads.

For roadways with asphalt surfaces to be striped with work zone or permanent thermoplastic markings, the Contractor has the option to apply paint and beads markings for a maximum 30-day period until placing the thermoplastic markings, or until starting the succeeding phase of work on the striped area. Maintain the paint and beads markings, at no expense to the Department, until placing the thermoplastic markings or starting the succeeding phase of work on the striped area. The work zone markings, whether paint and beads or thermoplastic, are paid under the Item, "Work Zone Pavement Markings" and the markings are paid for only once for the given phase of construction.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

If using paint and bead markings as described above, purchase the traffic paint from the open market.

If the Type II or work zone markings become dirty and require cleaning by washing, brushing, compressed air, or other approved methods before applying the Type I thermoplastic markings, this additional cleaning is subsidiary to the Item, "Reflectorized Pavement Markings."

Establish the alignment and layout for work zone striping and permanent striping.

Stripe all roadways before opening them to traffic.

Place pavement markings under these items in accordance with details shown on the plans, the latest "Texas Manual on Uniform Traffic Control Devices," or as directed.

When design details are not shown on the plans, provide pavement markings for arrows, words, and symbols conforming to the latest "Standard Highway Sign Designs for Texas" manual.

**Item 672: Raised Pavement Markers**

If other operations are complete on the project and if the curing time period is not yet elapsed, the contract time will be suspended until the curing is done.

Before placing the raised pavement markers on concrete pavement, blast clean the surface using an abrasive-blasting medium. This work is subsidiary to the Item, "Raised Pavement Markers."

Provide epoxy adhesive that is machine-mixed or nozzle-mixed and dispensed. Equip the machine or nozzle with a mechanism to ensure positive mix measurement control.

**Item 677: Eliminating Existing Pavement Markings and Markers**

Remove existing pavement markings on concrete or asphalt surfaces by flail milling or as directed.

**Item 678: Pavement Surface Preparation for Markings**

Do not blast clean asphalt concrete pavement. Clean asphalt concrete pavement as required under the applicable specifications or as directed.

On new concrete pavement or on existing concrete pavement when placing a new stripe on a new location, remove the curing compounds and contamination from the pavement surface by flail milling or as directed. In addition, air-blast the surface with compressed air just before placing the new stripe.

On existing concrete pavement when placing a new stripe on an existing location, after removing the existing stripe under the Item, "Eliminating Existing Pavement Markings and Markers," air-blast the surface with compressed air just before placing the new stripe.

**County:** Harris

**Control:** 1685-05-115

**Highway:** SH 6

Do not clean concrete pavement by grinding.

**Item 6185: Truck Mounted Attenuator (TMA) and Trailer Attenuator (TA)**

A shadow vehicle with Truck Mounted Attenuators (TMAs) or Trailer Attenuators (TAs) is required as shown on the appropriate Traffic Control Plan (TCP) sheets. TMAs/TAs must meet the requirements of the Compliant Work Zone Traffic Control Device List.

Level 3 Compliant TMAs/TAs are required for this project.

A total of one (1) shadow vehicle with a TMA/TA is required for the work with the exception of Pavement Marking Operations. The Contractor is responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMAs/TAs needed on the project.

A total of three (3) shadow vehicles with a TMA/TA are required for Pavement Marking Operations. The Contractor is responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMAs/TAs needed on the project.

**Basis of Estimate**

<b>Item</b>	<b>Description</b>	<b>Limit and Rate</b>	<b>Unit</b>
134	Backfilling Pavement Edges • Asphalt Emulsion	0.25 Gal. / Sq. Yd.	STA
316	Seal Coat • Asphalt • Aggregate	0.32 Gal. / Sq. Yd. 1/130 Cu. Yd. / Sq. Yd.	GAL CY
340	Dense-Graded Hot Mix Asphalt (Method) • Asphalt • Aggregate • Tack Coat	110 Lb. / Sq. Yd.-In. 6 % by weight 94 % by weight 0.11 Gal./ Sq. Yd.	TON GAL
347	Thin Overlay Mixture (TOM) • Asphalt PG 76-22 (Surface) • Aggregate SAC A (Surface)	110 Lb. / Sq. Yd.-In. 6.7 % by weight 93.3 % by weight	TON TON
3084	• Bonding Course	0.04 Gal./ Sq. Yd.	GAL



# ESTIMATE AND QUANTITY SHEET

CONTROLLING PROJECT ID 1685-05-115

DISTRICT Houston  
HIGHWAY SH 6

COUNTY Harris

CONTROL SECTION JOB				1685-05-115		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00123270			
COUNTY				Harris			
HIGHWAY				SH 6			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	134-6001	BACKFILL (TY A)	STA	73.450		73.450	
	316-6017	ASPH (AC-20-5TR)	GAL	28,588.160		28,588.160	
	316-6434	AGGR (TY-PB GR-4 OR TY-PL GR-4 ( SAC-B)	CY	687.210		687.210	
	340-6119	D-GR HMA(SQ) TY-D SAC-A PG70-22	TON	124.080		124.080	
	340-6272	TACK COAT	GAL	165.440		165.440	
	347-6001	TOM (ASPHALT) PG 76-22	TON	658.410		658.410	
	347-6002	TOM-C (AGGREGATE) SAC-A	TON	4,584.350		4,584.350	
	347-6007	TOM - F (AGGREGATE) SAC - A	TON	4,584.350		4,584.350	
	351-6001	FLEXIBLE PAVEMENT STRUCTURE REPAIR(5")	SY	800.000		800.000	
	354-6041	PLANE ASPH CONC PAV (1.5")	SY	1,504.000		1,504.000	
	354-6064	PLANE ASPH CONC PAV (2 1/2")	SY	89,338.000		89,338.000	
	500-6001	MOBILIZATION	LS	100.00%		100.00%	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	3.000		3.000	
	618-6053	CONDT (PVC) (SCH 80) (3")	LF	50.000		50.000	
	618-6074	CONDT (RM) (3")	LF	50.000		50.000	
	624-6028	REMOVE GROUND BOX	EA	9.000		9.000	
	662-6001	WK ZN PAV MRK NON-REMOV (W)4"(BRK)	LF	22,650.000		22,650.000	
	662-6002	WK ZN PAV MRK NON-REMOV (W)4"(DOT)	LF	3,150.000		3,150.000	
	662-6004	WK ZN PAV MRK NON-REMOV (W)4"(SLD)	LF	45,840.000		45,840.000	
	662-6012	WK ZN PAV MRK NON-REMOV (W)8"(SLD)	LF	15,855.000		15,855.000	
	662-6014	WK ZN PAV MRK NON-REMOV (W)12"(SLD)	LF	4,650.000		4,650.000	
	662-6016	WK ZN PAV MRK NON-REMOV (W)24"(SLD)	LF	1,875.000		1,875.000	
	662-6017	WK ZN PAV MRK NON-REMOV (W)(ARROW)	EA	111.000		111.000	
	662-6029	WK ZN PAV MRK NON-REMOV(W)(WORD)	EA	111.000		111.000	
	666-6018	REFL PAV MRK TY I (W)6"(DOT)(100MIL)	LF	175.000		175.000	
	666-6036	REFL PAV MRK TY I (W)8"(SLD)(100MIL)	LF	5,270.000		5,270.000	
	666-6042	REFL PAV MRK TY I (W)12"(SLD)(100MIL)	LF	1,550.000		1,550.000	
	666-6048	REFL PAV MRK TY I (W)24"(SLD)(100MIL)	LF	625.000		625.000	
	666-6054	REFL PAV MRK TY I (W)(ARROW)(100MIL)	EA	37.000		37.000	
	666-6078	REFL PAV MRK TY I (W)(WORD)(100MIL)	EA	37.000		37.000	
	666-6162	RE PV MRK TY I(BLACK)6"(SHADOW)(100MIL)	LF	7,550.000		7,550.000	
	666-6180	REFL PAV MRK TY II (W) 12" (SLD)	LF	300.000		300.000	
	666-6212	REFL PAV MRK TY II (Y) 12" (SLD)	LF	7,375.000		7,375.000	
	666-6306	RE PM W/RET REQ TY I (W)6"(BRK)(100MIL)	LF	7,550.000		7,550.000	
	666-6309	RE PM W/RET REQ TY I (W)6"(SLD)(100MIL)	LF	15,280.000		15,280.000	
	672-6010	REFL PAV MRKR TY II-C-R	EA	644.000		644.000	
	3084-6001	BONDING COURSE	GAL	3,574.000		3,574.000	



# ESTIMATE AND QUANTITY SHEET

**CONTROLLING PROJECT ID** 1685-05-115

**DISTRICT** Houston  
**HIGHWAY** SH 6

**COUNTY** Harris

<b>CONTROL SECTION JOB</b>				<b>1685-05-115</b>		TOTAL EST.	TOTAL FINAL
<b>PROJECT ID</b>				<b>A00123270</b>			
<b>COUNTY</b>				<b>Harris</b>			
<b>HIGHWAY</b>				<b>SH 6</b>			
<b>ALT</b>	<b>BID CODE</b>	<b>DESCRIPTION</b>	<b>UNIT</b>	EST.	FINAL		
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY	120.000		120.000	
	6185-6002	TMA (STATIONARY)	DAY	70.000		70.000	
	6185-6005	TMA (MOBILE OPERATION)	DAY	14.000		14.000	
	6292-6004	RVDS(PRESENCE DET ONLY)(INSTALL ONLY)	EA	8.000		8.000	
	6292-6005	RVDS(ADVANCE DET ONLY)(INSTALL ONLY)	EA	8.000		8.000	
	06	MATERIAL FURNISHED BY STATE	LS	1.000		1.000	
	08	EROSION CONTROL MAINTENANCE (NON-PART)	LS	1.000		1.000	
		LAW ENFORCEMENT	LS	1.000		1.000	
		SAFETY CONTINGENCY (NON-PART)	LS	1.000		1.000	

**CSJ 1685-05-115 SUMMARY OF QUANTITIES**

ITEM				134	316	316	340	340	347	347	347	351	354	354
DESC. CODE				6001	6017	6434	6119	6272	6001	6002	6007	6001	6041	6064
SHT NO.	STATION TO STATION			BACKFILL (TY A)	ASPH (AC-20-STR)	AGGR (TY-PB GR4 OR TY-PL GR-4 (SAC-B)	D-GR HMA (SQ) TY-D SAC-A PG70-22	TACK COAT	TOM (ASPH) PG 76-22	TOM-C (AGGREGATE) SAC-A	TOM-F (AGGREGATE) SAC-A	FLEX PAV STRUCT REPAIR (5")	PLANE ASPH CONC PAV (1.5")	PLANE ASPH CONC PAV (2.5")
				STA	GAL	CY	TON	GAL	TON	TON	TON	TON	SY	SY
SH 6														
CSJ 1685-05-115														
1	961+00	TO	974+00	13.00	5408.00	130.00	23.76	31.04	124.55	867.22	867.22	140.00	288.00	16,900.00
2	974+00	TO	988+00	14.00	5539.20	133.15	23.76	31.04	127.57	888.26	888.26	160.00	288.00	17,310.00
3	988+00	TO	1000+20	14.00	5545.60	133.31	23.76	31.04	127.72	889.29	889.29	160.00	288.00	17,330.00
4	1000+20	TO	1016+00	14.00	5635.80	135.48	23.76	31.04	129.80	903.76	903.76	160.00	288.00	17,612.00
5	1016+00	TO	1030+00	14.00	5662.01	136.10	23.76	31.04	130.40	907.93	907.93	160.00	288.00	17,693.25
6	1030+00	TO	1034+45	4.45	797.55	19.17	5.28	10.24	18.37	127.89	127.89	20.00	64.00	2,492.75
TOTAL				73.45	28588.16	687.21	124.08	165.44	658.41	4584.35	4584.35	800.00	1504.00	89,338.00

ITEM				662	662	662	662	662	662	662	662
DESC. CODE				6001	6002	6004	6012	6014	6016	6017	6029
SHT NO.	STATION TO STATION			WRK ZN PAV MRK NON-REMOV (W)4"(BRK)	WRK ZN PAV MRK NON-REMOV (W)4"(DOT)	WRK ZN PAV MRK NON-REMOV (W)4"(SLD)	WRK ZN PAV MRK NON-REMOV (W)8"(SLD)	WRK ZN PAV MRK NON-REMOV (W)12"(SLD)	WRK ZN PAV MRK NON-REMOV (W)24"(SLD)	WRK ZN PAV MRK NON-REMOV (W)(ARROW)	WRK ZN PAV MRK NON-REMOV(W)(WORD)
				LF	LF	LF	LF	LF	LF	LF	LF
SH 6											
CSJ 1685-05-115											
1	961+00	TO	974+00	4,650.00	525.00	8,880.00	4,275.00	2,700.00	450.00	27.00	27.00
2	974+00	TO	988+00	4,200.00	525.00	8,400.00	2,700.00		225.00	21.00	21.00
3	988+00	TO	1000+20	4,200.00	525.00	8,880.00	2,550.00	1,950.00	525.00	18.00	18.00
4	1000+20	TO	1016+00	4,200.00	525.00	8,400.00	2,205.00			15.00	15.00
5	1016+00	TO	1030+00	4,200.00	525.00	8,880.00	3,150.00		675.00	24.00	24.00
6	1030+00	TO	1034+45	1,200.00	525.00	2,400.00	975.00			6.00	6.00
TOTAL				22,650.00	3,150.00	45,840.00	15,855.00	4,650.00	1,875.00	111.00	111.00

REF FILES ATT.

LEVELS DISPLAYED	1	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
------------------	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----



**SUMMARY OF QUANTITIES**

FED. RD. DIV. NO.	PROJECT NO		SHEET NO.
6			15
STATE	DIST.	COUNTY	
TEXAS	HOU	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6



CSJ 1685-05-115 SUMMARY OF QUANTITIES

ITEM				666	666	666	666	666	666	666	666
DESC. CODE				6018	6036	6042	6048	6054	6078	6162	6180
SHT NO.	STATION TO STATION			REFL PAV MRK TY I (W)6"(DOT) (100 MIL)	REFL PAV MRK TY I (W)8"(SLD) (100 MIL)	REFL PAV MRK TY I (W)12"(SLD)(100MIL)	REFL PAV MRK TY I (W)24"(SLD) (100MIL)	REFL PAV MRK TY I (W)(ARROW) (100MIL)	REFL PAV MRK TY I (W)(WORD) (100MIL)	REFL PAV MRK TY I (BLACK)6" (SHADOW) (100MIL)	REFL PAV MRK TY II (W)12"(SLD)
				LF	LF	LF	LF	LF	LF	LF	LF
SH 6											
CSJ 1685-05-115											
1	961+00	TO	974+00	175.00	1,425.00	900.00	150.00	9.00	9.00	1,550.00	
2	974+00	TO	988+00		900.00		75.00	7.00	7.00	1,400.00	
3	988+00	TO	1000+20		835.00	650.00	175.00	6.00	6.00	1,400.00	75.00
4	1000+20	TO	1016+00		735.00			5.00	5.00	1,400.00	150.00
5	1016+00	TO	1030+00		1,050.00		225.00	8.00	8.00	1,400.00	75.00
6	1030+00	TO	1034+45		325.00			2.00	2.00	400.00	
TOTAL				175.00	5,270.00	1550.00	625.00	37.00	37.00	7,550.00	300.00

ITEM				666	666	666	672
DESC. CODE				6212	6306	6309	6010
SHT NO.	STATION TO STATION			REFL PAV MRK TY II (Y)12"(SLD)	RE PM W/RET REQ TY I (W)6"(BRK)(100MIL)	RE PM W/RET REQ TY I (W)6"(SLD)(100MIL)	REFL PAV MRKR TY II-C-R
				LF	LF	LF	EA
SH 6							
CSJ 1685-05-115							
1	961+00	TO	974+00	1,300.00	1,550.00	2,960.00	150.00
2	974+00	TO	988+00	1,250.00	1,400.00	2,800.00	115.00
3	988+00	TO	1000+20	1,400.00	1,400.00	2,960.00	112.00
4	1000+20	TO	1016+00	1,400.00	1,400.00	2,800.00	107.00
5	1016+00	TO	1030+00	1,600.00	1,400.00	2,960.00	123.00
6	1030+00	TO	1034+45	425.00	400.00	800.00	37.00
TOTAL				7,375.00	7,550.00	15,280.00	644.00

REF FILES ATT.

LEVELS DISPLAYED	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
------------------	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----



SUMMARY OF QUANTITIES

FED. RD. DIV. NO.	PROJECT NO		SHEET NO.
6			16
STATE	DIST.	COUNTY	
TEXAS	HOU	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6

CSJ 1685-05-115 SUMMARY OF QUANTITIES

ITEM	3084	6001	6185	6185	
DESC. CODE	6001	6001	6002	6005	
SHT NO.	STATION TO STATION	BONDING COURSE	PORTABLE CHANGEABLE MESSAGE SIGN	TMA (STATIONARY)	TMA (MOBILE OPERATION)
		GAL	DAY	DAY	DAY
SH 6					
CSJ 1685-05-115					
1	961+00 TO 974+00	676.00	20.00	35.00	2.00
2	974+00 TO 988+00	693.00	20.00		3.00
3	988+00 TO 1000+20	693.00	20.00		2.00
4	1000+20 TO 1016+00	704.00	20.00		2.00
5	1016+00 TO 1030+00	708.00	20.00		3.00
6	1030+00 TO 1034+45	100.00	20.00	35.00	2.00
TOTAL		3574.00	120.00	70.00	14.00

LEVELS DISPLAYED  
 1 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16  
 REF FILES ATT.  
 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63



SUMMARY OF QUANTITIES

FED. RD. DIV. NO.	PROJECT NO		SHEET NO.
6			17
STATE	DIST.	COUNTY	
TEXAS	HOU	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6

DATE: Sep 24, 2020  
 FILE: SM01\_SH 6 AT Bellaire Blvd and Beechnut St\_Summary of Quantities.dgn


DUU  
 CXL  
 CXL  
 CXL

MATERIALS FOR HIGHWAY TRAFFIC SIGNAL							
ITEM	DESC CODE	DESCRIPTION	UNIT	QUANTITY SH 6 @ BELLAIRE BLVD	QUANTITY SH 6 @ BEECHNUT ST	TOTAL	FINAL
618	6053	CONDT (PVC) (SCH 80) (3")	LF	30	20	50	
618	6074	CONDT (RM) (3")	LF	25	25	50	
624	602B	REMOVE GROUND BOX	EA	4	5	9	
6292	6004	RVDS(PRESENCE DET ONLY)(INSTALL ONLY)	EA	4	4	8	
		* RADAR PRESENCE DETECTOR CABLE (22/4C AWG) (COMM) / (18/2C AWG) (POWER)	LF	880	825	1705	
6292	6005	RVDS(ADVANCE DET ONLY)(INSTALL ONLY)	EA	4	4	8	
		* RADAR ADVANCE DETECTOR CABLE (22/4C AWG) (COMM) / (18/2C AWG) (POWER)	LF	880	825	1705	

\* MATERIAL SUBSIDIARY TO PERTINENT ITEMS


**TRAFFIC SIGNAL  
 SUMMARY OF QUANTITIES**

© 2020



CONT	SECT	JOB	WEIGHT
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	18	

FY	MSEC	HIGHWAY	RDBD	REFERENCE MARKERS							IRI(IN/MI)				
				BEGIN			END			LEN	PTYPE	MM/DD/YYYY	LEFT	RIGHT	SI
2020	08	SH0006	L1	0678	+	0.800	0678	+	0.900	0.1	05	9/8/2019	117	116	3.4
2020	08	SH0006	L1	0678	+	0.900	0678	+	1.000	0.1	05	9/8/2019	65	85	4.2
2020	08	SH0006	L1	0678	+	1.000	0678	+	1.076	0.1	05	9/8/2019	53	51	4.7
2020	08	SH0006	L1	0678	+	1.076	0678	+	1.176	0.1	05	9/8/2019	57	47	4.7
2020	08	SH0006	L1	0678	+	1.176	0678	+	1.276	0.1	05	9/8/2019	50	42	4.9
2020	08	SH0006	L1	0678	+	1.276	0678	+	1.376	0.1	05	9/8/2019	45	49	4.9
2020	08	SH0006	L1	0678	+	1.376	0678	+	1.476	0.1	05	9/8/2019	55	52	4.7
2020	08	SH0006	L1	0678	+	1.476	0678	+	1.576	0.1	05	9/8/2019	70	62	4.4
2020	08	SH0006	L1	0678	+	1.576	0678	+	1.676	0.1	05	9/8/2019	51	48	4.8
2020	08	SH0006	L1	0678	+	1.676	0678	+	1.776	0.1	05	9/8/2019	50	45	4.9
2020	08	SH0006	L1	0680	+	0.003	0680	+	0.103	0.1	05	9/8/2019	66	55	4.5
2020	08	SH0006	L1	0680	+	0.103	0680	+	0.203	0.1	05	9/8/2019	46	39	5.0
2020	08	SH0006	L1	0680	+	0.203	0680	+	0.303	0.1	05	9/8/2019	91	101	3.7
2020	08	SH0006	R1	0678	+	0.800	0678	+	0.900	0.1	05	9/8/2019	119	133	3.2
2020	08	SH0006	R1	0678	+	0.900	0678	+	1.000	0.1	05	9/8/2019	75	69	4.2
2020	08	SH0006	R1	0678	+	1.000	0678	+	1.100	0.1	05	9/8/2019	60	60	4.5
2020	08	SH0006	R1	0678	+	1.100	0678	+	1.200	0.1	05	9/8/2019	56	52	4.7
2020	08	SH0006	R1	0678	+	1.200	0678	+	1.300	0.1	05	9/8/2019	54	48	4.8
2020	08	SH0006	R1	0678	+	1.300	0678	+	1.400	0.1	05	9/8/2019	51	65	4.6
2020	08	SH0006	R1	0678	+	1.400	0678	+	1.500	0.1	05	9/8/2019	42	47	4.9
2020	08	SH0006	R1	0678	+	1.500	0678	+	1.600	0.1	05	9/8/2019	59	69	4.4
2020	08	SH0006	R1	0678	+	1.600	0678	+	1.700	0.1	05	9/8/2019	53	58	4.6
2020	08	SH0006	R1	0678	+	1.700	0678	+	1.800	0.1	05	9/8/2019	50	54	4.7
2020	08	SH0006	R1	0680	+	0.027	0680	+	0.127	0.1	05	9/8/2019	59	56	4.6
2020	08	SH0006	R1	0680	+	0.127	0680	+	0.227	0.1	05	9/8/2019	50	52	4.8
2020	08	SH0006	R1	0680	+	0.227	0680	+	0.298	0.1	05	9/8/2019	67	70	4.3



**Pavement Types**

**Description**

Codes	Description
01	Continuously Reinforced Concrete Pavement
02	Jointed Reinforced Concrete Pavement
03	Jointed Plain Concrete Pavement
04	Thick Asphaltic Concrete Pavement (greater than 5-1/2")
05	Intermediate Thickness Asphaltic Concrete Pavement (2-1/2" to 5-1/2")
06	Thin Surfaced Flexible Base Pavement (less than 2-1/2")
07	Asphalt Surfacing with Heavily Stabilized Base
08	Overlaid and/or Widened Old Concrete Pavement
09	Overlaid and/or Widened Old Flexible Pavement
10	Thin Surfaced Flexible Base Pavement (Surface Treatment-Seal Coat


Combination)



IRI DATA					
FED RD. DIV. NO.	State	Project Number			Sheet
6	Texas				19
DIST	COUNTY	CONT.	SECT.	JOB	Highwy
HOU	HARRIS	1685	05	115	SH 6

**NOTES:**  
 1. THE NUMBER OF POLICE OFFICERS TO ASSIST WITH INGRESS AND EGRESS OF TRUCKS AND EQUIPMENT WILL BE DETERMINED BY THE ENGINEER IN THE FIELD.  
 2. PORTABLE CHANGEABLE MESSAGE SIGN IS OPTIONAL AND WILL BE DETERMINED BY THE ENGINEER IN THE FIELD.

Shadow vehicles are required for lane closure.



*B. Kwater, P.E.*  
 10/1/20

**CONSTRUCTION WARNING SIGN SPACING**

POSTED SPEED OR 85% SPEED (MPH)	X MIN. DISTANCE (FEET)
30 OR LESS	90
35	120
40	160
45	240
50	320
55	500
65	750

- LEGEND**
- Type III Barricade
  - Channelizing Devices
  - Flag
  - Heavy Work Vehicle
  - Truck Mounted Attenuator
  - Trailer Mounted Flashing Arrow Panel
  - Portable Changeable Message Sign
  - Sign Post
  - Flagger


Posted Speed	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Device	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60' - 75'
35		205'	225'	245'	35'	70' - 90'
40		265'	295'	320'	40'	80' - 100'
45	L=WS	450'	495'	540'	45'	90' - 110'
50		500'	550'	600'	50'	100' - 125'
55		550'	605'	660'	55'	110' - 140'
60		600'	660'	720'	60'	120' - 150'
65		650'	715'	780'	65'	130' - 165'
70		700'	770'	840'	70'	140' - 115'

\*\*Taper lengths have been rounded off.  
 L=Length of Taper (FT.) W=Width of Offset (FT.) S=Posted Speed (MPH)


**GENERAL NOTES:**

1. All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
2. Drums or 42" cones are the typical channelizing devices. For Intermediate Term Stationary work, drums shall be used on tapers with drums or 42" cones used on tangent sections. Other channelizing devices may be used as directed by the Engineer.
3. All construction signs and barricades placed during any phase of work shall remain in place until removal is approved by the Engineer.
4. The Engineer may direct the Contractor to furnish additional signs and barricades as required to maintain traffic flow, detours and motorist safety during construction.
5. Static message boards or changeable message signs stating the date and duration of ramp or freeway lane closures shall be placed a minimum of seven (7) calendar days in advance of the actual closure.
6. Phase 2 of the PMS message should include appropriate information formatted as shown on BC16), such as "MERGE LEFT," recommended advisory speed, delay information, or other specific warnings.
7. Duplicate construction warning signs should be erected on the median side of freeways where median width will permit and traffic volume justifies the signing.
8. The number of closed lanes may be increased provided the spacing of traffic control devices, taper lengths and tangent lengths meet the requirements of the TMUTCD.
9. Warning signs for intermediate term stationary work should be spaced at 7' to the bottom of the sign.
10. Warning signs shown shall be appropriately altered for left lane closures. When signs are mounted at 1' height for short term stationary or short duration work, sign versions shown in the SHSD for Texas with distances on the sign face rather than mounted on a plaque below the sign may be used.
11. When possible, PMS units should be located in advance of the last available exit ramp prior to the lane closure to allow motorists an alternate route. They may also be relocated to improve advance warning in case of unanticipated queuing or congestion.
12. For intermediate term stationary work at night, floodlights should be used to illuminate the work area and equipment crossings. Floodlights shall not produce a disabling glare condition for road users or workers.
13. The END ROAD WORK (G20-2) sign may be omitted when it conflicts with G20-2 signs already in place on the project.

Only pre-qualified products shall be used. A list of compliant products and their sources may be obtained by writing or faxing:  
 Standards Engineer  
 Traffic Operations Division - TE  
 Texas Department of Transportation  
 125 East 11th Street  
 Austin, Texas 78701-2483  
 Phone (512) 416-3335  
 Fax (512) 416-3161  
 E-mail TRF-STANDARD@mailgw.dot.state.tx.us



Typical One Lane Closure



Typical Two Lane Closure

Typical Frontage Road

DN:	CK:	DATE:
DM:	CK:	
CK:	CK:	

LEVELS DISPLAYED

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----


**TYPICAL USAGE:**

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

Texas Department of Transportation ©2020

TRAFFIC CONTROL PLAN ONE & TWO LANE CLOSURE

REVISED	DATE	BY	REASON	SHEET
	NOV 6			20
COUNTY	CORREL	SECTION	JOB	NUMBER
HARRIS	1685	05	115	SH 6




SEE BC STANDARDS FOR ADDITIONAL TCP REQUIREMENTS AND DETAILS.

**LEGEND:**










 = WORK AREA

**NOTE:**  
 PROVIDE A UNIFORMED POLICE OFFICER TO ASSIST WITH INGRESS AND EGRESS OF TRUCKS AND EQUIPMENT AT ALL TIMES. A MINIMUM OF TWO POLICE OFFICERS WILL BE REQUIRED IN THE FIELD.



*B. Kwater, P.E.*  
 10/1/20

**LEGEND**

-  Type III Barricade
-  Channelizing Devices
-  Flag
-  Heavy Work Vehicle
-  Truck Mounted Attenuator
-  Trailer Mounted Flashing Arrow Panel
-  Portable Changeable Message Sign
-  Flagger
-  Sign Post

Posted Speed %	Formula	Minimum Desirable Taper Lengths %			Suggested Maximum Spacing of Device		Minimum Sign Spacing x Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60' - 75'	120'
35		205'	225'	245'	35'	70' - 90'	160'
40		265'	295'	320'	40'	80' - 100'	240'
45	L = WS	450'	495'	540'	45'	90' - 110'	320'
50		500'	550'	600'	50'	100' - 125'	400'
55		550'	605'	660'	55'	110' - 140'	500'
60		600'	660'	720'	60'	120' - 150'	* 600'
65		650'	715'	780'	65'	130' - 165'	* 700'
70		700'	770'	840'	70'	140' - 175'	* 800'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L = Length of Taper (FT.) W = Width of Offset (FT.) S = Posted Speed (MPH)

**TYPICAL USAGE:**

	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
MOBILE				
	✓	✓	✓	

- GENERAL NOTES:**
- Flags attached to signs are **REQUIRED**.
  - All traffic control devices illustrated are **REQUIRED**, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
  - The BE PREPARED TO STOP sign may be installed after the ONE LANE ROAD XXX FT sign, but proper sign spacing shall be maintained.
  - YIELD sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work zones should be no longer than one half city block. In rural areas on roadways with less than 4000 ADT and work areas should be no longer than 400'.
  - YIELD TO ONCOMING TRAFFIC sign shall be placed on a support at a 7' minimum mounting height.
  - Flaggers should use two-way radios or other methods of communication to control traffic.
  - Length of work area should be based on the ability of flaggers to communicate.
  - For intermediate term situations, when it is not feasible to remove and restore pavement markings, the channelization must be made dominant by using a very close spacing. This is especially important in locations of conflicting information, such as where traffic is directed over a double yellow centerline. In such locations a maximum channelizing device spacing of 10 feet is recommended. The 10 foot channelizing device spacing recommendation is intended for the area of conflicting information and not the entire work zone.


All dimensions are in feet unless otherwise noted.




**TRAFFIC CONTROL PLAN  
 CENTER LANE CLOSURE  
 AT INTERSECTION**

© TxDOT December 1995	DR - LR	CU - MT	DN - DN	CU - DM	REV. NO. 1
STATE PROJECT	PROJECT NO.			SHEET	
HOU	6				21
COUNTY	CONTROL	SECTION	JOB	HIGHWAY	
HARRIS	1685	05	115	SH 6	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



**TCP (3-1a)**  
**UNDIVIDED MULTILANE ROADWAY**




**TRAIL/SHADOW VEHICLE A**  
with RIGHT Directional display Flashing Arrow Board

LEGEND			
*	Trail Vehicle	ARROW BOARD DISPLAY	
**	Shadow Vehicle		
***	Work Vehicle		RIGHT Directional
	Heavy Work Vehicle		LEFT Directional
	Truck Mounted Attenuator (TMA)		Double Arrow
	Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)


TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**GENERAL NOTES**


- TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used the WORK vehicle must be equipped with an arrow board. The Engineer will determine if the LEAD VEHICLE and/or TRAIL VEHICLE are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
- Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
- "X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY" (CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
- On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the rearmost protection vehicle.




**TCP (3-1b)**  
**TWO-WAY ROADWAY WITH PAVED SHOULDERS**



**TCP (3-1c)**  
**TWO-WAY ROADWAY WITHOUT PAVED SHOULDERS**



**TRAIL/SHADOW VEHICLE B**  
with Flashing Arrow Board in CAUTION display



**STRIPING FOR TMA**









**TRAFFIC CONTROL PLAN  
MOBILE OPERATIONS  
UNDIVIDED HIGHWAYS**

**TCP (3-1) - 13**

FILE: tcp3-1.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	HOU	HARRIS	22	
1-97				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \_\_\_\_\_  
 FILE: \_\_\_\_\_



LEGEND		
* Trail Vehicle	ARROW BOARD DISPLAY	
** Shadow Vehicle		
*** Work Vehicle		RIGHT Directional
		LEFT Directional
		Double Arrow
		CAUTION (Alternating Diamond or 4 Corner Flash)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

**GENERAL NOTES**

- TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used on two way roads the WORK vehicle must have an arrow board. For divided roadways, the arrow board on the WORK vehicle is optional based on the type of work being performed. The Engineer will determine if the LEAD vehicle and/or TRAIL vehicle are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating, or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE, ADVANCE WARNING and TRAIL VEHICLE are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
- Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
- X VEHICLE CONVOY (CW21-10cT) or WORK CONVOY (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" x 48" diamond shaped WORK CONVOY (CW21-10T) or X VEHICLE CONVOY (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The X VEHICLE CONVOY sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
- For divided highways with two or three lanes in one direction, the appropriate LEFT LANE CLOSED (CW20-5bTL), RIGHT LANE CLOSED (CW20-5bTR), or CENTER LANE CLOSED (CW20-5dT) sign should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board may be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
- A double arrow shall not be displayed on the arrow board on the Advance Warning Vehicle.
- For divided highways with three or four lanes in each direction, use TCP(3-2).
- Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
- The Advance Warning Vehicle may straddle the edgeline when Shoulder width makes it necessary.
- On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a DO NOT PASS (R4-1) sign should be placed on the back of the rearmost protection vehicle.

Texas Department of Transportation



Traffic Operations Division Standard

**TRAFFIC CONTROL PLAN  
MOBILE OPERATIONS  
RAISED PAVEMENT  
MARKER INSTALLATION/  
REMOVAL  
TCP (3-3) - 14**

FILE: tcp3-3.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT September 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	HOU	HARRIS	23	
1-97 7-14				



TYPICAL ADVANCE SIGNING  
TO REMAIN IN PLACE DURING ALL PHASES  
OR AS DIRECTED BY AN ENGINEER



TYPICAL TRANSITION LENGTHS  
AND  
SUGGESTED MAXIMUM SPACING OF DEVICES

POSTED SPEED	FORMULA	MINIMUM DESIRABLE TAPER LENGTHS (ft)			SUGGESTED MAX. SPAC. OF DEVICE		MINIMUM SIGN SPACING * DISTANCE
		10' OFFSET	11' OFFSET	12' OFFSET	ON A TAPER	ON A TANGENT	
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60' - 75'	120'
35		205'	225'	245'	35'	70' - 90'	160'
40		265'	295'	320'	40'	80' - 100'	240'
45	L = WS	450'	495'	540'	45'	90' - 110'	320'
50		500'	550'	600'	50'	100' - 125'	400'
55		550'	605'	660'	55'	110' - 140'	500'
60		600'	660'	720'	60'	120' - 150'	⊙ 600'
65		650'	715'	780'	65'	130' - 165'	⊙ 700'
70	700'	770'	840'	70'	140' - 175'	⊙ 800'	

⊙ CONVENTIONAL ROADS ONLY  
⊙ TAPER LENGTHS HAVE BEEN ROUNDED OFF.

CONSTRUCTION WARNING  
SIGN SPACING

POSTED SPEED (MPH)	"X" SIGN SPACINGS (FEET)
30 OR LESS	120
35	120
40	240
45	320
50	400
55	500
60	600
65	700
70	800

LEGEND

- CONSTRUCTION AREA
- OPEN TO TRAFFIC

Texas Department of Transportation  
Houston District

BOULEVARD  
CLOSURES

TCPTC 3050-96

FILE#	DN#	CK#	DW#	CK#
© TxDOT 2006 REV. 5/2006	DIST HOU	FED REG 6	PROJECT NO.	SHEET 24
	COUNTY HARRIS	CONTROL 1685	SECT 05	JOB 115 HIGHWAY SH 6

STD. H-15


DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

**BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:**

- The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
- The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
- The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- As shown on BC(2), the OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER (see Sign Detail G20-10T) and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. However, the TRAFFIC FINES DOUBLE sign will not be required on projects consisting solely of mobile operation work, such as striping or milling edgeline rumble strips. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits.
- Except for devices required by Note 10, traffic control devices should be in place only while work is actually in progress or a definite need exists.
- The Engineer has the final decision on the location of all traffic control devices.
- Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

**WORKER SAFETY APPAREL NOTES:**

- Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.



**SIGN DETAIL (G20-10T)**

Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources and may be found on-line at the web address given below or by contacting:

Texas Department of Transportation  
 Traffic Operations Division - TE  
 Phone (512) 416-3118

<b>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT</b> <a href="http://www.txdot.gov">http://www.txdot.gov</a>	
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)	
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)	
MATERIAL PRODUCER LIST (MPL)	
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"	
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)	
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)	
TRAFFIC ENGINEERING STANDARD SHEETS	

SHEET 1 OF 12



**BARRICADE AND CONSTRUCTION  
 GENERAL NOTES  
 AND REQUIREMENTS**


**BC(1)-14**

FILE:	bc-14.dgn	DN:	TxDOT	CR:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	1685	SECT	05	JOB	115	HIGHWAY	SH 6
REVISIONS		DIST		COUNTY		SHEET NO.			
4-03	5-10	8-14	HOU		HARRIS		25		
9-07	7-13								

DATE: FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

**TYPICAL LOCATION OF CROSSROAD SIGNS**



- May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
  - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume. This information shall be shown in the plans.
  - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
  - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
  - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
  - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

**T-INTERSECTION**



**CSJ LIMITS AT T-INTERSECTION**

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

**TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING<sup>1,5,6</sup>**

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Spacing "X" Feet (Apprx.)
CW20 <sup>4</sup>	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25			50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"	55	500 <sup>2</sup>
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" x 48"	48" x 48"	60	600 <sup>2</sup>
			65	700 <sup>2</sup>
			70	800 <sup>2</sup>
			75	900 <sup>2</sup>
			80	1000 <sup>2</sup>
			*	* <sup>3</sup>


\* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

**GENERAL NOTES**


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

**WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS**




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS**



**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS**



**NOTES**

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "X" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- \* The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
- \*\* Required CSJ Limit signing. See Note 10 on BC(1). TRAFFIC FINES DOUBLE signs will not be required on projects consisting solely of mobile operations work.
- \* Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
- \* Contractor will install a regulatory speed limit sign at the end of the work zone.

**LEGEND**

—	Type 3 Barricade
○ ○ ○	Channelizing Devices
⬇	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



**BARRICADE AND CONSTRUCTION PROJECT LIMIT**

**BC(2)-14**

FILE: bc-14.dgn	DN: TxDOT	CR: TxDOT	DN: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13	HOU	HARRIS	26	


DATE: FILE:

# TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project.

Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



## GUIDANCE FOR USE:

### LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

### SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the travelled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

### GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:
 

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
  - Law enforcement.
  - Flagger stationed next to sign.
  - Portable changeable message sign (PCMS).
  - Low-power (drone) radar transmitter.
  - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:  
FILE:

SHEET 3 OF 12




## BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC (3) - 14

FILE:	bc-14.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		1685	05	115	SH 6
9-07	8-14	DIST	COUNTY	SHEET NO.	
7-13		HOU	HARRIS	27	


**TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS**



\* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

\*\* When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

**ATTACHMENT FOR SIGN SUPPORTS**




**Nails shall NOT be allowed. Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.**

Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

**STOP/SLOW PADDLES**

1. STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24" as detailed below.
2. When used at night, the STOP/SLOW paddle shall be retroreflectorized.
3. STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
4. Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



**CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS**

1. Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
2. When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition.
3. When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
4. If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
5. If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC sheets or the CWZTCD. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
6. Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

**GENERAL NOTES FOR WORK ZONE SIGNS**

1. Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
  2. Wooden sign posts shall be painted white.
  3. Barricades shall NOT be used as sign supports.
  4. All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
  5. The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
  6. The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD). The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
  7. The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
  8. Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
  9. The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.
- DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)**
1. The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
    - a. Long-term stationary - work that occupies a location more than 3 days.
    - b. Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
    - c. Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
    - d. Short, duration - work that occupies a location up to 1 hour.
    - e. Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

**SIGN MOUNTING HEIGHT**

1. The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
2. The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
3. Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
4. Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
5. Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

**SIZE OF SIGNS**

1. The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

**SIGN SUBSTRATES**

1. The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
2. "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
3. All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

**REFLECTIVE SHEETING**

1. All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
2. White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
3. Orange sheeting, meeting the requirements of DMS-8300 Type B<sub>FL</sub> or Type C<sub>FL</sub>, shall be used for rigid signs with orange backgrounds.

**SIGN LETTERS**

1. All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

**REMOVING OR COVERING**

1. When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
2. Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
3. Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
4. When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
5. Burlap shall NOT be used to cover signs.
6. Duct tape or other adhesive material shall NOT be affixed to a sign face.
7. Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

**SIGN SUPPORT WEIGHTS**

1. Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
2. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
3. Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
4. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
5. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
6. Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
7. Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
8. Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

**FLAGS ON SIGNS**

1. Flags may be used to draw attention to warning signs. When used the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

SHEET 4 OF 12



**BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES**



**BC (4) - 14**

FILE: bc-14.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
9-07	8-14	DIST	COUNTY	SHEET NO.
7-13		HOU	HARRIS	28

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: FILE:

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.





### SKID MOUNTED WOOD SIGN SUPPORTS

LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS  $\square$




### GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



### SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS



### WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

### OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

### GENERAL NOTES

- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
- No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
- When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.

- See BC(4) for definition of "Work Duration."
- \* Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
- $\Delta$  See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



### BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 14

FILE:	bc-14.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
©	TxDOT	NOVEMBER	2002	CONT	SECT	JOB	HIGHWAY		
REVISIONS		1685	05	115	SH	6			
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13		HOU	HARRIS	29					

DATE:  
FILE:

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

# RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

## PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each. Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the T MUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

## Phase 1: Condition Lists

### Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT
RIGHT X LANES CLOSED	RIGHT X LANES OPEN
CENTER LANE CLOSED	DAYTIME LANE CLOSURES
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE
EXIT CLOSED	RIGHT LN TO BE CLOSED
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI
XXXXXXXXX BLVD CLOSED	

### Other Condition List

ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT *

\* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

## Phase 2: Possible Component Lists

### Action to Take/Effect on Travel List

MERGE RIGHT	FORM X LINES RIGHT
DETOUR NEXT X EXITS	USE XXXXX RD EXIT
USE EXIT XXX	USE EXIT I-XX NORTH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N
TRUCKS USE US XXX N	WATCH FOR TRUCKS
WATCH FOR TRUCKS	EXPECT DELAYS
EXPECT DELAYS	PREPARE TO STOP
REDUCE SPEED XXX FT	END SHOULDER USE
USE OTHER ROUTES	WATCH FOR WORKERS
STAY IN LANE *	

### Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXXX TO XXXXXXXX
US XXX TO FM XXXX

### Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

### \*\* Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

\*\* See Application Guidelines Note 6.

## APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

## WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

## FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy	HOV	Tuesday	TUES
Vehicle Highway	HWY	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT

Roadway designation = IH-number, US-number, SH-number, FM-number



Traffic Operations Division Standard

# BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)


## BC(6) - 14

FILE#	bc-14.dgn	DW#	TxDOT	CK#	TxDOT	DW#	TxDOT	CK#	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
	REVISIONS	1685	05	115	SH 6				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13		HOU	HARRIS	30					

DATE: FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




**CONCRETE TRAFFIC BARRIER (CTB)**

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



**LOW PROFILE CONCRETE BARRIER (LPCB)**




**DELINEATION OF END TREATMENTS**

**END TREATMENTS FOR CTB'S USED IN WORK ZONES**

End treatments used on CTB's in work zones shall meet crashworthy standards as defined in the National Cooperative Highway Research Report 350. Refer to the CWZTCD List for approved end treatments and manufacturers.

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential Chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

**ATTENTION**  
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

**BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS**

**WARNING LIGHTS**


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B<sub>FL</sub> or C<sub>FL</sub> Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

**WARNING LIGHTS MOUNTED ON PLASTIC DRUMS**


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

**WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS**

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.



Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

**FLASHING ARROW BOARDS**

SHEET 7 OF 12

**TRUCK-MOUNTED ATTENUATORS**

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the National Cooperative Highway Research Report No. 350 (NCHRP 350) or the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



**BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR**

**BC (7) - 14**

FILE:	bc-14.dgn	DATE:	TxDOT	CR:	TxDOT	DR:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		1685	05	115	SH 6				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13		HOU	HARRIS	31					

DATE:  
FILE:



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for incorrect results or damages resulting from its use.

**GENERAL NOTES**

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

**GENERAL DESIGN REQUIREMENTS**

Pre-qualified plastic drums shall meet the following requirements:



- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 05 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

**RETROREFLECTIVE SHEETING**

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


**BALLAST**

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




**DIRECTION INDICATOR BARRICADE**

- The Direction Indicator Barricade may be used in tapers, transitions, and other areas where specific directional guidance to drivers is necessary.
- If used, the Direction Indicator Barricade should be used in series to direct the driver through the transition and into the intended travel lane.
- The Direction Indicator Barricade shall consist of One-Direction Large Arrow (CWI-6) sign in the size shown with a black arrow on a background of Type B<sub>FL</sub> or Type C<sub>FL</sub> Orange retroreflective sheeting above a rail with Type A retroreflective sheeting in alternating 4" white and orange stripes sloping downward at an angle of 45 degrees in the direction road users are to pass. Sheeting types shall be as per DMS 8300.
- Double arrows on the Direction Indicator Barricade will not be allowed.
- Approved manufacturers are shown on the CWZTCD List. Ballast shall be as approved by the manufacturers instructions.



**DETECTABLE PEDESTRIAN BARRICADES**

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a device that is detectable by a person with a visual disability traveling with the aid of a long cane shall be placed across the full width of the closed sidewalk.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades may use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

**SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS**

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B<sub>FL</sub> or Type C<sub>FL</sub> Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations they may be placed on every drum or spaced not more than an every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (8) - 14**

FILE: bc-14.dgn	DW: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		1685 05	115	SH 6
4-03 7-13	DIST	COUNTY	SHEET NO.	
9-07 8-14	HOU	HARRIS	32	


DATE: FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



**FIXED**  
(Rigid or self-righting)

**DRIVEABLE**




(Rigid or self-righting)

**PORTABLE**


**VERTICAL PANELS (VPs)**

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual Appendix B "Treatment of Pavement Drop-offs in Work Zones" for additional guidelines on the use of VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.



**OPPOSING TRAFFIC LANE DIVIDERS (OTLD)**


- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



Fixed Base w/ Approved Adhesive (Driveable Base, or Flexible Support can be used)

- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

**CHEVRONS**



**LONGITUDINAL CHANNELIZING DEVICES (LCD)**

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10) placed near the top of the LCD along the full length of the device.

**WATER BALLASTED SYSTEMS USED AS BARRIERS**

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate NCHRP 350 crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long cones and the top of the unit shall not be less than 32 inches in height.

**HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS**

**GENERAL NOTES**

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

\*\*Taper lengths have been rounded off.  
L=Length of Taper (FT.) W=Width of Offset (FT.)  
S=Posted Speed (MPH)

**SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS**

SHEET 9 OF 12



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (9) - 14**

FILE: bc-14.dgn	DW: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT SECT	JOB	HIGHWAY	
REVISIONS	1685 05	115	SH 6	
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13	HOU	HARRIS	33	


DATE: FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


**TYPE 3 BARRICADES**

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.



PLAN VIEW


1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

**TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION**



PERSPECTIVE VIEW

These drums are not required on one-way roadway



PLAN VIEW


Increase number of plastic drums on the side of approaching traffic if the crown width makes it necessary. (minimum of 2 and maximum of 4 drums)

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector

**CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS**

THIS DEVICE SHALL NOT BE USED ON PROJECTS LET AFTER MARCH 2014.



EDGE LINE CHANNELIZER

1. This device is intended only for use in place of a vertical panel to channelize traffic by indicating the edge of the travel lane. It is not intended to be used in transitions or tapers.
2. This device shall not be used to separate lanes of traffic (opposing or otherwise) or warn of objects.
3. This device is based on a 42 inch, two-piece cone with an alternate striping pattern: four 4 inch retroreflective bands, with an approximate 2 inch gap between bands. The color of the band should correspond to the color of the edgeline (yellow for left edgeline, white for right edgeline) for which the device is substituted or for which it supplements. The reflectorized bands shall be retroreflective Type A conforming to Departmental Material Specification DMS-8300, unless otherwise noted.
4. The base must weigh a minimum of 30 lbs.

SHEET 10 OF 12





**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (10) - 14**

FILE: bc-14.dgn	DW: TxDOT	CK: TxDOT	DR: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT SECT	JOB	HIGHWAY	
REVISIONS	1685 05	115	SH 6	
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13	HOU	HARRIS	34	

28" Cones shall have a minimum weight of 9 1/2 lbs.  
 42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers used at night shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



**TRAFFIC CONTROL FOR MATERIAL STOCKPILES**

DATE: FILE:

## WORK ZONE PAVEMENT MARKINGS

### GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

### RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

### PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


### MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

### REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

## Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE  
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER  
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
  - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
  - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

### RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:  
 YELLOW - (two amber reflective surfaces with yellow body).  
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

**BC(11) - 14**





FILE: bc-14.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
	1685	05	115	SH 6
REVISIONS				
2-98 9-07	DIST	COUNTY	SHEET NO.	
1-02 7-13	HOU	HARRIS	35	
11-02 8-14				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:  
FILE:



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

## PAVEMENT MARKING PATTERNS





Pattern A is the TxDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectorized pavement markings.

## CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS





Prefabricated markings may be substituted for reflectorized pavement markings.

## EDGE & LANE LINES FOR DIVIDED HIGHWAY



Prefabricated markings may be substituted for reflectorized pavement markings.


## LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS






Prefabricated markings may be substituted for reflectorized pavement markings.

## TWO-WAY LEFT TURN LANE


## STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS



## SOLID LINES




## BROKEN LINES



## REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC(12)-14

Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."


FILE: bc-14.dgn	DN: TxDOT	CK: TxDOT	DN: TxDOT	CK: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
1-97 9-07	1685	05	115	SH 6
2-98 7-13	DIST	COUNTY	SHEET NO.	
11-02 8-14	HOU	HARRIS	36	

DATE: FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


## WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS

### SOLID LINES




### BROKEN LINES

(FOR CENTER LINE OR LANE LINE)




### WIDE DOTTED LINES

(FOR LANE DROP LINES)



### WIDE GORE MARKINGS



#### NOTES:


- Short term pavement markings may be prefabricated markings (stick down tape) or temporary flexible-reflective roadway marker tabs unless otherwise specified elsewhere in plans.
- Short term pavement markings shall NOT be used to simulate edge lines.
- Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.
- Temporary flexible-reflective roadway marker tabs will require normal maintenance replacement when used on roadways with an ADT per lane of up to 7500 vehicles with no more than 10% truck mix. When roadways exceed these values, additional maintenance replacement of devices should be planned.
- No segment of roadway open to traffic shall remain without permanent pavement markings for a period greater than 14 calendar days. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
- For two lane, two-way roadways, DO NOT PASS signs shall be erected to mark the beginning of sections where passing is prohibited and PASS WITH CARE signs shall be erected to mark the beginning of sections where passing is permitted. Signs shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and may be used to indicate the limits of no-passing zones for up to 14 calendar days. Permanent pavement markings should then be placed.
- For low volume two lane, two-way roadways of 4000 ADT or less, no-passing lines may be omitted when approved by the Engineer. DO NOT PASS and PASS WITH CARE signs shall be erected (see note 6).
- For exit gores where a lane is being dropped place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are not allowed for this purpose.

#### TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS (TABS)


- Temporary flexible-reflective roadway marker tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
- Tabs shall meet requirements of Departmental Material Specification DMS-8242.
- When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
- No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 3.

DATE:  
FILE:


## WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS




### CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO LANE TWO-WAY HIGHWAYS




### LANE LINES FOR DIVIDED HIGHWAY



### LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



### TWO-WAY LEFT TURN LANE



If raised pavement markers are used to supplement REMOVABLE short term markings, the markers shall be applied to the top of the tape at the approximate mid length of the tape. This allows an easier removal of raised markers and tape.

#### PREFABRICATED PAVEMENT MARKINGS

- Temporary Removable Prefabricated Pavement Markings shall meet the requirements of DMS-8241.
- Non-removable Prefabricated Pavement Markings shall meet the requirements of either DMS-8240 "Permanent Prefabricated Pavement Markings" or DMS-8243 "Temporary Construction-Grade Prefabricated Pavement Markings."

#### RAISED PAVEMENT MARKERS

- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and DMS-4200.

#### DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)

- DMSs referenced above can be found along with embedded links to their respective MPLs at the following website:  
[http://www.txdot.gov/business/contractors\\_consultants/material\\_specifications/default.htm](http://www.txdot.gov/business/contractors_consultants/material_specifications/default.htm)





## WORK ZONE SHORT TERM PAVEMENT MARKINGS

### WZ (STPM) - 13

FILE:	wzstpm-13.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	April 1992	CONT:	1685	SECT:	05	JOB:	115	HIGHWAY:	SH 6
REVISIONS:		DIST:		COUNTY:		SHEET NO.:			
1-97		HOU:		HARRIS					37
3-03									
7-13									

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



DEPARTMENTAL MATERIAL SPECIFICATIONS	
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY (REMOVABLE) PREFABRICATED PAVEMENT MARKINGS	DMS-8241
SIGN FACE MATERIALS	DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B <sub>FL</sub> OR TYPE C <sub>FL</sub> SHEETING
BLACK	LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING

**GENERAL NOTES**

1. If spalling or holes occur, ROUGH ROAD (CW8-8) signs should be placed in advance of the condition and be repeated every two miles where the condition persists.
2. UNEVEN LANES (CW8-11) signs shall be installed in advance of the condition and repeated every mile. Signs installed along the uneven lane condition may be supplemented with the NEXT XX MILES (CW7-3aP) plaque or Advisory Speed (CW13-1P) plaque.
3. NO CENTER LINE (CW8-12) signs and temporary pavement markings as per the WZ(STPM) standard shall be installed if yellow centerlines separating two way traffic are obscured or obliterated. Repeat NO CENTER LINE signs every two miles where the center line markings are not in place. The signs and markings shall remain in place until permanent pavement markings are installed.
4. Signs shall be spaced at the distances recommended as per BC standards.
5. Additional signs may be required as directed by the Engineer. Signs shall remain in place until final surface is applied. Signs shall be considered subsidiary to Item 502 "BARRICADES, SIGNS AND TRAFFIC HANDLING."
6. Signs shall be fabricated and mounted on supports as shown on the BC standards and/or listed on the "Compliant Work Zone Traffic Control Devices" list.
7. Short term markings shall not be used to simulate edge lines.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition.

TABLE 1		
Edge Condition	Edge Height (D)	* Warning Devices
①	Less than or equal to: 1/4" (maximum-planing) 1/2" (typical-overlay)	Sign: CW8-11
②	Less than or equal to 3"	Sign: CW8-11
③	Distance "D" may be a maximum of 3" if uneven lanes with edge condition 2 or 3 are open to traffic after work operations cease. Uneven lanes should not be open to traffic when "D" is greater than 3".	

**TRAFFIC CONTROL DURING PLANING, OVERLAY AND LEVELING OPERATIONS ARE SHOWN ELSEWHERE IN THE PLANS.**

MINIMUM WARNING SIGN SIZE	
Conventional roads	36" x 36"
Freeways/expressways, divided roadways	48" x 48"




**SIGNING FOR UNEVEN LANES**

**WZ (UL) - 13**

FILE: wzu1-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT April 1992	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
8-95 2-98 7-13	DIST	COUNTY	SHEET NO.	
1-97 3-03	HOU	HARRIS	38	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:  
FILE:



SIGNS ARE SHOWN FOR ONE DIRECTION OF TRAVEL

\* When the optional larger WORKING FOR YOU GIVE US A BRAKE (G20-7T) 192" x 96" sign is required, the locations shall be noted elsewhere in the plans.

SUMMARY OF LARGE SIGNS

BACKGROUND COLOR	SIGN DESIGNATION	SIGN	SIGN DIMENSIONS	REFLECTIVE SHEETING	SQ FT	GALVANIZED STRUCTURAL STEEL		DRILLED SHAFT
						Size	(LF)	
							① ②	24" DIA. (LF)
Orange	G20-7T		96" X 48"	Type B <sub>FL</sub> or C <sub>FL</sub>	32	▲	▲ ▲	▲
Orange	G20-7T		192" X 96"	Type B <sub>FL</sub> or C <sub>FL</sub>	128	W8x18	16 17	12

▲ See Note 6 Below

**LEGEND**

	Sign
	Large Sign
	Traffic Flow

**DEPARTMENTAL MATERIAL SPECIFICATIONS**

PLYWOOD SIGN BLANKS	DMS-7100
ALUMINUM SIGN BLANKS	DMS-7110
SIGN FACE MATERIALS	DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B <sub>FL</sub> OR TYPE C <sub>FL</sub>
BLACK	LEGEND & BORDERS	NON-REFLECTIVE ACRYLIC FILM

**GENERAL NOTES**

- See BC and SMD sheets for additional sign support details.
- Sign locations shall be approved by the Engineer.
- For projects more than two miles in length, Give Us a BRAKE signs should be repeated halfway through the project. The Give Us a Brake (CW21-1T) may be used for this purpose.
- Work zone speed limits are sometimes used in conjunction with GIVE US A BRAKE signing. See BC(3) for location and spacing of construction speed zone signing when required.
- Give Us a Brake (CW21-1T) signs and supports shall be considered subsidiary to Item 502, "Barricades, Signs and Traffic Handling."
- The 96" X 48" Working For You Give Us A BRAKE (G20-7T) may use a 1/2" or 5/8" plywood substrate or 0.125" aluminum sheeting substrate and may be supported by two 4" x 6" wood posts with drilled holes for breakaway as per BC(5) and will be subsidiary to Item 502.
- The Working For You Give Us A BRAKE (G20-7T) 192" X 96" sign shall be paid for under the following specification items:  
 Item 636 - Aluminum Signs  
 Item 647 - Large Roadside Sign Supports and Assemblies.  
 Item 416 - Drilled Shaft Foundations
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.



**WORK ZONE  
"GIVE US A BRAKE"  
SIGNS**


**WZ (BRK) - 13**

FILE: wzbrk-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT August 1995	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
6-96 5-98 7-13	DIST	COUNTY		SHEET NO.
8-96 3-03	HOU	HARRIS		39




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 7/1/2020 9:49 AM  
 FILE: H:\Trf\SIGNAL\ Luis Gonzalez\1685-05-115-SH 6 at Bellaire Blvd. and SH 6 at Beechcroft Street\STANDARDS\wzbtfs-13.dgn



**NEAR SIDE LANE CLOSURE**  
 SHORT DURATION OR SHORT TERM STATIONARY



**FAR SIDE RIGHT LANE CLOSURE**  
 SHORT DURATION OR SHORT TERM STATIONARY




**FAR SIDE LEFT LANE CLOSURE**  
 SHORT DURATION OR SHORT TERM STATIONARY

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger


Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70	700'	770'	840'	70'	140'	800'	475'	
75	750'	825'	900'	75'	150'	900'	540'	

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

**WORKERS IN BUCKET TRUCKS SHALL NOT WORK ABOVE OPEN LANES OF TRAFFIC.**



**OPERATIONS IN THE INTERSECTION**  
 SHORT DURATION



**GENERAL NOTES**

- The minimum size channelizing device is the 28" cone. 42" Two-piece cones, drums, vertical panels or barricades will be required when the device must be left unattended at night.
- Obstructions or hazards at the work area shall be clearly marked and delineated at all times.
- Flaggers and Flagger Symbol (CW20-7) signs may be required according to field conditions.
- Vehicles parked in roadway shall be equipped with at least two high intensity rotating, flashing, oscillating or strobe type lights.
- High level warning devices (flag trees) may be used at corners of the vehicle.
- When work operations are performed on existing signals, the signals may be placed in flashing red mode when approved by the engineer. If existing signals do not have power, All-Way Stop (R1-1 and R1-3P) signs may be implemented when approved by the engineer.
- For Short-Term Stationary work the buffer space "B" from the above table should be used if field conditions permit. For Short Duration (less than 1 hour) any buffer space provided will enhance the safety of the setup.
- The arrow board at this location may be omitted for Short Duration work if the work vehicle has an arrow board in operation. As an option, the arrow board may be placed at the end of the taper in the closed lane if space is not available at the beginning of the taper.
- Signs and devices for the NEAR SIDE LANE CLOSURE may be altered for a left lane closure by using a LEFT LANE CLOSED (CW20-5TL) and adding channelizing devices on the centerline to protect the work space from opposing traffic.

Texas Department of Transportation  
 Traffic Operations Division Standard


**TRAFFIC SIGNAL WORK TYPICAL DETAILS**

**WZ(BTS-1)-13**

FILE: wzbtfs-13.dgn	DATE: TxDOT	BY: TxDOT	DATE: TxDOT	BY: TxDOT
© TxDOT April 1992	COM: SECT	JOB	HIGHWAY	
REVISIONS	1685 05	115	SH 6	
2-98 10-99 7-13	DIST	COUNTY	SHEET NO.	
4-98 3-03	HOU	HARRIS	40	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 7/1/2020 9:49 AM  
 FILES: H:\Tr\Signals\Luís Gonzalez\1685-05-115\_SH 6 at Bellaire Blvd. and SH 6 at Beecham Street\STANDARDS\wzbtis-13.dgn



**TYPICAL ADVANCE SIGNAL PROJECT SIGNING**  
 FOR LONG TERM and INTERMEDIATE-TERM STATIONARY WORK OPERATIONS

- NOTES**
1. Project signing as shown shall be in place whenever signal contract work is in progress.
  2. For closely adjoining projects, advance signing may not be required in advance of each intersection, but only in advance of the intersections at the project limits. Actual locations will be as directed by the Engineer.
  3. Advance signs shall be removed when signal construction operations are no longer under way, as directed by the Engineer.
  4. Warning sign spacing shown is typical for both directions.
  5. See the Table on sheet 1 of 2 for Typical warning sign spacing.

**GENERAL NOTES FOR WORK ZONE SIGNS**

1. Signs shall be installed and maintained in a straight and plumb condition.
2. Wooden sign posts shall be painted white.
3. Barricades shall NOT be used as sign supports.
4. Nails shall NOT be used to attach signs to any support.
5. All signs shall be installed in accordance with the plans or as directed by the Engineer.
6. The Contractor shall furnish the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD).
7. The Contractor shall furnish sign supports and substrates listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD), installed as per the manufacturer's recommendations.
8. Temporary signs that have damaged or cracked substrates and/or damaged or marred reflective sheeting shall be replaced as directed by the Engineer.
9. Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1".
10. Damaged wood posts shall be replaced. Splicing wood posts will not be allowed.

**DURATION OF WORK**

1. Work zone durations are defined in Part 6, Section 6G.02 of the Texas Manual on Uniform Traffic Control Devices (TMUTCD).

**SIGN MOUNTING HEIGHT**

1. Sign height of Long-term/Intermediate-term warning signs shall be as shown on Figure 6F-1 of the TMUTCD.
2. Sign height of Short-term/Short Duration warning signs shall be as shown on Figure 6F-2 of the TMUTCD.
3. Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

**REMOVING OR COVERING**

1. When sign messages may be confusing or do not apply, the signs shall be removed or completely covered, unless otherwise approved by the Engineer.
2. When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night without damaging the sign sheeting. Burlap, or heavy materials such as plywood or aluminum shall not be used to cover signs.
3. Duct tape or other adhesive material shall NOT be affixed to a sign face.
4. Signs and anchor stubs shall be removed and holes back filled upon completion of the work.

**REFLECTIVE SHEETING**

1. All signs shall be retroreflective and constructed of sheeting meeting the requirements of the DMS and color usage table shown on this sheet.

**SIGN SUPPORT WEIGHTS**




1. Weights used to keep signs from turning over should be sandbags filled with dry, cohesionless material.
2. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
3. Rock, concrete, iron, steel or other solid objects will not be permitted for use as sign support weights.
4. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
5. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber, such as tire inner tubes, shall not be used.
6. Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
7. Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
8. Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

LEGEND	
	Sign
	Channelizing Devices
	Type 3 Barricade

DEPARTMENTAL MATERIAL SPECIFICATIONS	
SIGN FACE MATERIALS	DMS-8300
FLEXIBLE ROLL-UP REFLECTIVE SIGNS	DMS-8310

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B <sub>FL</sub> OR TYPE C <sub>FL</sub> SHEETING
WHITE	BACKGROUND	TYPE A SHEETING
BLACK	LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING

Only pre-qualified products shall be used. A copy of the "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources and may be found at the following web address:  
[http://www.txdot.gov/txdot\\_library/publications/construction.htm](http://www.txdot.gov/txdot_library/publications/construction.htm)



**PEDESTRIAN CONTROL**

1. Holes, trenches or other hazards shall be adequately protected by covering, delineating or surrounding the hazard with orange plastic pedestrian fencing or longitudinal channelizing devices, or as directed by the Engineer.
2. "CROSSWALK CLOSURES" as detailed above will require the Engineer's approval prior to installation.
3. R9 series signs shown may be placed on supports detailed on the BC standards or CWZTCD list, or when fabricated from approved lightweight plastic substrates, they may be mounted on top of a plastic drum at or near the location shown.
4. For speeds less than 45 mph longitudinal channelizing devices may be used instead of traffic barriers when approved by the Engineer. Attenuation of blunt ends and installation of water filled devices shall be as per BC(9) and manufacturer's recommendations.
5. Location of devices are for general guidance. Actual device spacing and location must be field adjusted to meet actual conditions.
6. Where pedestrians with visual disabilities normally use the closed sidewalk Detectable Pedestrian Barricades should be used instead of the Type 3 Barricades shown.
7. The width of existing sidewalk should be maintained if practical.
8. Pavement markings for mid-black crosswalks shall be paid for under the appropriate bid items.
9. When crosswalks or other pedestrian facilities are closed or relocated, temporary facilities shall be detectable and shall include accessibility features consistent with the features present in the existing pedestrian facility.





**TRAFFIC SIGNAL WORK BARRICADES AND SIGNS**

**WZ (BTS-2) - 13**

FILE: wzbtis-13.dgn	DATE: TxDOT	BY: TxDOT	DATE: TxDOT	DATE: TxDOT
©TxDOT April 1992	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685 05	115	SH 6	
2-98 10-99 7-13	DIST	COUNTY	SHEET NO.	
4-98 3-03	HOU	HARRIS	41	


BEGIN PROJECT  
 BEGIN ACP OVERLAY  
 STA. 961+00.00



LIMIT OF PROP. 2.5" MILLING, SEAL COAT AND  
 2" ACP OVERLAY (TOM-F & TOM-C)

**NOTE:**

1. USE SLOW SPEED DURING MILLING TO AVOID DAMAGE OF THE REMAINING ASPHALT, SO A FINE TEXTURE IS ACHIEVED.
2. THE SEAL COAT (ITEM 316) WILL BE COVERED WITH THE THIN OVERLAY MIXTURE (TOM) (ITEM 347) PRIOR TO REOPENING TO TRAFFIC EACH DAY. THE ROADWAY WILL NOT BE OPENED TO TRAFFIC UNTIL THE TOM AND WORK ZONE PAVEMENT MARKING ARE IN PLACE.
3. FOR LIMITS OF ACP OVERLAY AT DRIVEWAYS AND ROADWAYS, SEE "INTERSECTION DETAILS".
4. FOR PAVEMENT MARKING, SEE "PAVEMENT MARKINGS LAYOUT" AND STANDARD SHEETS. ELIMINATING RAISED PAVEMENT MARKERS IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
5. REMOVE DIRT, DUST, OR OTHER LOOSE MATERIAL BEFORE PLACING SEAL COAT, NO ADDITIONAL PAYMENT WILL BE MADE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.



Beata  
 Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT,  
 ou=West Harris AO,  
 email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.30 11:39:03 -05'00'

N.T.S. 1 OF 6





PLAN LAYOUT  
 SH 6

FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 42
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6

DIR: 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 FILE: PLANLAYOUT.DGN  
 LEVELS DISPLAYED: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32

LEVELS DISPLAYED  
 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16  
 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63  
 DIR:  
 FILE: PLANLAYOUT.DGN



**NOTE:**

1. USE SLOW SPEED DURING MILLING TO AVOID DAMAGE OF THE REMAINING ASPHALT, SO A FINE TEXTURE IS ACHIEVED.
2. THE SEAL COAT (ITEM 316) WILL BE COVERED WITH THE THIN OVERLAY MIXTURE (TOM) (ITEM 347) PRIOR TO REOPENING TO TRAFFIC EACH DAY. THE ROADWAY WILL NOT BE OPENED TO TRAFFIC UNTIL THE TOM AND WORK ZONE PAVEMENT MARKING ARE IN PLACE.
3. FOR LIMITS OF ACP OVERLAY AT DRIVEWAYS AND ROADWAYS, SEE "INTERSECTION DETAILS".
4. FOR PAVEMENT MARKING, SEE "PAVEMENT MARKINGS LAYOUT" AND STANDARD SHEETS. ELIMINATING RAISED PAVEMENT MARKERS IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
5. REMOVE DIRT, DUST, OR OTHER LOOSE MATERIAL BEFORE PLACING SEAL COAT, NO ADDITIONAL PAYMENT WILL BE MADE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.





**Beata Kwater, P.E.**  
 Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT,  
 ou=West Harris AO,  
 email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.30 11:39:44 -05'00'

N.T.S. 2 OF 6



PLAN LAYOUT  
 SH 6

FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 43
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6



LIMIT OF PROP. 2.5" MILLING, SEAL COAT AND 2" ACP OVERLAY (TOM-F & TOM-C)

**NOTE:**

1. USE SLOW SPEED DURING MILLING TO AVOID DAMAGE OF THE REMAINING ASPHALT, SO A FINE TEXTURE IS ACHIEVED.
2. THE SEAL COAT (ITEM 316) WILL BE COVERED WITH THE THIN OVERLAY MIXTURE (TOM) (ITEM 347) PRIOR TO REOPENING TO TRAFFIC EACH DAY. THE ROADWAY WILL NOT BE OPENED TO TRAFFIC UNTIL THE TOM AND WORK ZONE PAVEMENT MARKING ARE IN PLACE.
3. FOR LIMITS OF ACP OVERLAY AT DRIVEWAYS AND ROADWAYS, SEE "INTERSECTION DETAILS".
4. FOR PAVEMENT MARKING, SEE "PAVEMENT MARKINGS LAYOUT" AND STANDARD SHEETS. ELIMINATING RAISED PAVEMENT MARKERS IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
5. REMOVE DIRT, DUST, OR OTHER LOOSE MATERIAL BEFORE PLACING SEAL COAT, NO ADDITIONAL PAYMENT WILL BE MADE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.



Beata Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT, ou=West Harris AO, email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.30 11:40:22 -05'00'



N.T.S. 3 OF 6



PLAN LAYOUT  
SH 6

FED. RD. DIV. NO.	STATE PROJECT NO.		SHEET NO.
6			44
STATE	DIST.	COUNTY	
TEXAS	12	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6

PLOTTED FROM: C:\PROJECTS\SH 6\DRAWINGS\PLAN LAYOUT.DGN  
 FILE: PLAN LAYOUT.DGN



LIMIT OF PROP. 2.5" MILLING, SEAL COAT AND  
2" ACP OVERLAY (TOM-F & TOM-C)

**NOTE:**

1. USE SLOW SPEED DURING MILLING TO AVOID DAMAGE OF THE REMAINING ASPHALT, SO A FINE TEXTURE IS ACHIEVED.
2. THE SEAL COAT (ITEM 316) WILL BE COVERED WITH THE THIN OVERLAY MIXTURE (TOM) (ITEM 347) PRIOR TO REOPENING TO TRAFFIC EACH DAY. THE ROADWAY WILL NOT BE OPENED TO TRAFFIC UNTIL THE TOM AND WORK ZONE PAVEMENT MARKING ARE IN PLACE.
3. FOR LIMITS OF ACP OVERLAY AT DRIVEWAYS AND ROADWAYS, SEE "INTERSECTION DETAILS".
4. FOR PAVEMENT MARKING, SEE "PAVEMENT MARKINGS LAYOUT" AND STANDARD SHEETS. ELIMINATING RAISED PAVEMENT MARKERS IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
5. REMOVE DIRT, DUST, OR OTHER LOOSE MATERIAL BEFORE PLACING SEAL COAT, NO ADDITIONAL PAYMENT WILL BE MADE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.

DIR: 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 FILE: PLANLAYOUT.DGN  
 LEVELS DISPLAYED: 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32



Beata Kwater, P.E.



Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT,  
 ou=West Harris AO,  
 email=Beata.Kwater@txdot.gov,  
 c=US  
 Date: 2020.10.30 11:40:57 -05'00'

N.T.S. 4 OF 6



PLAN LAYOUT  
SH 6

FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 45
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6



LIMIT OF PROP. 2.5" MILLING, SEAL COAT AND 2" ACP OVERLAY (TOM-F & TOM-C)

**NOTE:**

1. USE SLOW SPEED DURING MILLING TO AVOID DAMAGE OF THE REMAINING ASPHALT, SO A FINE TEXTURE IS ACHIEVED.
2. THE SEAL COAT (ITEM 316) WILL BE COVERED WITH THE THIN OVERLAY MIXTURE (TOM) (ITEM 347) PRIOR TO REOPENING TO TRAFFIC EACH DAY. THE ROADWAY WILL NOT BE OPENED TO TRAFFIC UNTIL THE TOM AND WORK ZONE PAVEMENT MARKING ARE IN PLACE.
3. FOR LIMITS OF ACP OVERLAY AT DRIVEWAYS AND ROADWAYS, SEE "INTERSECTION DETAILS".
4. FOR PAVEMENT MARKING, SEE "PAVEMENT MARKINGS LAYOUT" AND STANDARD SHEETS. ELIMINATING RAISED PAVEMENT MARKERS IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
5. REMOVE DIRT, DUST, OR OTHER LOOSE MATERIAL BEFORE PLACING SEAL COAT, NO ADDITIONAL PAYMENT WILL BE MADE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.

LEVELS DISPLAYED  
 DIR: 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 FILE: PLANLAYOUT.DGN  
 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63



Beata Kwater, P.E.  
 Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT, ou=West Harris AO,  
 email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.30 11:41:30 -05'00'

N.T.S. 5 OF 6



PLAN LAYOUT  
SH 6

FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 46
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6

END ACP OVERLAY  
STA. 1032+00.00

END PROJECT  
STA. 1034+45.00




ASPHALT WIDTH VARIES (108'-0" TYP)

MATCH LINE STA. 1030+00

LATERNA LANE

LIMIT OF PROP. 2.5" MILLING,  
SEAL COAT AND 2" ACP OVERLAY  
(TOM-F & TOM-C)


PAV. MRKGS ONLY



**NOTE:**

1. USE SLOW SPEED DURING MILLING TO AVOID DAMAGE OF THE REMAINING ASPHALT, SO A FINE TEXTURE IS ACHIEVED.
2. THE SEAL COAT (ITEM 316) WILL BE COVERED WITH THE THIN OVERLAY MIXTURE (TOM) (ITEM 347) PRIOR TO REOPENING TO TRAFFIC EACH DAY. THE ROADWAY WILL NOT BE OPENED TO TRAFFIC UNTIL THE TOM AND WORK ZONE PAVEMENT MARKING ARE IN PLACE.
3. FOR LIMITS OF ACP OVERLAY AT DRIVEWAYS AND ROADWAYS, SEE "INTERSECTION DETAILS".
4. FOR PAVEMENT MARKING, SEE "PAVEMENT MARKINGS LAYOUT" AND STANDARD SHEETS. ELIMINATING RAISED PAVEMENT MARKERS IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
5. REMOVE DIRT, DUST, OR OTHER LOOSE MATERIAL BEFORE PLACING SEAL COAT, NO ADDITIONAL PAYMENT WILL BE MADE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.

LEVELS DISPLAYED  
 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16  
 DIR: 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 FILE: PLANLAYOUT.DGN  
 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63



Beata  
Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
DN: cn=Beata Kwater, P.E., o=TXDOT,  
ou=West Harris AO,  
email=Beata.Kwater@txdot.gov, c=US  
Date: 2020.10.30 11:42:09 -05'00'

N.T.S. 6 OF 6




PLAN LAYOUT  
SH 6

FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 47
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6



**DETAIL "A"**




**LEGEND:**




LIMIT OF PROP. 1/2" PLANING AND 1/2" ACP OVERLAY (ITEM 340) OR AS DIRECTED BY THE ENGINEER IN THE FIELD. TACK COAT WOULD BE REQUIRED UNDER ITEM 340.

**LIMIT OF PLANING AND ACP OVERLAY AT ASPHALT INTERSECTING STREETS (MAJOR AND MINOR)**


**DETAIL "B"**




**LIMIT OF PLANING AND ACP OVERLAY AT CONCRETE INTERSECTING STREETS (MAJOR AND MINOR)**



**SECTION "A - A"**



**SECTION "B - B"**



**Beata Kwater, P.E.**

Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT, ou=West Harris AO, email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.14 10:58:36 -05'00'


NTS



**INTERSECTION DETAILS**



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			48
STATE	DIST.	COUNTY	
TEXAS	HOU	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6

BEGIN PAV. MRKGS  
STA. 961+00.00



LEGEND:

- (A) RE PM W/RET REQ TY I (W)6" (SLD) (100 MIL)
- (B) RE PM W/RET REQ TY I (W)6" (BRK) (100 MIL)
- (C) REFL PAV MRK TY I (W)8" (SLD) (100 MIL)
- (D) REFL PAV MRK TY I (W)12" (SLD) (100 MIL)
- (E) REFL PAV MRK TY I (W)24" (SLD) (100 MIL)
- (F) RE PV MRK TY I (BLACK)6" (SHADOW) (100MIL)
- (H) REFL PAV MRK TY I (W) (WORD) (100 MIL)
- (J) REFL PAV MRK TY I (W) (ARROW) (100 MIL)
- (M) REFL PAV MRK TY I (W)6" (DOT) (100 MIL)
- (N) REFL PAV MRK TY II (W)12" (SLD)
- (O) REFL PAV MRK TY II (Y)12" (SLD)
- (S) REFL PAV MRKR TY II-C-R



Beata  
Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
DN: cn=Beata Kwater, P.E., o=TXDOT,  
ou=West Harris AO,  
email=Beata.Kwater@txdot.gov, c=US  
Date: 2020.10.20 13:18:55 -05'00'

N.T.S.


1 OF 6



PAVEMENT MARKING  
LAYOUT  
SH 6



FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 49
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6

LEVELS DISPLAYED  
DIR: 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16  
FILE: 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
49 50 51 52 53 54 55 56 57 58 59 60 61 62 63



LEGEND:

- Ⓐ RE PM W/RET REQ TY I (W) 6" (SLD) (100 MIL)
- Ⓑ RE PM W/RET REQ TY I (W) 6" (BRK) (100 MIL)
- Ⓒ REFL PAV MRK TY I (W) 8" (SLD) (100 MIL)
- Ⓓ REFL PAV MRK TY I (W) 12" (SLD) (100 MIL)
- Ⓔ REFL PAV MRK TY I (W) 24" (SLD) (100 MIL)
- Ⓕ RE PV MRK TY I (BLACK) 6" (SHADOW) (100MIL)
- Ⓖ REFL PAV MRK TY I (W) (WORD) (100 MIL)
- Ⓙ REFL PAV MRK TY I (W) (ARROW) (100 MIL)
- Ⓜ REFL PAV MRK TY I (W) 6" (DOT) (100 MIL)
- Ⓝ REFL PAV MRK TY II (W) 12" (SLD)
- Ⓞ REFL PAV MRK TY II (Y) 12" (SLD)
- Ⓢ REFL PAV MRKR TY II-C-R



Beata Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT,  
 ou=West Harris AO,  
 email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.20 13:19:28 -05'00'

N.T.S.



2 OF 6



PAVEMENT MARKING LAYOUT SH 6



FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 50
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6

LEVELS DISPLAYED  
 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16  
 DIR: 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 FILE: 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63



LEGEND:

- Ⓐ RE PM W/RET REQ TY I (W) 6" (SLD) (100 MIL)
- Ⓑ RE PM W/RET REQ TY I (W) 6" (BRK) (100 MIL)
- Ⓒ REFL PAV MRK TY I (W) 8" (SLD) (100 MIL)
- Ⓓ REFL PAV MRK TY I (W) 12" (SLD) (100 MIL)
- Ⓔ REFL PAV MRK TY I (W) 24" (SLD) (100 MIL)
- Ⓕ RE PV MRK TY I (BLACK) 6" (SHADOW) (100MIL)
- Ⓖ REFL PAV MRK TY I (W) (WORD) (100 MIL)
- Ⓙ REFL PAV MRK TY I (W) (ARROW) (100 MIL)
- Ⓜ REFL PAV MRK TY I (W) 6" (DOT) (100 MIL)
- Ⓝ REFL PAV MRK TY II (W) 12" (SLD)
- Ⓞ REFL PAV MRK TY II (Y) 12" (SLD)
- Ⓢ REFL PAV MRKR TY II-C-R



Beata  
Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
DN: cn=Beata Kwater, P.E., o=TXDOT,  
ou=West Harris AO,  
email=Beata.Kwater@txdot.gov, c=US  
Date: 2020.10.20 13:20:11 -05'00'


N.T.S. 3 OF 6



PAVEMENT MARKING  
LAYOUT  
SH 6



LEVELS DISPLAYED	DIR:	FILE:
1 3 4 5 6 7 8 9 10 11 12 13 14 15 16		
17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32		
33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48		
49 50 51 52 53 54 55 56 57 58 59 60 61 62 63		

FED. RD. DIV. NO.	STATE PROJECT NO.		SHEET NO.
6			51
STATE	DIST.	COUNTY	
TEXAS	12	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6



LEGEND:

- Ⓐ RE PM W/RET REQ TY I (W) 6" (SLD) (100 MIL)
- Ⓑ RE PM W/RET REQ TY I (W) 6" (BRK) (100 MIL)
- Ⓒ REFL PAV MRK TY I (W) 8" (SLD) (100 MIL)
- Ⓓ REFL PAV MRK TY I (W) 12" (SLD) (100 MIL)
- Ⓔ REFL PAV MRK TY I (W) 24" (SLD) (100 MIL)
- Ⓕ RE PV MRK TY I (BLACK) 6" (SHADOW) (100MIL)
- Ⓖ REFL PAV MRK TY I (W) (WORD) (100 MIL)
- Ⓙ REFL PAV MRK TY I (W) (ARROW) (100 MIL)
- Ⓜ REFL PAV MRK TY I (W) 6" (DOT) (100 MIL)
- Ⓝ REFL PAV MRK TY II (W) 12" (SLD)
- Ⓞ REFL PAV MRK TY II (Y) 12" (SLD)
- Ⓢ REFL PAV MRKR TY II-C-R



Beata  
Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
DN: cn=Beata Kwater, P.E.,  
o=TXDOT, ou=West Harris AO,  
email=Beata.Kwater@txdot.gov,  
c=US  
Date: 2020.10.20 13:20:44 -05'00'

N.T.S.



4 OF 6



PAVEMENT MARKING  
LAYOUT  
SH 6



FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 52
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6

LEVELS DISPLAYED  
DIR: 1 3 4 5 6 7 8 9 10 11 12 13 14 15 16  
FILE: 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
49 50 51 52 53 54 55 56 57 58 59 60 61 62 63



LEGEND:

- Ⓐ RE PM W/RET REQ TY I (W) 6" (SLD) (100 MIL)
- Ⓑ RE PM W/RET REQ TY I (W) 6" (BRK) (100 MIL)
- Ⓒ REFL PAV MRK TY I (W) 8" (SLD) (100 MIL)
- Ⓓ REFL PAV MRK TY I (W) 12" (SLD) (100 MIL)
- Ⓔ REFL PAV MRK TY I (W) 24" (SLD) (100 MIL)
- Ⓕ RE PV MRK TY I (BLACK) 6" (SHADOW) (100MIL)
- Ⓖ REFL PAV MRK TY I (W) (WORD) (100 MIL)
- Ⓙ REFL PAV MRK TY I (W) (ARROW) (100 MIL)
- Ⓜ REFL PAV MRK TY I (W) 6" (DOT) (100 MIL)
- Ⓝ REFL PAV MRK TY II (W) 12" (SLD)
- Ⓞ REFL PAV MRK TY II (Y) 12" (SLD)
- Ⓢ REFL PAV MRKR TY II-C-R



Beata  
Kwater, P.E.

Digitally signed by Beata Kwater, P.E.  
DN: cn=Beata Kwater, P.E., o=TXDOT,  
ou=West Harris AO,  
email=Beata.Kwater@txdot.gov,  
c=US  
Date: 2020.10.20 13:21:20 -05'00'

N.T.S.


5 OF 6



PAVEMENT MARKING  
LAYOUT  
SH 6



FED. RD. DIV. NO. 6	STATE PROJECT NO.		SHEET NO. 53
STATE TEXAS	DIST. 12	COUNTY HARRIS	
CONT. 1685	SECT. 05	JOB 115	HIGHWAY NO. SH 6

LEVELS DISPLAYED	DIR:
1 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63	FILE:



LEGEND:

- (A) RE PM W/RET REQ TY I (W) 6" (SLD) (100 MIL)
- (B) RE PM W/RET REQ TY I (W) 6" (BRK) (100 MIL)
- (C) REFL PAV MRK TY I (W) 8" (SLD) (100 MIL)
- (D) REFL PAV MRK TY I (W) 12" (SLD) (100 MIL)
- (E) REFL PAV MRK TY I (W) 24" (SLD) (100 MIL)
- (F) RE PV MRK TY I (BLACK) 6" (SHADOW) (100MIL)
- (H) REFL PAV MRK TY I (W) (WORD) (100 MIL)
- (J) REFL PAV MRK TY I (W) (ARROW) (100 MIL)
- (M) REFL PAV MRK TY I (W) 6" (DOT) (100 MIL)
- (N) REFL PAV MRK TY II (W) 12" (SLD)
- (O) REFL PAV MRK TY II (Y) 12" (SLD)
- (S) REFL PAV MRKR TY II-C-R



Beata Kwater, P.E.  
 Digitally signed by Beata Kwater, P.E.  
 DN: cn=Beata Kwater, P.E., o=TXDOT, ou=West Harris AO, email=Beata.Kwater@txdot.gov, c=US  
 Date: 2020.10.20 13:21:53 -05'00'

N.T.S. 6 OF 6



## PAVEMENT MARKING LAYOUT SH 6

FED. RD. DIV. NO. 6	STATE PROJECT NO.	SHEET NO. 54
STATE TEXAS	DIST. 12	COUNTY HARRIS
CONT. 1685	SECT. 05	JOB 115
HIGHWAY NO. SH 6		


DIR:	FILE:
LEVELS DISPLAYED	
1 3 4 5 6 7 8 9 10 11 12 13 14 15 16	
17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32	
33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48	
49 50 51 52 53 54 55 56 57 58 59 60 61 62 63	

# INDEX OF SHEETS

SHEET NO.	DESCRIPTION	SHEET NO.	DESCRIPTION
I. GENERAL		III. ROADWAY DETAILS	
1	TITLE SHEET	42-47	PLAN LAYOUT SH 6
2	INDEX OF SHEETS	48	INTERSECTION DETAILS
3-4	TYPICAL SECTION	IV. TRAFFIC ITEMS	
5-12, 12A	GENERAL NOTES AND SPECIFICATION DATA	49-54	PAVEMENT MARKINGS LAYOUT SH 6
13-14	ESTIMATE AND QUANTITY SHEET	55	* PM -20 (HOU DIST)
15-17	SUMMARY OF QUANTITIES	56	* PM (2) -20
18	SUMMARY OF QUANTITIES-TRAFFIC SIGNAL	57	* PM (3) -20
19	IRI DATA	58	* PM (CLL) -14 (HOU DIST)
II. TRAFFIC CONTROL PLAN		59	* PM (DOT) -11 (HOU DIST)
20	TCP-ONE & TWO LANE CLOSURE	60	* PM(WAS)-07 (HOU DIST)
21	TCP-CENTER LANE CLOSURE AT INTERSECTION	61	TRAFFIC SIGNAL NOTES SH 6 AT BELLAIRE BLVD/BEECHNUT ST
22	* TCP(3-1) -13	62	TRAFFIC SIGNAL EXISTING LAYOUT SH 6 AT BELLAIRE BLVD
23	* TCP(3-3) -14	63, 63A	TRAFFIC SIGNAL PROPOSED LAYOUT SH 6 AT BELLAIRE BLVD
24	* TCPTC 3050 -96 (HOU DIST)	64	TRAFFIC SIGNAL EXISTING LAYOUT SH 6 AT BEECHNUT ST
25	* BC (1) -14	65, 65A	TRAFFIC SIGNAL PROPOSED LAYOUT SH 6 AT BEECHNUT ST
26	* BC (2) -14	66	* ED(1) -14
27	* BC (3) -14	67	* ED(3) -14
28	* BC (4) -14	V. ENVIRONMENTAL ISSUES	
29	* BC (5) -14	68	EPIC - HOU DIST
30	* BC (6) -14	69	SWP3 - HOU DIST
31	* BC (7) -14	70	EC(1) -16 (MOD)
32	* BC (8) -14		
33	* BC (9) -14		
34	* BC (10) -14		
35	* BC (11) -14		
36	* BC (12) -14		
37	* WZ (STPM) -13		
38	* WZ (UL) -13		
39	* WZ (BRK) -13		
40	* WZ (BTS-1) -13		
41	* WZ (BTS-2) -13		

THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ABOVE (\*)  
HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE  
SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.

\_\_\_\_\_, PE \_\_\_\_\_  
DATE



**Texas Department of Transportation** ©2020

## INDEX OF SHEETS

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			2
STATE	DIST.	COUNTY	
TEXAS	HOU	HARRIS	
CONT.	SECT.	JOB	HIGHWAY NO.
1685	05	115	SH 6


LEVELS DISPLAYED REF FILES ATT.

1 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100




# REFLECTIVE RAISED PAVEMENT MARKERS FOR VEHICLE POSITIONING GUIDANCE



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




**CENTERLINE FOR ALL TWO LANE ROADWAYS**



**CENTERLINE & LANE LINES  
FOR FOUR LANE TWO-WAY HIGHWAYS**



**CENTERLINE AND LANE LINES FOR TWO-WAY LEFT TURN LANE**




**LANE LINES FOR ONE-WAY ROADWAY (NON-FREEWAY FACILITIES)**


Raised pavement markers Type II-C-R shall have clear face toward normal traffic and red face toward wrong-way traffic.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**Type I (Top View)**



**Type II (Top View)**



**SECTION A**

**RAISED PAVEMENT MARKERS**




## POSITION GUIDANCE USING RAISED MARKERS REFLECTORIZED PROFILE MARKINGS PM(2) - 20

FILE: pm2-20.dgn	DN:	CK:	DW:	CK:
© TxDOT April 1977	CONT	SECT	JOB	HIGHWAY
4-92 2-10 REVISIONS	1685	05	115	SH 6
5-00 2-12	DIST	COUNTY		SHEET NO.
8-00 6-20	HOU	HARRIS		56


### GENERAL NOTES

- All raised pavement markers placed in broken lines shall be placed in line with and midway between the stripes.
- On concrete pavements the raised pavement markers should be placed to one side of the longitudinal joints.



### REFLECTORIZED PROFILE PATTERN DETAIL

USING REFLECTIVE PROFILE PAVEMENT MARKINGS




### NOTE

Profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.

DATE:  
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



Posted Speed	D (ft)	L (ft)
30 MPH	460	$L = \frac{WS^2}{60}$
35 MPH	565	
40 MPH	670	L = WS
45 MPH	775	
50 MPH	885	
55 MPH	990	
60 MPH	1,100	
65 MPH	1,200	
70 MPH	1,250	
75 MPH	1,350	

**NOTES**


- Lane reduction pavement markings are used where the number of through lanes is reduced because of narrowing of the roadway or because of a section of on-street parking in what would otherwise be a through lane. For Texas Super 2 Passing Lanes, see TS2(PL) standard sheets.
- On divided highways, an additional W9-1R "RIGHT LANE ENDS" sign may be installed in the median aligned with the W9-1R sign on the right side of the highway.
- Lane reduction arrows are required for speeds of 45 mph or greater. An optional third lane reduction arrow may be added based on engineering judgement. If used, the optional third lane reduction arrow should be centered between the first and last lane reduction arrows.
- For lane reductions on Freeways and Expressways, signing shall conform to the TxDOT Freeway Signing Handbook.

**GENERAL NOTES**

- Lane use word and arrow markings shall be used where through lanes approaching an intersection become mandatory turn lanes. Lane use word and arrow markings should be used in auxiliary lanes of substantial length. Lane use arrow markings or word and arrow markings may be used in other lanes and turn bays for emphasis. Details for words and arrows are as shown in the Standard Highway Sign Designs for Texas.
- When lane-use words and arrow markings are used, two sets of arrows should be used if the length of the bay is greater than 180 feet. When a single lane use arrow or word and arrow marking is used for a short turn lane, it should be located at or near the upstream end of the full-width turn lane.
- Use raised pavement marker Type I-C with undivided highways, flush medians and two way left turn lanes. Use raised pavement marker Type II-C-R with divided highways and raised medians.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.


MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




A two-way left-turn (TWLTL) lane-use arrow pavement marking should be used at or just downstream from the beginning of a two-way left-turn lane within a corridor. Repeating the marking after each intersection or dedicated turn bay is not required unless stated elsewhere in the plans.


**TYPICAL TRANSITION FOR TWLTL AND DIVIDED HIGHWAY**




**TYPICAL TWLTL AT ONE-WAY STREET AND RIGHT TURN AUXILIARY LANE**



**TYPICAL TWO-LANE HIGHWAY INTERSECTION WITH LEFT TURN BAYS**



**TYPICAL TWLTL AT TWO-WAY CROSS STREET AND RIGHT TURN LANE DROP**



DETAIL A


DETAIL B

Texas Department of Transportation  
Traffic Safety Division Standard

**TWO-WAY LEFT TURN LANES, RURAL LEFT TURN BAYS, AND LANE REDUCTION PAVEMENT MARKINGS PM(3) - 20**


FILE: pm3-20.dgn	DN:	CK:	DW:	CK:
© TxDOT April 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	1685	05	115	SH 6
5-00 2-10	DIST	COUNTY	SHEET NO.	
8-00 2-12	HOU	HARRIS	57	
3-03 6-20				

DATE:  
FILE:



CONTRAST LANE LINES USING PREFABRICATED PAVEMENT MARKINGS

➔ DIRECTION OF TRAFFIC




CONTRAST LANE LINES USING LIQUID APPLICATIONS  
(MULTIPOLYMER, THERMOPLASTIC, ETC.)

\* AS SHOWN ON THE PLANS.


PAVEMENT MARKINGS  
(CONTRAST LANE LINES)

PM (CLL) - 14

FILE:	DN:	CK:	DW:	CK:
© TxDOT 2003	DIST	FED REG	PROJECT NO.	SHEET
REVISIONS 01-19-08 02-19-08 10-2019 '9" to 10"	HOU	6		58
COUNTY	CONTROL	SECT	JOB	HIGHWAY
HARRIS	1685	05	115	SH 6



DETAIL "A"



4" or 6" WHITE (DOT) (TO INTERSECTING ROADWAY WITHOUT MANDATORY TURN LANES). SEE DETAIL "A"

4" or 6" WHITE (DOT) (TO INTERSECTING ROADWAY WITH ONE EXCLUSIVE AND ONE OPTIONAL TURN LANE). SEE DETAIL "A"

4" or 6" WHITE (DOT) SEE DETAIL "A"

8" WHITE SOLID W/ RAISED REFLECTIVE PAVEMENT MARKERS @ 20' SPA.

290+00

☉ MAINLANES

4" or 6" WHITE (DOT) (TO INTERSECTING ROADWAY W/ TWO EXCLUSIVE LEFT TURN LANES). SEE DETAIL "A"

4" or 6" WHITE (DOT) (TO INTERSECTING ROADWAY WITHOUT MANDATORY TURN LANES). SEE DETAIL "A"

\* 4" or 6" WHITE (SLD) 40 LF EA.







TYPICAL PLACEMENT OF DOTTED EXTENSION AT INTERSECTIONS



PAVEMENT MARKINGS (DOTTED EXTENSION DETAILS)

PM (DOT) - 11


FILE:	DN:	CK:	DW:	CK:
© TxDOT 2010	DIST	FED REG	PROJECT NO.	SHEET
REVISIONS	HOU	6		59
4/2010	COUNTY	CONTROL	SECT	JOB
4/2011	HARRIS	1685	05	115
				HIGHWAY
				SH 6




DIRECTION OF VIEW

ISOMETRIC ARROW


12 INCH GRID  
 AREA = 42 SQ. FT.  
 RIGHT LANE DROP ARROW  
 (FOR LEFT LANE, USE MIRROR IMAGE)



U-L ARROW



DIAMOND SYMBOL



SCALE 1/4" = 1'

Texas Department of Transportation  
 Houston District

PAVEMENT MARKINGS  
 (WORDS, ARROWS & SYMBOLS)


PM(WAS) -07

FILE:	DN:	CK:	DW:	CK:
© TxDOT 2007	DIST	FED REG	PROJECT NO.	SHEET
REVISIONS 03-19-07	HOU	6		60
	COUNTY	CONTROL	SECT	JOB
	HARRIS	1685	05	115
				SH 6

DATE: Sep 17, 2020  
FILE: SG01 SH 6 AT Bellaire Blvd and Beechnut St NOTES FOR UPGRADE TRAFFIC CONTROL SYSTEM.dgn

NOTES FOR PERMANENT TRAFFIC SIGNAL(S):

1. ONCE THE CONTRACT HAS BEEN EXECUTED OR DURING THE KICK-OFF MEETING, THE ENGINEER OR HIS/HER REPRESENTATIVE WILL COORDINATE OR ARRANGE FOR THE RADAR EQUIPMENT TO BE PROVIDED BY THE DEPARTMENT.
2. THE ENGINEER OR HIS/HER REPRESENTATIVE WILL COORDINATE THE ORDERING OF THE RADAR EQUIPMENT BY USING THE FORCE ACCOUNT.
3. ENGINEER OR HIS/HER REPRESENTATIVE WILL CONTACT ARNOLD TREVINO AT 713-866-7101 TO ORDER THE RADAR EQUIPMENT.
4. RADAR PRESENCE DETECTION DEVICE MUST UTILIZE TRUE-PRESENCE DETECTION. SYSTEMS USING LOCKING ALGORITHMS TO ATTEMPT PRESENCE DETECTION WILL NOT BE ACCEPTED.
5. RADAR ADVANCE DETECTION DEVICE MUST CONTINUOUSLY TRACK VEHICLE SPEED, DISTANCE, AND ESTIMATED TIME OF ARRIVAL.
6. RADAR PRESENCE DETECTION DEVICES AND RADAR ADVANCE DETECTION DEVICES MUST BE COMPATIBLE WITH EACH OTHER AND FROM THE SAME MANUFACTURER.
7. COMMUNICATION AND POWER TO THE RADAR DEVICES SHALL BE VIA CONTINUOUS CABLE RUN OF UP TO 1000 FEET WITH THE USE OF REPEATERS.
8. FINAL PLACEMENT OF RADAR DEVICES TO BE APPROVED BY ENGINEER.
9. THE VENDORS' REPRESENTATIVES OF THE RADAR EQUIPMENT SUPPLIED FOR THIS PROJECT MUST SUPERVISE THE INSTALLATION, SETUP AND TESTING OF THIS EQUIPMENT AND BE FACTORY CERTIFIED. THE REPRESENTATIVE MUST BE ON SITE DURING THIS TIME. ANY EQUIPMENT REQUIRED FOR SETUP AND OPERATION OF THE RADAR DEVICES MUST BE PROVIDED TO TXDOT OR THE CITY UPON COMPLETION. THE VENDORS' REPRESENTATIVE MUST PROVIDE TRAINING TO THE MUNICIPALITIES WHO WILL BE RESPONSIBLES FOR THE MAINTENANCE OF THE RADAR EQUIPMENT AFTER ACCEPTANCE OF THE PROJECT.
10. PROVIDE CONTINUED OPERATION OF THE EXISTING SIGNAL(S) DURING CONSTRUCTION AND UNTIL THE PROPOSED OPERATION IS COMPLETED.
11. DURING CONSTRUCTION OF THE PROPOSED SIGNAL WORK, IF THE EXISTING TRAFFIC SIGNAL EQUIPMENT REQUIRES REPLACEMENT DUE TO WEAR, DETERIORATION, OR ANY CIRCUMSTANCE OVER WHICH THE CONTRACTOR HAS NO CONTROL, THE EQUIPMENT WILL BE FURNISHED BY THE DEPARTMENT AT NO COST TO THE CONTRACTOR. INSTALL THIS EQUIPMENT AT NO COST TO THE DEPARTMENT. SUCH MATERIALS WILL BE PROVIDED AT THE DEPARTMENT'S SIGNAL SHOP LOCATED AT 6810 KATY ROAD, HOUSTON, TEXAS. CONTACT MR. MICHAEL AWA, P.E., AT TELEPHONE NUMBER (713) 802-5661.
12. MAINTAIN THE INTEGRITY AND FUNCTION OF EACH EXISTING SIGNALIZED INTERSECTION. ONCE THE INTEGRITY OR FUNCTION OF THE SIGNAL HAS BEEN ALTERED, PURSUE THE WORK AT THAT LOCATION WITHOUT DELAY OR INTERRUPTION TO RESTORE OPERATION TO ITS ORIGINAL OR FINAL OPERATIONAL DESIGN.
13. IF EXISTING GROUND BOXES ARE FOUND TO BE INSUFFICIENT IN SIZE TO ACCOMMODATE THE PROPOSED CONDUITS AND CABLES AS SHOWN ON THE PLANS OR IF THEY HAVE BEEN DAMAGED TO THE EXTENT THEY WILL NOT ACCOMMODATE THE ADDITIONAL CONDUITS AND CABLES, REPLACE THE GROUND BOX WITH A NEW GROUND BOX (SIZE AS REQUIRED) OR INSTALL A NEW GROUND BOX ADJACENT TO THE EXISTING GROUND BOX AS APPROVED BY THE ENGINEER. SUCH REPAIR OR REPLACEMENT IS SUBSIDIARY TO ITEM 624, "GROUND BOX".
14. IF THE ENGINEER IN THE FIELD FINDS THE EXISTING CONDUITS IN THE SIGNAL POLE FOUNDATION INADEQUATE TO ACCOMMODATE THE PROPOSED CABLES, ATTACH A NEW CONDUIT (SIZE AS REQUIRED) TO THE SIGNAL POLE FOUNDATION. IF ADEQUATE ROOM EXISTS BETWEEN THE SIGNAL POLE AND THE FOUNDATION, INSTALL THE CONDUIT UNDER THE SIGNAL POLE. IF ADEQUATE ROOM DOES NOT EXIST BETWEEN THE SIGNAL POLE AND THE FOUNDATION, ATTACH THE CONDUIT TO THE SIGNAL POLE FOR THE PROPOSED CABLES. SUCH WORK IS CONSIDERED SUBSIDIARY TO THE BID ITEM 618, "CONDUIT".
15. CLAMP ALL CONDUITS ATTACHED TO SIGNAL POLE FOUNDATIONS OR STEEL POLES WITH CONDUIT STRAPS AND CLAMP BACKS (MALLEABLE IRON) AT A MAXIMUM SPACING OF 5 FT. CENTER TO CENTER.
16. THE EXISTING VIVDS EQUIPMENT USED FOR VEHICLE DETECTION IS TO BE REMOVED AND DELIVERED TO THE DEPARTMENT'S SIGNAL SHOP, 6810 KATY ROAD, HOUSTON, TEXAS OR AS DIRECTED BY THE DEPARTMENT'S ENGINEER.



09/25/2020

**SH 6  
AT BELLAIRE BLVD/BEECHNUT ST  
TRAFFIC SIGNAL  
NOTES**

© 2020			
CONT	SECT	JOB	HIGHWAY
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	61	

DATE: Sep 25, 2020 FILE: H:\Trr\Signal\Luia Gonzalez\1685-05-115.SH 6 at Bellaire Blvd, and SH 6 at Beechnut Street\SG01.SH 6 at Bellaire Blvd\_Signal Layout 1.dgn

**LEGEND:**

- TRAFFIC DIRECTION
- POWER POLE
- POWER POLE W/TRANSFORMER
- OVERHEAD POWER LINE
- EXISTING SIGNAL HEAD
- EXISTING LUMINAIRE
- EXISTING VIVDS CAMERA (TO BE REMOVED)
- EXISTING GROUND BOX
- EXISTING SIGNAL CONTROLLER



**EXISTING SIGN SCHEDULE:**

**Bellaire Blvd**      **SH 6**

**CALLOUTS:**

- (A) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (B) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (C) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (D) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (E) EXIST. ELECTRICAL SERVICE POLE
- (F) EXIST. SIGNAL CONTROLLER (TO REMAIN)
- (G) EXIST. PEDESTAL POLE W/PEDESTRIAN SIGNAL HEAD AND PUSH BUTTON

**EXISTING SIGNAL HEADS SCHEDULE:**



**NOTES:**


1. THE CONTRACTOR SHALL LOCATE ALL UTILITIES PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL CONTACT PUBLIC AND PRIVATE UTILITIES FOR LOCATION OF UNDERGROUND FACILITIES AT LEAST 72 HOURS PRIOR TO ANY DRILLING, BORING, TRENCHING OR EXCAVATING. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY DAMAGE CAUSED BY CONTRACTOR'S FAILURE TO LOCATE AND PRESERVE THESE UTILITIES WHETHER UNDERGROUND, ABOVE GROUND OR OVERHEAD. UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS.

EXISTING GROUND BOX FOR LOOP DETECTOR ONLY TO BE REMOVED



09/25/2020

**SH 6 AT BELLAIRE BLVD TRAFFIC SIGNAL EXISTING LAYOUT**




CONT	SECT	JOB	HIGHWAY
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	62	

DATE: Sep 25, 2020  
 FILE: H:\rfs\signal\Luís Gonzalez\1685-05-115.SH 6 at Bellaire Blvd, and SH 6 at Beechnut Street\5001\_SH 6 at Bellaire Blvd\_Signal Layout 1A.dgn

- LEGEND:**
- TRAFFIC DIRECTION
  - POWER POLE
  - POWER POLE W/TRANSFORMER
  - OVERHEAD POWER LINE
  - EXISTING SIGNAL HEAD
  - EXISTING LUMINAIRE
  - EXISTING GROUND BOX
  - EXISTING SIGNAL CONTROLLER
  - PROP. PRESENCE RADAR
  - PROP. ADVANCE RADAR
  - PROP. CONDUIT (TRENCH)

- CALLOUTS:**
- (A) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
  - (B) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
  - (C) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
  - (D) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
  - (E) EXIST. ELECTRICAL SERVICE POLE
  - (F) EXIST. SIGNAL CONTROLLER (TO REMAIN)
  - (G) EXIST. PEDESTAL POLE W/PEDESTRIAN SIGNAL HEAD AND PUSH BUTTON





**PROPOSED RADAR DETECTIONS SCHEDULE:**

ADV1	DESIGNATED FOR SOUTHBOUND APPROACHING VEHICLES (SH 6)
ADV2	DESIGNATED FOR NORTHBOUND APPROACHING VEHICLES (SH 6)
ADV3	DESIGNATED FOR EASTBOUND APPROACHING VEHICLES (BELLAIRE BLVD)
ADV4	DESIGNATED FOR WESTBOUND APPROACHING VEHICLES (BELLAIRE BLVD)
PR1	DESIGNATED FOR WESTBOUND VEHICLES (BELLAIRE BLVD)
PR2	DESIGNATED FOR SOUTHBOUND VEHICLES (SH 6)
PR3	DESIGNATED FOR EASTBOUND VEHICLES (BELLAIRE BLVD)
PR4	DESIGNATED FOR NORTHBOUND VEHICLES (SH 6)




**EXISTING SIGNAL HEADS SCHEDULE:**



- NOTES:**
- THE CONTRACTOR SHALL LOCATE ALL UTILITIES PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL CONTACT PUBLIC AND PRIVATE UTILITIES FOR LOCATION OF UNDERGROUND FACILITIES AT LEAST 72 HOURS PRIOR TO ANY DRILLING, BORING, TRENCHING OR EXCAVATING. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY DAMAGE CAUSED BY CONTRACTOR'S FAILURE TO LOCATE AND PRESERVE THESE UTILITIES WHETHER UNDERGROUND, ABOVE GROUND OR OVERHEAD. UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS.
  - PROPOSED RADAR CONDUCTORS IN RUN D TO BE ROUTED INSIDE POLE D BY PULLING OUT THE EXISTING VIVDS CAMERA CONDUCTORS. IF UNABLE OR UNFEASIBLE, ROUTE THEM INSIDE A 3" RM CONDUIT ATTACHED TO STEEL SIGNAL POLE D.

**SH 6 AT BELLAIRE BLVD TRAFFIC SIGNAL PROPOSED LAYOUT**



09/25/2020

1685 05		115	SH 6
HOU	HARRIS	63	



DATE: Sep 25, 2020  
 FILE: H:\Trf51gnola\Luis Gonzalez\1685-05-115-SH 6 at Bellaire Blvd, and SH 6 at Beechnut Street\5001\_SH 6 AT Bellaire Blvd\_Signal\_Layout 2.dgn

CONDUIT AND CONDUCTOR RUNS								
RUN NO.	CONDUIT (618)				RADAR (6292)		RADAR (6292)	
	PVC		RM		PRES. RADAR		ADV. RADAR	
	3" (SCHD 80)		3"		# 18/2C & #22/4C		# 18/2C & #22/4C	
	(6053)		(6074)		(Subsidiary)		(Subsidiary)	
	NO.	TRENCH	NO.	LENGTH	NO.	LENGTH	NO.	LENGTH
EA	LF	EA	LF	EA	LF	EA	LF	
1	1	10			4	10	4	10
2	1	15			4	15	4	15
3					1	145	1	145
4					2	150	2	150
5					1	150	1	150
D			1	20	4	35	4	35
<b>TOTAL (LF)</b>		25		20		835		835

<b>EST. TOTAL</b>		30		25		880		880
-------------------	--	----	--	----	--	-----	--	-----

**NOTES:**

1. PROPOSED RADAR CONDUCTORS IN RUN D TO BE ROUTED INSIDE POLE D BY PULLING OUT THE EXISTING VIVDS CAMERA CONDUCTORS. IF UNABLE OR UNFEASIBLE, ROUTE THEM INSIDE A 3" RM CONDUIT ATTACHED TO STEEL SIGNAL POLE D.

**SH 6  
 AT BELLAIRE BLVD  
 TRAFFIC SIGNAL  
 PROPOSED LAYOUT**



09/25/2020

SHEET 2 OF 2

© 2020

CONT	SECT	JOB	HIGHWAY
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	63A	

DATE: Sep 25, 2020  
 FILE: H:\Trrsignals\Luis Gonzalez\1685-05-115-SH 6 at Bellaire Blvd, and SH 6 at Beechnut Street\5601\_SH 6 at Beechnut St-Signal Layout 1.dgn

**LEGEND:**

- TRAFFIC DIRECTION
- POWER POLE
- POWER POLE W/TRANSFORMER
- OVERHEAD POWER LINE
- EXISTING SIGNAL HEAD
- EXISTING LUMINAIRE
- EXISTING VIVDS CAMERA (TO BE REMOVED)
- EXISTING GROUND BOX
- EXISTING SIGNAL CONTROLLER

**EXISTING SIGN SCHEDULE:**



**Beechnut St**

**SH 6**

**CALLOUTS:**

- (A) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (B) EXIST. 34' STEEL STRAIN SIGNAL POLE AND ELECTRICAL SERVICE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (C) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (D) EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (E) EXIST. SIGNAL CONTROLLER (TO REMAIN)

**EXISTING SIGNAL HEADS SCHEDULE:**




**NOTES:**

1. THE CONTRACTOR SHALL LOCATE ALL UTILITIES PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL CONTACT PUBLIC AND PRIVATE UTILITIES FOR LOCATION OF UNDERGROUND FACILITIES AT LEAST 72 HOURS PRIOR TO ANY DRILLING, BORING, TRENCHING OR EXCAVATING. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY DAMAGE CAUSED BY CONTRACTOR'S FAILURE TO LOCATE AND PRESERVE THESE UTILITIES WHETHER UNDERGROUND, ABOVE GROUND OR OVERHEAD. UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS.



09/25/2020

**SH 6 AT BEECHNUT ST TRAFFIC SIGNAL EXISTING LAYOUT**



© 2829			
CONTRACT	SECTION	JOB	HIGHWAY
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	64	

DATE: Sep 25, 2020  
 FILE: H:\irf\signals\Luis Gonzalez\1685-05-115.SH 6 at Beechnut Street\5001.SH 6 at Beechnut St-Signal Layout 1A.dwg

**LEGEND:**

- TRAFFIC DIRECTION
- POWER POLE
- POWER POLE W/TRANSFORMER
- OVERHEAD POWER LINE
- EXISTING SIGNAL HEAD
- EXISTING LUMINAIRE
- EXISTING GROUND BOX
- EXISTING SIGNAL CONTROLLER
- PROP. PRESENCE RADAR
- PROP. ADVANCE RADAR
- PROP. CONDUIT (TRENCH)



**CALLOUTS:**

- (A)** EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (B)** EXIST. 34' STEEL STRAIN SIGNAL POLE AND ELECTRICAL SERVICE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (C)** EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (D)** EXIST. 34' STEEL STRAIN SIGNAL POLE WITH PROPOSED ADVANCED AND PRESENCE DETECTORS.
- (E)** EXIST. SIGNAL CONTROLLER (TO REMAIN)

**PROPOSED RADAR DETECTIONS SCHEDULE:**

ADV1		DESIGNATED FOR SOUTHBOUND APPROACHING VEHICLES (SH 6)
ADV2		DESIGNATED FOR NORTHBOUND APPROACHING VEHICLES (SH 6)
ADV3		DESIGNATED FOR EASTBOUND APPROACHING VEHICLES (BEECHNUT ST)
ADV4		DESIGNATED FOR WESTBOUND APPROACHING VEHICLES (BEECHNUT ST)
PR1		DESIGNATED FOR WESTBOUND VEHICLES (BEECHNUT ST)
PR2		DESIGNATED FOR SOUTHBOUND VEHICLES (SH 6)
PR3		DESIGNATED FOR EASTBOUND VEHICLES (BEECHNUT ST)
PR4		DESIGNATED FOR NORTHBOUND VEHICLES (SH 6)


**EXISTING SIGNAL HEADS SCHEDULE:**



**NOTES:**

- THE CONTRACTOR SHALL LOCATE ALL UTILITIES PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL CONTACT PUBLIC AND PRIVATE UTILITIES FOR LOCATION OF UNDERGROUND FACILITIES AT LEAST 72 HOURS PRIOR TO ANY DRILLING, BORING, TRENCHING OR EXCAVATING. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY DAMAGE CAUSED BY CONTRACTOR'S FAILURE TO LOCATE AND PRESERVE THESE UTILITIES WHETHER UNDERGROUND, ABOVE GROUND OR OVERHEAD. UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS.
- PROPOSED RADAR CONDUCTORS IN RUN B TO BE ROUTED INSIDE POLE B BY PULLING OUT THE EXISTING VIVDS CAMERA CONDUCTORS. IF UNABLE OR UNFEASIBLE, ROUTE THEM INSIDE A 3" RM CONDUIT ATTACHED TO STEEL SIGNAL POLE B.

**SH 6  
 AT BEECHNUT ST  
 TRAFFIC SIGNAL  
 PROPOSED LAYOUT**



09/25/2020

© 2020			
CONT	SECT	JOB	HIGHWAY
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	65	

DATE: SEP 25, 2020  
 FILE: H:\Trf\signals\Luis Gonzalez\1685-05-115.SH 6 at Beechnut Street\SG01.SH 6 AT Beechnut St\_Signal Layout 2.dgn

DWG  
 C11  
 DR1  
 C11

CONDUIT AND CONDUCTOR RUNS								
RUN NO.	CONDUIT (618)				RADAR (6292)		RADAR (6292)	
	PVC		RM		PRES. RADAR		ADV. RADAR	
	3" (SCHD 80)		3"		# 18/2C & #22/4C		# 18/2C & #22/4C	
	(6053)		(6074)		(Subsidiary)		(Subsidiary)	
	NO.	TRENCH	NO.	LENGTH	NO.	LENGTH	NO.	LENGTH
EA	LF	EA	LF	EA	LF	EA	LF	
1	1	10			4	10	4	10
2	1	5			4	5	4	5
3					1	150	1	150
4					2	145	2	145
5					1	145	1	145
B			1	20	4	35	4	35
<b>TOTAL (LF)</b>		15		20		785		785

<b>EST. TOTAL</b>		20		25		825		825
-------------------	--	----	--	----	--	-----	--	-----

**NOTES:**

1. PROPOSED RADAR CONDUCTORS IN RUN B TO BE ROUTED INSIDE POLE B BY PULLING OUT THE EXISTING VIVDS CAMERA CONDUCTORS. IF UNABLE OR UNFEASIBLE, ROUTE THEM INSIDE A 3" RM CONDUIT ATTACHED TO STEEL SIGNAL POLE B.

**SH 6  
 AT BEECHNUT ST  
 TRAFFIC SIGNAL  
 PROPOSED LAYOUT**



09/25/2020

SHEET 2 OF 2

CONT	SECT	JOB	HIGHWAY
1685	05	115	SH 6
DIST	COUNTY	SHEET NO.	
HOU	HARRIS	65A	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

## GENERAL NOTES FOR ALL ELECTRICAL WORK

- The location of all conduits, junction boxes, ground boxes, and electrical services is diagrammatic and may be shifted to accommodate field conditions.
- Provide new and unused materials. Ensure that all materials and installations comply with the applicable articles of the National Electrical Code (NEC), TxDOT standards and specifications, National Electrical Manufacturers Association (NEMA), and are listed by Underwriters Laboratories (UL) or a Nationally Recognized Testing Lab (NRTL). NRTLs such as Canadian Standard Association (CSA), Intertek Testing Services NA Inc., or FM Approvals LLC can be considered equivalent to UL. Where reference is made to NEMA listed devices, International Electrotechnical Commission (IEC) listed devices will not be considered an acceptable equal to a NEMA listed device. Acceptable devices may have both a NEMA and IEC listing. Faulty fabrication or poor workmanship in any material, equipment, or installation is justification for rejection. Replace or reinstall rejected material or equipment at no additional cost to the Department.
- Miscellaneous nuts, bolts and hardware, except for high strength bolts, may be stainless steel when plans specify galvanized, provided the bolt size is 1/2 in. or less in diameter.
- Provide the following test equipment as required by the Engineer to confirm compliance with the contract and the NEC: voltmeter, ammeter, megohm meter (1000 volt DC), ground resistance tester, torque wrenches, and torque screwdrivers. Ensure all equipment has been properly calibrated within the last year. Provide calibration certification to the Engineer upon request. Operate test equipment during inspection as requested by the Engineer.
- Install grounding as shown on the plans and in accordance with the NEC. Ensure all metallic conduits; metal poles; luminaires; and metal enclosures are bonded to the equipment grounding conductor. Provide stranded bare copper or green insulated grounding conductors. Ground rods, connectors, and bonding jumpers are subsidiary to the various bid items.
- When required by the Engineer, notify the Department in writing of materials from the Material Producers List (MPL) intended for use on each project. Prequalified materials are listed on the MPL on TxDOT's website under "Roadway Illumination and Electrical Supplies." No substitutions will be allowed for materials on this list.

## CONDUIT

### A. MATERIALS

- Provide conduit, junction boxes, fittings, and hardware as per TxDOT Departmental Material Specification (DMS) 11030 "Conduit" and Item 618 "Conduit" of TxDOT's "Standard Specifications For Construction And Maintenance Of Highways, Streets, And Bridges," latest edition. Provide conduits listed under Item 618 on the MPL under "Roadway Illumination and Electrical Supplies." Provide conduit types according to the descriptive code or as shown on the plans. Do not substitute other types of conduits for those shown. Provide liquidtight flexible metal conduit (LFMC) when flexible conduit is called for on galvanized steel rigid metallic conduit (RMC) systems. Provide liquidtight flexible nonmetallic conduit (LFNC) when flexible conduit is called for on polyvinyl chloride (PVC) systems.
- Provide galvanized steel RMC for all exposed conduits, unless otherwise shown on the plans. Properly bond all metal conduits.
- Unless otherwise shown on the plans, provide junction boxes with a minimum size as shown in the following table, which applies to the greatest number of conductors entering the box through one conduit with no more than four conduits per box. When a mixture of conductor sizes is present, count the conductors as if all are of the larger size. For situations not applicable to the table, size junction boxes in accordance with NEC.


AWG	3 CONDUCTORS	5 CONDUCTORS	7 CONDUCTORS
#1	10" x 10" x 4"	12" x 12" x 4"	16" x 16" x 4"
#2	8" x 8" x 4"	10" x 10" x 4"	12" x 12" x 4"
#4	8" x 8" x 4"	10" x 10" x 4"	10" x 10" x 4"
#6	8" x 8" x 4"	8" x 8" x 4"	10" x 10" x 4"
#8	8" x 8" x 4"	8" x 8" x 4"	8" x 8" x 4"

- Junction boxes with an internal volume of less than 100 cu. in. and supported by entering raceways must have threaded entries or hubs identified for the intended purpose and supported by connection of two or more rigid metal conduits. Secure conduit within 3 ft. of the enclosure or within 18 in. of the enclosure if all conduit entries are on the same side. Mechanically secure all junction boxes with an internal volume greater than 100 cu. inches.
- Provide hot dipped galvanized cast iron or sand cast aluminum outlet boxes for junction boxes containing only 10 AWG or 12 AWG conductors. Do not use die cast aluminum boxes. Size outlet boxes according to the NEC.
- Do not use intermediate metal conduit (IMC) or electrical metallic tubing (EMT) unless specifically required by the plan sheets. When EMT is called for, provide junction boxes made from galvanized steel sheeting, listed and approved for outdoor use, unless otherwise noted on the plans. Size all galvanized steel junction boxes in accordance with the NEC. Provide junction boxes for IMC conduit systems that meet the same requirements for junction boxes used with RMC systems.
- Provide PVC junction boxes intended for outdoor use on PVC conduit systems, unless otherwise noted on the plans.

- Provide PVC elbows in PVC conduit systems, unless otherwise shown on the plans. Use only a flat, high tensile strength polyester fiber pull tape for pulling conductors through the PVC conduit system. When galvanized steel RMC elbows are specifically called for in the plans and any portion of the RMC elbow is buried less than 18 in., ground the RMC elbow by means of a grounding bushing on a rigid metal extension. Grounding of the rigid metal elbow is not required if the entire RMC elbow is encased in a minimum of 2 in. of concrete. PVC extensions are allowed on these concrete encased rigid metal elbows. RMC or PVC elbows are subsidiary to various bid items.
- When required, provide High-Density Polyethylene (HDPE) conduit with factory installed internal conductors according to Item 622 "Duct Cable." At the Contractor's request and with approval by the Engineer, substitute HDPE conduit with no conductors for bored schedule 40 or schedule 80 PVC conduit bid under Item 618. Ensure bored HDPE substituted for PVC is schedule 40 and of the same size PVC called for in the plans. Ensure the substituted HDPE meets the requirements of Item 622, except that the conduit is supplied without factory-installed conductors. Make the transition of the HDPE conduit to PVC (or RMC elbow when required) at the bore pit. Provide conduit of the size and schedule as shown on the plans. Do not extend substituted conduit into ground boxes or foundations. Provide PVC or galvanized steel RMC elbows as called for at all ground boxes and foundations.
- Use two-hole straps when supporting 2 in. and larger conduits. On electrical service poles, properly sized stainless steel or hot dipped galvanized one-hole standoff straps are allowed on the service riser conduit.

### B. CONSTRUCTION METHODS

- Provide and install expansion joint conduit fittings on all structure-mounted conduits at the structure's expansion joints to allow for movement of the conduit. In addition, provide and install expansion joint fittings on all continuous runs of galvanized steel RMC conduit externally exposed on structures such as bridges at maximum intervals of 150 ft. When requested by the project Engineer, supply manufacturer's specification sheet for expansion joint conduit fittings. Repair or replace expansion joint fittings that do not allow for movement at no additional cost to the Department. Provide the method of determining the amount of expansion to the Engineer upon request. Do not use LFMC or LFNC as a substitute for the required expansion conduit fittings.
- Space all conduit supports at maximum intervals of 5 ft. Install conduit spacers when attaching metal conduit to surface of concrete structures. See "Conduit Mounting Options" on ED(2). Install conduit support within 3 ft. of all enclosures and conduit terminations.
- Do not attach conduit supports directly to pre-stressed concrete beams except as shown specifically in the plans or as approved by the Engineer.
- Unless otherwise shown on the plans, jack or bore conduit placed beneath existing roadways, driveways, sidewalks, or after the base or surfacing operation has begun. Backfill and compact the bore pits below the conduit per Item 476 "Jacking, Boring, or Tunneling Pipe or Box" prior to installing conduit or duct cable to prevent bending of the connections.
- When placing conduit in the sub-grade of new roadways, backfill all trenches with excavated material unless otherwise noted on the plans. When placing conduit in the sub-base of new roadways, backfill all trenches with cement-stabilized base as per requirements of Items 110 "Excavation", 400 "Excavation and Backfill for Structures", 401 "Flowable Backfill", 402 "Trench Excavation Protection", and 403 "Temporary Special Shoring."
- Provide and place warning tape approximately 10 in. above all trenched conduit as per Item 618.
- During construction, temporarily cap or plug open ends of all conduit and raceways immediately after installation to prevent entry of dirt, debris and animals. Temporary caps constructed of durable duct tape are allowed. Tightly fix the tape to the conduit opening. Clean out the conduit and prove it clear in accordance with Item 618 prior to installing any conductors.
- Ensure conduit entry into the top of any enclosure is waterproof by installing conduit sealing hubs or using boxes with threaded bosses. This includes surface mounted safety switches, meter cans, service enclosures, auxiliary enclosures and junction boxes. Grounding bushings on water tight sealing hubs are not required.
- Fit the ends of all PVC conduit terminations with bushings or bell end fittings. Provide and install a grounding type bushing on all metal conduit terminations.
- Install a bonding jumper from each grounding bushing to the nearest ground rod, grounding lug, or equipment grounding conductor. Ensure all bonding jumpers are the same size as the equipment grounding conductor. Bonding of conduit used as a casing under roadways for duct cable is not required, if the duct extends the full length through the casing.
- At all electrical services, install a 6 AWG solid copper grounding electrode conductor.
- Place conduits entering ground boxes so that the conduit openings are between 3 in. and 6 in. from the bottom of the box. See the ground box detail on sheet ED(4).
- Seal ends of all conduits with duct seal, expandable foam, or by other methods approved by the Engineer. Seal conduit immediately after completion of conductor installation and pull tests. Do not use duct tape as a permanent conduit sealant. Do not use silicone caulk as a conduit sealant.
- File smooth the cut ends of all mounting strut and conduit. Before installing, paint the field cut ends of all mounting strut and RMC (threaded or non-threaded) with zinc rich paint (94% or more zinc content) to alleviate overspray. Use zinc rich paint to touch up galvanized material as allowed under Item 445 "Galvanizing." Do not paint non-galvanized material with a zinc rich paint as an alternative for materials required to be galvanized.

				Traffic Operations Division Standard	
<h1>ELECTRICAL DETAILS CONDUITS &amp; NOTES</h1>					
<h2>ED(1) - 14</h2>					
FILE:	ed1-14.dgn	DW:	CK:	DW:	CK:
© TxDOT	October 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS		1685	05	115	SH 6
		DIST	COUNTY		SHEET NO.
		HOU	HARRIS		66

# ELECTRICAL CONDUCTORS

## A. MATERIAL INFORMATION

1. Provide Type XHHW insulated conductors in accordance with Departmental Material Specification (DMS) 11040 "Conductors" and Item 620 "Electrical Conductors." Provide conductors as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies" Item 620. Color code insulated conductors in conformance with the NEC. Identify grounded (neutral) conductors with white insulation. Identify grounding conductors (ground wires) with green insulation or bare conductors. Identify ungrounded (hot) conductors with any color insulation except green, white, or gray. Keep color scheme consistent throughout the wiring system. Identify conductors 6 American Wire Gauge (AWG) and smaller by continuous color jacket. Identify electrical conductors 4 AWG and larger by continuous color jacket or by colored tape. When identifying conductors with colored tape, mark at least 6 in. of the conductor's insulation with half laps of tape.
2. Provide a solid copper 6 AWG grounding electrode conductor to bond the electrical service equipment to the concrete encased grounding electrode or the ground rod at the service location. Connect the grounding electrode conductor to the ground rod with a UL listed connector in accordance with DMS 11040. Connect the grounding electrode conductor to the concrete encased grounding electrode as shown in the plans.
3. Where two or more circuits are present in one conduit or enclosure, permanently identify the conductors of each branch circuit by attaching a non-metallic tag around both circuit conductors at each accessible location. Provide tags with two straps, large enough to indicate circuit number, letter, or other identification as shown in the plans. Print circuit identification on the tag with a permanent marker.
4. Use listed compression or screw type pressure connectors, terminal blocks, or split bolt connectors for splicing as specified in DMS 11040. Use hot melt adhesive tape to fill the gap and seal the ends of heat shrink tubing. Provide UL listed gel-filled insulating splice covers. Splicing materials, insulating materials, breakaway disconnects, splice covers, and fuse holders are subsidiary to various bid items.

## B. CONSTRUCTION METHODS

1. Use only a flat, high tensile strength polyester fiber pull tape for pulling conductors through the conduit system. After installing conductors in conduit, perform conductor pull test. If a conductor cannot be freely pulled, make any needed alterations or repairs at no additional cost to the department. Perform insulation resistance tests in accordance with Item 620. Coordinate with the Engineer to witness the tests.
2. Leave 2 ft. minimum, 3 ft. maximum length for each conductor up to the splice in ground boxes. Leave 3 ft. minimum, 4 ft. maximum length of conductor in ground boxes when pulled through with no splice. Leave 1 ft. minimum, 1.5 ft. maximum length of conductor at enclosures, weatherheads and pole bases.
3. Make splices only in junction boxes, ground boxes, pole bases, or electrical enclosures and use only listed compression or screw type pressure connectors, terminal blocks, or split bolt connectors. Insulate splices with heavy wall heat shrink tubing or gel-filled insulating splice covers to provide a watertight splice. Overlap conductor insulation with heat shrink tubing a minimum of 2 in. past both sides of the splice. Where heat shrink tubing may not shrink sufficiently to provide a watertight seal around the individual conductors, prior to heating the tubing, increase the diameter of the conductor insulation using hot melt adhesive tape to provide a watertight seal between the individual conductors and the heat shrink tubing. Ensure the tape extends past the heat shrink tubing. Use hot melt adhesive tape to fill the gap and seal the ends of heat shrink tubing. Heat shrink tubing that appears to have been burned, or overheated, is considered defective and must be replaced.
4. Size and install gel-filled insulating splice covers according to manufacturer's specifications when used in place of heat shrink tubing.
5. Wire nuts with factory applied waterproof sealant may be used for 8 AWG or smaller conductors in above ground junction boxes, but not in pole bases or ground boxes. Install wire nuts in an upright position to prevent the accumulation of water.
6. Support conductors in illumination poles with a J-hook at the top of the pole.
7. When terminating conductors, remove the insulation and jacketing material without nicking the individual strands of the conductor. Conductors with nicked individual conductor strands or removed strands will be considered damaged.
8. Replace conductors and cables that are damaged beyond repair or that fail an insulation resistance test at no additional cost to the department.
9. Do not repair damaged conductors with duct tape, electrical tape, or wire nuts. Use only approved splicing methods.
10. Do not terminate more than one conductor under a single connector, unless the connector is rated for multiple conductors. Do not exceed the pressure connector's listing for maximum number and size of conductors allowed.
11. Install breakaway connectors on conductors bid under Item 620 whenever those conductors pass through a breakaway support device. Follow manufacturer's instructions when terminating conductors to breakaway connectors. Properly torque threaded connections. Proper terminations are critical to the safe operation of breakaway devices. Trim waterproofing boots on breakaway connectors to fit snugly around the conductor to ensure waterproof connection. Only one conductor may enter a single opening in a boot. Provide waterproof boots with the correct number of openings. Leave unused openings factory sealed. Use prequalified breakaway connectors as shown on the MPL.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

12. Provide and install a separate stranded equipment grounding conductor (EGC) in all conduits that contain circuit wiring of 50 volts or more. Unless shown elsewhere, size the EGC to be the same size as the largest current carrying conductor contained in the conduit. Ensure all EGCs are bonded together at every accessible location. For traffic signal installations, provide a minimum size 8 AWG EGC. The EGC is paid for under Item 620.

## C. TEMPORARY WIRING

1. Install temporary conductors and electrical equipment in accordance with the NEC article "Temporary Installations" and Department standard sheets.
2. Provide a ground fault circuit interrupter (GFCI) for power outlets for portable electrical equipment, power tools, ice machines, ice storage bins and refrigerators located outdoors at grade. GFCI may be any one of the following: molded cord and plug set, receptacle, or circuit breaker type.
3. Use listed wire nuts with factory applied sealant for temporary wiring where approved.
4. Enclose conductor splices within a listed enclosure or ground box, or ensure the splices are more than 10 ft. above grade vertically and more than 5 ft. horizontally from any metal structure. Where installing temporary conductors in areas subject to vehicle traffic or mobile construction equipment, ensure the vertical clearance to ground is at least 18 ft. when measured at the lowest point. Ground messenger wires that support power conductors in conformance with the NEC.
5. Protect and when necessary repair any existing electrical conduits uncovered during the construction process in a timely manner and in conformance with the NEC.


## GROUND RODS & GROUNDING ELECTRODES

### A. MATERIAL INFORMATION


1. Provide and install a grounding electrode at electrical services. Provide ground rods according to DMS 11040 and the plans. Larger diameter or longer length rods may be called for in some specific locations, see the individual plans sheets. Concrete encased grounding electrodes may be called for in specific locations including electrical service, see individual plan sheets.

### B. CONSTRUCTION METHODS


1. Furnish auxiliary ground rods for lightning protection and install in soil, concrete, or both, as called for in the plans. For ground rods installed in concrete, ensure the connection of the conductor to the ground rod is readily accessible for inspection or repairs. For ground rods installed in soil, ensure that the upper end is between 2 to 4 in. below finished grade.
2. Do not place ground rods in the same drilled hole as a timber pole.
3. Install ground rods so the imprinted part number is at the upper end of the rod.
4. Remove all non-conductive coatings such as concrete splatter from the rod at the clamp location.
5. Route all conductors as short and straight as possible for connection to lightning protection ground rods. When a bend is required, ensure a minimum radius bend of four inches for these conductors.
6. Unless otherwise called for in the plans, protect grounding electrode conductors with non-metallic conduit. When protecting grounding electrode conductors with metal conduit, provide and install a grounding type bushing and properly sized bonding jumper on each end of the metal conduit.
7. Written authorization is required before installing a ground rod in a horizontal trench for rocky soil or a solid rock bottom.



**SPLICE OPTION 3  
Listed Screw Type**



**SPLICE OPTION 1  
Compression Type**



**SPLICE OPTION 2  
Split Bolt Type**

				Traffic Operations Division Standard	
<h2>ELECTRICAL DETAILS CONDUCTORS</h2>					
<h3>ED(3) - 14</h3>					
FILE:	ed3-14.dgn	DN:	TxDOT	CK:	TxDOT
© TxDOT	October 2014	CONT:	SECT:	JOB:	HIGHWAY:
REVISIONS		1685	05	115	SH 6
		DIST:	COUNTY:		SHEET NO.
		HOU:	HARRIS		67

**I. STORMWATER POLLUTION PREVENTION**

Texas Pollutant Discharge Elimination System (TPDES) TXR 150000: Stormwater Discharge Permit or Construction General Permit is required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506. Refer to Storm Water Pollution Prevention Plan (SWP3) Houston District standard plan.  
No Additional Comments

**II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS**

United States Army Corps of Engineers (USACE) Permit is required for filling, dredging, excavating or other work in water bodies, rivers, creeks, streams, wetlands or wet areas. The Contractor must adhere to all of the terms and general conditions associated with the following permit(s). If additional work not represented in the plans is required, contact the Engineer immediately.

No United States Army Corps (USACE) Permit Required

Work is authorized by the United States Army Corps of Engineers (USACE) under a Nationwide Permit (NWP) without a Pre-Construction Notification (PCN). Project specific permit was not issued by USACE, therefore is not in the plan set. The USACE general conditions are in the "General Notes."

Work is authorized by the United States Army Corps of Engineers (USACE) under a Nationwide Permit (NWP) with a Pre-Construction Notification (PCN). The project specific permit issued by the United States Army Corps of Engineers (USACE) is included in the plan set. The USACE general conditions are in the "General Notes."

Work is authorized by the United States Army Corps of Engineers (USACE) under a Individual Permit (IP). The project specific permit issued by the United States Army Corps of Engineers (USACE) is included in the plan set.

Work would be authorized by the United States Army Corps of Engineers (USACE) permit. The project specific permit issued by the USACE will be provided to the contractor.

United States Coast Guard (USCG) Permit is required for projects that involve the construction or modification (including changes to lighting) of a bridge or causeway across a water body determined to be navigable by the United States Coast Guard (USCG) under Section 9 of the Rivers and Harbors Act. If additional work not represented in the plans is required, contact the Engineer immediately.

No United States Coast Guard (USCG) Coordination Required

United States Coast Guard (USCG) Permit

United States Coast Guard (USCG) Exemption

Additional Comments

**III. CULTURAL RESOURCES**

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the area and contact the Engineer immediately.  
No Additional Comments

**IV. VEGETATION RESOURCES**

Preserve native vegetation to the extent practical. Refer to TxDOT Standard Specifications in order to comply with requirements for invasive species, beneficial landscaping and tree/brush removal.  
No Additional Comments

**V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS**

If any of the listed species below are observed, cease work in the area, do not disturb species or habitat and contact the Engineer immediately.

The work may not remove active nests (from bridges, structures, or vegetation adjacent to the roadway, etc.) during nesting season (February 15 to September 30). If removal of structures or vegetation is necessary during the nesting season, the Contractor shall conduct a bird survey no more than 3 days in advance of the clearing/demolish start date. All bird surveys shall be conducted by a Field Biologist and adhere to the guidance document "Avoiding Migratory Birds and Handling Potential Violations" found in the TxDOT Environmental Compliance Toolkits at the time of the survey. (See below for Field Biologist and Ornithologist qualifications)

No Additional Comments


Field Biologist, Ornithologist – a field biologist is defined as an individual qualified to perform field investigations, presence/absence surveys and habitat surveys for protected avian species or species of concern. A mandatory bachelor's degree in biology or a related science is required. At a minimum, the Field Biologist, Ornithologist, shall have completed and reported a minimum of three presence/absence and habitat surveys for protected avian species in the past five years. A minimum of three projects must have been conducted in Texas. Surveys shall have been performed for documentation of species in accordance with a protocol approved by USFWS or TPWD, or following generally accepted methodologies.

**VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES**

Refer to TxDOT Standard Specifications in the event potentially contaminated materials are observed, such as dead or distressed vegetation, trash disposal areas, drums, canisters, barrels, leaching or seepage of substances, unusual smells or odors, or stained soil, cease work in the area and contact the Engineer immediately.  
No Additional Comments

**VII. OTHER ENVIRONMENTAL ISSUES**

DATE: Aug 30, 2019  
FILE:

				TxDOT Houston District	
ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS  EPIC					
FILE:	EPIC Sheet.dgn	DN:	CK:	DW:	CK:
© TxDOT:	March 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS		1685	05	115	SH 6
UPDATED section V, text and added definition (10/17)		DIST	COUNTY		SHEET NO.
ADDED USCG and USACE notes in Section VII (04/18)		HOU	HARRIS		68

**SITE DESCRIPTION**

PROJECT LIMITS: FROM 560 FT NORTH OF BELLAIRE BLVD TO HARRIS/FORT BEND C/L

PROJECT DESCRIPTION: PLANING, ACP OVERLAY, TRAFFIC SIGNALS AND PAVEMENT MRKGS

MAJOR SOIL DISTURBING ACTIVITIES: PLANE ASPH CONC PAV, REMOVE GROUND BOX, AND BACKFILL

TOTAL PROJECT AREA: 18.46 AC

TOTAL AREA TO BE DISTURBED: 0.00 AC

WEIGHTED RUNOFF COEFFICIENT: 0.66 (EXISTING)  
(AFTER CONSTRUCTION): 0.66

EXISTING CONDITION OF SOIL & VEGETATIVE COVER AND % OF EXISTING VEGETATIVE COVER: THESE SOILS ARE COVERED WITH 80% TO 90% OF VARIOUS GRASSES.

NAME OF RECEIVING WATERS: MAIN RECEIVING BODY OF WATER IS BUFFALO BAYOU, SEGMENT NO. 1014

**EROSION AND SEDIMENT CONTROLS**

**SOIL STABILIZATION PRACTICES:**

- TEMPORARY SEEDING
  - PERMANENT PLANTING, SODDING, OR SEEDING
  - MULCHING
  - SOIL RETENTION BLANKET
  - BUFFER ZONES
  - PRESERVATION OF NATURAL RESOURCES
- OTHER: \_\_\_\_\_

**STRUCTURAL PRACTICES:**

- SILT FENCES
  - HAY BALES
  - ROCK BERMS
  - DIVERSION, INTERCEPTOR, OR PERIMETER DIKES
  - DIVERSION, INTERCEPTOR, OR PERIMETER SWALES
  - DIVERSION DIKE AND SWALE COMBINATIONS
  - PIPE SLOPE DRAINS
  - PAVED FLUMES
  - ROCK BEDDING AT CONSTRUCTION EXIT
  - TIMBER MATTING AT CONSTRUCTION EXIT
  - CHANNEL LINERS
  - SEDIMENT TRAPS
  - SEDIMENT BASINS
  - STORM INLET SEDIMENT TRAP
  - STONE OUTLET STRUCTURES
  - CURBS AND GUTTERS
  - STORM SEWERS
  - VELOCITY CONTROL DEVICES
  - EROSION CONTROL LOGS
- OTHER: \_\_\_\_\_

**NARRATIVE - SEQUENCE OF CONSTRUCTION (STORM WATER MANAGEMENT) ACTIVITIES:**

- AFTER THE SIGNS AND BARRICADES HAVE BEEN INSTALLED:
1. INSTALL THE SILT FENCES AS DIRECTED BY THE ENGINEER.
  2. MAINTAIN THE SILT FENCES DURING THE PROJECT.
  3. REMOVE THE SILT FENCES ON COMPLETION OF WORK AT EACH LOCATION.

**STORM WATER MANAGEMENT:**

ANY DEVICES REQUIRED TO MINIMIZE SEDIMENT RUNOFF IN THE EVENT OF A STORM WILL BE PLACED IN POSITION BEFORE CONSTRUCTION BEGINS. THE STORM WATER DRAINAGE WILL BE PROVIDED BY THE EXISTING SYSTEM ALREADY IN PLACE. WATER WITHIN THE RIGHT OF WAY WILL BE CARRIED BY DITCHES TO LOWS IN THE ROAD PROFILE WHERE IT WILL OUTFALL INTO THE RECEIVING WATERS.

POST CONSTRUCTION STORM WATER MANAGEMENT THERE WILL BE NO DEVICES INSTALLED DURING THE CONSTRUCTION PROCESS TO CONTROL STORM WATER DISCHARGES THAT WILL REMAIN AFTER CONSTRUCTION OPERATIONS HAVE BEEN COMPLETED.

**OTHER EROSION AND SEDIMENT CONTROLS:**

**MAINTENANCE:** All erosion and sediment controls will be maintained in good working order. If a repair is necessary it will be done at the earliest date possible, but no later than 7 calendar days after the surrounding exposed ground has dried sufficiently to prevent further damage from heavy equipment. The area adjacent to creeks and drainageways shall have priority followed by devices protecting storm sewer inlets.

**INSPECTION:** All inspections will be performed by a TxDOT Inspector per one of the options below as directed by the Area Engineer

1. At least every 7 calendar days
2. At least every 14 days or after 0.5 inches or more of rainfall

An inspection and maintenance report should be made for each inspection. Based on the inspection results, the controls shall be revised according to the inspection report.

**WASTE MATERIALS:** The dumpster used to store all waste material will meet all state and local city solid waste management regulations. All trash and construction debris will be deposited in the dumpster. The dumpster will be emptied as necessary or as required by local regulation and the trash will be hauled to a local dump. No construction waste material will be buried on site.

**HAZARDOUS WASTE (INCLUDING SPILL REPORTING):** In the event of a spill which may be considered hazardous, the Houston District Safety Office shall be contacted immediately at 713-802-5952.

**SANITARY WASTE:** ALL SANITARY WASTE WILL BE COLLECTED FROM THE PORTABLE UNITS AS NECESSARY OR AS REQUIRED BY LOCAL REGULATIONS BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

**OFFSITE VEHICLE TRACKING:**

- HAUL ROADS DAMPENED FOR DUST CONTROL
- LOADED HAUL TRUCKS TO BE COVERED WITH TARPULIN
- EXCESS DIRT ON ROAD REMOVED DAILY
- STABILIZED CONSTRUCTION ENTRANCE

OTHER: \_\_\_\_\_

**REMARKS:** Disposal areas, stockpiles, and haul roads shall be constructed in a manner that will minimize and control the sediment that may enter receiving waterways. Disposal areas shall not be located in any waterway, waterbody or streambed. Construction staging areas and vehicle maintenance areas shall be constructed by the Contractor in a manner which minimizes the runoff of all pollutants. All waterways shall be cleared as soon as practical of temporary embankments, temporary bridges, matting, falsework, piling, debris, and other obstructions placed during construction operations that are not part of the finished work.



*B. Kwator, P.E.*  
*10/1/20*




**TxDOT STORM WATER POLLUTION PREVENTION PLAN**

**SWP3**


FILE: <u>STDGI.DGN</u>	DATE TxDOT: _____	DATE TxDOT: _____	DATE TxDOT: _____	DATE TxDOT: _____
© TxDOT JANUARY 2007	DIST: <u>HOU</u>	FED REC: <u>6</u>	PROJECT NO: _____	SHEET: <u>68</u>
REVISIONS	COUNTY: <u>HARRIS</u>	CONTROL: <u>1685</u>	SECT: <u>05</u>	JOB: <u>115</u>
8/2010 INSPECTION NOTE				SH: <u>6</u>
9/2013 INSPECTION NOTE				
11/2013 SPEC TO SWP3				
03/2014 SPEC				



DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



TEMPORARY SEDIMENT CONTROL FENCE



HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

**SEDIMENT CONTROL FENCE USAGE GUIDELINES**


A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT<sup>2</sup>. Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.

**LEGEND**  
Sediment Control Fence  
SCF

**GENERAL NOTES**

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.



VERTICAL TRACKING



*B. Kwater, P.E.*  
10/1/20

Texas Department of Transportation		Design Division Standard	
<b>TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE &amp; VERTICAL TRACKING EC(1)-16 (MOD)</b>			
FILE: ec116	Dist TxDOT	Dist KM	Dist VP
© TxDOT: JULY 2016	CONTRACT	SECTION	JOB
REVISIONS		1685 05	115 SH 6
		DIST	COUNTY
		12	HARRIS
		SHEET NO. 70	