

INDEX OF SHEETS

SEE SHEET NO 2

STATE OF TEXAS DEPARTMENT OF TRANSPORTATION

PLANS OF PROPOSED STATE HIGHWAY IMPROVEMENT

FEDERAL AID PROJECT NO. STP 2021 (277) TAPS

HARRISON COUNTY HIGHWAY - CIDER LN

NET LENGTH OF PROJECT= 1,905.00 FT. = 0.360 MI.

LIMITS: FROM US 80 TO CAL YOUNG RD

FOR THE CONSTRUCTION OF PEDESTRIAN INFRASTRUCTURE CONSISTING OF PEDESTRIAN RAMPS & SHARED PATH

Table with project details: FEDERAL AID PROJECT NO., STP 2021 (277) TAPS, DIST, COUNTY, SHEET NO.

DESIGN SPEED = N/A, A. D. T. (2021) = 620, A. D. T. (2041) = 950

FINAL PLANS


LETTING DATE: DATE CONTRACTOR BEGAN WORK: DATE WORK WAS COMPLETED & ACCEPTED: FINAL CONTRACT COST: CONTRACTOR: CONTRACTOR ADDRESS: LIST OF APPROVED FIELD CHANGES:

PLANS PREPARED BY: GLOBAL CIVIL SOLUTIONS, LLC

SUBMITTED FOR LETTING: 1/25/2022, PROJECT MANAGER GLOBAL CIVIL SOLUTIONS, LLC


THE CONTRACTOR SHALL MAKE HIS OWN INVESTIGATIONS AND ARRANGEMENTS FOR DELIVERY OF MATERIALS.

REQUIRED SIGNS SHALL BE IN ACCORDANCE WITH THE CURRENT BARRICADE AND CONSTRUCTION OR BC SHEETS AND THE "TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES".




BEGIN PROJECT CSJ: 0919-03-064 US 80 @ CIDER LN CURB STA 10+10

END PROJECT CSJ: 0919-03-064 @ CIDER LN CURB STA 29+15 CAL YOUNG RD



EXCEPTIONS: NONE EQUATIONS: NONE RAILROAD CROSSINGS: NONE

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL-AID CONSTRUCTION CONTRACTS (FORM FHWA 1273, MAY 2012)



THE CONSTRUCTION WORK WAS PERFORMED IN SUBSTANTIAL COMPLIANCE WITH THE CONTRACT.

P. E. DATE

CONFERENCE DATE 2-1-2022, CITY MANAGER, HALLSVILLE

TDLR TABS# 2022011163, TDLR INSPECTION REQUIRED

RECOMMENDED FOR LETTING: 2/4/2022

DocuSigned by: Deanne Simmons, P.E., DISTRICT DIRECTOR OF TRANSPORTATION PLANNING AND DEVELOPMENT

APPROVED FOR LETTING: 2/4/2022

DocuSigned by: District Engineer

DATE: 1/25/2022 10:47:37 AM FILE: P:\Jobs\2021003-Pedestrian TxDOT AT\ignto\CADD\ GENERAL\001-ATL-DIST-TITLE-SHEET.dgn

COUNTY: HARRISON PROJ. NO.: STP 2021(277) TAPS HWY. NO.: LETTING DATE: DATE ACCEPTED:

SHEET

DESCRIPTION

1
2
3
4, 4A-4B
5, 5A
6

I GENERAL
TITLE SHEET
INDEX OF SHEETS
TYPICAL SECTIONS
GENERAL NOTES
ESTIMATE & QUANTITIES
QUANTITY SUMMARY

II TRAFFIC CONTROL PLAN

7

SEQUENCE OF OPERATION

III TRAFFIC CONTROL PLAN STANDARDS

8-19
20-21
22-23

#BC (1)-21 THRU BC (12)-21
#TCP (1-1)-18 - TCP (1-2)-18
#TCP (2-1)-18 - TCP (2-2)-18

IV ROADWAY

24
25-29
30-32
33-34

SURVEY CONTROL INDEX SHEET
SIDEWALK PLAN
SIDEWALK PROFILE
MISCELLANEOUS DETAILS

V ROADWAY STANDARDS

35
36-39
40
41
42-44

#CCCG-21
#PED-18
#PM(4)-20
#SMD (GEN)-08
#SMD (SLIP-1)-08 THRU SMD (SLIP-3)-08

VI DRAINAGE

45
46
47
48
49-51
52
53-54

HYDROLOGIC AND INLET CALCULATIONS
STORM SEWER AND HYDRAULIC CALCULATIONS
EXISTING DRAINAGE AREA MAP
PROPOSED DRAINAGE AREA MAP
PROPOSED STORM DRAIN
STORM DRAIN PROFILE
DITCH CROSS SECTIONS

VII DRAINAGE STANDARDS

55
56
57-58
59
60-61
62

#PB
#PBGC
#PCO
#PSET-SP
#PSL
#SETP-PD

SHEET

DESCRIPTION

63
64
65

VIII ENVIRONMENTAL ISSUES
ENVIRONMENTAL PERMITS, ISSUES, AND COMMITMENTS (EPIC)
SWP3 SITE MAP
TXDOT STORM WATER POLLUTION PREVENTION PLAN (SWP3)

IX ENVIRONMENTAL STANDARDS

66
67-69


#EC(1)-16
#EC(9)-16





THE STANDARD SHEETS (#) SPECIFICALLY IDENTIFIED
HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE
SUPERVISION AS BEING APPLICABLE TO THIS PROJECT

MF. Muwaquet, P. E. 1/25/2022
DATE

NO.	DATE	REVISION	BY




 GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801

 Texas Department of Transportation
© 2022 TXDOT

INDEX OF SHEETS


DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE	DISTRICT	COUNTY
CHECK MF	TEXAS	ATL	HARRISON
CHECK FS	CONTROL	SECTION	JOB
	0919	03	064
			SHEET NO. 2

P:\Jobs\2021003-Pedestrian\TXDOT\1\General\CADD\1 GENERAL\002_ATL_DIST_INDEX_SHEET.dgn
1/25/2022 11:02:09 AM




PROPOSED TYPICAL SECTION
WITH SIDEWALK ADJACENT TO CURB
FROM BEGIN PROJECT TO STA 14+85.00

NOT TO SCALE



PROPOSED TYPICAL SECTION
WITH SIDEWALK ADJACENT TO CURB
FROM STA 16+35.00 TO STA 25+44.30

NOT TO SCALE



PROPOSED TYPICAL SECTION
WITH SIDEWALK ADJACENT TO CURB
FROM STA 25+44.30 TO END PROJECT

NOT TO SCALE

NOTES:

1. FOR SWALE INFORMATION, PLEASE SEE "DITCH CROSS SECTIONS" SHEET
2. SEE MISCELLANEOUS DETAILS SHEET FOR DOWEL AND EXPANSION JOINT DETAILS
3. ADDITIONAL WORK TO CONNECT PROP SIDEWALK TO EXISTING CURB SHALL BE SUBSIDIARY TO THE VARIOUS SIDEWALK ITEMS.

NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801



TYPICAL SECTIONS

DESIGN	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MI	6	STP 2021 (277) TAPS	CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
PS	TEXAS	ATL	HARRISON
CHECK	CONTROL	SECTION	JOB
MFM	0919	03	064
CHECK	FS		

GENERAL NOTES:

General Requirements and Covenants:

Clean the existing curb and gutter, curb outlets and curb inlets in accordance with section 427.4.2.1.2 "Blast Cleaning" as part of the final clean up. Surfaces will exhibit a uniform appearance free from stains, marks, and all foreign matter. This work will be subsidiary to the pertinent bid items

Contractor questions on this project are to be addressed to the following individuals:

Wendy Starkes, P.E. - Area Engineer
Wendy.Starkes@Txdot.gov
Jacob Vise, P.E. - Assistant Area Engineer
Jacob.Vise@Txdot.gov

Contractor questions will be accepted through email, phone, and in person by the above individuals.

All contractor questions will be reviewed by the Engineer. Once a response is developed, it will be posted to TxDOT's Public FTP at the following Address:

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting%20Responses/>

All questions submitted that generate a response will be posted through this site. The site is organized by District, Project Type (Construction or Maintenance), Letting Date, CCSJ/Project Name.

All roadside signs, mailbox supports, delineators, and object markers located within the project limits shall be plumbed as part of the final cleanup. This work will not be paid for separately but will be considered subsidiary to the various bid items.

Repair all pavement damaged by the Contractor's forces during construction. Such repair is to be considered incidental to the various bid items in the project and must be approved by engineer.

ITEM 5 – Control of the Work:

Place construction points, stakes, and marks at intervals of no more than 100 ft., or as directed. Place stakes and marks so as not to interfere with normal maintenance operations.

It is the Contractor's responsibility to verify the accuracy of any department provided control points prior to use.

Contact all utility companies for the exact location of underground utilities before boring, trenching or any other work that might interfere with or damage existing utilities.

Repair any damage caused to utilities by Contractor operations at own expense and restore service in a timely manner.

Work on any project will not be accepted until all components have been shown to be fully operational.

ITEM 7 – Legal Relations and Responsibilities:

The total area disturbed for this project is 0.65 acres. The disturbed area in this project, all project locations in the Contract, and the Contractor project specific locations (PSLs) within 1 mile of the project limits will be used to establish the authorization requirements for storm water discharges. Common plans of development which disturb less than 1 acre are not subject to requirements under TCEQ's Construction General Permit (CGP); however, if (PSLs) established during construction raise the disturbed area to 1 or more acres then all activities would be subject to the CGP. If required, the Department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans. The Contractor is to obtain required authorization from the TCEQ for Contractor PSLs for construction support activities on or off the ROW.

This project is considered a maintenance activity and is exempt from the Construction General Permit (CGP) coverage.

The Contractor will not remove active nests from bridges and other structures during nesting season of the birds associated with the nests.

Transmit copies of correspondence between Contractor and resource agencies as listed in Article 7.7 "Preservation of Cultural and Natural Resources and the Environment".

No significant traffic generator events.

ITEM 8 – Prosecution and Progress:

Working days will be charged in accordance with Section 8.3.1.4, "Standard Workweek"

ITEM 132 – Embankment:

Furnish material with an organic content less than 1.0%. The Engineer will test using UV-VIS equipment and procedure determined by TxDOT. Allow two weeks for testing.

ITEM 160 – Topsoil:

Finish slopes with a tracked vehicle running vertically up and down the slope.

ITEM 162 – Sodding for Erosion Control:

Finish slopes with a tracked vehicle running vertically up and down the slope.

Mow tall growing vegetation as directed, to provide optimum growing conditions for temporary or permanent seeded areas in accordance with Item 730 “Roadside Mowing” except for measurement and payment. This work will be subsidiary to pertinent bid items.

Repair mulch sod, damaged by causes other than the Contractor’s operations, as directed using mulch sod, seeding, and fertilizer. This work will be measured and paid for in accordance with the applicable bid items of the contract

ITEM 432 - Riprap:

Provide ½” expansion joint material with an area equal to the area of contact between the two concrete surfaces. The joint material will be visually inspected for approval.

ITEM 464 – Reinforced Concrete Pipe:

Backfill driveway culverts to obtain a minimum cover of 6 inches. Place backfill in accordance with section 132.3.4.1 “Ordinary Compaction” using approved equipment.

The Engineer will determine flow lines of pipes under private driveways. When unstable foundation materials are encountered, the Engineer will have the option of directing the placement of a foundation seal of Class "A" concrete instead of an undercut.

ITEM 465 – Junction Boxes, Manholes, and Inlets:

When unstable foundation materials are encountered, the Engineer will have the option of directing the placement of a foundation seal of Class "A" concrete instead of an undercut.

ITEM 467 – Safety End Treatments:

When unstable foundation materials are encountered, the Engineer will have the option of directing the placement of a foundation seal of Class "A" concrete instead of an undercut.

Provide precast safety end treatments with a toewall measuring at least 12 inches. Construct toewalls for cast-in-place safety end treatments as shown in the plans.

Remove trees, bushes, and underbrush as directed. This work will be subsidiary to the pertinent bid items.

ITEM 502 – Barricades, Signs, and Traffic Handling:

The Contractor Force Account “Safety Contingency” that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor’s Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

The Contractor's responsible person (CRP) will be responsible for ensuring that the signs and traffic control devices are in place and functioning properly.

Restrict the movement of equipment across traffic lanes to an absolute minimum.

Use strobe lights or rotating beacons on all motorized equipment, operating on or adjacent to the road surface.

Place and maintain U.S. mailboxes within project limits in such a manner as to ensure continuous mail service. See BC Standard for more information.

ITEM 506 – Temporary Erosion, Sedimentation, and Environmental Controls:

Sprinkle water for dust control. Meet the requirements of Item 204, “Sprinkling” except for measurement and payment. Sprinkling will be considered subsidiary to this Item.

Place erosion or pollution control measures deemed necessary by the Engineer. Work performed for which there is no applicable pay items in the contract will be reimbursed in accordance with Article 9.7, “Payment for Extra Work and Force Account Method”.

ITEM 529 – Concrete Curb, Gutter, and Combined Curb and Gutter:

Use an approved curb template that will match the existing curb.

At the Contractor’s option, place the Type II curb and gutter monolithically.

Before placing machine laid curb, paint the surface with a coating of cement paste, having the consistency of a thick paint, or with another approved adhesive.

ITEM 530 – Intersections, Driveways, and Turnouts:

Unless otherwise shown in the plans, furnish W2.9 x W2.9 welded wire reinforcing in all concrete driveways.

Meet the requirements of Item 110, "Excavation" and Item 132, "Embankment, Type "C", except for measurement and payment, for construction of driveways and turnouts.

ITEM 644 – Sign Identification Decals:

Type A signs will be made of flat aluminum.

Existing sign assemblies will be removed after the proposed sign is installed. Contractor will leave existing sign in place while proposed sign goes up. The existing sign will be removed immediately after the proposed sign is installed.

For this project, the standard triangular slip base two bolt casting will be used. This casting must be furnished from an approved manufacturer.

Erect the proposed signs an appropriate distance from adjacent signs in accordance with the Texas MUTCD, as directed and as shown on the plans.

Verify the elevation difference between the edge of the travel lane and bottom of the sign.

Do not remove existing sign assemblies until signs are ready to be installed on new mounts.

ITEM 677 – Eliminating Existing Pavement Markings and Markers:

Furnish a high-pressure water blasting system for removing paint, thermoplastic, epoxy, and preformed tape materials from the following surfaces without causing any grooves or trenching of that surface, including asphalt, concrete, friction coarse asphalt, grooved asphalt, and grooved concrete.

Use a high-pressure water blasting system that consist of a vacuum recovery system that must provide for a nearly dry surface eliminating the possibility of uncontained run-off blasting water and debris.

All components required for the complete operation of the water blasting system – Ultra High Pressure (UHP) pump, vacuum system, clean water supply, vacuum recovery storage, blasting components will be mounted and transported on a single, fully self-contained and supporting truck chassis, thereby eliminating the need for any additional water, vacuum, or other transport vehicles.

ITEM 678 – Pavement Surface Preparation for Markings:

Furnish a high-pressure water blasting system for removing paint, thermoplastic, epoxy, and preformed tape materials from the following surfaces without causing any grooves or trenching

of that surface, including asphalt, concrete, friction coarse asphalt, grooved asphalt, and grooved concrete.

Use a high-pressure water blasting system that consist of a vacuum recovery system that must provide for a nearly dry surface eliminating the possibility of uncontained run-off blasting water and debris.

All components required for the complete operation of the water blasting system – Ultra High Pressure (UHP) pump, vacuum system, clean water supply, vacuum recovery storage, blasting components will be mounted and transported on a single, fully self-contained and supporting truck chassis, thereby eliminating the need for any additional water, vacuum, or other transport vehicles.

ITEM 6001 – Portable Changeable Message Sign:

Portable Changeable Message signs will be used on this contract. The Portable Changeable Message Signs will be used in advance of signal work where changing conditions may warrant the use of message boards. They may also be required at other locations as directed by the Engineer. The Engineer will provide the Contractor with the location and the messages to be displayed for each specific event. The Engineer or his representative will inspect each location once the Contractor has placed the message boards to verify that the placement and message is correct. The Contractor will change the message board location and modify the message being displayed as directed before leaving the location to the satisfaction of the Engineer or his representative. The Portable Changeable Message Signs will be paid for by the day after installed and fully operational. All locations that the Contractor will be called upon to use the Portable Changeable Message Signs will be for a minimum of 10 days. The Engineer will notify the Contractor when the Portable Changeable Message Signs are needed, and the Contractor will have the Portable Changeable Message Signs on location and fully operational in 5 working days. In cases of emergency the Contractor will have the Portable Changeable Message Signs on location and fully operational in 3 working days. Refer to traffic control plan sheets for typical temporary portable changeable message sign layout.

ITEM 6185–Truck Mounted Attenuator (TMA) and Trailer Attenuator (TA):

The shadow vehicle with truck mounted attenuator (TMA) will not be optional but will be required as shown on the appropriate traffic control plan sheets.

A total of one (1) shadow vehicle with TMA will be required for work. The contractor will be responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMA's needed for the project.

A total of two (2) shadow vehicles with TMA will be required for Pavement Marking Operations.



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0919-03-064

DISTRICT Atlanta
HIGHWAY CIDER LN

COUNTY Harrison

CONTROL SECTION JOB				0919-03-064		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00133230			
COUNTY				Harrison			
HIGHWAY				CIDER LN			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	104-6017	REMOVING CONC (DRIVEWAYS)	SY	554.000		554.000	
	104-6029	REMOVING CONC (CURB OR CURB & GUTTER)	LF	101.000		101.000	
	104-6044	REMOVING CONC (FLUME)	SY	18.000		18.000	
	110-6001	EXCAVATION (ROADWAY)	CY	152.000		152.000	
	132-6004	EMBANKMENT (FINAL)(DENS CONT)(TY B)	CY	29.000		29.000	
	160-6003	FURNISHING AND PLACING TOPSOIL (4")	SY	629.000		629.000	
	162-6002	BLOCK SODDING	SY	629.000		629.000	
	168-6001	VEGETATIVE WATERING	MG	53.400		53.400	
	432-6002	RIPRAP (CONC)(5 IN)	CY	70.500		70.500	
	464-6001	RC PIPE (CL III)(12 IN)	LF	52.000		52.000	
	464-6005	RC PIPE (CL III)(24 IN)	LF	70.000		70.000	
	465-6017	INLET (COMPL)(PCO)(4FT)(NONE)	EA	2.000		2.000	
	465-6019	INLET (COMPL)(PCO)(4FT)(RIGHT)	EA	1.000		1.000	
	465-6078	INLET (COMPL)(PSL)(RG)(3FTX3FT)	EA	1.000		1.000	
	467-6326	SET (TY II) (12 IN) (RCP) (6: 1) (P)	EA	2.000		2.000	
	479-6005	ADJUSTING MANHOLES (WATER VALVE BOX)	EA	2.000		2.000	
	496-6004	REMOV STR (SET)	EA	2.000		2.000	
	496-6007	REMOV STR (PIPE)	LF	62.000		62.000	
	500-6001	MOBILIZATION	LS	1.000		1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	5.000		5.000	
	506-6041	BIODEG EROSN CONT LOGS (INSTL) (12")	LF	125.000		125.000	
	506-6043	BIODEG EROSN CONT LOGS (REMOVE)	LF	125.000		125.000	
	529-6008	CONC CURB & GUTTER (TY II)	LF	1,134.000		1,134.000	
	530-6001	INTERSECTIONS (CONC)	SY	183.000		183.000	
	530-6004	DRIVEWAYS (CONC)	SY	540.000		540.000	
	531-6002	CONC SIDEWALKS (5")	SY	1,556.000		1,556.000	
	531-6004	CURB RAMPS (TY 1)	EA	1.000		1.000	
	531-6005	CURB RAMPS (TY 2)	EA	3.000		3.000	
	531-6008	CURB RAMPS (TY 5)	EA	1.000		1.000	
	531-6010	CURB RAMPS (TY 7)	EA	1.000		1.000	
	531-6013	CURB RAMPS (TY 10)	EA	2.000		2.000	
	531-6033	CONC SIDEWALKS (SPECIAL) (TYPE B)	SY	327.000		327.000	
	644-6068	RELOCATE SM RD SN SUP&AM TY 10BWG	EA	2.000		2.000	
	666-6048	REFL PAV MRK TY I (W)24"(SLD)(100MIL)	LF	122.000		122.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF	114.000		114.000	
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF	25.000		25.000	
	678-6008	PAV SURF PREP FOR MRK (24")	LF	122.000		122.000	

DISTRICT	COUNTY	CCSJ	SHEET
Atlanta	Harrison	0919-03-064	5



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0919-03-064

DISTRICT Atlanta
HIGHWAY CIDER LN

COUNTY Harrison

CONTROL SECTION JOB				0919-03-064		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00133230			
COUNTY				Harrison			
HIGHWAY				CIDER LN			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	3076-6066	TACK COAT	GAL	13.300		13.300	
	3076-6081	D-GR HMA TY-D PG70-22 (EXEMPT)	TON	60.000		60.000	
	6001-6002	PORTABLE CHANGEABLE MESSAGE SIGN	EA	2.000		2.000	
	6027-6009	GROUND BOX (ADJUST)	EA	2.000		2.000	
	6185-6002	TMA (STATIONARY)	DAY	40.000		40.000	
	18	EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000		1.000	
		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000		1.000	

SUMMARY OF ROADWAY ITEMS																								
SHT NO	104			160	162	168	432	479	529	530		531					644	666	677		678	6027		
	6017	6029	6044	6003	6002	6001	6002	6005	6008	6001	6004	6002	6004	6005	6008	6010	6013	6033	6068	6048	6001	6007	6008	6009
	REMOVING CONC (DRIVEWAYS)	REMOVING CONC (CURB OR CURB & GUTTER)	REMOVING CONC (FLUME)	FURNISHING AND PLACING TOP SOIL (4")	BLOCK SODDING	VEGETATIVE WATERING (420,000 gallons/acre)	RIPRAP (CONC) (5 IN)	ADJUSTING MANHOLES (WATER VALVE BOX)	CONC CURB & GUTTER (TY II)	INTERSECTIONS (CONC)	DRIVEWAYS (CONC)	CONC SIDEWALK (5")	CURB RAMPS (TY 1)	CURB RAMPS (TY 2)	CURB RAMPS (TY 5)	CURB RAMPS (TY 7)	CURB RAMPS (TY 10)	CONC SIDEWALKS (SPECIAL) (TYPE B)	RELOCATE SM RD SN SUP&AM TY 10BWG	REFL PAV MARK TY 1 (W)24"(SLD) (100MIL)	ELIM EXT PAV MRK & MRKS (4")	ELIM EXT PAV MRK & MRKS (24")	PAV SURF PREP FOR MRK (24")	GROUND BOX (ADJUST)
SY	LF	SY	SY	SY	MG	CY	EA	LF	SY	SY	SY	EA			EA	EA	SY	EA	LF	LF	LF	LF	EA	
SHEET 1 of 5	115			128	128	11.2	0.5		254		198	308	1	1		1				24	30		24	
SHEET 2 of 5	298			154	154	13.4	13.4	1	296	183	168	394				2								
SHEET 3 of 5	141			137	137	11.9	43.6	1	415		174	555												1
SHEET 4 of 5		101	18	155	155	12.1	13.0		169			215					327							
SHEET 5 of 5				55	55	4.8						84		2	1			2	98	84	25	98	1	
PROJECT TOTAL	554	101	18	629	629	53.4	70.5	2	1134	183	540	1556	1	3	1	1	2	327	2	122	114	25	122	2

LOCATION	506	506	6001	6185
	6041	6043	6002	6002
	BIODEG EROSN CONT LOGS (INSTL) (12")	BIODEG EROSN CONT LOGS (REMOVE)	PORTABLE CHANGEABLE MESSAGE SIGN	TMA (STATIONARY)
	LF	LF	EA	DAY
CIDER LN	125	125	2	40
PROJECT TOTAL	125	125	2	40

SPEC ITEM	3076	3076
	6066	6081
	TACK COAT (0.1 GAL/SY)	D-GR HMA TY-D PG70-22 (EXEMPT)
UNITS	GAL	TON
TOTALS	13.3	60

SUMMARY OF DRAINAGE ITEMS										
LOCATION	110	132	464	464	465	465	465	467	496	496
	6001	6004	6001	6005	6017	6019	6078	6326	6004	6007
	EXCAVATION (ROADWAY)	EMBANKMENT (FINAL)(DENS CONT)(TY B)	RC PIPE (CL III)(12 IN)	RC PIPE (CL III)(24 IN)	INLET (COMPL)(PCO) (4FT)(NONE)	INLET (COMPL)(PCO) (4FT)(RIGHT)	INLET (COMPL)(PSL) (RG)(3FTX3FT)	SET (TY II) (12 IN) (RCP) (6: 1) (P)	REMOV STR (SET)	REMOV STR (PIPE)
	CY	CY	LF	LF	EA	EA	EA	EA	EA	LF
BEGIN PROJ TO STA 19+50.00 (1 OF 3)				54	1	1	1			
STA 19+50.00 TO STA 24+30.00 (2 OF 3)			52	16	1			2	2	62
STA 24+30.00 TO END PROF (3 OF 3)										
TOTAL FOR DITCHES ONLY	152	29								
PROJECT TOTALS	152	29	52	70	2	1	1	2	2	62

DITCH EARTHWORK SUMMARY (FOR CONTRACTOR INFORMATION ONLY)							
STATION	STATION CUT, CY	STATION FILL, CY	ACCUM. CUT, CY	ACCUM. FILL, CY	MASS ORDINATE	ADDITIONAL CUT, CY	REMARKS FILL, CY
1610.00	0.00	0.00	0.00	0.00		0.00	0.00
1644.55	1.00	2.00	1.00	2.00	-1.00	0.00	0.00
1703.00	2.00	2.00	3.00	4.00	-1.00	0.00	0.00
1750.00	2.00	2.00	5.00	6.00	-1.00	0.00	0.00
1800.00	2.00	2.00	7.00	8.00	-1.00	0.00	0.00
1863.26	1.00	3.00	8.00	11.00	-3.00	0.00	0.00
1923.16	7.00	1.00	15.00	12.00	3.00	0.00	0.00
2013.29	22.00	1.00	37.00	13.00	24.00	0.00	0.00
2098.52	26.00	1.00	63.00	14.00	49.00	0.00	0.00
2115.90	7.00	0.00	70.00	14.00	56.00	0.00	0.00
2200.00	30.00	0.00	100.00	14.00	86.00	0.00	0.00
2250.00	12.00	0.00	112.00	14.00	98.00	0.00	0.00
2318.86	8.00	3.00	120.00	17.00	103.00	0.00	0.00
2445.61	14.00	6.00	134.00	23.00	111.00	0.00	0.00
2516.35	11.00	0.00	145.00	23.00	122.00	0.00	0.00
2544.51	2.00	0.00	147.00	23.00	124.00	0.00	0.00
2709.83	4.00	5.00	151.00	28.00	123.00	0.00	0.00
2735.85	1.00	1.00	152.00	29.00	123.00	0.00	0.00
	TOTAL		152.00	29.00	123.00		

NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
 1151 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801




QUANTITY SUMMARY

SHEET 1 OF 1

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO. STP 2021 (277) TAPS	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MF	CONTROL 0919	SECTION 03	JOB 064
CHECK FS			SHEET NO. 6

P:\Jobs\2021003-Pedestrian\DOT\ATL\General\006_ATL_DIST_QUANTITY_SUMMARY.dgn
 12/17/22 PM 2/3/2022

P:\Jobs\2021003-Pedestrian TxDOT Atlanta\CADD\11 TRAFFIC CONTROL PLAN\007*SEQUENCE OF OPERATION.dgn



VICINITY MAP

GENERAL

- A. INSTALL ALL SIGNS, BARRICADES AND TRAFFIC CONTROL DEVICES AS SHOWN AND IN ACCORDANCE WITH THE STANDARD BC SHEETS AND AS DIRECTED.
- B. ADDITIONAL SIGNS, BARRICADES OR TRAFFIC CONTROL DEVICES OTHER THAN THOSE SPECIFIED MAY BE REQUIRED FOR THE SAFE MOVEMENT OF TRAFFIC THROUGH THE PROJECT. PAYMENT FOR ALL SUCH SIGNS, BARRICADES OR TRAFFIC CONTROL DEVICES WILL BE CONSIDERED AS SUBSIDIARY TO THE ITEM "BARRICADES, SIGNS AND TRAFFIC HANDLING".
- C. WORK SITES WILL BE CAREFULLY MONITORED TO ENSURE THAT TRAFFIC CONTROL MEASURES ARE OPERATING EFFECTIVELY AND THAT ALL DEVICES USED ARE CLEARLY VISIBLE, CLEAN AND IN GOOD REPAIR.
- D. THE CONTRACTOR WILL PROVIDE SAFE ACCESS TO AND FROM ALL PRIVATE PROPERTY AT ALL TIMES AND IN ALL WEATHER CONDITIONS.
- E. THE CONTRACTOR WILL BE REQUIRED TO SUBMIT A DETAILED SCHEDULE OF WORK TO THE PROJECT ENGINEER PRIOR TO THE BEGINNING OF CONSTRUCTION WHICH GENERALLY CONFORMS TO THE SEQUENCE SHOWN ON THE TCP SEQUENCE OF OPERATION.
- F. COMPLETE ALL WORK ON PROJECT AS SHOWN ON THE VARIOUS PLAN SHEETS AND IN COMPLIANCE WITH THE GENERAL NOTES OF THIS CONTRACT.
- G. ANY REQUEST TO ALTER THE SEQUENCE OF OPERATION OR TRAFFIC CONTROL PLAN WILL BE SUBMITTED TO THE ENGINEER FOR HIS WRITTEN APPROVAL.

SEQUENCE OF OPERATION

- 1) SET PROJECT BARRICADES.
- 2) INSTALL REQUIRED TEMPORARY EROSION CONTROL DEVICES.
- 3) CONSTRUCT PROPOSED SIDEWALK, ADA RAMPS, DRIVEWAYS, SIGNS, ETC.
- 4) PLACE PERMANENT PAVEMENT MARKINGS.
- 5) COMPLETE ALL OTHER WORK AS SHOWN ON THE PLANS.
- 6) CLEAN UP PROJECT AND REMOVE TEMPORARY EROSION CONTROL DEVICES AND PROJECT BARRICADES.



Texas Department of Transportation
2022. all rights reserved

SEQUENCE OF OPERATION

FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.			SHEET NO.
6				7
STATE	DIST.	COUNTY		
TEXAS	ATLANTA	HARRISON		
CONT.	SECT.	JOB	HIGHWAY NO.	
0919	03	064	CIDER LN	

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
 FILE:

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY NOTES:



1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

1. Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).


THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12

 Texas Department of Transportation		 Traffic Safety Division Standard	
BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS			
BC (1) - 21			
FILE:	bc-21.dgn	DN:	TxDOT
© TxDOT	November 2002	CK:	TxDOT
		DW:	TxDOT
		CK:	TxDOT
		CONT	SECT
		0919	03
		JOB	HIGHWAY
		064	CIDER LN
		DIST	COUNTY
		ATL	HARRISON
		SHEET NO.	8


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect resulting from its use.

TYPICAL LOCATION OF CROSSROAD SIGNS



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
 - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
 - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
 - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
 - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
 - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

T-INTERSECTION



CSJ LIMITS AT T-INTERSECTION

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING^{1,5,6}

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Δ Spacing "x" Feet (Apprx.)
CW20 ⁴	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25			50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"	55	500 ²
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" x 48"	48" x 48"	60	600 ²
			65	700 ²
			70	800 ²
			75	900 ²
			80	1000 ²
			*	* ³


* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS



SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS



NOTES

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
 - CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
 - Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
 - Contractor will install a regulatory speed limit sign at the end of the work zone.

LEGEND	
—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
x	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC (2) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	ATL	HARRISON	9	

DATE: FILE:

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
 - Law enforcement.
 - Flagger stationed next to sign.
 - Portable changeable message sign (PCMS).
 - Low-power (drone) radar transmitter.
 - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act." No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

SHEET 3 OF 12




BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC (3) - 21

FILE:	bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		0919	03	064	CIDER LN
9-07	8-14	DIST	COUNTY	SHEET NO.	
7-13	5-21	ATL	HARRISON	10	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - Long-term stationary - work that occupies a location more than 3 days.
 - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - Short, duration - work that occupies a location up to 1 hour.
 - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

STOP/SLOW PADDLES

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflectorized when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.





BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC (4) - 21


FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0919	03	064	CIDER LN				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	ATL	HARRISON	11					

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.






SKID MOUNTED WOOD SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

GENERAL NOTES

- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
- No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
- When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.

- * See BC(4) for definition of "Work Duration."
- ** Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
- See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	ATL	HARRISON	12	

DATE: FILE:

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Canal	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy	HOV	Tuesday	TUES
Vehicle	HWY	Time Minutes	TIME MIN
Highway	HR, HRS	Upper Level	UPR LEVEL
Hour(s)	HR, HRS	Vehicles (s)	VEH, VEHS
Information	INFO	Warning	WARN
It Is	ITS	Wednesday	WED
Junction	JCT	Weight Limit	WT LIMIT
Left	LFT	West	W
Left Lane	LFT LN	Westbound	(route) W
Lane Closed	LN CLOSED	Wet Pavement	WET PVMT
Lower Level	LWR LEVEL	Will Not	WONT
Maintenance	MAINT		

Roadway designation # IH-number, US-number, SH-number, FM-number

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE
ROAD CLOSED AT SH XXX
ROAD CLSD AT FM XXXX
RIGHT X LANES CLOSED
CENTER LANE CLOSED
NIGHT LANE CLOSURES
VARIOUS LANES CLOSED
EXIT CLOSED
MALL DRIVEWAY CLOSED
XXXXXXXX BLVD CLOSED

Other Condition List

FRONTAGE ROAD CLOSED
SHOULDER CLOSED XXX FT
RIGHT LN CLOSED XXX FT
RIGHT X LANES OPEN
DAYTIME LANE CLOSURES
I-XX SOUTH EXIT CLOSED
EXIT XXX CLOSED X MILE
RIGHT LN TO BE CLOSED
X LANES CLOSED TUE - FRI

ROADWORK XXX FT
FLAGGER XXXX FT
RIGHT LN NARROWS XXXX FT
MERGING TRAFFIC XXXX FT
LOOSE GRAVEL XXXX FT
DETOUR X MILE
ROADWORK PAST SH XXXX
BUMP XXXX FT
TRAFFIC SIGNAL XXXX FT

ROAD REPAIRS XXXX FT
LANE NARROWS XXXX FT
TWO-WAY TRAFFIC XX MILE
CONST TRAFFIC XXX FT
UNEVEN LANES XXXX FT
ROUGH ROAD XXXX FT
ROADWORK NEXT FRI-SUN
US XXX EXIT X MILES
LANES SHIFT *

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List

MERGE RIGHT
DETOUR NEXT X EXITS
USE EXIT XXX
STAY ON US XXX SOUTH
TRUCKS USE US XXX N
WATCH FOR TRUCKS
EXPECT DELAYS
REDUCE SPEED XXX FT
USE OTHER ROUTES
STAY IN LANE *

Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXX TO XXXXXXX
US XXX TO FM XXXX

Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

** Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

** See Application Guidelines Note 6.

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

SHEET 6 OF 12


<h3>BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)</h3>			
<h2>BC (6) - 21</h2>			
FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT November 2002	CONT	SECT	JOB
REVISIONS		0919 03	064
9-07 8-14	DIST	COUNTY	SHEET NO.
7-13 5-21	ATL	HARRISON	13

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




CONCRETE TRAFFIC BARRIER (CTB)

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES
 LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

LOW PROFILE CONCRETE BARRIER (LPCB)




DELINEATION OF END TREATMENTS

END TREATMENTS FOR CTB'S USED IN WORK ZONES
 End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS

WARNING LIGHTS


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B_{FL} or C_{FL} Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.



Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS

- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.




Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

ATTENTION
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

FLASHING ARROW BOARDS

TRUCK-MOUNTED ATTENUATORS

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.

BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR

BC (7) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
©TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0919	03	064	CIDER LN				
9-07	8-14	DIST	COUNTY		SHEET NO.				
7-13	5-21	ATL	HARRISON		14				

DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign
(Maximum Sign Dimension)
Chevron CW1-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer



12" x 24" Vertical Panel
mount with diagonals sloping down towards travel way

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12





BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (8) - 21


FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0919	03	064	CIDER LN				
4-03	8-14	DIST	COUNTY		SHEET NO.				
9-07	5-21	ATL	HARRISON		15				
7-13									

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




VERTICAL PANELS (VPs)

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS



LONGITUDINAL CHANNELIZING DEVICES (LCD)

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

GENERAL NOTES

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths * X			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS ² / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

*X Taper lengths have been rounded off.
L=Length of Taper (FT.) W=Width of Offset (FT.)
S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	ATL	HARRISON	16	


DATE: FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPE 3 BARRICADES

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL



Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.


TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION



PERSPECTIVE VIEW




PLAN VIEW

Increase number of plastic drums on the side of approaching traffic if the crown width makes it necessary. (minimum of 2 and maximum of 4 drums)

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.
42" 2-piece cones shall have a minimum weight of 30 lbs. including base.



TRAFFIC CONTROL FOR MATERIAL STOCKPILES

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (10) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	ATL	HARRISON	17	

DATE: FILE:

WORK ZONE PAVEMENT MARKINGS

GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



STAPLES OR NAILS SHALL NOT BE USED TO SECURE
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER
TABS TO THE PAVEMENT SURFACE

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:
 YELLOW - (two amber reflective surfaces with yellow body).
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

SHEET 11 OF 12




BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS


BC(11)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
2-98 9-07 5-21	DIST	COUNTY	SHEET NO.	
1-02 7-13	ATL	HARRISON	18	
11-02 8-14				

PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TXDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectORIZED pavement markings.






RAISED PAVEMENT MARKERS

TWO-WAY LEFT TURN LANE


STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS



SOLID LINES




BROKEN LINES



REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC (12) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
1-97 9-07 5-21				
2-98 7-13				
11-02 8-14				
	DIST	COUNTY	SHEET NO.	
	ATL	HARRISON	19	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:




TCP (1-1a)

WORK SPACE NEAR SHOULDER
Conventional Roads



TCP (1-1b)

WORK SPACE ON SHOULDER
Conventional Roads



TCP (1-1c)

WORK VEHICLES ON SHOULDER
Conventional Roads

LEGEND

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
** Taper lengths have been rounded off.
L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES
- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - Inactive work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
 - See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
 - CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.



TRAFFIC CONTROL PLAN
CONVENTIONAL ROAD
SHOULDER WORK



TCP (1-1) - 18

FILE: tcp1-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CON:	SECT:	JOB:	HIGHWAY:
REVISIONS	0919	03	064	CIDER LN
2-94 4-98	DIST:	COUNTY:	SHEET NO.:	
8-95 2-12	ATL	HARRISON	20	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

Warning Sign Sequence in Opposite Direction Same as Below



LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed X	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES**
- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
 - Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or R1-2 "YIELD" sign is less than 150 feet.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
- TCP (1-2a)**
- R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
 - R1-2 "YIELD" sign with R1-2aP "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.
- TCP (1-2b)**
- Flaggers should use two-way radios or other methods of communication to control traffic.
 - Length of work space should be based on the ability of flaggers to communicate.
 - If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
 - Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the Engineer.
 - Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

Texas Department of Transportation
Traffic Operations Division Standard


TRAFFIC CONTROL PLAN
ONE-LANE TWO-WAY
TRAFFIC CONTROL

TCP (1-2) - 18

FILE: tcp1-2-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
4-90 4-98	DIST	COUNTY		SHEET NO.
2-94 2-12	ATL	HARRISON		21
1-97 2-18				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:




TCP (2-1a)

WORK SPACE NEAR SHOULDER
Conventional Roads



TCP (2-1b)

WORK SPACE ON SHOULDER
Conventional Roads



TCP (2-1c)

WORK VEHICLES ON SHOULDER
Conventional Roads

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only

** Taper lengths have been rounded off.

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	✓

GENERAL NOTES

- Flags attached to signs where shown, are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated in the plans, or for routine maintenance work, when approved by the Engineer.
- Stockpiled material should be placed a minimum of 30 feet from nearest traveled way.
- Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.
- See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
- Inactive work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
- CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.





TRAFFIC CONTROL PLAN
CONVENTIONAL ROAD
SHOULDER WORK

TCP (2-1) - 18

FILE: tcp2-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CON:	SECT:	JOB:	HIGHWAY:
REVISIONS	0919	03	064	CIDER LN
2-94 4-98	DIST:	COUNTY:	SHEET NO.:	
8-95 2-12	ATL	HARRISON	22	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



LEGEND

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

GENERAL NOTES

- Flags attached to signs where shown, are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4 "ONE LANE ROAD XXX FT" sign, but proper sign spacing shall be maintained.
- Flaggers should use two-way radios or other methods of communication to control traffic.
- Length of work space should be based on the ability of flaggers to communicate.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.

TCP (2-2a)

- The R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work space should be no longer than one half city block. In rural areas, roadways with less than 2000 ADT, work space should be no longer than 400 feet.
- The R1-2aP "YIELD TO ONCOMING TRAFFIC" sign shall be placed on a support at a 7 foot minimum mounting height.

TCP (2-2b)

- Channelizing devices on the center line may be omitted when a pilot car is leading traffic and approved by the Engineer.
- If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain stopping sight distance to the flagger and a queue of stopped vehicles. (See table above).
- Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.


Texas Department of Transportation Traffic Operations Division Standard




TRAFFIC CONTROL PLAN
ONE-LANE TWO-WAY
TRAFFIC CONTROL

TCP (2-2) - 18

FILE: tcp2-2-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS		0919	03	064
8-95	3-03	DIST	COUNTY	SHEET NO.
1-97	2-12	ATL	HARRISON	23
4-98	2-18			

DATE:
FILE:

CONTROL POINT LEGEND	
	DENOTES PRIMARY CONTROL POINT (AS NOTED)



- NOTES:
- ALL COORDINATES SHOWN HEREON ARE BASED ON THE TEXAS COORDINATE SYSTEM, NORTH CENTRAL ZONE (4202), NORTH AMERICAN DATUM OF 1983 (2011 ADJ.; EPOCH 2010.00). BEARINGS ARE BASED ON GRID NORTH
 - HORIZONTAL COORDINATES ARE BASED ON GPS VRS OBSERVATIONS, MEASURED FROM TxDOT CORS STATION TXNO.
 - COORDINATES AND DISTANCES ARE U.S. SURVEY FEET, DISPLAYED IN SURFACE VALUES, AND MAY BE CONVERTED TO NAD83 (GRID) VALUES BY APPLYING THE TxDOT SURFACE ADJUSTMENT FACTOR (SAF) OF 1.00012 USING THE FORMULA: SURFACE / SAF = GRID

POINT	SURFACE COORDINATES			DESCRIPTION
	NORTHING	EASTING	ELEVATION	
504	6891662.91	3173425.28	408.185	5/8" IRS W/ YELLOW CAP STAMPED "CP"
503	6891887.53	3173498.76	399.277	5/8" IRS W/ YELLOW CAP STAMPED "CP"
502	6892346.36	3173219.44	392.466	5/8" IRS W/ YELLOW CAP STAMPED "CP"
501	6892909.19	3173028.53	400.545	5/8" IRS W/ YELLOW CAP STAMPED "CP"
500	6893405.26	3172783.58	406.202	5/8" IRS W/ YELLOW CAP STAMPED "CP"

NO.	DATE	REVISION	BY

CRIADO

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801

 **Texas Department of Transportation**
 ©2022 TxDOT

SURVEY CONTROL INDEX SHEET



DESIGN MII	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE	DISTRICT	COUNTY
CHECK MFM	TEXAS	ATL	HARRISON
CHECK FS	CONTROL	SECTION	JOB
	0919	03	064
			SHEET NO. 24



S. Kevin Wendell
 01/27/2022



SFILES
S04VES

US 80



MATCHLINE STA 11+25


MATCHLINE STA 13+75



NOTES:

- * FOR CONTRACTOR INFORMATION ONLY
- 1. THE EXISTENCE AND LOCATION OF ALL UTILITIES AND DRAINAGE STRUCTURES INDICATED IN THE PLANS ARE TAKEN FROM THE BEST RECORDS AVAILABLE AND ARE NOT GUARANTEED TO BE ACCURATE. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES TO FIELD VERIFY UTILITIES PRIOR TO BEGINNING CONSTRUCTION.

NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
1151 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801



LEGEND

- | | | | |
|----------------------------------|--|------------------------|---|
| PROP SODDING | R RAMP | POWER POLE | DRIVEWAY ID |
| PROP CONC DRWY | L LANDING PAD | TRAFFIC SIGNAL POLE | ELECTRIC PEDESTAL |
| PROP CONC RIPRAP | F FLARE | GUY WIRE | ELECTRIC METER |
| PROP CONC SIDEWALK | SL LONG SLOPE MAY NOT EXCEED 5% OR ADJACENT ROAD SLOPE | FENCE | ELECTRIC JUNCTION BOX |
| EXISTING SIDEWALK/DRWY TO REMAIN | T TRANSITION | WATER VALVE | OVERHEAD ELECTRIC LINE |
| | LS LEVEL SIDEWALK (2% MAX) | TRAFFIC CONTROL BOX | DRIVEWAYS (CONC) |
| | TRAFFIC FLOW | WATER METER | CONC SIDEWALK (5") |
| | EXISTING SIGN | SPRINKLER HEAD | CURB RAMP (TY 1) |
| | PROPOSED SIGN | TELEPHONE JUNCTION BOX | CURB RAMP (TY 2) |
| | STORM SEWER MANHOLE | TELEPHONE PEDESTAL | CURB RAMP (TY 7) |
| | | SURVEY MONUMENT | REFL PAV MARK TY 1 (W) 24" (SLD) (100MIL) |
| | | UTILITY MARKER POST | ELIM EXT PAV MRK & MRKS (4") |
| | | | PAV SURF PREP FOR MRK (24") |
| | | | ---SLPT--- TOP OF DITCH |
| | | | ---SLPB--- BOTTOM OF DITCH |

ITEM	DESCRIPTION	UNIT	QTY
0104 6017	REMOVING CONC (DRIVEWAYS)	SY	115
0160 6003	FURNISHING AND PLACING TOP SOIL (4")	SY	128
0162 6002	BLOCK SODDING	SY	128
0168 6001	VEGETATIVE WATERING	MG	11.2
0432 6002	RIPRAP (CONC) (5 IN)	CY	0.5
0529 6008	CONC CURB & GUTTER (TY II)	LF	254
0530 6004	DRIVEWAYS (CONC)	SY	198
0531 6002	CONC SIDEWALK (5")	SY	308
0531 6004	CURB RAMP (TY 1)	EA	1
0531 6005	CURB RAMP (TY 2)	EA	1
0531 6010	CURB RAMP (TY 7)	EA	1
0666 6048	REFL PAV MARK TY 1 (W) 24" (SLD) (100MIL)	LF	24
0677 6001	ELIM EXT PAV MRK & MRKS (4")	LF	30
0678 6008	PAV SURF PREP FOR MRK (24")	LF	24

SIDEWALK PLAN

BEGIN PROJECT TO STA 13+75




SHEET 1 OF 5

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MF	CONTROL	SECTION	JOB
CHECK FS	0919	03	064

25

P:\Jobs\2021\003-Pedestrian\Roadway\025-ATL-SIDEWALK PLAN 1 OF 5.dgn 10:47:55 AM 1/25/2022

P:\Jobs\2021\003-Pedestrian\Roadway\026-ATL-SIDEWALK PLAN 2 OF 5.dgn
 3:00:26 PM
 2/27/2022



NOTES:
 * FOR CONTRACTOR INFORMATION ONLY
 1. THE EXISTENCE AND LOCATION OF ALL UTILITIES AND DRAINAGE STRUCTURES INDICATED IN THE PLANS ARE TAKEN FROM THE BEST RECORDS AVAILABLE AND ARE NOT GUARANTEED TO BE ACCURATE. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES TO FIELD VERIFY UTILITIES PRIOR TO BEGINNING CONSTRUCTION.

NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801



LEGEND			
	PROP SODDING	R	RAMP
	PROP CONC DRWY	L	LANDING PAD
	PROP CONC RIPRAP	F	FLARE
	PROP CONC SIDEWALK	SL	LONG SLOPE MAY NOT EXCEED 5% OR ADJACENT ROAD SLOPE
	EXISTING SIDEWALK/DRWY TO REMAIN	T	TRANSITION
		LS	LEVEL SIDEWALK (2% MAX)
			TRAFFIC FLOW
			EXISTING SIGN
			PROPOSED SIGN
			STORM SEWER MANHOLE
	POWER POLE		DRIVEWAY ID
	TRAFFIC SIGNAL POLE		ELECTRIC PEDESTAL
	GUY WIRE		ELECTRIC METER
	FENCE		ELECTRIC JUNCTION BOX
	WATER VALVE		OVERHEAD ELECTRIC LINE
	TRAFFIC CONTROL BOX		TELEPHONE JUNCTION BOX
	WATER METER		TELEPHONE PEDESTAL
	SPRINKLER HEAD		TOP OF DITCH
	SURVEY MONUMENT		BOTTOM OF DITCH
	UTILITY MARKER POST		

ITEM	DESCRIPTION	UNIT	QTY
0104 6017	REMOVING CONC (DRIVEWAYS)	SY	298
0160 6003	FURNISHING AND PLACING TOP SOIL (4")	SY	154
0162 6002	BLOCK SODDING	SY	154
0168 6001	VEGETATIVE WATERING	MG	13.4
0432 6002	RIPRAP (CONC) (5 IN)	CY	13.4
0479 6005	ADJUSTING MANHOLES (WATER VALVE BOX)	EA	1
0529 6008	CONC CURB & GUTTER (TY II)	LF	296
0530 6001	INTERSECTIONS (CONC)	SY	183
0530 6004	DRIVEWAYS (CONC)	SY	168
0531 6002	CONC SIDEWALK (5")	SY	394
0531 6013	CURB RAMPS (TY 10)	EA	2




SIDEWALK PLAN

STA 13+75 TO STA 18+75

SHEET 2 OF 5

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO. STP 2021 (277) TAPS	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MF	CONTROL 0919	SECTION 03	JOB 064
CHECK FS			SHEET NO. 26

P:\Jobs\2021\003-Pedestrian\Roadway\027_ATL_SIDEWALK_PLAN_3 OF 5.dgn
10:47:58 AM
1/25/2022



NOTES:
* FOR CONTRACTOR INFORMATION ONLY
1. THE EXISTENCE AND LOCATION OF ALL UTILITIES AND DRAINAGE STRUCTURES INDICATED IN THE PLANS ARE TAKEN FROM THE BEST RECORDS AVAILABLE AND ARE NOT GUARANTEED TO BE ACCURATE. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES TO FIELD VERIFY UTILITIES PRIOR TO BEGINNING CONSTRUCTION.

NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801



LEGEND	
	PROP SODDING
	PROP CONC DRWY
	PROP CONC RIPRAP
	PROP CONC SIDEWALK
	EXISTING SIDEWALK/DRWY TO REMAIN
R	RAMP
L	LANDING PAD
F	FLARE
SL	LONG SLOPE MAY NOT EXCEED 5% OR ADJACENT ROAD SLOPE
T	TRANSITION
LS	LEVEL SIDEWALK (2% MAX)
	TRAFFIC FLOW
	EXISTING SIGN
	PROPOSED SIGN
	STORM SEWER MANHOLE
	POWER POLE
	TRAFFIC SIGNAL POLE
	GUY WIRE
	FENCE
	WATER VALVE
	TRAFFIC CONTROL BOX
	WATER METER
	SPRINKLER HEAD
	SURVEY MONUMENT
	UTILITY MARKER POST
	DRIVEWAY ID
	ELECTRIC PEDESTAL
	ELECTRIC METER
	ELECTRIC JUNCTION BOX
	OVERHEAD ELECTRIC LINE
	TELEPHONE JUNCTION BOX
	TELEPHONE PEDESTAL
----	TOP OF DITCH
----	BOTTOM OF DITCH


ITEM	DESCRIPTION	UNIT	QTY
0104 6017	REMOVING CONC (DRIVEWAYS)	SY	141
0160 6003	FURNISHING AND PLACING TOP SOIL (4")	SY	137
0162 6002	BLOCK SODDING	SY	137
0168 6001	VEGETATIVE WATERING	MG	11.9
0432 6002	RIPRAP (CONC) (5 IN)	CY	43.6
0479 6005	ADJUSTING MANHOLES (WATER VALVE BOX)	EA	1
0529 6008	CONC CURB & GUTTER (TY II)	LF	415
0530 6004	DRIVEWAYS (CONC)	SY	174
0531 6002	CONC SIDEWALK (5")	SY	555
6027 6009	GROUND BOX (ADJUST)	EA	1

SIDEWALK PLAN

STA 18+75 TO STA 23+75



SHEET 3 OF 5

DESIGN	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MI	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
PS	TEXAS	ATL	HARRISON
CHECK	CONTROL	SECTION	JOB
MFM			
CHECK	NO.	NO.	NO.
FS	0919	03	064



MATCHLINE STA 23+75

MATCHLINE STA 26+25



MATCHLINE STA 26+25

MATCHLINE STA 27+75

NOTES:
 * FOR CONTRACTOR INFORMATION ONLY
 1. THE EXISTENCE AND LOCATION OF ALL UTILITIES AND DRAINAGE STRUCTURES INDICATED IN THE PLANS ARE TAKEN FROM THE BEST RECORDS AVAILABLE AND ARE NOT GUARANTEED TO BE ACCURATE. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES TO FIELD VERIFY UTILITIES PRIOR TO BEGINNING CONSTRUCTION.


LOCATION	STATION	OFFSET
A	27+09.56	13.50
B	27+35.85	13.95
C	27+46.73	13.30
D	27+55.16	14.98

LEGEND

- | | | | |
|----------------------------------|--|----------------------------|------------------------|
| PROP SODDING | R RAMP | POWER POLE | DRIVEWAY ID |
| PROP CONC DRWY | L LANDING PAD | TRAFFIC SIGNAL POLE | ELECTRIC PEDESTAL |
| PROP CONC RIPRAP | F FLARE | GUY WIRE | ELECTRIC METER |
| PROP CONC SIDEWALK | SL LONG SLOPE MAY NOT EXCEED 5% OR ADJACENT ROAD SLOPE | FENCE | ELECTRIC JUNCTION BOX |
| EXISTING SIDEWALK/DRWY TO REMAIN | T TRANSITION | WATER VALVE | OVERHEAD ELECTRIC LINE |
| | LS LEVEL SIDEWALK (2% MAX) | TRAFFIC CONTROL BOX | TELEPHONE JUNCTION BOX |
| | TRAFFIC FLOW | WATER METER | TELEPHONE PEDESTAL |
| | EXISTING SIGN | SPRINKLER HEAD | |
| | PROPOSED SIGN | SURVEY MONUMENT | |
| | STORM SEWER MANHOLE | UTILITY MARKER POST | |
| | | ---SLPT--- TOP OF DITCH | |
| | | ---SLPB--- BOTTOM OF DITCH | |

ITEM	DESCRIPTION	UNIT	QTY
0104 6029	REMOVING CONC (CURB OR CURB & GUTTER)	LF	101
0104 6044	REMOVING CONC (FLUME)	SY	18
0160 6003	FURNISHING AND PLACING TOP SOIL (4")	SY	155
0162 6002	BLOCK SODDING	SY	155
0168 6001	VEGETATIVE WATERING	MG	12.1
0432 6002	RIPRAP (CONC) (5 IN)	CY	13.0
0529 6008	CONC CURB & GUTTER (TY II)	LF	169
0531 6002	CONC SIDEWALK (5")	SY	215
0531 6033	CONC SIDEWALKS (SPECIAL) (TYPE B)	SY	327

NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801



SIDEWALK PLAN



STA 23+75 TO STA 27+75

SHEET 4 OF 5

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MF	CONTROL	SECTION	JOB
CHECK FS	0919	03	064


28

P:\Jobs\2021\003-Pedestrian\Roadway\028.ATL_SIDEWALK PLAN 4 OF 5.dgn
 10:48:00 AM
 1/25/2022




NOTES:
 * FOR CONTRACTOR INFORMATION ONLY
 1. THE EXISTENCE AND LOCATION OF ALL UTILITIES AND DRAINAGE STRUCTURES INDICATED IN THE PLANS ARE TAKEN FROM THE BEST RECORDS AVAILABLE AND ARE NOT GUARANTEED TO BE ACCURATE. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES TO FIELD VERIFY UTILITIES PRIOR TO BEGINNING CONSTRUCTION.

NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801



SIDEWALK PLAN

STA 27+75 TO END PROJECT

SHEET 5 OF 5



DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MFM	CONTROL	SECTION	JOB 29
CHECK FS	0919	03	064

LEGEND	
	PROP SODDING
	PROP CONC DRWY
	PROP CONC RIPRAP
	PROP CONC SIDEWALK
	EXISTING SIDEWALK/DRWY TO REMAIN
R	RAMP
L	LANDING PAD
F	FLARE
SL	LONG SLOPE MAY NOT EXCEED 5% OR ADJACENT ROAD SLOPE
T	TRANSITION
LS	LEVEL SIDEWALK (2% MAX)
	TRAFFIC FLOW
	EXISTING SIGN
	PROPOSED SIGN
	STORM SEWER MANHOLE
	POWER POLE
	TRAFFIC SIGNAL POLE
	GUY WIRE
	FENCE
	WATER VALVE
	TRAFFIC CONTROL BOX
	WATER METER
	SPRINKLER HEAD
	SURVEY MONUMENT
	UTILITY MARKER POST
	DRIVEWAY ID
	ELECTRIC PEDESTAL
	ELECTRIC METER
	ELECTRIC JUNCTION BOX
	OVERHEAD ELECTRIC LINE
	TELEPHONE JUNCTION BOX
	TELEPHONE PEDESTAL
---SLPT---	TOP OF DITCH
---SLPB---	BOTTOM OF DITCH


ITEM	DESCRIPTION	UNIT	QTY
0160 6003	FURNISHING AND PLACING TOP SOIL (4")	SY	55
0162 6002	BLOCK SODDING	SY	55
0168 6001	VEGETATIVE WATERING	MG	4.8
0531 6002	CONC SIDEWALK (5")	SY	84
0531 6005	CURB RAMPS (TY 2)	EA	2
0531 6008	CURB RAMPS (TY 5)	EA	1
0644 6068	RELOCATE SM RD SN SUP&AM TY 10BWG	EA	2
0666 6048	REFL PAV MARK TY 1 (W)24" (SLD) (100MIL)	LF	98
0677 6001	ELIM EXT PAV MRK & MRKS (4")	LF	84
0677 6007	ELIM EXT PAV MRK & MRKS (24")	LF	25
0678 6008	PAV SURF PREP FOR MRK (24")	LF	98
6027 6009	GROUND BOX (ADJUST)	EA	1

P:\Jobs\2021\003-Pedestrian\Roadway\029_ATL_SIDEWALK_PLAN 5 OF 5.dgn
 10:48:01 AM
 1/25/2022

P:\Jobs\2021003-Pedestrian\TXDOT\ATL\atlnh\CADD\LV ROADWAY\031-ATL-SIDEWALK PROFILE 2 OF 3.dgn
 1/25/2022 10:48:05 AM



NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801





SIDEWALK PROFILE

STA 15+50 TO STA 21+00

SHEET 2 OF 3

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO.
GRAPHICS PS	STATE	DISTRICT	COUNTY
CHECK MF	TEXAS	ATL	HARRISON
CHECK FS	CONTROL	SECTION	JOB
	0919	03	064
			SHEET NO. 31

P:\Jobs\2021003-Pedestrian\TxDOT\11on\CAD\01\ROADWAY\032_ATL_SIDEWALK_PROFILE_3 OF 3.dgn
 10:48:08 AM
 1/25/2022



NO.	DATE	REVISION	BY



GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801




SIDEWALK PROFILE

STA 21+00 TO END PROJECT


SHEET 3 OF 3

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO.
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MF	CONTROL 0919	SECTION 03	JOB 064
CHECK FS	SHEET NO. 32		

ROADWAY TRANSITION




CURB ELEVATION



DIFFERENTIAL BETWEEN RAMP AND ROADWAY LOGITUDINAL SLOPE	H	
1%	0.04'	0.50"
2%	0.08'	1.00"
3%	0.12'	1.50"
4%	0.16'	2.00"
5%	0.20'	2.40"
6%	0.24'	2.90"

SEQUENCE OF WORK NARRATIVE


1. ESTABLISH AND MAINTAIN TRAFFIC CONTROL AND SW3P FEATURES PER THE VARIOUS STANDARDS INCLUDED IN THIS PLAN SET OR AS DIRECTED.
2. REMOVE EXISTING CONCRETE, ASPHALT, FOUNDATIONS, OR OTHER FEATURES WHERE INDICATED IN THE PLANS WITHIN THE AREA OF PROPOSED WORK.
3. EXCAVATE OR BACKFILL AS NECESSARY TO ACHIEVE PROPOSED GRADES, PLACE BEDDING MATERIALS.
4. FORM PROPOSED CONCRETE FEATURES.
5. PLACE CONCRETE OR ASPHALT, REMOVE AND INSTALL PAVEMENT MARKINGS, AND RELOCATE SIGNS WHERE INDICATED.
6. REMOVE FORMWORK AND BACKFILL DISTURBED AREAS FOR A SMOOTH FINISHED GRADE. GRADE TO DRAIN AS NECESSARY.
7. PLACE AND IRRIGATE BLOCK SODDING WHERE INDICATED AND AS SPECIFIED.
8. REMOVE ANY DEBRIS, TRAFFIC CONTROL, AND SW3P FEATURES AT THE COMPLETION OF CONSTRUCTION.



INLET DOWELING DETAIL N. T. S.


CURB RAMPS

ALL CURB RAMPS ARE TO BE 6" IN THICKNESS UNLESS OTHERWISE SHOWN



PLACE GROOVED JOINTS AT A MAX SPACING OF 10 FT
PLACE 3/4" EXPANSION JOINTS AT A MAX SPACING OF 40 FT TO COINCIDE WITH THE CURB EXOANSION JOINTS.

** CONTRACTOR TO USE NO. 4 REINFORCING BARS AS SPECIFIED IN ITEM 432. CONTRACTOR MAY USE HIGHER STRENGTH CLASS A CONCRETE IN LIEU OF CLASS B.



EXPANSION JOINT DETAIL

P:\Jobs\2021003-Pedestr-1 on TxDOT AT1 on CAD\01-ROADWAY\031-ATL-MISCELLANEOUS DETAILS 1 OF 2.dgn 10:48:11 AM 1/25/2022




GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801




MISCELLANEOUS DETAILS

DESIGN				SHEET 1 OF 2	
MI	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.		CIDER LN
PS	6				
GRAPHICS	STATE	DISTRICT	COUNTY	SHEET NO.	
PS	TEXAS	ATL	HARRISON	33	
CHECK	CONTROL	SECTION	JOB		
MFM	0919	03	064		
CHECK					
FS					




NOTE: CHAMFER ALL EXPOSED CORNERS 3/4".
 * 2" MIN. REQUIRED FOR LATERAL SUPPORT.

TYPE B SIDEWALK OR RAMP W/ SIDE CURB (INVERTED)
 N. T. S.
 TO BE PAID FOR UNDER ITEM 531 6033 CONC SIDEWALK (SPECIAL) (TYPE B)



SIDEWALK ADJACENT TO CURB DETAILS



IF PROPOSED ON EXISTING PAVEMENT, DRILL & INSTALL EPOXY PER ITEM 360

DRIVEWAY SLOPES W/ SIDEWALKS ADJACENT TO CURB (SECTION B-B)

P:\Jobs\2021003-Pedestrian\TxDOT\Atlanta\CADD\IV ROADWAY\034-ATL-MISCELLANEOUS DETAILS 2 OF 2.dgn
 10:48:11 AM
 1/25/2022



GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801




MISCELLANEOUS DETAILS


SHEET 2 OF 2			
DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.	HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE TEXAS	DISTRICT ATL	COUNTY HARRISON
CHECK MF	CONTROL 0919	SECTION 03	JOB 064
CHECK FS			SHEET NO. 34

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE:
FILE:




TYPE I CURB (MONOLITHIC)
2" - 4" HEIGHT




TYPE I CURB
2" - 4" HEIGHT




TYPE I CURB AND GUTTER
2" - 4" HEIGHT




TYPE II CURB (MONOLITHIC)
5" - 5 3/4" HEIGHT




TYPE II CURB
5" - 5 3/4" HEIGHT




TYPE II CURB AND GUTTER
5" - 5 3/4" HEIGHT




TYPE III CURB (KEYED)
2" - 4" HEIGHT




TYPE IIa CURB
5" - 5 3/4" HEIGHT




TYPE IIa CURB AND GUTTER
5" - 5 3/4" HEIGHT



TYPE IV CURB (KEYED)
5" - 5 3/4" HEIGHT




EXPANSION JOINT DETAIL



CURB TRANSITION
Note: To be paid for as Highest Curb

GENERAL NOTES

- All materials and construction shall be in accordance with Item 529, "Concrete Curb, Gutter, and Combined Curb and Gutter."
- Concrete shall be Class A.
- When reinforcing bars are used, they shall be No.4 unless otherwise shown. The use of fiber reinforced concrete in lieu of reinforcing steel is acceptable. Use fibers meeting the requirements of DMS 4550, "Fibers for Concrete," and dose fibers in accordance with Material Producers List (MPL) "Fibers for Class A and B Concrete Applications."
- Round exposed sharp edges with a rounding tool, to a minimum radius of 1/4 inch.
- All existing curbs and driveways to be removed shall be sawed or removed at existing joints.
- Where concrete curb is to be placed on existing concrete pavement, Bar B may be drilled and the grouted in place, or may be inserted into fresh concrete.
- Expansion and contraction joints shall be constructed to match pavement joints in all curbs and curb and gutter adjacent to jointed concrete pavement. Where placement of curb or curb and gutter is not adjacent to concrete pavement, expansion joints shall be provided at structures, curb returns at streets, and at locations directed by The Engineer.
- Vertical and horizontal dowel bars and transverse reinforcing bars shall be placed at four feet C-C.
- Dimension 'T' shown is the thickness of concrete pavement. When curb is installed adjacent to flexible pavement dimension 'T' is 8" maximum.
- Usual profile grade line. Refer to typical sections and plan-profile sheets for exact locations.
- One-half inch expansion joint material shall be provided where curb or curb and gutter is adjacent to sidewalk or riprap.
- When horizontal permissible construction joints are used, the longitudinal pavement steel shall be placed in accordance with pavement details shown elsewhere in the plans. Reinforcing steel for curb section shall then conform to that required for concrete curb.
- Bar B used as needed to support curb reinforcing steel during concrete placement.














CURB TRANSITION NOTE:
Field conditions may require a longer or shorter transition, and shall be shown elsewhere in the plans, or as directed by the Engineer.

				Design Division Standard	
<h2>CONCRETE CURB AND GUTTER</h2>					
<h3>CCCG-21</h3>					
FILE: cccg21.dgn	DN: TxDOT	CK: AN	DW: SS	CK: KM	
© TxDOT: FEBRUARY 2021	CONT	SECT	JOB	HIGHWAY	
REVISTONS	0919	03	064	CIDER LN	
	DIST	COUNTY	SHEET NO.		
	ATL	HARRISON	35		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:



NOTES / LEGEND:

SEE GENERAL NOTES ON SHEET 2 OF 4 FOR MORE INFORMATION.

DENOTES PLANTING OR NON-WALKING SURFACE NOT PART OF PEDESTRIAN CIRCULATION PATH.



GUTTER LINE

DENOTES PREFERRED LOCATION OF PEDESTRIAN PUSH BUTTON IF APPLICABLE.



RAMP LIMITS OF PAYMENT

DETECTABLE WARNING SURFACE



GRADE BREAK

PEDESTRIAN FACILITIES
CURB RAMPS

PED-18

FILE: ped18	DN: TxDOT	DW: VP	CK: KM	CK: PK & JG
© TxDOT: MARCH, 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
REVISED 08, 2009	DIST	COUNTY	SHEET NO.	
REVISED 06, 2012	ATL	HARRISON	36	
REVISED 01, 2018				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

GENERAL NOTES

CURB RAMP

1. Install a curb ramp or blended transition at each pedestrian street crossing.
2. All slopes shown are maximum allowable. Cross slopes of 1.5% and lesser running should be used. Adjust curb ramp length or grade of approach sidewalks as directed.
3. Maximum allowable cross slope on sidewalk and curb ramp surfaces is 2%.
4. The minimum sidewalk width is 5'. Where the sidewalk is adjacent to the back of curb, a 6' sidewalk width is desirable. Where a 5' sidewalk cannot be provided due to site constraints, sidewalk width may be reduced to 4' for short distances. 5' x 5' passing areas at intervals not to exceed 200' are required.
5. Turning Spaces shall be 5' x 5' minimum. Cross slope shall be maximum 2%.
6. Clear space at the bottom of curb ramps shall be a minimum of 4' x 4' wholly contained within the crosswalk and wholly outside the parallel vehicular travel path.
7. Provide flared sides where the pedestrian circulation path crosses the curb ramp. Flared sides shall be sloped at 10% maximum, measured parallel to the curb. Returned curbs may be used only where pedestrians would not normally walk across the ramp, either because the adjacent surface is planted, substantially obstructed, or otherwise protected.
8. Additional information on curb ramp location, design, light reflective value and texture may be found in the latest draft of the Proposed Guidelines for Pedestrian Facilities in the Public Right of Way (PROWAG) as published by the U.S. Architectural and Transportation Barriers Compliance Board (Access Board).
9. To serve as a pedestrian refuge area, the median should be a minimum of 6' wide, measured from back of curbs. Medians should be designed to provide accessible passage over or through them.
10. Small channelization islands, which do not provide a minimum 5' x 5' landing at the top of curb ramps, shall be cut through level with the surface of the street.
11. Crosswalk dimensions, crosswalk markings and stop bar locations shall be as shown elsewhere in the plans. At intersections where crosswalk markings are not required, curb ramps shall align with theoretical crosswalks unless otherwise directed.
12. Provide curb ramps to connect the pedestrian access route at each pedestrian street crossing. Handrails are not required on curb ramps.
13. Curb ramps and landings shall be constructed and paid for in accordance with Item 531 "Sidewalks".
14. Place concrete at a minimum depth of 5" for ramps, flares and landings, unless otherwise directed.
15. Furnish and install No. 3 reinforcing steel bars at 18" o.c. both ways, unless otherwise directed.
16. Provide a smooth transition where the curb ramps connect to the street.
17. Curbs shown on sheet 1 within the limits of payment are considered part of the curb ramp for payment, whether it is concrete curb, gutter, or combined curb and gutter.
18. Existing features that comply with applicable standards may remain in place unless otherwise shown on the plans.

DETECTABLE WARNING MATERIAL


19. Curb ramps must contain a detectable warning surface that consists of raised truncated domes complying with PROWAG. The surface must contrast visually with adjoining surfaces, including side flares. Furnish and install an approved cast-in-place dark brown or dark red detectable warning surface material adjacent to uncolored concrete, unless specified elsewhere in the plans.
20. Detectable Warning Materials must meet TxDOT Departmental Materials Specification DMS 4350 and be listed on the Material Producer List. Install products in accordance with manufacturer's specifications.
21. Detectable warning surfaces must be firm, stable and slip resistant.
22. Detectable warning surfaces shall be a minimum of 24 inches in depth in the direction of pedestrian travel, and extend the full width of the curb ramp or landing where the pedestrian access route enters the street.
23. Detectable warning surfaces shall be located so that the edge nearest the curb line is at the back of curb and neither end of that edge is greater than 5 feet from the back of curb. Detectable warning surfaces may be curved along the corner radius.
24. Shaded areas on Sheet 1 of 4 indicate the approximate location for the detectable warning surface for each curb ramp type.

DETECTABLE WARNING PAVERS (IF USED)

25. Furnish detectable warning paver units meeting all requirements of ASTM C-936, C-33. Lay in a two by two unit basket weave pattern or as directed.
26. Lay full-size units first followed by closure units consisting of at least 25 percent (25%) of a full unit. Cut detectable warning paver units using a power saw.


SIDEWALKS

27. Provide clear ground space at operable parts, including pedestrian push buttons. Operable parts shall be placed within unobstructed reach range specified in PROWAG section R406.
28. Place traffic signal or illumination poles, ground boxes, controller boxes, signs, drainage facilities and other items so as not to obstruct the pedestrian access route or clear ground space.
29. Street grades and cross slopes shall be as shown elsewhere in the plans.
30. Changes in level greater than 1/4 inch are not permitted.
31. The least possible grade should be used to maximize accessibility. The running slope of sidewalks and crosswalks within the public right of way may follow the grade of the parallel roadway. Where a continuous grade greater than five percent (5%) must be provided, handrails may be desirable to improve accessibility. Handrails may also be needed to protect pedestrians from potentially hazardous conditions. If provided, handrails shall comply with PROWAG R409.
32. Handrail extensions shall not protrude into the usable landing area or into intersecting pedestrian routes.
33. Driveways and turnouts shall be constructed and paid for in accordance with Item "Intersections, Driveways and Turnouts". Sidewalks shall be constructed and paid for in accordance with Item, "Sidewalks".
34. Sidewalk details are shown elsewhere in the plans.




SECTION VIEW DETAIL
CURB RAMP AT DETECTIBLE WARNINGS


DETECTABLE WARNING SURFACE DETAILS



PARALLEL CURB RAMP
TYPICAL PLACEMENT OF DETECTABLE WARNING SURFACE ON LANDING AT STREET EDGE.



PERPENDICULAR CURB RAMP
TYPICAL PLACEMENT OF DETECTABLE WARNING SURFACE ON SLOPING RAMP RUN.



* NOTE:
BOTH ENDS OF THE
DETECTABLE WARNING SURFACE
SHALL BE 5' OR LESS
FROM BACK OF CURB.





DIRECTIONAL CURB RAMP
TYPICAL PLACEMENT OF DETECTABLE WARNING SURFACE ON SLOPING RAMP RUN.

SHEET 2 OF 4

Texas Department of Transportation		Design Division Standard	
PEDESTRIAN FACILITIES CURB RAMPS			
PED-18			
FILE: ped18	DN: TxDOT	DW: VP	CK: KM
© TxDOT: MARCH, 2002	CONT	SECT	JOB
REVISIONS	0919	03	064
REVISED 08, 2009	DIST	COUNTY	SHEET NO.
REVISED 06, 2012	ATL	HARRISON	37
REVISED 01, 2018			


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

SIDEWALK TREATMENT AT DRIVEWAYS




NOTES:

- * WHERE DRIVEWAYS CROSS THE PEDESTRIAN ROUTE, SIDES SHALL BE FLARED AT 10% MAX SLOPE.
- ** IF CURB HEIGHT IS GREATER THAN 6 INCHES, USE GRADE LESS THAN OR EQUAL TO 5%. HANDRAIL AND DETECTABLE WARNING ARE NOT REQUIRED.




PROTECTED ZONE

NOTE: IN PEDESTRIAN CIRCULATION AREA, MAXIMUM 4" PROJECTION FOR POST OR WALL MOUNTED OBJECTS BETWEEN 27" AND 80" ABOVE THE SURFACE.




CLEAR SPACE ADJACENT TO PEDESTRIAN PUSH BUTTON



PLAN VIEW
PLACEMENT OF STREET FIXTURES

NOTE: ITEMS NOT INTENDED FOR PUBLIC USE. MINIMUM 4' X 4' CLEAR GROUND SPACE REQUIRED AT PUBLIC USE FIXTURES.




WHEN AN OBSTRUCTION OF A HEIGHT GREATER THAN 27" FROM THE SURFACE WOULD CREATE A PROTRUSION OF MORE THAN 4" INTO THE PEDESTRIAN CIRCULATION AREA, CONSTRUCT ADDITIONAL CURB OR FOUNDATION AT THE BOTTOM TO PROVIDE A MAXIMUM 4" OVERHANG.

PROTRUDING OBJECTS OF A HEIGHT ≤ 27" ARE DETECTABLE BY CANE AND DO NOT REQUIRE ADDITIONAL TREATMENT.

DETECTION BARRIER FOR VERTICAL CLEARANCE < 80"

SHEET 3 OF 4



PEDESTRIAN FACILITIES
CURB RAMPS


PED-18

FILE: ped18	DN: TxDOT	DW: VP	CK: KM	CK: PK & JG
© TxDOT: MARCH, 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
REVISED 08, 2005	DIST	COUNTY	SHEET NO.	
REVISED 06, 2012	ATL	HARRISON	38	
REVISED 01, 2018				


DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPICAL CROSSING LAYOUTS
SEE SHEET 1 OF 4 FOR DETAILS AND DIMENSIONS





SKewed INTERSECTION WITH "LARGE" RADIUS




AT INTERSECTION W/FREE RIGHT TURN & ISLAND



SKewed INTERSECTION WITH "SMALL" RADIUS



MID-BLOCK PLACEMENT PERPENDICULAR RAMPS



NORMAL INTERSECTION WITH "SMALL" RADIUS

LEGEND:


- SHOWS DOWNWARD SLOPE. →
- DENOTES PREFERRED LOCATION OF PEDESTRIAN PUSH BUTTON (IF APPLICABLE). ☒
- DENOTES PLANTING OR NON-WALKING SURFACE NOT PART OF PEDESTRIAN CIRCULATION PATH. ↙ ↘ ↙ ↘ ↙ ↘

SHEET 4 OF 4

		Design Division Standard	
<h2>PEDESTRIAN FACILITIES CURB RAMPS</h2> <h3>PED-18</h3>			
FILE: ped18	DN: TxDOT	DW: VP	CK: KM
© TxDOT: MARCH, 2002	CON: 0919	SECT: 03	JOB: 064
REVISIONS	DIST: ATL		COUNTY: HARRISON
REVISED 08, 2005	SHEET NO. 39		HIGHWAY: CIDER LN
REVISED 06, 2012			
REVISED 01, 2018			

DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




HIGH-VISIBILITY LONGITUDINAL CROSSWALK AT CONTROLLED APPROACH

GENERAL NOTES

1. Longitudinal crosswalk lines should not be placed in the wheel path of vehicles. Center the crosswalk lines on travel lanes, lane lines, and shoulder lines (if present).
2. A minimum 6" clear distance shall be provided to the curb face. If the last crosswalk line falls into this distance it must be omitted.
3. For divided roadways, adjustments in spacing of the crosswalk lines should be made in the median so that the crosswalk lines are maintained in their proper location across the travel portion of the roadway.
4. At skewed crosswalks, the crosswalk lines are to remain parallel to the lane lines.
5. Each crosswalk shall be a minimum of 6' wide.
6. The High-Visibility Longitudinal Crosswalk is the preferred crosswalk pattern on State Highways. Other crosswalk patterns as shown in the "Texas Manual on Uniform Traffic Control Devices" may be used. All crosswalk designs and dimension shall comply with the "Texas Manual on Uniform Traffic Control Devices."
7. Final placement of Stop Bar/Yield Triangles and Crosswalk shall be approved by the Engineer in the field.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



UNSIGNALIZED MID BLOCK HIGH-VISIBILITY LONGITUDINAL CROSSWALK

NOTES

1. Use yield triangles with "Yield Here to Pedestrians" signs at unsignalized mid block crosswalks.
2. Use stop bars with "Stop Here on Red" signs at mid block crosswalks controlled by traffic signals or pedestrian hybrid beacons.



CROSSWALK PAVEMENT MARKINGS

PM(4) - 20

FILE: pm4-20.dgn	DN:	CK:	DW:	CK:
© TxDOT June 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
	DIST	COUNTY	SHEET NO.	
	ATL	HARRISON	40	

DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/25/2022 10:48:14 AM
 FILE: P:\Jobs\2021003-Pedestrian TxDOT Atlanta\CADD\ROADWAY STANDARDS\041_SMD(GEN)-08.dgn

SIGN SUPPORT DESCRIPTIVE CODES

(Descriptive Codes correspond to project estimate and quantities sheets)

SM RD SGN ASSM TY XXXXX(X)XX(X-XXXX)

Post Type

FRP = Fiberglass Reinforced Plastic Pipe (see SMD(FRP))
 TWT = Thin-Walled Tubing (see SMD(TWT))
 10BWG = 10 BWG Tubing (see SMD(SLIP-1) to (SLIP-3))
 S80 = Schedule 80 Pipe (see SMD(SLIP-1) to (SLIP-3))

Number of Posts (1 or 2)


Anchor Type

UA = Universal Anchor - Concreted (see SMD(FRP) and (TWT))
 UB = Universal Anchor - Bolted down (see SMD(FRP) and (TWT))
 WS = Wedge Anchor Steel - (see SMD(TWT))
 WP = Wedge Anchor Plastic (see SMD(TWT))
 SA = Slipbase - Concreted (see SMD(SLIP-1) to (SLIP-3))
 SB = Slipbase - Bolted Down (see SMD(SLIP-1) to (SLIP-3))

Sign Mounting Designation

P = Prefab. "Plain" (see SMD(SLIP-1) to (SLIP-3), (TWT), (FRP))
 T = Prefab. "T" (see SMD(SLIP-1) to (SLIP-3), (TWT))
 U = Prefab. "U" (see SMD(SLIP-1) to (SLIP-3))
 IF REQUIRED
 1EXT or 2EXT = Number of Extensions (see SMD(SLIP-1) to (SLIP-3), (TWT))
 BM = Extruded Wind Beam (see SMD(SLIP-1) to (SLIP-3))
 WC = 1.12 #/ft Wing Channel (see SMD(SLIP-1) to (SLIP-3))
 EXAL = Extruded Aluminum Sign Panels (see SMD(SLIP-3))


REQUIRED CLEARANCE FOR BREAKAWAY SUPPORT



To avoid vehicle undercarriage snagging, any substantial remains of a breakaway support, when it is broken away, should not project more than 4 inches above a 60-inch chord (i.e., typical space between wheel paths).


SIGN LOCATION

PAVED SHOULDERS



LESS THAN 6 FT. WIDE


When the shoulder is 6 ft. or less in width, the sign must be placed at least 12 ft. from the edge of the travel lane.



GREATER THAN 6 FT. WIDE


When the shoulder is greater than 6 ft in width, the sign must be placed at least 6 ft. from the edge of the shoulder.

T-INTERSECTION




When this sign is needed at the end of a two-lane, two way roadway, the right edge of the sign should be in line with the centerline of the roadway. Place as close to ROW as practical.

No more than 2 sign posts should be located within a 7 ft. circle.




BEHIND BARRIER




BEHIND GUARDRAIL

**Sign clearance based on distance required for proper guard rail or concrete barrier performance.



BEHIND CONCRETE BARRIER

TYPICAL SIGN ATTACHMENT DETAIL




Bolts used to mount sign panels to the clamp are 5/16-18 UNC galvanized square head with nut, nylon washer, flat washer and lock washer. The bolt length is 1 inch for aluminum.

When two sign clamps are used to mount signs back-to-back, use a 5/16-18 UNC galvanized hex head per ASTM A307 with nut and helical-spring lock washer. The approximate bolt lengths for various post sizes and sign clamp types are given in the table at right. The bolt length may need to be adjusted depending upon field conditions.

Sign clamps may be either the specific size clamp or the universal clamp.


Pipe Diameter	Approximate Bolt Length	
	Specific Clamp	Universal Clamp
2" nominal	3"	3 or 3 1/2"
2 1/2" nominal	3 or 3 1/2"	3 1/2 or 4"
3" nominal	3 1/2 or 4"	4 1/2"

SIGNS WITH PLAQUES




When a supplemental plaque or secondary sign is used, the 7 ft sign height is measured to the bottom of the supplemental plaque or secondary sign.

CURB & GUTTER OR RAISED ISLAND



RESTRICTED RIGHT-OF-WAY (When 6 ft min. is not possible.)



Right-of-way restrictions may be created by rocks, water, vegetation, forest, buildings, a narrow island, or other factors.

In situations where a lateral restriction prevents the minimum horizontal clearance from the edge of the travel lane, signs should be placed as far from the travel lane as practical.

*** Post may be shorter if protected by guardrail or if Engineer determines the post could not be hit due to extreme slope.

* Signs shall be mounted using the following condition that results in the greatest sign elevation:

- (1) a minimum of 7 to a maximum of 7.5 feet above the edge of the travel lane or
- (2) a minimum of 7 to a maximum of 7.5 feet above the grade at the base of the support when sign is installed on the backslope.

The maximum values may be increased when directed by the Engineer.

See the Traffic Operations Division website for detailed drawings of sign clamps, Triangular Slipbase System components and Wedge Anchor System components.

The website address is:
<http://www.txdot.gov/publications/traffic.htm>




SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS GENERAL NOTES & DETAILS

SMD(GEN)-08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0919	03	064	CIDER LN
		DIST	COUNTY		SHEET NO.
		ATL	HARRISON		41

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TRIANGULAR SLIPBASE INSTALLATION GENERAL REQUIREMENTS



NOTE

There are various devices approved for the Triangular Slipbase System. Please reference the Material Producer List for approved slip base systems. http://www.txdot.gov/business/producer_list.htm The devices shall be installed per manufacturers' recommendations. Installation procedures shall be provided to the Engineer by Contractor.

GENERAL NOTES:

- Slip base shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to approval of the TxDOT Traffic Standards Engineer.
- Material used as post with this system shall conform to the following specifications:
 - 10 BWG Tubing (2.875" outside diameter)
 - 0.134" nominal wall thickness
 - Seamless or electric-resistance welded steel tubing or pipe
 - Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008
 - Other steels may be used if they meet the following:
 - 55,000 PSI minimum yield strength
 - 70,000 PSI minimum tensile strength
 - 20% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.122" to 0.138"
 - Outside diameter (uncoated) shall be within the range of 2.867" to 2.883"
 - Galvanization per ASTM A123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833.
 - Schedule 80 Pipe (2.875" outside diameter)
 - 0.276" nominal wall thickness
 - Steel tubing per ASTM A500 Gr C
 - Other seamless or electric-resistance welded steel tubing or pipe with equivalent outside diameter and wall thickness may be used if they meet the following:
 - 46,000 PSI minimum yield strength
 - 62,000 PSI minimum tensile strength
 - 21% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.248" to 0.304"
 - Outside diameter (uncoated) shall be within the range of 2.855" to 2.895"
 - Galvanization per ASTM A123
- See the Traffic Operations Division website for detailed drawings of sign clamps and Texas Universal Triangular Slipbase System components. The website address is: <http://www.txdot.gov/publications/traffic.htm>
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.

ASSEMBLY PROCEDURE


Foundation

- Prepare 12-inch diameter by 42-inch deep hole. If solid rock is encountered, the depth of the foundation may be reduced such that it is embedded a minimum of 18 inches into the solid rock.
- The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor-driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class A.
- Push the pipe end of the slip base stub into the center of the concrete. Rotate the stub back and forth while pushing it down into the concrete to assure good contact between the concrete and stub. Continue to work the stub into the concrete until it is between 2 to 4 inches above the ground.
- Plumb the stub. Allow a minimum of 4 days to set, unless otherwise directed by the Engineer.
- The triangular slipbase system is multidirectional and is designed to release when struck from any direction.

Support

- Cut support so that the bottom of the sign will be 7 to 7.5 feet above the edge of the travelway (i.e., edge of the closest lane) when slip plate is below the edge of pavement or 7 to 7.5 feet above slip plate when the slip plate is above the edge of the travelway. The cut shall be plumb and straight.
- Attach sign to support using connections shown. When multiple signs are installed on the same support, ensure the minimum clearance between each sign is maintained. See SMD(SLIP-2) for clearances based on sign types.

CONCRETE ANCHOR



5/8" diameter Concrete Anchor - 8 places (embed a minimum of 5 1/2" and torque to min. of 50 ft-lbs). Anchor may be expansion or adhesive type.

SM RD SGN ASSM TY XXXXX(X)SB(X-XXXX)

Concrete anchor consists of 5/8" diameter stud bolt with UNC series bolt threads on the upper end. Heavy hex nut per ASTM A563, and hardened washer per ASTM F436. The stud bolt shall have a minimum yield and ultimate tensile strength of 50 and 75 KSI, respectively. Nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." Adhesive type anchors shall have stud bolts installed with Type III epoxy per DMS-6100, "Epoxyes and Adhesives." Adhesive anchors may be loaded after adequate epoxy cure time per the manufacturer's recommendations. Top of bolt shall extend at least flush with top of the nut when installed. The anchor, when installed in 4000 psi normal-weight concrete with a 5 1/2" minimum embedment, shall have a minimum allowable tension and shear of 3900 and 3100 psi, respectively.


















Texas Department of Transportation
Traffic Operations Division

SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

SMD(SLIP-1)-08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0919	03	064	CIDER LN
		DIST	COUNTY		SHEET NO.
		ATL	HARRISON		42

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



- GENERAL NOTES:**
1. SIGN SUPPORT # OF POSTS MAX. SIGN AREA

10 BWG	1	16 SF
10 BWG	2	32 SF
Sch 80	1	32 SF
Sch 80	2	64 SF
 2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
 3. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
 4. Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
 5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
 6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
 7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
 8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
 9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
 10. Additional route markers may be added vertically, provided the total sign area does not exceed the maximum allowable amount per Note 1.
 11. Additional sign clamp required on the "T-bracket" post for 24 inch height signs. Place the clamp 3 inches above bottom of sign when possible.
 12. Post open ends shall be fitted with Friction Caps.
 13. Sign blanks shall be the sizes and shapes shown on the plans.

REQUIRED SUPPORT	
SIGN DESCRIPTION	SUPPORT
48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)
48x60-inch signs	TY S80(1)XX(T)
48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)
48x60-inch signs	TY S80(1)XX(T)
48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)
48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)
Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)

Friction caps may be manufactured from hot rolled or cold rolled steel sheets. The minimum sheet metal thickness shall be 24 gauge for all cap sizes. The rim edges shall be reasonably straight and smooth. Caps shall be sized and formed in such a manner as to produce a drive-on friction fit and have no tendency to rock when seated on the pipe. The depth shall be sufficient to give positive protection against entrance of rainwater. They shall be free of sharp creases or indentations and show no evidence of metal fracture. Caps shall have an electrodeposited coating of zinc in accordance with the requirements of ASTM B633 Class FE/ZN 8.

Texas Department of Transportation
Traffic Operations Division




SIGN MOUNTING DETAILS
SMALL ROADSIDE SIGNS
TRIANGULAR SLIPBASE SYSTEM
SMD(SLIP-2)-08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0919	03	064	CIDER LN
		DIST	COUNTY		SHEET NO.
		ATL	HARRISON		43

DATE:
FILE:








DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:



GENERAL NOTES:

- | SIGN SUPPORT | # OF POSTS | MAX. SIGN AREA |
|--------------|------------|----------------|
| 10 BWG | 1 | 16 SF |
| 10 BWG | 2 | 32 SF |
| Sch 80 | 1 | 32 SF |
| Sch 80 | 2 | 64 SF |
- The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
- Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
- Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
- For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
- When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
- Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
- Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
- Sign blanks shall be the sizes and shapes shown on the plans.
- Additional sign clamp required on the "T-bracket" post for 24 inch high signs. Place the clamp 3 inches above bottom of sign when possible.
- Post open ends shall be fitted with Friction Caps.



Use Extruded Alum. Windbeam as stiffeners See SMD (2-1) for additional details
See Detail E for clamp installation

		REQUIRED SUPPORT	
		SIGN DESCRIPTION	SUPPORT
Regulatory	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)	
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)	
	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)	
	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)	
	48x60-inch signs	TY S80(1)XX(T)	
Warning	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)	
	48x60-inch signs	TY S80(1)XX(T)	
	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)	
	48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)	
	Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)	

Texas Department of Transportation
Traffic Operations Division

SIGN MOUNTING DETAILS
SMALL ROADSIDE SIGNS
TRIANGULAR SLIPBASE SYSTEM
SMD(SLIP-3)-08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0919	03	064	CIDER LN
		DIST	COUNTY		SHEET NO.
		ATL	HARRISON		44

RUNOFF COMPUTATION BY RATIONAL METHOD: INLET CATCHMENTS FOR EXISTING CONDITIONS

AREA (ACRES)		AREA DISTRIBUTION (ACRES) vs C			WEIGHTED	TIME OF CONCENTRATION (MIN)		RAIN FALL INTENSITY, I (INCH/HR)					RUNOFF, Q (CFS)					DESIGN, Q, 5-Year	REMARK
NO.	A	GRASS=0.40	ASPHALT=0.85	CONC=0.90	C	CALC Tc	DESIGN Tc	5-Year	10-Year	25-Year	50-Year	100-Year	5-Year	10-Year	25-Year	50-Year	100-Year	5-Year	
DI-1	2.05	1.19	0.17	0.69	0.61	4.5	10	5.71	6.61	7.80	8.69	9.59	7.09	8.21	9.68	10.79	11.91	7.09	EXIST DROP INLET
DI-2	0.77	0.49	0.23	0.05	0.57	4.5	10	5.71	6.61	7.80	8.69	9.59	2.49	2.89	3.40	3.79	4.19	2.49	EXIST DROP INLET
DI-3	0.53	0.37	0.16	0.00	0.54	4.0	10	5.71	6.61	7.80	8.69	9.59	1.62	1.88	2.21	2.47	2.72	1.62	EXIST DROP INLET

RUNOFF COMPUTATION BY RATIONAL METHOD: INLET CATCHMENTS FOR PROPOSED CONDITIONS

AREA (ACRES)		AREA DISTRIBUTIONS (ACRES) vs C			WEIGHTED	TIME OF CONCENTRATION (MIN)		RAIN FALL INTENSITY, I (INCH/HR)					RUNOFF, Q (CFS)					DESIGN, Q, 5-Year	REMARK
NO.	A	GRASS=0.40	ASPHALT=0.85	CONC=0.90	C	CALC Tc	DESIGN Tc	5-Year	10-Year	25-Year	50-Year	100-Year	5-Year	10-Year	25-Year	50-Year	100-Year	5-Year	
DI-1	2.05	1.16	0.17	0.72	0.61	4.5	10	5.71	6.61	7.80	8.69	9.59	7.17	8.31	9.80	10.92	12.05	7.17	EXISTING DROP INLET
DI-2	0.22	0.19	0.02	0.01	0.46	10.7	11	5.56	6.44	7.60	8.48	9.35	0.57	0.66	0.78	0.86	0.95	0.57	PROP DROP INLET
DI-2A	0.07	0.07	0.00	0.00	0.40	2.8	10	5.71	6.61	7.80	8.69	9.59	0.16	0.19	0.22	0.24	0.27	0.16	PROP PIPE UNDER DRWY
DI-3	0.10	0.10	0.00	0.00	0.40	7.9	10	5.71	6.61	7.80	8.69	9.59	0.23	0.26	0.31	0.35	0.38	0.23	EXISTING DROP INLET
CI-4	0.05	0.00	0.02	0.03	0.88	6.3	10	5.71	6.61	7.80	8.69	9.59	0.25	0.29	0.34	0.38	0.42	0.25	PROP CURB INLET
CI-5	0.37	0.00	0.16	0.21	0.88	7.3	10	5.71	6.61	7.80	8.69	9.59	1.86	2.15	2.53	2.83	3.12	1.86	PROP CURB INLET
CI-6	0.30	0.00	0.13	0.17	0.88	4.1	10	5.71	6.61	7.80	8.69	9.59	1.50	1.74	2.05	2.29	2.53	1.50	PROP CURB INLET

ON-GRADE INLETS CALCULATIONS

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)	(23)	(24)	(25)	(26)	(27)	(28)
INLET ID	INLET TYPE	DRAINAGE AREA A	WEIGHTED C	CA	CALC TIME OF CONCENTRATION Tc	MIN USED Tc	INTENSITY I	DESIGN FLOW Q	BY PASS FLOW, Qco	TOTAL DESIGN FLOW, Q	INVERSE RDWY X-SLOPE	GUTTER LONGIT. SLOPE S	PONDED DEPTH y	PONDED WIDTH T	CURB OPENING DEPRESSION DEPTH a	FUNCTION OF S & Sx E	GUTTER DEPRESSION WIDTH W	GRATE INLET REQ'D Lr	CURB INLET REQ'D Lr	SLOT INLET REQ'D Lr	DESIGN LENGTH La	RATIO La/Lr	RATIO a/W	CARRY OVER Qco	CARRY OVER TO	INLET CAPACITY Qi	REMARK
		(AC)		(AC)	(MIN)	(MIN)	(INC/HR)	(CFS)	(CFS)	(CFS)	1/Sx	(%)	(FT)	(FT)	(FT)		(FT)	(FT)	(FT)	(FT)	(FT)			(CFS)		(CFS)	
CI-5	CURB INLET	0.37	0.88	0.33	7.25	10	5.71	1.86	0.08	1.94	50	0.66%	0.21	10.34	0.25		1.33	n/a	7.01	n/a	5	0.71	0.18797	0.20	CI-4	1.73	CI-5
CI-6	CURB INLET	0.30	0.88	0.26	4.12	10	5.71	1.50		1.50	50	0.76%	0.18	9.15	0.25		1.33	n/a	6.24	n/a	5	0.80	0.18797	0.08	CI-5	1.42	CI-6

CURB INLETS ON SAG CALCULATIONS

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)	(23)	(24)	(25)	(26)	(27)	(28)	(29)
INLET ID	INLET TYPE	INLET LOCATION / STATION	DRAINAGE AREA A	WEIGHTED C	CA	CALC CONCENTRATION TIME Tc	MIN USED Tc	INTENSITY I	RUNOFF FLOW Q	BY-PASS FLOW Qco	TOTAL DESIGN FLOW Qt	INVERSE RDWY X-SLOPE	PONDED WIDTH ALLOWED T...	PONDED DEPTH ALLOWED Y...	LONGIT. SLOPE	% OF TOTAL FLOW %Qt	PONDED DEPTH y	PONDED WIDTH T	LONGIT. SLOPE	% OF TOTAL FLOW %Qt	PONDED DEPTH y	PONDED WIDTH T	CURB OPENING DEPRESSION DEPTH, a	GUTTER DEPRESSION WIDTH W	h	CURB INLET REQ'D LENGTH Lr	CURB INLET USED	COMMENT
			(AC)		(AC)	(MIN)	(MIN)	(INC/HR)	(CFS)	(CFS)	(CFS)	1/Sx	(FT)	(FT)	(%)	(%)	(FT)	(FT)	(FT/FT)	(%)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	
CI-4	PROP CURB INLET	16+44.55	0.05	0.88	0.044		10	5.71	0.25	0.20	0.46	50	12.00	0.24	4.58%	40%	0.06	2.96	2.02%	60%	0.08	4.02	0.25	1.33	0.49	0.6	10	

DROP INLET CALCULATIONS

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)
ID	TYPE	LOCATION	AREA NO	DRAINAGE AREA A	WEIGHTED C	CA	ATUAL TIME Tc	INLET TIME	INTENSITY I	DESIGN FLOW Q	CARRY OVER FLOW CO	TOTAL DESIGN FLOW QT	ALLOWABLE HEAD ON GRATE H	GRATE PERIMETER P	WEIR CAPACITY OF GRATE QW	CLEAR OPENING AREA OF GRATE, A/2	ORIFICE CAPACITY OF GRATE Qo	INLET CAPACITY QC	REMARKS
				(AC)		(AC)	(MIN)	(MIN)	(IN/HR)	(CFS)	(CFS)	(CFS)	(FT)	(FT)	(CFS)	(SF)	(CFS)	(CFS)	
DI-1			DI-1	2.05	0.61	1.26		10.00	5.71	7.17		7.17	0.7	12.00	9.65	16.00	34.94	9.65	
DI-2			DI-2 & DI-2A	0.29	0.86	0.25		10.70	5.56	1.39		1.39	0.7	9.00	7.24	9.00	19.66	7.24	
DI-3			DI-3	0.10	0.40	0.04		10.00	5.71	0.23		0.23	0.7	9.00	7.24	9.00	19.66	7.24	

NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801

EJES INCORPORATED
 12801 N. CENTRAL EXPY.
 STE. 700
 DALLAS, TEXAS 75243
 TEL: 214-343-1210 / FAX: 214-343-3885
 FIRM REG F-2488


Texas Department of Transportation
 ©2022 TXDOT

HYDROLOGIC AND INLET CALCULATIONS

SHEET 1 OF 1

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
MI	TEXAS	ATL	HARRISON
CHECK	CONTROL	SECTION	JOB
MFM	0919	03	064

45



FILES

STORM SEWER CALCULATIONS


(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	21
LINE NO.	STATION/LOCATION		DRAINAGE AREA NO.	INLET CA	ACCUM. TIME	TIME USED	INTENSITY I	DISCHARGE Q	U/S SOFIT EL	D/S SOFIT EL	CONDUIT LENGTH	PIPE SLOPE	RCP SIZE REQUIRED	PIPE DIA. USED	UNIFORM DEPTH	VELOCITY	TRAVEL TIME ALONG PIPE	TIME AT CONDUIT END	REMARK	
	FROM	TO																		
L4	CI-4	CI-5	CI-4	0.04	10	10	5.71	0.25	388.94	388.00	58.45	1.61%	4.06"	24"	0.32	0.76	1.3	11.3		
L6	CI-6	DI-3	CI-6	0.26	10	10	5.71	1.50	395.91	394.75	19.00	6.11%	6.19"	24"	0.23	7.39		10.0		
L2	DI-2	CI-5	CI-2	0.09	11	11	5.56	0.49	389.03	388.89	11.56	1.21%	5.50"	36"	0.19	2.63	0.1	10.8	EXISTING 36" RCP	
L5	CI-5	OUTFALL	CI-4,CI-5,DI-2	0.47	11	11	5.71	2.69	388.84	388.43	34.00	1.21%	10.42"	36"	0.50	3.43	0.2	10.9	EXISTING 36" RCP	
L-2A	US	DS	CI-2A	0.03	10	10	5.71	0.16	396.14	395.66	51.80	0.93%	3.80"	12"	0.11	3.31	0.3	10.3		

HYDRAULIC GRADELINE CALCULATIONS

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)
LINE NO.	D/S ID	U/S ID	DESIGN FLOW	CONDUIT LENGTH	PIPE SIZE USED	FRICITION SLOPE S	PIPE SLOPE	FRICITION LOSS	D/S HGL	D/S HGL + LOSS	NORMAL DEPTH	U/S FL ELEV	U/S FL + NORMAL DEPTH	U/S HGL	REMARKS
			(CFS)	(FT)	(IN)	(%)	(%)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	
L4	CI-4	CI-5	0.25	58.45	24	0.0004	1.61%	0.0224	388.00	388.02	0.32	386.94	387.26	388.02	
L6	CI-6	DI-3	1.50	19.00	24	0.0542	6.11%	1.0293	394.75	395.78	0.23	393.91	394.14	395.78	
L2	DI-2	CI-5	0.49	11.56	36	0.0087	1.21%	0.1007	388.89	388.99	0.19	386.03	386.22	388.99	
L5	CI-5	OUTFALL	2.69	34.00	36	0.0043	1.21%	0.1467	388.43	388.58	0.5	385.84	386.34	388.58	
L2A	US	DS	0.16	51.80	12	0.0287	0.93%	1.4875	395.40	396.89	0.11	395.14	395.25	396.89	

CHANNEL COMPUTATIONS

INLET ID	STATION	CHANNEL CHARACTERISTICS								CHANNEL CAPACITY, Qcap				DITCH FLOW LINE ELEV	WATER SURFACE	DESIGN FLOW Q	REMARK
		CHANNEL LEFT SIDE SLOPE	CHANNEL RIGHT SIDE SLOPE	CHANNEL BOTTOM WIDTH, W (FT)	WATER DEPTH D (FT)	WETTED PERIMETER Wp (FT)	WETTED AREA A (FT)	HYDRAULIC RADIUS, R (FT)	CHANNEL SLOPE, S %	CONCRETE LINING, n = 0.015		GRASS CHANNEL, n = 0.03					
										(CFS)	(FPS)	(CFS)	(FPS)				
DI-2	17+50.00	3:1	4:1	0	1.00	7.285	3.500	0.480	0.94%	20.37	5.82	10.19	2.91	390.84	391.84	5.563	CHANNEL CAPACITY > DESIGN FLOW
	19+23.16	2:1	2:1	0	1.00	4.472	2.000	0.447	0.56%	8.57	4.28			394.00	395.00	5.563	CHANNEL CAPACITY > DESIGN FLOW
	20+13.29	2:1	2:1	0	1.00	4.472	2.000	0.447	0.44%	7.59	3.80			394.40	395.40	5.563	CHANNEL CAPACITY > DESIGN FLOW
DI-2A	20+98.00	1:1	1:1	0	1.00	2.829	1.000	0.354	4.77%	10.69	10.69			394.67	395.67	0.160	CHANNEL CAPACITY > DESIGN FLOW
	22+50.00	3:1	3:1	0	1.00	6.325	3.000	0.474	1.15%	19.15	6.38	9.58	3.19	397.04	397.04	0.160	CHANNEL CAPACITY > DESIGN FLOW
DI-3	23+18.86	4:1	4:1	0	1.00	8.246	4.000	0.485	0.56%			9.04	2.26	397.84	398.84	0.228	CHANNEL CAPACITY > DESIGN FLOW
	24+00.00	4:1	4:1	0	1.00	8.246	4.000	0.485	0.56%			9.04	2.26	398.29	399.29	0.228	CHANNEL CAPACITY > DESIGN FLOW
	24+50.00	4:1	4:1	0	1.00	8.246	4.000	0.485	1.34%			13.99	3.50	398.61	399.61	0.228	CHANNEL CAPACITY > DESIGN FLOW



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801

EJES INCORPORATED
 12801 N. CENTRAL EXPY.
 STE. 700
 DALLAS, TEXAS 75243
 TEL: 214-343-1210 / FAX: 214-343-3885
 FIRM REG F-2488



Texas Department of Transportation
 © 2022 TXDOT

STORM SEWER AND HYDRAULIC CALCULATIONS


DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
CHECK MI	STATE	DISTRICT	COUNTY
MI	TEXAS	ATL	HARRISON
CHECK MFM	CONTROL	SECTION	JOB
MFM	0919	03	064

SHEET 1 OF 1
46

FILES




- LEGEND**
- EXISTING INLET DRAINAGE AREA
 - PROPOSED INLET DRAINAGE AREA
 - ~ FLOW DIRECTION
 - (X/XX/XX) DRAINAGE AREA NUMBER
DRAINAGE AREA SIZE, A (ACRES)
DRAINAGE AREA DISCHARGE, Q (cfs)
 - EXISTING STORM SEWER
 - PROPOSED STORM SEWER
 - PROPOSED INLET




- DRAINAGE DESIGN CRITERIA**
- RATIONAL METHOD:
 $Q(cfs) = C \times I (in/hr) \times A (acres)$
 - DESIGN FREQUENCY = 5-YEAR
 - | SURFACE TYPE | RUNOFF COEF, C |
|--------------|----------------|
| Grass | 0.40 |
| Asphalt | 0.85 |

- NOTES**
- DRAINAGE AREA BOUNDARIES ARE BASED ON EXISTING CONTOUR MAPS OBTAINED FROM THE CITY OF HALLSVILLE AND FIELD VERIFICATION AS PERFORMED BY EJES, INC.



1/25/2022



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801



EJES INCORPORATED
12801 N. CENTRAL EXPY.
STE. 700
DALLAS, TEXAS 75243
TEL: 214-343-1210 / FAX: 214-343-3885
FIRM REG F-2488




EXISTING DRAINAGE AREA MAP

SHEET 1 OF 1

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
CHECK MI	STATE	DISTRICT	COUNTY
CHECK MFM	TEXAS	ATL	HARRISON
	CONTROL	SECTION	JOB
	0919	03	064
			SHEET NO. 47




- LEGEND**
- EXISTING INLET DRAINAGE AREA
 - PROPOSED INLET DRAINAGE AREA
 - ~ FLOW DIRECTION
 - (X/XX/XX) DRAINAGE AREA NUMBER
DRAINAGE AREA SIZE, A (ACRES)
DRAINAGE AREA DISCHARGE, Q (cfs)
 - EXISTING STORM SEWER
 - PROPOSED STORM SEWER
 - PROPOSED INLET




- DRAINAGE DESIGN CRITERIA**
- RATIONAL METHOD:
 $Q(cfs) = C \times I (in/hr) \times A (acres)$
 - DESIGN FREQUENCY = 5-YEAR
 - | SURFACE TYPE | RUNOFF COEF, C |
|--------------|----------------|
| Grass | 0.40 |
| Asphalt | 0.85 |

- NOTES**
- DRAINAGE AREA BOUNDARIES ARE BASED ON EXISTING CONTOUR MAPS OBTAINED FROM THE CITY OF HALLSVILLE AND FIELD VERIFICATION AS PERFORMED BY EJES, INC.



1/25/2022



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801

EJES INCORPORATED
12801 N. CENTRAL EXPY.
STE. 700
DALLAS, TEXAS 75243
TEL: 214-343-1210 / FAX: 214-343-3885
FIRM REG F-2488


Texas Department of Transportation
©2022 TxDOT

PROPOSED DRAINAGE AREA MAP

SHEET 1 OF 1

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
CHECK	STATE	DISTRICT	COUNTY
MII	TEXAS	ATL	HARRISON
CHECK	CONTROL	SECTION	JOB
MFM	0919	03	064

SHEET NO. 48





LEGEND

- PROPOSED CONC RIPRAP
- PROPOSED DITCH FL
- DROP INLET
- EXISTING STORM SEWER

CALL BEFORE YOU DIG!
 TEXAS ONE CALL PARTICIPANTS REQUEST
 48 HOURS NOTICE BEFORE YOU DIG, DRILL,
 OR BLAST - STOP CALL
 Texas One Call System
 1-800-DIG-TESS

NOTES:

1. VERIFY ALL EXISTING UTILITIES BEFORE BEGINNING ANY TYPE OF WORK.
2. SEE ROADWAY DETAILS SHEET FOR CURB RADIUS AND ADDITIONAL INFORMATION.
3. ALL PIPES ARE CLASS III, UNLESS OTHERWISE NOTED.
4. VERIFY ALL PROPOSED INVERT ELEVATIONS, PIPE DIAMETERS AND FINISHED GRADE ELEVATIONS BEFORE INSTALLING INLET AND JUNCTION BOX.
5. THE HORIZONTAL LOCATION OF THE CURB INLET AS SHOWN IN PLANS REFERS TO THE CONTROL POINT AT FACE OF CURB AT MIDPOINT OF INLET CONTROL ELEVATIONS IS AT TOP OF CURB.
6. THE ITEM "GRADE TO DRAIN" IS CONSIDERED SUBSIDIARY TO VARIOUS ITEMS AND WILL NOT BE PAID FOR SEPARATELY.
7. THE INSTALLATION, MOVING & REMOVAL OF CONCRETE TRAFFIC BARRIERS INCLUDING TEMP. PAVING ARE SUBSIDIARY TO PIPE INSTALLATION PAY ITEM.
8. FOR DITCH SECTIONS, SEE CROSS SECTIONS SHEETS.



NO.	DATE	REVISION	BY


GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801


EJES
 INCORPORATED
 12801 N. CENTRAL EXPY.
 STE. 700
 DALLAS, TEXAS 75243
 TEL: 214-343-1210 / FAX: 214-343-3885
 FIRM REG F-2488

Texas Department of Transportation
 ©2022 TxDOT

PROPOSED STORM DRAIN
BEGIN PROJECT TO STA 19-50.00
 SHEET 1 OF 3

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
CHECK MI	STATE	DISTRICT	COUNTY
MF	TEXAS	ATL	HARRISON
	CONTROL	SECTION	JOB
	0919	03	064
			SHEET NO.
			49






LEGEND

- PROPOSED CONC RIPRAP
- PROPOSED DITCH FL
- DROP INLET
- EXISTING STORM SEWER

CALL BEFORE YOU DIG!
 TEXAS ONE CALL PARTICIPANTS REQUEST
 48 HOURS NOTICE BEFORE YOU DIG, DRILL,
 OR BLAST - STOP CALL
 Texas One Call System
 1-800-DIG-TESS

- NOTES:**
1. VERIFY ALL EXISTING UTILITIES BEFORE BEGINNING ANY TYPE OF WORK.
 2. SEE ROADWAY DETAILS SHEET FOR CURB RADIUS AND ADDITIONAL INFORMATION.
 3. ALL PIPES ARE CLASS III, UNLESS OTHERWISE NOTED.
 4. VERIFY ALL PROPOSED INVERT ELEVATIONS, PIPE DIAMETERS AND FINISHED GRADE ELEVATIONS BEFORE INSTALLING INLET AND JUNCTION BOX.
 5. THE HORIZONTAL LOCATION OF THE CURB INLET AS SHOWN IN PLANS REFERS TO THE CONTROL POINT AT FACE OF CURB AT MIDPOINT OF INLET CONTROL ELEVATIONS IS AT TOP OF CURB.
 6. THE ITEM "GRADE TO DRAIN" IS CONSIDERED SUBSIDIARY TO VARIOUS ITEMS AND WILL NOT BE PAID FOR SEPARATELY.
 7. THE INSTALLATION, MOVING & REMOVAL OF CONCRETE TRAFFIC BARRIERS INCLUDING TEMP. PAVING ARE SUBSIDIARY TO PIPE INSTALLATION PAY ITEM.
 8. FOR DITCH SECTIONS, SEE CROSS SECTIONS SHEETS.



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801

EJES
 INCORPORATED
 12801 N. CENTRAL EXPY.
 STE. 700
 DALLAS, TEXAS 75243
 TEL: 214-343-1210 / FAX: 214-343-3885
 FIRM REG F-2488


Texas Department of Transportation
 ©2022 TxDOT

PROPOSED STORM DRAIN
STA 19-50.00 TO STA 24-30.00

SHEET 2 OF 3

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
CHECK MII	TEXAS	ATL	HARRISON
CHECK MFM	CONTROL	SECTION	JOB
	0919	03	064

50





LEGEND



- PROPOSED CONC RIPRAP
- PROPOSED DITCH FL
- DROP INLET
- EXISTING STORM SEWER

CALL BEFORE YOU DIG!
 TEXAS ONE CALL PARTICIPANTS REQUEST
 48 HOURS NOTICE BEFORE YOU DIG, DRILL,
 OR BLAST - STOP CALL

 1-800-DIG-TESS

NOTES:

1. VERIFY ALL EXISTING UTILITIES BEFORE BEGINNING ANY TYPE OF WORK.
2. SEE ROADWAY DETAILS SHEET FOR CURB RADIUS AND ADDITIONAL INFORMATION.
3. ALL PIPES ARE CLASS III, UNLESS OTHERWISE NOTED.
4. VERIFY ALL PROPOSED INVERT ELEVATIONS, PIPE DIAMETERS AND FINISHED GRADE ELEVATIONS BEFORE INSTALLING INLET AND JUNCTION BOX.
5. THE HORIZONTAL LOCATION OF THE CURB INLET AS SHOWN IN PLANS REFERS TO THE CONTROL POINT AT FACE OF CURB AT MIDPOINT OF INLET CONTROL ELEVATIONS IS AT TOP OF CURB.
6. THE ITEM "GRADE TO DRAIN" IS CONSIDERED SUBSIDIARY TO VARIOUS ITEMS AND WILL NOT BE PAID FOR SEPARATELY.
7. THE INSTALLATION, MOVING & REMOVAL OF CONCRETE TRAFFIC BARRIERS INCLUDING TEMP. PAVING ARE SUBSIDIARY TO PIPE INSTALLATION PAY ITEM.
8. FOR DITCH SECTIONS, SEE CROSS SECTIONS SHEETS.



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801


EJES
 INCORPORATED
 12801 N. CENTRAL EXPY.
 STE. 700
 DALLAS, TEXAS 75243
 TEL: 214-343-1210 / FAX: 214-343-3885
 FIRM REG F-2488

Texas Department of Transportation
 ©2022 TxDOT


PROPOSED STORM DRAIN
STA 24+30.00 TO END PROJECT
 SHEET 3 OF 3

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
CHECK MII	TEXAS	ATL	HARRISON
CHECK MFM	CONTROL	SECTION	JOB
	0919	03	064
			SHEET NO. 51







NOTES:
 1. SEALING EXISTING INLETS SHALL BE PAID FOR DIRECTLY, BUT WILL BE CONSIDERED SUBSIDIARY TO ITEM 465.




L4 = CI-4 TO CI-5 PROFILE
 STA 16+44.55 - STA 17+03.00




L5 = CI-5 TO OUTFALL
 L2 = DI-2 TO CI-2
 STA 17+03.00



L2A PROFILE
 STA 20+30.36 - STA 20+80.16



L6 = CI-6 TO DI-3 PROFILE
 STA 20+18.86



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
 11551 FOREST CENTRAL DRIVE
 SUITE 220
 DALLAS, TX 75243
 F-12801

EJES
 INCORPORATED
 12801 N. CENTRAL EXPY.
 STE. 700
 DALLAS, TEXAS 75243
 TEL: 214-343-1210 / FAX: 214-343-3885
 FIRM REG F-2488

Texas Department of Transportation
 ©2022 TXDOT

STORM DRAIN PROFILE

SHEET 1 OF 1

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
CHECK MII	TEXAS	ATL	HARRISON
CHECK MFM	CONTROL	SECTION	JOB
	0919	03	064


52




HORIZ & VERTICAL SCALE IN FEET

NOTES:
1. OFFSET DISTANCES ARE FROM THE BACK OF CURB.


STA 17+50.00




STA 21+15.90




STA 17+03.00 - DITCH DROP INLET




STA 20+98.52




STA 20+13.29




STA 19+23.16




STA 16+44.55 - SAG INLET





STA 18+63.26



STA 16+10.00



STA 18+00.00



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801

EJES INCORPORATED
12801 N. CENTRAL EXPY.
STE. 700
DALLAS, TEXAS 75243
TEL: 214-343-1210 / FAX: 214-343-3885
FIRM REG F-2488

Texas Department of Transportation
©2022 TXDOT

DITCH CROSS SECTIONS

SHEET 1 OF 2

DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
MI	TEXAS	ATL	HARRISON
CHECK	CONTROL	SECTION	JOB
MFM	0919	03	064

53


FILES & SOLDES




HORIZ & VERTICAL
SCALE IN FEET

NOTES:
1. OFFSET DISTANCES ARE
FROM THE BACK OF CURB.


STA 25+44.51




STA 25+16.35




STA 24+45.61




STA 23+18.86




STA 22+50.00




STA 22+00.00





STA 27+46.68



STA 27+35.85



STA 27+09.83



NO.	DATE	REVISION	BY

GLOBAL CIVIL SOLUTIONS, LLC
11551 FOREST CENTRAL DRIVE
SUITE 220
DALLAS, TX 75243
F-12801

EJES 12801 N. CENTRAL EXPY. FIRM REG
STE. 700 DALLAS, TEXAS 75243 F-2488
INCORPORATED TEL: 214-343-1210 / FAX: 214-343-3885

Texas Department of Transportation
©2022 TxDOT

DITCH CROSS SECTIONS

SHEET 2 OF 2






DESIGN BY	FED. RD. DIV. NO.	FEDERAL AID PROJECT NO.	HIGHWAY NO.
MB	6		CIDER LN
GRAPHICS	STATE	DISTRICT	COUNTY
MB	TEXAS	ATL	HARRISON
CHECK	CONTROL	SECTION	JOB
MI	0919	03	064
CHECK			
MFM			

54

FILES & DATES

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:



- FABRICATION NOTES:**
1. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
 2. Provide Grade 60 reinforcing steel or equivalent area of WWR.
 3. Provide typical clear cover of 1 1/2" to reinforcing steel at interior or exterior walls.
 4. Walls or slabs with a thickness of 8" or greater require shrinkage and temperature reinforcing steel. Provide steel area = 0.11 in²/ft each way.
 5. No substitution is allowed for vertical and horizontal #4 bars in corners.
 6. Manufacture base and risers to nearest 3" increment.
 7. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is 3/4".
 8. Provide lifting devices in conformance with Manufacturer's recommendations.
 9. See sheet PDD for sizes, dimensions, and reinforcing steel not shown.

- INSTALLATION NOTES:**
1. If required elsewhere. Inverts (benching) to be provided by Contractor. Concrete or mortar used for invert is subsidiary to specified inlet or manhole.
 2. Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or 1/2 the joint depth, whichever is greater.
 3. Do not grout rubber gasket joints without Manufacturer's recommendation.
 4. For rigid pipe, cut hole in thin wall panel (KO) 4" Max, 2" Min larger than pipe OD.
 5. For flexible pipe, consult boot/seal Manufacturer's specification for placement tolerance and hole size. Center pipe in hole and install boot/seal per Manufacturer's specification.


- GENERAL NOTES:**
1. Precast Base consists of base slab, base unit, risers (as required), reducing slab (as required), and reduced risers (as required). See sheet PDD for sizes.
 2. Designed according to ASTM C913.
 3. Payment for precast base is subsidiary to the specified inlet, per Item 465, "Junction Boxes, Manholes, and Inlets."

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING				Bridge Division Standard	
PRECAST BASE					
PB					
FILE: presto01-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0919	03	064	CIDER LN	
	DIST	COUNTY	SHEET NO.		
	ATL	HARRISON	55		


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:




PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF PLAN




PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF PLAN




PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF ELEVATION



PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF ELEVATION



TYPICAL PARTIAL ELEVATION OF PRECAST SAFETY END TREATMENTS

Showing square PSET for parallel drainage, cross drainage shown similar.

① Completely fill the void between the precast structure and the connecting pipe or box with cementitious grouts and mortars in accordance with DMS-4675 "Cementitious Grouts and Mortars for Miscellaneous Application".

CONSTRUCTION NOTES:

- Do not grout rubber gasket joints without Manufacturer's recommendations.
- Do not use bricks, masonry blocks, native stone, or similar materials in conjunction with grouted connections when filling void spaces around pipes or box culverts.

MATERIAL NOTES:

Provide grouted connections in accordance with DMS-4675 "Cementitious Grouts and Mortars for Miscellaneous Application".

GENERAL NOTES:

- See applicable standards for notes and details not shown:
 - Precast Base (PB)
 - Precast Junction Box (PJB)
 - Precast Round Manhole (PRM)
 - Precast Safety End Treatments C/D Square (PSET-SC)
 - Precast Safety End Treatments P/D Square (PSET-SP)
- Provide Concrete Box Culverts in accordance with Item 462 "Concrete Box Culverts and Drains".
- Provide Reinforced Concrete Pipe (RCP) in accordance with Item 464 "Reinforced Concrete Pipe".
- Provide Thermoplastic Pipe (TP) in accordance with Special Specification Thermoplastic Pipe.
- Payment for grouted connections is considered subsidiary to other bid items.




PIPE AND BOX GROUTED CONNECTIONS FOR PRECAST STRUCTURES

PBGC


FILE: pbgcsd1-20.dgn	DN: TxDOT	CK: TAR	DW: JTR	CK: TAR
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
DIST	COUNTY		SHEET NO.	
ATL	HARRISON		56	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE:
FILE:




FRONT VIEW
(SHOWING LEFT AND RIGHT EXTENSIONS)



RIGHT VIEW




REAR VIEW
(EXTENSIONS NOT SHOWN)




LEFT VIEW

① Matches inside face of wall of precast base or riser below inlet.



PLAN VIEW
(SHOWING LEFT AND RIGHT EXTENSIONS)



DETAIL "A"

HS20 LOADING SHEET 1 OF 2




**PRECAST CURB INLET
OUTSIDE ROADWAY**

PCO

FILE: presto03-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
DIST	COUNTY		SHEET NO.	
ATL	HARRISON		57	


DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:




LID SECTION A-A


LID SECTION B-B



LID PLAN VIEW
(SHOWING LEFT AND RIGHT EXTENSIONS)



THROAT ELEVATION VIEW
(SHOWING LEFT AND RIGHT EXTENSIONS)



THROAT PLAN VIEW
(SHOWING LEFT AND RIGHT EXTENSIONS)

FABRICATION NOTES:

1. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
2. Provide Grade 60 reinforcing steel or equivalent area of WWR.
3. Extensions may be right, left, both or none. Provide extensions as specified elsewhere in the plans.
4. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is ¾". Lid may employ a butt joint with dowels at the Contractor's option.
5. Provide lifting devices in conformance with Manufacturer's recommendations.
6. Provide cast iron solid cover, unless noted otherwise elsewhere in the plans.
7. Chamfer vertical edges of inlet lid ¾" as shown in Front View, sheet 1.

INSTALLATION NOTES:

1. Inlet throat and lid are not intended for direct traffic. Do not place in roadway.
2. Seal tongue and groove joints and butt joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or ½ the joint depth, whichever is greater.
3. Do not grout rubber gasket joints without Manufacturer's recommendation.

GENERAL NOTES:

1. Designed according to ASTM C913.
2. Open area of main throat = 360 sq in. Open area of one extension throat = 324 sq in.
3. Payment for inlet is per Item 465, "Junction Boxes, Manholes, and Inlets" by type, size, and extension placement. Extensions are subsidiary to inlet.

Cover dimensions are clear dimensions, unless noted otherwise.

SIZE (Y)	N	MH DIA *	Ra
3'	9"	18"	(4) #5 Additional
4'	16"	32"	(4) #5 Additional
5'	16"	32"	(4) #5 Additional
6'	16"	32"	(4) #5 Additional


* Nominal ring and cover size.

HS20 LOADING SHEET 2 OF 2

		Bridge Division Standard	
PRECAST CURB INLET OUTSIDE ROADWAY			
PCO			
FILE: presto03-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
©TxDOT February 2020	CONT	SECT	HIGHWAY
REVISIONS	0919	03	064 CIDER LN
DIST	COUNTY	SHEET NO.	
ATL	HARRISON	58	


DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:




PLAN

(Showing bell end connection.)




LONGITUDINAL ELEVATION

(Showing bell end connection.)




INSTALLATION DETAIL FOR SAFETY PIPE RUNNERS

(If required)




OPTION A




OPTION B

END DETAILS FOR INSTALLATION OF SAFETY PIPE RUNNERS

(If required)




MULTIPLE PIPE INSTALLATION




OPTION WITH SQUARE BOTTOM

SECTION A-A



OPTION WITH INVERT BOTTOM



OPTIONAL JOINT FOR RCP

(Showing joint between RCP and precast safety end treatment.)

REQUIREMENTS FOR CULVERT PIPES AND SAFETY PIPE RUNNERS

Pipe I.D.	RCP Wall "B" Thickness	TP Wall Thickness	"D"	Slope	Min Length	Pipe Runners Required		Required Pipe Runner Size		
						Single Pipe	Multiple Pipe	Nominal Dia.	O.D.	I.D.
12"	2"	1.15"	17.00"	6:1	4' - 9"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
15"	2 1/4"	1.30"	20.50"	6:1	6' - 5"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
18"	2 1/2"	1.60"	24.00"	6:1	8' - 0"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
24"	3"	1.95"	31.00"	6:1	11' - 3"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
30"	3 1/2"	2.65"	38.50"	6:1	14' - 8"	No	Yes	4" STD	4.500"	4.026"
36"	4"	2.75"	45.50"	6:1	17' - 11"	Yes	Yes	4" STD	4.500"	4.026"
42"	4 1/2"	2.7"	52.50"	6:1	21' - 2"	Yes	Yes	4" STD	4.500"	4.026"

- Dimension "D" is based on reinforced concrete pipe (RCP) meeting the requirements of ASTM C-76, Class III, (RCP Wall "B" thickness). Adjust "D" for any other wall thickness used. For thermoplastic pipe (TP) take into account the annular space requirements for grouted connections.
- Slope as shown elsewhere in the plans. Slope of 6:1 or flatter is required for vehicle safety.
- Toewall to be used only when dimension is shown elsewhere in the plans.
- Fill the top 4" of void between precast end treatments with concrete riprap. Concrete riprap is considered subsidiary to the Item 467, "Safety End Treatment".
- Adjust clear distance between pipes to provide for the minimum distance between safety end treatments.
- Provide cement stabilized bedding and backfill in accordance with the Item 400, "Excavation and Backfill for Structures". Bedding and backfill is considered subsidiary to the Item 467, "Safety End Treatment". When concrete riprap is specified around the safety end treatment, backfill as directed by Engineer.
- Thermoplastic pipe wall thickness may vary. Adjust accordingly. Thermoplastic pipe requires the safety end treatments to have a bell end for grouted connections.

GENERAL NOTES:

Precast safety end treatment for reinforced concrete pipe (RCP), and thermoplastic pipe (TP) may be used for TYPE II end treatment as specified in Item "Safety End Treatment".
 When precast safety end treatment is used as a Contractor's alternate to mitered RCP, riprap will not be required unless noted otherwise on the plans.
 Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.
 Manufacture this product in accordance with Item 467, "Safety End Treatment" except as noted below:
 A. Provide minimum reinforcing of #4 at 6" (Grade 40) or #4 at 9" (Grade 60) each way or 6"x6" - D12 x D12 or 5"x5" - D10 x D10 welded wire reinforcement (WWR).
 B. For precast (steel formed) sections, provide Class "C" concrete (f'c = 3,600 psi).
 At the option and expense of the Contractor the next larger size of safety end treatment may be furnished; as long as the "D" dimension cast is that of the required size of pipe.
 Pipe runners are designed for a traversing load of 10,000 Lbs at yield as recommended by Research Report 280-2F, "Safety Treatment of Roadside Parallel-Drainage Structures", Texas Transportation Institute, March 1981.
 Provide pipe runners meeting the requirements of ASTM A53 (Type E or S, Grade B), ASTM A500 (Grade B), or API 5LX52.
 Galvanize all steel components except reinforcing steel after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.
 Connect RCP using the Optional Joint for RCP detail shown or in accordance with Item 464, "Reinforced Concrete Pipe". Connect TP by grouting. See Pipe and Box Grouted Connections (PBGC) standard for grouted connections with TP and precast safety end treatment.

Texas Department of Transportation Bridge Division Standard


PRECAST SAFETY END TREATMENT TYPE II ~ PARALLEL DRAINAGE

PSET-SP















FILE: psetspss-21.dgn	DN: RLW	CK: KLR	DW: JTR	CK: GAF
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
12-21: Added 42" TP	DIST	COUNTY	SHEET NO.	
	ATL	HARRISON	59	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



ORIENT TAPER TO CORRESPOND WITH ROADWAY CROSS-SLOPE.



① Matches inside face of wall of precast base or riser below inlet.

HL93 LOADING SHEET 1 OF 2



PRECAST SLAB LID

PSL

FILE: presto05-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
DIST	COUNTY		SHEET NO.	
ATL	HARRISON		60	


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

Style	Size (X x Y)	W ^②	A x B (nominal)	Short Span Reinf Steel Area	Long Span Reinf Steel Area
SL	3'x3'	6"	n/a	0.37 in ² /ft	0.37 in ² /ft
RH,RC,RG,SH,S1,FG	3'x3'	6"	3'x3' or 32" Dia	0.37 in ² /ft	0.37 in ² /ft
SFG	3'x3'	6"	3'x3'	0.32 in ² /ft	0.32 in ² /ft
SL	4'x4'	6"	n/a	0.34 in ² /ft	0.34 in ² /ft
RH,RC,RG,SH,S1,FG	4'x4'	6"	3'x3' or 32" Dia	0.41 in ² /ft	0.41 in ² /ft
SH,S1,FG	4'x4'	6"	4'x4'	0.41 in ² /ft	0.41 in ² /ft
SFG	4'x4'	6"	4'x4'	0.32 in ² /ft	0.32 in ² /ft
SL	3'x5'	6"	n/a	0.39 in ² /ft	0.39 in ² /ft
RH,RC,RG,SH,S1,FG	3'x5'	6"	3'x3' or 32" Dia	0.48 in ² /ft	0.48 in ² /ft
SH,S1,FG	3'x5'	6"	3'x5'	0.48 in ² /ft	0.48 in ² /ft
SFG	3'x5'	6"	3'x5'	0.32 in ² /ft	0.32 in ² /ft
SL	4'x5'	6"	n/a	0.42 in ² /ft	0.42 in ² /ft
RH,RC,RG,SH,S1,FG	4'x5'	6"	3'x3' or 32" Dia	0.42 in ² /ft	0.42 in ² /ft
SH,S1,FG	4'x5'	6"	4'x4'	0.63 in ² /ft	0.63 in ² /ft
SH,S1,FG	4'x5'	6"	3'x5'	0.66 in ² /ft	0.66 in ² /ft
SL	5'x5'	6"	n/a	0.36 in ² /ft	0.36 in ² /ft
RH,RC,RG,SH,S1,FG	5'x5'	6"	3'x3' or 32" Dia	0.43 in ² /ft	0.43 in ² /ft
SH,S1,FG	5'x5'	6"	4'x4'	0.63 in ² /ft	0.63 in ² /ft
SH,S1,FG	5'x5'	6"	3'x5'	0.63 in ² /ft	0.63 in ² /ft
SL	5'x6'	6"/8"	n/a	0.48 in ² /ft	0.48 in ² /ft
RH,RC,RG,SH,S1,FG	5'x6'	6"/8"	3'x3' or 32" Dia	0.48 in ² /ft	0.48 in ² /ft
SH,S1,FG	5'x6'	6"/8"	4'x4'	0.60 in ² /ft	0.60 in ² /ft
SH,S1,FG	5'x6'	6"/8"	3'x5'	0.60 in ² /ft	0.60 in ² /ft
SL	6'x6'	6"/8"	n/a	0.43 in ² /ft	0.43 in ² /ft
RH,RC,RG,SH,S1,FG	6'x6'	6"/8"	3'x3' or 32" Dia	0.56 in ² /ft	0.56 in ² /ft
SH,S1,FG	6'x6'	6"/8"	4'x4'	0.56 in ² /ft	0.56 in ² /ft
SH,S1,FG	6'x6'	6"/8"	3'x5'	0.59 in ² /ft	0.59 in ² /ft
SL	8'x8'	8"/10"	n/a	0.45 in ² /ft	0.45 in ² /ft
RH,RC,RG,SH,S1,FG	8'x8'	8"/10"	3'x3' or 32" Dia	0.45 in ² /ft	0.45 in ² /ft
SH,S1,FG	8'x8'	8"/10"	4'x4'	0.45 in ² /ft	0.45 in ² /ft
SH,S1,FG	8'x8'	8"/10"	3'x5'	0.45 in ² /ft	0.45 in ² /ft

^② See sheet PDD for corresponding wall thickness (W) of base unit or riser.

Construct cast-in-place reinforced concrete apron, when shown elsewhere in plans. Use Class "A" concrete. Apron is subsidiary to PSL. Apron is 1'-6" Min width around precast zone drain.



DETAIL "A"

(Reinforcing not shown for clarity)
When an apron is to be cast around PSL, use detail above to create an apron ledge on all 4 sides.

FABRICATION NOTES:

1. Locate penetration (Style 'RH'), ring and cover (Style 'RC'), ring and grate (Style 'RG'), and frame and grate (Style 'FG') in a corner. Only one penetration is allowed per slab lid.
2. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
3. Provide Grade 60 reinforcing steel or equivalent area of WWR.
4. Provide clear cover of 3/4" to reinforcing from lower outside shoulder of slab for structural reinforcement, and 2" from top of slab for shrinkage and temperature reinforcement. Place short span reinforcing closest to surface.
5. Slabs with a thickness of 8" or greater require shrinkage and temperature reinforcing. Provide steel area = 0.11 in²/ft each way.
6. No substitution is allowed for diagonal #4 bars around openings.
7. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is 3/4".
8. Provide lifting devices in conformance with Manufacturer's recommendations.

INSTALLATION NOTES:

1. Precast slab lids are intended for direct traffic and may be placed in roadway.
2. Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or 1/2 the joint depth, whichever is greater.
3. Do not grout rubber gasket joints without Manufacturer's recommendation.
4. Initial installation of grade adjustment rings for Styles 'RH' and 'SH' is limited to 1'-0" Max as shown.
5. Grade adjustment rings for Styles 'RH' and 'SH' may be increased to 2'-0" Max when future construction affects final grade of structure. Make adjustments greater than 2'-0" with additional risers. Adjustments can be made up to Max depth shown on sheet PDD. Structure must be evaluated if Max depth will be exceeded.
6. Orient long dimension of grate slots perpendicular to traffic, unless noted otherwise on plans.

GENERAL NOTES:

1. Designed according to ASTM C913.
2. Payment for lid is per Item 465, "Junction Boxes, Manholes, and Inlets" by type, style, size, and opening size (when applicable).

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING SHEET 2 OF 2




PRECAST SLAB LID

PSL

FILE: presto05-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
DIST	COUNTY		SHEET NO.	
ATL	HARRISON		61	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: FILE:




NOTE: All cross pipes, calculations, and dimensions are based on the pipe culverts mitered as shown in this detail. Alternate styles of mitered ends will require that appropriate adjustments be made to the values presented on this standard.

SIDE ELEVATION OF TYPICAL PIPE CULVERT MITER

(Showing corrugated metal pipe (CMP) culvert. Details at reinforced concrete pipe (RCP) culvert are similar.)




ISOMETRIC VIEW OF TYPICAL INSTALLATION




SIDE ELEVATION OF CAST-IN-PLACE CONCRETE

(Showing reinforced concrete pipe (RCP) culvert. Details at corrugated metal pipe (CMP) culvert are similar.)




PIPE WITH ANCHOR BARS




SECTION C-C

CROSS PIPE DETAILS


Limits of riprap (to be included with SET for payment)



SHOWING TYPICAL PIPE CULVERT AND RIPRAP




SHOWING CROSS PIPE WITH ANCHOR BAR




SHOWING CROSS PIPE WITH BOLTED ANCHOR

SECTION A-A



DETAIL "A"

(Showing invert with corrugated metal pipe (CMP) culvert. Reinforced concrete pipe (RCP) culvert details are similar. Cross pipes not shown for clarity.)



SECTION B-B

(Cross pipes not shown for clarity.)

CROSS PIPE LENGTHS, REQUIRED PIPE SIZES, AND RIPRAP QUANTITIES

Nominal Culvert I.D.	Conc Riprap (CY) (6)	Pipe Culvert Spa ~ G	Single Barrel ~ Q1	Multi-Barrel ~ Q1	Q2	Conditions for Use of Cross Pipes	Cross Pipe Sizes
12"	0.6	0' - 9"	N/A	2' - 1"	1' - 9"	3 or more pipe culverts	3" Std (3.500" O.D.)
15"	0.7	0' - 11"	N/A	2' - 5"	2' - 2"		
18"	0.8	1' - 2"	N/A	2' - 10"	2' - 8"		
21"	0.9	1' - 4"	N/A	3' - 2"	3' - 1"		
24"	0.9	1' - 7"	N/A	3' - 6"	3' - 7"	3 or more pipe culverts	3 1/2" Std (4.000" O.D.)
27"	1.0	1' - 8"	N/A	3' - 10"	3' - 11"		
30"	1.1	1' - 10"	N/A	4' - 2"	4' - 4"		
33"	1.2	1' - 11"	4' - 2"	4' - 5"	4' - 8"	All pipe culverts	4" Std (4.500" O.D.)
36"	1.3	2' - 1"	4' - 5"	4' - 9"	5' - 1"	All pipe culverts	
42"	1.5	2' - 4"	4' - 11"	5' - 5"	5' - 10"	All pipe culverts	5" Std (5.563" O.D.)
48"	1.7	2' - 7"	5' - 5"	6' - 0"	6' - 7"		
54"	2.0	3' - 0"	5' - 11"	6' - 9"	7' - 6"		
60"	2.2	3' - 3"	6' - 5"	7' - 4"	8' - 3"		
66"	2.4	3' - 3"	6' - 11"	7' - 10"	8' - 9"	All pipe culverts	5" Std (5.563" O.D.)
72"	2.7	3' - 4"	7' - 5"	8' - 5"	9' - 4"		

- The proper installation of the first cross pipe is critical for vehicle safety. Place the top of the first cross pipe no more than 6" above the flow line.
- Provide cross pipes, except the first bottom pipe, of the size shown in the table. Provide a 3 1/2" standard pipe (4" O.D.) for the first bottom pipe.
- Install the third cross pipe from the bottom of the culvert using a bolted connection. Ensure that riprap concrete does not flow into the cross pipe so as to permit disassembly of the bolted connection to allow cleanout access. At the Contractor's option, install all other cross pipes using the bolted connection details.
- Match cross slope as shown elsewhere in the plans. Cross slope of 6:1 or flatter is required for vehicle safety.
- Riprap placed beyond the limits shown will be paid for as concrete riprap in accordance with Item 432, "Riprap".
- Quantities shown are for one end of one reinforced concrete pipe (RCP) culvert. For multiple pipe culverts or for corrugated metal pipe (CMP) culverts, quantities will need to be adjusted. Riprap quantities are for contractor's information only.

MATERIAL NOTES:

Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise. Provide cross pipes that meet the requirements of ASTM A53 (Type E or S, Gr B), ASTM A500 (Gr B), or API 5LX52. Provide ASTM A307 bolts and nuts. Galvanize all steel components, except concrete reinforcing, after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.

GENERAL NOTES:

Cross pipes are designed for a traversing load of 10,000 pounds at yield as recommended by Research Report 280-2F, "Safety Treatment of Roadside Parallel-Drainage Structures", Texas Transportation Institute, March 1981. Safety end treatments (SET) shown herein are intended for use in those installations where out of control vehicles are likely to traverse the openings approximately perpendicular to the cross pipes. Construct concrete riprap and all necessary inverts in accordance with the requirements of Item 432, "Riprap". Payment for riprap and toewall is included in the Price Bid for each Safety End Treatment.

Texas Department of Transportation Bridge Division Standard

SAFETY END TREATMENT FOR 12" DIA TO 72" DIA PIPE CULVERTS TYPE II ~ PARALLEL DRAINAGE

SETP-PD

FILE: setppdse-20.dgn	DN: GAF	CK: CAT	DW: JRP	CK: GAF
REVISIONS	CONT	SECT	JOB	HIGHWAY
	0919	03	064	CIDER LN
	DIST	COUNTY	SHEET NO.	
	ATL	HARRISON	62	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

1.
2.
 No Action Required Required Action

Action No.

- Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000
- Comply with the SW3P and revise when necessary to control pollution or required by the Engineer.
- Post Construction Site Notice (CSN) with SW3P information on or near the site, accessible to the public and TCEQ, EPA or other inspectors.
- When Contractor project specific locations (PSL's) increase disturbed soil area to 5 acres or more, submit NOI to TCEQ and the Engineer.

II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required
 Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
 Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
 Individual 404 Permit Required
 Other Nationwide Permit Required: NWP# _____

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

1.
2.
3.
4.

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

Best Management Practices:

Erosion	Sedimentation	Post-Construction TSS
<input type="checkbox"/> Temporary Vegetation	<input checked="" type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input checked="" type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	<input type="checkbox"/> Grassy Swales

III. CULTURAL RESOURCES

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

- No Action Required Required Action

Action No.

1.
2.
3.
4.

IV. VEGETATION RESOURCES

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

- No Action Required Required Action

Action No.

1.
2.
3.
4.

V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.

- No Action Required Required Action

Action No.

1.
2.
3.
4.

If any of the listed species are observed, cease work in the immediate area, do not disturb species or habitat and contact the Engineer immediately. The work may not remove active nests from bridges and other structures during nesting season of the birds associated with the nests. If caves or sinkholes are discovered, cease work in the immediate area, and contact the Engineer immediately.

LIST OF ABBREVIATIONS

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SW3P: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NWP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used.

Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act.

Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- * Dead or distressed vegetation (not identified as normal)
- * Trash piles, drums, canister, barrels, etc.
- * Undesirable smells or odors
- * Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

- Yes No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

- Yes No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

- No Action Required Required Action

Action No.

1.
2.
3.


VII. OTHER ENVIRONMENTAL ISSUES




(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required Required Action

Action No.

1.
2.
3.

 Texas Department of Transportation		Design Division Standard	
ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS EPIC			
FILE: epic.dgn	DN: TxDOT	CK: RG	DW: VP
©TxDOT: February 2015	CONT	SECT	HIGHWAY
12-12-2011 (DS) REVISIONS	0919	03	064
05-07-14 ADDED NOTE SECTION IV. 01-23-2015 SECTION I. CHANGED ITEM 1122 TO ITEM 506, ADDED GRASSY SWALES.	DIST	COUNTY	SHEET NO.
	ATL	HARRISON	63



- CL-CI == EROSION CONTROL LOG AT CURB INLET
- CL-DI == EROSION CONTROL LOG AT DROP INLET

NO.	TYPE	UNIT	QUANTITY	DATE INSTALLED	DATE REMOVED
1	EROSION CONTROL LOG	LF	30		
2	EROSION CONTROL LOG	LF	45		
3	EROSION CONTROL LOG	LF	50		



SWP3 SITE MAP

DESIGN MI	FED. RD. DIV. NO. 6	FEDERAL AID PROJECT NO.		HIGHWAY NO. CIDER LN
GRAPHICS PS	STATE	DISTRICT	COUNTY	SHEET NO.
CHECK MFM	TEXAS	ATL	HARRISON	64
CHECK FS	CONTROL	SECTION	JOB	
	0919	03	064	

DATE: 1/25/2022 10:48:20 AM
 FILE: P:\Jobs\2021003-Pedestrian TxDOT Atlanta\CADD\VIII ENVIRONMENTAL ISSUES\065 - TxDOT STORM WATER POLLUTION PREVENTION PLAN\SWP3.dwg
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this drawing to a digital format.

SITE DESCRIPTION

PROJECT LIMITS: FROM US 80 TO CAL YOUNG RD

PROJECT DESCRIPTION: FOR THE CONSTRUCTION OF PEDESTRIAN INFRASTRUCTURE CONSISTING OF PEDESTRIAN RAMPS & SHARED PATH

MAJOR SOIL DISTURBING ACTIVITIES: VEGETATIVE CLEARING, EXCAVATION AND/OR FILL, GRADING, CONSTRUCTION OF CURB RAMPS, SIDEWALK, AND MISCELLANEOUS PEDESTRIAN ELEMENTS, FINAL SURFACE PREPARATION AND STABILIZATION (GRADING, TOPSOIL, AND SODDING)

TOTAL PROJECT AREA: 2.18 Acres

TOTAL AREA TO BE DISTURBED: 0.65 Acres

EXISTING CONDITION OF SOIL & VEGETATIVE COVER AND % OF EXISTING VEGETATIVE COVER: N/A

NAME OF RECEIVING WATERS: N/A

ANTICIPATED EFFECT OF STORM WATER ON THREATENED AND ENDANGERED SPECIES AND WILDLIFE HABITAT: REFER TO EPIC SHEET

NARRATIVE - SEQUENCE OF CONSTRUCTION (STORM WATER MANAGEMENT) ACTIVITIES:

STORM WATER MANAGEMENT:

DETAILED SITE MAP OR LAYOUT INDICATING THE FOLLOWING: (SEE SWP3 SITE MAP OR LAYOUT)

- LOCATION(S) OF ALL MAJOR STRUCTURAL CONTROLS EITHER PLANNED OR IN PLACE
 - LOCATIONS WHERE TEMPORARY OR PERMANENT STABILIZATION PRACTICES ARE EXPECTED TO BE USED
 - LOCATIONS OF CONCRETE VEHICLE WASHOUT AREAS
 - LOCATIONS OF PORTABLE SANITARY WASTE UNITS
 - LOCATIONS OF TRASH DUMPSTERS
- _____
- _____
- _____
- _____
- _____
- _____
- _____
- _____
- _____
- _____

EROSION AND SEDIMENT CONTROLS

SOIL STABILIZATION PRACTICES:

- PERMANENT PLANTING, SODDING, OR SEEDING
- TEMPORARY SEEDING
- MULCHING
- SOIL RETENTION BLANKET
- BUFFER ZONES
- PRESERVATION OF NATURAL RESOURCES
- SLOPE TEXTURING

OTHER: EROSION CONTROL AND STABILIZATION MEASURES MUST BE INITIATED IMMEDIATELY IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY CEASED AND WILL NOT RESUME FOR A PERIOD EXCEEDING 14 CALENDAR DAYS. STABILIZATION MEASURES THAT PROVIDE A PROTECTIVE COVER MUST BE INITIATED IMMEDIATELY IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE PERMANENTLY CEASED.

STRUCTURAL PRACTICES:

- SILT FENCES
- HAY BALES
- ROCK BERMS
- PAVED FLUMES
- CHANNEL LINERS
- SEDIMENT TRAPS
- FILTER DAMS
- CURBS AND GUTTERS
- STORM SEWERS
- ROCK BEDDING AT CONSTRUCTION EXIT
- TIMBER MATTING AT CONSTRUCTION EXIT
- DIVERSION, INTERCEPTOR, OR PERIMETER DIKES
- DIVERSION, INTERCEPTOR, OR PERIMETER SWALES
- DIVERSION DIKE AND SWALE COMBINATIONS
- STORM INLET SEDIMENT TRAP
- VELOCITY CONTROL DEVICES
- EROSION CONTROL LOGS

OTHER: _____

MAINTENANCE: ALL EROSION AND SEDIMENT CONTROLS WILL BE MAINTAINED IN GOOD WORKING ORDER. IF MAINTENANCE IS NECESSARY, IT WILL BE DONE PRIOR TO THE NEXT RAIN EVENT IF FEASIBLE. IF MAINTENANCE PRIOR TO THE NEXT ANTICIPATED STORM EVENT IS IMPRACTICABLE, THE REASON SHALL BE DOCUMENTED IN THE SWP3 AND MAINTENANCE MUST BE SCHEDULED AND ACCOMPLISHED AS SOON AS PRACTICABLE. EROSION AND SEDIMENT CONTROLS THAT HAVE BEEN INTENTIONALLY DISABLED, RUN-OVER, REMOVED OR OTHERWISE RENDERED INEFFECTIVE MUST BE REPLACED OR CORRECTED IMMEDIATELY UPON DISCOVERY. REFER TO APPLICABLE TPDES GENERAL PERMIT FOR ADDITIONAL INFORMATION.

INSPECTION: ITEM 506 AN INSPECTION WILL BE PERFORMED EVERY 7 CALENDAR DAYS. A MAINTENANCE REPORT WILL BE MADE PER EACH INSPECTION. BASED ON INSPECTION RESULTS, THE CONTROLS SHALL BE REVISED PER THE INSPECTION REPORT.

OFFSITE VEHICLE TRACKING: THE CONTRACTOR SHALL BE REQUIRED, ON A REGULAR BASIS OR AS MAY BE DIRECTED BY THE ENGINEER, TO DAMPEN HAUL ROADS FOR DUST CONTROL, STABILIZE CONSTRUCTION ENTRANCES, REMOVE EXCESS DIRT FROM THE ROADWAY, AND COVER LOADED HAUL TRUCKS WITH TARPULIN.

CONCRETE TRUCK WASHOUT AREAS: THE CONTRACTOR WILL BE REQUIRED TO CONTAIN WASH WATER FROM CONCRETE TRUCKS AS DETAILED IN THE GENERAL PERMIT. SPECIFIC LOCATIONS MAY BE DETERMINED IN THE FIELD BUT MUST BE SHOWN ON THE SWP3 SITE MAP OR LAYOUT PRIOR TO BEGINNING CONSTRUCTION ACTIVITIES.

WASTE MATERIALS

HAZARDOUS WASTE (INCLUDING SPILL REPORTING): AT A MINIMUM, ANY PRODUCTS IN THE FOLLOWING CATEGORIES ARE CONSIDERED TO BE HAZARDOUS: PAINTS, ACIDS FOR CLEANING MASONRY SURFACES, CLEANING SOLVENTS, ASPHALT PRODUCTS, CHEMICAL ADDITIVES FOR SOIL STABILIZATION, CONCRETE CURING COMPOUNDS AND ADDITIVES OR MOTOR OIL. MATERIALS SHALL BE STORED IN ACCORDANCE WITH APPLICABLE REGULATIONS. IN THE EVENT OF A SPILL WHICH MAY BE HAZARDOUS, IMMEDIATELY REPORT SPILL IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.


WASTE MATERIALS: THE BURYING OF CONSTRUCTION WASTE MATERIAL ON SITE WILL NOT BE PERMITTED. DISPOSAL OF WASTE MATERIALS SHALL MEET ALL STATE AND LOCAL SOLID WASTE MANAGEMENT REGULATIONS. WASTE MATERIALS STORED ON SITE SHALL BE COLLECTED IN A METAL DUMPSTER WITH A LOCKING, SECURE COVER AND A DRAIN PLUG IN PLACE.

SANITARY WASTE: ALL SANITARY WASTE WILL BE DISPOSED OF IN ACCORDANCE WITH ALL STATE AND LOCAL REGULATIONS. SPECIFIC LOCATIONS OF PORTABLE UNITS MUST BE SHOWN ON THE SWP3 SITE MAP OR LAYOUT.

REMARKS: DISPOSAL AREAS, STOCKPILES, AND HAUL ROADS SHALL BE CONSTRUCTED IN A MANNER THAT WILL MINIMIZE AND CONTROL THE AMOUNT OF SEDIMENT THAT MAY ENTER RECEIVING WATERS. DISPOSAL AREAS SHALL NOT BE LOCATED IN ANY WETLAND, WATERBODY OR STREAMBED. CONSTRUCTION STAGING AREAS AND VEHICLE MAINTENANCE AREAS SHALL BE CONSTRUCTED BY THE CONTRACTOR IN A MANNER TO MINIMIZE THE RUNOFF OF POLLUTANTS. ALL WATERWAYS SHALL BE CLEARED AS SOON AS PRACTICAL OF TEMPORARY EMBANKMENT, TEMPORARY BRIDGES, MATTING FALSEWORK, PILING, DEBRIS OR OTHER OBSTRUCTIONS PLACED DURING CONSTRUCTION OPERATIONS THAT ARE NOT A PART OF THE FINISHED WORK.

NOTES: THE CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT ALL SUBCONTRACTORS ARE AWARE OF AND COMPLY WITH ALL COMPONENTS OF THE SWP3.





 Texas Department of Transportation
 © \$YEAR\$
TxDOT STORM WATER POLLUTION PREVENTION PLAN
 (LESS THAN ONE ACRE)
SWP3



FILE: swp3less1acre.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
Revisions				
May 2017	CONTRACT NO. 0919	SECTION 03	JOB NO. 064	HIGHWAY CIDER LN
	DIST. ATL	COUNTY HARRISON	SHEET NO. 65	

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE
FILE



TEMPORARY SEDIMENT CONTROL FENCE



HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

SEDIMENT CONTROL FENCE USAGE GUIDELINES

A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT². Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.


LEGEND

Sediment Control Fence



GENERAL NOTES

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.




VERTICAL TRACKING


				Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING					
EC(1)-16					
FILE: ec116	DN: TxDOT	CK: KM	DW: VP	DN/CK: LS	
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0919	03	064	CIDER LN	
	DIST	COUNTY	SHEET NO.		
	ATL	HARRISON	66		

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. The use of this standard for the conversion of this standard to other formats or for incorrect results or damages resulting from its use. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE:
FILE:




PLAN VIEW



PLAN VIEW




PLAN VIEW



SECTION A-A

EROSION CONTROL LOG DAM


CL-D



SECTION B-B

EROSION CONTROL LOG AT BACK OF CURB


CL-BOC



SECTION C-C


EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY

CL-ROW



DIAMETER MEASUREMENTS OF EROSION CONTROL LOGS SPECIFIED IN PLANS

- LEGEND
- CL-D EROSION CONTROL LOG DAM
 - CL-BOC EROSION CONTROL LOG AT BACK OF CURB
 - CL-ROW EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY
 - CL-SST EROSION CONTROL LOGS ON SLOPES STAKE AND TRENCHING ANCHORING
 - CL-SSL EROSION CONTROL LOGS ON SLOPES STAKE AND LASHING ANCHORING
 - CL-DI EROSION CONTROL LOG AT DROP INLET
 - CL-CI EROSION CONTROL LOG AT CURB INLET
 - CL-GI EROSION CONTROL LOG AT CURB & GRATE INLET



REBAR STAKE DETAIL

SEDIMENT BASIN & TRAP USAGE GUIDELINES

An erosion control log sediment trap may be used to filter sediment out of runoff draining from an unstabilized area.

Log Traps: The drainage area for a sediment trap should not exceed 5 acres. The trap capacity should be 1800 CF/Acre (0.5" over the drainage area).

Control logs should be placed in the following locations:

1. Within drainage ditches spaced as needed or min. 500' on center
2. Immediately preceding ditch inlets or drain inlets
3. Just before the drainage enters a water course
4. Just before the drainage leaves the right of way
5. Just before the drainage leaves the construction limits where drainage flows away from the project.

The logs should be cleaned when the sediment has accumulated to a depth of 1/2 the log diameter.

Cleaning and removal of accumulated sediment deposits is incidental and will not be paid for separately.

GENERAL NOTES:


1. EROSION CONTROL LOGS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, OR AS DIRECTED BY THE ENGINEER.
2. LENGTHS OF EROSION CONTROL LOGS SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND AS REQUIRED FOR THE PURPOSE INTENDED.
3. UNLESS OTHERWISE DIRECTED, USE BIODEGRADABLE OR PHOTODEGRADABLE CONTAINMENT MESH ONLY WHERE LOG WILL REMAIN IN PLACE AS PART OF A VEGETATIVE SYSTEM. FOR TEMPORARY INSTALLATIONS, USE RECYCLABLE CONTAINMENT MESH.
4. FILL LOGS WITH SUFFICIENT FILTER MATERIAL TO ACHIEVE THE MINIMUM COMPACTED DIAMETER SPECIFIED IN THE PLANS WITHOUT EXCESSIVE DEFORMATION.
5. STAKES SHALL BE 2" X 2" WOOD OR #3 REBAR, 2'-4' LONG, EMBEDDED SUCH THAT 2" PROTRUDES ABOVE LOG, OR AS DIRECTED BY THE ENGINEER.
6. DO NOT PLACE STAKES THROUGH CONTAINMENT MESH.
7. COMPOST CRADLE MATERIAL IS INCIDENTAL & WILL NOT BE PAID FOR SEPARATELY.
8. SANDBAGS USED AS ANCHORS SHALL BE PLACED ON TOP OF LOGS & SHALL BE OF SUFFICIENT SIZE TO HOLD LOGS IN PLACE.
9. TURN THE ENDS OF EACH ROW OF LOGS UPSLOPE TO PREVENT RUNOFF FROM FLOWING AROUND THE LOG.
10. FOR HEAVY RUNOFF EVENTS, ADDITIONAL UPSTREAM STAKES MAY BE NECESSARY TO KEEP LOG FROM FOLDING IN ON ITSELF.

SHEET 1 OF 3

		Design Division Standard	
<p>TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES</p> <p>EROSION CONTROL LOG</p> <p>EC(9) - 16</p>			
FILE: ec916	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CONT	SECT	HIGHWAY
REVISIONS	0919	03	064 CIDER LN
DIST	COUNTY		SHEET NO.
ATL	HARRISON		67


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:




EROSION CONTROL LOGS ON SLOPES
STAKE AND TRENCHING ANCHORING

CL-SST



END SECTION RAP DETAIL




EROSION CONTROL LOGS ON SLOPES
STAKE AND LASHING ANCHORING

CL-SSL



EROSION CONTROL LOG SPACING TABLE				
SLOPE	LOG DIAMETER			
	6"	8"	12"	18"
1:1 OR STEEPER	5'	10'	15'	20'
2:1	10'	20'	30'	40'
3:1	15'	30'	45'	60'
4:1 OR FLATTER	20'	40'	60'	80'

* ADJUSTMENTS CAN BE MADE FOR SOIL TYPE:
SOFT, LOAMY SOILS-ADJUST ROWS CLOSER TOGETHER;
HARD, ROCKY SOILS- ADJUST ROWS FARTHER APART




STAKE AND TRENCHING ANCHORING DETAIL

CL-SST




STAKE AND LASHING ANCHORING DETAIL

CL-SSL



TRENCH DEPTH TABLE	
LOG DIAMETER	DEPTH
6"	2"
8"	3"
12"	4"
18"	5"




STAKE NOTCH DETAIL

SHEET 2 OF 3


		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16			
FILE: ec116	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CON: 03	SECT: 064	JOB: CIDER LN
REVISIONS		DIST: ATL	COUNTY: HARRISON
		SHEET NO. 68	

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




EROSION CONTROL LOG AT DROP INLET

CL-DI



EROSION CONTROL LOG AT CURB INLET


CL-CI



EROSION CONTROL LOG AT CURB INLET


CL-CI

NOTE:
EROSION CONTROL LOGS USED AT CURB INLETS SHOULD ONLY BE USED IF THEY WILL NOT IMPEDE TRAFFIC OR FLOOD THE ROADWAY OR WHEN THE STORM SEWER SYSTEM IS NOT FULLY FUNCTIONAL.



EROSION CONTROL LOG AT CURB & GRADE INLET

CL-GI



		Design Division Standard		
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16				
FILE: ec916	DN: TxDOT	CK: KM	DW: LS/PT	CK: LS
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY
REVISIONS	0919	03	064	CIDER LN
DIST	COUNTY		SHEET NO.	
ATL	HARRISON		69	

DATE:
FILE: