

FHWA TEXAS DIVISION	PROJECT NO.	SHEET NO.
	F 2023(196), ETC.	1
STATE	DISTRICT	COUNTY
TEXAS	LFK	SHELBY, ETC
CONTROL	SECTION	JOB HIGHWAY NO.
0064	01	069,ETC SH 87, ETC

SEE SHEET 2 FOR INDEX OF SHEETS

STATE OF TEXAS  
DEPARTMENT OF TRANSPORTATION

PLANS OF PROPOSED  
STATE HIGHWAY IMPROVEMENT

PROJECT NO. F 2023(196), ETC.

SH 87, ETC.  
SHELBY, ETC.

NET LENGTH OF ROADWAY = 1,258,562 FT. = 238.364 MI.

LIMITS: FROM SH 7 TO SH 147, ETC.

FOR THE CONSTRUCTION OF SEAL COAT  
CONSISTING OF RESURFACE WITH SEAL COAT

FOR LOCATION MAP  
SEE SHEETS 3-4

FINAL PLANS

LETTING DATE: \_\_\_\_\_  
DATE CONTRACTOR BEGAN WORK: \_\_\_\_\_  
DATE WORK WAS COMPLETED: \_\_\_\_\_  
DATE WORK WAS ACCEPTED: \_\_\_\_\_  
FINAL CONTRACT COST: \$ \_\_\_\_\_  
CONTRACTOR: \_\_\_\_\_

CONSTRUCTION WORK ON THIS PROJECT WAS PERFORMED  
IN ACCORDANCE WITH PLANS, CONTRACT AND APPROVED  
CHANGE ORDERS.

\_\_\_\_\_ DATE \_\_\_\_\_

BARRICADES AND WARNING SIGNS

PROVIDE AND ERECT BARRICADES AND WARNING SIGNS  
IN ACCORDANCE WITH THE BARRICADE & CONSTRUCTION  
STANDARDS, TCP STANDARDS, THE "TEXAS MANUAL ON  
UNIFORM TRAFFIC CONTROL DEVICES" AND AS DIRECTED.

RAILROAD CROSSINGS	
PROJ. REF.	REFERENCE MARKER
2	756+0.036
3	334+1.323
4	318+0.032
16	748+0.187
21	370+0.446

NO EXCEPTIONS  
NO EQUATIONS

© 2022 BY TEXAS DEPARTMENT OF  
TRANSPORTATION ALL RIGHTS RESERVED



RECOMMENDED FOR LETTING: \_\_\_\_\_ APPROVED FOR LETTING: \_\_\_\_\_

DocuSigned by:  
*Jennifer Adams*  
9/23/2022

DISTRICT ADVANCE  
TRANSPORTATION PLANNING DIRECTOR

DocuSigned by:  
*Kelly O. Morris, P.E.*  
9/23/2022

DISTRICT ENGINEER

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF  
TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS  
LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT:  
REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL-AID CONSTRUCTION  
CONTRACTS (FORM FHWA 1273, JULY 2022).

FILE: c:\txdot\pw\onl\ine\txdot3\cathy.l\oerch\d0408470\LFK\*TI+leSheet\*Dist Rev.dgn  
DATE: 9/22/2022 4:01:09 PM

SHEET NO.      DESCRIPTION

- GENERAL**
- 1      TITLE SHEET
  - 2      INDEX OF SHEETS
  - 3-4    LOCATION MAP
  - 5, 5A-5D    GENERAL NOTES
  - 6, 6A-6E    ESTIMATE & QUANTITY SHEET
  - 7      PROJECT INFORMATION AND SURFACE AREAS
  - 8-11    QUANTITY SUMMARIES

**TRAFFIC CONTROL PLAN**

- # 12-23    BC (1)-21 THRU BC (12)-21
- # 24      TCP (3-1)-13
- # 25      TCP (3-2)-13
- # 26      TCP (3-3)-14
- # 27      TCP (3-4)-13
- # 28      TCP (SC-1)-21
- # 29      TCP (SC-2)-21
- # 30      TCP (SC-3)-21
- # 31      TCP (SC-4)-21
- # 32      TCP (SC-5)-21
- # 33      TCP (SC-6)-21
- # 34      TCP (SC-7)-21

**ROADWAY DETAILS**

- 35      COUNTY ROAD DETAIL

**TRAFFIC ITEMS**


- # 36      TYPICAL PAVEMENT MARKING DETAILS (LUFKIN DISTRICT STANDARD)
- # 37      PM (1)-20
- # 38      PM (2)-20
- # 39      PM (3)-20
- # 40      PM (4)-22
- # 41      RCD (1)-16
- # 42      RCD (2)-16
- # 43      TS2 (PL-1)-18

**ENVIRONMENTAL ISSUES**

- 44      TXDOT SWP3 INDEX
- # 45      EC (1)-16
- 46      EPIC

**RAILROAD**

- 47-51    RAILROAD SCOPE OF WORK
- 52-53    RAILROAD REQUIREMENTS FOR NON-BRIDGE CONSTRUCTION PROJECTS



DocuSigned by:  
*Charles M. Brazil, P.E.*  
 AF852E728AEC4C0...

9/26/2022


THE STANDARD SHEETS SPECIFICALLY IDENTIFIED BY \* HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.

DocuSigned by:  
*Charles M. Brazil, P.E.*      9/26/2022  
 CHARLES M. BRAZIL, P.E.      DATE

9/23/2022 4:03:47 PM c:\txdot\pwworking\line\txdot\3\cathy. loerch\0408470\index of sheets.dgn


**INDEX OF SHEETS**

TEXAS DEPARTMENT OF TRANSPORTATION ©2022			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		2




NOT TO SCALE

LOCATION MAP


 TEXAS DEPARTMENT OF TRANSPORTATION ©2022 SHEET 1 OF 2			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY	SHEET NO.	
LFK	SHELBY, ETC	3	

9/22/2022 4:19:21 PM  
C:\TxDOT\pwworking\line\TXdot\3\cathy.1oerch\40408470\location map.dgn



NOT TO SCALE

### LOCATION MAP

 TEXAS DEPARTMENT OF TRANSPORTATION ©2022 SHEET 2 OF 2			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY	SHEET NO.	
LFK	SHELBY, ETC	4	

### LOCATION MAP FOR HOUSTON, TRINITY, SAN JACINTO, AND POLK COUNTIES

**GENERAL NOTES:**

Construction vehicles shall not exceed 25 mph within the work area.

Complete final clean-up work after surface treatment placement on each project prior to extending surface treatment operations to more than 2 additional projects, unless otherwise directed.

Various bridges within the project limits will not require the placement of surface treatment. The Engineer will determine which bridges will not require the placement of surface treatment. Place new pavement markings across all bridges within the project limits unless otherwise directed.

Existing regulatory, warning and guide signs within project limits are to remain visible to the traveling public at all times. If a sign must be repositioned during construction operations, move and install the sign to an approved location. Use care when working near existing signs and repair or replace signs damaged by work operations. All work involved repositioning existing signs will be subsidiary to various bid items.

Furnish materials and make repairs to the existing roadway at any location damaged by construction operations. This work shall be done in an approved manner and will be subsidiary to various bid items.

Provide suitable access at all times to adjacent businesses, private property and side roads.

Observe the posted load ratings for all load zoned bridges and roadways. Do not exceed the posted tandem axle weight limit of load zoned roads and bridges at any time during construction.

Contractor questions on this project are to be addressed to the following individual(s):

Clint Jones, Area Engineer      [Clint.Jones@txdot.gov](mailto:Clint.Jones@txdot.gov)  
 Homar Munoz, Asst. Area Engineer      [Homar.Munoz@txdot.gov](mailto:Homar.Munoz@txdot.gov)

Contractor questions will be accepted through email, phone, and in person by the above individuals.

All contractor questions will be reviewed by the Engineer. Once a response is developed, it will be posted to TxDOT's Public FTP at the following Address:

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting%20Responses/>

All questions submitted that generate a response will be posted through this site. The site is organized by District, Project Type (Construction or Maintenance), Letting Date, CCSJ/Project Name.

The contractor's attention is directed to the EPIC sheet(s) included in this plan set for additional information regarding environmental permits, issues, and commitments.

**Item 5: Control of the Work**

Work in this contract requires crossing tracks on railroad property. Cooperate with the railroad company and comply with all requirements as outlined in Item 5, Section 8., "Cooperation with Railroads", plan sheets "Railroad Scope of Work" and "Railroad Requirements for Non-Bridge Construction Projects". Any agreements and insurance requirements for this project must be completed and acceptable by the Railroad's Representative and the Department before performing any work on railroad property.

This project will consist of five (5) separate crossing as shown elsewhere in the plans. Obtain the proper insurance policies, certificates and endorsements as shown on the plan sheet "Railroad Scope of Work" under Item V. "Railroad Insurance Requirements", for each respective crossing listed.

Individual projects will be inspected for acceptance in accordance with Article 5.12 "Final Acceptance", following completion of work on individual projects.

**Item 7: Legal Relations and Responsibilities**

No significant traffic generator events identified.

This project includes hurricane evacuation routes. Furnish at the pre-construction meeting a written plan outlining procedures to suspend work, secure the job site and safely handle traffic through and across the project in the event of a hurricane evacuation.

During the hurricane season, do not close any travel lanes on SH 87, US 287, or SH 21 except when the Contractor can demonstrate that he can provide labor, equipment, material, work plan, and quality of work to satisfactorily return all lanes to an open, all-weather travel surface within three days of receiving written or verbal notice but no later than 3 days prior to hurricane landfall. Construction of temporary lanes to an all-weather surface will be paid in accordance with Article 9.7, "Payment for Extra Work and Force Account Method".

In addition to lane closures, cease work 3 days prior to hurricane landfall on or near the roadway that adversely impacts the flow of traffic and reduces the capacity of the highway during an evacuation. Prohibit the Contractor's, sub-contractors' or material suppliers' vehicles from entering or exiting the stream of traffic including material hauling and delivery, and mobilization or demobilization of equipment. When directed, this prohibition will include a reasonable time period for the evacuees to return to their point of origin.

In the event of the declaration of a hurricane watch, warning, other severe weather warning or national or state emergency that requires the roadways in the vicinity be used as evacuation routes, cease all work that requires the Contractor's, sub-contractors' or material suppliers' vehicles to enter the stream of traffic on these primary or secondary evacuation routes. This work includes material hauling and delivery, and mobilization or demobilization of equipment.

Red-cockaded Woodpecker (federally listed endangered species) habitat is

present adjacent to the ROW along FM 2426. Conservation measures have been agreed upon by the United States Fish and Wildlife Service and TxDOT to ensure that the proposed action will not adversely affect the red-cockaded woodpecker. The conservation measures below must be followed in order to be in compliance with the Endangered Species Act:

1. NO WORK shall be performed on FM 2426 from April 1 to July 31.
2. WORK shall begin one hour after sunrise and cease one hour before sunset.
3. NO STOCKPILES or EQUIPMENT STORAGE shall be allowed along or within the ROW along FM 2426.

Texas Golden Gladecress (federally-listed endangered species) habitat is present within the ROW along SH 21. The conservation measure below must be followed in order to be in compliance with the Endangered Species Act.

1. NO STOCKPILES or EQUIPMENT STORAGE shall be allowed within the ROW along SH 21 from 0.5 mile east of LP 547 to 1.2 miles east of LP 547 and along FM 353 from 0.8 mile east of SH 147 to 1.02 mile east of SH 147
2. NO EQUIPMENT or VEHICLES shall leave the pavement on SH 21 from 0.5 miles east of LP 547 to 1.2 miles east of LP 547 and on FM 353 from 0.8 miles east of SH 147 to 1.02 miles east of SH 147.

Neches River Rose-mallow (federally-listed endangered species) habitat is present within the ROW on SH 94. The conservation measure below must be followed in order to be in compliance with the Endangered Species Act.

1. NO STOCKPILES or EQUIPMENT STORAGE shall be allowed within the ROW along SH 94 from 1.13 miles west of Trinity/Angelina County line to 1.0 mile West of the Trinity/Angelina County line.
2. NO EQUIPMENT or VEHICLES shall leave the pavement on SH 94 from 1.13 miles West of the Trinity/Angelina County line to 1.0 mile West of the Trinity/Angelina County line.

Engineer shall notify United States Forest Service prior to starting work on the following roadways:

1. Sabine National Forest: FM 2426, FM 353, SH 87
2. Davy Crockett National Forest: SH 94
3. Angelina National Forest: SH 147, SH 63
4. Sam Houston National Forest: SH 150

NO stock piling or equipment storage along roadways listed above.

The proposed work of this project is to resurface with seal coat. This activity maintains the original line and grade, hydraulic capacity and original purpose of the site. Therefore, this project meets the definition of a routine maintenance activity as defined in the TPDES General Permit No. TXR150000 issued March 5, 2018 and TCEQ's TPDES CGP does not apply.

Burning locations must be approved by the Engineer prior to beginning. Burning activities must be conducted in compliance with Texas Commission on Environmental Quality (TCEQ) regulations. Notify the Engineer when burning activities will take place.

No work will be allowed on SH 87 (0064-01-069 at Shelbyville), SH 87 (0304-07-024 at Center), SH 94 (0319-02-032 at Groveton), SH 94 (0319-03-054 at Centerville), FM 356 (0475-11-039 at Onalaska), FM 350 (0928-01-015 at Livingston), FM 225 (0594-04-029 at Douglass), SL 547 (0118-09-009 at San Augustine), SH 150 (0395-02-048 at Coldspring) and FM 95 (0706-05-013 at Chireno) on Monday through Friday between the hours of 7 am to 9 am and from 2 pm to 4 pm when school is in session or as directed by the engineer.

The following roads are to be scheduled as the last five (5) roads in the construction sequencing:

- Ref No. 2 – FM 2426
- Ref No. 3 – SH 87
- Ref No. 4 – SH 87
- Ref No. 16 – FM 2497
- Ref No. 21 – SL 547

#### Item 8: Prosecution and Progress

For this project, working days will be computed and charged in accordance with Item 8, Section 3.1.2, "Six-day Workweek".

The latest roadway start date for this project is May 1, 2023.

Work shall not be performed on May 26 through May 29 or July 1 through July 4.

Submit monthly progress schedules no later than the 20<sup>th</sup> calendar day of the month. Failure to comply with this deadline may result in the Engineer withholding progress (monthly) payments.

#### Item 302: Aggregates for Surface Treatments

Furnish Type PB or PL aggregate on the roads specified. Do not mix types of rock on the same roadway.

All aggregate shall be stockpiled, sampled, tested and approved prior to precoating of material.

Provide enough aggregate to allow for loss at the stockpile sites.

Temporary aggregate stockpile locations shall be approved prior to stockpiling.

Clean all stockpile locations by mowing or scraping prior to placement of aggregate. Cleaning

of stockpile sites will be subsidiary to the various bid items.

When directed, flush aggregate stockpiled for surface treatment with water to remove excessive dust particles, in such sequence that will permit free water to drain from the stockpiled aggregate prior to surfacing operations. This work will be subsidiary to various bid items.

Surplus aggregate remaining in temporary stockpiles due to errors in the plans, changes in the application rates, or changes in project locations will be paid for in accordance with Article 4.4, "Changes in the Work". Load and haul surplus aggregate to permanent stockpile sites as directed. Push aggregate into neat, clean stockpiles. Remove other surplus aggregate from the project.

Temporary stockpile sites shall be cleaned and cleared of debris as directed prior to final acceptance of each individual project.

#### Item 316: Seal Coat

Open season for asphalt placement is from May 1 thru August 31. Do not place asphalt outside the open season without written approval.

The uniformity and rate of distribution of asphaltic material will be checked periodically during construction. Apply the seal coat in lane widths unless otherwise directed. Where extra width of surfacing has been provided in transitions and climbing lanes, seal the entire surface width.

Resurface county road turnouts and intersection areas as directed.

The target asphalt content for pre-coating will be 1.0%.

Furnish medium pneumatic tire rollers in accordance Item 210, "Rolling". Provide enough rollers to perform the work as directed. Furnish one back-up roller for use at the project site. Make a minimum of three (3) roller passes on each asphalt shot.

Sweep all roadways with a powered rotary broom prior to placement of the surface treatment to remove all loose or excess material or debris. After rolling, sweep as soon as aggregate has sufficiently bonded to remove excess. Use a vacuum broom on all roadway sections having curb and gutter and all roadway sections within the city limits of any city.

Do not stage or park construction equipment on private property unless permission has been obtained from the owner.

Limits of seal coat projects may vary. Verify limits of work at each intersection prior to placement of seal coat. Payment will be based on verified quantities placed.

Apply asphalt and aggregate at rates as directed. The rates of application shown in the plans are for estimating purposes only.

Provide a transverse spray bar with end nozzle capable of applying lighter rates in the wheel

paths (regardless of the width of the roadway) when directed due to existing surface conditions.

Mark the length of each asphalt shot and rock load, as directed, prior to placement of surfacing.

Use precautions to preventing spilling when transferring asphalt from the transport to the asphalt distributor. Clean-up and properly dispose of all asphalt spilled during seal coat transport, transfer and placement operations.

#### Item 502: Barricades, Signs, and Traffic Handling

Traffic Control Plan (TCP):

Ensure the Contractor's Responsible Person (CRP) or their alternate for Barricades, Signs and Traffic Handling is available at all times and able to receive instructions from the Engineer or authorized Department representative. The CRP shall be a person that is usually at the project site during normal working hours.

For protection of the traveling public, direct traffic through the work area using signs, flaggers and other devices. Required signs are shown in the plans on the Barricade and Construction Standards and Traffic Control Plan Sheets. The latest edition of the "Texas Manual on Uniform Traffic Control Devices" shall also be used as a guide for handling traffic on this project.

Use "Do Not Pass" (R4-1) signs to mark the beginnings of roadway sections where passing is prohibited and use "Pass With Care" (R4-2) signs to mark the beginnings of roadway sections where passing is permitted. Install signs at the time signing for project limits are erected. Sign placement shall be verified and approved.

Maintain and keep signs in place until permanent striping has been completed.

Immediately cover or remove construction warning signs that are not applicable. Failure to remove or cover construction signs that are not applicable may result in suspension of work.

Restrict construction work to single lane widths with only minor disruptions in traffic flow. Lane closures shall conform to the Traffic Control Plan for lane closures as shown in the plans. No overnight closures will be permitted.

Limit lane closures for multilane roads (4 or more lanes) to 2 mi. in length, unless otherwise approved.

Limit lane closures for 2 lane roads to 2 mi. in length, unless otherwise approved.

Lane closure lengths can exclude the end tapers.

Plan the sequence of work to minimize the time lane closures are in place. Install lane closures only where construction operations are anticipated to start within 1 hr. and limited to the amount of lane that can be reached by the construction activity within 2 hr. unless otherwise approved.

Provide flashing arrow panels to supplement required signs and devices for lane closures.

Provide a pilot car to lead traffic through the work area. The pilot car will not be paid for directly, but will be subsidiary to various bid items.

Halt traffic during the time asphalt is being applied to the roadway. No vehicles will be allowed to pass the asphalt distributor during asphalt application.

Provide adequate flaggers to protect the traveling public when working on or near a roadway carrying traffic. All flaggers shall wear hardhats and reflective vests.

Install "Be Prepared to Stop" (CW3-4) and "Flagger Ahead" (CW20-7aD) signs when flaggers are present. Position the signs where good visibility and traffic control can be maintained.

Use a flashing arrow board in addition to the required signs to warn motorists of flaggers.

Use additional flaggers at roadway intersections to direct traffic entering the work area, when deemed necessary by the Engineer.

Open all traffic lanes to traffic at the close of work each day.

Provide one high-intensity yellow, rotating dome-light on all equipment such as distributors, spreader boxes, lay-down machines, dump trucks, rollers, backhoes, road graders, loaders, etc. within the work zone. Mount lights high enough to be visible from all directions and operating when the equipment is in the work zone. On all other equipment such as automobiles, trailers, etc. use emergency flashers while within the work zone.

Notify the Engineer prior to placing any materials or equipment on the right of way. Locate equipment, stockpiles or other materials not in use as far as possible from the driving lanes and in no case closer than 30 ft. unless otherwise authorized. Any equipment, stockpiles, or materials placed within 30 ft. of the driving lane must have adequate signs, barricades or other warning devices as approved. As a minimum place an 8 ft. wide TY III Barricade or barrels on the approach side of each site that is within 30 ft. of the driving lane. Use TY III Barricade or barrels for the site similarly on the departure side if the location is within 30 ft. of the opposing traffic lane.

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

Texas Transportation Code 547.105 authorizes the use of warning lights to promote safety and provides an effective means of gaining the travelling public's attention as they drive in areas where construction crews are present. In order to influence the public to move over when high

risk construction activities are taking place, minimize the utilization of blue warning lights. These lights must be used only while performing work on or near the travel lanes or shoulder where the travelling public encounters construction crews that are not protected by a standard work zone set up such as a lane closure, shoulder closure, or one-way traffic control. Refrain from leaving the warning lights engaged while travelling from one work location to another or while parked on the right of way away from the pavement or a work zone.

Provide an illuminated flagger station when nighttime work is performed.

Install "Stay Alert" (G20-10T) and "OBEY" (R20-3T) signs at the beginning of the construction zone at "T" intersections as directed.

All workers on TxDOT right-of-way shall wear reflective clothing meeting ANSI Class II requirements during the day and ANSI Class III requirements during the night.

#### **Item 506: Temporary Erosion, Sedimentation, and Environmental Controls**

Other erosion or water pollution control measure deemed necessary by the Engineer will be paid for in accordance with article 4.4, "Changes in the Work".

Place temporary sediment control fence at locations as directed.

#### **Item 662: Work Zone Pavement Markings**

After placement of permanent striping on the finish course, remove all short term pavement markings.

#### **Item 666: Reflectorized Pavement Markings**

Remove loose aggregate immediately prior to placing pavement markings.

Place reflectorized pavement markings no sooner than 3 days nor later than 14 days after placement of the surface treatment.

Before construction operations begin, observe and mark existing passing/no passing zones. Passing/no passing zones shall be verified prior to placement of permanent pavement markings.

Place a minimum of 500 ft. of 4 in. double yellow no passing lines on the approach to all stop condition intersections for two lane roads unless otherwise shown in the plans or directed.

#### **Item 672: Raised Pavement Markers**

Place permanent raised pavement markers after permanent striping has been completed.

#### **Item 677: Eliminating Existing Pavement Markings and Markers**

Remove all raised pavement markers, including those located on bridge decks which are not to be sealed, in an approved manner prior to placement of the surface treatment. Repair damage to



existing pavement caused by removing markers in an approved manner with approved patching material. This work will be subsidiary to various bid items. Properly dispose of raised pavement markers off of the ROW.

Eliminate existing crosswalks, school zones and stop bars, railroad crossing markings and profile pavement markings along the proposed roadways or adjacent side streets as directed prior to placement of the surface treatment. Properly dispose of material generated daily.

Blading is an allowable method for eliminating existing raised pavement markings as approved by the Engineer.

Removal of existing temporary work zone tape and tabs is subsidiary to Item 316.

**Item 6185: Truck Mounted Attenuator (TMA) and Trailer Attenuator (TA)**

Three (3) TMAs will be required on all divided highways for mobile operations and two (2) TMAs will be required on all other roadways for each mobile operation. Quantities were estimated based on one mobile working operation, as per the number of working days. If multiple crews are utilized, additional TMAs will be required.



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0064-01-069

DISTRICT Lufkin  
HIGHWAY FM 1818, FM 225, FM 227, FM 2426, FM 2497, FM 3126, FM 325, FM 343, FM 350, FM 353, FM 356, FM 95, FM 980, SH 147, SH 150, SH 21, SH 63, SH 87, SH 94, SL 34, SL 547, US 287

COUNTY Angelina, Houston, Nacogdoches, Polk, Sabine, San Augustine, San Jacinto, Shelby, Trinity

CONTROL SECTION JOB				0064-01-069		0109-03-042		0118-01-023		0118-02-037		0118-08-086		0118-09-009	
PROJECT ID				A00061366		A00191460		A00067097		A00067098		A00067115		A00184804	
COUNTY				Shelby		Houston		Houston		Houston		Nacogdoches		San Augustine	
HIGHWAY				SH 87		US 287		SH 21		SH 21		SH 21		SL 547	
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL
	316-6003	AGGR (LOAD HAUL & DISTRIB)	CY												
	316-6048	ASPH (AC-20-5TR)	TON	397.000		59.000		164.000		46.000		86.000		35.000	
	316-6124	AGGR(TY-PB GR-3 SAC-A)	CY			429.000									
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY	1,820.000								393.000		160.000	
	316-6224	AGGR(TY-PB GR-4 SAC-B)	CY												
	316-6402	AGGR (TY-PE, E, L OR PL GR 3)	CY					1,145.000		316.000					
	500-6001	MOBILIZATION	LS	0.060		0.010		0.030		0.010		0.010		0.010	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	6.000											
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA	693.000		53.000						86.000			
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	1,329.000		432.000		1,008.000		329.000		425.000		158.000	
	666-6171	REFL PAV MRK TY II (W) 6" (BRK)	LF	13,860.000		3,670.000		120.000				850.000			
	666-6174	REFL PAV MRK TY II (W) 6" (SLD)	LF	103,330.000		19,600.000		81,904.000		26,254.000		32,378.000		11,884.000	
	666-6178	REFL PAV MRK TY II (W) 8" (SLD)	LF	865.000						122.000		270.000			
	666-6208	REFL PAV MRK TY II (Y) 6" (BRK)	LF	380.000				4,250.000		1,460.000		430.000			
	666-6210	REFL PAV MRK TY II (Y) 6" (SLD)	LF	107,086.000		21,682.000		63,694.000		18,642.000		30,689.000		11,544.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF	24.000											
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF	132.000				25.000						311.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA	8.000						1.000		2.000		2.000	
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA	8.000						1.000		2.000		2.000	
	668-6089	PREFAB PAV MRK TY C (W) (RR XING)	EA	2.000										2.000	
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF	570.000											
	672-6007	REFL PAV MRKR TY I-C	EA	179.000		185.000		4.000		8.000		29.000			
	672-6009	REFL PAV MRKR TY II-A-A	EA	1,708.000		247.000		1,023.000		320.000		422.000		150.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF	32,500.000								63,497.000			
	677-6006	ELIM EXT PAV MRK & MRKS (18")	LF	24.000											
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF	702.000				25.000						311.000	
	677-6008	ELIM EXT PAV MRK & MRKS (ARROW)	EA	8.000						1.000		2.000		2.000	
	677-6012	ELIM EXT PAV MRK & MRKS (WORD)	EA	8.000						1.000		2.000		2.000	
	677-6016	ELIM EXT PAV MRK & MRKS (RR XING)	EA	2.000										2.000	
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY	10.000											
	6185-6005	TMA (MOBILE OPERATION)	DAY	214.000											
18		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000											
		RAILROAD FLAGGING: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000											
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000											



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0064-01-069

DISTRICT Lufkin  
HIGHWAY FM 1818, FM 225, FM 227, FM 2426, FM 2497, FM 3126, FM 325, FM 343, FM 350, FM 353, FM 356, FM 95, FM 980, SH 147, SH 150, SH 21, SH 63, SH 87, SH 94, SL 34, SL 547, US 287

COUNTY Angelina, Houston, Nacogdoches, Polk, Sabine, San Augustine, San Jacinto, Shelby, Trinity

CONTROL SECTION JOB				0118-11-009		0118-12-021		0118-13-015		0244-01-048		0304-04-046		0304-07-024	
PROJECT ID				A00139266		A00132999		A00133003		A00191464		A00067023		A00026118	
COUNTY				Nacogdoches		San Augustine		Shelby		Angelina		Sabine		Shelby	
HIGHWAY				SL 34		FM 353		FM 353		SH 63		SH 87		SH 87	
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL
	316-6003	AGGR (LOAD HAUL & DISTRIB)	CY							688.000					
	316-6048	ASPH (AC-20-5TR)	TON	14.000		145.000		56.000		95.000		281.000		490.000	
	316-6124	AGGR(TY-PB GR-3 SAC-A)	CY												
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY			666.000		254.000				1,290.000		2,247.000	
	316-6224	AGGR(TY-PB GR-4 SAC-B)	CY	60.000											
	316-6402	AGGR (TY-PE, E, L OR PL GR 3)	CY												
	500-6001	MOBILIZATION	LS	0.010		0.020		0.010		0.010		0.050		0.070	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO												
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA							83.000				195.000	
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	83.000		910.000		351.000		660.000		1,287.000		2,080.000	
	666-6171	REFL PAV MRK TY II (W) 6" (BRK)	LF							840.000				1,770.000	
	666-6174	REFL PAV MRK TY II (W) 6" (SLD)	LF	804.000						52,800.000		100,860.000		161,464.000	
	666-6178	REFL PAV MRK TY II (W) 8" (SLD)	LF									80.000		122.000	
	666-6208	REFL PAV MRK TY II (Y) 6" (BRK)	LF			910.000		650.000		4,110.000		4,330.000		11,410.000	
	666-6210	REFL PAV MRK TY II (Y) 6" (SLD)	LF	6,506.000		69,698.000		26,512.000		26,884.000		84,037.000		116,118.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF											72.000	
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF	10.000		22.000		20.000						130.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA									1.000		2.000	
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA									1.000		2.000	
	668-6089	PREFAB PAV MRK TY C (W) (RR XING)	EA											2.000	
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF											280.000	
	672-6007	REFL PAV MRKR TY I-C	EA							45.000		5.000		35.000	
	672-6009	REFL PAV MRKR TY II-A-A	EA	84.000		920.000		367.000		757.000		1,313.000		2,265.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF					27,162.000				189,227.000			
	677-6006	ELIM EXT PAV MRK & MRKS (18")	LF											72.000	
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF	10.000		22.000		20.000						410.000	
	677-6008	ELIM EXT PAV MRK & MRKS (ARROW)	EA									1.000		2.000	
	677-6012	ELIM EXT PAV MRK & MRKS (WORD)	EA									1.000		2.000	
	677-6016	ELIM EXT PAV MRK & MRKS (RR XING)	EA											2.000	
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY												
	6185-6005	TMA (MOBILE OPERATION)	DAY												
18		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		RAILROAD FLAGGING: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS												



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0064-01-069

DISTRICT Lufkin  
HIGHWAY FM 1818, FM 225, FM 227, FM 2426, FM 2497, FM 3126, FM 325, FM 343, FM 350, FM 353, FM 356, FM 95, FM 980, SH 147, SH 150, SH 21, SH 63, SH 87, SH 94, SL 34, SL 547, US 287

COUNTY Angelina, Houston, Nacogdoches, Polk, Sabine, San Augustine, San Jacinto, Shelby, Trinity

CONTROL SECTION JOB				0319-02-032		0319-03-054		0319-05-019		0340-01-045		0390-03-037		0395-02-048	
PROJECT ID				A00061129		A00061132		A00191463		A00132994		A00067107		A00067118	
COUNTY				Trinity		Trinity		Angelina		Houston		Angelina		San Jacinto	
HIGHWAY				SH 94		SH 94		FM 325		US 287		SH 147		SH 150	
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL
	316-6003	AGGR (LOAD HAUL & DISTRIB)	CY					354.000							
	316-6048	ASPH (AC-20-5TR)	TON	229.000		432.000		57.000		354.000		271.000		317.000	
	316-6124	AGGR(TY-PB GR-3 SAC-A)	CY												
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY	1,049.000		1,980.000				1,625.000		1,243.000		1,453.000	
	316-6224	AGGR(TY-PB GR-4 SAC-B)	CY												
	316-6402	AGGR (TY-PE, E, L OR PL GR 3)	CY												
	500-6001	MOBILIZATION	LS	0.040		0.070		0.010		0.050		0.040		0.050	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO												
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA					978.000		198.000		261.000		313.000	
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	1,071.000		1,960.000		489.000		1,711.000		924.000		1,118.000	
	666-6171	REFL PAV MRK TY II (W) 6" (BRK)	LF					4,910.000		3,380.000		4,890.000		2,090.000	
	666-6174	REFL PAV MRK TY II (W) 6" (SLD)	LF	85,632.000		157,418.000		19,547.000		101,778.000		67,966.000		75,568.000	
	666-6178	REFL PAV MRK TY II (W) 8" (SLD)	LF	312.000				200.000				143.000		693.000	
	666-6208	REFL PAV MRK TY II (Y) 6" (BRK)	LF	6,750.000		11,780.000				5,900.000		4,910.000		4,580.000	
	666-6210	REFL PAV MRK TY II (Y) 6" (SLD)	LF	50,213.000		98,410.000		19,547.000		72,519.000		52,163.000		63,719.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF	55.000		90.000								18.000	
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF	211.000				108.000		25.000				100.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA	4.000				2.000				7.000		3.000	
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA	4.000				2.000				1.000		7.000	
	668-6089	PREFAB PAV MRK TY C (W) (RR XING)	EA												
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF												
	672-6007	REFL PAV MRKR TY I-C	EA	17.000				284.000		47.000		73.000		68.000	
	672-6009	REFL PAV MRKR TY II-A-A	EA	1,026.000		1,865.000		122.000		1,286.000		1,105.000		1,526.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF	142,595.000		270,830.000				1,413.000				1,374.000	
	677-6006	ELIM EXT PAV MRK & MRKS (18")	LF	55.000		90.000								18.000	
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF	211.000				108.000		25.000				100.000	
	677-6008	ELIM EXT PAV MRK & MRKS (ARROW)	EA	4.000				2.000				7.000		3.000	
	677-6012	ELIM EXT PAV MRK & MRKS (WORD)	EA	4.000				2.000				1.000		7.000	
	677-6016	ELIM EXT PAV MRK & MRKS (RR XING)	EA												
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY												
	6185-6005	TMA (MOBILE OPERATION)	DAY												
18		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		RAILROAD FLAGGING: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS												



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0064-01-069

DISTRICT Lufkin  
HIGHWAY FM 1818, FM 225, FM 227, FM 2426, FM 2497, FM 3126, FM 325, FM 343, FM 350, FM 353, FM 356, FM 95, FM 980, SH 147, SH 150, SH 21, SH 63, SH 87, SH 94, SL 34, SL 547, US 287

COUNTY Angelina, Houston, Nacogdoches, Polk, Sabine, San Augustine, San Jacinto, Shelby, Trinity

CONTROL SECTION JOB				0475-11-039		0594-04-029		0706-05-013		0928-01-015		0937-02-035		1794-01-026	
PROJECT ID				A00067102		A00184802		A00067113		A00067101		A00067032		A00067048	
COUNTY				Polk		Nacogdoches		Nacogdoches		Polk		Houston		Angelina	
HIGHWAY				FM 356		FM 225		FM 95		FM 350		FM 227		FM 1818	
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL
	316-6003	AGGR (LOAD HAUL & DISTRIB)	CY												
	316-6048	ASPH (AC-20-5TR)	TON	158.000		359.000		177.000		124.000		251.000		325.000	
	316-6124	AGGR(TY-PB GR-3 SAC-A)	CY												
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY	722.000		1,648.000				566.000		1,150.000		1,490.000	
	316-6224	AGGR(TY-PB GR-4 SAC-B)	CY					811.000							
	316-6402	AGGR (TY-PE, E, L OR PL GR 3)	CY												
	500-6001	MOBILIZATION	LS	0.030		0.060		0.030		0.020		0.040		0.050	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO												
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA												
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	851.000		2,069.000		1,120.000		671.000		1,570.000		1,674.000	
	666-6171	REFL PAV MRK TY II (W) 6" (BRK)	LF												
	666-6174	REFL PAV MRK TY II (W) 6" (SLD)	LF	50,720.000		165,244.000		89,444.000		53,666.000		125,538.000		133,088.000	
	666-6178	REFL PAV MRK TY II (W) 8" (SLD)	LF	164.000						825.000					
	666-6208	REFL PAV MRK TY II (Y) 6" (BRK)	LF	4,720.000		3,300.000		4,890.000		2,130.000		2,790.000		11,460.000	
	666-6210	REFL PAV MRK TY II (Y) 6" (SLD)	LF	45,382.000		150,550.000		67,086.000		28,396.000		112,819.000		72,230.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF	40.000		48.000		48.000		34.000					
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF	156.000		27.000		46.000		112.000		44.000		39.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA	9.000						4.000					
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA	4.000						4.000					
	668-6089	PREFAB PAV MRK TY C (W) (RR XING)	EA												
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF											123.000	
	672-6007	REFL PAV MRKR TY I-C	EA	10.000						45.000					
	672-6009	REFL PAV MRKR TY II-A-A	EA	870.000		2,061.000		1,101.000		608.000		1,553.000		1,613.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF	100,822.000		319,094.000		500.000		84,192.000		760.000		217,943.000	
	677-6006	ELIM EXT PAV MRK & MRKS (18")	LF	90.000		48.000		48.000		34.000					
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF			27.000		46.000		112.000		44.000		162.000	
	677-6008	ELIM EXT PAV MRK & MRKS (ARROW)	EA	5.000						4.000					
	677-6012	ELIM EXT PAV MRK & MRKS (WORD)	EA							4.000					
	677-6016	ELIM EXT PAV MRK & MRKS (RR XING)	EA												
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY												
	6185-6005	TMA (MOBILE OPERATION)	DAY												
18		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		RAILROAD FLAGGING: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS												



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0064-01-069

DISTRICT Lufkin  
HIGHWAY FM 1818, FM 225, FM 227, FM 2426, FM 2497, FM 3126, FM 325, FM 343, FM 350, FM 353, FM 356, FM 95, FM 980, SH 147, SH 150, SH 21, SH 63, SH 87, SH 94, SL 34, SL 547, US 287

COUNTY Angelina, Houston, Nacogdoches, Polk, Sabine, San Augustine, San Jacinto, Shelby, Trinity

CONTROL SECTION JOB				1810-02-026		2268-01-018		2300-01-022		2443-02-018		2589-01-026		3160-03-009	
PROJECT ID				A00184803		A00061128		A00067109		A00067116		A00067106		A00067103	
COUNTY				Nacogdoches		Sabine		Nacogdoches		San Jacinto		Angelina		Polk	
HIGHWAY				FM 225		FM 2426		FM 343		FM 980		FM 2497		FM 3126	
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL	EST.	FINAL
	316-6003	AGGR (LOAD HAUL & DISTRIB)	CY												
	316-6048	ASPH (AC-20-5TR)	TON	238.000		161.000		257.000		250.000		201.000		68.000	
	316-6124	AGGR(TY-PB GR-3 SAC-A)	CY												
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY	1,092.000											
	316-6224	AGGR(TY-PB GR-4 SAC-B)	CY									922.000		309.000	
	316-6402	AGGR (TY-PE, E, L OR PL GR 3)	CY			1,124.000		1,799.000		1,749.000					
	500-6001	MOBILIZATION	LS	0.040		0.030		0.050		0.050		0.030		0.010	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO												
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA					6.000							
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	1,341.000		1,228.000		2,002.000		1,962.000		1,040.000		360.000	
	666-6171	REFL PAV MRK TY II (W) 6" (BRK)	LF												
	666-6174	REFL PAV MRK TY II (W) 6" (SLD)	LF	107,206.000		98,220.000		150,260.000		154,018.000		83,184.000		28,788.000	
	666-6178	REFL PAV MRK TY II (W) 8" (SLD)	LF							105.000					
	666-6208	REFL PAV MRK TY II (Y) 6" (BRK)	LF	5,530.000		4,400.000		8,400.000		11,200.000		5,330.000		1,740.000	
	666-6210	REFL PAV MRK TY II (Y) 6" (SLD)	LF	82,626.000		79,927.000		112,498.000		99,093.000		58,153.000		20,147.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF												
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF			60.000		15.000		15.000		57.000		46.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA												
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA												
	668-6089	PREFAB PAV MRK TY C (W) (RR XING)	EA			2.000						2.000			
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF												
	672-6007	REFL PAV MRKR TY I-C	EA							7.000					
	672-6009	REFL PAV MRKR TY II-A-A	EA	1,329.000		1,234.000		1,881.000		1,889.000		1,016.000		344.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF	197,122.000		182,547.000		271,158.000		1,550.000		146,667.000		50,675.000	
	677-6006	ELIM EXT PAV MRK & MRKS (18")	LF												
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF			64.000		15.000		15.000		57.000		46.000	
	677-6008	ELIM EXT PAV MRK & MRKS (ARROW)	EA												
	677-6012	ELIM EXT PAV MRK & MRKS (WORD)	EA												
	677-6016	ELIM EXT PAV MRK & MRKS (RR XING)	EA			2.000						2.000			
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY												
	6185-6005	TMA (MOBILE OPERATION)	DAY												
18		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		RAILROAD FLAGGING: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS												
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS												



CONTROLLING PROJECT ID 0064-01-069

DISTRICT Lufkin  
HIGHWAY FM 1818, FM 225, FM 227, FM 2426, FM 2497, FM 3126, FM 325, FM 343, FM 350, FM 353, FM 356, FM 95, FM 980, SH 147, SH 150, SH 21, SH 63, SH 87, SH 94, SL 34, SL 547, US 287

# Estimate & Quantity Sheet

COUNTY Angelina, Houston, Nacogdoches, Polk, Sabine, San Augustine, San Jacinto, Shelby, Trinity

CONTROL SECTION JOB				TOTAL EST.	TOTAL FINAL
PROJECT ID					
COUNTY					
HIGHWAY					
ALT	BID CODE	DESCRIPTION	UNIT		
	316-6003	AGGR (LOAD HAUL & DISTRIB)	CY	1,042.000	
	316-6048	ASPH (AC-20-5TR)	TON	6,097.000	
	316-6124	AGGR(TY-PB GR-3 SAC-A)	CY	429.000	
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY	20,848.000	
	316-6224	AGGR(TY-PB GR-4 SAC-B)	CY	2,102.000	
	316-6402	AGGR (TY-PE, E, L OR PL GR 3)	CY	6,133.000	
	500-6001	MOBILIZATION	LS	1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	6.000	
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA	2,866.000	
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	32,213.000	
	666-6171	REFL PAV MRK TY II (W) 6" (BRK)	LF	36,380.000	
	666-6174	REFL PAV MRK TY II (W) 6" (SLD)	LF	2,338,563.000	
	666-6178	REFL PAV MRK TY II (W) 8" (SLD)	LF	3,901.000	
	666-6208	REFL PAV MRK TY II (Y) 6" (BRK)	LF	127,740.000	
	666-6210	REFL PAV MRK TY II (Y) 6" (SLD)	LF	1,868,570.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF	429.000	
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF	1,711.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA	45.000	
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA	38.000	
	668-6089	PREFAB PAV MRK TY C (W) (RR XING)	EA	10.000	
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF	973.000	
	672-6007	REFL PAV MRKR TY I-C	EA	1,041.000	
	672-6009	REFL PAV MRKR TY II-A-A	EA	32,005.000	
	677-6001	ELIM EXT PAV MRK & MRKS (4")	LF	2,301,628.000	
	677-6006	ELIM EXT PAV MRK & MRKS (18")	LF	479.000	
	677-6007	ELIM EXT PAV MRK & MRKS (24")	LF	2,532.000	
	677-6008	ELIM EXT PAV MRK & MRKS (ARROW)	EA	41.000	
	677-6012	ELIM EXT PAV MRK & MRKS (WORD)	EA	34.000	
	677-6016	ELIM EXT PAV MRK & MRKS (RR XING)	EA	10.000	
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY	10.000	
	6185-6005	TMA (MOBILE OPERATION)	DAY	214.000	
18		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000	
		RAILROAD FLAGGING: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000	
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000	

DISTRICT	COUNTY	CCSJ	SHEET
Lufkin	Shelby	0064-01-069	6E


PROJECT INFORMATION AND SURFACE AREAS

PROJ. REF. NO	MAINT SECT	COUNTY	HIGHWAY	CONTROL SECTION JOB	LIMITS		REFERENCE MARKER		ROADWAY LENGTH		WIDTHS				NOTES	SURFACE AREAS				
							FROM	TO	FT	MI	TRAVEL LANES		SHLDR			TRAVEL LANES	SHLDR	MEDIANS/PASSING LANES	INTERSECTION TURNOUTS	TOTAL
											NO.	FT	NO.	FT		SY	SY	SY	SY	SY
1	1	SABINE	SH 87	0304-04-046	FM 83 WEST	FM 2928	378+0.950	388+0.592	50,424	9.550	2	12	2	1-9	3 INT	134,464	37,099	1,569	950	174,082
2	1	SABINE	FM 2426	2268-01-018	FM 1	SH 87	756-0.037	764+1.336	49,109	9.301	2	11	2	1-9		120,045	14,826	0	0	134,871
3	2	SHELBY	SH 87	0064-01-069	COLLIER ST	SH 147	334+0.609	344+0.539	51,665	9.785	2	12	2	1-10	6 INT	137,773	25,191	75,984	6,711	245,659
4	2	SHELBY	SH 87	0304-07-024	US 59	US 96	318-0.050	332+1.160	80,747	15.293	2	12	2	2-9	3 INT 2 RA	215,325	70,108	14,093	3,794	303,320
5	3	HOUSTON	SH 21	0118-01-023	SL 304	2.564 MI S OF FM 1733	720+0.400	728+0.410	40,313	7.635	2	12	2	1-8	1 INT	107,501	29,148	0	674	137,323
6	3	HOUSTON	SH 21	0118-02-037	2.564 MI S OF FM 1733	FM 1733	728+0.410	730+0.940	13,126	2.486	2	12	2	1		35,003	2,917	0	0	37,920
7	3	HOUSTON	US 287	0340-01-045	SL 304	1.18 MI S OF FM 232	636+1.414	646+1.055	68,429	12.960	2	12	2	1-9	1 INT	182,477	15,312	21,120	406	219,315
8	3	HOUSTON	FM 227	0937-02-035	BU 287 V	FM 3016	670-1.182	680+0.749	62,769	11.888	2	11			8 INT	153,434	0	0	1,803	155,237
9	4	TRINITY	SH 94	0319-02-032	US 287	1.6 MI S OF FM 358	710-0.916	716+0.970	42,816	8.109	2	12	2	2-14		114,175	27,428	0	0	141,603
10	4	TRINITY	SH 94	0319-03-054	1.6 MI S OF FM 358	NECHES RIVER BRIDGE	716+0.970	732+0.370	78,371	14.843	2	12	2	2-10	4 INT	208,989	58,301	0	0	267,290
11	5	POLK	FM 356	0475-11-039	TRINITY COUNTY LINE	END OF STATE MAINTENANCE	702+0.290	706+1.710	28,565	5.410	2	12	2	2-7	2 INT	70,628	19,582	7,209	0	97,419
12	5	POLK	FM 350	0928-01-015	US 190	END OF STATE MAINTENANCE	412-1.452	414+1.608	26,833	5.082	2	11			2 INT	69,738	5,746	908	0	76,392
13	5	POLK	FM 3126	3160-03-009	US 190	FM 2457	398-0.014	400+0.700	14,393	2.726	2	12	2	1		38,382	3,199	0	0	41,581
14	6	ANGELINA	SH 147	0390-03-037	SOUTH END OF SH 147 BRIDGE	SH 63	370+2.243	378+0.480	33,982	6.436	2	12	2	1-8	2 INT	90,619	39,019	31,715	6,357	167,710
15	6	ANGELINA	FM 1818	1794-01-026	FM 58	US 69	718+0.183	730+0.821	66,544	12.603	2	11			2 INT	192,238	0	521	8,332	201,091
16	6	ANGELINA	FM 2497	2589-01-026	SH 94	US 59	362+0.024	370+0.572	41,591	7.877	2	12	2	1	1 INT	110,908	9,243	0	4,215	124,366
17	7	NACOGDOCHES	FM 225	0594-04-029	0.84 MI S OF SH 204 (S OF CEDAR AVE)	5.1 MI S OF SH 21	330+1.199	346+1.065	82,732	15.669	2	12	2	1	1 INT	202,235	18,386	0	1,734	222,355
18	7	NACOGDOCHES	FM 225	1810-02-026	5.1 MI S OF SH 21	CR 715	346+1.065	356+1.098	53,603	10.152	2	12		1-10	1 INT	131,028	12,494	0	3,880	147,402
19	7	NACOGDOCHES	FM 343	2300-01-022	FM 225	US 59	708-0.102	722+0.219	79,807	15.115	2	12			2 INT	212,819	0	549	2,489	215,857
20	8	NACOGDOCHES	SH 21	0118-08-086	FM 95	SAN AUGUSTINE COUNTY LINE	800+0.982	804+0.048	16,405	3.107	2	11	2	1-6	3 INT	40,101	2,215	8,016	2,594	52,926
21	8	SAN AUGUSTINE	SL 547	0118-09-009	SH 21	SH 21	748-0.033	748+1.060	6,299	1.193	2	11	2	5-9	6 INT RA	15,398	3,958	0	2,172	21,528
22	8	NACOGDOCHES	SL 34	0118-11-009	FM 95	SH 21	346+0.792	346+1.415	3,305	0.626	2	11				8,080	0	0	0	8,080
23	8	SAN AUGUSTINE	FM 353	0118-12-021	SH 147	SHELBY COUNTY LINE	750+0.048	756+0.992	36,379	6.890	2	12				88,927	0	0	902	89,829
24	8	SHELBY	FM 353	0118-13-015	SAN AUGUSTINE COUNTY LINE	SH 87	756+1.020	760+0.590	14,008	2.653	2	11				34,241	0	0	0	34,241
25	8	NACOGDOCHES	FM 95	0706-05-013	SL 34	SH 103	360-1.835	366+0.683	44,764	8.478	2	12				109,423	0	0	0	109,423
26	9	SAN JACINTO	SH 150	0395-02-048	FM 945 NORTH	SH 156	686+1.710	694+0.980	39,679	7.515	2	12	2	1-8	1 INT	105,811	65,293	24,246	748	196,098
27	9	SAN JACINTO	FM 980	2443-02-018	WALKER COUNTY LINE	US 190	682+1.903	698+0.852	78,466	14.861	2	12			RA	209,243	0	0	598	209,841
28	3	HOUSTON	US 287	0109-03-042	ANDERSON CL	3.27 MILES SOUTH OF ANDERSON CL (NB)	616+1.021	620+1.246	17,266	3.270	2	12	1	10		46,686	2,593			49,279
29	6	ANGELINA	FM 325	0319-05-019	BU 5-G (TIMBERLAND DR)	SL 287/US 59	714-0.050	714+1.800	9,773	1.851	4	11	2	1		47,780				47,780
30	6	ANGELINA	SH 63	0244-01-048	5 MILES NORTH OF JASPER CL	JASPER CL	740+0.179	744+1.209	26,400	5.000	2	12				70,400		8,667		79,067
<b>PROJECT TOTALS</b>									<b>1,258,562</b>	<b>238.364</b>						<b>3,303,871</b>	<b>462,058</b>	<b>194,597</b>	<b>48,359</b>	<b>4,008,884</b>

NOTE: REF NO. 16 ON FM 2497 - EXCEPTION FOR PREVIOUS CONSTRUCTION PROJECT 2589-01-023, ETC.  
 AT CEDAR CREEK AND CEDAR CREEK RELIEF BRIDGE REPLACEMENTS.  
 REF NO. 28 ON US 287 INCLUDES LIMITS ON NB AND SB ROADBEDS WHERE DIVIDED HIGHWAY EXISTS

LEGEND	
RA - RAMP	INT - STATE MAINTAINED ROAD

PROJECT INFORMATION AND SURFACE AREAS

 TEXAS DEPARTMENT OF TRANSPORTATION ©2022			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		7



SUMMARY OF SURFACE TREATMENT

PROJ. REF. NO.	COUNTY	2020 AADT	% TRUCKS	SAC REQUIREMENT	HIGHWAY	CSJ NO.	TOTAL AREA TO BE SEALED	ITEM NO					
								BID CODE					
								316	316	316	316	316	316
								6048	6124	6402	6126	6003	6003
								ASPH (AC-20-5TR)	AGGR (TY-PB GR-3 SAC-A)	AGGR (TY-PE, E, L OR PL GR 3)	AGGR (TY-PB GR-4 SAC-A)	AGGR (LOAD HAUL & DISTRIB)	AGGR (LOAD HAUL & DISTRIB)
								SY	1 CY/115 SY	1 CY/120 SY	1 CY/135 SY	1 CY/135 SY	1 CY/115 SY
								TON	CY	CY	CY	CY	CY
1	SABINE	1696	34.4	A	SH 87	0304-04-046	174,082	281			1,290		
2	SABINE	2421	27.7	B	FM 2426	2268-01-018	134,871	161		1,124			
3	SHELBY	6640	8.4	A	SH 87	0064-01-069	245,659	397			1,820		
4	SHELBY	4086	11.3	A	SH 87	0304-07-024	303,320	490			2,247		
5	HOUSTON	2059	29.1	A	SH 21	0118-01-023	137,323	164		1,145			
6	HOUSTON	1016	25.3	A	SH 21	0118-02-037	37,920	46		316			
7	HOUSTON	2214	30.4	A	US 287	0340-01-045	219,315	354			1,625		
8	HOUSTON	1156	10.6	A	FM 227	0937-02-035	155,237	251			1,150		
9	TRINITY	2438	17.4	A	SH 94	0319-02-032	141,603	229			1,049		
10	TRINITY	3035	17.4	A	SH 94	0319-03-054	267,290	432			1,980		
11	POLK	6654	10.2	A	FM 356	0475-11-039	97,419	158			722		
12	POLK	4967	7.2	A	FM 350	0928-01-015	76,392	124			566		
13	POLK	2431	9.2	B	FM 3126	3160-03-009	41,581	68			309		
14	ANGELINA	2797	9.7	A	SH 147	0390-03-037	167,710	271			1,243		
15	ANGELINA	562	18.7	A	FM 1818	1794-01-026	201,091	325			1,490		
16	ANGELINA	2505	3.5	B	FM 2497	2589-01-026	124,366	201			922		
17	NACOGDOCHES	2846	13	A	FM 225	0594-04-029	222,355	359			1,648		
18	NACOGDOCHES	1891	8.7	B	FM 225	1810-02-026	147,402	238			1,092		
19	NACOGDOCHES	2255	5.5	A	FM 343	2300-01-022	215,857	257		1,799			
20	NACOGDOCHES	2579	15.5	A	SH 21	0118-08-086	52,926	86			393		
21	SAN AUGUSTINE	1139	13.3	A	SL 547	0118-09-009	21,528	35			160		
22	NACOGDOCHES	1344	11.2	B	SL 34	0118-11-009	8,080	14			60		
23	SAN AUGUSTINE	528	14.3	A	FM 353	0118-12-021	89,829	145			666		
24	SHELBY	152	11.8	B	FM 353	0118-13-015	34,241	56			254		
25	NACOGDOCHES	959	5	B	FM 95	0706-05-013	109,423	177			811		
26	SAN JACINTO	6953	10.4	A	SH 150	0395-02-048	196,098	317			1,453		
27	SAN JACINTO	984	10.2	A	FM 980	2443-02-018	209,841	250		1,749			
28	HOUSTON	7109	11.6	A	US 287	0109-03-042	49,279	59	429				
29	ANGELINA	5653	11.4		FM 325	0319-05-019	47,780	57				354	
30	ANGELINA	3204	23.8		SH 63	0244-01-048	79,067	95					688
<b>PROJECT TOTALS</b>							<b>4,008,884</b>	<b>6,097</b>	<b>429</b>	<b>6,133</b>	<b>22,950</b>	<b>354</b>	<b>688</b>

SEE GENERAL NOTES FOR CONSTRUCTION SEQUENCING

NOTE: REF NO. 16 ON FM 2497 - EXCEPTION FOR PREVIOUS CONSTRUCTION PROJECT 2589-01-023, ETC. AT CEDAR CREEK AND CEDAR CREEK RELIEF BRIDGE REPLACEMENTS.  
REF NO. 28 ON US 287 INCLUDES LIMITS ON NB AND SB ROADBEDS WHERE DIVIDED HIGHWAY EXISTS

ASPHALTS ESTIMATED AT THE FOLLOWING RATES:

AC-20-5TR AT 0.28 GAL/SY FOR GR 3 AGGREGATE


AC-20-5TR AT 0.38 GAL/SY FOR GR 4 AGGREGATE

$$\text{TONS} = \frac{\text{RATE} * (\text{SGA}) * \text{SY}}{2000}$$

SPECIFIC GRAVITY OF ASPHALT

(SGA) ESTIMATED AT 1.02 \* 8.3268

QUANTITY SUMMARIES

 TEXAS DEPARTMENT OF TRANSPORTATION ©2022 SHEET 1 OF 4			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		8

SUMMARY OF MISCELLANEOUS TCP		
ITEM NO	6185	6001
BID CODE	6005	6001
CSJ NO.	TMA (MOBILE OPERATION)	PORTABLE CHANGEABLE MESSAGE SIGN
	DAY	DAY
0064-01-069, ETC	214	10
<b>PROJECT TOTALS</b>	<b>214</b>	<b>10</b>

**NOTE:**

MESSAGE BOARDS TO BE USED DAILY AND SHALL BE UTILIZED ON US 287, SH 21, SH 87, SH 94, SH 150 AND AT LOCATIONS AS DIRECTED BY THE ENGINEER.


SUMMARY OF WORK ZONE PAVEMENT MARKINGS						
ITEM NO				662	662	
BID CODE				6109	6111	
PROJ. REF. NO.	COUNTY	HIGHWAY	CSJ NO.	LENGTH	WK ZN PAV MRK SHT TERM (TAB)TY W	WK ZN PAV MRK SHT TERM (TAB)TY Y-2
				FT	EA	EA
1	SABINE	SH 87	0304-04-046	50,424		1,287
2	SABINE	FM 2426	2268-01-018	49,109		1,228
3	SHELBY	SH 87	0064-01-069	51,665	693	1,329
4	SHELBY	SH 87	0304-07-024	80,747	195	2,080
5	HOUSTON	SH 21	0118-01-023	40,313		1,008
6	HOUSTON	SH 21	0118-02-037	13,126		329
7	HOUSTON	US 287	0340-01-045	68,429	198	1,711
8	HOUSTON	FM 227	0937-02-035	62,769		1,570
9	TRINITY	SH 94	0319-02-032	42,816		1,071
10	TRINITY	SH 94	0319-03-054	78,371		1,960
11	POLK	FM 356	0475-11-039	28,565		851
12	POLK	FM 350	0928-01-015	26,833		671
13	POLK	FM 3126	3160-03-009	14,393		360
14	ANGELINA	SH 147	0390-03-037	33,982	261	924
15	ANGELINA	FM 1818	1794-01-026	66,544		1,674
16	ANGELINA	FM 2497	2589-01-026	41,591		1,040
17	NACOGDOCHES	FM 225	0594-04-029	82,732		2,069
18	NACOGDOCHES	FM 225	1810-02-026	53,603		1,341
19	NACOGDOCHES	FM 343	2300-01-022	79,807	6	2,002
20	NACOGDOCHES	SH 21	0118-08-086	16,405	86	425
21	SAN AUGUSTINE	SL 547	0118-09-009	6,299		158
22	NACOGDOCHES	SL 34	0118-11-009	3,305		83
23	SAN AUGUSTINE	FM 353	0118-12-021	36,379		910
24	SHELBY	FM 353	0118-13-015	14,008		351
25	NACOGDOCHES	FM 95	0706-05-013	44,764		1,120
26	SAN JACINTO	SH 150	0395-02-048	39,679	313	1,118
27	SAN JACINTO	FM 980	2443-02-018	78,466		1,962
28	HOUSTON	US 287	0109-03-042	17,266	53	432
29	ANGELINA	FM 325	0319-05-019	9,773	978	489
30	ANGELINA	SH 63	0244-01-048	26,400	83	660
<b>PROJECT TOTALS</b>					<b>2,866</b>	<b>32,213</b>

NOTE: REF NO. 16 ON FM 2497 - EXCEPTION FOR PREVIOUS CONSTRUCTION PROJECT 2589-01-023, ETC.

AT CEDAR CREEK AND CEDAR CREEK RELIEF BRIDGE REPLACEMENTS.

REF NO. 28 ON US 287 INCLUDES LIMITS ON NB AND SB ROADBEDS WHERE DIVIDED HIGHWAY EXISTS

**QUANTITY SUMMARIES**

 TEXAS DEPARTMENT OF TRANSPORTATION ©2022 SHEET 2 OF 4			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		9


**SUMMARY OF PAVEMENT MARKINGS**

PROJ. REF. NO.	COUNTY	HIGHWAY	CSJ NO.	ITEM NO	666	666	666	666	666	677	677	677	677	677	677
				BID CODE	6171	6174	6178	6208	6210	6001	6006	6007	6008	6012	6016
				LENGTH	REFL PAV MRK TY II (W) 6" (BRK)	REFL PAV MRK TY II (W) 6" (SLD)	REFL PAV MRK TY II (W) 8" (SLD)	REFL PAV MRK TY II (Y) 6" (BRK)	REFL PAV MRK TY II (Y) 6" (SLD)	ELIM EXT PAV MRK & MRKS (4")	ELIM EXT PAV MRK & MRKS (18")	ELIM EXT PAV MRK & MRKS (24")	ELIM EXT PAV MRK & MRKS (ARROW)	ELIM EXT PAV MRK & MRKS (WORD)	ELIM EXT PAV MRK & MRKS (RR XING)
	LF	LF	LF	LF	LF	LF	LF	LF	LF	LF	EA	EA	EA		
1	SABINE	SH 87	0304-04-046	50,424		100,860	80	4,330	84,037	189,227			1	1	
2	SABINE	FM 2426	2268-01-018	49,109		98,220		4,400	79,927	182,547		64			2
3	SHELBY	SH 87	0064-01-069	51,665	13,860	103,330	865	380	107,086	32,500	24	702	8	8	2
4	SHELBY	SH 87	0304-07-024	80,747	1,770	161,464	122	11,410	116,118		72	410	2	2	2
5	HOUSTON	SH 21	0118-01-023	40,313	120	81,904		4,250	63,694			25			
6	HOUSTON	SH 21	0118-02-037	13,126		26,254	122	1,460	18,642				1	1	
7	HOUSTON	US 287	0340-01-045	68,429	3,380	101,778		5,900	72,519	1,413		25			
8	HOUSTON	FM 227	0937-02-035	62,769		125,538		2,790	112,819	760		44			
9	TRINITY	SH 94	0319-02-032	42,816		85,632	312	6,750	50,213	142,595	55	211	4	4	
10	TRINITY	SH 94	0319-03-054	78,371		157,418		11,780	98,410	270,830	90				
11	POLK	FM 356	0475-11-039	28,565		50,720	164	4,720	45,382	100,822	90		5		
12	POLK	FM 350	0928-01-015	26,833		53,666	825	2,130	28,396	84,192	34	112	4	4	
13	POLK	FM 3126	3160-03-009	14,393		28,788		1,740	20,147	50,675		46			
14	ANGELINA	SH 147	0390-03-037	33,982	4,890	67,966	143	4,910	52,163				7	1	
15	ANGELINA	FM 1818	1794-01-026	66,544		133,088		11,460	72,230	217,943		162			
16	ANGELINA	FM 2497	2589-01-026	41,591		83,184		5,330	58,153	146,667		57			2
17	NACOGDOCHES	FM 225	0594-04-029	82,732		165,244		3,300	150,550	319,094	48	27			
18	NACOGDOCHES	FM 225	1810-02-026	53,603		107,206		5,530	82,626	197,122					
19	NACOGDOCHES	FM 343	2300-01-022	79,807		150,260		8,400	112,498	271,158		15			
20	NACOGDOCHES	SH 21	0118-08-086	16,405	850	32,378	270	430	30,689	63,497			2	2	
21	SAN AUGUSTINE	SL 547	0118-09-009	6,299		11,884			11,544			311	2	2	2
22	NACOGDOCHES	SL 34	0118-11-009	3,305		804			6,506			10			
23	SAN AUGUSTINE	FM 353	0118-12-021	36,379				910	69,698			22			
24	SHELBY	FM 353	0118-13-015	14,008				650	26,512	27,162		20			
25	NACOGDOCHES	FM 95	0706-05-013	44,764		89,444		4,890	67,086	500	48	46			
26	SAN JACINTO	SH 150	0395-02-048	39,679	2,090	75,568	693	4,580	63,719	1,374	18	100	3	7	
27	SAN JACINTO	FM 980	2443-02-018	78,466		154,018	105	11,200	99,093	1,550		15			
28	HOUSTON	US 287	0109-03-042	17,266	3,670	19,600			21,682						
29	ANGELINA	FM 325	0319-05-019	9,773	4,910	19,547	200		19,547			108	2	2	
30	ANGELINA	SH 63	0244-01-048	26,400	840	52,800		4,110	26,884						
<b>PROJECT TOTALS</b>					<b>36,380</b>	<b>2,338,563</b>	<b>3,901</b>	<b>127,740</b>	<b>1,868,570</b>	<b>2,301,628</b>	<b>479</b>	<b>2,532</b>	<b>41</b>	<b>34</b>	<b>10</b>

NOTE: REF NO. 16 ON FM 2497 - EXCEPTION FOR PREVIOUS CONSTRUCTION PROJECT 2589-01-023, ETC.  
 AT CEDAR CREEK AND CEDAR CREEK RELIEF BRIDGE REPLACEMENTS.  
 REF NO. 28 ON US 287 INCLUDES LIMITS ON NB AND SB ROADBEDS WHERE DIVIDED HIGHWAY EXISTS

9/29/2022 10:46:06 AM c:\txdot\pwworking\lne\ltxdot3\cathy.l\oerch\d0408470\dsums 3. dgm

**QUANTITY SUMMARIES**



TEXAS DEPARTMENT OF TRANSPORTATION  
©2022 SHEET 3 OF 4


CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		10

**SUMMARY OF PREFAB & RAISED PAVEMENT MARKINGS**

PROJ. REF. NO.	COUNTY	HIGHWAY	CSJ NO.	ITEM NO	668	668	668	668	668	668	672	672
				BID CODE	6075	6076	6077	6085	6089	6108	6007	6009
				LENGTH	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (RR XING)	PREFAB PAV MRK TY C (Y) (24") (SLD)	REFL PAV MRKR TY I-C	REFL PAV MRKR TY II-A-A
LF	LF	LF	EA	EA	EA	LF	EA	EA				
1	SABINE	SH 87	0304-04-046	50,424			1	1			5	1,313
2	SABINE	FM 2426	2268-01-018	49,109		60				2		1,234
3	SHELBY	SH 87	0064-01-069	51,665	24	132	8	8	2	570	179	1,708
4	SHELBY	SH 87	0304-07-024	80,747	72	130	2	2	2	280	35	2,265
5	HOUSTON	SH 21	0118-01-023	40,313		25					4	1,023
6	HOUSTON	SH 21	0118-02-037	13,126			1	1			8	320
7	HOUSTON	US 287	0340-01-045	68,429		25					47	1,286
8	HOUSTON	FM 227	0937-02-035	62,769		44						1,553
9	TRINITY	SH 94	0319-02-032	42,816	55	211	4	4			17	1,026
10	TRINITY	SH 94	0319-03-054	78,371	90							1,865
11	POLK	FM 356	0475-11-039	28,565	40	156	9	4			10	870
12	POLK	FM 350	0928-01-015	26,833	34	112	4	4			45	608
13	POLK	FM 3126	3160-03-009	14,393		46						344
14	ANGELINA	SH 147	0390-03-037	33,982			7	1			73	1,105
15	ANGELINA	FM 1818	1794-01-026	66,544		39				123		1,613
16	ANGELINA	FM 2497	2589-01-026	41,591		57		2				1,016
17	NACOGDOCHES	FM 225	0594-04-029	82,732	48	27						2,061
18	NACOGDOCHES	FM 225	1810-02-026	53,603								1,329
19	NACOGDOCHES	FM 343	2300-01-022	79,807		15						1,881
20	NACOGDOCHES	SH 21	0118-08-086	16,405			2	2			29	422
21	SAN AUGUSTINE	SL 547	0118-09-009	6,299		311	2	2	2			150
22	NACOGDOCHES	SL 34	0118-11-009	3,305		10						84
23	SAN AUGUSTINE	FM 353	0118-12-021	36,379		22						920
24	SHELBY	FM 353	0118-13-015	14,008		20						367
25	NACOGDOCHES	FM 95	0706-05-013	44,764	48	46						1,101
26	SAN JACINTO	SH 150	0395-02-048	39,679	18	100	3	7			68	1,526
27	SAN JACINTO	FM 980	2443-02-018	78,466		15					7	1,889
28	HOUSTON	US 287	0109-03-042	17,266							185	247
29	ANGELINA	FM 325	0319-05-019	9,773		108	2	2			284	122
30	ANGELINA	SH 63	0244-01-048	26,400							45	757
<b>PROJECT TOTALS</b>					<b>429</b>	<b>1,711</b>	<b>45</b>	<b>38</b>	<b>10</b>	<b>973</b>	<b>1,041</b>	<b>32,005</b>

NOTE: REF NO. 16 ON FM 2497 - EXCEPTION FOR PREVIOUS CONSTRUCTION PROJECT 2589-01-023, ETC.  
 AT CEDAR CREEK AND CEDAR CREEK RELIEF BRIDGE REPLACEMENTS.  
 REF NO. 28 ON US 287 INCLUDES LIMITS ON NB AND SB ROADBEDS WHERE DIVIDED HIGHWAY EXISTS

**QUANTITY SUMMARIES**

 TEXAS DEPARTMENT OF TRANSPORTATION ©2022 SHEET 4 OF 4			
CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		11

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:23:46 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\g0408474\bc-21.dgn

**BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:**

- The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
- The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
- The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
- Traffic control devices should be in place only while work is actually in progress or a definite need exists.
- The Engineer has the final decision on the location of all traffic control devices.
- Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

**WORKER SAFETY NOTES:**


- Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
- Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

**COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES**

- Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
- Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).

<b>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT</b> <a href="http://www.txdot.gov">http://www.txdot.gov</a>
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS


SHEET 1 OF 12

 Texas Department of Transportation		Traffic Safety Division Standard
<b>BARRICADE AND CONSTRUCTION          GENERAL NOTES          AND REQUIREMENTS</b>		
<b>BC (1) - 21</b>		
FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT: 0064	SECT: 01
	JOB: 069, ETC	
	HIGHWAY: SH 87, ETC	
REVISIONS	DIST	COUNTY
4-03 7-13		
9-07 8-14		
5-10 5-21	LFK	SHELBY, ETC
		SHEET NO. 12

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 8/3/2022 8:23:47 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\g0408474\bc-21.dgn

**TYPICAL LOCATION OF CROSSROAD SIGNS**



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
  - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
  - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
  - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
  - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
  - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

**T-INTERSECTION**



**CSJ LIMITS AT T-INTERSECTION**

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

**TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING<sup>1,5,6</sup>**

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Δ Spacing "x" Feet (Apprx.)
CW20 <sup>4</sup>	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25			50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14	48" x 48"	48" x 48"	55	500 <sup>2</sup>
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12			60	600 <sup>2</sup>
			65	700 <sup>2</sup>
			70	800 <sup>2</sup>
			75	900 <sup>2</sup>
	80	1000 <sup>2</sup>		
	*	*	*	* <sup>3</sup>


\* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

**GENERAL NOTES**


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

**WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS**




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS**



**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS**



**NOTES**

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
  - CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
  - Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
  - Contractor will install a regulatory speed limit sign at the end of the work zone.

LEGEND	
—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12

Texas Department of Transportation  
Traffic Safety Division Standard

**BARRICADE AND CONSTRUCTION PROJECT LIMIT**


**BC (2) - 21**

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	LFK	SHELBY, ETC	13	

# TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



## GUIDANCE FOR USE:

### LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

### SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

## GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:
 

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
  - Law enforcement.
  - Flagger stationed next to sign.
  - Portable changeable message sign (PCMS).
  - Low-power (drone) radar transmitter.
  - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:23:49 PM  
FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\bc-21.dgn

SHEET 3 OF 12




## BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC (3) - 21

FILE:	bc-21.dgn	DW:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0064	01	069, ETC	SH 87, ETC				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	LFK	SHELBY, ETC	14					

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


**TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS**



\* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

\*\* When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

**ATTACHMENT FOR SIGN SUPPORTS**



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

**GENERAL NOTES FOR WORK ZONE SIGNS**

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

**DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)**

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
  - Long-term stationary - work that occupies a location more than 3 days.
  - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
  - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
  - Short, duration - work that occupies a location up to 1 hour.
  - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

**SIGN MOUNTING HEIGHT**

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

**SIZE OF SIGNS**

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

**SIGN SUBSTRATES**

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

**REFLECTIVE SHEETING**

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B<sub>FL</sub> or Type C<sub>FL</sub>, shall be used for rigid signs with orange backgrounds.

**SIGN LETTERS**

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

**REMOVING OR COVERING**

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

**SIGN SUPPORT WEIGHTS**


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

**FLAGS ON SIGNS**

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

**STOP/SLOW PADDLES**

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflective when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B <sub>FL</sub> OR C <sub>FL</sub> SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

**CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS**

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.



**BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES**


**BC (4) - 21**

FILE:	bc-21.dgn	DN:	TxDOT	CR:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0064	01	069, ETC	SH	87, ETC			
9-07	8-14	DIST	COUNTY		SHEET NO.				
7-13	5-21	LFK	SHELBY, ETC		15				

DATE: 8/3/2022 8:23:50 PM  
 FILE: c:\txdot\p\_w\_online\txdot\catny\_loerch\40408474\bc-21.dgn





DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




### SKID MOUNTED WOOD SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS





### GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



### SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



### WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

### OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

### GENERAL NOTES

1. Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
2. No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
3. When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.

- \* See BC(4) for definition of "Work Duration."
- \*\* Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
- See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



## BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CR:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0064	01	069, ETC	SH 87, ETC				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	LFK	SHELBY, ETC	16					

DATE: 8/3/2022 8:23:52 PM  
FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408474\bc-21.dgn

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

# RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

## PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

## Phase 1: Condition Lists

### Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT
RIGHT X LANES CLOSED	RIGHT X LANES OPEN
CENTER LANE CLOSED	DAYTIME LANE CLOSURES
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE
EXIT CLOSED	RIGHT LN TO BE CLOSED
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI
XXXXXXXXX BLVD CLOSED	

### Other Condition List

ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT *

\* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

## Phase 2: Possible Component Lists

### Action to Take/Effect on Travel List

MERGE RIGHT	FORM X LINES RIGHT
DETOUR NEXT X EXITS	USE XXXXX RD EXIT
USE EXIT XXX	USE EXIT I-XX NORTH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N
TRUCKS USE US XXX N	WATCH FOR TRUCKS
WATCH FOR TRUCKS	EXPECT DELAYS
EXPECT DELAYS	PREPARE TO STOP
REDUCE SPEED XXX FT	END SHOULDER USE
USE OTHER ROUTES	WATCH FOR WORKERS
STAY IN LANE *	

### Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXXX TO XXXXXXX
US XXX TO FM XXXX

### Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

### \*\* Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

\*\* See Application Guidelines Note 6.

## APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

## WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

## FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:23:54 PM  
FILE: c:\txdot\p\_w\_online\txdot3\catny\_loerch\40408474\bc-21.dgn

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy Vehicle	HOV	Tuesday	TUES
Highway	HWY	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT


Roadway designation # IH-number, US-number, SH-number, FM-number

<h3>BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)</h3>			
<h2>BC (6) - 21</h2>			
FILE:	bc-21.dgn	DN:	TxDOT
© TxDOT	November 2002	CR:	TxDOT
REVISIONS	0064 01	DW:	TxDOT
9-07	8-14	OW:	TxDOT
7-13	5-21	CK:	TxDOT
		CONT	SECT
		JOB	HIGHWAY
		0064 01	069, ETC
		DIST	SH 87, ETC
		COUNTY	SHEET NO.
		LFK	SHELBY, ETC
			17

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 8/3/2022 8:23:55 PM  
 FILE: c:\txdot\p\_w\_online\txdot3\catny\_loerch\0408474\bc-21.dgn

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.



**CONCRETE TRAFFIC BARRIER (CTB)**

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.




**LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES**

LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

Max. spacing of barrier reflectors is 20 feet. Attach the delineators as per manufacturer's recommendations.

**LOW PROFILE CONCRETE BARRIER (LPCB)**



Install a minimum of 3 Barrier Reflectors as per manufacturer's recommendations.

**DELINEATION OF END TREATMENTS**

**END TREATMENTS FOR CTB'S USED IN WORK ZONES**

End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

**BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS**

**WARNING LIGHTS**


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B<sub>FL</sub> or C<sub>FL</sub> Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

**WARNING LIGHTS MOUNTED ON PLASTIC DRUMS**


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

**WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS**

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.




Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

**ATTENTION**  
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

**FLASHING ARROW BOARDS**

SHEET 7 OF 12

**TRUCK-MOUNTED ATTENUATORS**

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



**BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR**

**BC (7) -21**

FILE:	bc-21.dgn	DN:	TxDOT	CR:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0064	01	069, ETC	SH 87, ETC				
9-07	8-14	DIST	COUNTY		SHEET NO.				
7-13	5-21	LFK	SHELBY, ETC		18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:23:57 PM  
 FILE: c:\txdot\pw\_online\txdot3\caty\loerch\0408474\bc-21.dgn

**GENERAL NOTES**

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

**GENERAL DESIGN REQUIREMENTS**

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectORIZED space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

**RETROREFLECTIVE SHEETING**

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.

**BALLAST**

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.



**DETECTABLE PEDESTRIAN BARRICADES**

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign  
(Maximum Sign Dimension)  
Chevron CW1-8, Opposing Traffic Lane  
Divider, Driveway sign D70a, Keep Right  
R4 series or other signs as approved  
by Engineer



12" x 24"  
Vertical Panel  
mount with diagonals  
sloping down towards  
travel way

Plywood, Aluminum or Metal sign  
substrates shall NOT be used on  
plastic drums

**SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS**

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B<sub>FL</sub> or Type C<sub>FL</sub> Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (8) - 21**

FILE:	bc-21.dgn	DW:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0064	01	069, ETC	SH 87, ETC				
4-03	8-14	DIST	COUNTY	SHEET NO.					
9-07	5-21	LFK	SHELBY, ETC	19					
7-13									


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:23:58 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408474\bc-21.dgn



**FIXED**  
(Rigid or self-righting)


**DRIVEABLE**



**PORTABLE**


**VERTICAL PANELS (VPs)**

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.



**OPPOSING TRAFFIC LANE DIVIDERS (OTLD)**


- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



Fixed Base w/ Approved Adhesive (Driveable Base, or Flexible Support can be used)

- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

**CHEVRONS**



**LONGITUDINAL CHANNELIZING DEVICES (LCD)**

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

**WATER BALLASTED SYSTEMS USED AS BARRIERS**

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long cones and the top of the unit shall not be less than 32 inches in height.

**HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS**

**GENERAL NOTES**

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

\*\*Taper lengths have been rounded off.  
 L=Length of Taper (FT.) W=Width of Offset (FT.)  
 S=Posted Speed (MPH)

**SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS**

SHEET 9 OF 12



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (9) - 21**

FILE: bc-21.dgn	DW: TxDOT	CR: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	LFK	SHELBY, ETC	20	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:00 PM  
 FILE: c:\txdot\p\_w\_online\txdot3\catny\_loerch\0408474\bc-21.dgn


**TYPE 3 BARRICADES**

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




**TYPICAL STRIPING DETAIL FOR BARRICADE RAIL**




Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.

**TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES**




**TRAFFIC CONTROL FOR MATERIAL STOCKPILES**

Each roadway of a divided highway shall be barricaded in the same manner.



**PERSPECTIVE VIEW**


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.



**PLAN VIEW**


1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

**TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION**



**PERSPECTIVE VIEW**

These drums are not required on one-way roadway




**PLAN VIEW**

Increase number of plastic drums on the side of approaching traffic if the crown width makes it necessary. (minimum of 2 and maximum of 4 drums)

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector

**CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS**



Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.  
 42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (10) -21**

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	LFK	SHELBY, ETC	21	

## WORK ZONE PAVEMENT MARKINGS

### GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

### RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

### PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


### MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

### REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

## Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE  
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER  
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
  - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
  - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

### RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:  
 YELLOW - (two amber reflective surfaces with yellow body).  
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS


**BC(11)-21**

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS		0064	01	069, ETC
2-98	9-07	5-21		
1-02	7-13			
11-02	8-14			
	DIST	COUNTY	SHEET NO.	
	LFK	SHELBY, ETC	<b>22</b>	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:02 PM  
FILE: c:\txdot\pw\_online\txdot\catny\_loerch\0408474\bc-21.dgn

## PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TxDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

## CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

## EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

## LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectORIZED pavement markings.





RAISED PAVEMENT MARKERS

## TWO-WAY LEFT TURN LANE


## STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS




### SOLID LINES



### BROKEN LINES




### AUXILIARY OR LANEDROP LINE



### REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC(12)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
1-97 9-07 5-21	DIST	COUNTY	SHEET NO.	
2-98 7-13	LFK	SHELBY, ETC	23	
11-02 8-14				

Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:03 PM  
FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408474\bc-21.dgn




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:11 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408474\tcp3-1.dgn



TCP (3-1a)  
**UNDIVIDED MULTILANE ROADWAY**




**TRAIL/SHADOW VEHICLE A**  
 with RIGHT Directional display Flashing Arrow Board

LEGEND			
*	Trail Vehicle	ARROW BOARD DISPLAY	
**	Shadow Vehicle		
***	Work Vehicle		RIGHT Directional
	Heavy Work Vehicle		LEFT Directional
	Truck Mounted Attenuator (TMA)		Double Arrow
	Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)


TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**GENERAL NOTES**


1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used the WORK vehicle must be equipped with an arrow board. The Engineer will determine if the LEAD VEHICLE and/or TRAIL VEHICLE are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE are required.
4. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
5. Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
6. Each vehicle shall have two-way radio communication capability.
7. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
8. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
9. "X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY" (CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
10. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the rearmost protection vehicle.




TCP (3-1b)  
**TWO-WAY ROADWAY WITH PAVED SHOULDERS**



**TRAIL/SHADOW VEHICLE B**  
 with Flashing Arrow Board in CAUTION display



TCP (3-1c)  
**TWO-WAY ROADWAY WITHOUT PAVED SHOULDERS**



**STRIPING FOR TMA**

Texas Department of Transportation  
 Traffic Operations Division Standard



**TRAFFIC CONTROL PLAN  
 MOBILE OPERATIONS  
 UNDIVIDED HIGHWAYS**

**TCP (3-1) - 13**



FILE: tcp3-1.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
2-94 4-98				
8-95 7-13				
1-97				
DIST	COUNTY	SHEET NO.		
LFK	SHELBY, ETC	24		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:19 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408474\tcp3-2.dgn



**RIGHT LANE CLOSURE ON DIVIDED HIGHWAY - TCP(3-2a)**




**INTERIOR LANE CLOSURE ON MULTI-LANE DIVIDED HIGHWAY - TCP(3-2b)**

LEGEND			
*	Trail Vehicle	ARROW BOARD DISPLAY	
**	Shadow Vehicle		
***	Work Vehicle	→	RIGHT Directional
☐	Heavy Work Vehicle	←	LEFT Directional
▲	Truck Mounted Attenuator (TMA)	↔	Double Arrow
↶	Traffic Flow	⚠	CAUTION (Alternating Diamond or 4 Corner Flash)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

**GENERAL NOTES**

- ADVANCE WARNING, TRAIL and SHADOW vehicles shall be equipped with Type B or Type C flashing arrow boards as per the Barricade and Construction (BC) standards. Arrow boards on WORK vehicles will be optional based on the type of work being performed. The arrow boards shall be operated from inside the vehicle.
- For TCP(3-2a) the Engineer will determine if the TRAIL VEHICLE is required based on prevailing roadway conditions, traffic volume, and sight distance restrictions. All other vehicles shown for both TCP(3-2a) and TCP(3-2b) are required.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the ADVANCE WARNING, SHADOW, and TRAIL vehicles are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DMS 8300, Type A.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE may vary according to terrain, work activity and other factors.
- Standard 48" X 48" diamond shaped warning signs with the same message as those shown may be used where adequate mounting space exists.
- The signs shown should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or a truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board, must be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
- Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
- The principles on this sheet may be used to close lanes from the left side of the roadway considering the number of lanes, shoulder width, sight distance, and ramp frequency.
- Signs and flashing arrow board modes shall be appropriately altered when implementing left lane closures or interior closures which close the left lanes.
- The Advance Warning Vehicle may straddle the edgeline when shoulder width makes it necessary.



**STRIPING FOR TMA**

Texas Department of Transportation  
 Traffic Operations Division Standard









**TRAFFIC CONTROL PLAN  
 MOBILE OPERATIONS  
 DIVIDED HIGHWAYS**

**TCP(3-2)-13**

FILE: tcp3-2.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	LFK	SHELBY, ETC	25	
1-97				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:29 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\tcp3-3.dgn



LEGEND		
* Trail Vehicle		ARROW BOARD DISPLAY
** Shadow Vehicle		
*** Work Vehicle		RIGHT Directional
		LEFT Directional
		Double Arrow
		CAUTION (Alternating Diamond or 4 Corner Flash)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**GENERAL NOTES**

1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used on two way roads the WORK vehicle must have an arrow board. For divided roadways, the arrow board on the WORK vehicle is optional based on the type of work being performed. The Engineer will determine if the LEAD vehicle and/or TRAIL vehicle are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating, or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE, ADVANCE WARNING and TRAIL VEHICLE are required.
4. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
5. Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
6. Each vehicle shall have two-way radio communication capability.
7. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
8. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
9. X VEHICLE CONVOY (CW21-10cT) or WORK CONVOY (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" x 48" diamond shaped WORK CONVOY (CW21-10T) or X VEHICLE CONVOY (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The X VEHICLE CONVOY sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
10. For divided highways with two or three lanes in one direction, the appropriate LEFT LANE CLOSED (CW20-5bTL), RIGHT LANE CLOSED (CW20-5bTR), or CENTER LANE CLOSED (CW20-5dT) sign should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board may be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
11. A double arrow shall not be displayed on the arrow board on the Advance Warning Vehicle.
12. For divided highways with three or four lanes in each direction, use TCP(3-2).
13. Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
14. The Advance Warning Vehicle may straddle the edgeline when Shoulder width makes it necessary.
15. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a DO NOT PASS (R4-1) sign should be placed on the back of the rearmost protection vehicle.




Texas Department of Transportation

**TRAFFIC CONTROL PLAN  
 MOBILE OPERATIONS  
 RAISED PAVEMENT  
 MARKER INSTALLATION/  
 REMOVAL  
 TCP (3-3) - 14**

FILE: tcp3-3.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT September 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069,ETC	SH 87, ETC
2-94 4-98	DIST	COUNTY	SHEET NO	
8-95 7-13	LFK	SHELBY, ETC	26	
1-97 7-14				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



LEGEND		
*	Trail Vehicle	ARROW BOARD DISPLAY
**	Shadow Vehicle	
***	Work Vehicle	RIGHT Directional
	Heavy Work Vehicle	LEFT Directional
	Truck Mounted Attenuator (TMA)	Double Arrow
	Traffic Flow	Channelizing Devices


Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

**GENERAL NOTES**

1. This traffic control plan is for use on conventional roads posted at 45 mph or less and is intended for mobile operations that move continuously or intermittently (stopping up to approximately 15 minutes) such as short-line striping and in-lane rumble strips. When activities are anticipated to take longer amounts of time or traffic conditions warrant, a short duration or short-term stationary traffic control plan should be used.
2. A Truck Mounted Attenuator shall be used on Shadow Vehicle. Striping on the back panel of all truck mounted attenuators shall be 8" red and white reflective sheeting placed in an inverted "V" design. Reflective sheeting shall meet or exceed the reflectivity and color requirements of departmental material specification DMS-8300, Type A.
3. All traffic control devices shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD), latest edition.
4. The use of yellow rotating beacons or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the drivers side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
5. Flashing arrow board shall be used on Shadow Vehicle. Flashing arrow board shall be Type B or Type C as per BC Standards. The arrow board operation shall be controlled from inside the truck.



Texas Department of Transportation  
 Traffic Operations Division Standard


**TRAFFIC CONTROL PLAN  
 MOBILE OPERATIONS FOR  
 ISOLATED WORK AREAS  
 UNDIVIDED HIGHWAYS**

**TCP(3-4)-13**


FILE: tcp3-4.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT July, 2013	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
	DIST	COUNTY	SHEET NO.	
	LFK	SHELBY, ETC	27	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:47 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\tcpsc-1-21.dgn



TCP (SC-1a)  
**ONE LANE TWO-WAY (2 LANES)  
 CONTROL WITH PILOT VEHICLE**



TCP (SC-1b)  
**ONE LANE TWO-WAY (3 LANES)  
 CONTROL WITH PILOT VEHICLE  
 AND CHANNELIZING DEVICES**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

**GENERAL NOTES**

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work when approved by the Engineer.
- The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
- Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger sign is less than 1500 feet.
- Flaggers should use two-way radios or other methods of communication at all times to control traffic.
- Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.
- If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
- If the seal coat operation crosses intersections, traffic in these areas must be controlled. Care must be taken to prevent vehicles from crossing the asphalt before the aggregate is placed. This may require positioning other member of the traffic control crew at the intersection.
- Temporary rumble strips are not required on seal coat operations.
- Pilot car is used to guide vehicles through traffic control zone, vehicle shall have an identification name displayed and "PILOT CAR, FOLLOW ME" (G20-4) sign or message board mounted in a conspicuous position on rear.

**TCP (SC-1a)**



- Channelizing devices on the center-line may be omitted when a pilot car is leading traffic.

SHEET 1 OF 7

		Traffic Safety Division Standard	
<b>TRAFFIC CONTROL PLAN SEAL COAT OPERATIONS</b>			
<b>TCP (SC-1) - 21</b>			
FILE: tcpsc-1-21.dgn	DN:	CK:	DW: CK:
© TxDOT	April 2021	CONT	SECT JOB HIGHWAY
REVISIONS	0064	01	069, ETC SH 87, ETC
DIST	COUNTY	SHEET NO	
LFK	SHELBY, ETC	28	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:24:56 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408474\tcpsc-2-21.dgn



LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	$L = WS$	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

**GENERAL NOTES**

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The CW20-1D "ROAD WORK AHEAD" sign may be repeated if the visibility of the work zone is less than 1500 feet.
- If the seal coat operation crosses intersections, traffic in these areas must be controlled. Care must be taken to prevent vehicles from crossing the asphalt before the aggregate is placed. This may require positioning other member of the traffic control crew at the intersection.
- Temporary rumble strips are not required on seal coat operations.

**TCP (SC-2a)**


- Where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the posted speed in mph. This tighter device spacing is intended for the areas of conflicting markings, not the entire work zone.

SHEET 2 OF 7

		Traffic Operations Division Standard	
<b>TRAFFIC CONTROL PLAN</b> <b>LANE CLOSURES ON MULTILANE CONVENTIONAL ROADS</b>			
<b>TCP (SC-2) - 21</b>			
FILE:	tcpsc-2-21.dgn	DN:	CK:
© TxDOT	April 2021	CONT	SECT
REVISIONS	0064	01	069, ETC
DIST	LFK	COUNTY	SHELY, ETC
			SHEET NO 29


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:25:05 PM  
 FILE: c:\txdot\p\_w\_online\txdot3\catny\_loerch\0408474\tcpsc-3-21.dgn



TCP (SC-3a)

**CENTER LANES CLOSED  
 CONTROL WITH CHANNELIZING DEVICES**



TCP (SC-3b)

**ONE LANES CLOSED  
 CONTROL WITH CHANNELIZING DEVICES**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed * X	Formula $L = \frac{WS^2}{60}$	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	$L = WS$	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

**GENERAL NOTES**


- Flags attached to signs where shown are REQUIRED.
  - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work when approved by the Engineer.
  - If the seal coat operation crosses intersections, traffic in these areas must be controlled. Care must be taken to prevent vehicles from crossing the asphalt before the aggregate is placed. This may require positioning other members of the traffic control crew at the intersection.
  - Temporary rumble strips are not required on seal coat operations.
- TCP (SC-3b)**
- For shorter durations where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the posted speed in mph. This tighter devices spacing is intended for the area of conflicting markings, not the entire work zone.

SHEET 3 OF 7

		Traffic Safety Division Standard	
<b>TRAFFIC CONTROL PLAN SEAL COAT OPERATIONS</b>			
<b>TCP (SC-3) - 21</b>			
FILE: tcpsc-3-21.dgn	DN:	CK:	DW:
© TxDOT April 2021	CONT	SECT	HIGHWAY
REVISIONS	0064	01	069, ETC SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		30

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:25:13 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\tcpsc-4-21.dgn



**ONE LANE TWO-WAY (T-INTERSECTION)  
 CONTROL WITH PILOT VEHICLE**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

**GENERAL NOTES**

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work when approved by the Engineer.
- The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
- Flaggers should use two-way radios or other methods of communication at all times to control traffic.
- Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.
- If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
- Temporary rumble strips are not required on seal coat operations.
- Pilot car is used to guide vehicles through traffic control zone, vehicle shall have an identification name displayed and "PILOT CAR, FOLLOW ME" (G20-4) sign or message board mounted in a conspicuous position on rear.


SHEET 4 OF 7

		Traffic Safety Division Standard	
<b>TRAFFIC CONTROL PLAN          SEAL COAT OPERATIONS</b>			
<b>TCP (SC-4) - 21</b>			
FILE: tcpsc-4-21.dgn	DN:	CK:	DW:
© TxDOT	April 2021	CONT	SECT
REVISIONS	0064	01	069, ETC
DIST	COUNTY		SHEET NO
LFK	SHELBY, ETC		31




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 8/3/2022 8:25:21 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\tcpsc-5-21.dgn



TCP (SC-5a)  
**ONE LANE CLOSURE**



TCP (SC-5b)  
**LANE AND RAMP CLOSURE AT EXIT RAMP**



TCP (SC-5c)  
**LANE AND RAMP CLOSURE AT ENTRANCE RAMP**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
		✓		

**GENERAL NOTES**

- Flags attached to signs where shown, are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- Channelizing devices used to close lanes may be supplemented with the Chevron Alignment Sign placed on every other channelizing device. Chevrons may be attached to plastic drums as per BC Standards.
- Temporary rumble strips are not required on seal coat operations.

SHEET 5 OF 7


		Traffic Safety Division Standard	
<b>TRAFFIC CONTROL PLAN LANE CLOSURES FOR DIVIDED HIGHWAYS</b>			
<b>TCP (SC-5) - 21</b>			
FILE: tcpsc-5-21.dgn	DN:	CK:	DW:
© TxDOT April 2021	CONT	SECT	JOB
REVISIONS	0064	01	069, ETC
DIST	COUNTY		SHEET NO
LFK	SHELBY, ETC		32

# WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS (TABS)


## NOTES:

- Short term pavement markings shall be temporary flexible-reflective roadway marker tabs with protective cover unless otherwise specified elsewhere in plans.
- Short term pavement markings shall NOT be used to simulate edge lines.
- Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.
- Temporary flexible-reflective roadway marker tabs will require normal maintenance replacement when used on roadways with an ADT per lane of up to 7500 vehicles with no more than 10% truck mix. When roadways exceed these values, additional maintenance replacement of devices should be planned.
- No segment of roadway open to traffic shall remain without permanent pavement markings for a period greater than 14 calendar days. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
- For exit gores where a lane is being dropped place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are not allowed for this purpose.


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




**CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO LANE TWO-WAY HIGHWAYS**



**LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS**



**LANE LINES FOR DIVIDED HIGHWAY**



**TWO-WAY LEFT TURN LANE**

## TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS (TABS)

- Temporary flexible-reflective roadway marker tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
- Tabs shall meet requirements of Departmental Material Specification DMS-8242.
- When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
- No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 3.

## DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)

- DMSs referenced above can be found along with embedded links to their respective MPLs at the following website:  
<http://www.txdot.gov>

# WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS (TABS)

SOLID LINES	DOUBLE NO-PASSING LINE	40' ± 6"	Type Y-2
	SINGLE NO-PASSING LINE or CHANNELIZATION LINE	40' ± 6"	Type Y-2 or W
BROKEN LINES (FOR CENTER LINE OR LANE LINE)		40' ± 6"	Type Y-2 or W
WIDE DOTTED LINES (FOR LANE DROP LINES)		40' ± 6"	Type W
WIDE GORE MARKINGS		40' ± 6"	Type W

SHEET 6 OF 7



## WORK ZONE SHORT TERM PAVEMENT MARKINGS FOR SEAL COAT OPERATIONS

TCP (SC-6) - 21


FILE:	tcpsc-6-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CR:	TxDOT
© TxDOT	April 2021	CONT	0064	SECT	01	JOB	069, ETC	SH	87, ETC
REVISIONS		DIST	LFK	COUNTY	SHELB, ETC		SHEET NO		
								33	

8/3/2022

c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\tcpsc-6-21.dgn


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:25:38 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408474\tcpsc-7-21.dgn



**NOTE**  
 Signing shown for one direction of travel only.

**NO PASSING ZONES ON TWO-LANE TWO-WAY ROADS**



**"DO NOT PASS" SIGN (R4-1) and NO-PASSING ZONES**

- A. Prior to the beginning of construction, all currently striped no-passing zones shall be signed with the DO NOT PASS (R4-1) signs and PASS WITH CARE (R4-2) signs placed at the beginning and end of each zone for each direction of travel except as otherwise provided herein. Signs marking these individual no-passing zones need not be covered prior to construction if the signs supplement the existing pavement markings.
- B. At the discretion of the Engineer, in areas of numerous no-passing zones, several zones may be combined as a single zone. If passing is to be prohibited over one or more lengthy sections, a DO NOT PASS sign and a NEXT XX MILES (R20-1TP) plaque may be used at the beginning of such zones. The DO NOT PASS sign and the NEXT XX MILES plaque should be repeated every mile to the end of the no-passing zone. In areas where there is considerable distance between no-passing zones, the end of the no-passing zone may be signed with a PASS WITH CARE sign and a NEXT XX MILES plaque.
- C. Depending on traffic volumes and length of sections, it may be desirable to prohibit passing throughout the project to prevent damage to windshield and lights. The DO NOT PASS sign and NEXT XX MILES plaque should be used and repeated as often as necessary for this purpose. Where several existing zones are to be combined into one individual no-passing zone, the sign at the beginning of the zone should be covered until the surfacing operation has passed this location so as not to have the DO NOT PASS sign conflict with the existing pavement markings. Also, unless one days operation completes the entire length of such combined zones, appropriate DO NOT PASS and PASS WITH CARE signs should be placed at the beginning and end of the no-passing zones where the surfacing operation has stopped for the day.
- D. R4-1 and R4-2 are to remain in place until standard pavement markings are installed.

**"NO CENTER LINE" SIGN (CW8-12)**

- A. Center line markings are yellow pavement markings that delineate the separation of travel lanes that have opposite directions of travel on a roadway. Divided highways do not typically have center line markings.
- B. At the time construction activity obliterates the existing center line markings (low volume roads may not have an existing centerline), a NO CENTER LINE (CW8-12) sign should be erected at the beginning of the work area, at approximately 2 mile intervals within the work area, beyond major intersections and other locations deemed necessary by the Engineer.
- C. The NO CENTER LINE signs are to remain in place until standard pavement markings are installed.

**"LOOSE GRAVEL" SIGN (CW8-7)**

- A. When construction begins, a LOOSE GRAVEL (CW8-7) sign should be erected at each end of the work area and repeated at intervals of approximately 2 miles in rural areas and closer in urban areas.
- B. The LOOSE GRAVEL signs are to remain in place until the condition no longer exists.

**PAVEMENT MARKINGS**

- A. Temporary markings for surfacing projects shall be Temporary Flexible-reflective Roadway Marker Tabs unless otherwise approved by the Engineer. Tabs are to be installed to provide true alignment for striping crews or as directed by the Engineer. Tabs will be placed at the spacing indicated. Tabs should be applied to the pavement no more than two (2) days before the surfacing is applied. After the surfacing is rolled and swept, the cover over the reflective strip shall be removed.
- B. Tabs shall not be used to simulate edge lines.

**COORDINATION OF SIGN LOCATIONS**

- A. The location of warning signs at the beginning and end of a work area are to be coordinated with other signing typically shown on the Barricade and Construction Standards for project limits to ensure adequate sign spacing.
- B. Where possible the ROAD WORK AHEAD (CW20-1D), LOOSE GRAVEL (CW8-7), and NO CENTER LINE (CW8-12) signs should be placed in the sequence shown following the OBEY WARNING SIGNS STATE LAW (R20-3T) and the TRAFFIC FINES DOUBLE (R20-5T) sign, and one "X" sign spacing prior to the CONTRACTOR (G20-6T) sign typically located at or near the limits of surfacing. LOOSE GRAVEL and NO CENTER LINE signs will then be repeated as described above.

Posted Speed *	Minimum Sign Spacing "X" Distance
30	120'
35	160'
40	240'
45	320'
50	400'
55	500'
60	600'
65	700'
70	800'
75	900'

\* Conventional Roads Only


TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

**GENERAL NOTES**


1. The traffic control devices detailed on this sheet will be furnished and erected as directed by the Engineer on sections of roadway where tabs must be placed prior to the surfacing operation which will cover or obliterate the existing pavement markings.
2. The devices shown on this sheet are to be used to supplement those required by the BC Standards or others required elsewhere in the plans.
3. Signs shall be erected as detailed on the BC Standards or the Compliant Work Zone Traffic Control Devices List (CWZTCD) on supports approved for Short Duration / Short Term Stationary Work Zone Sign Supports.
4. When surfacing operations take place on divided highways, freeways or expressways, the size of diamond shaped construction warning signs shall be 48" x 48".
5. Signs on divided highways, freeways and expressways will be placed on both right and left sides of the roadway based on roadway conditions as directed by the Engineer.

SHEET 7 OF 7

<b>TRAFFIC CONTROL DETAILS FOR SEAL COAT OPERATIONS</b>			
<b>TCP (SC-7) - 21</b>			
FILE: tcpsc-7-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT
© TxDOT April 2021	CONT	SECT	JOB
REVISIONS	0064	01	069, ETC SH 87, ETC
DIST	COUNTY		SHEET NO
LFK	SHELBY, ETC		34



TYPICAL PLAN VIEW OF NON-CONCRETE COUNTY ROAD  
PERPENDICULAR APPROACH



TYPICAL PLAN VIEW OF NON-CONCRETE COUNTY ROAD  
SKEWED APPROACH

**NOTES:**

PLACE SEAL COAT ONLY ON PAVED COUNTY ROADS. IF COUNTY ROAD IS NOT PAVED TO RIGHT OF WAY, ONLY PLACE SEAL COAT ON PAVED SURFACE.

SOME COUNTY ROADS HAVE 24" SOLID WHITE STOP BAR STRIPES. IF STOP BAR IS LOCATED WITHIN THE LIMITS OF SEAL COAT, CONTRACTOR TO ELIMINATE THE EXISTING MARKING (ITEM 677).

8/3/2022 10:12:53 PM c:\txdot\pwworking\line\txdot3\cathy. loersch\0408475\County Road and City Street Detail.dgn

N. T. S.

DocuSign  
*ccm3*, P.E.  
 AF852E728AEC4C0...  
 8/5/2022





COUNTY ROAD  
DETAIL

TEXAS DEPARTMENT OF TRANSPORTATION  
©2022

CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY	SHEET NO	
LFK	SHELBY, ETC	35	

DISCLAIMER  
 THE USE OF THIS DETAIL IS GOVERNED BY THE TEXAS ENGINEERING PRACTICE ACT. NO WARRANTY OF ANY KIND IS MADE BY TxDOT FOR ANY PURPOSE WHATSOEVER. TxDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS DETAIL TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.  
 8/3/2022 8:26:17 PM  
 c:\t\tdot\pw\onl\ine\t\tdot3\cathy.l\oerch\d0408480\TypPavMarkDet\DistStd.dgn

07/05/2022 05:36 PM  
 pwt\tdot.projectwiseonl\ine.com\t\tdot3\Documents\11 - LFK\Design Projects\00640403\4 - Design\Plan Set\2. TCP\TypPavMarkDet\DistStd.dgn



\*DETAILS SHOWN FOR ILLUSTRATION ONLY.  
 STRIPES MAY BE PLACED AT EXISTING  
 LOCATIONS AS DIRECTED BY THE ENGINEER.

NOT TO SCALE

LUFKIN DISTRICT STANDARD

**TYPICAL PAVEMENT MARKING DETAILS**


TEXAS DEPARTMENT OF TRANSPORTATION ©2022

CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY	SHEET NO	
LFK	SHELBY, ETC	36	


ISSUED 03-08  
 REVISED 10-20-2016: MODIFIED TITLE BLOCK

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 8/3/2022 8:26:26 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408480\dml-20.dgn




**EDGE LINE AND LANE LINES  
 ONE-WAY ROADWAY  
 WITH OR WITHOUT SHOULDERS**




**TYPICAL TWO-LANE, TWO-WAY PAVEMENT  
 MARKINGS THROUGH INTERSECTIONS**




**CENTERLINE AND LANE LINES  
 FOUR LANE TWO-WAY ROADWAY  
 WITH OR WITHOUT SHOULDERS**




**TYPICAL MULTI-LANE, TWO-WAY PAVEMENT  
 MARKINGS THROUGH INTERSECTIONS**



**TWO LANE TWO-WAY ROADWAY  
 WITH OR WITHOUT SHOULDERS**




For posted speed on road being marked equal to or less than 40 MPH.



For posted speed on road being marked equal to or greater than 45 MPH.

**YIELD LINES**



**FOUR LANE DIVIDED ROADWAY CROSSOVERS**

**NOTES**


- Where divided highways are separated by median widths at the median opening itself of 30 feet or more, median openings shall be signed as two separate intersections. Each median opening has two width measurements, with one measurement for each approach. The narrow median width will be the controlling width to determine if signs are required. Yield signs are the typical intersection control. Stop signs are optional as determined by the Engineer.
- Install median striping (double yellow centerlines and stop bars/yield triangles) when a 50' or greater median centerline can be placed. Stop bars shall only be used with stop signs. Yield triangles shall only be used with yield signs.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown in the plans or as directed by the Engineer.

**GENERAL NOTES**

- Edgeline striping shall be as shown in the plans or as directed by the Engineer. The edgeline should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement raveling or other conditions. Edgelines are not required in curb and gutter sections of roadways.
- The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the inside of edgeline to the inside of edgeline of a two lane roadway.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**GUIDE FOR PLACEMENT OF STOP LINES,  
 EDGE LINE & CENTERLINE**

Based on Traveled Way and Pavement Widths for Undivided Highways



**TYPICAL STANDARD  
 PAVEMENT MARKINGS**


**PM(1) - 20**

FILE: pml-20.dgn	DN:	CK:	DW:	CK:
© TxDOT November 1978	CONT	SECT	JOB	HIGHWAY
8-95 3-03 REVISIONS	0064	01	069, ETC	SH 87, ETC
5-00 2-12	DIST	COUNTY	SHEET NO.	
8-00 6-20	LFK	SHELBY, ETC	37	


# REFLECTIVE RAISED PAVEMENT MARKERS FOR VEHICLE POSITIONING GUIDANCE

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



DATE: 8/3/2022 8:26:35 PM  
FILE: c:\txdot\pw\_online\txdot\3\catny\_loerch\40408480\pm2-20.dgn




**CENTERLINE FOR ALL TWO LANE ROADWAYS**



**CENTERLINE & LANE LINES  
FOR FOUR LANE TWO-WAY HIGHWAYS**



**CENTERLINE AND LANE LINES FOR TWO-WAY LEFT TURN LANE**




**LANE LINES FOR ONE-WAY ROADWAY (NON-FREEWAY FACILITIES)**


Raised pavement markers Type II-C-R shall have clear face toward normal traffic and red face toward wrong-way traffic.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**Type I (Top View)**



**Type II (Top View)**



**SECTION A**

## RAISED PAVEMENT MARKERS




## POSITION GUIDANCE USING RAISED MARKERS REFLECTORIZED PROFILE MARKINGS PM(2) - 20

FILE: pm2-20.dgn	DN:	CK:	DW:	CK:
© TxDOT April 1977				
4-92 2-10	REVISIONS	0064	01	069, ETC SH 87, ETC
5-00 2-12		DIST	COUNTY	SHEET NO
8-00 6-20		LFK	SHELBY, ETC	38


### GENERAL NOTES

1. All raised pavement markers placed in broken lines shall be placed in line with and midway between the stripes.
2. On concrete pavements the raised pavement markers should be placed to one side of the longitudinal joints.



### REFLECTORIZED PROFILE PATTERN DETAIL

USING REFLECTIVE PROFILE PAVEMENT MARKINGS




### NOTE

Profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:26:44 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\40408480\pm3-20.dgn



Posted Speed	D (ft)	L (ft)
30 MPH	460	$L = \frac{WS^2}{60}$
35 MPH	565	
40 MPH	670	L=WS
45 MPH	775	
50 MPH	885	
55 MPH	990	
60 MPH	1,100	
65 MPH	1,200	
70 MPH	1,250	
75 MPH	1,350	

**LANE REDUCTION**

**NOTES**


- Lane reduction pavement markings are used where the number of through lanes is reduced because of narrowing of the roadway or because of a section of on-street parking in what would otherwise be a through lane. For Texas Super 2 Passing Lanes, see TS2(PL) standard sheets.
- On divided highways, an additional W9-1R "RIGHT LANE ENDS" sign may be installed in the median aligned with the W9-1R sign on the right side of the highway.
- Lane reduction arrows are required for speeds of 45 mph or greater. An optional third lane reduction arrow may be added based on engineering judgement. If used, the optional third lane reduction arrow should be centered between the first and last lane reduction arrows.
- For lane reductions on Freeways and Expressways, signing shall conform to the TxDOT Freeway Signing Handbook.

**GENERAL NOTES**


- Lane use word and arrow markings shall be used where through lanes approaching an intersection become mandatory turn lanes. Lane use word and arrow markings should be used in auxiliary lanes of substantial length. Lane use arrow markings or word and arrow markings may be used in other lanes and turn bays for emphasis. Details for words and arrows are as shown in the Standard Highway Sign Designs for Texas.
- When lane-use words and arrow markings are used, two sets of arrows should be used if the length of the bay is greater than 180 feet. When a single lane use arrow or word and arrow marking is used for a short turn lane, it should be located at or near the upstream end of the full-width turn lane.
- Use raised pavement marker Type I-C with undivided highways, flush medians and two way left turn lanes. Use raised pavement marker Type II-C-R with divided highways and raised medians.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




**TYPICAL TWLTL AT ONE-WAY STREET AND RIGHT TURN AUXILIARY LANE**




A two-way left-turn (TWLTL) lane-use arrow pavement marking should be used at or just downstream from the beginning of a two-way left-turn lane within a corridor. Repeating the marking after each intersection or dedicated turn bay is not required unless stated elsewhere in the plans.


**TYPICAL TRANSITION FOR TWLTL AND DIVIDED HIGHWAY**



**TYPICAL TWLTL AT TWO-WAY CROSS STREET AND RIGHT TURN LANE DROP**



**TYPICAL TWO-LANE HIGHWAY INTERSECTION WITH LEFT TURN BAYS**



DETAIL A

DETAIL B




**TWO-WAY LEFT TURN LANES, RURAL LEFT TURN BAYS, AND LANE REDUCTION PAVEMENT MARKINGS PM(3) - 20**

FILE: pm3-20.dgn	DN:	CK:	DW:	CK:
© TxDOT April 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
5-00 2-10	DIST	COUNTY	SHEET NO	
8-00 2-12	LFK	SHELBY, ETC	39	
3-03 6-20				



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



**HIGH-VISIBILITY LONGITUDINAL CROSSWALK AT CONTROLLED APPROACH**


**GENERAL NOTES**

1. Longitudinal crosswalk lines should not be placed in the wheel path of vehicles. Center the crosswalk lines on travel lanes, lane lines, and shoulder lines (if present).
2. A minimum 6" clear distance shall be provided to the curb face. If the last crosswalk line falls into this distance it must be omitted.
3. For divided roadways, adjustments in spacing of the crosswalk lines should be made in the median so that the crosswalk lines are maintained in their proper location across the travel portion of the roadway.
4. At skewed crosswalks, the crosswalk lines are to remain parallel to the lane lines.
5. Each crosswalk shall be a minimum of 6' wide.
6. The High-Visibility Longitudinal Crosswalk is the preferred crosswalk pattern on State Highways. Other crosswalk patterns as shown in the "Texas Manual on Uniform Traffic Control Devices" may be used. All crosswalk designs and dimension shall comply with the "Texas Manual on Uniform Traffic Control Devices."
7. Final placement of Stop Bar and Crosswalk shall be approved by the Engineer in the field.

**MATERIAL SPECIFICATIONS**

PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**UNSIGNALIZED MID BLOCK HIGH-VISIBILITY LONGITUDINAL CROSSWALK**

**NOTES:**

1. Use stop bars with "Stop Here for Pedestrians" signs at unsignalized mid block crosswalks.
2. Use stop bars with "Stop Here on Red" signs at mid block crosswalks controlled by traffic signals or pedestrian hybrid beacons.



**CROSSWALK PAVEMENT MARKINGS**


**PM(4) - 22**

FILE: pm4-22.dgn	DN:	CK:	DW:	CK:
© TxDOT June 2020	CONT	SECT	JOB	HIGHWAY
3-22 REVISIONS	0064	01	069, ETC	SH 87, ETC
	DIST	COUNTY	SHEET NO.	
	LFK	SHELBY, ETC	40	


DATE:  
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: FILE:



**2-WAY, MULTIPLE LANES EACH DIRECTION**



**2 LANES, 2-WAY**



**1-WAY STREET WITH CURB**

- NOTES**
- T: Tip of gate to edge of curb: 1' max for Quiet Zone SSM, 90% of traveled way covered by gates for all other locations
  - U: Non-traversable curb length from gate: 100' min. for a Quiet Zone SSM, 10' min for all other locations.


**TABLE 1**

Approach Speed (mph)	Desirable Placement (feet)
20	100
25	100
30	100
35	100
40	125
45	175
50	250
55	325
60	400
65	475
70	550
75	650

**LEGEND**

	Sign
	Object Marker
	Traffic Flow
	Cantilever
	Gate Assembly
	Mast Flasher Pair

- GENERAL NOTES**
- Medians and curbs must be non-traversable to qualify as a Quiet Zone Supplementary Safety Measure (SSM). Non-traversable curbs in Quiet Zones are 6" tall minimum and used on roadways where speed does not exceed 40 mph.
  - Raised pavement markers may be used to supplement striping. See PM(2) and PM(3) standard sheets.
  - Medians preferred whenever possible to prevent vehicles from driving around gates.
  - Longitudinal edge striping may be continued thru crossing as needed. Illumination may also be considered for nighttime visibility.
  - See SMD standard sheets for sign mounting details.
  - See the Standard Highway Sign Design for Texas (SHSD) manual for sign and pavement marking details.



**CROSSING SURFACE CROSS SECTION**

**NOTES**

- A1: Center of RR mast to center of rail: 12' minimum, 15' typical.
- A2: Tip of gate to center of rail: 12' minimum, 15' typical.
- B: Center of mast (cantilever, gate, or mast flasher) of nearest active traffic control device to stop line: 8' (NOTE: Stop line may be moved as needed, but should be at least 8' back from gates, if present).
- C: Center of detectable warning device to nearest rail: 6' minimum
- D: Center of gate mast to center of cantilever mast: 6' typical. NOTE: Cantilever may be located in front or behind gates.
- E: Edge of median or curb to nearest rail: 10' typical. NOTE: Design median edge to be parallel with rail.
- F: Edge of planking panel from edge of pavement or sidewalk: 3' minimum. NOTE: Field panels need not be in line with gauge panels.
- G: Length of panels along rail: 8' typical.
- H: Width of field panel: 2' typical (check with railroad company).
- I: Distance between rails: 4'-8.5".
- J: Tip of gate to tip of gate: 2' maximum for Quiet Zone SSM or 90% of traveled way covered by gates for all other locations.
- K: Nearest edge of RR cabin from edge of pavement: 30' typical. NOTE: Cabinet not required to be parallel to edge of pavement.
- L: Nearest edge of RR cabin from nearest rail: 25' typical.
- M: Center of RR mast to edge of sidewalk: 6' minimum.
- N: Center of gate mast to leading edge of non-traversable median: 100' minimum to qualify as a Quiet Zone SSM. NOTE: 60' will suffice if there is a street intersection within the 100' and all street intersections within 60' are closed.
- O: Width of median: 8'-6" minimum, 10' typical when using median gates. NOTE: Center of gate mast minimum 4'-3" from face of curb.
- P: Center of RR mast to face of curb: 4'-3" minimum. Center of RR mast to edge of pavement (with shoulder): 6' minimum. Center of RR mast to edge of pavement (no shoulder): 8'-3" minimum. NOTE: BNSF prefers 5'-3", 7', and 9'-3" minimums, respectively.
- Q: Gate length: 28' or less typical, but railroad company may allow up to 32' under special circumstances.
- R: Stop line to first RR Crossing transverse line (bike lane): 50' typical.
- S: Stop line to GRADE CROSSING ADVANCE WARNING (W10-1) sign and adjacent RR Crossing pavement markings. See Table 1. See RCD(2) for other signs.


Texas Department of Transportation  
Traffic Operations Division Standard

**RAILROAD CROSSING DETAILS  
SIGNING, STRIPING, AND  
DEVICE PLACEMENT  
RCD(1)-16**

FILE: rcd1-16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT FEBRUARY 2016	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
	DIST	COUNTY	SHEET NO.	
	LFK	SHELBY, ETC	41	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



### PASSIVE CROSSING

- NOTES**
1. Stop or yield sign may also be installed to the left of the crossbuck sign, rather than below it.
  2. A 2" white retroreflective strip shall be installed on front and back of crossbuck sign post.




### PATHWAY CROSSING

- NOTES**
1. A shared use pathway is considered a separate pathway crossing when more than 25' from traveled way of adjacent roadway.
  2. Detectable warning used at stop bar.
  3. Smaller sign sizes preferred than shown to the right on this sheet.

Approach Speed (mph)	Desirable Placement (feet)
20	100
25	100
30	100
35	100
40	125
45	175
50	250
55	325
60	400
65	475
70	550
75	650


- GENERAL NOTES**
1. Railroad company to provide active traffic control devices, CROSSBUCK (R15-1), NUMBER OF TRACKS Plaque (R15-2P) (if more than 1 track), and EMERGENCY NOTIFICATION (I-13) signs.
  2. LOW GROUND CLEARANCE (W10-5) signs may be relocated further upstream of crossing to provide advance warning of alternate route.
  3. GRADE CROSSING AND INTERSECTION ADVANCE WARNING (W10-2) signs may be modified as needed to fit roadway geometry.
  4. Table 1 placement distances may vary per Sect. 2C.05 of the TMUTCD.
  5. See Table 1 to determine placement of STOP AHEAD (W3-1) and YIELD AHEAD (W3-2) signs unless shown otherwise.
  6. DO NOT STOP ON TRACKS (R8-8) signs installed when potential for vehicles stopping on tracks is significant as determined by sealing engineer. Install so sign does not block view of RR mast.
  7. See the Standard Highway Sign Design for Texas (SHSD) manual for sign and pavement marking details.



**NOTE**  
 This design shows a 4-way stop scenario only. Other signs may be substituted for traffic signal or other traffic control scenarios. This note also applies to T-intersection design below.

	"A" < 100'	"A" ≥ 100'
"B"	See Table 1. Place pavement markings and signs on opposite side of intersection from rail if spacing from Table 1 would put markings within intersection.	See Table 1. Place pavement markings and signs between rail and intersection if spacing from Table 1 would put markings within intersection.
"C"	See Table 1.	GRADE CROSSING AND INTERSECTION ADVANCE WARNING (W10-2, W10-3, W10-4) signs should only be installed if W10-1 sign is not between intersection and railroad crossing. If needed, see Table 1.

### GRADE CROSSING NEAR A PARALLEL STREET



#### 2-WAY

Min 7' median width to support sign    Min 6' median width to support sign


#### 2-WAY WITH MEDIAN

#### 1-WAY

**SIGNS**

 1 W10-1 36" DIA.	 2 W10-2L 36" X36"	 3 W10-2R 36" X36"	 IF NEEDED W10-5 36" X36"  W10-5P 30" X24"
 5 R8-8 24" X30"	 6 W3-1 30" X30"	 R1-1 36" X36" ALL WAY R1-3P 18" X6"	 R15-1 48" X9"  R15-2P 27" X18"  R1-1 36" X36"
 R15-1 48" X9"  R15-2P 27" X18"  R1-2 48" X48" X48"	 R15-1 48" X9"  R15-2P 27" X18" 10	 W10-1 36" DIA.  NO GATES OR LIGHTS W10-13P 30" X24" 11 **	 I-13 15" X9" 12
 13 W3-2 30" X30"	 NO TRAIN HORN W10-9P 30" X24"	 LOW GROUND CLEARANCE W10-5P 30" X24"	


**\*\* Includes a NO TRAIN HORN Plaque (W10-9P) if crossing is in a Quiet Zone. LOW GROUND CLEARANCE Plaque (W10-5P) if needed is mounted below W10-2/W10-3/W10-4 signs.**



**NOTE**  
 Railroad crossing pavement markings and adjacent signs not included when distance between near edge of intersection and near rail is less than 100'. GRADE CROSSING AND INTERSECTION ADVANCE WARNING (W10-3) signs installed on roadway parallel with rail in this case.

### T-INTERSECTION

\*Use Table 1 if sufficient space exists.



**NOTE**  
 Separate active traffic control devices, railroad crossing pavement markings, and adjacent signs required when tracks are more than 100' apart.

### 2 ADJACENT CROSSINGS

Texas Department of Transportation  
 Traffic Operations Division Standard


## RAILROAD CROSSING DETAILS SIGNING & STRIPING

### RCD(2)-16


FILE: rcd2-16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT FEBRUARY 2016	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
	DIST	COUNTY	SHEET NO.	
	LFK	SHELBY, ETC	42	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 8/3/2022 8:27:17 PM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\0408480\ts2-1-18.dgn



**SEPARATED**



**ALTERNATING**

LEGEND	
	Sign
	Traffic Flow

TYPICAL TAPER LENGTH (L)	
Formula *	$L = WS$

\* Transition length should be rounded up to nearest 5 foot increment.

L=Length of Transition (FT)  
 W=Width of Offset (FT)  
 S=Posted Speed (MPH)

**EXAMPLE**  
 A 12 foot lane is added on a 70 mph roadway. The length of the transition should be:  
 $L = 12 \times 70 = 840 \text{ ft}$

**TABLE 1  
 ADVANCE WARNING SIGN  
 DISTANCE (D)  
 AND BUFFER DISTANCE (B)**

Posted Speed	D (FT)	B (FT)
40	670	305
45	775	360
50	885	425
55	990	495
60	1100	570
65	1200	645
70	1250	730
75	1350	820

**GENERAL NOTES**

- For minimum and desirable design details, see the Roadway Design Manual, Chapter 4, Section 6, Super 2 Highways.
- For Raised Pavement Markers (RPM) details, see Pavement Markings Standard sheet, PM(2). Note that RPMs are not recommended on the 4" dotted white extension lines.
- For rumble strip options available for the designed shoulder width, see rumble strip standard sheet RS(4).




**TEXAS SUPER 2  
 PASSING LANES**

**TS2 (PL-1) - 18**

FILE: ts2-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT May 2010	CONT	SECT	JOB	HIGHWAY
REVISIONS	0064	01	069, ETC	SH 87, ETC
2-12	DIST	COUNTY	SHEET NO	
3-12	LFK	SHELBY, ETC	43	
3-18				

THE PROPOSED WORK OF THIS PROJECT IS TO RESURFACE WITH SEAL COAT. THIS ACTIVITY MAINTAINS THE ORIGINAL LINE AND GRADE, HYDRAULIC CAPACITY AND ORIGINAL PURPOSE OF THE SITE. THEREFORE, THIS PROJECT MEETS THE DEFINITION OF A ROUTINE MAINTENANCE ACTIVITY AS DEFINED IN THE TPDES GENERAL PERMIT NO. TXR150000 ISSUED MARCH 5, 2018 AND TCEQ'S TPDES CGP DOES NOT APPLY. HOWEVER, THE CONTRACTOR SHALL PLACE BMP'S AS DIRECTED.

8/16/2022 9:23:14 PM  
c:\txdot\pwworking\the\txdot3\cathy. loerch\0408481\SWP3\index\*small\disturbance.dgn



DocuSign  
*Charles M. Brazil, P.E.*  
AF852E728AEC4C0...  
8/19/2022


TXDOT  
SWP3  
INDEX



CONT	SECT	JOB	HIGHWAY
0064	01	069, ETC	SH 87, ETC
DIST	COUNTY	SHEET NO.	
LFK	SHELBY, ETC	44	


DISCLAIMER: This use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for incorrect results or damages resulting from its use.

80372022  
cf116dot1pw\_online\txdot3\cathy\_loerch\0408481\ec116.dgn



**TEMPORARY SEDIMENT CONTROL FENCE**

SCF



**HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL**

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

**SEDIMENT CONTROL FENCE USAGE GUIDELINES**

A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT<sup>2</sup>. Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.


**LEGEND**

Sediment Control Fence

SCF

**GENERAL NOTES**

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.



**VERTICAL TRACKING**

		Design Division Standard	
<b>TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE &amp; VERTICAL TRACKING</b> <b>EC(1) - 16</b>			
FILE: ec116	DN: TxDOT	CK: KM	DW: VP
© TxDOT: JULY 2016	CONT	SECT	JOB
REVISIONS	0064	01	069, ETC SH 87, ETC
DIST	COUNTY		SHEET NO.
LFK	SHELBY, ETC		45

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of electronic files to paper formats or for incorrect results or damages resulting from its use.

DATE: 9/29/2022 11:33:48 AM  
 FILE: c:\txdot\pw\_online\txdot3\catny\_loerch\4040848\0064-01-069 District 069.dwg

**I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402**

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

1. N/A

No Action Required  Required Action

The proposed work of this project is for the construction of Seal Coat consisting of resurface with Seal Coat. This activity maintains the original line and grade, hydraulic capacity and original purpose of the site. Therefore, this project meets the definition of a routine maintenance activity as defined in the TPDES General Permit No. TXR150000 issued March 5, 2018 and TCEQ's TPDES CGP does not apply.

**II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404**

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required
- Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
- Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
- Individual 404 Permit Required
- Other Nationwide Permit Required: NWP# \_\_\_\_\_

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

1. N/A

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

**Best Management Practices:**

<b>Erosion</b>	<b>Sedimentation</b>	<b>Post-Construction TSS</b>
<input type="checkbox"/> Temporary Vegetation	<input type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	<input type="checkbox"/> Grassy Swales

**III. CULTURAL RESOURCES**

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

No Action Required  Required Action

Various roadway locations within the project limits contain Historical markers and in-kind areas.

Action No.

1. Equipment storage or stockpiling is not permitted in any pulloff or parking area labelled as a historic marker, or where historic markers are present.

**IV. VEGETATION RESOURCES**

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

No Action Required  Required Action

Action No.

1. N/A

**V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.**

No Action Required  Required Action

Action No.

1. Red-cockaded Woodpecker (federally listed endangered species) habitat is present adjacent to the ROW along FM 2426. Conservation measures have been agreed upon by the United States Fish and Wildlife Service and TxDOT to ensure that the proposed action will not adversely affect the red-cockaded woodpecker. The conservation measures below must be followed in order to be in compliance with the Endangered Species Act:

1. NO WORK shall be performed on FM 2426 from April 1 to July 31.
2. WORK shall begin one hour after sunrise and cease one hour before sunset.
3. NO STOCKPILES or EQUIPMENT STORAGE shall be allowed along or within the ROW along FM 2426.

2. Texas Golden Gladdess (federally-listed endangered species) habitat is present within the ROW along SH 21. The conservation measure below must be followed in order to be in compliance with the Endangered Species Act.

1. NO STOCKPILES or EQUIPMENT STORAGE shall be allowed within the ROW along SH 21 from 0.5 mile east of LP 547 to 1.2 miles east of LP 547 and along FM 353 from 0.8 mile east of SH 147 to 1.02 mile east of SH 147
2. NO EQUIPMENT or VEHICLES shall leave the pavement on SH 21 from 0.5 mile east of LP 547 to 1.2 miles east of LP 547 and on FM 353 from 0.8 mile east of SH 147 to 1.02 mile east of SH 147.

3. Neches River Rose-mallow (federally-listed endangered species) habitat is present within the ROW on SH 94. The conservation measure below must be followed in order to be in compliance with the Endangered Species Act.

1. NO STOCKPILES or EQUIPMENT STORAGE shall be allowed within the ROW along SH 94 from 1.13 miles west of Trinity/Angelina County line to 1.0 mile west of the Trinity/Angelina County line.
2. NO EQUIPMENT or VEHICLES shall leave the pavement on SH 94 from 1.13 miles west of the Trinity/Angelina County line to 1.0 mile west of the Trinity/Angelina County line.

**LIST OF ABBREVIATIONS**

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SWP3: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NWP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

**VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES**

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used. Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act. Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- \* Dead or distressed vegetation (not identified as normal)
- \* Trash piles, drums, canister, barrels, etc.
- \* Undesirable smells or odors
- \* Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

Yes  No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

Yes  No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

No Action Required  Required Action

1. N/A


**VII. OTHER ENVIRONMENTAL ISSUES**

Engineer shall notify United States Forest Service prior to starting work on the following roadways:

1. Sabine National Forest: FM 2426, FM 353, SH 87
2. Davy Crockett National Forest: SH 94
3. Angelina National Forest: SH 147, SH 63
4. Sam Houston National Forest: SH 150

NO stock piling or equipment storage along roadways listed above.

No Action Required  Required Action

		<i>Design Division</i>	
<b>EPIC</b>			
<b>(ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS)</b>			
FILE: epic.dgn	DN: TxDOT	CK: RG	DW: VP
©TxDOT: February 2015	CONT	SECT	JOB
12-12-2011 (DS) REVISIONS	0064	01	069, ETC SH 87, ETC
05-07-14 ADDED NOTE SECTION IV.	DIST	COUNTY	SHEET NO.
01-23-2015 SECTION I. CHANGED ITEM 1122 TO ITEM 506, ADDED GRASSY SWALES.	LFK	SHELBY, ETC	46

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \_\_\_\_\_  
 FILE: \_\_\_\_\_

**I. WORK AT CROSSING LOCATIONS (AT GRADE, HIGHWAY OVERPASS, HIGHWAY UNDERPASS, PEDESTRIAN, OR CLOSED/ABANDONED)**

DOT #: 023898G  
 Crossing Type: AT GRADE  
 RR Company Owing Track at Crossing: BNSF RAILWAY COMPANY  
 Operating RR Company at Track: BNSF RAILWAY COMPANY  
 RR MP: 96.800  
 RR Subdivision: LONGVIEW  
 City: PINELAND  
 County: SABINE  
 CSJ at this Crossing: 2268-01-018  
 Highway/Roadway name crossing the railroad: FM 2426  
 # of regularly scheduled trains per day at this crossing: 4  
 # of switching movements per day at this crossing: 0  
 % of estimated contract cost of work within railroad ROW: 0.1%

Scope of Work at this Crossing to Be Performed by State Contractor:  
 DISTRICT WIDE SEALCOAT PROJECT WHICH WILL CONSIST OF APPLYING ASPHALT AND AGGREGATE TO THE EXISTING PAVEMENT SURFACE UP TO THE EXISTING TRACK CROSSING.

Scope of Work at this Crossing to Be Performed by Railroad Company:  
 PROVIDE FLAGGING SERVICES WHENEVER THE WORK IS WITHIN 25 FEET OF THE NEAREST RAIL.

\*\* Choose: Highway Overpass, Highway Underpass, At Grade, Pedestrian, or Closed/Abandoned

**II. OTHER PROJECT WORK WITHIN RAILROAD RIGHTS-OF-WAY (ROW)**

N/A

**III. FLAGGING & INSPECTION**

# of Days of Railroad Flagging Expected: 1

On this project, night or weekend flagging is:

- Expected
- Not Expected

Flagging services will be provided by:

- Railroad Company: TxDOT will pay flagging invoices
- Outside Party: Contractor will pay flagging invoices, to be reimbursed by TxDOT

Contractor must incorporate flaggers into anticipated construction schedule. The Railroad requires a 30 day notice if their flaggers are to be utilized. If Contractor falls behind schedule due to their own negligence and is not ready for scheduled flaggers, any flagging charges will be paid by Contractor.

Contact Information for Flagging:

- UPRR - UP.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging  
- UP.request@nrssinc.net  
Call Center 877-984-6777
- BNSF - BNSF.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging
- KCS - KCS.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging  
- Bottom Line On-Track Safety Services  
bottomline076@aol.com, 903-767-7630

OTHERS \_\_\_\_\_

Contractor must incorporate Construction Inspection into anticipated construction schedule.

- Not Required
- Required: Contact Information for Construction Inspection:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**IV. CONSTRUCTION WORK TO BE PERFORMED BY THE RAILROAD**

On this project, construction work to be performed by a railroad company is:

- Required
- Not Required

Coordinate with TxDOT for any work to be performed by the Railroad Company. TxDOT must issue a work order for any work done by the Railroad Company prior to the work being performed.

**V. RAILROAD INSURANCE REQUIREMENTS**

Railroad reference number shall be provided by TxDOT CST or DO.

The Contractor shall confirm the insurance requirements with the Railroad as the insurance limits are subject to change without notice.

Insurance policies must be issued for and on behalf of the Railroad. Where more than one Railroad Company is operating on the same right of way or where several Railroad Companies are involved and operate on their own separate rights of way, provide separate insurance policies in the name of each Railroad Company.

No direct compensation will be made to the Contractor for providing the insurance coverages shown below or any deductibles. These costs are incidental to the various bid items.

Type of Insurance	Amount of Coverage (Minimum)
Workers Compensation	\$500,000 / \$500,000 / \$500,000
Commercial General Liability	\$2,000,000 / \$4,000,000
Business Automobile	\$2,000,000 combined single limit

Railroad Protective Liability	
<input type="checkbox"/> Not Required	
<input checked="" type="checkbox"/> Non - Bridge Projects	\$2,000,000 / \$6,000,000
<input type="checkbox"/> Bridge Projects	\$5,000,000 / \$10,000,000
<input type="checkbox"/> Other	

**VI. CONTRACTOR'S RIGHT OF ENTRY (ROE) AGREEMENT**

On this project, an ROE agreement is:

- Not Required
- Required: TxDOT CST to assist in obtaining with the UPRR (see Item 5, Article 8.3)
- Required: UPRR Maintenance Consent Letter. TxDOT CST to assist.
- Required: Contractor to obtain (see Item 5, Article 8.4)

With the following railroad companies: \_\_\_\_\_

To view previously approved ROE Agreement templates agreed upon between the State and Railroad, see:

<http://www.txdot.gov/inside-txdot/division/rail/samples.html>

Approved ROE Agreement templates are not to be modified by the Contractor.

Contractor shall not operate within Railroad Right of Way without an executed Construction & Maintenance Agreement between the State and the Railroad and an executed ROE agreement between the Contractor and the Railroad if required on project.

**VII. RAILROAD COORDINATION MEETING**

On this project, a Railroad Coordination Meeting is:

- Not Required
- Required

See Item 5, Article 8.1 for more details.

**VIII. SUBCONTRACTORS**

Contractor shall not subcontract work without written consent of TxDOT. Subcontractors are required to maintain the same insurance coverage as required of the Contractor.

**IX. EMERGENCY NOTIFICATION**

**In Case of Railroad Emergency**  
 Call BNSF Railway Company  
 Railroad Emergency Line at 800-832-5452 Option 1  
 Location: DOT 023898G  
 RR Milepost: 96.800  
 Subdivision: Longview

<span style="font-weight: bold;">Texas Department of Transportation</span>				Rail Division	
<b>RAILROAD SCOPE OF WORK PROJECT SPECIFIC DETAILS</b>					
SHEET 1 OF 5					
FILE:	RR Scope of Work.dgn	DN: TxDOT	CK:	DW:	CK:
© TxDOT	June 2014	CONT	SECT	JOB	HIGHWAY
9/2021	REVISIONS	0064	01	069, ETC	SH 87, ETC
DIST	COUNTY	SHEET NO.			
LFK	SHELBY, ETC	47			



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \_\_\_\_\_  
 FILE: \_\_\_\_\_

**I. WORK AT CROSSING LOCATIONS (AT GRADE, HIGHWAY OVERPASS, HIGHWAY UNDERPASS, PEDESTRIAN, OR CLOSED/ABANDONED)**

DOT #: 023939J  
 Crossing Type: AT GRADE  
 RR Company Owing Track at Crossing: BNSF RAILWAY COMPANY  
 Operating RR Company at Track: BNSF RAILWAY COMPANY  
 RR MP: 139.600  
 RR Subdivision: LONGVIEW  
 City: CENTER  
 County: SHELBY  
 CSJ at this Crossing: 0064-01-069  
 Highway/Roadway name crossing the railroad: SH 87  
 # of regularly scheduled trains per day at this crossing: 4  
 # of switching movements per day at this crossing: 0  
 % of estimated contract cost of work within railroad ROW: 0.1%

Scope of Work at this Crossing to Be Performed by State Contractor:  
 DISTRICT WIDE SEALCOAT PROJECT WHICH WILL CONSIST OF APPLYING ASPHALT AND AGGREGATE TO THE EXISTING PAVEMENT SURFACE UP TO THE EXISTING TRACK CROSSING.

Scope of Work at this Crossing to Be Performed by Railroad Company:  
 PROVIDE FLAGGING SERVICES WHENEVER THE WORK IS WITHIN 25 FEET OF THE NEAREST RAIL.

\*\* Choose: Highway Overpass, Highway Underpass, At Grade, Pedestrian, or Closed/Abandoned

**II. OTHER PROJECT WORK WITHIN RAILROAD RIGHTS-OF-WAY (ROW)**

N/A

**III. FLAGGING & INSPECTION**

# of Days of Railroad Flagging Expected: 1

On this project, night or weekend flagging is:

- Expected  
 Not Expected

Flagging services will be provided by:

- Railroad Company: TxDOT will pay flagging invoices  
 Outside Party: Contractor will pay flagging invoices, to be reimbursed by TxDOT

Contractor must incorporate flaggers into anticipated construction schedule. The Railroad requires a 30 day notice if their flaggers are to be utilized. If Contractor falls behind schedule due to their own negligence and is not ready for scheduled flaggers, any flagging charges will be paid by Contractor.

Contact Information for Flagging:

- UPRR - UP.info@railpros.com  
 Call Center 877-315-0513, Select #1 for flagging  
 - UP.request@nrssinc.net  
 Call Center 877-984-6777  
  
 BNSF - BNSF.info@railpros.com  
 Call Center 877-315-0513, Select #1 for flagging  
  
 KCS - KCS.info@railpros.com  
 Call Center 877-315-0513, Select #1 for flagging  
 - Bottom Line On-Track Safety Services  
 bottomline076@aol.com, 903-767-7630

OTHERS \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Contractor must incorporate Construction Inspection into anticipated construction schedule.

- Not Required  
 Required: Contact Information for Construction Inspection:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**IV. CONSTRUCTION WORK TO BE PERFORMED BY THE RAILROAD**

On this project, construction work to be performed by a railroad company is:

- Required  
 Not Required

Coordinate with TxDOT for any work to be performed by the Railroad Company. TxDOT must issue a work order for any work done by the Railroad Company prior to the work being performed.

**V. RAILROAD INSURANCE REQUIREMENTS**

Railroad reference number shall be provided by TxDOT CST or DO.

The Contractor shall confirm the insurance requirements with the Railroad as the insurance limits are subject to change without notice.

Insurance policies must be issued for and on behalf of the Railroad. Where more than one Railroad Company is operating on the same right of way or where several Railroad Companies are involved and operate on their own separate rights of way, provide separate insurance policies in the name of each Railroad Company.

No direct compensation will be made to the Contractor for providing the insurance coverages shown below or any deductibles. These costs are incidental to the various bid items.

Type of Insurance	Amount of Coverage (Minimum)
Workers Compensation	\$500,000 / \$500,000 / \$500,000
Commercial General Liability	\$2,000,000 / \$4,000,000
Business Automobile	\$2,000,000 combined single limit

Railroad Protective Liability	
<input type="checkbox"/> Not Required	
<input checked="" type="checkbox"/> Non - Bridge Projects	\$2,000,000 / \$6,000,000
<input type="checkbox"/> Bridge Projects	\$5,000,000 / \$10,000,000
<input type="checkbox"/> Other	

**VI. CONTRACTOR'S RIGHT OF ENTRY (ROE) AGREEMENT**

On this project, an ROE agreement is:

- Not Required  
  
 Required: TxDOT CST to assist in obtaining with the UPRR (see Item 5, Article 8.3)  
 Required: UPRR Maintenance Consent Letter. TxDOT CST to assist.  
  
 Required: Contractor to obtain (see Item 5, Article 8.4)

With the following railroad companies: \_\_\_\_\_

To view previously approved ROE Agreement templates agreed upon between the State and Railroad, see:

<http://www.txdot.gov/inside-txdot/division/rail/samples.html>

Approved ROE Agreement templates are not to be modified by the Contractor.

Contractor shall not operate within Railroad Right of Way without an executed Construction & Maintenance Agreement between the State and the Railroad and an executed ROE agreement between the Contractor and the Railroad if required on project.

**VII. RAILROAD COORDINATION MEETING**

On this project, a Railroad Coordination Meeting is:

- Not Required  
 Required

See Item 5, Article 8.1 for more details.

**VIII. SUBCONTRACTORS**

Contractor shall not subcontract work without written consent of TxDOT. Subcontractors are required to maintain the same insurance coverage as required of the Contractor.

**IX. EMERGENCY NOTIFICATION**

**In Case of Railroad Emergency**  
 Call BNSF Railway Company  
 Railroad Emergency Line at 800-832-5452 Option 1  
 Location: DOT 023939J  
 RR Milepost: 139.600  
 Subdivision: Longview



**RAILROAD SCOPE OF WORK  
PROJECT SPECIFIC DETAILS**

SHEET 2 OF 5

FILE: RR Scope of Work.dgn	DN: TxDOT	CK: _____	DW: _____	CK: _____
© TxDOT June 2014	CONT	SECT	JOB	HIGHWAY
9/2021	REVISIONS	0064 01	069, ETC	SH 87, ETC
	DIST	COUNTY		SHEET NO.
	LFK	SHELBY, ETC		48

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \_\_\_\_\_  
 FILE: \_\_\_\_\_

**I. WORK AT CROSSING LOCATIONS (AT GRADE, HIGHWAY OVERPASS, HIGHWAY UNDERPASS, PEDESTRIAN, OR CLOSED/ABANDONED)**

DOT #: 755251F  
 Crossing Type: AT GRADE  
 RR Company Owning Track at Crossing: UNION PACIFIC RAILROAD COMPANY  
 Operating RR Company at Track: UNION PACIFIC RAILROAD COMPANY  
 RR MP: 166.780  
 RR Subdivision: LUFKIN  
 City: TIMPSON  
 County: SHELBY  
 CSJ at this Crossing: 0304-07-024  
 Highway/Roadway name crossing the railroad: SH 87  
 # of regularly scheduled trains per day at this crossing: 8  
 # of switching movements per day at this crossing: 0  
 % of estimated contract cost of work within railroad ROW: 0.1%

Scope of Work at this Crossing to Be Performed by State Contractor:  
 DISTRICT WIDE SEALCOAT PROJECT WHICH WILL CONSIST OF APPLYING ASPHALT AND AGGREGATE TO THE EXISTING PAVEMENT SURFACE UP TO THE EXISTING TRACK CROSSING.

Scope of Work at this Crossing to Be Performed by Railroad Company:  
 PROVIDE FLAGGING SERVICES WHENEVER THE WORK IS WITHIN 25 FEET OF THE NEAREST RAIL.

\*\* Choose: Highway Overpass, Highway Underpass, At Grade, Pedestrian, or Closed/Abandoned

**II. OTHER PROJECT WORK WITHIN RAILROAD RIGHTS-OF-WAY (ROW)**

N/A

**III. FLAGGING & INSPECTION**

# of Days of Railroad Flagging Expected: 1

On this project, night or weekend flagging is:

- Expected
- Not Expected

Flagging services will be provided by:

- Railroad Company: TxDOT will pay flagging invoices
- Outside Party: Contractor will pay flagging invoices, to be reimbursed by TxDOT

Contractor must incorporate flaggers into anticipated construction schedule. The Railroad requires a 30 day notice if their flaggers are to be utilized. If Contractor falls behind schedule due to their own negligence and is not ready for scheduled flaggers, any flagging charges will be paid by Contractor.

Contact Information for Flagging:

- UPRR - UP.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging  
- UP.request@nrssinc.net  
Call Center 877-984-6777
- BNSF - BNSF.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging
- KCS - KCS.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging  
- Bottom Line On-Track Safety Services  
bottomline076@aol.com, 903-767-7630

OTHERS \_\_\_\_\_

Contractor must incorporate Construction Inspection into anticipated construction schedule.

- Not Required
- Required: Contact Information for Construction Inspection:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**IV. CONSTRUCTION WORK TO BE PERFORMED BY THE RAILROAD**

On this project, construction work to be performed by a railroad company is:

- Required
- Not Required

Coordinate with TxDOT for any work to be performed by the Railroad Company. TxDOT must issue a work order for any work done by the Railroad Company prior to the work being performed.

**V. RAILROAD INSURANCE REQUIREMENTS**

Railroad reference number shall be provided by TxDOT CST or DO.

The Contractor shall confirm the insurance requirements with the Railroad as the insurance limits are subject to change without notice.

Insurance policies must be issued for and on behalf of the Railroad. Where more than one Railroad Company is operating on the same right of way or where several Railroad Companies are involved and operate on their own separate rights of way, provide separate insurance policies in the name of each Railroad Company.

No direct compensation will be made to the Contractor for providing the insurance coverages shown below or any deductibles. These costs are incidental to the various bid items.

Type of Insurance	Amount of Coverage (Minimum)
Workers Compensation	\$500,000 / \$500,000 / \$500,000
Commercial General Liability	\$2,000,000 / \$4,000,000
Business Automobile	\$2,000,000 combined single limit

Railroad Protective Liability	
<input type="checkbox"/> Not Required	
<input checked="" type="checkbox"/> Non - Bridge Projects	\$2,000,000 / \$6,000,000
<input type="checkbox"/> Bridge Projects	\$5,000,000 / \$10,000,000
<input type="checkbox"/> Other	

**VI. CONTRACTOR'S RIGHT OF ENTRY (ROE) AGREEMENT**

On this project, an ROE agreement is:

- Not Required
- Required: TxDOT CST to assist in obtaining with the UPRR (see Item 5, Article 8.3)
- Required: UPRR Maintenance Consent Letter. TxDOT CST to assist.

- Required: Contractor to obtain (see Item 5, Article 8.4)

With the following railroad companies: \_\_\_\_\_

To view previously approved ROE Agreement templates agreed upon between the State and Railroad, see:

<http://www.txdot.gov/inside-txdot/division/rail/samples.html>

Approved ROE Agreement templates are not to be modified by the Contractor.

Contractor shall not operate within Railroad Right of Way without an executed Construction & Maintenance Agreement between the State and the Railroad and an executed ROE agreement between the Contractor and the Railroad if required on project.

**VII. RAILROAD COORDINATION MEETING**

On this project, a Railroad Coordination Meeting is:

- Not Required
- Required

See Item 5, Article 8.1 for more details.

**VIII. SUBCONTRACTORS**

Contractor shall not subcontract work without written consent of TxDOT. Subcontractors are required to maintain the same insurance coverage as required of the Contractor.

**IX. EMERGENCY NOTIFICATION**

**In Case of Railroad Emergency**  
 Call Union Pacific Railroad Company  
 Railroad Emergency Line at 888-877-7267  
 Location: DOT 755251F  
 RR Milepost: 166.780  
 Subdivision: Lufkin

<span style="font-weight: bold;">Texas Department of Transportation</span>				Rail Division	
RAILROAD SCOPE OF WORK					
PROJECT SPECIFIC DETAILS					
SHEET 3 OF 5					
FILE:	RR Scope of Work.dgn	DN: TxDOT	CK:	DW:	CK:
© TxDOT	June 2014	CONT	SECT	JOB	HIGHWAY
9/2021	REVISIONS	0064	01	069, ETC	SH 87, ETC
	DIST	COUNTY		SHEET NO.	
	LFK	SHELBY, ETC		49	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \_\_\_\_\_  
 FILE: \_\_\_\_\_

**I. WORK AT CROSSING LOCATIONS (AT GRADE, HIGHWAY OVERPASS, HIGHWAY UNDERPASS, PEDESTRIAN, OR CLOSED/ABANDONED)**

DOT #: 755803T  
 Crossing Type: AT GRADE  
 RR Company Owning Track at Crossing: UNION PACIFIC RAILROAD COMPANY  
 Operating RR Company at Track: UNION PACIFIC RAILROAD COMPANY  
 RR MP: 108.230  
 RR Subdivision: LUFKIN  
 City: DIBOLL  
 County: ANGELINA  
 CSJ at this Crossing: 2589-01-026  
 Highway/Roadway name crossing the railroad: RYAN CHAPEL RD/FM 2497  
 # of regularly scheduled trains per day at this crossing: 8  
 # of switching movements per day at this crossing: 0  
 % of estimated contract cost of work within railroad ROW: 0.1%

Scope of Work at this Crossing to Be Performed by State Contractor:  
 DISTRICT WIDE SEALCOAT PROJECT WHICH WILL CONSIST OF APPLYING ASPHALT AND AGGREGATE TO THE EXISTING PAVEMENT SURFACE UP TO THE EXISTING TRACK CROSSING.

Scope of Work at this Crossing to Be Performed by Railroad Company:  
 PROVIDE FLAGGING SERVICES WHENEVER THE WORK IS WITHIN 25 FEET OF THE NEAREST RAIL.

\*\* Choose: Highway Overpass, Highway Underpass, At Grade, Pedestrian, or Closed/Abandoned

**II. OTHER PROJECT WORK WITHIN RAILROAD RIGHTS-OF-WAY (ROW)**

N/A

**III. FLAGGING & INSPECTION**

# of Days of Railroad Flagging Expected: 1  
 On this project, night or weekend flagging is:  
 Expected  
 Not Expected  
 Flagging services will be provided by:  
 Railroad Company: TxDOT will pay flagging invoices  
 Outside Party: Contractor will pay flagging invoices, to be reimbursed by TxDOT

Contractor must incorporate flaggers into anticipated construction schedule. The Railroad requires a 30 day notice if their flaggers are to be utilized. If Contractor falls behind schedule due to their own negligence and is not ready for scheduled flaggers, any flagging charges will be paid by Contractor.

Contact Information for Flagging:  
 UPRR - UP.info@railpros.com  
 Call Center 877-315-0513, Select #1 for flagging  
 - UP.request@nrssinc.net  
 Call Center 877-984-6777  
 BNSF - BNSF.info@railpros.com  
 Call Center 877-315-0513, Select #1 for flagging  
 KCS - KCS.info@railpros.com  
 Call Center 877-315-0513, Select #1 for flagging  
 - Bottom Line On-Track Safety Services  
 bottomline076@aol.com, 903-767-7630

OTHERS \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Contractor must incorporate Construction Inspection into anticipated construction schedule.

Not Required  
 Required: Contact Information for Construction Inspection:  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**IV. CONSTRUCTION WORK TO BE PERFORMED BY THE RAILROAD**

On this project, construction work to be performed by a railroad company is:  
 Required  
 Not Required

Coordinate with TxDOT for any work to be performed by the Railroad Company. TxDOT must issue a work order for any work done by the Railroad Company prior to the work being performed.

**V. RAILROAD INSURANCE REQUIREMENTS**

Railroad reference number shall be provided by TxDOT CST or DO.  
 The Contractor shall confirm the insurance requirements with the Railroad as the insurance limits are subject to change without notice. Insurance policies must be issued for and on behalf of the Railroad. Where more than one Railroad Company is operating on the same right of way or where several Railroad Companies are involved and operate on their own separate rights of way, provide separate insurance policies in the name of each Railroad Company.

No direct compensation will be made to the Contractor for providing the insurance coverages shown below or any deductibles. These costs are incidental to the various bid items.

Type of Insurance	Amount of Coverage (Minimum)
Workers Compensation	\$500,000 / \$500,000 / \$500,000
Commercial General Liability	\$2,000,000 / \$4,000,000
Business Automobile	\$2,000,000 combined single limit

Railroad Protective Liability	
<input type="checkbox"/> Not Required	
<input checked="" type="checkbox"/> Non - Bridge Projects	\$2,000,000 / \$6,000,000
<input type="checkbox"/> Bridge Projects	\$5,000,000 / \$10,000,000
<input type="checkbox"/> Other	

**VI. CONTRACTOR'S RIGHT OF ENTRY (ROE) AGREEMENT**

On this project, an ROE agreement is:  
 Not Required  
 Required: TxDOT CST to assist in obtaining with the UPRR (see Item 5, Article 8.3)  
 Required: UPRR Maintenance Consent Letter. TxDOT CST to assist.  
 Required: Contractor to obtain (see Item 5, Article 8.4)  
 With the following railroad companies: \_\_\_\_\_

To view previously approved ROE Agreement templates agreed upon between the State and Railroad, see:

<http://www.txdot.gov/inside-txdot/division/rail/samples.html>

Approved ROE Agreement templates are not to be modified by the Contractor.

Contractor shall not operate within Railroad Right of Way without an executed Construction & Maintenance Agreement between the State and the Railroad and an executed ROE agreement between the Contractor and the Railroad if required on project.

**VII. RAILROAD COORDINATION MEETING**

On this project, a Railroad Coordination Meeting is:  
 Not Required  
 Required

See Item 5, Article 8.1 for more details.

**VIII. SUBCONTRACTORS**

Contractor shall not subcontract work without written consent of TxDOT. Subcontractors are required to maintain the same insurance coverage as required of the Contractor.

**IX. EMERGENCY NOTIFICATION**

**In Case of Railroad Emergency**  
 Call Union Pacific Railroad Company  
 Railroad Emergency Line at 888-877-7267  
 Location: DOT 755803T  
 RR Milepost: 108.230  
 Subdivision: Lufkin

Rail Division

## RAILROAD SCOPE OF WORK

### PROJECT SPECIFIC DETAILS

SHEET 4 OF 5

FILE: RR Scope of Work.dgn	DN: TxDOT	CK: _____	DW: _____	CK: _____
© TxDOT June 2014	CONT	SECT	JOB	HIGHWAY
9/2021	REVISIONS	0064 01	069, ETC	SH 87, ETC
	DIST	COUNTY	SHEET NO.	
	LFK	SHELBY, ETC	50	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \_\_\_\_\_  
 FILE: \_\_\_\_\_

**I. WORK AT CROSSING LOCATIONS (AT GRADE, HIGHWAY OVERPASS, HIGHWAY UNDERPASS, PEDESTRIAN, OR CLOSED/ABANDONED)**

DOT #: 024052K  
 Crossing Type: AT GRADE  
 RR Company Owing Track at Crossing: BNSF RAILWAY COMPANY  
 Operating RR Company at Track: BNSF RAILWAY COMPANY  
 RR MP: 120.430  
 RR Subdivision: LONGVIEW  
 City: SAN AUGUSTINE  
 County: SAN AUGUSTINE  
 CSJ at this Crossing: 0118-09-009  
 Highway/Roadway name crossing the railroad: LP 547  
 # of regularly scheduled trains per day at this crossing: 4  
 # of switching movements per day at this crossing: 0  
 % of estimated contract cost of work within railroad ROW: 0.1%

Scope of Work at this Crossing to Be Performed by State Contractor:  
 DISTRICT WIDE SEALCOAT PROJECT WHICH WILL CONSIST OF APPLYING ASPHALT AND AGGREGATE TO THE EXISTING PAVEMENT SURFACE UP TO THE EXISTING TRACK CROSSING.

Scope of Work at this Crossing to Be Performed by Railroad Company:  
 PROVIDE FLAGGING SERVICES WHENEVER THE WORK IS WITHIN 25 FEET OF THE NEAREST RAIL.

\*\* Choose: Highway Overpass, Highway Underpass, At Grade, Pedestrian, or Closed/Abandoned

**II. OTHER PROJECT WORK WITHIN RAILROAD RIGHTS-OF-WAY (ROW)**

N/A

**III. FLAGGING & INSPECTION**

# of Days of Railroad Flagging Expected: 1

On this project, night or weekend flagging is:

- Expected
- Not Expected

Flagging services will be provided by:

- Railroad Company: TxDOT will pay flagging invoices
- Outside Party: Contractor will pay flagging invoices, to be reimbursed by TxDOT

Contractor must incorporate flaggers into anticipated construction schedule. The Railroad requires a 30 day notice if their flaggers are to be utilized. If Contractor falls behind schedule due to their own negligence and is not ready for scheduled flaggers, any flagging charges will be paid by Contractor.

Contact Information for Flagging:

- UPRR - UP.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging  
- UP.request@nrssinc.net  
Call Center 877-984-6777
- BNSF - BNSF.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging
- KCS - KCS.info@railpros.com  
Call Center 877-315-0513, Select #1 for flagging  
- Bottom Line On-Track Safety Services  
bottomline076@aol.com, 903-767-7630

OTHERS \_\_\_\_\_

Contractor must incorporate Construction Inspection into anticipated construction schedule.

- Not Required
- Required: Contact Information for Construction Inspection:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**IV. CONSTRUCTION WORK TO BE PERFORMED BY THE RAILROAD**

On this project, construction work to be performed by a railroad company is:

- Required
- Not Required

Coordinate with TxDOT for any work to be performed by the Railroad Company. TxDOT must issue a work order for any work done by the Railroad Company prior to the work being performed.

**V. RAILROAD INSURANCE REQUIREMENTS**

Railroad reference number shall be provided by TxDOT CST or DO.

The Contractor shall confirm the insurance requirements with the Railroad as the insurance limits are subject to change without notice.

Insurance policies must be issued for and on behalf of the Railroad. Where more than one Railroad Company is operating on the same right of way or where several Railroad Companies are involved and operate on their own separate rights of way, provide separate insurance policies in the name of each Railroad Company.

No direct compensation will be made to the Contractor for providing the insurance coverages shown below or any deductibles. These costs are incidental to the various bid items.

Type of Insurance	Amount of Coverage (Minimum)
Workers Compensation	\$500,000 / \$500,000 / \$500,000
Commercial General Liability	\$2,000,000 / \$4,000,000
Business Automobile	\$2,000,000 combined single limit

Railroad Protective Liability	
<input type="checkbox"/> Not Required	
<input checked="" type="checkbox"/> Non - Bridge Projects	\$2,000,000 / \$6,000,000
<input type="checkbox"/> Bridge Projects	\$5,000,000 / \$10,000,000
<input type="checkbox"/> Other	

**VI. CONTRACTOR'S RIGHT OF ENTRY (ROE) AGREEMENT**

On this project, an ROE agreement is:

- Not Required
- Required: TxDOT CST to assist in obtaining with the UPRR (see Item 5, Article 8.3)
- Required: UPRR Maintenance Consent Letter. TxDOT CST to assist.
- Required: Contractor to obtain (see Item 5, Article 8.4)

With the following railroad companies: \_\_\_\_\_

To view previously approved ROE Agreement templates agreed upon between the State and Railroad, see:

<http://www.txdot.gov/inside-txdot/division/rail/samples.html>

Approved ROE Agreement templates are not to be modified by the Contractor.

Contractor shall not operate within Railroad Right of Way without an executed Construction & Maintenance Agreement between the State and the Railroad and an executed ROE agreement between the Contractor and the Railroad if required on project.

**VII. RAILROAD COORDINATION MEETING**

On this project, a Railroad Coordination Meeting is:

- Not Required
- Required

See Item 5, Article 8.1 for more details.

**VIII. SUBCONTRACTORS**

Contractor shall not subcontract work without written consent of TxDOT. Subcontractors are required to maintain the same insurance coverage as required of the Contractor.

**IX. EMERGENCY NOTIFICATION**

**In Case of Railroad Emergency**  
 Call BNSF Railway Company  
 Railroad Emergency Line at 800-832-5452 Option 1  
 Location: DOT 024052K  
 RR Milepost: 120.430  
 Subdivision: Longview

<span style="font-weight: bold;">Texas Department of Transportation</span>				Rail Division	
RAILROAD SCOPE OF WORK					
PROJECT SPECIFIC DETAILS					
SHEET 5 OF 5					
FILE:	RR Scope of Work.dgn	DN: TxDOT	CK:	DW:	CK:
© TxDOT	June 2014	CONT	SECT	JOB	HIGHWAY
9/2021	REVISIONS	0064	01	069, ETC	SH 87, ETC
	DIST	COUNTY		SHEET NO.	
	LFK	SHELBY, ETC		51	

**PART 1 - GENERAL**

**1.01 DESCRIPTION**

This project includes construction work within the right of way and/or properties of the Railroad and adjacent to its tracks, wire lines and other facilities. These sheets describe the minimum special requirements for coordination with the Railroad when working upon, over or under Railroad Right of Way or when impacting current or future Railroad operations. Coordinate with the Railroad while performing the work outlined herein, and afford the same cooperation with the Railroad as with TxDOT. Complete all submittals and work in accordance with TxDOT Standard Specifications, Railroad Guidelines and AREMA recommendations as modified by these minimum special requirements or as directed in writing by the Railroad Designated Representative.

For purposes of this project, the Railroad Designated Representative is the person or persons designated by the Railroad Manager of Industry and Public Projects to handle specific tasks related to the project.

**1.02 REQUEST FOR INFORMATION / CLARIFICATION**

Submit Requests for Information ("RFI") involving work within any Railroad Right of Way to the TxDOT Engineer. The TxDOT Engineer will submit the RFI to the Railroad Designated Representative for review and approval for RFI's corresponding to work within Railroad Right of Way. Allow six (6) weeks total time for review and approval, which includes four (4) weeks for review and approval by the Railroad.

**1.03 PLANS / SPECIFICATIONS**

TxDOT has received written Railroad approval of the plans and specifications for this project. Any revisions or changes in the plans after award of the Contract must have the approval of TxDOT and the Railroad.

**PART 2 - UTILITIES AND FIBER OPTIC**

Construct all utility installations in accordance with current AREMA recommendations, Railroad, TxDOT and owning utility specifications and requirements. Railroad general guidelines can be found on the Railroad website or by contacting the Railroad Designated Representative.

**PART 3 - CONSTRUCTION**

**3.01 GENERAL**

- A. Perform all work in compliance with all applicable Railroad, Federal Railroad Administration (FRA), and TxDOT rules and regulations. Arrange and conduct work in a manner that does not endanger or interfere with the safe operation of the tracks and property of the Railroad and the traffic moving on such tracks, or the wires, signals and other property of the Railroad, its tenants or licensees, at or in the vicinity of the Work. The safe operation of railroad train movements takes precedence over any work to be performed by the Contractor. The Contractor is responsible for train delay cost and lost revenue claims due to any delays or interruption of train operations resulting from Contractor's construction or other activities.
- B. Construction activities within 15 feet of the operational tracks will only be allowed if absolutely necessary and the Railroad's Designated Representative grants approval. Construction activities within 15 feet of the operational track(s) preferably allow the tracks to stay operational. In such cases, coordination and approval by the Railroad Track Manager is required with regard to schedule, flagging, and slow orders. See Sections 3.07 and 3.08 for additional information.
- C. Provide track protection for all work equipment (including rubber tired equipment) operating within 25 feet from nearest rail. When not in use, keep Contractor machinery and materials at least 50 feet from the Railroad's nearest track.
- D. Vehicular crossings of railroad track are allowed only at existing crossings, or haul road crossings developed with Railroad approval.
- E. The Contractor is also advised that new railroad facilities within the project may be built by the Railroad. If applicable, these facilities are delineated in the plans. Be aware of the limits of responsibilities and coordinate efforts with the Railroad and TxDOT.
- F. Railroad requirements do not allow work within 50 feet of track centers when a train passes the work site and all personnel must clear the area within 50 feet of the track centerline and secure all equipment. Additional allowances may be pursued as outlined in 3.02 and 3.03.
- G. All permanent clearances shall be verified before project closing.

**3.02 RAILROAD OPERATIONS**

- A. Trains and/or equipment are expected on any track, at any time, in either direction. Become familiar with the train schedules in this location and structure bid assuming intermittent track windows in this period, as defined in Paragraph B that follows.
- B. All railroad tracks within and adjacent to the contract site are active, and rail traffic over these facilities shall be maintained throughout the Project. Activities may include both through moves and switching moves to local customers. Railroad traffic and operations will occur continuously throughout the day and night on these tracks and shall be maintained at all times as defined herein. Coordinate and schedule the work so that construction activities do not interfere with railroad operations.
- C. Coordinate work windows with TxDOT and the Railroad's Designated Representative. Types of work windows include Conditional Work Windows and Absolute Work Windows, as defined below:
  - 1. Conditional Work Window: A Conditional Work Window is a period of time that railroad operations have priority over construction activities. When construction activities may occur on and/or adjacent to the railroad tracks within 25 feet of the nearest track, a railroad flag person will be required. At the direction of the railroad flag person, upon approach of a train, and when trains are present on the tracks, the tracks must be cleared (i.e., no construction equipment, materials or personnel within 25 feet, or as directed by the Railroad Designated Representative, from the tracks). Conditional Work Windows are available for the Project.
  - 2. Absolute Work Window: An Absolute Work Window is a period of time that construction activities are given priority over railroad operations. During this time frame, the designated railroad track(s) will be inactive for train movements and may be fouled by the Contractor. At the end of an Absolute Work Window, the railroad tracks and/or signals must be completely operational for train operations and all Railroad, Public Utilities Commission (PUC) and FRA requirements, codes and regulations for operational tracks must be satisfied. In the situation where the operating tracks and/or signals have been affected, the Railroad will perform inspections of the work prior to placing that track back into service. Railroad flag persons will be required for construction activities requiring an Absolute Work Window. Absolute Work Windows will not generally be granted. Any request will require a detailed explanation for Railroad review.

**3.03 RIGHT OF ENTRY, ADVANCE NOTICE AND WORK STOPPAGES**

- A. Do not perform any work within Railroad Right of Way without a valid executed Right of Entry Agreement if required on this project.
- B. Give advance notice to the Railroad as required in the "Contractor's Right of Entry Agreement" before commencing work in connection with construction upon or over Railroad Right of Way and observe the Railroad's rules and regulations with respect thereto.
- C. Perform all work upon Railroad Right of Way in a manner to avoid interference with or endanger the operations of the Railroad. Whenever work may affect the operations or safety of trains, submit the work method to the Railroad Designated Representative for approval. Approval does not relieve the Contractor from liability. Do not commence any work which requires flagging service or inspection service until the flagging protection required by the Railroad is available at the job site. See Section 3.15 for railroad flagging requirements.
- D. Make requests in writing for both Absolute and Conditional Work Windows, at least 30 days in advance of any work. Include in the written request:
  - 1. Exactly what the work entails.
  - 2. The days and hours that work will be performed.
  - 3. The exact location of work, and proximity to the tracks.
  - 4. The type of window requested and the amount of time requested.
  - 5. The designated contact person.

Provide a written confirmation notice to the Railroad at least 48 hours before commencing work in connection with approved work windows when work is within 25 feet of nearest rail. Perform all work in accordance with previously approved work plans.
- E. Make provisions to protect operations and property of the Railroad should a condition arising from, or in connection with the work, require immediate and unusual action. If in the judgment of the Railroad Designated Representative such provisions are insufficient, the Railroad Designated Representative may require or provide such provisions as deemed necessary. In any event, such provisions shall be at the Contractor's expense and without cost to the Railroad or TxDOT. The Railroad or TxDOT shall have the right to order the Contractor to temporarily cease operations in the event of an emergency or, if in the opinion of the Railroad Designated Representative, the Contractor's operations could endanger railroad operations. In the event of such an order, immediately notify TxDOT of the order.

**3.04 INSURANCE**

Do not begin work upon or over Railroad Right of Way until furnishing the Railroad with the insurance policies, binders, certificates and endorsements required by the "Contractor's Right of Entry Agreement", and until the Railroad Designated Representative has advised TxDOT that such insurance is in accordance with the Agreement.

**3.05 RAILROAD SAFETY ORIENTATION**

- A. Complete the railroad course "Orientation for Contractor's Safety", and maintain current registration prior to working on railroad property. This course is required to be completed annually by Contractor and Subcontractor personnel working on site.
 

"UPRR, BNSF, KCS/TEXMEX will not accept on-track safety training certificates from other railroads. Refer to Railroad specific contractor right of entry for training information."
- B. Know and follow the "Contractor's Right of Entry Agreement" EXHIBIT D, MINIMUM SAFETY REQUIREMENTS regarding clothing, personal protective equipment, and general safety requirements.

**3.06 COOPERATION**

The Railroad will cooperate with Contractor so that work may be conducted in an efficient manner, and will cooperate with Contractor in enabling use of Railroad Right of Way in performing the work.

**3.07 MINIMUM CONSTRUCTION CLEARANCES FOR FALSEWORK AND OTHER TEMPORARY STRUCTURES**


Abide by the following minimum temporary clearances during the course of construction:

- A. 15' - 0" (BNSF) (UPRR) and 14' - 0" (KCS) horizontal from centerline of track
- B. 22' (KCS) and 21' - 6" (UPRR & BNSF) vertically above top of rail.

For construction clearance less than listed above, obtain local Railroad Operating Unit review and approval.

**3.08 APPROVAL OF REDUCED CLEARANCES**

- A. Maintain minimum track clearances during construction as specified in Section 3.07.
- B. Submit any proposed infringement on the specified minimum clearances to the Railroad Designated Representative through TxDOT at least 30 days in advance of the work. Do not proceed with such infringement without written approval by the Railroad Designated Representative.
- C. Do not commence work involving an approved infringement without receiving written assurance from the Railroad Designated Representative that arrangements have been made for any necessary flagging service.

				Rail Division	
<b>RAILROAD REQUIREMENTS FOR NON-BRIDGE CONSTRUCTION PROJECTS</b>					
FILE:	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT	
© TxDOT October 2018	CONT	SECT	JOB	HIGHWAY	
REVISIONS March 2020	0064	01	069, etc	SH 87, etc	
	DIST	COUNTY	SHEET NO.		
	LFK	SHELBY, ETC	52		

**3.09 MAINTENANCE OF RAILROAD FACILITIES**

- A. Maintain all ditches and drainage structures free of silt or other obstructions resulting from Contractor's operations. Repair eroded areas and any other damage within Railroad Right of Way and repair any other damage to the property of the Railroad, or its tenants.
- B. Perform all such maintenance and repair of damages due to the Contractor's operations at Contractor's expense.
- C. Submit a proposed method of erosion control for review by the Railroad prior to beginning any grading on the project site. Comply with all applicable local, state and federal regulations when developing and implementing such erosion control.

**3.10 SITE INSPECTIONS BY RAILROAD'S DESIGNATED REPRESENTATIVE**

- A. In addition to the office reviews of construction submittals, site inspections may be performed by the Railroad Designated Representative at significant points during construction, including the following if applicable:
  1. Pre-construction meetings.
  2. Pile driving/drilling of caissons or drilled shafts.
  3. Reinforcement and concrete placement for railroad bridge substructure and/or superstructure.
  4. Erection of precast concrete or steel bridge superstructure.
  5. Placement of waterproofing (prior to placing ballast on bridge deck).
  6. Completion of the bridge structure.
- B. Site inspection is not limited to the milestone events listed above. Site visits to check progress of the work may be performed at any time throughout the construction as deemed necessary by the Railroad.
- C. Provide a detailed construction schedule, including the proposed temporary horizontal and vertical clearances and construction sequence for all work to TxDOT for submittal to the Railroad Designated Representative for review prior to commencement of work. Include the anticipated dates when the above listed events will occur. Update this schedule for the above listed events as necessary and each month at a minimum to allow the Railroad to schedule site inspections.

**3.11 RAILROAD REPRESENTATIVES**

Railroad representatives, conductors, flag person or watch person will be provided by the Railroad at expense of TxDOT to protect Railroad facilities, property and movements of its trains or engines. In general, the Railroad will furnish such personnel or other protective services as follows:

- A. When any part of any equipment is standing or being operated within 25 feet, measured horizontally, from nearest rail of any track on which trains may operate, or when any object is off the ground and any dimension thereof could extend inside the 25 foot limit, or when any erection or construction activities are in progress within such limits, regardless of elevation above or below track.
- B. For any excavation below elevation of track subgrade if, in the opinion of the Railroad Designated Representative, track or other railroad facilities may be subject to settlement or movement.
- C. During any clearing, grubbing, excavation or grading in proximity to railroad facilities, which, in the opinion of the Railroad Designated Representative, may endanger railroad facilities or operations.
- D. During any Contractor's operations when, in the opinion of the Railroad Designated Representative, railroad facilities, including, but not limited to, tracks, buildings, signals, wire lines, or pipe lines, may be endangered.
- E. Arrange with the Railroad Designated Representative to provide the adequate number of flag persons to accomplish the work.

**3.12 COMMUNICATIONS AND SIGNAL LINES**

If required, the Railroad will rearrange its communications and signal lines, its grade crossing warning devices, train signals and tracks, and facilities that are in use and maintained by the Railroad's forces in connection with its operation at expense of TxDOT. This work by the Railroad will be done by its own forces and it is not a part of the Work under this Contract.

**3.13 TRAFFIC CONTROL**

Coordinate any operations that control traffic across or around railroad facilities with the Railroad Designated Representative.

**3.14 CONSTRUCTION EXCAVATIONS AND BORING ACTIVITIES UNDER TRACK**

- A. Take special precaution and care in connection with excavating and shoring. Excavations for construction of footings, piers, columns, walls or other facilities that require shoring shall comply with requirements of TxDOT, OSHA, AREMA and Railroad "Guidelines for Temporary Shoring".
- B. The project plans indicate whether there are fiber optic lines or other such telecommunications systems that require consideration. Regardless, contact the necessary call center to determine if such cable systems are present:

UPRR 1-800-336-9193  
7:00 AM to 9:00 PM CST Monday-Friday except holidays,  
staffed 24 hrs/day for emergencies  
48 hrs notice required

BNSF 1-800-533-2891  
24 hour number  
5 working days notice required

KCS 1-800-344-8377  
Texas One Call, a 24 hour number  
48 hrs notice required, excluding weekends and holidays

If a telecommunications system is buried anywhere on or near railroad property, coordinate with TxDOT, the Railroad and the Telecommunication Company(ies) to arrange for relocation or protective measures prior to beginning work on or near railroad property. Refer to the project General Notes for additional information.


- C. Projects involving a boring or jack and bore operation under track such as drainage pipes or culverts and utilities require an installation plan reviewed and approved by the Railroad and TxDOT prior to proceeding with such construction. A railroad inspector and contractor assisted monitoring of ground and track movement is required to maintain safe passage of rail traffic. Stop installation and do not allow passage of trains if movements in excess of 1/4 inch vertical or horizontal is detected in the tracks. Immediately repair the damage to the satisfaction of TxDOT and the Railroad before proceeding.

**3.15 RAILROAD FLAGGING**

Per the Right of Entry Agreement for flagging, notify the Railroad Representative at least 10 working days in advance of Contractor's work and at least 30 working days in advance of any Contractor's work in which any person or equipment will be within 25 feet of nearest rail or as specified in the Contractor Right of Entry (CROE).

**3.16 CLEANING OF RIGHT-OF-WAY**

When work is complete, remove all tools, implements, and other materials brought into Railroad Right of Way and leave the right of Way in a clean and presentable condition to the satisfaction of TxDOT and the Railroad.

 Texas Department of Transportation				Rail Division	
<b>RAILROAD REQUIREMENTS FOR NON-BRIDGE CONSTRUCTION PROJECTS</b>					
FILE:	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
© TxDOT October 2018	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0064	01	069, ETC	SH 87, ETC	
March 2020	DIST	COUNTY	SHEET NO.		
	LFK	SHELBY, ETC	53		

DATE: \$DATE\$ \$TIME\$  
 FILE: \$FILES\$