

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.	
	C 0065-07-009, ETC	1	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

DESIGN SPEED = N/A  
 A. D. T. ( 2021 ) = 50, 717  
 A. D. T. ( 2041 ) = 71, 004

FRONTAGE ROAD  
 FC: URBAN MAJOR COLLECTOR  
 A. D. T. ( 2021 ) = 4, 023  
 A. D. T. ( 2041 ) = 5, 632

**INDEX OF SHEETS**

SEE SHEET NO. 2

**STATE OF TEXAS  
 DEPARTMENT OF TRANSPORTATION**

**PLANS OF PROPOSED  
 STATE HIGHWAY IMPROVEMENT**

STATE AID PROJECT  
 PROJECT NO: C 0065-07-009, ETC  
 CSJ: 0065-06-070, etc.

**US 69  
 HARDIN COUNTY, ETC.**

0065-06-070 - NET LENGTH OF ROADWAY = 15,222.24FT. = 2.883 MI.  
 0065-07-070 - NET LENGTH OF ROADWAY = 2803.68FT. = 0.531 MI.  
 0200-11-099 - NET LENGTH OF ROADWAY = 18,136.8FT. = 3.435 MI.  
 TOTAL NET LENGTH OF PROJECT = 36,162.72FT. = 6.849 MI.

0065-06-070 - LIMIT: FROM: US69 US96 Y. SOUTH. TO: HARDIN COUNTY LINE  
 0065-07-070 - LIMIT: FROM: HARDIN COUNTY LINE SOUTH. TO: TRAM ROAD  
 0200-11-099 - LIMIT: FROM: LNVA CANAL, SOUTH. TO: DELAWARE STREET

FOR THE CONSTRUCTION OF A OVERLAY PROJECT


CONSISTING OF SURFACING AND ROADWAY RESTORATION

REQUIRED SIGNS SHALL BE IN ACCORDANCE WITH  
 BC (1)-21 THRU BC (12)-21 AND THE "TEXAS MANUAL  
 ON UNIFORM TRAFFIC CONTROL DEVICES".

END PROJECT  
 CSJ: 0065-06-070  
 STA: 617+11  
 REF MRK: 512+1.237

END PROJECT  
 CSJ: 0065-07-070  
 STA: 359+25  
 REF MRK: 514+2.093

END PROJECT  
 CSJ: 0200-11-099  
 STA: 214+25  
 REF MRK: 518+0.768



BEGIN PROJECT  
 CSJ: 0065-06-070  
 STA: 464+87  
 REF MRK: 514+2.093

BEGIN PROJECT  
 CSJ: 0065-07-070  
 STA: 328+82  
 REF MRK: 516+0.475

BEGIN PROJECT  
 CSJ: 0200-11-099  
 STA: 32+50  
 REF MRK: 522+0.272

EXCEPTIONS: N/A  
 EQUATIONS: N/A  
 RAILROAD CROSSINGS: N/A



SUBMITTED FOR LETTING: 1/6/2023  
 Designed by: *Linda Lindsay*, P.E.  
 DISTRICT DESIGN ENGINEER  
 APPROVED FOR LETTING: 1/6/2023  
*Monte N. York, P.E.*  
 DISTRICT ENGINEER

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION,  
 JUNE 1, 2004 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS,  
 SHALL GOVERN ON THIS PROJECT: REQUIRED SPECIAL LABOR  
 PROVISIONS FOR ALL STATE CONSTRUCTION PROJECTS. (SP000--2381)

© 2022  
 BY TEXAS DEPARTMENT OF TRANSPORTATION  
 ALL RIGHTS RESERVED.

FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\001 Title.dgn  
 DATE: 1/3/2023 3:13:10 PM

# INDEX OF SHEETS

**SHEET      DESCRIPTION**

**GENERAL**

- 1    TITLE SHEET
- 2    INDEX OF SHEETS
- 3-5   TYPICAL SECTIONS
- 6-14   GENERAL NOTES
- 15-16   ESTIMATE & QUANTITY
- 17-19   QUANTITY SUMMARY

**TRAFFIC CONTROL PLAN**

- 20    SEQUENCE OF WORK
- # 21-32   BC (1)-21 THRU BC (12)-21
- # 33    TCP (2-1)-18
- # 34    TCP (2-4)-18
- # 35    TCP (3-2)-13
- # 36    TCP (3-3)-14
- # 37    TCP (5-1)-18
- # 38-42   TCP (6-1)-12 THRU TCP (6-5)-12
- # 43    TCP (SC-5)-22
- # 44    TCP (SC-6)-22
- # 45    TCP (SC-7)-22
- # 46    WZ (STPM)-13
- # 47    WZ (UL)-13
- # 48    WZ (RS)-22

**ROADWAY DETAILS**


- 49-64   ROADWAY LAYOUT
- 65-66   DOWEL BAR RETROFIT DETAILS
- # 67    CCCG-22
- # 68    JS-14
- # 69-70   REPCP-14

**PAVEMENT MARKINGS & DELINEATION**

- 71-86   STRIPING LAYOUT
- # 87    PM (1)-22
- # 88    PM (2)-22
- # 89    FPM (1)-22
- # 90    FPM (2)-22
- # 91    FPM (3)-22

**ENVIRONMENTAL**

- 92    ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS



THE STANDARD SHEETS SPECIFICALLY IDENTIFIED WITH A "##" HAVE BEEN ISSUED BY ME AND ARE APPLICABLE TO THIS PROJECT.

*Jason D. Waldrep, P.E.*

NAME \_\_\_\_\_ DATE 01/03/2023


FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\2 Index.dgn  
DATE: 1/3/2023 3:13:13 PM

## INDEX OF SHEETS



FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.	2
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69


FILE: T:\BMTDESIGN\Projects\0665-06-070+US69\DCN\TYPICAL SECTIONS.dgn  
 DATE: 1/3/2023 3:13:16 PM



**EXISTING TYPICAL SECTION**

STA. 333+77 TO STA. 359+44.5  
 STA. 471+76 TO STA. 498+76  
 STA. 504+05 TO STA. 543+91  
 STA. 554+36 TO STA. 605+27


EXISTING 12" CONCRETE PAVEMENT  
 EXISTING 6" CEMENT STABILIZED BASE  
 EXISTING 6" SELECT EMB (TY C)



**PROPOSED TYPICAL SECTION**


STA. 333+77 TO STA. 359+44.5  
 STA. 471+76 TO STA. 498+76  
 STA. 504+05 TO STA. 543+91  
 STA. 554+36 TO STA. 605+27

PROPOSED 1.5" PFC OVERLAY  
 PROPOSED SEAL COAT



DEPRESSED GUTTER A  
 STA. 519+08 TO STA. 520+29  
 STA. 536+87 TO STA. 537+43


DEPRESSED GUTTER B  
 STA. 518+60 TO STA. 519+08  
 STA. 536+10 TO STA. 536+87



Jason D. Waldrep, P.E.

01/03/2023  
 US69


**TYPICAL SECTION**



SCALE IN FEET  
 Texas Department of Transportation


FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				3	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		

FILE: T:\BMTDESIGN\Projects\0065-06-070+US69\DCN\TYPICAL SECTIONS.dgn  
 DATE: 1/3/2023 3:13:18 PM




**EXISTING TYPICAL SECTION**

STA. 328+82 TO STA. 333+77  
 STA. 464+87 TO STA. 471+76  
 STA. 498+76 TO STA. 504+05  
 STA. 543+91 TO STA. 554+36  
 STA. 605+27 TO STA. 617+11



**PROPOSED TYPICAL SECTION**


STA. 328+82 TO STA. 333+77  
 STA. 464+87 TO STA. 471+76  
 STA. 498+76 TO STA. 504+05  
 STA. 543+91 TO STA. 554+36  
 STA. 605+27 TO STA. 617+11



*Jason D. Waldrep, P.E.*

01/03/2023  
**US69**


**TYPICAL SECTIONS**



SCALE IN FEET  
 Texas Department of Transportation


FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.
				4
STATE	DISTRICT	COUNTY		
TEXAS	BMT	HARDIN		
CONTROL	SECTION	JOB	HIGHWAY NO.	
0065	06	070, ETC	US69	

FILE: T:\BMTDESIGN\Projects\0665-06-070+US69\DCN\TYPICAL SECTIONS.dgn  
 DATE: 1/3/2023 3:13:19 PM




EXISTING TYPICAL SECTION

STA. 32+50 TO STA. 213+80




PROPOSED TYPICAL SECTION

STA. 32+50 TO STA. 213+80



DETAIL "A"  
ALL CURB SECTIONS  
NTS


SLOPES DENOTED WITH # ARE TO MATCH EXISTING SLOPE



Jason D. Waldrep, P.E.

01/03/2023  
US69

TYPICAL SECTIONS



SCALE IN FEET  
Texas Department of Transportation

FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				5	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		

**GENERAL NOTES:**

Contractor questions on this project are to be addressed to the following individual(s):

Name Dave Collins, P.E., Beaumont Area Engineer

Email [dave.collins@txdot.gov](mailto:dave.collins@txdot.gov)

Name Taylor Kane, P.E., Beaumont Asst. Area Engineer

Email [Taylor.Kane@txdot.gov](mailto:Taylor.Kane@txdot.gov)

Contractor questions will be accepted through email, phone and in person by the above individuals.

For Q&A's on Proposals navigate to:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>.

Use the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink for the project you want to view the Q&A for and click on the link in the window that pops up.

All questions submitted that generate a response will be posted through this site. The site is organized by District, Project Type (Construction or Maintenance), Letting Date, CCSJ/Project Name.

The contractor is advised that a 55 mph construction speed zone will be applicable for this project. The construction speed zone will be limited to the actual work areas under construction.

Assume full responsibility for the preservation of all sod, shrubbery, and trees at the site during construction. Carefully preserve and replace, in their original position, all sod and shrubbery removed. Replace all Contractor damaged sod or shrubbery at the Contractor's own expense.

Maintain adequate drainage throughout the limits of the project during all construction phases.

Provide a weekly a list of equipment, including idle equipment, used on the project each week.

**Item 4 Scope of Work**

Remove all vegetation from pavement edges, intersections and driveways before planing or ACP operations. This work will not be paid for directly but will be subsidiary to the various bid items.

It is the contractor's responsibility to field verify all drainage structure's shown in the plans.

It is the contractor's responsibility to mark the location of all existing striping and place proposed striping back in the same location or as shown in the plans.

**Item 5 Control of the Work**

Station the project before commencing work. Mark the stations every 100 feet. Maintain stationing throughout the duration of the project. Remove the station markings at the completion of the project. Consider this work to be subsidiary to the various bid items of the contract.

Verify all horizontal and vertical control, approach grades to structures and driveways before beginning work. Notify the Engineer immediately if discrepancies are discovered.

**Item 6 Control of Materials**

Flammable/combustible materials must be stored at a designated location as approved.

Do not store flammable/combustible materials under or adjacent to Bridge class structures. Daily removal of these materials will be considered incidental work.

Mixing of materials, storing of materials, storing of equipment, or repairing of equipment on top of concrete pavement or bridge decks will not be permitted unless specifically authorized.

**Item 7 Legal Relations and Responsibilities**

Furnish all materials, labor and incidentals required to provide for traffic across the highway and for temporary ingress and egress to private property in accordance with article 7.2.4 of the standard specifications at no additional cost to the state. Maintain ingress and egress to the adjacent property at all times. Consider this work to be subsidiary to the various bid items of the contract.

The Contractor will be completely responsible for the immediate removal of any material that gets upon any vehicle as a result of their operation.

State contract mowers will mow the right of way during the growing season. The Contractor will be notified by the Engineer one week in advance of the anticipated time when mowers will be in the limits of the project. Clean the right of way to such a condition that allows the mowing contractors to safely mow.

Personal vehicles of the contractor's employees will not be parked within the right of way at any time including any section closed to public traffic, unless the vehicle is being used for construction procedures. However, the Contractor's employees may park on the right of way at sites where the contractor has their office, equipment and materials storage yard.

The Contractor should be familiar with the limits of right of way when operations require equipment near the right of ways edge. In this case care will be taken by the Contractor and its subcontractors to protect and avoid disturbance to the right of way monumentation. Any monument disturbed by the Contractor will be repaired and/or replaced to the satisfaction of the Engineer. This work will be corrected at the contractor's expense.

No significant traffic generator events have been identified in the project limits.

**Item 8 Prosecution and Progress**

Working days will be charged during all observed curing times, even if no other work is being performed

Compute and charge working days in accordance with Section 8.3.3.2.1, in the Standard Specifications for Construction and Maintenance of Highways, Streets, and Bridges; "Nighttime Work Only".

Nighttime Work hours are defined as follows:

Sunday night at 8 P.M. to Monday morning at 6 A.M.

Monday night at 8 P.M. to Tuesday morning at 6 A.M.

Tuesday night at 8 P.M. to Wednesday morning at 6 A.M.

Wednesday night at 8 P.M. to Thursday morning at 6 A.M.

Thursday night at 8 P.M. to Friday morning at 6 A.M.

Following a Request, In Writing (by the Contractor), Approval, In Writing (from the Area Engineer) Daytime Work will be allowed for daytime hours ranging from 9 A.M. to 3 P.M.

Adjoining projects may be in progress during the construction of a portion of this project. Plan and prosecute the sequence of construction and the traffic control plan with adjacent construction projects, if applicable. Manage construction of all phases to minimize disruption to traffic.

Notify the Engineer 72 hours in advance of any temporary or permanent lane, ramp or connector affected by closures, detours, or restrictions to lane widths, alterations to vertical clearances or modifications to alignment/radii. Any other modification to the roadway that may adversely affect the mobility of oversized/overweight trucks will require 5 business day advance written notice to the Engineer.

Maintain one lane open to traffic during construction, unless otherwise approved.

Schedule work so that all travel lanes are open during non-working hours and weekends, unless otherwise approved.

Supplemental lighting in addition to lighting on equipment and work vehicles will be required to insure adequate lighting for workers safety and inspection. All operations including planing and ACP placement must be adequately lighted using supplemental lighting. All supplemental lights are subject to the approval of the Engineer. Supplemental lighting will be added to the milling machine, asphalt distributor, aggregate spreader, rollers and laydown machine unless otherwise approved. This is considered subsidiary to the various bid Items of the contract.

The Engineer will suspend time charges after completion of all work and removal of the barricades. The Department will grant final acceptance when all performance periods are complete.

Accrue Contract time charges through the Contractor's completion of the final punch list. Time will not be suspended until all work is completed.

Submit a work schedule to the Engineer at the preconstruction meeting indicating completion dates for each location, and the number of crews required for the completion of the contract within the contract time period. If at any time during the contract the work progress is behind the initial schedule, submit documentation indicating how the project will be accelerated to ensure project completion in the remaining contract time.

Provide a sequence of work with an estimated project schedule to the Engineer at the preconstruction meeting. By noon of each Wednesday, provide the Engineer a written outline of the proposed work schedule for the following week. This outline will also list the times and places for any proposed traffic control changes.

For this project, create and maintain the critical path method (CPM) schedule.

Work will not be permitted when impending bad weather or low temperatures may impair the quality of work.

This project consists of three project locations. Work is restricted to one project location at a time as spelled out in the Sequence of Work prior to moving to another project location.

The construction sequence may be modified as directed and approved.

Law enforcement will be considered for this contract under the following conditions unless otherwise directed:

- Work involving controlled access facilities,
- Night work operations that create substantial traffic safety risks for workers and/or road users,
- Major traffic shifts involving high speed (greater than 55 MPH) and/or high-volume roadways (ADT exceeds 10,000),
- Traffic shifts at intersections where unexpected or sudden queuing is anticipated,
- Complex intersections where flaggers may not be able to maintain adequate traffic control.

Provide full-time, off-duty uniformed officer(s), with transportation jurisdiction and full police powers in the county or city in which the project is located, during construction as directed. The

officer(s) must be able to show proof of certification by the Texas Commission on Law Enforcement Officers Standards.

Officer(s) will be paid by force account and must be approved. The vehicle used must be a marked law enforcement vehicle in the city or county where the project is located. Complete the daily tracking form provided by the Department and submit invoices that agree with the tracking form for payment at the end of each month approved services were provided.

### **HURRICANE**

In the event of the declaration of a hurricane watch, warning, other severe weather warning or national or state emergency that requires the roadways in the vicinity be used as evacuation routes, cease all work that requires the Contractor's, sub-contractors' or material suppliers' vehicles to enter the stream of traffic on these primary or secondary evacuation routes. This work includes material hauling and delivery, and mobilization or demobilization of equipment.

This project is on a hurricane evacuation route. Furnish at the pre-construction meeting a written plan outlining procedures to suspend work, secure the jobsite and safely handle traffic through and across the project in the event of a hurricane evacuation.

In addition to lane closures, cease work 3 days before hurricane landfall on or near the roadway that adversely impacts the flow of traffic and reduces the capacity of the highway during an evacuation. Prohibit the Contractor's, sub-Contractors' or material suppliers' vehicles from entering or exiting the stream of traffic including material hauling and delivery, and mobilization or demobilization of equipment. When directed, this prohibition will include a reasonable time period for the evacuees to return to their point of origin.

### **Item 302 Aggregates for Surface Treatments**

The Contractor will designate a responsible person for receiving and resolving damage claims from the public. This person must be available to receive calls during normal business hours every day, Monday through Friday, during the course of this project. Before beginning work this person's name, mailing address, and a toll-free number will be provided to the Engineer to be made available to persons who contact the Department with claims

The aggregate for the surface treatment will be surface dry before application unless otherwise directed.

Aggregate stockpile locations will be approved before stockpiling.

When directed, flush aggregate stockpiled for surface treatment with water to remove excessive dust particles, in such sequence that will permit free water to drain from the stockpiled aggregate before surfacing operations. This work will be considered subsidiary to various bid items.

### **Item 316 Seal Coat**

Furnish medium pneumatic-tire rollers in accordance with Item 210, "Rolling."

All trucks hauling materials to be paid for by truck measurement will be "struck off" before delivery to the project.

Remove all vegetation from pavement edges, intersections, curbs and gutters and driveways before plaining or ACP operations. This work will not be paid for directly but will be subsidiary to the various bid items.

The open season for the application of asphalt is May 1st through September 15th unless otherwise directed in writing.

Seal intersections and driveways before sealing the main lanes. Seal all existing roadway surfaces, including extra widths, crossovers, roadside parks, picnic areas, mailbox turnouts, public road intersections, and public drives, within the limits of each project. Do not seal intersections or driveways surfaced with ACP or constructed of concrete.

Sweep all roadways with a powered rotary broom before placement of the surface treatment to remove all loose or excess material or debris. After rolling, sweep as soon as aggregate has sufficiently bonded to remove excess. Use a vacuum broom on all roadway sections with curb and gutter and all roadway sections within the city limits of any city.

### **Item 361 Repair of Concrete Pavement**

Volumetric Trucks meeting the requirements of Section 421.3.1.2, Section 421.4.5.2 and other applicable Specifications will be required for all locations.

Quantities listed on the plans are approximate. Actual locations and dimensions will be determined in the field. The Contractor will coordinate with the Beaumont Area Office to identify and mark the locations prior to beginning work.

Provide a minimum of two volumetric trucks with sufficient resources to refill/reload, and be ready to pour within 45 minutes.

Complete repairs so that longitudinal joints fall on edge of travel lane or center of travel lane. No joints will be allowed in the wheel paths.

Schedule work so that concrete placement follows full-depth saw-cutting by no more than 72 hours on typical roadways. **Due to concern of pavement dropping after it is sawed, repairs located within bridge approach slabs are to be replaced the day after sawing.**

All required saw-cutting will be subsidiary to this Item.

Method "B" joint sealing will be required. Seal around entire perimeter of repairs and transverse joints if present. This work will be subsidiary.

Contractor will not wash out concrete on project site. Any excess concrete placed during repairs will be removed from the project on that day and will not be allowed to remain overnight.



All removed portions of concrete will be removed from the project the same day as removed from the roadway. Breaking removed portions of concrete on top of the existing pavement will not be allowed.

**Maturity Testing**

Maturity testing, Tex-426-A, will be allowed for concrete pavement. Unless otherwise approved, use the maturity method in accordance with test method Tex-426-A to estimate concrete strength. The Maturity system will not be paid for directly but is considered subsidiary to this item.

Provide to the Engineer an approved maturity system for testing concrete compressive strength in accordance with Section 360.4.11.4.2., "Maturity Method." This system must include the logger/sensor, handheld reader, and software. Provide two (2) sensors per mix design and one (1) sensor to be placed in the last concrete pour per location site per day. Up to ten (10) additional sensors may be required and placed as directed. Furnish the concrete necessary to establish the maturity curve for testing. This work is to be performed before any concrete being placed and will not be paid for directly but will be considered subsidiary to this Item.

Provide a vibratory screed at least two feet longer than the width of the pavement to be used in finishing all repaired areas ten feet in length or longer.

Concrete to replace removed base material to be placed simultaneously with the concrete for the pavement repair.

Provide "HES" concrete. A set accelerating admixture may be necessary to meet the flexural strength requirements and will require written approval.

Design the Class HES concrete to meet the requirements of Class P and a minimum average compressive strength of 1800 psi in 4 hours.

High range water reducers will be used only to meet special requirements and will require written approval. A satisfactory work plan for control must be submitted by the Contractor for approval. An evaluation of the concrete containing the admixture will be performed.

Where repairs in jointed pavement require the removal of transverse joints, construct new joint at the same location.

All repairs located within jointed concrete pavement will be considered JRCP and repaired as per the details on the plans for JRCP.

Concrete removal will not be permitted when impending weather conditions may result in rainfall which will delay the concrete placement or cure.

Saw cutting of existing concrete pavement across existing cracks will not be allowed.

**Item 438: Cleaning and Sealing Joints**

**Allow the Joint Seal to cure a minimum of 7 days before applying the One Course Surface Treatment.**

Provide Class 3 "Hot Poured Rubber", in accordance with DMS-6310.

Existing joint seal material to be removed by sawing unless otherwise approved.

Clean and seal entire length of all joints in concrete pavement.

After the removal of the existing joint sealant material is complete, the vertical joint faces will be cleaned by sandblasting.

Collect and dispose of all the removed material daily.

After sandblasting the joints, water blast each joint to ensure removal of all fines and dust. Follow water blasting with air blasting to ensure a dry joint prior to placing the hot poured rubber. Ensure a surface dry joint prior to placing the hot poured rubber.

**Item 439 Bridge Deck Overlays**

Care should be taken to prevent filling in bridge joints. This work will be subsidiary to Item 439.

Submit a plan to the Engineer for termination (or taper) of the overlay at bridge ends for approval.

**Item 502 Barricades, Signs, and Traffic Handling**

Construct all work zone signs, sign supports, and barricades from material other than wood unless approved otherwise. Metal posts, if used, are to be galvanized.

Aluminum signs, if used, will meet the following minimum thickness requirements:

<u>Square Feet</u>	<u>Minimum Thickness</u>
Less than 7.5	0.080 inches
7.5 to 15	0.100 inches
Greater than 15	0.125 inches

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be used for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

Restrict work to one side of the roadway at a time.

Provide all flaggers and pilot vehicle drivers with two-way radio communication capability.  
Provide flaggers at each side road intersection.

#### **Item 506 Temporary Erosion, Sedimentation, and Environmental Controls**

It is not anticipated that any erosion, sedimentation, or environmental control devices will be needed on this project. The Contractor Force Account "SW3P Contingency" that has been established for this project is intended to be used in the event that such controls become necessary. The SW3P for this project will consist of the use of any temporary erosion control measures deemed necessary and as specified under this Item. This work will be paid for in accordance with Article 4.4., "Changes in the Work.

#### **Item 585 Ride Quality for Pavement Surfaces**

##### For US 69 Main Lanes:

Use Surface Test Type B pay adjustment schedule 3 to evaluate ride quality of travel lanes in accordance with this item.

##### For US 69 Frontage Roads:

Use Surface Test Type A to evaluate ride quality of the travel lanes and ramps.

#### **Item 506 Temporary Erosion, Sedimentation, and Environmental Controls**

It is not anticipated that any erosion, sedimentation, or environmental control devices will be needed on this project. The Contractor Force Account "SW3P Contingency" that has been established for this project is intended to be used in the event that such controls become necessary. The SW3P for this project will consist of the use of any temporary erosion control measures deemed necessary and as specified under this Item. This work will be paid for in accordance with Article 4.4., "Changes in the Work.

#### **Item 666 Retro reflectorized Pavement Markings**

Furnish Type II drop-on glass beads.

#### **Item 672 Raised Pavement Markers**

Remove all existing traffic buttons before the application of the seal coat. Consider this work to be subsidiary to the various bid items of the contract. Location and details of the existing buttons are available at the Area Engineer 's office.

#### **Item 677 Eliminating Existing Pavement Markings and Markers**

Remove all contaminates and loose material. Consider this work to be subsidiary to the various bid items of the contract.

Remove existing raised pavement markers before the addition of the asphaltic pavement or seal coat. Dispose of the removed markers from the project at the end of each workday. Consider this work to be subsidiary to the various bid items of the contract.

Remove existing stripping without gouging or creating undue groves in existing PFC hot mix overlays. Lightly flail the existing markings to remove the topcoat or raised portion of the existing stripe while leaving the existing striping contained within the pores of the PFC in place. Apply non-reflective, black, non-removable work zone pavement markings, in accordance with Item 662 to cover and fill existing residual striping contained in the pores. Payment for the Item 662 topcoat will be subsidiary to Item 677.

#### **Item 720 Repair of Spalling in Concrete Pavement**

Locations and dimensions for the repairs listed on the plans are approximate. Actual locations and dimension will be determined in the field. 500 gallons of repair material has been included in the estimated quantity to be used as directed in areas encountered that exhibit small spalls or corner breaks.

Provide rapid-set concrete meeting DMS-4655, for patches with a volume of 0.30 cubic feet or more AND 3 inches minimum in the least dimension. Otherwise, provide polymeric patching material meeting DMS-6170, Type II, semi-rigid material.

#### **Item 3004 Continuous Diamond Grinding of Concrete Pavement**

All material generated, including concrete slurry, as a result of roadway diamond grinding will be collected and kept from entering waterways, culverts, roadway inlets, and ditches. Diamond grinding will be conducted in such a manner so that all materials will be collected before the end of each day and especially before any rainfall event. Material from grinding will not be allowed to be tracked by traffic to other areas. Adequate sweeping, vacuuming and hauling equipment will be maintained on the project to conduct material collection and recovery on a continuous basis. Curb inlets will be blocked and protected during grinding and sweeping operations, but fully opened before a rainfall event.

The Contractor will, before beginning diamond grinding operations, provide a plan outlining the method of collection and disposal of this material for approval. The plan will include the name and location of the facility, authorized to handle such material, receiving the solid waste. All work, equipment, materials and fees necessary to collect and dispose of this material will be considered subsidiary to this item and not paid for directly.

Material produced by the grinding operation may be recycled in accordance with all applicable rules and regulations as required. The Contractor will submit

a plan for recycling to the Engineer for approval before any grinding being performed.

Consider the Diamond Grinding accepted when the average IRI of each lane is 170 or less. Multiple passes may be required to achieve this outcome and will not result in additional payment.

#### Item 3079 Permeable Friction Course

Allow the One Course Surface Treatment to cure a minimum of 14 days before placement of the Permeable Friction Course.

Do not place the mixture when the air temperature is 70 degrees Fahrenheit and falling.

Provide a separate Laboratory space, building or testing area, large enough to accommodate TxDOT equipment and testing on site at the Hot Mix Plant near or within the area of Contractor's testing equipment. The contractor will provide the SGC" Superpave Gytratory Compactor" and

TGC "Texas Gytratory Compactor". All other equipment must be provided by TxDOT. TxDOT will be responsible for maintaining state provided equipment. The Contractor will provide TxDOT with the Calibration paperwork on the shared equipment that they provide.

Provide an all-weather parking area for the sole use of at least 2 State-owned vehicles. Situate the parking area near the Laboratory area at an acceptable location. Maintain the parking area until the project is completed and restore the area to a condition acceptable to the Engineer upon project completion.

Laboratory area shall have a roof, floor, doors, and screened windows. Ensure the floor is strong enough to support testing equipment and has an impervious floor covering. Ensure that the Laboratory area is tied down, weatherproof, piped for water and fuel, and electrically wired by personnel meeting the requirements of Article 7.18., "Electrical Requirements."

Provide secured and controlled access to the Laboratory area through security measures such as bars, locks, alarms, or security fencing for the Laboratory area.

Furnish and install adequate equipment, outlets, lighting, air-conditioning, heating, and ventilation for the Laboratory area. Heating and Air Conditioning shall maintain the Laboratory working area temperature within a range of (68°F through 72°F).

Provide partitioned restroom furnished with restroom supplies, a lavatory, and a flush toilet connected to a sewer or septic tank within the Laboratory area.

Laboratory area will have the use of an internet service provider (ISP) that can provide more than one computer access to ISP account at one time. ISP provider must be able to supply a minimum 100 gigabyte download speed per account.

Required appurtenances within the Laboratory Area:

1. A 10lb ABC fire extinguisher with up-to-date inspection tag and a working smoke detector.
  2. Additional workbench and tables at least 3 ft. wide, 6 ft. long, and 3 ft. high.
  3. Minimum two chairs and one desk, filing cabinets, solar screen blinds or shades.
  4. An operational telephone system.
  5. Water fountain or bottled water fountain able to provide cold water and have cup dispenser and cups.
  6. Water (for testing purposes) from an approved source
  7. Adequately power ventilate the room for the ignition oven. Provide a NEMA 6-50R (208/240 volt, 50 amp) outlet within 2.25 ft. of the ignition oven location and an independent exhaust outlet to the outside located a maximum of 8 ft. from the oven. Provide a level, sturdy and
  8. fireproof surface for the ignition oven with a minimum of 6 in. clearance between the furnace and other vertical surfaces. Vent the ignition oven to the outside.
  9. A minimum of 20 ft. of total work counter length at least 3 ft. wide and 3 ft. above the floor and strong enough to support required testing equipment
  10. A laboratory sink measuring 24 × 30 in. and 12 in. deep
  11. Door openings for the Laboratory area must be 48-inches minimum width. If steps are required to gain access to the facility's then a landing dock will be provided with minimum dimensions of 60 inches wide by 60 inches deep. The strong floor and landing of the facility shall support the weight of all equipment and personnel providing a stable, essentially zero deflection during testing operations acceptable to the Engineer.
- Provide multifunction color printer/fax/scanner/copier capable of reproducing 11 X 17

For the Laboratory area the work performed, materials furnished, utilities, and utility services (including phone and internet), appurtenances including office equipment testing equipment, labor, tools, and incidentals will not be paid measured or paid for directly but will be subsidiary to pertinent items.

The plant will be the sampling location for all aggregates.

Use aggregate that meets the SAC requirement of class A for all surface mixes. RAP aggregate must meet the requirements of Table 1.

Aggregates used on shoulders and ramps are required to meet SAC requirements. Provide mix designs. Mix designs must be verified and approved.

Remove all vegetation from pavement edges, intersections, curbs and gutters and driveways before planning or ACP operations. This work will not be paid for directly but will be subsidiary to the various bid items.

Operate the spreading and finishing machine at a uniform forward speed consistent with the plant production rate, hauling capability, and roller train capacity to result in a continuous operation. The speed will be slow enough, so that stopping between trucks is not ordinarily required. If the Engineer determines sporadic delivery of material is adversely affecting the HMA placement, the Engineer may require paving operations to cease until acceptable methods are employed to minimize starting and stopping of the paver.

A material transfer device (MTD) will be required for all surface courses of HMA on this project. An MTD is defined as a self-propelled, wheel-mounted vehicle capable of receiving HMA from the haul trucks separate from the paver. The MTD will have a minimum storage capacity of approximately 25 tons and will be equipped with a pivoting discharge conveyor and a means of completely remixing the HMA before placement. The Engineer may approve an alternative device on a trial basis for the surface course. This device will be capable of receiving HMA separate from the paver and must have remixing capabilities. For all other courses of HMA, other than the surface, an alternative device may be used as long as it is capable of receiving HMA separate from the paver.

Evaluate the density of areas with severe thermal segregation using a nuclear density gauge in accordance with Tex-207-F, Part III. Unless otherwise directed, remove and replace the material in any areas that have both severe thermal segregation and a density gauge reading of less than 90%.

Overlay across the ends of any curb ramps must not create a barrier to their use. Changes in level up to ¼" may be vertical; between ¼" and ½" must be beveled with a slope no greater than 1:2; greater than ½" will require a "ramp".

Station limits may be adjusted as directed to meet varying field conditions

#### Item 3081 Thin Overlay Mixture

Allow the One Course Surface Treatment to Cure a minimum of 14 days prior to placement of the Thin Overlay Mixture (TOM).

Use trackless tack on this project, Applied at a rate of 0.06 gallons per square yard.

Provide One Inch compacted depth, Type C mix.

Provide a separate Laboratory space, building or testing area, large enough to accommodate TxDOT equipment and testing on site at the Hot Mix Plant near or within the area of Contractor's testing equipment. The contractor will provide the SGC" Superpave Gyratory Compactor" and TGC "Texas Gyratory Compactor". All other equipment must be provided by TxDOT. TxDOT will be responsible for maintaining state provided equipment. The Contractor will provide TxDOT with the Calibration paperwork on the shared equipment that they provide.

Provide an all-weather parking area for the sole use of at least 2 State-owned vehicles. Situate the parking area near the Laboratory area at an acceptable location. Maintain the parking area until the project is completed and restore the area to a condition acceptable to the Engineer upon project completion.

Laboratory area shall have a roof, floor, doors, and screened windows. Ensure the floor is strong enough to support testing equipment and has an impervious floor covering. Ensure that the Laboratory area is tied down, weatherproof, piped for water and fuel, and electrically wired by personnel meeting the requirements of Article 7.18., "Electrical Requirements."

Provide secured and controlled access to the Laboratory area through security measures such as bars, locks, alarms, or security fencing for the Laboratory area.

Furnish and install adequate equipment, outlets, lighting, air-conditioning, heating, and ventilation for the Laboratory area. Heating and Air Conditioning shall maintain the Laboratory working area temperature within a range of (68°F through 72°F).

Provide partitioned restroom furnished with restroom supplies, a lavatory, and a flush toilet connected to a sewer or septic tank within the Laboratory area.

Laboratory area will have the use of an internet service provider (ISP) that can provide more than one computer access to ISP account at one time. ISP provider must be able to supply a minimum 100 gigabyte download speed per account.

Required appurtenances within the Laboratory Area:

12. A 10lb ABC fire extinguisher with up-to-date inspection tag and a working smoke detector.

13. Additional workbench and tables at least 3 ft. wide, 6 ft. long, and 3 ft. high.
  14. Minimum two chairs and one desk, filing cabinets, solar screen blinds or shades.
  15. An operational telephone system.
  16. Water fountain or bottled water fountain able to provide cold water and have cup dispenser and cups.
  17. Water (for testing purposes) from an approved source
  18. Adequately power ventilate the room for the ignition oven. Provide a NEMA 6-50R (208/240-volt, 50 amp) outlet within 2.25 ft. of the ignition oven location and an independent exhaust outlet to the outside located a maximum of 8 ft. from the oven. Provide a level, sturdy and fireproof surface for the ignition oven with a minimum of 6 in. clearance between the furnace and other vertical surfaces. Vent the ignition oven to the outside.
  19. A minimum of 20 ft. of total work counter length at least 3 ft. wide and 3 ft. above the floor and strong enough to support required testing equipment
  20. A laboratory sink measuring 24 × 30 in. and 12 in. deep
  21. Door openings for the Laboratory area must be 48-inches minimum width. If steps are required to gain access to the facilities, then a landing dock will be provided with minimum dimensions of 60 inches wide by 60 inches deep. The strong floor and landing of the facility shall support the weight of all equipment and personnel providing a stable, essentially zero deflection during testing operations acceptable to the Engineer.
- Provide multifunction color printer/fax/scanner/copier capable of reproducing 11 X 17

For the Laboratory area the work performed, materials furnished, utilities, and utility services (including phone and internet), appurtenances including office equipment testing equipment, labor, tools, and incidentals will not be paid measured or paid for directly but will be subsidiary to pertinent item.

The plant will be the sampling location for all aggregates.

Use aggregate meeting a Surface Aggregate Classification (SAC) requirement of "A" for surface course mixtures. The SAC requirement for the coarse aggregate is SAC "A" (no blending allowed).

Provide mix designs. Mix designs must be verified and approved.

In addition to mix design, furnish the engineer with 6 samples molded at optimum asphalt content. Three samples molded at 7% air voids content, and 3 samples molded at 9% air voids (or whatever is required to get a trimmed air void content of 7% +/- 1%). Mold samples 6

inches diameter by 2.4 inches thick (Hamburg sized samples). Furnished material is to be sent to Texas Transportation Institute (TTI) for Hamburg Wheel Test and Overlay test. This work is subsidiary to the various bid Items.

Antistripping Agent – Lime or an approved anti-stripping agent must be used when crushed gravel is used to meet a SAC "A" requirement.

Operate the spreading and finishing machine at a uniform forward speed consistent with the plant production rate, hauling capability, and roller train capacity to result in a continuous operation. The speed will be slow enough, so that stopping between trucks is not ordinarily required. If the Engineer determines sporadic delivery of material is adversely affecting the HMA placement, the Engineer may require paving operations to cease until acceptable methods are employed to minimize starting and stopping of the paver.

A material transfer device (MTD) will be required for all surface courses of HMA on this project. An MTD is defined as a self-propelled, wheel-mounted vehicle capable of receiving HMA from the haul trucks separate from the paver. The MTD will have a minimum storage capacity of approximately 25 tons and will be equipped with a pivoting discharge conveyor and a means of completely remixing the HMA before placement. The Engineer may approve an alternative device on a trial basis for the surface course. This device will be capable of receiving HMA separate from the paver and must have remixing capabilities. For all other courses of HMA, other than the surface, an alternative device may be used as long as it is capable of receiving HMA separate from the paver.

Evaluate the density of areas with severe thermal segregation using a nuclear density gauge in accordance with Tex-207-F, Part III. Unless otherwise directed, remove and replace the material in any areas that have both severe thermal segregation and a density gauge reading of less than 90%.

Perform rolling with tandem rollers enough to cover the entire mat in one pass, unless approved otherwise.

On the first day of production correlate the density gauge in accordance with Tex-207-F, Part III using a minimum of 4 roadway cores of 4 inches in diameter. Take the roadway cores in a transverse direction at one location approximately 2 feet apart. Determine a new correlation factor when directed.

The default quantity for Lot 1 is 500 tons; however, when requested by the Contractor, the Engineer may increase the quantity for Lot 1 to no more than 1000 tons.

Suspend production and take corrective action if any aggregate is retained on the maximum sieve size shown in Table 6

**Control:0065-06-070**

Miscellaneous areas, including driveways, mailbox turnouts, crossovers, gores, spot level-up areas, areas that involve significant handwork or discontinuous paving, are not subject to in-place air void determination. In all other areas, the Engineer may obtain density gauge readings using a nuclear density gauge in accordance with Tex-207-F, Part III or a non-nuclear density gauge. The Engineer will allow paving to resume when the proposed corrective action is likely to yield between 3.8% and 8.50% in-place air voids.

Overlay across the ends of any curb ramps must not create a barrier to their use. Changes in level up to 1/4" may be vertical; between 1/4" and 1/2" must be beveled with a slope no greater than 1:2; greater than 1/2" will require a "ramp".

**Item 6001 Portable Changeable Message Sign**

Portable changeable message signs (PCMS) will be required at all nighttime work locations while work is taking place.

The Message on the sign will be specified on BC (6)-21, Phase I: "NIGHT LANE CLOSURES" and Phase II: "TONIGHT 08 PM – 06 AM" Provide screen type "Continuous Line Matrix." More than one PCMS may be required on this project. Payment for PCMS's will be per day used and for each sign used.

When possible, PCMS units should be located in advance of the last available alternate route prior to the lane closure. They may also be relocated to improve advance warning in case of unanticipated queuing or congestion.

**Item 6185**

Shadow vehicles with TMA and high intensity rotating, flashing, oscillating or strobe lights are required. Use one TMA preceding every stationary work zone and two TMA's for mobile operations.

In addition to the shadow vehicles with truck mounted attenuator (TMA) that are specified as being required for this project, provide one additional shadow vehicle with TMA for TCP as detailed in the general notes of the standards elsewhere in the plans.

Therefore, two total shadow vehicles with TMA will be required for this type of work. The contractor will be responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMA's needed for the project.



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0065-06-070

DISTRICT Beaumont  
HIGHWAY US 69

COUNTY Hardin, Jefferson

CONTROL SECTION JOB				0065-06-070		0065-07-070		0200-11-099		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00187852		A00187854		A00018478			
COUNTY				Hardin		Jefferson		Jefferson			
HIGHWAY				US 69		US 69		US 69			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL		
	104-6021	REMOVING CONC (CURB)	LF					3,461.000		3,461.000	
	316-6017	ASPH (AC-20-5TR)	GAL	43,772.000		7,869.000		45,277.000		96,918.000	
	316-6404	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	CY	869.000		156.000		898.000		1,923.000	
	354-6015	PLAN & TEXT CONC PAV(0" TO 1")	SY					3,409.000		3,409.000	
	354-6043	PLANE ASPH CONC PAV (1")	SY					22,558.000		22,558.000	
	361-6077	FULL-DEPTH REPAIR CPCD (VAR DEPTH)	CY					160.000		160.000	
	361-6078	FULL-DEPTH REPAIR CPJR (VAR DEPTH)	CY					160.000		160.000	
	438-6001	CLEANING AND SEALING EXISTING JOINTS	LF	145,265.000		12,312.000		126,340.000		283,917.000	
	439-6013	MULTI-LAYER POLYMER OVERLAY	SY	35,909.000		3,795.000				39,704.000	
	500-6001	MOBILIZATION	LS	1.000						1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	9.000						9.000	
	529-6001	CONC CURB (TY I)	LF					110.000		110.000	
	529-6002	CONC CURB (TY II)	LF					3,351.000		3,351.000	
	662-2016	WK ZN PAV MRK NON-REMOV (W) 24" (SLD)	LF					443.000		443.000	
	662-6005	WK ZN PAV MRK NON-REMOV (W)6"(BRK)	LF	8,950.000		1,530.000		11,510.000		21,990.000	
	662-6008	WK ZN PAV MRK NON-REMOV (W)6"(SLD)	LF	30,448.000		6,086.000		8,645.000		45,179.000	
	662-6012	WK ZN PAV MRK NON-REMOV (W)8"(SLD)	LF	10,545.000		1,290.000		12,678.000		24,513.000	
	662-6013	WK ZN PAV MRK NON-REMOV (W)12"(LNDP)	LF	980.000						980.000	
	662-6037	WK ZN PAV MRK NON-REMOV (Y)6"(SLD)	LF	30,448.000		6,086.000		1,815.000		38,349.000	
	662-6041	WK ZN PAV MRK NON-REMOV (Y)24"(SLD)	LF					200.000		200.000	
	662-6109	WK ZN PAV MRK SHT TERM (TAB)TY W	EA	5,362.000		3,652.000		6,906.000		15,920.000	
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	2,107.000						2,107.000	
	662-6122	WK ZN PAV MRK NON-REMOV (W)12"(DOT)	LF	744.000						744.000	
	666-6029	REFL PAV MRK TY I (W)8"(DOT)(090MIL)	LF					474.000		474.000	
	666-6035	REFL PAV MRK TY I (W)8"(SLD)(090MIL)	LF	10,545.000		1,290.000		12,678.000		24,513.000	
	666-6038	REFL PAV MRK TY I (W)12"(LNDP)(090MIL)	LF	980.000						980.000	
	666-6305	RE PM W/RET REQ TY I (W)6"(BRK)(090MIL)	LF	8,950.000		1,530.000		11,510.000		21,990.000	
	666-6308	RE PM W/RET REQ TY I (W)6"(SLD)(090MIL)	LF	30,448.000		6,086.000		8,645.000		45,179.000	
	666-6320	RE PM W/RET REQ TY I (Y)6"(SLD)(090MIL)	LF	30,448.000		6,086.000		1,815.000		38,349.000	
	666-6349	REFL PAV MRK TY I (W)12"(DOT)(090MIL)	LF	744.000						744.000	
	668-6074	PREFAB PAV MRK TY C (W) (12") (SLD)	LF					188.000		188.000	
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF					443.000		443.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA	6.000				31.000		37.000	
	668-6078	PREFAB PAV MRK TY C (W) (DBL ARROW)	EA					23.000		23.000	
	668-6080	PREFAB PAV MRK TY C (W) (UTURN ARROW)	EA					13.000		13.000	
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA	6.000				13.000		19.000	
	668-6092	PREFAB PAV MRK TY C (W) (36")(YLD TRI)	EA					158.000		158.000	



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0065-06-070

DISTRICT Beaumont  
HIGHWAY US 69

COUNTY Hardin, Jefferson

CONTROL SECTION JOB				0065-06-070		0065-07-070		0200-11-099		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00187852		A00187854		A00018478			
COUNTY				Hardin		Jefferson		Jefferson			
HIGHWAY				US 69		US 69		US 69			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL		
	668-6108	PREFAB PAV MRK TY C (Y) (24") (SLD)	LF					200.000		200.000	
	672-6007	REFL PAV MRKR TY I-C	EA					140.000		140.000	
	672-6010	REFL PAV MRKR TY II-C-R	EA	937.000		937.000		574.000		2,448.000	
	713-6005	CRACK CLEANING AND SEALING (JCP)	LF	2,000.000				19,140.000		21,140.000	
	720-6001	SPALLING REPAIR (HYDRAULIC CEMENT)	CF	180.000		3.000		2,340.000		2,523.000	
	3004-6001	CONTINUOUS DIAMOND GRINDING CONC PVMT	SY					122,930.000		122,930.000	
	3039-6001	DOWEL BAR RETROFIT	EA					1,368.000		1,368.000	
	3076-6066	TACK COAT	GAL	344.000		100.000				444.000	
	3076-6078	D-GR HMA TY-D SAC-A PG76-22 (EXEMPT)	TON	237.000		69.000				306.000	
	3079-6011	PFC-C PG76-22 SAC-A	TON	9,558.000		1,666.000				11,224.000	
	3079-6023	TACK COAT	GAL	6,951.000		1,211.000				8,162.000	
	3081-6007	TOM-C PG76-22 SAC-A	TON					6,917.000		6,917.000	
	3081-6015	TACK COAT	GAL					7,546.000		7,546.000	
	3086-6001	SOIL DENS.AND RAISING CONC.SLABS(HDPF)	LB					8,764.000		8,764.000	
	6001-6002	PORTABLE CHANGEABLE MESSAGE SIGN	EA	2.000		2.000		2.000		6.000	
	6185-6002	TMA (STATIONARY)	DAY	40.000		10.000		80.000		130.000	
	6185-6005	TMA (MOBILE OPERATION)	DAY	20.000		5.000		50.000		75.000	
	18	SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000						1.000	
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000						1.000	



CSJ 0065-06-070

BASIS OF ESTIMATE							
ITEM NO.	DESC. CODE	DESCRIPTION	RATE	# OF UNITS	UNIT	QTY	UNIT
316	6017	ASPH (AC-20-5TR)	0.36 GAL/SY	121590	SY	43772	GAL
316	6404	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	140 SY/CY	121590	SY	869	CY
3076	6078	D-GR HMA TY-D SAC-A PG76-22 (EXEMPT)	82.5 LBS/SY/IN	5735	SY	237	TON
3076	6066	TACK COAT	0.06 GAL/SY	5735	SY	344	GAL
3079	6011	PFC-C PG76-22 SAC-A	165 LBS/SY/IN	115855	SY	9558	TON
3079	6023	TACK COAT	0.06 GAL/SY	115855	SY	6951	GAL

ROADWAY ITEM SUMMARY

*316	*316	*3076	*3076	*3079	*3079	438	439	713	720
6017	6404	6078	6066	6011	6023	6001	6013	6005	6001
ASPH (AC-20-5TR)	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	D-GR HMA TY-D SAC-A PG76-22 (EXEMPT)	TACK COAT	PFC-C PG76-22 SAC-A	TACK COAT	CLEANING AND SEALING EXISTING JOINTS	MULTI-LAYER POLYMER OVERLAY	CRACK CLEANING AND SEALING (JCP)	SPALLING REPAIR (HYDRAULIC CEMENT)
SY	SY	SY	SY	SY	SY	LF	SY	LF	GAL
121590	121590	5735	5735	115855	115855	145265	35909	2000	180

\*FOR CONTRACTORS INFORMATION ONLY

WORK ZONE PAVEMENT MARKING SUMMARY

662	662	662	662	662	662	662	6185	6185	6001
6005	6008	6012	6013	6037	6109	6122	6002	6005	6002
WK ZN PAV MRK NON-REMOV (W)6"(BRK)	WK ZN PAV MRK NON-REMOV (W)6"(SLD)	WK ZN PAV MRK NON-REMOV (W)8"(SLD)	WK ZN PAV MRK NON-REMOV (W)12"(LNDP)	WK ZN PAV MRK NON-REMOV (Y)6"(SLD)	WK ZN PAV MRK SHT TERM (TAB)TY W	WK ZN PAV MRK NON-REMOV (W)12"(DOT)	TMA (STATIONARY)	TMA (MOBILE OPERATION)	PORTABLE CHANGEABLE MESSAGE SIGN
LF	LF	LF	LF	LF	EA	LF	DAY	DAY	EA
8950	30448	10545	980	30448	5362	744	40	20	2

PAVEMENT MARKING SUMMARY

666	666	666	666	666	666	668	668	672
6035	6038	6305	6308	6320	6349	6077	6085	6010
REFL PAV MRK TY I (W) 8"(SLD)(090MIL)	REFL PAV MRK TY I (W) 12"(LNDP)(090MIL)	RE PM W/RET REQ TY I (W) 6"(BRK)(090MIL)	RE PM W/RET REQ TY I (W) 6"(SLD)(090MIL)	RE PM W/RET REQ TY I (Y) 6"(SLD)(090MIL)	REFL PAV MRK TY I (W) 12" (DOT)(090MIL)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (WORD)	REFL PAV MRKR TY II-C-R
LF	LF	LF	LF	LF	LF	EA	EA	EA
10545	980	8950	30448	30448	744	6	6	937

QUANTITY SUMMARY



FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.
				17
STATE	DISTRICT	COUNTY		
TEXAS	BMT	HARDIN		
CONTROL	SECTION	JOB	HIGHWAY NO.	
0065	06	070, ETC	US69	

CSJ0065-07-070

BASIS OF ESTIMATE							
ITEM NO.	DESC. CODE	DESCRIPTION	RATE	# OF UNITS	UNIT	QTY	UNIT
316	6017	ASPH (AC-20-5TR)	0.36 GAL/SY	21858	SY	7869	GAL
316	6404	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	140 SY/CY	21858	SY	156	CY
3076	6078	D-GR HMA TY-D SAC-A PG76-22 (EXEMPT)	82.5 LBS/SY/IN	1667	SY	69	TON
3076	6066	TACK COAT	0.06 GAL/SY	1667	SY	100	GAL
3079	6011	PFC-C PG76-22 SAC-A	165 LBS/SY/IN	20191	SY	1666	TON
3079	6023	TACK COAT	0.06 GAL/SY	20191	SY	1211	GAL

ROADWAY ITEM SUMMARY

*316	*316	*3076	*3076	*3079	*3079	438	439	720
6017	6404	6078	6066	6011	6023	6001	6013	6001
ASPH (AC-20-5TR)	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	D-GR HMA TY-D SAC-A PG76-22 (EXEMPT)	TACK COAT	PFC-C PG76-22 SAC-A	TACK COAT	CLEANING AND SEALING EXISTING JOINTS	MULTI-LAYER POLYMER OVERLAY	SPALLING REPAIR (HYDRAULIC CEMENT)
SY	SY	SY	SY	SY	SY	LF	SY	GAL
21858	21858	1667	1667	20191	20191	12312	3795	3

\*FOR CONTRACTORS INFORMATION ONLY

WORK ZONE PAVEMENT MARKING SUMMARY

662	662	662	662	662	6185	6185	6001
6005	6008	6012	6037	6109	6002	6005	6002
WK ZN PAV MRK NON-REMOV (W)6"(BRK)	WK ZN PAV MRK NON-REMOV (W)6"(SLD)	WK ZN PAV MRK NON-REMOV (W)8"(SLD)	WK ZN PAV MRK NON-REMOV (Y)6"(SLD)	WK ZN PAV MRK SHT TERM (TAB)TY W	TMA (STATIONARY)	TMA (MOBILE OPERATION)	PORTABLE CHANGEABLE MESSAGE SIGN
LF	LF	LF	LF	EA	DAY	DAY	EA
1530	6086	1290	6086	3652	10	5	2

PAVEMENT MARKING SUMMARY

666	666	666	666	672
6035	6305	6308	6320	6010
REFL PAV MRK TY I (W) 8"(SLD)(090MIL)	RE PM W/RET REQ TY I (W) 6"(BRK)(090MIL)	RE PM W/RET REQ TY I (W) 6"(SLD)(090MIL)	RE PM W/RET REQ TY I (Y) 6"(SLD)(090MIL)	REFL PAV MRKR TY II-C-R
LF	LF	LF	LF	EA
1290	1530	6086	6086	937

QUANTITY SUMMARY

© 2022 Texas Department of Transportation

FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.
				18
STATE	DISTRICT	COUNTY		
TEXAS	BMT	HARDIN		
CONTROL	SECTION	JOB	HIGHWAY NO.	
0065	06	070, ETC	US69	

BASIS OF ESTIMATE							
ITEM NO.	DESC. CODE	DESCRIPTION	RATE	# OF UNITS	UNIT	QTY	UNIT
316	6017	ASPH (AC-20-5TR)	0.36 GAL/SY	125770	SY	45277	GAL
316	6404	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	140 SY/CY	125770	SY	898	CY
3081	6007	TOM C PG76-22 SAC-A	110 LBS/SY/IN	125770	SY	6917	TON
3081	6015	TACK COAT	0.06 GAL/SY	125770	SY	7546	GAL
3086	6001	SOIL DENS. AND TAISING CONC SLABS (HDPF)	8.5 LBS/SY	1031	SY	8764	LBS

ROADWAY ITEM SUMMARY

*316	*316	354	354	361	361	438	713	720	3004	3039	*3081	*3081	*3086
6017	6404	6015	6043	6077	6078	6001	6005	6001	6001	6001	6007	6007	6001
ASPH (AC-20-5TR)	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	PLAN & TEXT CONC PAV (0" TO 1")	PLANE ASPH CONC PAV(1")	FULL-DEPTH REPAIR CPCD (VAR DEPTH)	FULL-DEPTH REPAIR CPJR (VAR DEPTH)	CLEANING AND SEALING EXISTING JOINTS	CRACK CLEANING AND SEALING (JCP)	SPALLING REPAIR (HYDRAULIC CEMENT)	CONTINUOUS DIAMOND GRINDING CONC PVMT	DOWEL BAR RETROFIT	TOM C PG76-22 SAC-A	TOM C PG76-22 SAC-A	SOIL DENS. AND RAISING CONC SLABS (HDPF)
SY	SY	SY	SY	CY	CY	LF	LF	CF	SY	EA	SY	SY	SY
125770	125770	3409	22558	160	160	126340	19140	2340	122930	1368	125770	125770	1031

\*FOR CONTRACTORS INFORMATION ONLY

MISCELLANEOUS ITEM SUMMARY

WORK ZONE PAVEMENT MARKING SUMMARY

104	529	529	662	662	662	662	662	662	662	6185	6185	6001
6021	6001	6002	6005	6008	6012	6016	6037	6041	6109	6002	6005	6002
REMOVING CONC (CURB)	CONC CURB (TY I)	CONC CURB (TY II)	WK ZN PAV MRK NON-REMOV (W) 6"(BRK)	WK ZN PAV MRK NON-REMOV (W) 6"(SLD)	WK ZN PAV MRK NON-REMOV (W) 8"(SLD)	WK ZN PAV MRK NON-REMOV (W) 24"(SLD)	WK ZN PAV MRK NON-REMOV (Y) 6"(SLD)	WK ZN PAV MRK NON-REMOV (Y) 24"(SLD)	WK ZN PAV MRK SHT TERM (TAB) TY W	TMA (STATIONARY)	TMA (MOBILE OPERATION)	PORTABLE CHANGEABLE MESSAGE SIGN
LF	LF	LF	LF	LF	LF	LF	LF	LF	EA	DAY	DAY	EA
3461	110	3351	11510	8645	12678	443	1815	200	6906	80	50	2

PAVEMENT MARKING SUMMARY

666	666	666	666	666	668	668	668	668	668	668	668	668	672	672
6029	6035	6305	6308	6320	6074	6076	6077	6078	6080	6085	6092	6108	6007	6010
REFL PAV MRK TY I (W) 8"(DOT)(090MIL)	REFL PAV MRK TY I (W) 8"(SLD)(090MIL)	RE PM W/RET REQ TY I (W) 6"(BRK)(090MIL)	RE PM W/RET REQ TY I (W) 6"(SLD)(090MIL)	RE PM W/RET REQ TY I (Y) 6"(SLD)	PREFAB PAV MRK TY C (W) (12")(SLD)	PREFAB PAV MRK TY C (W) (24")(SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	PREFAB PAV MRK TY C (W) (UTURN ARROW)	PREFAB PAV MRK TY C (W)	PREFAB PAV MRK TY C (W) (36")(YLD TRI)	PREFAB PAC MRK TY C (Y)	REFL PAV MRKR TY I-C	REFL PAV MRKR TY II-C-R
LF	LF	LF	LF	LF	LF	LF	EA	EA	EA	EA	EA	LF	EA	EA
474	12678	11510	8645	1815	188	443	31	23	13	13	158	200	140	574

QUANTITY SUMMARY



FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.
				19
STATE	DISTRICT	COUNTY		
TEXAS	BMT	HARDIN		
CONTROL	SECTION	JOB	HIGHWAY NO.	
0065	06	070, ETC	US69	

DATE: 1/3/2023 3:13:28 PM  
FILE: T:\BMT\DESIGN\Projects\0065-06-070-US69\DCN\SequenceOfWork.dgn

Sequence of Work

US 69

CSJ: 0065-06-070, Etc.


1. Install Project Limit Signs on both Main Lanes and Frontage Roads as per the TXMUTCD and Traffic Control Standards. Maintain these signs for the duration of the project.

0065-06-070 & 0065-07-070 US 69 Main Lanes Projects

1. Unless approved by the Engineer Complete work on the North Bound Main Lanes before proceeding to the South Bound Main Lanes.
2. Install Barricades Signs and Traffic Handling per the TXMUTCD and Traffic Control Standards.
3. Install a One Course Surface Treatment (OCST) North Bound and Temporary Work Zone Tabs as shown elsewhere in the plans,
  - a. The installation of these tabs will be performed daily, as needed and/or directed by the Engineer. Multiple applications of Tabs may be required in the event they fail to last beyond the following 14-day cure period. Multiple Mobilizations will be required for this maintenance and will be subsidiary to this item.
  - b. Allow the OCST to cure for 14 days prior to Performing Overlay Operations.
4. Install PFC (includes 1.5" to 0" transitions at each Bridge as shown elsewhere in the plans) overlay operations North Bound Main Lanes.
  - a. Install Temporary Work Zone Tabs as shown elsewhere in the plans,
  - b. The installation of these tabs will be performed daily, as needed and as directed by the Engineer.
    - i. Work Zone Striping will be used in the event the Tabs deteriorate to point when, in the opinion of the Engineer, they are needed.
5. Install Polymer Overlay to North Bound Main Lane Bridge Decks as shown elsewhere in the plans.
6. Install Permanent Striping and Pavement Markings North Bound Main Lanes.
7. Repeat items 1 through 6 for the South Bound Main Lanes.

0200-11-099 US 69 Frontage Road Project

1. Install Barricades Signs and Traffic Handling per the TXMUTCD and Traffic Control Standards.
2. Perform Diamond Grinding, Planing, Curb Repair, Cleaning and Sealing Joints and Dowel Bar Retrofitting for the North Bound Frontage Road.
3. Install OCST on the North Bound Frontage Road and Temporary Work Zone Tabs as shown elsewhere in the plans.
  - a. The installation of these tabs will be performed daily, as needed, as directed by the Engineer. Multiple applications of Tabs may be required in the event they fail to last beyond the following 14-day cure period. Multiple Mobilizations will be required for this maintenance and will be subsidiary to this item.
  - b. Allow the OCST to cure for 14 days prior to Performing Overlay Operations.
4. Perform 1" TOM Overlay operations North Bound Frontage Road,
  - a. Install Temporary Work Zone Tabs as shown elsewhere in the plans,
  - b. The installation of these tabs will be performed daily, as needed and as directed by the Engineer.
    - i. Work Zone Striping will be used in the event the Tabs deteriorate to point when, in the opinion of the Engineer, they are needed.
5. Install Permanent Striping and Pavement Markings on North Bound Frontage Road.
6. Repeat Steps 1 through 5 for the South Bound Frontage Road.
7. Perform final cleanup.



*Jason D. Waldrep, P.E.*

01/03/2023

**US69**

**SEQUENCE  
OF WORK**

CONT	SECT	JOB	HIGHWAY
0065	06	070, ETC	US69
DIST	COUNTY		SHEET NO.
BMT	HARDIN		20

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:31 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard\bc-21.dgn

**BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:**

- The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
- The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
- The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
- Traffic control devices should be in place only while work is actually in progress or a definite need exists.
- The Engineer has the final decision on the location of all traffic control devices.
- Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

**WORKER SAFETY NOTES:**


- Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
- Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

**COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES**

- Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
- Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).


<b>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT</b> <a href="http://www.txdot.gov">http://www.txdot.gov</a>
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12

 Texas Department of Transportation		Traffic Safety Division Standard	
<b>BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS</b>			
<b>BC (1) -21</b>			
FILE:	bc-21.dgn	DN:	TxDOT
© TxDOT	November 2002	CK:	TxDOT
		DW:	TxDOT
		CR:	TxDOT
CONT	SECT	JOB	HIGHWAY
0065	06	070, ETC	US69
REVISIONS		DIST	COUNTY
4-03	7-13		
9-07	8-14		
5-10	5-21	BMT	HARDIN
			SHEET NO.
			21


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

**TYPICAL LOCATION OF CROSSROAD SIGNS**



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
  - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
  - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
  - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
  - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
  - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

**T-INTERSECTION**



**CSJ LIMITS AT T-INTERSECTION**

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

**TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING<sup>1,5,6</sup>**

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Δ Spacing "x" Feet (Apprx.)
CW20 <sup>4</sup>	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25			50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"	55	500 <sup>2</sup>
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" x 48"	48" x 48"	60	600 <sup>2</sup>
			65	700 <sup>2</sup>
			70	800 <sup>2</sup>
			75	900 <sup>2</sup>
			80	1000 <sup>2</sup>
			*	* <sup>3</sup>


\* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

**GENERAL NOTES**


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

**WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS**




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS**



**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS**



**NOTES**

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
  - CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
  - Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
  - Contractor will install a regulatory speed limit sign at the end of the work zone.

LEGEND	
—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



**BARRICADE AND CONSTRUCTION PROJECT LIMIT**

**BC (2) - 21**


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	BMT	HARDIN	22	

DATE: 1/3/2023 3:13:33 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard\bc-21.dgn

# TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



## GUIDANCE FOR USE:

### LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

### SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

## GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:
 

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
  - Law enforcement.
  - Flagger stationed next to sign.
  - Portable changeable message sign (PCMS).
  - Low-power (drone) radar transmitter.
  - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:35 PM  
FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard.dwg\bc-21.dgn

SHEET 3 OF 12



## BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT


BC (3) -21

FILE:	bc-21.dgn	DW:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0065	06	070, ETC		US69			
9-07	8-14								
7-13	5-21	DIST	COUNTY		SHEET NO.				
		BMT	HARDIN		23				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:37 PM  
 FILE: T:\BMTDESIGN\Projects\0065-06-070\_US69\VDG\Standard\ds.bc-21.dgn


**TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS**



\* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

\*\* When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

**ATTACHMENT FOR SIGN SUPPORTS**



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

**GENERAL NOTES FOR WORK ZONE SIGNS**

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

**DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)**

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
  - Long-term stationary - work that occupies a location more than 3 days.
  - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
  - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
  - Short, duration - work that occupies a location up to 1 hour.
  - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

**SIGN MOUNTING HEIGHT**

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

**SIZE OF SIGNS**

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

**SIGN SUBSTRATES**

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

**REFLECTIVE SHEETING**

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B<sub>FL</sub> or Type C<sub>FL</sub>, shall be used for rigid signs with orange backgrounds.

**SIGN LETTERS**

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

**REMOVING OR COVERING**

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

**SIGN SUPPORT WEIGHTS**


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

**FLAGS ON SIGNS**

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

**STOP/SLOW PADDLES**

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflective when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B <sub>FL</sub> OR C <sub>FL</sub> SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

**CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS**

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

Texas Department of Transportation  
 Traffic Safety Division Standard



**BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES**

**BC (4) - 21**

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	OW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	BMT	HARDIN	24	




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.





### SKID MOUNTED WOOD SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



### GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



### SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

**WEDGE ANCHORS**  
Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

**OTHER DESIGNS**  
MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

- GENERAL NOTES**
- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
  - No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
  - When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.
- \* See BC(4) for definition of "Work Duration."
  - \*\* Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
  - See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



## BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	OW:	TxDOT	CR:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS	0065	06	070, ETC	US69					
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	BMT	HARDIN	25					

DATE: 1/3/2023 3:13:38 PM  
FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\VDGN\Standards\bc-21.dgn

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

# RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

## PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

## Phase 1: Condition Lists

### Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT
RIGHT X LANES CLOSED	RIGHT X LANES OPEN
CENTER LANE CLOSED	DAYTIME LANE CLOSURES
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE
EXIT CLOSED	RIGHT LN TO BE CLOSED
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI
XXXXXXXX BLVD CLOSED	

### Other Condition List

ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT *

\* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

## Phase 2: Possible Component Lists

### Action to Take/Effect on Travel List

MERGE RIGHT	FORM X LINES RIGHT
DETOUR NEXT X EXITS	USE XXXXX RD EXIT
USE EXIT XXX	USE EXIT I-XX NORTH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N
TRUCKS USE US XXX N	WATCH FOR TRUCKS
WATCH FOR TRUCKS	EXPECT DELAYS
EXPECT DELAYS	PREPARE TO STOP
REDUCE SPEED XXX FT	END SHOULDER USE
USE OTHER ROUTES	WATCH FOR WORKERS
STAY IN LANE *	

### Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXX TO XXXXXX
US XXX TO FM XXXX

### Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

### \*\* Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

\*\* See Application Guidelines Note 6.

## APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

## WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

## FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:40 PM  
FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\VDG\Standard\bc-21.dgn

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Canal	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy Vehicle	HOV	Tuesday	TUES
Highway	HWY	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT

Roadway designation # IH-number, US-number, SH-number, FM-number


SHEET 6 OF 12

<h3>BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)</h3>			
<h2>BC (6) - 21</h2>			
FILE:	bc-21.dgn	DN:	TxDOT
© TxDOT	November 2002	CR:	TxDOT
REVISIONS	0065 06	DW:	TxDOT
9-07	8-14	OW:	TxDOT
7-13	5-21	CK:	TxDOT
DIST	COUNTY	HIGHWAY	
BMT	HARDIN	US69	
SHEET NO.		26	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/3/2023 3:13:42 PM  
 FILE: I:\BMT\DESIGN\Projects\0065-06-070\_US69\DCN\Standards\bc-21.dgn

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




**CONCRETE TRAFFIC BARRIER (CTB)**

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



**LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES**  
 LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

**LOW PROFILE CONCRETE BARRIER (LPCB)**



**DELINEATION OF END TREATMENTS**

**END TREATMENTS FOR CTB'S USED IN WORK ZONES**  
 End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

**BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS**

**WARNING LIGHTS**


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B<sub>FL</sub> or C<sub>FL</sub> Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

**WARNING LIGHTS MOUNTED ON PLASTIC DRUMS**


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

**WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS**

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.




Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

**ATTENTION**  
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

**FLASHING ARROW BOARDS**

SHEET 7 OF 12

**TRUCK-MOUNTED ATTENUATORS**

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.

Texas Department of Transportation  
 Traffic Safety Division Standard

**BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR**

**BC (7) -21**

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	OW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		0065 06	070, ETC	US69
9-07	8-14	DIST	COUNTY	SHEET NO.
7-13	5-21	BMT	HARDIN	27

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:44 PM  
 FILE: I:\BMT\DESIGN\Projects\0065-06-070\_US69\VDG\Standards\bc-21.dgn

**GENERAL NOTES**

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

**GENERAL DESIGN REQUIREMENTS**

Pre-qualified plastic drums shall meet the following requirements:



- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

**RETROREFLECTIVE SHEETING**

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


**BALLAST**

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




**DETECTABLE PEDESTRIAN BARRICADES**

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign  
(Maximum Sign Dimension)  
Chevron CW1-8, Opposing Traffic Lane  
Divider, Driveway sign D70a, Keep Right  
R4 series or other signs as approved  
by Engineer



12" x 24"  
Vertical Panel  
mount with diagonals  
sloping down towards  
travel way

Plywood, Aluminum or Metal sign  
substrates shall NOT be used on  
plastic drums

**SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS**

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B<sub>FL</sub> or Type C<sub>FL</sub> Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (8) - 21**

FILE:	bc-21.dgn	DN:	TxDOT	CR:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0065	06	070, ETC	US69				
4-03	8-14	DIST	COUNTY	SHEET NO.					
9-07	5-21	BMT	HARDIN	28					
7-13									


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:46 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard\bc-21.dgn



**FIXED**  
(Rigid or self-righting)


**DRIVEABLE**



**PORTABLE**


**VERTICAL PANELS (VPs)**

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




**OPPOSING TRAFFIC LANE DIVIDERS (OTLD)**

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

**CHEVRONS**



**LONGITUDINAL CHANNELIZING DEVICES (LCD)**

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

**WATER BALLASTED SYSTEMS USED AS BARRIERS**

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

**HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS**

**GENERAL NOTES**

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths * *			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

\* \* \* Taper lengths have been rounded off.  
 L=Length of Taper (FT.) W=Width of Offset (FT.)  
 S=Posted Speed (MPH)

**SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS**

SHEET 9 OF 12



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (9) - 21**

FILE: bc-21.dgn	DW: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	BMT	HARDIN	29	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:48 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\VDG\Standards\bc-21.dgn


**TYPE 3 BARRICADES**

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




**TYPICAL STRIPING DETAIL FOR BARRICADE RAIL**



Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.


**TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES**

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

**TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION**



PERSPECTIVE VIEW




PLAN VIEW

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector

**CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS**




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.  
 42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



**TRAFFIC CONTROL FOR MATERIAL STOCKPILES**



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (10) -21**

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	BMT	HARDIN	30	

## WORK ZONE PAVEMENT MARKINGS

### GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

### RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

### PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


### MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

### REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

## Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE  
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER  
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
  - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
  - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

### RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:  
 YELLOW - (two amber reflective surfaces with yellow body).  
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

**BC(11)-21**

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS		0065	06	070, ETC
2-98	9-07	5-21		US69
1-02	7-13			
11-02	8-14			
	DIST	COUNTY	SHEET NO.	
	BMT	HARDIN	31	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:50 PM  
 FILE: I:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard.ds\bc-21.dgn

## PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TXDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

## CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

## EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

## LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectORIZED pavement markings.





RAISED PAVEMENT MARKERS

## TWO-WAY LEFT TURN LANE


## STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS




### SOLID LINES



### BROKEN LINES




### AUXILIARY OR LANEDROP LINE



### REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC(12)-21

Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
1-97 9-07 5-21				
2-98 7-13				
11-02 8-14	BMT	HARDIN		SHEET NO. 32


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:52 PM  
FILE: I:\BMT\DESIGN\Projects\06-070\_US69\DN\Standards\bc-21.dgn




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:53 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\VDG\Standards\tcp2-1-18.dgn




TCP (2-1a)

**WORK SPACE NEAR SHOULDER**  
 Conventional Roads



TCP (2-1b)

**WORK SPACE ON SHOULDER**  
 Conventional Roads



TCP (2-1c)

**WORK VEHICLES ON SHOULDER**  
 Conventional Roads

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70	700'	770'	840'	70'	140'	800'	475'	
75	750'	825'	900'	75'	150'	900'	540'	

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	✓

**GENERAL NOTES**

- Flags attached to signs where shown, are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated in the plans, or for routine maintenance work, when approved by the Engineer.
- Stockpiled material should be placed a minimum of 30 feet from nearest traveled way.
- Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.
- See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
- Additional work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
- CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.




**TRAFFIC CONTROL PLAN**  
**CONVENTIONAL ROAD**  
**SHOULDER WORK**

**TCP (2-1) - 18**


FILE: tcp2-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 2-12	BMT	HARDIN	33	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:55 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard\tcp2-4-18.dgn



TCP (2-4a)  
**ONE LANE CLOSED**



TCP (2-4b)  
**TWO LANES CLOSED**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
		✓	✓	

**GENERAL NOTES**

- Flags attached to signs where shown, are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The downstream taper is optional. When used, it should be 100 feet minimum length per lane.
- For short term applications, when post mounted signs are not used, the distance legend may be shown on the sign face rather than on a CW16-3aP supplemental plaque.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.

**TCP (2-4a)**

- If this TCP is used for a left lane closure, CW20-5TL "LEFT LANE CLOSED" signs shall be used and channelizing devices shall be placed on the centerline to protect the work space from opposing traffic with the arrow board placed in the closed lane near the end of the merging taper.

**TCP (2-4b)**

- For shorter durations where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the speed in mph. This tighter devices spacing is intended for the area of conflicting markings, not the entire work zone.

Texas Department of Transportation  
 Traffic Operations Division Standard



**TRAFFIC CONTROL PLAN  
 LANE CLOSURES ON MULTILANE  
 CONVENTIONAL ROADS**

**TCP (2-4) - 18**



FILE: tcp2-4-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
8-95 3-03	DIST	COUNTY	SHEET NO.	
1-97 2-12	BMT	HARDIN	34	
4-98 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:13:57 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\VDGN\Standard.dwg\tcp3-2.dgn



**RIGHT LANE CLOSURE ON DIVIDED HIGHWAY - TCP(3-2a)**



**INTERIOR LANE CLOSURE ON MULTI-LANE DIVIDED HIGHWAY - TCP(3-2b)**


LEGEND				
*	Trail Vehicle	ARROW BOARD DISPLAY		
**	Shadow Vehicle			
***	Work Vehicle		RIGHT Directional	
	Heavy Work Vehicle		LEFT Directional	
	Truck Mounted Attenuator (TMA)		Double Arrow	
	Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)	

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**GENERAL NOTES**









- ADVANCE WARNING, TRAIL and SHADOW vehicles shall be equipped with Type B or Type C flashing arrow boards as per the Barricade and Construction (BC) standards. Arrow boards on WORK vehicles will be optional based on the type of work being performed. The arrow boards shall be operated from inside the vehicle.
- For TCP(3-2a) the Engineer will determine if the TRAIL VEHICLE is required based on prevailing roadway conditions, traffic volume, and sight distance restrictions. All other vehicles shown for both TCP(3-2a) and TCP(3-2b) are required.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the ADVANCE WARNING, SHADOW, and TRAIL vehicles are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DMS 8300, Type A.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE may vary according to terrain, work activity and other factors.
- Standard 48" X 48" diamond shaped warning signs with the same message as those shown may be used where adequate mounting space exists.
- The signs shown should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or a truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board, must be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
- Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
- The principles on this sheet may be used to close lanes from the left side of the roadway considering the number of lanes, shoulder width, sight distance, and ramp frequency.
- Signs and flashing arrow board modes shall be appropriately altered when implementing left lane closures or interior closures which close the left lanes.
- The Advance Warning Vehicle may straddle the edgeline when shoulder width makes it necessary.



**STRIPING FOR TMA**

		<b>Traffic Operations Division Standard</b>	
<b>TRAFFIC CONTROL PLAN          MOBILE OPERATIONS          DIVIDED HIGHWAYS</b>			
<b>TCP(3-2)-13</b>			
FILE: tcp3-2.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT December 1985	CONT: 0065	SECT: 06	JOB: 070, ETC
REVISIONS	0065	06	US69
2-94 4-98			
8-95 7-13			
1-97			
BMT	HARDIN		SHEET NO. 35

DATE: 1/3/2023 3:13:59 PM  
 FILE: I:\BMT\DESIGN\Projects\0065-06-070-US69\VDGN\Standard\std\tcp3-3.dgn  
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



LEGEND		
* Trail Vehicle	ARROW BOARD DISPLAY	
** Shadow Vehicle		
*** Work Vehicle		RIGHT Directional
		LEFT Directional
		Double Arrow
		CAUTION (Alternating Diamond or 4 Corner Flash)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

**GENERAL NOTES**

- TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used on two way roads the WORK vehicle must have an arrow board. For divided roadways, the arrow board on the WORK vehicle is optional based on the type of work being performed. The Engineer will determine if the LEAD vehicle and/or TRAIL vehicle are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating, or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE, ADVANCE WARNING and TRAIL VEHICLE are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
- Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
- X VEHICLE CONVOY (CW21-10cT) or WORK CONVOY (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" x 48" diamond shaped WORK CONVOY (CW21-10T) or X VEHICLE CONVOY (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The X VEHICLE CONVOY sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
- For divided highways with two or three lanes in one direction, the appropriate LEFT LANE CLOSED (CW20-5bTL), RIGHT LANE CLOSED (CW20-5bTR), or CENTER LANE CLOSED (CW20-5dT) sign should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board may be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
- A double arrow shall not be displayed on the arrow board on the Advance Warning Vehicle.
- For divided highways with three or four lanes in each direction, use TCP(3-2).
- Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
- The Advance Warning Vehicle may straddle the edgeline when Shoulder width makes it necessary.
- On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a DO NOT PASS (R4-1) sign should be placed on the back of the rearmost protection vehicle.


Texas Department of Transportation  
 Traffic Operations Division Standard

**TRAFFIC CONTROL PLAN**  
**MOBILE OPERATIONS**  
**RAISED PAVEMENT**  
**MARKER INSTALLATION/REMOVAL**  
**TCP (3-3) - 14**


FILE: tcp3-3.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT September 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
2-94 4-98				
8-95 7-13				
1-97 7-14	BMT		HARDIN	SHEET NO. 36

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:02 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DCM\Standard\Standard\std\tcp5-1-18.dgn



TCP (5-1a)  
**WORK AREA ON SHOULDER**



TCP (5-1b)  
**WORK AREA ON SHOULDER**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	90'
35		205'	225'	245'	35'	70'	120'
40		265'	295'	320'	40'	80'	155'
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70	700'	770'	840'	70'	140'	475'	
75	750'	825'	900'	75'	150'	540'	
80	800'	880'	960'	80'	160'	615'	

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	TCP (5-1a)	TCP (5-1b)	TCP (5-1b)	

- GENERAL NOTES**
1. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the performance or quality of the work. Type 3 barricades or drums may be substituted when workers on foot are no longer present when approved by the Engineer.
  2. 28" tall or taller one-piece cones will be allowed only for Short Duration or Short Term stationary operations when workers are present to maintain the devices upright and in proper location. Intermediate Term stationary work areas should use Drums, Vertical Panels or 42" tall two-piece cones.




**TRAFFIC CONTROL PLAN  
 SHOULDER WORK FOR  
 FREEWAYS / EXPRESSWAYS**


**TCP (5-1) - 18**

FILE: tcp5-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT February 2012	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
2-18	DIST	COUNTY	SHEET NO.	
	BMT	HARDIN	37	

DATE: 1/3/2023 3:14:04 PM  
 FILE: I:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard\tcp6-1.dgn  
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



TCP (6-1a)  
**TYPICAL FREEWAY ONE LANE CLOSURE**



TCP (6-1b)  
**TYPICAL FREEWAY TWO LANE CLOSURE**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed	Formula	Minimum Desirable Taper Lengths "L"			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'

\*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

**GENERAL NOTES**

- All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
- Drums or 42" cones are the typical channelizing devices. For Intermediate Term Stationary work, drums shall be used on tapers with drums or 42" cones used on tangent sections. Other channelizing devices may be used as directed by the Engineer.
- All construction signs and barricades placed during any phase of work shall remain in place until removal is approved by the Engineer.
- The Engineer may direct the Contractor to furnish additional signs and barricades as required to maintain traffic flow, detours and motorist safety during construction.
- Static message boards or changeable message signs stating the date and duration of ramp or freeway lane closures shall be placed a minimum of seven (7) calendar days in advance of the actual closure.
- Phase 2 of the PCMS message should include appropriate information formatted as shown on BC(6), such as "MERGE LEFT," recommended advisory speed, delay information, or other specific warnings.
- Duplicate construction warning signs should be erected on the medians side of freeways where median width will permit and traffic volume justifies the signing.
- The number of closed lanes may be increased provided the spacing of traffic control devices, taper lengths and tangent lengths meet the requirements of the TMUTCD.
- Warning signs for intermediate term stationary work should be mounted at 7' to the bottom of the sign.
- Warning signs shown shall be appropriately altered for left lane closures. When signs are mounted at 1' height for short term stationary or short duration work, sign versions shown in the SHSD for Texas with distances on the sign face rather than mounted on a plaque below the sign may be used.
- When possible, PCMS units should be located in advance of the last available exit ramp prior to the lane closure to allow motorists an alternate route. They may also be relocated to improve advance warning in case of unanticipated queuing or congestion.
- For Intermediate Term Stationary work at night, floodlights should be used to illuminate the work area and equipment crossings. Floodlights shall not produce a disabling glare condition for road users or workers.
- The END ROAD WORK (G20-2) sign may be omitted when it conflicts with G20-2 signs already in place on the project.

\* A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.




**TRAFFIC CONTROL PLAN  
 FREEWAY LANE CLOSURES**

**TCP (6-1) - 12**


FILE:	tcp6-1.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	February 1998	CONT	SECT	JOB	HIGHWAY				
8-12	REVISIONS	0065	06	070, ETC	US69				
	DIST	COUNTY		SHEET NO.					
	BMT	HARDIN		38					

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:06 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard.dwg\tcp6-2.dgn



TCP (6-2a)  
**ENTRANCE RAMP OPEN**  
**WORK WITHIN 500' OF RAMP**



TCP (6-2b)  
**ENTRANCE RAMP CLOSED**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed	Formula	Minimum Desirable Taper Lengths "L"			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'

\*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

**GENERAL NOTES**

- All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
- ADDED LANE Symbol (CW4-3) sign may be omitted when sign between ramp and mainline can be seen from both roadways.
- See "Advance Notice List" on BC(6) for recommended date and time formatting options for PCMS Phase 2 message.
- The END ROAD WORK (G20-2) sign may be omitted when it conflicts with G20-2 signs already in place on the project.

\*A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.

Additional requirements for lane closures and advance signing shall be as shown on TCP (6-1) or as directed by the Engineer.




**TRAFFIC CONTROL PLAN**  
**WORK AREA NEAR RAMP**

**TCP (6-2) - 12**


FILE:	tcp6-2.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
©TxDOT	February 1994	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0065 06	070, ETC		US69				
1-97	8-98			DIST	COUNTY	SHEET NO.			
4-98	8-12			BMT	HARDIN	39			

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:07 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard.dwg\tcp6-3.dgn



TCP (6-3a)  
**ENTRANCE RAMP OPEN**



TCP (6-3b)  
**EXIT RAMP CLOSED**  
**TRAFFIC EXITS PRIOR TO CLOSED RAMP**

STREET B  
 EXIT  
 CLOSED

USE  
 STREET A  
 EXIT

Or, as an option when  
 exits are numbered

EXIT XY  
 CLOSED

USE  
 EXIT XX

Place 1 mile (approx.)  
 in advance of Street A  
 exit.

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed	Formula	Minimum Desirable Taper Lengths "L" **			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'

\*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

GENERAL NOTES:  
 1. All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.

\*A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.

Additional requirements for lane closures and advance signing shall be as shown on TCP (6-1) or as directed by the Engineer.

Texas Department of Transportation  
 Traffic Operations Division Standard

**TRAFFIC CONTROL PLAN**  
**WORK AREA BEYOND RAMP**


**TCP (6-3) - 12**

FILE: tcp6-3.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 1994	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065 06		070, ETC	US69
1-97 8-98	DIST	COUNTY	SHEET NO.	
4-98 8-12	BMT	HARDIN	40	



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:09 PM  
 FILE: T:\BMT\DESIGN\Projects\065-06-070\_US69\DGN\Standard.dwg\tcp6-4.dgn




**TCP (6-4a)**  
**EXIT RAMP CLOSED**  
**TRAFFIC EXITS PAST CLOSED RAMP**

STREET A EXIT CLOSED	USE STREET B EXIT
EXIT XX CLOSED	USE EXIT XY

Or, as an option when exits are numbered

Place 1 mile (approx.) in advance of closed ramp.



**TCP (6-4b)**  
**EXIT RAMP OPEN**

LEGEND			
	Type 3 Barricade		Channelizing Devices (CDs)
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed	Formula	Minimum Desirable Taper Lengths "L"			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'

\*\*Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

- GENERAL NOTES**
- All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
  - See BC Standards for sign details.

\*A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.

Additional requirements for lane closures and advance signing shall be as shown on TCP (6-1) or as directed by the Engineer.




**TRAFFIC CONTROL PLAN**  
**WORK AREA AT EXIT RAMP**

**TCP (6-4) - 12**


FILE: tcp6-4.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 1994	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
1-97 8-98	DIST	COUNTY	SHEET NO.	
4-98 8-12	BMT	HARDIN	41	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:11 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DCN\Standard.dgn



TCP (6-5a)  
**EXIT RAMP OPEN**



TCP (6-5b)  
**EXIT RAMP OPEN  
 TWO LANE CLOSURE WITHIN  
 1500' PAST EXIT RAMP**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed	Formula	Minimum Desirable Taper Lengths "L" * * *			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'

\* \* \* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

- GENERAL NOTES**
- All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
  - See BC standards for sign details.
  - If adequate longitudinal buffer length "B" does not exist between the work space and the exit ramp, consideration should be given to closing the ramp.

\*A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.

Additional requirements for lane closures and advance signing shall be as shown on TCP (6-1) or as directed by the Engineer.




**TRAFFIC CONTROL PLAN  
 WORK AREA BEYOND EXIT RAMP**

**TCP (6-5) - 12**


FILE:	tcp6-5.dgn	DN:	TxDOT	CK:	TxDOT	OW:	TxDOT	CK:	TxDOT
©TxDOT	February 1998	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0065	06	070, ETC	US69				
1-97	8-98			DIST	COUNTY	SHEET NO.			
4-98	8-12			BMT	HARDIN	42			

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/3/2023 3:14:13 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DM\Standards\tcpsc-5-22.dgn



TCP (SC-5a)  
**ONE LANE CLOSURE**



TCP (SC-5b)  
**LANE AND RAMP CLOSURE AT EXIT RAMP**



TCP (SC-5c)  
**LANE AND RAMP CLOSURE AT ENTRANCE RAMP**

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing Distance "x"	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L = Length of Taper (FT) W = Width of Offset (FT)  
 S = Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
		✓		

- GENERAL NOTES**
- Flags attached to signs where shown, are REQUIRED.
  - All traffic control devices illustrated are REQUIRED, except:
    - If project signing is present, END ROAD WORK (G20-2) sign is optional with approval by the Engineer.
    - USE NEXT RAMP (CW25-1T) sign is optional with approval by the Engineer.
  - Channelizing devices used to close lanes may be supplemented with the Chevron Alignment Sign placed on every other channelizing device. Chevrons may be attached to plastic drums as per BC Standards.
  - The PCMS may be omitted if: it is replaced with a RAMP CLOSED AHEAD (CW20RP-3D) sign or when a permanent Dynamic Message Sign (DMS) is available in the appropriate location to display a similar message as called for on the PCMS.
  - Temporary rumble strips are not required on seal coat operations.

SHEET 5 OF 8

Texas Department of Transportation  
 Traffic Safety Division Standard


**TRAFFIC CONTROL PLAN  
 SEAL COAT OPERATIONS  
 DIVIDED HIGHWAYS**

**TCP (SC-5) - 22**


FILE: tcpsc-5-22.dgn	DN:	CK:	DW:	CK:
© TxDOT October 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
4-21	DIST	COUNTY	SHEET NO.	
10-22	BMT	HARDIN	43	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/3/2023 3:14:15 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard.dwg\fcpsc-6-22.dgn



TCP (SC-6a)  
**MULTIPLE LANE EXIT RAMP CLOSURE**



TCP (SC-6b)  
**SINGLE LANE EXIT RAMP CLOSURE**



TCP (SC-6c)  
**TYPICAL EXIT RAMP CLOSURE**

LEGEND			
	Type 3 Barricade		Channelizing Devices (CDs)
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed	Formula	Minimum Desirable Taper Lengths "L" **			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'
85		850'	935'	1020'	85'	170'	695'

\*\* Taper lengths have been rounded off.  
 L = Length of Taper (FT) W = Width of Offset (FT)  
 S = Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES**
- Place channelizing devices at 20' spacings. Tighter spacing allowed as necessary to address field conditions or observed driver behavior.
  - See the Standard Highway Sign Design for Texas (SHSD) for sign details.
  - The PCMS may be omitted if replaced with a RAMP CLOSED AHEAD (CW20RP-3D) sign or when a permanent Dynamic Message Sign (DMS) is available in an appropriate location to display a similar message as called for on the PCMS.
  - When it is determined that a through lane should be closed in addition to the exit ramp, refer to TCP(6-4) for traffic control details.
  - A Truck Mounted Attenuator (TMA), where shown, is REQUIRED and shall have a RAMP CLOSED (R11-2bT) sign mounted on the rear of the truck.

**TRAFFIC CONTROL PLAN  
 SEAL COAT OPERATIONS  
 DIVIDED HIGHWAYS**


**TCP (SC-6) - 22**

FILE: fcpsc-6-22.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT October 2022	CONT	SECT	JOB	HIGHWAY
10-22	REVISIONS	0065 06	070, ETC	US69
	DIST	COUNTY	SHEET NO.	
	BMT	HARDIN	44	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard.dwg\cpsc-7-22.dgn


**WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS (TABS)**




**CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO LANE TWO-WAY HIGHWAYS**



**LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS**



**LANE LINES FOR DIVIDED HIGHWAY**




**TWO-WAY LEFT TURN LANE**

**WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS (TABS)**

SOLID LINES	DOUBLE NO-PASSING LINE	
	SINGLE NO-PASSING LINE OR CHANNELIZATION LINE	
	8" WIDE SOLID LINE	
BROKEN LINES (FOR CENTER LINE OR LANE LINE)		
WIDE DOTTED LINES (FOR LANE DROP LINES)		
WIDE GORE MARKINGS		

**TABS ON CENTERLINES OF TWO-LANE TWO-WAY ROADS**



**TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER TABS**

1. Temporary markings for surfacing projects shall be Temporary Flexible-Reflective Roadway Marker Tabs with protective cover unless otherwise approved by the Engineer. Tabs are to be installed to provide true alignment for striping crews or as directed by the Engineer. Tabs will be placed at the spacing indicated. Tabs should be applied to the pavement no more than two days before the surfacing is applied. After the surfacing is rolled and swept, the protective cover over the reflective strip shall be removed.
2. Temporary Flexible-Reflective Roadway Marker Tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with a yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
3. Temporary Flexible-Reflective Roadway Marker Tabs will require normal maintenance replacement when used on roadways with an Average Daily Traffic (ADT) per lane of up to 7500 vehicles with no more than 10% truck mix. When roadway volumes exceed these values, additional maintenance replacement of these devices should be planned for.
4. When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
5. No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 4.
6. Tabs shall meet requirements of Departmental Material Specification DMS-8242.
7. Tabs shall NOT be used to simulate edge lines.

**NOTES:**


1. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
2. For exit gores where a lane is being dropped, place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are NOT acceptable.
3. Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.

**DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)**

1. DMSs referenced above may be found along with embedded links to their respective MPLs at the following website: <http://www.txdot.gov>

SHEET 7 OF 8

**TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER TABS**



Height of sheeting is usually more than 1/4" and less than 1".

Texas Department of Transportation  
 Traffic Safety Division Standard

**TEMPORARY PAVEMENT MARKINGS FOR SEAL COAT OPERATIONS**


**TCP (SC-7) -22**

FILE: tcpsc-7-22.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT October 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
4-21	DIST	COUNTY	SHEET NO.	
10-22	BMT	HARDIN	45	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:19 PM  
 FILE: T:\BMTDESIGN\Projects\0065-06-070\_US69\DGN\Standard\wzstpm-13.dgn

## WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS





### NOTES:

- Short term pavement markings may be prefabricated markings (stick down tape) or temporary flexible-reflective roadway marker tabs unless otherwise specified elsewhere in plans.
- Short term pavement markings shall NOT be used to simulate edge lines.
- Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.
- Temporary flexible-reflective roadway marker tabs will require normal maintenance replacement when used on roadways with an ADT per lane of up to 7500 vehicles with no more than 10% truck mix. When roadways exceed these values, additional maintenance replacement of devices should be planned.
- No segment of roadway open to traffic shall remain without permanent pavement markings for a period greater than 14 calendar days. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
- For two lane, two-way roadways, DO NOT PASS signs shall be erected to mark the beginning of sections where passing is prohibited and PASS WITH CARE signs shall be erected to mark the beginning of sections where passing is permitted. Signs shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and may be used to indicate the limits of no-passing zones for up to 14 calendar days. Permanent pavement markings should then be placed.
- For low volume two lane, two-way roadways of 4000 ADT or less, no-passing lines may be omitted when approved by the Engineer. DO NOT PASS and PASS WITH CARE signs shall be erected (see note 6).
- For exit gores where a lane is being dropped place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are not allowed for this purpose.

### TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS (TABS)

- Temporary flexible-reflective roadway marker tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
- Tabs shall meet requirements of Departmental Material Specification DMS-8242.
- When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
- No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 3.

## WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS



If raised pavement markers are used to supplement REMOVABLE short term markings, the markers shall be applied to the top of the tape at the approximate mid length of the tape. This allows an easier removal of raised markers and tape.

### PREFABRICATED PAVEMENT MARKINGS

- Temporary Removable Prefabricated Pavement Markings shall meet the requirements of DMS-8241.
- Non-removable Prefabricated Pavement Markings shall meet the requirements of either DMS-8240 "Permanent Prefabricated Pavement Markings" or DMS-8243 "Temporary Construction-Grade Prefabricated Pavement Markings."

### RAISED PAVEMENT MARKERS

- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and DMS-4200.

### DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)

- DMSs referenced above can be found along with embedded links to their respective MPLs at the following website:  
[http://www.txdot.gov/business/contractors\\_consultants/material\\_specifications/default.htm](http://www.txdot.gov/business/contractors_consultants/material_specifications/default.htm)







## WORK ZONE SHORT TERM PAVEMENT MARKINGS

### WZ (STPM) - 13

FILE:	wzstpm-13.dgn	DN:	TxDOT	CK:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	April 1992	CONT:	0065	SECT:	06	JOB:	070, ETC	HIGHWAY:	US69
REVISIONS:		DIST:	BMT	COUNTY:	HARDIN	SHEET NO.:	46		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:14:21 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DCN\Standard\wz\ul-13.dgn



DEPARTMENTAL MATERIAL SPECIFICATIONS	
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY (REMOVABLE) PREFABRICATED PAVEMENT MARKINGS	DMS-8241
SIGN FACE MATERIALS	DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B <sub>FL</sub> OR TYPE C <sub>FL</sub> SHEETING
BLACK	LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING

**GENERAL NOTES**

- If spalling or holes occur, ROUGH ROAD (CW8-8) signs should be placed in advance of the condition and be repeated every two miles where the condition persists.
- UNEVEN LANES (CW8-11) signs shall be installed in advance of the condition and repeated every mile. Signs installed along the uneven lane condition may be supplemented with the NEXT XX MILES (CW7-3aP) plaque or Advisory Speed (CW13-1P) plaque.
- NO CENTER LINE (CW8-12) signs and temporary pavement markings as per the WZ(STPM) standard shall be installed if yellow centerlines separating two way traffic are obscured or obliterated. Repeat NO CENTER LINE signs every two miles where the center line markings are not in place. The signs and markings shall remain in place until permanent pavement markings are installed.
- Signs shall be spaced at the distances recommended as per BC standards.
- Additional signs may be required as directed by the Engineer. Signs shall remain in place until final surface is applied. Signs shall be considered subsidiary to Item 502 "BARRICADES, SIGNS AND TRAFFIC HANDLING."
- Signs shall be fabricated and mounted on supports as shown on the BC standards and/or listed on the "Compliant Work Zone Traffic Control Devices" list.
- Short term markings shall not be used to simulate edge lines.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition.

TABLE 1		
Edge Condition	Edge Height (D)	* Warning Devices
①	Less than or equal to: 1/4" (maximum-planing) 1/2" (typical-overlay)	Sign: CW8-11
②	Less than or equal to 3"	Sign: CW8-11
③	Distance "D" may be a maximum of 3" if uneven lanes with edge condition 2 or 3 are open to traffic after work operations cease. Uneven lanes should not be open to traffic when "D" is greater than 3".	

**TRAFFIC CONTROL DURING PLANING, OVERLAY AND LEVELING OPERATIONS ARE SHOWN ELSEWHERE IN THE PLANS.**

MINIMUM WARNING SIGN SIZE	
Conventional roads	36" x 36"
Freeways/expressways, divided roadways	48" x 48"



**SIGNING FOR UNEVEN LANES**


**WZ (UL) - 13**

FILE: wzul-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT	APRIL 1992	CONT SECT	JOB	HIGHWAY
REVISIONS		0065 06	070, ETC	US69
8-95	2-98	7-13	DIST	COUNTY
1-97	3-03		BMT	HARDIN
				SHEET NO. 47


DATE: 1/3/2023 3:14:23 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\VDGN\Standards\wzrs22.dgn

Warning sign and rumble strip sequence in opposite direction is same as below.

Flagger to Flagger (Length of Work Area)	ADT	# of Rumble Strip Arrays
1/8 Mile	< 4,500	1
	≥ 4,500	2
1/4 Mile	< 3,500	1
	≥ 3,500	2
1/2 Mile	< 2,600	1
	≥ 2,600	2
1 Mile	< 1,600	1
	≥ 1,600	2
> 1 Mile	N/A	2



**RUMBLE STRIPS ON ONE-LANE TWO-WAY APPLICATION**



**RUMBLE STRIPS FOR LANE CLOSURE ON CONVENTIONAL ROADWAY**

**GENERAL NOTES**

- Each Rumble Strip Array should consist of three rumble strips spaced center to center at the spacing shown in Table 2, placed transverse across the lane at locations shown.
- The CW17-2T "RUMBLE STRIPS AHEAD" sign should be located after the CW20-1D "ROAD WORK AHEAD" sign and spaced as shown. If traffic is observed to be queuing, or is expected to queue beyond the Rumble Strips, the CW17-2T sign and the first Rumble Strip Array may be located upstream of the CW20-1D sign as necessary to provide needed warning.
- Temporary Rumble Strips will be considered subsidiary to Item 502, and shall be a product listed on the Compliant Work Zone Traffic Control Devices.
- Remove Temporary Rumble Strips before removing the advanced warning signs.
- Temporary Rumble Strips should not be used on horizontal curves, loose gravel, soft or bleeding asphalt, heavily rutted pavements or unpaved surfaces.
- Temporary Rumble Strips shall be installed and maintained as per manufacturer's recommendations.
- This standard sheet shall be used in conjunction with other appropriate TCP standard, TMUTCD typical application or project specific detail for the project.
- The one-lane two-way application may utilize a flagger, an Automated Flagger Assistance Device (AFAD) or a Portable Traffic Signal (PTS).
- Replace defective Temporary Rumble Strips as directed by the Engineer.
- Temporary Rumble Strips may be used on freeways or expressways based on engineering judgment and written direction from the Engineer.

Speed	Approximate distance between strips in an array
≤ 40 MPH	10'
> 40 MPH & ≤ 55 MPH	15'
= 60 MPH	20'
≥ 65 MPH	* 35' +

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Panel		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT)  
 S=Posted Speed (MPH)

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

◆ Signs are for illustrative purposes only. Signs required may vary depending on the TCP, TMUTCD Typical Application, or project specific details for the project.  
 \* For posted speeds in excess of 65 MPH, it is recommended that spacing is increased as speed limits increase. Increasing space between rumble strips will improve effectiveness.

Texas Department of Transportation  
 Traffic Safety Division Standard


## TEMPORARY RUMBLE STRIPS

### WZ (RS) - 22

FILE: wzrs22.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2012	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
2-14 1-22	DIST	COUNTY	SHEET NO.	
4-16	BMT	HARDIN	48	



FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:14:29 PM





LEGEND

- ← TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"

NOTES:

NO OVERLAY WITHIN U-TURN SECTIONS. ALL U-TURN SECTIONS WILL BE JOINT SEALED AND HAVE DIAMOND GRINDING.  
 ALL PAVEMENT IS TO BE DIAMOND GROUND, JOINT SEALED, CRACK SEALED, AND SEAL COATED BEFORE TOM OVERLAY.  
 SEE TYPICAL SECTION DETAIL FOR CURB AND GUTTER OVERLAY TRANSITION.



Jason D. Waldrep, P.E.


01/03/2023

US69

ROADWAY LAYOUT

0 50 100


SCALE IN FEET



SHEET 01 OF 16


FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		49
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\MI11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:14:31 PM



LEGEND

- ← TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"



END WORK AT RAMP  
 PAVEMENT TRANSITION  
 STA. 47+00

10' TY 2 CURB

20' TY 2 CURB

6' TY 2 CURB

6' TY 2 CURB

STA 48+00

10' TY 2 CURB  
 50' TY 2 CURB

6' TY 2 CURB

12' 12' 12'

MATCH LINE - STA. 55+94.5

4' TY 2 CURB

6' TY 2 CURB

10' TY 2 CURB

10' TY 2 CURB

STA 52+62

45+00

50+00

30' TY 2 CURB

22' TY 2 CURB

4' TY 2 CURB

12' 12' 12'


100' TY 2 CURB

12' 12' 12'

BEGIN SEAL COAT  
 BEGIN TOM OVERLAY  
 BEGIN DIAMOND GRINDING  
 STA. 51+00

ANDERSON ST.

MATCH LINE - STA. 41+94




Jason D. Waldrep, P.E.

01/03/2023

US69

ROADWAY LAYOUT




SCALE IN FEET

© 2022 Texas Department of Transportation

SHEET 02 OF 16



FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				50	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		



LEGEND

- ← TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"


FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:14:51 PM



Jason D. Waldrep, P.E.  
 01/03/2023

US69


ROADWAY LAYOUT



© 2022 Texas Department of Transportation


FEDERAL AID PROJECT NO.		SHEET NO.	
		51	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:14:54 PM



**LEGEND**

- ← TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"



Jason D. Waldrep, P.E.

01/03/2023


**US69 ROADWAY LAYOUT**

0 50 100  
SCALE IN FEET

© 2022 Texas Department of Transportation


FEDERAL AID PROJECT NO.		SHEET NO.	
0665 06 070, ETC		52	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0665	06	070, ETC	US69

FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:14:58 PM



**LEGEND**


- ← TRAFFIC FLOW
- ▨ DIAMOND GRINDING 1"
- ▩ SEAL COAT AND TOM OVERLAY 1"



*Jason D. Waldrep, P.E.*

01/03/2023

**US69**  
**ROADWAY LAYOUT**




SCALE IN FEET

© 2022 Texas Department of Transportation

SHEET 05 OF 16


FEDERAL AID PROJECT NO.		SHEET NO.	
		53	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\M111 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:03 PM



**LEGEND**

- TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"



Jason D. Waldrep, P.E.

01/03/2023

**US69 ROADWAY LAYOUT**




SCALE IN FEET

© 2022 Texas Department of Transportation

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		54
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

SHEET 06 OF 16

FILE: \\BMTDESIGN\Projects\0665-06-070\US69\DCN\MI11 and Overlay Layouts.dgn  
 DATE: 3/3/2023 3:15:07 PM




**LEGEND**

- ← TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"

**US69 ROADWAY LAYOUT**

0 50 100  
SCALE IN FEET




Jason D. Waldrep, P.E.

© 2022 Texas Department of Transportation SHEET 07 OF 16


FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		55
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL SECTION	JOB	HIGHWAY NO.
0065	06 070, ETC	US69

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:12 PM



**LEGEND**

- ← TRAFFIC FLOW
- DIAMOND GRINDING 1"
- SEAL COAT AND TOM OVERLAY 1"



Jason D. Waldrep, P.E.

01/03/2023

**US69 ROADWAY LAYOUT**


0 50 100  
 SCALE IN FEET

© 2022 Texas Department of Transportation

FEDERAL AID PROJECT NO.		SHEET NO.	
		56	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69



FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\M11 and Overlay Layouts.dgn  
 DATE: 1/3/2023 3:15:16 PM




LEGEND

← TRAFFIC FLOW

DIAMOND GRINDING 1"

SEAL COAT AND TOM OVERLAY 1"




Jason D. Waldrep, P.E.

01/03/2023

US69

ROADWAY LAYOUT





© 2022 Texas Department of Transportation

FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				57	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		

SHEET 09 OF 16



FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\MM111\MM1 Layouts.DGN  
 DATE: 1/3/2023 3:15:20 PM



**LEGEND**

- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY

**NOTES:**  
 100 FT HMA TAPERS WILL BE USED AT EACH BRIDGE APPROACH TO TRANSITION FROM PFC TO POLYMER OVERLAYS  
 SEE TYPICAL SECTION DETAILS FOR DRAIN INLET TRANSITIONS  
 REMOVE AND REPLACE ALL MBGF WITHIN OVERLAY LIMITS




*Jason D. Waldrep, P.E.*

01/03/2023

**US69**

**ROADWAY LAYOUT**




SCALE IN FEET  
 © 2022 Texas Department of Transportation

FEDERAL AID PROJECT NO.		SHEET NO.	
		58	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

SHEET 10 OF 16

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\MI11 and Overlay Layouts.dgn  
 DATE: 1/3/2023 3:15:23 PM



**LEGEND**

- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY

MATCH LINE - STA. 348+57.5

MATCH LINE - STA. 469+00

MATCH LINE - STA. 469+00


MATCH LINE - STA. 482+00

END POLYMER OVERLAY  
 BEGIN HMA TRANSITION OVERLAY  
 STA. 471+76

END HMA TRANSITION OVERLAY  
 BEGIN SEAL COAT AND PFC OVERLAY  
 STA. 472+76


*Jason D. Waldrep, P.E.*

01/03/2023



**US69**

**ROADWAY LAYOUT**




© 2022 Texas Department of Transportation

SHEET 11 OF 16


FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				59	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		

FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:27 PM




**LEGEND**

- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY




**US69**

**ROADWAY LAYOUT**



*Jason D. Waldrep, P.E.*

01/03/2023




© 2022 Texas Department of Transportation

FEDERAL AID PROJECT NO.		SHEET NO.	
TEXAS		60	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

SHEET 12 OF 16

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DCN\MI11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:31 PM





**LEGEND**

- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY

**US69**

**ROADWAY LAYOUT**





*Jason D. Waldrep, P.E.*

01/03/2023

© 2022 Texas Department of Transportation  
 SHEET 13 OF 16

FEDERAL AID PROJECT NO.		SHEET NO.	
		61	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69


FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\MI11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:34 PM



**LEGEND**


- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY

**US69**  
**ROADWAY LAYOUT**



*Jason D. Waldrep, P.E.*


01/03/2023



© 2022 Texas Department of Transportation SHEET 14 OF 16

FEDERAL AID PROJECT NO.		SHEET NO.	
0065 06 070, ETC		62	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:38 PM




**LEGEND**

- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY

END OVERLAY AT  
 RAMP PAVEMENT TRANSITION  
 STA. 587+64


END OVERLAY AT  
 RAMP PAVEMENT TRANSITION  
 STA. 593+15



*Jason D. Waldrep, P.E.*

01/03/2023

**US69**  
**ROADWAY LAYOUT**




© 2022 Texas Department of Transportation

FEDERAL AID PROJECT NO.		SHEET NO.	
		63	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

SHEET 15 OF 16

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\M11 and Overlay Layouts.DGN  
 DATE: 1/3/2023 3:15:41 PM




BEGIN POLYMER OVERLAY  
 END HMA TRANSITION  
 OVERLAY  
 STA. 605+27

BEGIN HMA TRANSITION OVERLAY  
 END SEAL COAT AND PFC OVERLAY  
 STA. 604+27


REMOVE AND REPLACE MBGF,  
 SGT. AND MOW STRIP  
 STA. 605+27

END 0065-06-070  
 END POLYMER OVERLAY  
 STA. 617+11



LEGEND

- ← TRAFFIC FLOW
- POLYMER OVERLAY BRIDGE DECK
- HMA TRANSITION 2" TO 0"
- PFC OVERLAY




Jason D. Waldrep, P.E.


01/03/2023

US69

ROADWAY LAYOUT



SCALE IN FEET




SHEET 16 OF 16

FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				64	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		




FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\Dowel Bar Detail.s.dgn  
 DATE: 1/3/2023 3:15:44 PM




**PLAN VIEW**

SEAL EXISTING TRANSVERSE JOINT/CRACK AT BOTTOM AND SIDES OF THE DOWEL BAR SLOT WITH CAULKING FILLER PRIOR TO PLACING DOWEL BAR AND FOAM CORE INSERT.




**ELEVATION VIEW**




THICKNESS OF FOAM CORE INSERT TO MATCH WIDTH OF EXISTING TRANSVERSE JOINT.  
 1/4" to 1/2" (Typ.)


DOWEL BAR DIAMETER (18" LENGTH)	
PAVEMENT THICKNESS	DOWEL DIAMETER (d)
≤ 10"	1 1/4"
> 10"	1 1/2"



**SECTION A-A**




**LOCATION PLAN**



**SKEWED SCENARIO**

ROUTE, CLEAN, AND SEAL WORKING TRANSVERSE CRACKS IN ACCORDANCE WITH ITEM 438.



Jason D. Waldrep, P.E.

01/03/2023

NOT TO SCALE



FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		65
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

**DOWEL BAR RETROFIT DETAIL**

FILE: T:\BMT\DESIGN\Projects\0065-06-070\*US69\DGN\Dowel Bar Detail.s.dgn  
 DATE: 1/3/2023 3:15:46 PM


STATION RANGE		LANE	*3039	*3086	*361	*720	
			6001	6001	6077 & 607	6001	
			DOWEL BAR RETROFIT	SOIL DENS. AND RAISING CONC SLABS (HDPF)	FULL DEPTH REPAIR	SPALLING REPAIR	
			EA	SY	SY	SY	
32+00	-	41+94	SBOL	6	40	---	---
			SBIL	18	---	---	---
			NBIL	18	---	---	---
			NBOL	24	40	---	---
41+94	-	55+94	SBOL	6	370	---	---
			SBIL	30	---	---	10
			NBIL	12	---	7	---
			NBOL	---	80	7	7
55+94	-	71+01	SBOL	42	7	---	7
			SBIL	60	---	---	---
			NBIL	18	27	---	7
			NBOL	42	---	7	---
71+01	-	99+01	SBOL	72	---	100	2
			SBIL	42	---	---	7
			NBIL	48	20	7	14
			NBOL	198	---	53	14
99+01	-	127+01	SBOL	36	280	20	27
			SBIL	24	---	14	27
			NBIL	60	---	54	7
			NBOL	18	---	33	---
127+01	-	154+94	SBOL	42	---	14	7
			SBIL	36	---	---	46
			NBIL	36	100	33	14
			NBOL	---	67	86	106
154+94	-	183+00	SBOL	72	---	67	20
			SBIL	96	---	14	33
			NBIL	---	---	---	---
			NBOL	---	---	---	---
183+00	-	210+98	SBOL	114	---	14	7
			SBIL	120	---	14	14
			NBIL	---	---	---	---
			NBOL	---	---	---	---
TOTALS			1290	1031	544	376	

\* - FOR THE CONTRACTORS INFORMAITON ONLY. THESE LOCATIONS/QUANTITIES SHOULD BE VERIFIED WITH THE AREA ENGINEER.


NB - NORTH BOUND  
 SB - SOUTH BOUND  
 IL - INSIDE LANE  
 OL - OUTSIDE LANE

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/3/2023  
 FILE: T:\BMT\DESIGN\Projects\065-06-070\_US69\DGN\Standards\cccg22.dgn




**TYPE I CURB (MONOLITHIC)**  
 2" - 4" HEIGHT




**TYPE I CURB**  
 2" - 4" HEIGHT




**TYPE I CURB AND GUTTER**  
 2" - 4" HEIGHT




**TYPE II CURB (MONOLITHIC)**  
 5" - 5 3/4" HEIGHT




**TYPE II CURB**  
 5" - 5 3/4" HEIGHT




**TYPE II CURB AND GUTTER**  
 5" - 5 3/4" HEIGHT




**TYPE III CURB (KEYED)**  
 2" - 4" HEIGHT




**TYPE IIa CURB**  
 5" - 5 3/4" HEIGHT




**TYPE IIa CURB AND GUTTER**  
 5" - 5 3/4" HEIGHT



**TYPE IV CURB (KEYED)**  
 5" - 5 3/4" HEIGHT




**EXPANSION JOINT DETAIL**



**CURB TRANSITION**  
 Note: To be paid for as Highest Curb

**GENERAL NOTES**

- All materials and construction shall be in accordance with Item 529, "Concrete Curb, Gutter, and Combined Curb and Gutter."
- Concrete shall be Class A.
- When reinforcing bars are used, they shall be No.4 unless otherwise shown. The use of fiber reinforced concrete in lieu of reinforcing steel is acceptable. Use fibers meeting the requirements of DMS 4550, "Fibers for Concrete," and dose fibers in accordance with Material Producers List (MPL) "Fibers for Class A and B Concrete Applications."
- Round exposed sharp edges with a rounding tool, to a minimum radius of 1/4 inch.
- All existing curbs and driveways to be removed shall be sawed or removed at existing joints.
- Where concrete curb is to be placed on existing concrete pavement, Bar B may be drilled and grouted in place, or may be inserted into fresh concrete.
- Expansion and contraction joints shall be constructed to match pavement joints in all curbs and curb and gutter adjacent to jointed concrete pavement. Where placement of curb or curb and gutter is not adjacent to concrete pavement, expansion joints shall be provided at structures, curb returns at streets, and at locations directed by The Engineer.
- Vertical and horizontal dowel bars and transverse reinforcing bars shall be placed at four feet C-C.
- Dimension 'T' shown is the thickness of concrete pavement. When curb is installed adjacent to flexible pavement dimension 'T' is 8" maximum.
- Usual profile grade line. Refer to typical sections and plan-profile sheets for exact locations.
- One-half inch expansion joint material shall be provided where curb or curb and gutter is adjacent to sidewalk or riprap.
- When horizontal permissible construction joints are used, the longitudinal pavement steel shall be placed in accordance with pavement details shown elsewhere in the plans. Reinforcing steel for curb section shall then conform to that required for concrete curb.
- Bar B placement as needed (typically at four ft. C-C) to support curb reinforcing steel during concrete placement.




**CURB TRANSITION NOTE:**  
 Field conditions may require a longer or shorter transition, and shall be shown elsewhere in the plans, or as directed by the Engineer.


		<b>Design Division Standard</b>	
<h2>CONCRETE CURB AND GUTTER</h2>			
<h3>CCCG-22</h3>			
FILE: cccg21.dgn	DN: TxDOT	CK: AN	DW: CS
© TxDOT: JUNE 2022	CONT: 06	SECT: 06	JOB: HIGHWAY
REVISIONS	0065	06	070, ETC.
	DIST: BMT	COUNTY: HARDIN, ETC.	SHEET NO. 67

DATE: 1/3/2023  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standards\js14.dgn  
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


METHOD B: JOINT SEALING COMPOUND




LONGITUDINAL SAWED CONTRACTION JOINT




LONGITUDINAL OR TRANSVERSE CONSTRUCTION JOINT



TRANSVERSE SAWED CONTRACTION JOINT




TRANSVERSE FORMED EXPANSION JOINT




FORMED ISOLATION JOINT


METHOD A: PREFORMED COMPRESSION SEALS (PCS) (DMS-6310 CLASS 6)




LONGITUDINAL SAWED CONTRACTION JOINT



LONGITUDINAL CONSTRUCTION JOINT



TRANSVERSE SAWED CONTRACTION JOINT



TRANSVERSE FORMED EXPANSION JOINT

GENERAL NOTES


- UNLESS OTHERWISE SHOWN IN THE PLANS, EITHER METHOD "A" OR METHOD "B" MAY BE USED.
- THE LOCATION OF JOINTS SHALL BE AS SHOWN ELSEWHERE IN THE PLANS.
- THE JOINT RESERVOIR FOR SEALANT OR PCS SHALL BE SAWED UNLESS OTHERWISE SHOWN ON THE PLANS FOR THE LONGITUDINAL AND TRANSVERSE CONSTRUCTION JOINTS AND THE SAWED JOINTS.
- DIMENSIONS d1, d2, AND d3 SHOWN IN METHOD A SHALL BE IN ACCORDANCE WITH THE PREFORMED COMPRESSION SEAL MANUFACTURER'S RECOMMENDATION.
- REFER TO DMS-6310 "JOINT SEALANTS AND FILLERS" FOR THE CLASSIFICATIONS.
- FOR SAWED LONGITUDINAL JOINT, LONGITUDINAL OR TRANSVERSE CONSTRUCTION JOINT, USE JOINT SEALANT CLASS 5 OR 8 UNLESS OTHERWISE SHOWN ON THE PLAN OR APPROVED.
- FOR TRANSVERSE SAWED CONTRACTION, TRANSVERSE FORMED EXPANSION JOINT, AND ISOLATION JOINT USE JOINT SEALANT CLASS 5 OR 8 AT NEW JOINTS. USE JOINT SEALANT CLASS 4, 5, 7, OR 8 FOR MAINTAINING EXISTING JOINTS.
- THE JOINTS SHALL BE CLEANED IN ACCORDANCE WITH THE ITEM 438 "CLEANING AND SEALING JOINTS" OR ITEM 713 "CLEANING AND SEALING JOINTS AND CRACKS (CONCRETE PAVEMENT)".
- ISOLATION JOINTS ACCOMMODATE HORIZONTAL AND VERTICAL MOVEMENTS THAT OCCUR BETWEEN A PAVEMENT AND A STRUCTURE. ISOLATION JOINTS MAY BE USED FOR BRIDGE ABUTMENTS, INTERSECTIONS, CURB AND GUTTER, OLD AND NEW PAVEMENTS, OR AROUND DRAINAGE INLETS, MANHOLES, FOOTINGS AND LIGHTING STRUCTURES.

		<b>Design Division Standard</b>	
<b>CONCRETE PAVING DETAILS</b> <b>JOINT SEALS</b> <b>JS-14</b>			
FILE: js14.dgn	DN: TxDOT	DN: HC	CK: AN
© TxDOT: DECEMBER 2014	CONT	SECT	HIGHWAY
REVISIONS	0065 06	070, ETC	US69
DIST	COUNTY		SHEET NO.
BMT	HARDIN		68


DATE: 1/3/2023  
 FILE: T:\BMT\DESIGN\Projects\0665-06-070\_US69\DGN\Standards\repcp14.dgn  
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TABLE NO.1 STEEL BAR SIZE AND SPACING						
TYPE PAVEMENT	SLAB THICKNESS AND BAR SIZE		LONGITUDINAL*		TRANSVERSE*	
			REGULAR BARS	TIEBARS	BARS	TIEBARS
	T (IN.)	BAR SIZE	SPACING (IN.)	SPACING (IN.)	SPACING (IN.)	SPACING (IN.)
CRCP	6.0	#5	7.5	7.5	24	24
	6.5		7.0	7.0		
	7.0		6.5	6.5		
	7.5		6.0	6.0		
	8.0	#6	9.0	9.0	24	24
	8.5		8.5	8.5		
	9.0		8.0	8.0		
	9.5		7.5	7.5		
	10.0		7.0	7.0		
	10.5		6.75	6.75		
11.0	6.5	6.5				
11.5	6.25	6.25				
≥12.0	6.0	6.0				
JRCP	<8.0	#5	24.0	12.0	24	24
	≥8.0	#6	24.0	12.0	24	24
CPCD	<8.0	#5	NONE	12.0	NONE	24
	≥8.0	#6	NONE	12.0	NONE	24

\* USE 12" SPACING AS FIRST AND LAST SPACING AT END OR SIDE FOR ALL BARS.



PLAN VIEW



DETAIL A  
GROUTED TIEBARS & REINFORCEMENT


FULL-DEPTH REPAIR OF CRCP, JRCP, AND CPCD

GENERAL NOTES


- ITEM 361, "REPAIR OF CONCRETE PAVEMENT" SHALL GOVERN FOR THIS WORK.
- MULTIPLE PIECE TIEBARS SHALL BE USED WHEN THE REPAIR AREA MUST BE PLACED IN TWO STAGES DUE TO SEQUENCE OF CONSTRUCTION.
- FULL DEPTH SAW CUTS SHALL BE MADE AROUND THE PERIMETER OF THE AREA TO BE REPAIRED. THE CUT SHALL BE MADE AT A RIGHT ANGLE TO THE PAVEMENT EDGE AND TO THE CENTER LINE OF THE PAVEMENT.
- AT LEAST ONE LONGITUDINAL FULL DEPTH SAW CUT SHALL BE AT AN EXISTING LONGITUDINAL JOINT.
- ADDITIONAL SAW CUTS MAY BE REQUIRED WITHIN THE AREA OF THE REPAIR TO FACILITATE REMOVAL OF THE CONCRETE OR TO ALLEVIATE BINDING OF THE FULL DEPTH SAW CUT AT THE REPAIR EDGE.
- THE SAW CUTS WHICH EXTEND OUTSIDE THE AREA OF THE REPAIR WILL BE CLEANED AND FILLED WITH A CEMENTITIOUS GROUT APPROVED BY THE ENGINEER.
- EXISTING LONGITUDINAL AND TRANSVERSE JOINTS REMOVED DUE TO REPAIR OPERATION SHOULD BE RESTORED IN ACCORDANCE WITH STANDARD SHEET "CONCRETE PAVING DETAILS, JOINT SEALS."

GENERAL NOTES

- ITEM 361, "REPAIR OF CONCRETE PAVEMENT" SHALL GOVERN FOR THIS WORK.
- THE SAW CUTS WHICH EXTEND OUTSIDE THE AREA OF THE REPAIR WILL BE CLEANED AND FILLED WITH A CEMENTITIOUS GROUT APPROVED BY THE ENGINEER.
- EXISTING LONGITUDINAL AND TRANSVERSE JOINTS REMOVED DUE TO REPAIR OPERATION SHOULD BE RESTORED IN ACCORDANCE WITH STANDARD SHEET "CONCRETE PAVING DETAILS, JOINT SEALS."



PLAN VIEW



LONGITUDINAL STEEL BARS:

\*REPAIR AREAS MAY BE ADJUSTED AFTER REMOVING DISTRESSED CONCRETE. SWITCH THE HALF-DEPTH REPAIR TO FULL-DEPTH REPAIR IF EXPOSED EXISTING LONGITUDINAL BARS ARE DEFICIENT, AS APPROVED. COMPENSATION WILL BE MADE FOR UNEXPECTED VOLUMES OF REPAIR AREAS OR CHANGES IN SCOPE OF WORK.

\*INCREASE THE REPAIR AREA AND PERFORM A FULL-DEPTH REPAIR AS DIRECTED IF LONGITUDINAL STEEL BARS WERE DAMAGED BY THE REMOVAL OPERATIONS. NO ADDITIONAL COMPENSATION WILL BE MADE.



SECTION A-A  
HALF-DEPTH REPAIR

SHEET 1 OF 2

				Design Division Standard	
<b>REPAIR OF CONCRETE PAVEMENT</b>					
<b>REPCP-14</b>					
FILE: repcp14.dgn	DN: TxDOT	DN: HC	DW: HC	CK: AN	
© TxDOT: DECEMBER 2014	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0065	06	070, ETC	US69	
	DIST	COUNTY		SHEET NO.	
	BMT	HARDIN		69	

DISCLAIMER:  
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standard\repcp14.dgn



**DETAIL B**  
**GROUTED TIEBARS & DOWELS**

**GENERAL NOTES**

1. ITEM 361, "REPAIR OF CONCRETE PAVEMENT" SHALL GOVERN FOR THIS WORK.
2. MULTIPLE PIECE TIEBARS SHALL BE USED WHEN THE REPAIR AREA MUST BE PLACED IN TWO STAGES DUE TO SEQUENCE OF CONSTRUCTION.
3. FULL DEPTH SAW CUTS SHALL BE MADE AROUND THE PERIMETER OF THE AREA TO BE REPAIRED. THE CUT SHALL BE MADE AT A RIGHT ANGLE TO THE PAVEMENT EDGE AND TO THE CENTER LINE OF THE PAVEMENT.
4. AT LEAST ONE LONGITUDINAL FULL DEPTH SAW CUT SHALL BE AT AN EXISTING LONGITUDINAL JOINT.
5. ADDITIONAL SAW CUTS MAY BE REQUIRED WITHIN THE AREA OF THE REPAIR TO FACILITATE REMOVAL OF THE CONCRETE OR TO ALLEVIATE BINDING OF THE FULL DEPTH SAW CUT AT THE REPAIR EDGE.
6. THE SAW CUTS WHICH EXTEND OUTSIDE THE AREA OF THE REPAIR WILL BE CLEANED AND FILLED WITH A CEMENTITIOUS GROUT APPROVED BY THE ENGINEER.
7. EXISTING LONGITUDINAL AND TRANSVERSE JOINTS REMOVED DUE TO REPAIR OPERATION SHOULD BE RESTORED IN ACCORDANCE WITH STANDARD SHEET "CONCRETE PAVING DETAILS, JOINT SEALS."
8. DOWEL BAR PLACEMENT TOLERANCE SHALL BE +/- 1/4 IN. HORIZONTALLY AND VERTICALLY UNLESS OTHERWISE SPECIFIED. WHERE DOWEL BAR BASKETS ARE USED, REMOVE THE SHIPPING WIRES.

PAVEMENT THICKNESS (INCHES)	SIZE AND DIA.	LENGTH (IN.)	SPACING (IN.)
<10	#8 (1 IN.)	18.0	12.0
≥10	#10 (1 1/4 IN.)		

**REPAIR OF TRANSVERSE JOINT OF CPCD**

SHEET 2 OF 2





**REPAIR OF CONCRETE PAVEMENT**

**REPCP-14**


FILE: repcp14.dgn	DN: TxDOT	DN: HC	DW: HC	CK: AN
© TxDOT: DECEMBER 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
	DIST	COUNTY	SHEET NO.	
	BMT	HARDIN	70	

FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DMN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:01 PM



**LEGEND**

- [A] RE PM W/RET REQ TY I (W) 6" (BRK)
- [B] RE PM W/RET REQ TY I (W) 6" (SLD)
- [C] RE PM W/RET REQ TY I (Y) 6" (SLD)
- [D] PREFAB PAV MRK TY C (W) (ARROW)
- [E] PREFAB PAV MRK TY C (W) (WORD)
- [J] PREFAB PAV MRK TY C (W) (24") (SLD)
- [K] REFL PAV MRK TY I (W) 8" (SLD)
- [M] PREFAB PAV MRK TY C (W) (36") (YLD TRI)
- [N] PREFAB PAV MRK TY C (W) (DBL ARROW)
- [O] PREFAB PAV MRK TY C (W) (UTURN ARROW)
- ← TRAFFIC FLOW



*Jason D. Waldrep, P.E.*

01/03/2023

**US69**

**STRIPING LAYOUT**




SCALE IN FEET  
 © 2022 Texas Department of Transportation

FEDERAL AID PROJECT NO.		SHEET NO.	
		71	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69



SHEET 01 OF 16

FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\VDGN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/31/2023 3:16:04 PM



**LEGEND**

- A RE PM W/RET REQ  
TY I (W) 6" (BRK)
- K REFL PAV MRK  
TY I (W) 8" (SLD)
- TRAFFIC FLOW




*Jason D. Waldrep, P.E.*

01/03/2023

**US69**

**STRIPING LAYOUT**




SCALE IN FEET  
 © 2022 Texas Department of Transportation

SHEET 02 OF 16

FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				72	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		





FILE: T:\BMTDESIGN\Projects\0065-06-070\*US69\DGN\STRIPING LAYOUTS Current Joshua Bailey Edits.DGN  
 DATE: 1/3/2023 3:16:06 PM




**LEGEND**

- [A] RE PM W/RET REQ  
TY I (W) 6" (BRK)
- [K] REFL PAV MRK  
TY I (W) 8" (SLD)
- ← TRAFFIC FLOW



*Jason D. Waldrep, P.E.*  
 01/03/2023


**US69  
 STRIPING LAYOUT**



© 2022 Texas Department of Transportation  
 SHEET 03 OF 16

FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
		73		73	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:09 PM



**LEGEND**


- A RE PM W/RET REQ TY I (W) 6" (BRK)
- D PREFAB PAV MRK TY C (W) (ARROW)
- E PREFAB PAV MRK TY C (W) (WORD)
- H REFL PAV MRK TY II (W) 8" (DOT)
- J PREFAB PAV MRK TY C (W) (24") (SLD)
- K REFL PAV MRK TY I (W) 8" (SLD)
- M PREFAB PAV MRK TY C (W) (36") (YLD TRI)
- N PREFAB PAV MRK TY C (W) (DBL ARROW)
- O PREFAB PAV MRK TY C (W) (TURN ARROW)
- TRAFFIC FLOW



Jason D. Waldrep, P.E.

01/03/2023


**US69 STRIPING LAYOUT**



Texas Department of Transportation SHEET 04 OF 16

FHWA DIVISION	FEDERAL AID PROJECT NO.		SHEET NO.
TEXAS	0665 06 070, ETC		74
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69


FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:12 PM



**LEGEND**

- [A] RE PM W/RET REQ TY I (W) 6" (BRK)
- [D] PREFAB PAV MRK TY C (W) (ARROW)
- [J] PREFAB PAV MRK TY C (W) (24") (SLD)
- [K] REFL PAV MRK TY I (W) 8" (SLD)
- [N] PREFAB PAV MRK TY C (W) (DBL ARROW)

← TRAFFIC FLOW



Jason D. Waldrep, P.E.

01/03/2023

**US69 STRIPING LAYOUT**



0 50 100  
SCALE IN FEET

© 2022 Texas Department of Transportation

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		75
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

SHEET 05 OF 16

FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:14 PM



**LEGEND**


- A RE PM W/RET REQ TY I (W) 6" (BRK)
- B RE PM W/RET REQ TY I (Y) 6" (SLD)
- C PREFAB PAV MRK TY C (W) (ARROW)
- D PREFAB PAV MRK TY C (W) (WORD)
- E PREFAB PAV MRK TY C (W) (WORD)
- H REFL PAV MRK TY II (W) 8" (DOT)
- J PREFAB PAV MRK TY C (W) (24") (SLD)
- K REFL PAV MRK TY I (W) 8" (SLD)
- M PREFAB PAV MRK TY C (W) (36") (YLD TRI)
- N PREFAB PAV MRK TY C (W) (DBL ARROW)
- O PREFAB PAV MRK TY C (W) (TURN ARROW)
- TRAFFIC FLOW

**US69**

**STRIPING LAYOUT**



SCALE IN FEET





*Jason D. Waldrep, P.E.*

01/03/2023

FEDERAL AID PROJECT NO.		SHEET NO.	
		76	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

SHEET 06 OF 16

FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:17 PM



**LEGEND**

- [A] RE PM W/RET REQ TY I (W) 6" (BRK)
- [B] RE PM W/RET REQ TY I (W) 6" (SLD)
- [D] PREFAB PAV MRK TY C (W) (ARROW)
- [E] PREFAB PAV MRK TY C (W) (WORD)
- [H] REFL PAV MRK TY II (W) 8" (DOT)
- [I] PREFAB PAV MRK TY C (W) (12") (SLD)
- [J] PREFAB PAV MRK TY C (W) (24") (SLD)
- [K] REFL PAV MRK TY I (W) 8" (SLD)
- [M] PREFAB PAV MRK TY C (W) (36") (YLD TRI)
- [N] PREFAB PAV MRK TY C (W) (DBL ARROW)
- [O] PREFAB PAV MRK TY C (W) (TURN ARROW)
- ← TRAFFIC FLOW


**US69**

**STRIPING LAYOUT**



SCALE IN FEET  
 Texas Department of Transportation

SHEET 07 OF 16




*Jason D. Waldrep, P.E.*

01/03/2023

FHWA DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
TEXAS		77
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69


FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:20 PM



**LEGEND**

- A RE PM W/RET REQ TY I (W) 6" (BRK)
- B RE PM W/RET REQ TY I (W) 6" (SLD)
- C RE PM W/RET REQ TY I (Y) 6" (SLD)
- D PREFAB PAV MRK TY C (W) (ARROW)
- E PREFAB PAV MRK TY C (W) (WORD)
- L PREFAB PAV MRK TY C (W) (24") (SLD)
- K REFL PAV MRK TY I (W) 8" (SLD)
- Q PREFAB PAV MRK TY C (Y) (24") (SLD)
- O PREFAB PAV MRK TY C (W) (TURN ARROW)

← TRAFFIC FLOW



Jason D. Waldrep, P.E.

01/03/2023

**US69 STRIPING LAYOUT**



0 50 100  
SCALE IN FEET

© 2022 Texas Department of Transportation

SHEET 08 OF 16


FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		78
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

FILE: T:\BMTDESIGN\Projects\0065-06-070\US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:23 PM



LEGEND

- [A] RE PM W/RET REQ  
 TY I (W) 6" (BRK)
- [B] RE PM W/RET REQ  
 TY I (W) 6" (SLD)
- ← TRAFFIC FLOW



*Jason D. Waldrep, P.E.*

01/03/2023

**US69**

**STRIPING LAYOUT**




SCALE IN FEET  
 © 2022 Texas Department of Transportation

SHEET 09 OF 16



FHWA TEXAS DIVISION		FEDERAL AID PROJECT NO.		SHEET NO.	
				79	
STATE	DISTRICT	COUNTY			
TEXAS	BMT	HARDIN			
CONTROL	SECTION	JOB	HIGHWAY NO.		
0065	06	070, ETC	US69		

FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\VDGN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:26 PM



**LEGEND**


- [A] RE PM W/RET REQ TY I(W)6" (BRK)
- [B] RE PM W/RET REQ TY I(W)6" (SLD)
- [C] RE PM W/RET REQ TY I(Y)6" (SLD)
- [F] REFL PAV MRKR TY II-C-R
- [K] REFL PAV MRK TY I(W)8" (SLD)
- ← TRAFFIC FLOW



*Jason D. Waldrep, P.E.*

01/03/2023

**US69**  
**STRIPING LAYOUT**



© 2022 Texas Department of Transportation

FEDERAL AID PROJECT NO.		SHEET NO.	
		80	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

SHEET 1 OF 16





FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:28 PM



**LEGEND**

- [A] RE PM W/RET REQ TY I(W)6" (BRK)
  - [B] RE PM W/RET REQ TY I(W)6" (SLD)
  - [C] RE PM W/RET REQ TY I(Y)6" (SLD)
  - [F] REFL PAV MRKR TY II-C-R
  - [K] REFL PAV MRK TY I(W)8" (SLD)
- ← TRAFFIC FLOW



*Jason D. Waldrep, P.E.*

01/03/2023

**US69 STRIPING LAYOUT**




SCALE IN FEET

© 2022 Texas Department of Transportation SHEET 11 OF 16

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		81
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69


FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DN\STRIPING LAYOUTS Current Joshua Bailey Edits.DGN  
 DATE: 1/3/2023 3:16:31 PM



- LEGEND**
- [A] RE PM W/RET REQ TY I(W)6" (BRK)
  - [B] RE PM W/RET REQ TY I(W)6" (SLD)
  - [C] RE PM W/RET REQ TY I(Y)6" (SLD)
  - [F] REFL PAV MRKR TY II-C-R
  - [K] REFL PAV MRK TY I(W)8" (SLD)
  - [P] PREFAB PAV MRK TY C(W) (6") (SLD)
  - [Q] PREFAB PAV MRK TY C(W) (6") (BRK)
  - [T] PREFAB PAV MRK TY C (Y) (6") (SLD)
- ← TRAFFIC FLOW



**US69 STRIPING LAYOUT**



© 2022 Texas Department of Transportation SHEET 12 OF 16


FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		82
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

*Jason D. Waldrep, P.E.*

01/03/2023



FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:34 PM




**LEGEND**

- A RE PM W/RET REQ TY I(W)6" (BRK)
- B RE PM W/RET REQ TY I(W)6" (SLD)
- C RE PM W/RET REQ TY I(Y)6" (SLD)
- D PREFAB PAV MRK TY C(W) (ARROW)
- E PREFAB PAV MRK TY C(W) (WORD)
- F REFL PAV MRKR TY II-C-R
- P REFL PAV MRK TY II(W) 12" (DOT)
- Q REFL PAV MRK TY I(W)12" (LNDP)
- K REFL PAV MRK TY I(W)8" (SLD)

← TRAFFIC FLOW

**US69**

**STRIPING LAYOUT**



*Jason D. Waldrep, P.E.*


01/03/2023

© 2022 Texas Department of Transportation

SHEET 13 OF 16

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		83
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

FILE: T:\BMTDESIGN\Projects\0665-06-070\US69\DM\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:37 PM



**LEGEND**

- [A] RE PM W/RET REQ TY I(W)6" (BRK)
- [B] RE PM W/RET REQ TY I(W)6" (SLD)
- [C] RE PM W/RET REQ TY I(Y)6" (SLD)
- [F] REFL PAV MRKR TY II-C-R
- [K] REFL PAV MRK TY I(W)8" (SLD)

← TRAFFIC FLOW

**US69 STRIPING LAYOUT**

0 50 100  
SCALE IN FEET

© 2022 Texas Department of Transportation


SHEET 14 OF 16

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		84
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69

Jason D. Waldrep, P.E.

01/03/2023


FILE: T:\BMTDESIGN\Projects\0665-06-070\*US69\DGN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:40 PM



**LEGEND**

- A RE PM W/RET REQ TY I(W)6" (BRK)
- B RE PM W/RET REQ TY I(W)6" (SLD)
- C RE PM W/RET REQ TY I(Y)6" (SLD)
- D PREFAB PAV MRK TY C(W) (ARROW)
- E PREFAB PAV MRK TY C(W) (WORD)
- F REFL PAV MRKR TY II-C-R
- P REFL PAV MRK TY II(W) 12" (DOT)
- Q REFL PAV MRK TY I(W)12" (LNDP)
- K REFL PAV MRK TY I(W)8" (SLD)

← TRAFFIC FLOW



Jason D. Waldrep, P.E.

01/03/2023

US69

**STRIPING LAYOUT**




SCALE IN FEET  
 © 2022 Texas Department of Transportation

SHEET 15 OF 16

FHWA TEXAS DIVISION	FEDERAL AID PROJECT NO.	SHEET NO.
		85
STATE	DISTRICT	COUNTY
TEXAS	BMT	HARDIN
CONTROL	SECTION	JOB HIGHWAY NO.
0065	06	070, ETC US69


FILE: T:\BMTDESIGN\Projects\065-06-070\US69\DN\STRIPING LAYOUTS Current Joshua Bailey Edits.dgn  
 DATE: 1/3/2023 3:16:43 PM



**LEGEND**


- A RE PM W/RET REQ TY I(W)6" (BRK)
- B RE PM W/RET REQ TY I(W)6" (SLD)
- C RE PM W/RET REQ TY I(Y)6" (SLD)
- D PREFAB PAV MRK TY C(W) (ARROW)
- E PREFAB PAV MRK TY C(W) (WORD)
- F REFL PAV MRKR TY II-C-R
- P REFL PAV MRK TY II(W) 12" (DOT)
- Q REFL PAV MRK TY I(W)12" (LNDP)

← TRAFFIC FLOW



Jason D. Waldrep, P.E.  
 01/03/2023

**US69**  
**STRIPING LAYOUT**




© 2022 Texas Department of Transportation


FEDERAL AID PROJECT NO.		SHEET NO.	
		86	
STATE	DISTRICT	COUNTY	
TEXAS	BMT	HARDIN	
CONTROL	SECTION	JOB	HIGHWAY NO.
0065	06	070, ETC	US69

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/3/2023 3:16:46 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standards\dms\pm1-22.dgn




**EDGE LINE AND LANE LINES  
ONE-WAY ROADWAY  
WITH OR WITHOUT SHOULDERS**



**TYPICAL TWO-LANE, TWO-WAY PAVEMENT  
MARKINGS THROUGH INTERSECTIONS**




**CENTERLINE AND LANE LINES  
FOUR LANE TWO-WAY ROADWAY  
WITH OR WITHOUT SHOULDERS**




**DETAIL "A"**  
 9" min. - 10" typ.  
 (18" max. for traveled way greater than 48' only)


\* 2" minimum for restripe projects when approved by the Engineer.  
 \*\* 8" minimum for restripe projects when approved by the Engineer.



**TYPICAL MULTI-LANE, TWO-WAY PAVEMENT  
MARKINGS THROUGH INTERSECTIONS**




**TWO LANE TWO-WAY ROADWAY  
WITH OR WITHOUT SHOULDERS**




**DETAIL "B"**

\* 2" minimum for restripe projects when approved by the Engineer.



**YIELD LINES**

For posted speed on road being marked equal to or greater than 45 MPH.




For posted speed on road being marked equal to or less than 40 MPH.

**GENERAL NOTES**

- Edge line striping shall be as shown in the plans or as directed by the Engineer. The edge line should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement raveling or other conditions. Edge lines are not required in curb and gutter sections of roadways.
- The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the center of edge line to the center of edge line of a two lane roadway.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




NOTE: Traveled way is exclusive of shoulder widths. Refer to General Note 2 for additional details.

**GUIDE FOR PLACEMENT OF STOP LINES,  
EDGE LINE & CENTERLINE**  
 Based on Traveled Way and Pavement Widths for Undivided Roadways

**NOTES**

- Where divided highways are separated by median widths at the median opening itself of 30 feet or more, median openings shall be signed as two separate intersections. Each median opening has two width measurements, with one measurement for each approach. The narrow median width will be the controlling width to determine if signs are required. Yield signs are the typical intersection control. Stop signs and stop bars are optional as determined by the Engineer.
- Install median striping (double yellow centerlines and stop lines/yield lines) when a 50' or greater median centerline can be placed. Stop lines shall only be used with stop signs. Yield lines shall only be used with yield signs.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.



**FOUR LANE DIVIDED ROADWAY CROSSOVERS**

**TYPICAL STANDARD  
PAVEMENT MARKINGS**


**PM(1) - 22**

FILE:	pm1-22.dgn	DN:	CK:	DW:	CK:
© TxDOT	December 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69	
11-78	8-00	6-20			
8-95	3-03	12-22			
5-00	2-12				
DIST	COUNTY	SHEET NO.			
BMT	HARDIN	87			


# REFLECTIVE RAISED PAVEMENT MARKERS FOR VEHICLE POSITIONING GUIDANCE

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/3/2023 3:16:48 PM  
 FILE: T:\BMTDESIGN\Projects\0065-06-070\_US69\DM\Standard.dwg\pm2-22.dgn



**CENTERLINE FOR ALL TWO LANE TWO-WAY ROADWAYS**




**CENTERLINE & LANE LINES  
FOR FOUR LANE TWO-WAY ROADWAYS**




**DETAIL "A"**

**DETAIL "B"**

**DETAIL "C"**




**CENTERLINE AND LANE LINES FOR TWO-WAY LEFT TURN LANE**



**LANE LINES FOR ONE-WAY ROADWAY (NON-FREEWAY FACILITIES)**

Raised pavement markers Type II-C-R shall have clear face toward normal traffic and red face toward wrong-way traffic.  
 See Note 3.



**REFLECTORIZED PROFILE  
PATTERN DETAIL**

USING REFLECTIVE PROFILE PAVEMENT MARKINGS

6" EDGE LINE, 6" CENTERLINE  
OR 6" LANE LINE

**NOTES**


1. Edge lines should typically be 6" wide and the materials shall be specified in the plans.
2. Profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.

**GENERAL NOTES**


1. All raised pavement markers placed along broken lines shall be placed in line with and midway between the stripes.
2. On concrete pavements the raised pavement markers should be placed to one side of the longitudinal joints.
3. Use raised pavement marker Type I-C with undivided roadways, flush medians and two way left turn lanes. Use raised pavement marker Type II-C-R with divided highways and raised medians.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**Type I (Top View)**



**Type II (Top View)**



**SECTION A**

**RAISED PAVEMENT MARKERS**




**POSITION GUIDANCE USING  
RAISED MARKERS  
REFLECTORIZED PROFILE  
MARKINGS  
PM(2) - 22**

FILE: pm2-22.dgn	DN:	CK:	DW:	CK:
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
4-77 8-00 6-20	DIST	COUNTY	SHEET NO.	
4-92 2-10 12-22	BMT	HARDIN	88	
5-00 2-12				




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:16:50 PM  
 FILE: T:\BMTDESIGN\Projects\0065-06-070\_US69\DMG\Standards\Fpm(1)-22.dgn



**NOTE**  
 ReflectORIZED raised pavement markers Type II-C-R shall be spaced on 80' centers with the clear face toward normal traffic and the red face toward wrong way traffic. All raised pavement markers placed along broken lines shall be placed in line with and midway between the stripes.

**TRAFFIC LANE LINES PAVEMENT MARKING**




**TYPICAL ENTRANCE RAMP GORE MARKING**

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.


LEGEND	
	Traffic flow
	Pavement marking arrows (white)
	ReflectORIZED Raised Markers (RPM) Type II-C-R

**GENERAL NOTE**  
 On concrete pavements the raised pavement markers shall be placed to one side of the longitudinal joints.




**NOTE**  
 Edge lines should typically be 6" wide and the materials shall be as specified in the plans. See details above if reflective profile pavement markings are to be used.

**EDGE LINE PAVEMENT MARKINGS**




**NOTE**  
 See the Roadway Design Manual Chapter 3 to determine if a tapered acceleration lane may be used.

**TAPERED ACCELERATION LANE**




Type II (Top View)




SECTION A

**REFLECTORIZED RAISED PAVEMENT MARKER (RPM)**



**NOTES**  
 1. ReflectORIZED raised pavement markers Type-II-C-R in the wrong way arrow shall have the clear face toward normal traffic and the red face toward the wrong way traffic.  
 2. Red reflectORIZED wrong way arrows, not to exceed two, may be placed on exit ramps. Locations of the arrows shall be as shown in the plans or as directed by the engineer.

**WRONG WAY ARROW**



**NOTE**  
 See the Roadway Design Manual Chapter 3 to determine lengths of the acceleration lane and taper.

**PARALLEL ACCELERATION LANE**


Texas Department of Transportation  
 Traffic Safety Division Standard

**TYPICAL STANDARD FREEWAY PAVEMENT MARKINGS WITH RAISED PAVEMENT MARKERS FPM(1)-22**

FILE: fpm(1)-22.dgn	DN:	CK:	DW:	CK:
©TxDOT October 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
5-74 8-00 2-12	DIST	COUNTY	SHEET NO.	
4-92 2-08 10-22	BMT	HARDIN	89	
5-00 2-10				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/3/2023 3:16:53 PM  
 FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DGN\Standards\Fpm(2)-22.dgn




**SINGLE LANE EXIT WITH AUXILIARY LANE**

(See Note 2)




**TAPERED DECELERATION LANE**

**NOTE**  
 Reference Roadway Design Manual Chapter 3 to determine if tapered deceleration lane may be used.




**PARALLEL DECELERATION LANE**


**NOTE**  
 Reference Roadway Design Manual Chapter 3 to determine length of deceleration lane and taper.




**DETAIL A**



**DETAIL B**



**DETAIL C**



**DETAIL D**

**GENERAL NOTES**

1. Pavement markings shall be white except as otherwise noted.
2. Length of 12" white line may vary depending on location.
3. Wide (12") dotted lane line (see Detail B) is used to separate a through lane that continues beyond the interchange from an adjacent mandatory exit lane.
4. Normal (6") dotted lane line (see Detail C) is used at parallel acceleration and deceleration lanes.
5. See FPM(1) for traffic lane line pavement marking details.

**LEGEND**

	Traffic flow
	Pavement marking arrows (white)
	Reflectorized Raised Markers (RPM) Type II-C-R
	Arrow markings are optional, however "ONLY" is required if arrow is used

**MATERIAL SPECIFICATIONS**

PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**TYPICAL STANDARD FREEWAY PAVEMENT MARKINGS ENTRANCE AND EXIT RAMP**

**FPM(2) - 22**

FILE: fpm(2)-22.dgn	DN:	CK:	DW:	CK:
©TxDOT October 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0065	06	070, ETC	US69
2-77 5-00 2-12	DIST	COUNTY	SHEET NO.	
4-92 8-00 10-22	BMT	HARDIN	90	
8-95 2-10				




**SINGLE LANE EXIT - LANE DROP OR EXIT ONLY**

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.

LEGEND	
	Traffic flow
	Pavement marking arrows (white)
	ReflectORIZED Raised Markers (RPM) Type II-C-R
	Arrow markings are optional, however "ONLY" is required if arrow is used





**SINGLE LANE EXIT - LANE DROP OR EXIT ONLY (LEFT SIDE)**

**GENERAL NOTES**

1. Pavement markings shall be white except as otherwise noted.
2. Length of 12" white line may vary depending on location.
3. Wide (12") dotted lane line (see FPM(2) Detail B) is used to separate a through lane that continues beyond the interchange from an adjacent mandatory exit lane.
4. Edge lines are not required in curb and gutter sections of frontage roads.
5. See FPM(1) for traffic lane line pavement marking details.

**NOTES**

1. Large Guide signs shall conform to the TxDOT Freeway Signing Handbook.
2. An optional third lane reduction arrow may be added based on engineering judgement. If used, the optional third lane reduction arrow should be centered between the first and last lane reduction arrows.
3. Arrows and sign details can be found in the Standard Highway Sign Designs for Texas (SHSD) at <http://www.txdot.gov>.
4. These guidelines may also be applied to the design of a right side lane reduction. Use LANE ENDS MERGE LEFT (W9-5TL) and RIGHT LANE ENDS 1/2 MILE (W9-4TR) signs in lieu of what is shown on drawing.



**FREEWAY LANE REDUCTION**

ADVANCED WARNING SIGN DISTANCE (D)		
Posted Speed	D (ft)	L (ft)
45 MPH	775	L=WS
50 MPH	885	
55 MPH	990	
60 MPH	1,100	
65 MPH	1,200	
70 MPH	1,250	
75 MPH	1,350	
80 MPH	1,500	
85 MPH	1,625	



**TYPICAL STANDARD FREEWAY PAVEMENT MARKINGS SINGLE LANE DROP (EXIT ONLY) AND LANE REDUCTION DETAILS FPM(3) - 22**

FILE: fpm(3)-22.dgn	DW: DW	CK: CK	CK: CK
© TxDOT October 2022	CONT	SECT	JOB
REVISIONS	0065	06	070, ETC
4-92 2-10	DIST	COUNTY	SHEET NO.
5-00 2-12	BMT	HARDIN	91
8-00 10-22			

DATE: 1/3/2023 3:16:54 PM FILE: T:\BMT\DESIGN\Projects\0065-06-070\_US69\DN\Standards\Fpm(3)-22.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES \$TIME\$  
FILE: \$FILES

**I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402**

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

- 1. TxDOT - Beaumont District
  - 2. Cities of Rose Hill Acrows and Beaumont, Texas
- No Action Required     Required Action

Action No.

- 1. Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000
- 2. Comply with the SW3P and revise when necessary to control pollution or as required by the Engineer.
- 3. The project is estimated to involve less than one acre of soil disturbance. In the event the project disturbance acreage becomes equal to or greater than one acre, the CGP is applicable. Contact TxDOT project inspector for coordination with DEQC for necessary action.
- 4. Take measures to prevent construction materials and debris including, but not limited to wastewater (i.e., cooling liquid, etc.) associated with concrete removal from entering any inlets, ditches, or waterways.

**II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404**

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions, including Regional conditions for the State of Texas, associated with the following permit(s):

- No Permit Required
- Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
- Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
- Individual 404 Permit Required: Permit # \_\_\_\_\_
- Other Nationwide Permit Required: NWP# \_\_\_\_\_

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

- 1. Maintain a neat and clean worksite next to the water and do not allow any debris to fall into the water.
- 2. Comply with "Work In or Near Waters/Wetlands Regulatory Requirements and Best Management Practices" section found in the Beaumont District Environmental Field Guide.

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

Best Management Practices:

<b>Erosion</b>	<b>Sedimentation</b>	<b>Post-Construction TSS</b>
<input type="checkbox"/> Temporary Vegetation	<input type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	

**III. CULTURAL RESOURCES**

- No Action Required
- Required Action

Action No.

- 1. Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

**IV. VEGETATION RESOURCES**

- No Action Required
- Required Action

Action No.

- 1. No vegetation removal or trimming of any kind is allowed. Exceptions are allowed for mowed and maintained grass.

**V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.**

- No Action Required
- Required Action

Action No.

- 1. If any animal enters the work area, do not harm, harass, or attempt to handle; let the animal leave on its own.
- 2. If caves or sinkholes are discovered on site, cease work in the area and contact the TxDOT Inspector or DEQC for guidance.
- 3. Comply with "Wildlife: Regulatory Requirements and Best Management Practices" section found in the Beaumont District Environmental Field Guide.
- 4. Contractor shall maintain compliance with the Migratory Bird Treaty Act (MBTA) and Texas Parks and Wildlife (TPW) Code Section 64.002. The full MBTA guidance may be found here: <https://ftp.dot.state.tx.us/pub/txdot-info/env/toolkit/350-1-gui.pdf>
- 5. Resource specific BMPs (section I) and Pavement BMPs (Section II, F) from the 'Updated Best Management Practices (BMPs) for TxDOT Maintenance Program EA shall be reviewed and implemented where appropriate. The maintenance EA BMPs may be found here: <https://ftp.txdot.gov/pub/txdot-info/env/080-01-bmp.pdf>

**LIST OF ABBREVIATIONS**

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SW3P: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NWP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

**VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES**

- No Action Required
- Required Action

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used. Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act.

Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- \* Dead or distressed vegetation (not identified as normal)
- \* Trash piles, drums, canister, barrels, etc.
- \* Undesirable smells or odors
- \* Evidence of leaching or seepage of substances
- \* Any other evidence indicating possible hazardous materials or contamination discovered on site.

List below any bridge class structure(s), not including box culverts, being replaced, rehabilitated, removed, extended or modified as part of this project, or state "None", if applicable.

If "None", then no further action is required. Otherwise TxDOT is responsible for completing asbestos assessment/inspection and evaluation for presence of lead.

Provide results below:

Structure Location	PSN	Element	Lead
None			

If Asbestos is present, then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary.

If Asbestos is not present, then TxDOT is still required to notify DSHS prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Hazardous Materials or Contamination Issues Specific to this Project:

Action No.

- 1. Comply with TxDOT Standard Specification 7.12 and Special Provision 006-012 if evidence of hazardous materials or contamination is noted during construction.
- 2. Notify TxDOT Inspector or DEQC of any hazardous materials spills including fuel, hydraulic fluid, etc.


**VII. OTHER ENVIRONMENTAL ISSUES**


(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required
- Required Action

Action No.

- 1. Comply with "General Construction" section found in the Beaumont District Environmental Field Guide.

		<b>Beaumont District Standard</b>
<h2>ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS</h2> <h3>EPIC</h3>		
FILE: epic.dgn	DN: TxDOT	CK: AM DW: VP CK: AR
©TxDOT February 2019	CONT SECT	JOB HIGHWAY
	0065 06	070, ETC US 69, ETC
	DIST COUNTY	SHEET NO.
	BMT HARDIN, ETC	92


12/01/2022  
 APPROVED BY DATE

DISTRICT ENVIRONMENTAL DEPARTMENT