

100% SUBMITTAL

STATE OF TEXAS

DEPARTMENT OF TRANSPORTATION

PLANS OF PROPOSED STATE HIGHWAY IMPROVEMENT

FEDERAL AID PROJECT: BR 2022 (355)

HAMILTON COUNTY
CR

AT HONEY CREEK (MAP #212)

FOR THE CONSTRUCTION OF BRIDGE REPLACEMENT
CONSISTING OF REPLACE BRIDGE AND APPROACHES

ROADWAY: FT: 390.00	MI. = 0.073
BRIDGE: FT: 140.00	MI. = 0.026
TOTAL: FT: 530.00	MI. = 0.099


DESIGN	ERF	FED. RD. DIST. NO.	6	FEDERAL AID PROJECT NO.	BR 2022 (355)	SHEET NO.	1
GRAPHICS	ERF	STATE	TEXAS	STATE DIST.	WACO	COUNTY	HAMILTON
CHECKED	JMS	CONT.	0909	SECT.	29	JOB	046
CHECKED	FG	HIGHWAY NO.					CR

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	INDEX OF SHEETS

DESIGN SPEED = MEETS OR IMPROVES EXISTING CONDITIONS

ADT	YEAR
66	2020
92	2041



BEGIN PROJECT
CSJ: 0909-29-046
@ CR238 (HCR 207)
STA 402+00.00

END PROJECT
CSJ: 0909-29-046
@ CR238 (HCR 207)
STA 407+30.00

EXCEPTIONS: NONE
EQUATIONS: NONE
RAILROAD CROSSINGS: NONE

CONCURRENCE 2/13/2023
James Gates
COUNTY JUDGE

SUBMITTED FOR LETTING 2/13/2023
Amulo Datta
PROJECT MANAGER
AMERICAN STRUCTUREPOINT, INC.



RECOMMENDED FOR LETTING 2/13/2023
Michael H Gates
AREA ENGINEER


RECOMMENDED FOR LETTING 2/21/2023
DocuSigned by:
Victoria Stahl, P.E.
9AD8C743F95E4E3
DIRECTOR OF TRANSPORTATION PLANNING & DEVELOPMENT


APPROVED FOR LETTING 2/21/2023
DocuSigned by:
Stanley Swiatek
8E9B0796D0564C9
DISTRICT ENGINEER


SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL-AID CONSTRUCTION CONTRACTS (FORM FHWA 1273, July 2022).

SHEET NO.	DESCRIPTION
GENERAL	
1	TITLE SHEET
2	INDEX OF SHEETS
3	TYPICAL SECTIONS
4, 4A-4E	GENERAL NOTES
5, 5A	ESTIMATE & QUANTITIES
6	SUMMARY OF QUANTITIES
TRAFFIC CONTROL	
7	SEQUENCE OF CONSTRUCTION
TRAFFIC CONTROL STANDARDS	
8 - 19	* BC(1)-21 THRU BC(12)-21
20	* WZ(RCD)-13
ROADWAY	
21	SURVEY CONTROL INDEX SHEET
22 - 23	PRIMARY HORIZONTAL AND VERTICAL CONTROL
24	HORIZONTAL ALIGNMENT DATA
25	PLAN AND PROFILE
ROADWAY STANDARDS	
26	* BED-14
27	* GF(31)-19
28	* GF(31)TRTL2-19
29	* GF(31)DAT-19
30	* SGT(11S)31-18
31	* SGT(12S)31-18
32	* SGT(15)31-20
33	* D&OM(1)-20
34	* D&OM(2)-20
35	* D&OM(3)-20
36	* D&OM(5)-20
37	* D&OM(VIA)-20
38	* WF(2)-10
DRAINAGE	
39	DRAINAGE AREA MAP
40	HYDRAULIC DATA SHEET
41	OMIT
BRIDGE	
42 - 43	BRIDGE LAYOUT
44	SOIL BORING LOGS
45	ESTIMATED QUANTITIES & BEARING SEAT ELEVATIONS
BRIDGE STANDARDS	
46 - 48	*** AIG-24-15
49	*** BIG-24-15
50 - 51	*** SIG-24-15
52	*** AJ
53 - 54	*** CSAB
55 - 56	*** FD
57	*** IGCS
58 - 59	*** IGD
60 - 62	*** IGEB
63 - 64	*** IGMS
65 - 66	*** IGSD-24
67	*** IGSK
68	*** IGTS
69 - 70	*** MEBR(C)
71 - 74	*** PCP
75	*** PCP-FAB
76 - 77	*** PMDF
78 - 79	*** SRR
80 - 81	*** TYPE SSTR

SHEET NO.	DESCRIPTION
ENVIRONMENTAL	
82 - 83	STORM WATER POLLUTION PREVENTION PLAN (SWP3)
84	EPIC
85	SWP3 LAYOUT
ENVIRONMENTAL STANDARDS	
86	** EC(1)-16
87	** EC(2)-16
88 - 97	** TA-BMP (WACO DISTRICT STANDARD)


Jose M. Sandoval
 2/21/2023
 AMERICAN STRUCTUREPOINT, INC.
 TBPE FIRM NO. F-10069
 THE STANDARD SHEETS IDENTIFIED WITH (*) HAVE BEEN SELECTED UNDER MY RESPONSIBLE SUPERVISION AS APPLICABLE TO THIS PROJECT.



Fernando Gaytan
 2/21/2023
 AMERICAN STRUCTUREPOINT, INC.
 TBPE FIRM NO. F-10069
 THE STANDARD SHEETS IDENTIFIED WITH (**) HAVE BEEN SELECTED UNDER MY RESPONSIBLE SUPERVISION AS APPLICABLE TO THIS PROJECT.


Emily Wason Berver
 2/21/2023
 HARDESTY & HANOVER, LLC
 TBPE FIRM NO. F-3379
 THE STANDARD SHEETS IDENTIFIED WITH (***) HAVE BEEN SELECTED UNDER MY RESPONSIBLE SUPERVISION AS APPLICABLE TO THIS PROJECT.

3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com


AMERICAN STRUCTUREPOINT
INC.

TBPE FIRM NO. F-10069



Texas Department of Transportation ©2023

CR 238 (HCR 207) AT HONEY CREEK
INDEX OF SHEETS


FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	2




EXISTING TYPICAL SECTION
STA 402+00.00 TO STA 407+30.00




PROPOSED TYPICAL SECTION
STA 402+00.00 TO STA 403+40.67
STA 405+24.23 TO STA 407+30.00



PROPOSED TYPICAL SECTION
STA 403+40.67 TO STA 403+64.00
STA 405+04.00 TO STA 405+24.23



DETAIL "B"



DETAIL "A"

PRINT DATE	REVISION DATE
2/8/2023	



Jose M. Sandoval
JOSE M. SANDOVAL
DATE

2/8/2023
DATE

STRUCTUREPOINT INC.
3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com
TBPE FIRM NO. F-10069



**CR 238 (HCR 207) AT HONEY CREEK
TYPICAL SECTIONS**

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	3

BASIS OF ESTIMATE TABLES

Table 1: Basis of Estimate for Erosion Control Items				
Item	Description	Rate	Basis	Quantities
*166	FERTILIZER			
	FERTILIZER (20-10-10) (PERMANENT)	300 LBS / AC	0.28 AC	0.05 TON
	FERTILIZER (20-10-10) (TEMPORARY)	300 LBS / AC	0.28 AC	0.05 TON
168	VEGETATIVE WATERING			
	(3 APPLICATIONS - PERM)	13,100 GAL/AC/APP	0.28 AC	11.5 MG
	(3 APPLICATIONS - TEMP)	13,100 GAL/AC/APP	0.28 AC	11.5 MG

* FOR Contractor'S INFORMATION ONLY

Table 3: Basis of Estimate for Base Work				
Item	Description	Rate	Basis	Quantities
247	FLEXIBLE BASE			
	(TY D GR 1-2 FNAL POS)	138 LB/CF	5,238 CF	194 CY 361 *TON

* FOR Contractor'S INFORMATION ONLY

GENERAL

The construction, operation and maintenance of the proposed project will be consistent with the state implementation plan as prepared by the Texas Commission on Environmental Quality.

The disturbed area for this project, as shown on the plans is 0.28 acres. However, the Total Disturbed Area (TDA) will establish the required authorization for storm water discharges. The TDA of this project will be determined by the sum of the disturbed area in all project locations in the contract, and all disturbed area on all Project-Specific Locations (PSL) located in the project limits and/or within 1 mile of the project limits. The department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction site as shown on the plans, according to the TDA of the project. The Contractor will obtain any required authorization from the TCEQ for the discharge of storm water from any PSL for construction support activities on or off of the project row according to the TDA of the project. When the TDA for the project exceeds 1 acre, provide a copy of the appropriate application of permit (NOI, or Construction Site Notice) to the Engineer, for any PSL located in the project limits or within 1 mile of the project limits. Follow the directives and adhere to all requirements set forth in the TCEQ, Texas Pollution Discharge Elimination System, Construction General Permit (TPDES, CGP).

Contractor questions on this project are to be emailed to the Waco District at the following address:

Bill Compton - Wacoprebid@txdot.gov, 254-867-2770, 100 S. Loop Dr., Waco, TX
Carmen Chau - Wacoprebid@txdot.gov, 254-867-2794, 100 S. Loop Dr., Waco, TX

Or Via phone or in person to the following individual(s):
Area Engineer's: Phone: Michael Yates, P.E. (254) 865-7115
Assistant Area Engineer's: Phone: Mohab Samuel, P.E. (254) 865-7115

Contractor questions will be accepted through email, phone, and in person by the above individuals. Questions may also be submitted via the Letting Pre-Bid Q&A web page. This webpage can be accessed from the Notice to Contractors dashboard located at the following Address:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>

All contractor questions will be reviewed by the Engineer. All questions and any corresponding responses that are generated will be posted through the same Letting Pre-Bid Q&A web page.

The Letting Pre-Bid Q&A web page for each project can be accessed by using the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink for the project you want to view the Q&A for and click on the link in the window that pops up.

Paper copies of cross-sections may be produced by using the provided .pdf file located on the above FTP Website at the bidders' expense and at copying companies. This data is for non-construction purposes only and it is the responsibility of the prospective bidder to validate the enclosed data with appropriate plans, specifications and estimate for the project(s).

GENERAL NOTES**ITEM 5: CONTROL OF THE WORK**

Provide the Engineer with a weekly work schedule of planned activities including anticipated quantities of materials to be placed daily (CY of each concrete placement, tons of HMAC to be placed daily, etc.). Schedules will be provided for the following week as part of each week's project meetings or by 5PM on Thursday as approved by the Engineer. Failure to provide notifications are required here may be deemed as insufficient notice per item 5.10.

Provide the Engineer Daily by 3PM the planned activities for the following day including location, quantities of materials to be placed, etc. in a format acceptable to the Engineer.

Submit all fabrication and shop drawings per TxDOT's online shop drawing submittal system and copy the Area Engineer on the email submittal, unless otherwise directed.

Where a precast or cast-in-place concrete element is shown in the plans, Contractor may submit a precast concrete alternate in accordance with "Standard Operating Procedure for Alternate Precast Proposal Submission" found online at:

<https://www.txdot.gov/inside-txdot/forms-publications/consultants-Contractors/publications/bridge.html#design>.

Acceptance or denial of an alternate is at the sole discretion of the Department. Contractor is responsible for impacts to the project schedule and cost resulting from the use of alternates.

ITEM 6: CONTROL OF MATERIALS

To comply with the latest provisions of Build America, Buy America Act (BABA Act) of the Bipartisan Infrastructure Law, the contractor must submit a notarized original of the TxDOT Construction Material Buy America Certification Form for all items classified as construction materials. This form is not required for materials classified as a manufactured product.

Refer to the Buy America Material Classification Sheet for clarification on material categorization.

The Buy America Material Classification Sheet is located at the below link.

<https://www.txdot.gov/business/resources/materials/buy-america-material-classification-sheet.html> for clarification on material categorization.

References to manufacturer's trade name or catalog numbers are for the purpose of identification only and the Contractor will be permitted to furnish like materials of other manufacturers provided they are of equal quality and comply with specifications for this project.

This project has a structure with surface coatings which contain hazardous constituent which is lead paint. Contractor is responsible for the health and safety of his employees and compliance with all OSHA standards and regulations.

ITEM 7: LEGAL RELATIONS AND RESPONSIBILITIES

No significant traffic generator events identified.

If utilizing private property for waste disposal sites, field office sites, equipment storage sites or for any other purpose involved with this project, provide to the Engineer written proof of the property owner's approval of the use of this property. This proof may be in the form of a letter or agreement signed by the property owner or other documents acceptable to the Engineer. Provide such proof prior to occupying the site.

Personal vehicles of the Contractor's employees will not be parked within the right of way at any time including any section closed to public traffic unless the vehicle is being utilized for construction procedures. However, the Contractor's employees may park on the right of way at the sites where the Contractor has his office, equipment, and materials storage yard.

The Contractor is alerted to the possible presence of swallows under the existing bridges or culverts. Because the migratory bird treaty act prohibits harm to swallows, their eggs or their nestlings, the Contractor will not begin potentially disturbing activities on or near the bridge until the birds have abandoned any occupied nests (approximately September 1). Active nests may not be removed regardless of the date.

Prior to the swallows returning to the nests (approximately March 1), abandoned nests will be removed from the bridge. The Contractor will prevent the establishment of new nests on any portion of the structure. Methods for preventing the establishment of new nests must be approved by the Engineer. Examples of acceptable nest prevention methods are bird-deterrent netting and bird-repelling sprays and/or gels to be applied to the structure. This work will not be paid for directly but will be subsidiary to the various bid items. No relief or compensation will be considered for project delays due the Contractors in attention / in action to preventing nesting or for nesting already underway at the commencement of work.

Notify the Engineer in writing a minimum of 7 days in advance of opening any bridge structure to public use, to allow the Engineer an opportunity to conduct a safety assessment prior to opening.

The Contractor will submit detailed site-specific plans for work in each "water of the United States" designated on the EPIC sheet. These plans must be approved by the Engineer prior to starting any work in these areas. The plans must also describe facilities and work activities adjacent the Ordinary High-Water Marks. The plan must show actual dimensions and materials for:

- Proposed construction roads and work areas leading to or in close proximity to the Ordinary High-Water Marks
- Temporary material or equipment storage areas in close proximity to the Ordinary High-Water Marks
- Locations of proposed sediment and erosion control devices
- Identification of construction equipment and construction techniques to accomplish the work

Once this drawing and supporting information is reviewed and approved by TxDOT, all construction workers should be made aware of the limits designated on the drawings by the Contractor's supervision. Work in all waters of the US will be limited to the minimum necessary required to

construct the bridge, culvert, or roadway fills. Work will also include all activities needed for bridge and culvert demolitions. Working or disturbing soil in the stream channel outside the limits of the work plan will not be allowed. Orange fencing will be provided and maintained to establish the TxDOT approved boundaries in which work may be conducted between the Ordinary High-Water Marks. Orange fencing will not be paid for but will be considered subsidiary to Item 502, "Barricades, Signs and Traffic Handling".

ITEM 8: PROSECUTION AND PROGRESS

This Project will be a Standard Workweek in accordance with Article 8.3.1.4.

Meet bi-weekly or at intervals as agreed upon with the Engineer to notify him or her of planned work for the upcoming 3-week period.

For this project, provide a Bar Chart progress schedule.

ITEM 100: PREPARING RIGHT OF WAY

The limits of preparing right of way will be measured at the following locations:

From Sta. 402+00.00 to Sta. 407+30.00

along the centerline of construction.

Remove the existing roadway delineators and object markers as shown on the plans, or as directed, during construction within the right of way. Delineator and object marker removals are subsidiary to this Item.

Remove all trees within the right of way within station limits designated for Preparing Right of Way unless designated for preservation or as directed by the Engineer.

Trees to be removed near gas lines shall be cut and ground 1' below grade.

Preserve trees within temporary construction easements in accordance with Article 100.2., unless otherwise directed.

Prune trees designated for preservation as directed. All work required in preserving and pruning trees will be included in the price bid for Item 100, "Preparing Right of Way".

The removal of any existing fence will not be paid for directly but will be considered subsidiary to the bid Item 100, "Preparing Right Of Way".

All trees and brush removed each day will be disposed of within the same day of removal unless otherwise approved. If removed vegetation is burned, ashes from burned vegetation will not be placed or allowed to be transported by storm water into any stream. Burn locations, if approved, will be no closer than 300 feet from a stream. Earth berms must be used around burn areas to keep ash in place.

The Contractor is prohibited from removing grass vegetation throughout the entire project limits and then ceasing construction for long periods, typically over three weeks. The Contractor schedule will be developed based on staged vegetation removal, limiting disturbed soil to no more than 25 percent at one time, unless otherwise approved. Should the Contractor not be able to adequately control sediment and erosion for areas disturbed, TxDOT will substantially reduce the size of areas that the Contractor may disturb soil. Should the project be evaluated to have sediment control problems as a result of the Contractor disturbing excessive amounts of soil, the Contractor will be required to immediately re-vegetate (seed and water) those disturbed areas at no cost to TxDOT.

The following five (5) notes apply to All Oak Tree Species:

1. To avoid the spread of Oak Wilt or other disease, all species of oak trees that are damaged or cut (branches, roots and/or stumps) for any reason during this contract, must be treated with a commercial wound dressing within 20 minutes of causing the damage or cut.
2. To prevent the spread of infection from tree to tree when pruning oak trees (all species), the Contractor must disinfect all pruning tools with a solution of 70% isopropyl alcohol after all cutting is complete on each oak tree.
3. Potentially dangerous trees or limbs will be removed as soon as possible.
4. The Engineer can stop all Work operations if the dressing, cut and removal requirements are not followed.
5. Pruning shall be in accordance with ANSI A300 pruning standard.

The Contractor will be responsible for leaving the project site clean and neat in appearance upon completion and before final acceptance by the Engineer.

Wood chips may be left on the right of way no deeper than two (2) inches outside of city limits. Do not trespass on private property while performing work on this contract. Do not cut or damage timber outside the right-of-way lines.

Remove all fallen parts of trees, damaged limbs, and dead limbs. This work will not be paid for directly but will be considered subsidiary to this item.

ITEM 110: EXCAVATION

In a cut section, when soils are encountered at subgrade depths that are unstable and are deemed unsuitable by the Engineer, undercut this material for a minimum depth of one (1.0) foot below the maximum depth as determined and replace with a material having a plasticity index less than 25 and a liquid limit of less than 50.

ITEMS 110 & 132: EXCAVATION & EMBANKMENT

The Contractor may modify side slopes from those shown in the cross section as needed to allow grades to match / tie into fixed features. In no case should slope be modified beyond the maximum grades shown on the typical section and approved by the Engineer. Additionally slope adjustments will not be allowed simply to reduce work quantities.

ITEM 160: TOPSOIL

Salvage the existing topsoil from the cut/fill areas. Topsoil not stored in small windrows will be stockpiled in locations with heights no greater than four (4) feet and dumped loose from Contractor equipment. The Contractor will minimize topsoil compaction and limit equipment being driven over stockpiled topsoil.

Avoid topsoil areas that have invasive plant species. Contain / separate topsoil from areas with identified invasive species into separate windrows / piles. Mark topsoil from invasive species areas accordingly and track and return materials to only their original areas or dispose of such materials accordingly. Invasive species will include Giant Cane,

Additional Topsoil will come from approved sources outside of the ROW. Topsoil must come from a location within six (6) inches of the natural ground surface to ensure it contains nutrients and is not sterile soil. Off ROW topsoil will contain a minimum organic content of three & one-half (3.5%) percent, based on soil test results.

ITEM 164: SEEDING FOR EROSION CONTROL

Temporary seeding mixtures (cool and warm) will also include three (3) lbs of Bermuda grass seed per acre, with all seeds being planted concurrently.

Contractor will mow or disc wheat and or oats in spring prior to vegetation going to seed.

Permanent seed mixes for both urban and rural projects including sand or clay soils in the Waco District will be bid and installed to include a minimum of one & one-half (1.5) pounds per acre Green Sprangletop seed and four (4) pounds per acre Bermudagrass seed, with other seed types also being included and quantities remaining unchanged.

ITEM 247: FLEXIBLE BASE

Construct uniform layer thickness of 6 inches, or less with the required density and moisture content. Construction no layers less than 3 inches in thickness.

Minimum PI is equal to three (3) for all grades, or a minimum Bar Linear Shrinkage of 2%.

ITEM 400: EXCAVATION AND BACKFILL OF STRUCTURES

Aggregate for cement stabilized backfill will be coarse aggregates, GRADE 3, 4 or 5 and fine aggregate, as shown in Item 421, "Hydraulic Cement Concrete". The ratio of coarse aggregate to sand should not contain more than sixty percent (60%) sand unless otherwise approved.

CLASS B bedding is required for all storm drain installations. In areas requiring Cement Stabilized Backfill, CSB will be used in lieu of Class B materials for bedding.

ITEM 416: DRILLED SHAFT FOUNDATIONS

Provide a minimum of one core per bent, regardless of placement method.

ITEM 420 CONCRETE SUBSTRUCTURES

Form columns to a point a minimum of one foot below the proposed future or existing bottom of channel elevation indicated on the bridge layouts by an acceptable method. This form work is not paid for directly but is considered subsidiary to this item.

BENT NUMBERING:

For bridges with four or more spans, number every third bent (counting the abutments) on the up-station and down-station faces of the outside column(s) at approximately the mid height of the column. For structures with three columns or less per bent, place numbers on column A. Where there are four or more columns per bent, place numbers on both outside columns. Bent numbers will be as shown on the bridge layout.

Provide block numbers with a height of 6". Place numbers using appropriate die cut stencils and black paint. All materials, labor and incidentals associated with placing bent numbers are subsidiary to the various bid items.

NATIONAL BRIDGE INVENTORY NUMBERS:

Provide National Bridge Inventory (NBI) numbers on all bridge structures and bridge class culverts.

Where beam types allow access to the face of abutment backwall, place NBI numbers on the face of each abutment backwall using 3" block numbers. Locate NBI numbers between the outside beams at opposite corners of the bridge.

Where beam types do not allow access to the face of abutment backwall, place NBI numbers on the face of each abutment cap using 3" block numbers. Locate NBI numbers below the outside beams at opposite corners of the bridge.

Where a bridge begins, ends or contains a bent common to multiple structures, place NBI numbers on both faces near both ends of the common bent cap. The number placed at each of the four locations will correspond to the NBI number assigned to the bridge immediately above the number. Locate NBI numbers below the outside beam. Place using 3" Block Numbers.

For all conditions, use appropriate die cut stencils and black paint for placement. All materials, labor and incidentals associated with placing NBI numbers are subsidiary to the various bid items.

ITEM 421: HYDRAULIC CEMENT CONCRETE

Furnish mix designs to the Engineer in a format compatible to the latest version of the Department's Construction Management System (Site Manager). Mix Design templates will be provided by the Engineer.

Provide sulfate resistant concrete for box culverts and all drilled shafts.

Supply the Engineer with a list of certified personnel and copies of their current ACI certificates before beginning production and when personnel changes are made. Supply hard copies of calibration reports for testing equipment when required by the Engineer.

ITEM 422: CONCRETE SUPERSTRUCTURES

Provide Carpet Drag, burlap drag or broom finish for bridge deck, approach slabs and direct traffic culvert top slabs.

ITEM 427: SURFACE FINISHES FOR CONCRETE

Apply a rub finish to all Surface Area I within 30 days after form removal.

ITEM 432: RIPRAP

Weep holes and granular material are required, and locations will be determined prior to placement of concrete riprap at bridge abutments.

ITEM 450: RAILING

Provide slip formed barrier and cast-in-place barrier uniform in color and texture.

ITEM 496: REMOVING STRUCTURES

Submit to the Engineer for approval a detailed plan for bridge removal including methods, equipment and sequencing.

ITEM 500: MOBILIZATION

Material On Hand (MOH) will not be used in calculating partial payments for Mobilization.

ITEM 502: BARRICADES, SIGNS, AND TRAFFIC HANDLING

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

A meeting between the Contractor and Engineer to discuss upcoming changes in construction phasing and traffic switches is required at least fourteen (14) days prior to the phase change. Items to be discussed at this meeting include temporary signing, traffic control, pavement markings, the processes necessary for the phase change and subcontractor scheduling.

Place barricades and signs in locations that do not obstruct the sight distance of drivers entering the highway from driveways or side streets.

The Contractor Responsible Person(s) (CRP) for Work Zone Traffic Controls will inspect and ensure any deficiencies are corrected each and every day throughout the duration of this contract. Any misaligned or damaged traffic control devices will be repaired as soon as practical after deficiency is discovered.

ITEM 506: TEMPORARY EROSION, SEDIMENTATION AND ENVIRONMENTAL CONTROLS

Take all practicable precautions to prevent debris from being discharged into the Waters of Texas or a designated wetland. Install Best Management Practices before demolition begins and maintain them during the demolition. Remove any debris or construction material that escapes containment devices and are discharged into the restricted areas before the next rain event or within 24 hours of the discharge.

If temporary construction stream crossings are allowed under a Nationwide Permit, submit in writing for approval the type and location of each temporary stream crossing. Use temporary bridges, timber mats, or other structurally sound and non-eroding material for temporary stream crossings. A temporary culvert crossing will consist of storm sewer pipes and 4- to 8-inch nominal size rock. Temporary stream crossings must not cause more than minimal changes to the hydraulic flow characteristics of the stream, increase flooding, or cause more than minimal degradation of water quality. Remove the temporary stream crossings in their entirety and return the affected areas to their pre-existing elevation. All work and materials use for temporary construction stream crossings will not be paid for directly but are subsidiary to pertinent Items.

Provide SWP3 Signs. Obtain from the Engineer a copy of the project's completed TPDES Storm Water Program Construction Site Notice and Contractor Site Notice. Laminate the sheets and bond with adhesive to 36" X 36" sign blanks. Ensure the sheets remain dry. Apply Type C Blue reflective sheeting as the background and add the text "SWP3" in 5" white lettering, centered at the top. Attach the signs to approved temporary mounts and locate at each of the project limits just inside the right of way line at a readable height or as directed by the Engineer. If the sign cannot be placed outside the clear zone, it must adhere to the TMUTCD. SWP3 signs, maintenance, and reposting (for replacement or as needed to ensure readability) will be subsidiary to Item 502.

Leave all right of way areas undisturbed until actual construction is to be performed in said areas.

No soil disturbing activities will begin on any section of TxDOT ROW without adequate sedimentation controls first being installed and functioning at adjacent drainage outfalls. Begin and continuously prosecute the repairs, additions and maintenance of erosion and sedimentation control devices within seven days after the Contractor receives each Form 2118, Field Inspection and Maintenance Report, from the Engineer. Failure of the Contractor to fulfill either of the above requirements places TxDOT in potential non-compliance with permit requirements and may result in withholding estimates or stopping work or both until all environmental permit requirements are fulfilled.

Concrete Washouts are required per the CGP. The Concrete Washout Area(s) structural controls must consist of temporary berms, temporary shallow pits, and/or temporary storage tanks to prevent contaminated runoff and must be lined as to prevent contamination of underlying soil. Ensure pits properly maintained including removal of concrete as not to allow overflow. The location(s) of washout area will be approved by the Engineer. When washout pits are no longer needed, they will be removed, and area will be restored to original condition. This work, materials and labor will not be measured or paid for directly but will be subsidiary to Item 506, "Temporary Erosion, Sedimentation, and Environmental Controls."

Cleaning and sweeping of open roadways due to material spillage or loss from Contractor equipment or tires will be the responsibility of the Contractor at no cost to TxDOT. This work will not be charged as Item 738, "Cleaning and Sweeping Highways". Cleaning and sweeping of roadways will be completed as directed, including multiple times per day, if necessary, to maintain acceptable roadways for the traveling public and to meet environmental regulations. Construction activities will cease when material deposited on the roadway is not properly removed or when equipment is not available as needed. Adequate construction exits will be planned, constructed, and maintained by the Contractor per Item 506, "Temporary Erosion, Sedimentation, and Environmental Controls".

THIS PAGE INTENTIONALLY LEFT BLANK

ITEM 540: METAL BEAM GUARD FENCE

Furnish steel posts throughout the project except as specifically noted in the plans.

Wooden block outs will not be allowed.

ITEM 544: GUARDRAIL END TREATMENTS

The use of wooden block-outs will not be allowed.

ITEM 658: DELINEATOR AND OBJECT MARKER ASSEMBLIES

All flexible and GF2 delineators will have a tubular body.

The delineator assembly BRF Class A (D-SW) and (D-SY) are to be single delineators (Class I) attached to a flat, plastic bracket to facilitate the mounting of the delineator on top of the bridge rail at the locations shown on the plans. Submit a sample for approval before ordering materials.



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0909-29-046

DISTRICT Waco
HIGHWAY CR 207

COUNTY Hamilton

CONTROL SECTION JOB				0909-29-046		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00140255			
COUNTY				Hamilton			
HIGHWAY				CR 207			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	100-6002	PREPARING ROW	STA	5.300		5.300	
	110-6001	EXCAVATION (ROADWAY)	CY	312.000		312.000	
	110-6002	EXCAVATION (CHANNEL)	CY	630.000		630.000	
	132-6004	EMBANKMENT (FINAL)(DENS CONT)(TY B)	CY	890.000		890.000	
	160-6003	FURNISHING AND PLACING TOPSOIL (4")	SY	1,362.000		1,362.000	
	164-6001	BROADCAST SEED (PERM) (RURAL) (SANDY)	SY	1,362.000		1,362.000	
	164-6071	BROADCAST SEED (TEMP)(WARM OR COOL)	SY	1,362.000		1,362.000	
	168-6001	VEGETATIVE WATERING	MG	23.000		23.000	
	169-6002	SOIL RETENTION BLANKETS (CL 1) (TY B)	SY	1,362.000		1,362.000	
	247-6053	FL BS (CMP IN PLC)(TYD GR1-2)(FNAL POS)	CY	194.000		194.000	
	400-6005	CEM STABIL BKFL	CY	105.000		105.000	
	416-6004	DRILL SHAFT (36 IN)	LF	147.000		147.000	
	420-6013	CL C CONC (ABUT)	CY	38.600		38.600	
	420-6029	CL C CONC (CAP)	CY	11.500		11.500	
	420-6037	CL C CONC (COLUMN)	CY	12.000		12.000	
	422-6001	REINF CONC SLAB	SF	3,640.000		3,640.000	
	425-6035	PRESTR CONC GIRDER (TX28)	LF	555.920		555.920	
	432-6033	RIPRAP (STONE PROTECTION)(18 IN)	CY	862.000		862.000	
	450-6054	RAIL (TY SSTR) (W/DRAIN SLOTS)	LF	328.000		328.000	
	454-6004	ARMOR JOINT (SEALED)	LF	46.000		46.000	
	496-6009	REMOV STR (BRIDGE 0 - 99 FT LENGTH)	EA	1.000		1.000	
	500-6001	MOBILIZATION	LS	0.100		0.100	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	5.000		5.000	
	506-6001	ROCK FILTER DAMS (INSTALL) (TY 1)	LF	176.000		176.000	
	506-6011	ROCK FILTER DAMS (REMOVE)	LF	176.000		176.000	
	506-6038	TEMP SEDMT CONT FENCE (INSTALL)	LF	1,036.000		1,036.000	
	506-6039	TEMP SEDMT CONT FENCE (REMOVE)	LF	1,036.000		1,036.000	
	540-6002	MTL W-BEAM GD FEN (STEEL POST)	LF	100.000		100.000	
	540-6007	MTL BEAM GD FEN TRANS (TL2)	EA	2.000		2.000	
	540-6016	DOWNSTREAM ANCHOR TERMINAL SECTION	EA	2.000		2.000	
	540-6018	MTL BM GD FEN TRANS (NON - SYM)	EA	2.000		2.000	
	544-6001	GUARDRAIL END TREATMENT (INSTALL)	EA	2.000		2.000	
	552-6003	WIRE FENCE (TY C)	LF	100.000		100.000	
	644-6076	REMOVE SM RD SN SUP&AM	EA	3.000		3.000	
	658-6014	INSTL DEL ASSM (D-SW)SZ (BRF)CTB (BI)	EA	6.000		6.000	
	658-6062	INSTL DEL ASSM (D-SW)SZ 1(BRF)GF2(BI)	EA	4.000		4.000	
	08	CONTRACTOR FORCE ACCOUNT EROSION CONTROL MAINTENANCE (NON-PARTICIPATING)	LS	1.000		1.000	



DISTRICT	COUNTY	CCSJ	SHEET
Waco	Hamilton	0909-29-046	5



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0909-29-046

DISTRICT Waco
HIGHWAY CR 207

COUNTY Hamilton

CONTROL SECTION JOB				0909-29-046		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00140255			
COUNTY				Hamilton			
HIGHWAY				CR 207			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	08	CONTRACTOR FORCE ACCOUNT SAFETY CONTINGENCY (NON-PARTICIPATING)	LS	1.000		1.000	

REMOVAL SUMMARY			
LOCATION	100 6002	496 6009	644 6076
	PREPARING ROW	REMOV STR (BRIDGE 0 - 99 FT LENGTH)	REMOVE SM RD SN SUP&AM
	STA	EA	EA
402+00 TO 407+30	5.3	1	3
PROJECT TOTALS	5.3	1	3

EARTHWORK SUMMARY			
LOCATION	110 6001	110 6002	132 6004
	EXCAVATION (ROADWAY)	EXCAVATION (CHANNEL)	EMBANKMENT (FINAL) (DENS CONT) (TY B)
	CY	CY	CY
402+00 TO 407+30	312	630	890
PROJECT TOTALS	312	630	890


TRAFFIC ITEM SUMMARY		
LOCATION	658 6014	658 6062
	INSTL DEL ASSM (D-SW) SZ (BRF) CTB (BI)	INSTL DEL ASSM (D-SW) SZ 1 (BRF) GF2 (BI)
	EA	EA
402+00 TO 407+30	6	4
PROJECT TOTALS	6	4

ROADWAY SUMMARY							
LOCATION	247 6053	540 6002	540 6007	540 6016	540 6018	544 6001	552 6003
	FL BS (CMP IN PLC) (TYD GR1-2) (FNAL POS)	MTL W-BEAM GD FEN (STEEL POST)	MTL BEAM GD FEN TRANS (TL2)	DOWNSTREAM ANCHOR TERMINAL SECTION	MTL BM GD FEN TRANS (NON - SYM)	GUARDRAIL END TREATMENT (INSTALL)	WIRE FENCE (TY C)
	CY	LF	EA	EA	EA	EA	LF
402+00 TO 407+30	194	100	2	2	2	2	100
PROJECT TOTALS	194	100	2	2	2	2	100

EROSION CONTROL SUMMARY									
LOCATION	160 6003	164 6001	164 6071	168 6001	169 6002	506 6001	506 6011	506 6038	506 6039
	FURNISHING AND PLACING TOPSOIL (4")	BROADCAST SEED (PERM) (RURAL) (SANDY)	BROADCAST SEED (TEMP) (WARM OR COOL)	VEGETATIVE WATERING	SOIL RETENTION BLANKETS (CL 1) (TY B)	ROCK FILTER DAMS (INSTALL) (TY 1)	ROCK FILTER DAMS (REMOVE)	TEMP SEDMT CONT FENCE (INSTALL)	TEMP SEDMT CONT FENCE (REMOVE)
	SY	SY	SY	MG	SY	LF	LF	LF	LF
402+00 TO 407+30	1362	1362	1362	23	1362	176	176	1036	1036
PROJECT TOTALS	1362	1362	1362	23	1362	176	176	1036	1036

BRIDGE SUMMARY										
LOCATION	400 6005	416 6004	420 6013	420 6029	420 6037	422 6001	425 6035	432 6033	450 6054	454 6004
	CEM STABIL BKFL	DRILL SHAFT (36 IN)	CL C CONC (ABUT)	CL C CONC (CAP)	CL C CONC (COLUMN)	REINF CONC SLAB	PRESTR CONC GIRDER (TX28)	RIPRAP (STONE PROTECTION) (18 IN)	RAIL (TY SSTR) (W/DRAIN SLOTS)	ARMOR JOINT (SEALED)
	CY	LF	CY	CY	CY	SF	LF	CY	LF	LF
402+00 TO 407+30	105	147	38.6	11.5	12	3640	555.92	862	328.0	46
PROJECT TOTALS	105	147	38.6	11.5	12	3640	555.92	862	328.0	46


REV DATE: 2/13/2023
 CSJ: 0909-29-046
 FILE LOCATION: P:\2020\0007\2090929046\4 - Design\Plan Set\1. General\20200072.04.QTY.SUM.dgn



**AMERICAN
STRUCTUREPOINT
INC.**

3711 SOUTH MOPAC EXPRESSWAY
 BUILDING ONE, SUITE 350
 AUSTIN, TX 78703
 TEL 512.494.6037 FAX 317.543.0270
 www.structurepoint.com


TBPE FIRM NO. F-10069



**Texas Department
of Transportation** ©2023


CR 238 (HCR 207) AT HONEY CREEK
SUMMARY OF QUANTITIES

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	6



VICINITY MAP

CR 238 AT HONEY CREEK



SIGNS G20-10T, G20-5T, G20-6T, G20-2, G20-2bT, CW20-1D, R20-3T, R20-5T, G20-9TP AND R20-5aTP WILL BE REQUIRED AT PROJECT LIMITS.

CW20-1D AND G20-2 WILL BE REQUIRED AT ALL CROSSROADS.

G20-1a WILL BE REQUIRED AT ALL MAJOR CROSSROADS.

REFER TO BC STANDARDS FOR SIGN R2-1 PLACEMENT.

SIGNAGE LEGEND

R20-5aTP (36X18)	- WHEN WORKERS ARE PRESENT
G20-10T (60X48)	- STAY ALERT TALK OR TEXT LATER
G20-5T (48X24)	- BEGIN ROAD WORK NEXT X MILES
G20-6T (48X30)	- NAME, ADDRESS, CITY, STATE, CONTRACTOR
G20-9TP (36X30)	- BEGIN WORK ZONE
G20-2bT (36X18)	- END WORK ZONE
R20-3T (48X42)	- OBEY WARNING SIGNS STATE LAW
G20-1a (72X36)	- ROAD WORK NEXT X MILES
CW20-1D (48X48)	- ROAD WORK AHEAD
R20-5T (36X36)	- TRAFFIC FINES DOUBLE
G20-2 (48X24)	- END ROAD WORK
R2-1 (24X30)	- SPEED LIMIT XX

GENERAL

- A. INSTALL ALL SIGNS, BARRICADES AND TRAFFIC CONTROL DEVICES AS SHOWN AND IN ACCORDANCE WITH STANDARD SHEETS BC(1)-21 THRU BC(12)-21 AND AS DIRECTED.
- B. ADDITIONAL SIGNS, BARRICADES OR TRAFFIC CONTROL DEVICES OTHER THAN THOSE SPECIFIED MAY BE REQUIRED FOR THE SAFE MOVEMENT OF TRAFFIC THROUGH THE PROJECT. PAYMENT FOR ALL SUCH SIGNS, BARRICADES OR TRAFFIC CONTROL DEVICES WILL BE CONSIDERED AS SUBSIDIARY TO ITEM 502, "BARRICADES, SIGNS AND TRAFFIC HANDLING".
- C. WORK SITES WILL BE CAREFULLY MONITORED TO ENSURE THAT TRAFFIC CONTROL MEASURES ARE OPERATING EFFECTIVELY AND THAT ALL DEVICES USED ARE CLEARLY VISIBLE, CLEAN AND IN GOOD REPAIR.
- D. THE TRAFFIC CONTROL SEQUENCE OF WORK AND TRAFFIC CONTROL SHOWN ON THESE PLANS IS A SUGGESTED METHOD OF HANDLING TRAFFIC DURING CONSTRUCTION. SIGNS, BARRICADES, ETC. SHOWN IN THE PLANS ARE CONSIDERED TO BE MINIMUM REQUIRED FOR TRAFFIC HANDLING ON THIS PROJECT.
- E. ADDITIONAL TRAFFIC CONTROL DEVICES AND SIGNAGE MAY BE REQUIRED BASED ON CONTRACTORS' CONSTRUCTION OR DURING SHORT-TERM OPERATIONS NOT ADDRESSED IN THESE SHEETS.
- F. THE ENGINEER MAY DIRECT THE CONTRACTOR TO VARY THE NUMBER AND LOCATION OF SIGNS, BARRICADES AND CHANNELIZING DEVICES FROM THOSE INDICATED IN THE PLANS IN ORDER TO MAINTAIN SAFE AND UNINTERRUPTED FLOW OF TRAFFIC, PARTICULARLY IN THOSE AREAS OF IMMEDIATE WORK.
- G. THE CONTRACTOR WILL PROVIDE SAFE ACCESS TO AND FROM ALL PRIVATE PROPERTY AT ALL TIMES AND IN ALL WEATHER CONDITIONS, UNLESS OTHERWISE DIRECTED.
- H. THE CONTRACTOR WILL BE REQUIRED TO SUBMIT A DETAILED SCHEDULE OF WORK TO THE PROJECT ENGINEER PRIOR TO THE BEGINNING OF CONSTRUCTION WHICH GENERALLY CONFORMS TO THE SEQUENCE SHOWN ON THE TCP SEQUENCE OF OPERATION.
- I. COMPLETE ALL WORK ON PROJECT AS SHOWN ON THE VARIOUS PLAN SHEETS AND IN COMPLIANCE WITH THE GENERAL NOTES OF THIS PROJECT.
- J. ANY REQUEST TO ALTER THE SEQUENCE OF OPERATION OR TRAFFIC CONTROL PLAN WILL BE SIGNED AND SEALED BY A PROFESSIONAL ENGINEER AND SUBMITTED TO THE PROJECT ENGINEER FOR HIS WRITTEN APPROVAL.

SEQUENCE OF OPERATION

- 1) SET PROJECT BARRICADES.
- 2) INSTALL SWP3 AND BMP'S AS SHOWN AND AS DIRECTED.
- 3) REMOVE EXISTING BRIDGE.
- 4) CONSTRUCT REPLACEMENT BRIDGE AND APPROACHES INCLUDING BASE.
- 5) INSTALL MBGF, SGT'S AND DELINEATORS.
- 6) INSTALL PERMANENT SEEDING AS SHOWN.
- 7) PERFORM CLEANUP AND PERFORM OTHER WORK AS DIRECTED.
- 8) IF APPROVED, OPEN ROAD AND BRIDGE TO TRAFFIC.

NOTES

- 1) ALL TRAFFIC CONTROL DEVICES WILL CONFORM WITH THE TEXAS "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS" (TMUTCD), AND WILL BE MAINTAINED AS DIRECTED. ADDITIONAL GUIDELINES FOR TRAFFIC CONTROL DEVICES MAY BE FOUND IN THE TMUTCD.
- 2) FOR CHANNELING DEVICE PLACEMENT AND SPACING FOR ALL PHASES, REFER TO BC(1) THRU BC(12) STANDARDS.

PRINT DATE	REVISION DATE
2/8/2023	

JOSE M. SANDOVAL
DATE: 2/8/2023

3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com

TBPE FIRM NO. F-10069

CR 238 (HCR 207) AT HONEY CREEK
SEQUENCE OF CONSTRUCTION

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	7

DATE: 2/8/2023 1:37:54 PM
 FILE: T:\Road_Dept\Department\Team Texas\txdot cadd standards\traffic control\BC-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY NOTES:

1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

1. Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).

THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS) "
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12




**BARRICADE AND CONSTRUCTION
GENERAL NOTES
AND REQUIREMENTS**

BC (1) -21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
4-03	7-13	0909	29	046	CR				
9-07	8-14	DIST	COUNTY		SHEET NO.				
5-10	5-21	WACO	HAMILTON		8				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any sign to other formats or for incorrect results or damages resulting from its use.

TYPICAL LOCATION OF CROSSROAD SIGNS



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
 - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
 - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
 - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
 - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
 - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

T-INTERSECTION



CSJ LIMITS AT T-INTERSECTION

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING^{1,5,6}

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Δ Spacing "X" Feet (Apprx.)
CW20 ⁴	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25	36" x 36"	48" x 48"	50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14			55	500 ²
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12			60	600 ²
			65	700 ²
	48" x 48"	48" x 48"	70	800 ²
			75	900 ²
			80	1000 ²
			*	*


* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS



SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS



NOTES

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "X" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
 - CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
 - Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
 - Contractor will install a regulatory speed limit sign at the end of the work zone.

LEGEND	
—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC(2)-21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	WACO	HAMILTON	9	

DATE: 2/8/2023 1:37:54 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\traffic control\BC(2)-21.dgn

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
 - Law enforcement.
 - Flagger stationed next to sign.
 - Portable changeable message sign (PCMS).
 - Low-power (drone) radar transmitter.
 - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

SHEET 3 OF 12



BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC(3)-21


FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0909	29	046	CR				
9-07	8-14	DIST	COUNTY		SHEET NO.				
7-13	5-21	WACO	HAMILTON		10				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 2/21/2023 3:11:14 PM
 FILE: T:\Road_Dept\Department\Team Texas\txdot cadd standards\traffic control\BC(3)-21.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/21/2023 3:11:14 PM
FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\traffic control\BC-21.dgn


TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS




Attachment to wooden supports will be by bolts and nuts or screws. Use TxDOT's or manufacturer's recommended procedures for attaching sign substrates to other types of sign supports

Nails shall NOT be allowed.
Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.

Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

STOP/SLOW PADDLES

1. STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
2. STOP/SLOW paddles shall be retroreflectORIZED when used at night.
3. STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
4. Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

1. Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
2. When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
3. When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
4. If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
5. If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRs standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
6. Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

GENERAL NOTES FOR WORK ZONE SIGNS

1. Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
2. Wooden sign posts shall be painted white.
3. Barricades shall NOT be used as sign supports.
4. All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
5. The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
6. The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
7. The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
8. Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
9. The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

1. The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - a. Long-term stationary - work that occupies a location more than 3 days.
 - b. Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - c. Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - d. Short, duration - work that occupies a location up to 1 hour.
 - e. Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

SIGN MOUNTING HEIGHT

1. The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
2. The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
3. Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
4. Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
5. Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

1. The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

1. The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
2. "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
3. All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

1. All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
2. White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
3. Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

1. All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

1. When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
2. Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
3. Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
4. When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
5. Burlap shall NOT be used to cover signs.
6. Duct tape or other adhesive material shall NOT be affixed to a sign face.
7. Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS

1. Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
2. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
3. Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
4. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
5. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
6. Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
7. Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
8. Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

1. Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

SHEET 4 OF 12

Texas Department of Transportation



Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION
TEMPORARY SIGN NOTES

BC(4)-21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		090929	046	CR
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	WACO	HAMILTON	11	

DATE: 2/21/2023 3:11:15 PM
 FILE: T:\Road Dept\Department\Team Texas\tdot cadd standards\traffic control\BC-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.





SKID MOUNTED WOOD SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

WEDGE ANCHORS
 Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

OTHER DESIGNS
 MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

- GENERAL NOTES**
- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
 - No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
 - When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.
- * See BC(4) for definition of "Work Duration."
 - ** Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
 - See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	WACO	HAMILTON	12	

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE
ROAD CLOSED AT SH XXX
ROAD CLSD AT FM XXXX
RIGHT X LANES CLOSED
CENTER LANE CLOSED
NIGHT LANE CLOSURES
VARIOUS LANES CLOSED
EXIT CLOSED
MALL DRIVEWAY CLOSED
XXXXXXXX BLVD CLOSED

Other Condition List

FRONTAGE ROAD CLOSED
SHOULDER CLOSED XXX FT
RIGHT LN CLOSED XXX FT
RIGHT X LANES OPEN
DAYTIME LANE CLOSURES
I-XX SOUTH EXIT CLOSED
EXIT XXX CLOSED X MILE
RIGHT LN TO BE CLOSED
X LANES CLOSED TUE - FRI
ROADWORK XXX FT
FLAGGER XXXX FT
RIGHT LN NARROWS XXXX FT
MERGING TRAFFIC XXXX FT
LOOSE GRAVEL XXXX FT
DETOUR X MILE
ROADWORK PAST SH XXXX
BUMP XXXX FT
TRAFFIC SIGNAL XXXX FT
ROAD REPAIRS XXXX FT
LANE NARROWS XXXX FT
TWO-WAY TRAFFIC XX MILE
CONST TRAFFIC XXX FT
UNEVEN LANES XXXX FT
ROUGH ROAD XXXX FT
ROADWORK NEXT FRI-SUN
US XXX EXIT X MILES
LANES SHIFT *

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List

MERGE RIGHT
DETOUR NEXT X EXITS
USE EXIT XXX
STAY ON US XXX SOUTH
TRUCKS USE US XXX N
WATCH FOR TRUCKS
EXPECT DELAYS
REDUCE SPEED XXX FT
USE OTHER ROUTES
STAY IN LANE *

Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXX TO XXXXXXX
US XXX TO FM XXXX

Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

** Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

** See Application Guidelines Note 6.

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy Vehicle	HOV	Tuesday	TUES
Highway	HWY	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT

Roadway designation # IH-number, US-number, SH-number, FM-number




BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)

BC (6) -21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	WACO	HAMILTON	13	


DATE: 2/21/2023 3:11:16 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\traffic control\BC-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




CONCRETE TRAFFIC BARRIER (CTB)

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES
 LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

LOW PROFILE CONCRETE BARRIER (LPCB)



DELINEATION OF END TREATMENTS

END TREATMENTS FOR CTB'S USED IN WORK ZONES
 End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS

WARNING LIGHTS


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B_{FL} or C_{FL} Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.




Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

ATTENTION
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

FLASHING ARROW BOARDS

SHEET 7 OF 12

TRUCK-MOUNTED ATTENUATORS

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR

BC (7) -21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0909	29	046	CR				
9-07	8-14	DIST	COUNTY		SHEET NO.				
7-13	5-21	WACO	HAMILTON		14				

DATE: 2/21/2023 3:11:16 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\traffic control\BC-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS




- Pre-qualified plastic drums shall meet the following requirements:
- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
 - The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
 - Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
 - Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
 - The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
 - The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectORIZED space between any two adjacent stripes shall not exceed 2 inches in width.
 - Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
 - Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
 - Drum body shall have a maximum unballasted weight of 11 lbs.
 - Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign
 (Maximum Sign Dimension)
 Chevron CW1-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer



12" x 24" Vertical Panel
 mount with diagonals sloping down towards travel way

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(8)-21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0909	29	046	CR				
4-03	8-14	DIST	COUNTY	SHEET NO.					
9-07	5-21	WACO	HAMILTON	15					
7-13									


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/21/2023 3:11:16 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\traffic control\BC-21.dgn



FIXED
(Rigid or self-righting)


DRIVEABLE



PORTABLE


VERTICAL PANELS (VPs)

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




OPPOSING TRAFFIC LANE DIVIDERS (OTLD)

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS



LONGITUDINAL CHANNELIZING DEVICES (LCD)

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

GENERAL NOTES

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths *X			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS ² / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

*X Taper lengths have been rounded off.
 L=Length of Taper (FT.) W=Width of Offset (FT.)
 S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	WACO	HAMILTON	16	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPE 3 BARRICADES

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL




TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION



PERSPECTIVE VIEW




PLAN VIEW

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.
 42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



TRAFFIC CONTROL FOR MATERIAL STOCKPILES

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(10)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	WACO	HAMILTON	17	

WORK ZONE PAVEMENT MARKINGS

GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:
 YELLOW - (two amber reflective surfaces with yellow body).
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

BC(11)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
	0909	29	046	CR
REVISIONS	DIST	COUNTY	SHEET NO.	
2-98 9-07 5-21	WACO	HAMILTON	18	
1-02 7-13				
11-02 8-14				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act." No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:37:58 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\traffic control\BC-21.dgn

PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TXDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectORIZED pavement markings.






RAISED PAVEMENT MARKERS

TWO-WAY LEFT TURN LANE


STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS



SOLID LINES




BROKEN LINES



REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC(12)-21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
1-97 9-07 5-21	DIST	COUNTY	SHEET NO.	
2-98 7-13	WACO	HAMILTON	19	
11-02 8-14				

DATE: 2/21/2023 3:11:18 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\traffic_control\BC-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:37:59 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\traffic control\wzrcd-13.dgn



ROAD CLOSURE BEYOND THE INTERSECTION
 Signing for a Numbered Route with an Off-Site Detour



ROAD CLOSURE AT THE INTERSECTION
 Signing for an Un-numbered Route with an Off-Site Detour

LEGEND	
	Type 3 Barricade
	Sign

Posted Speed *	Minimum Sign Spacing "X" Distance
30	120'
35	160'
40	240'
45	320'
50	400'
55	500'
60	600'
65	700'
70	800'
75	900'

* Conventional Roads Only

GENERAL NOTES

1. This sheet is intended to provide details for temporary work zone road closures. For permanent road closure details see the D&OM standards.
2. Barricades used shall meet the requirements shown on Barricade and Construction Standard BC(10) and listed on the Compliant Work Zone Traffic Control Devices list (CWZTCD).
3. Stockpiled materials shall not be placed on the traffic side of barricades.
4. Barricades at the road closure should extend from pavement edge to pavement edge.
5. Detour signing shown is intended to illustrate the type of signing that is appropriate for numbered routes or un-numbered routes as labeled. It does not indicate the full extent of detour signing required. Detour routes should be signed as shown elsewhere in the plans.
6. If the road is open for a significant distance beyond the intersection or there are significant origin/destination points beyond the intersection, the signs and barricades at this location should be located at the edge of the traveled way.
7. The Street Name (M4-12T) sign is to be placed above the DETOUR (M4-9S) sign.
8. For urban areas where there is a shorter distance between the intersection and the actual closure location, the ROAD CLOSED XX MILES AHEAD (R11-3a) sign may be replaced with a ROAD CLOSED TO THRU TRAFFIC (R11-4) sign. If adequate space does not exist between the intersection and the closure a single ROAD CLOSED AHEAD (CW20-3D) sign spaced as per the table above may replace the ROAD CLOSED 1000 FT (CW20-3B) and ROAD CLOSED 500 FT (CW20-3C) signs.
9. Signs and barricades shown shall be subsidiary to Item 502. Locations where these details will be required shall be as shown elsewhere in the plans.




WORK ZONE ROAD CLOSURE DETAILS

WZ (RCD) - 13

FILE: wzrcd-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT August 1995	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
1-97 4-98 7-13	DIST	COUNTY	SHEET NO.	
2-98 3-03	WACO	HAMILTON	20	

CONTROL POINTS (SURFACE COORDINATES)							
POINT	NORTH	EAST	ELEVATION	STATION	OFFSET	LT/RT	DESCRIPTION
CP1	10,673,257.161	3,000,182.068	1,090.07'	OFF CHAIN	N/A	N/A	3 1/2" ALUMINUM DISK SET IN CONCRETE
CP2	10,673,001.777	3,000,339.312	1,080.29'	402+60.40	19.9'	RT	3 1/2" ALUMINUM DISK SET IN CONCRETE
CP3	10,672,480.303	3,000,585.180	1,078.16'	OFF CHAIN	N/A	N/A	3 1/2" ALUMINUM DISK SET IN CONCRETE




C1
 PI STATION = 403+35.64
 DELTA = 5° 33' 31" (RT)
 DEGREE OF CURVE = 19° 05' 55"
 TANGENT = 14.56
 LENGTH = 29.11
 RADIUS = 300.00
 PC STATION = 403+21.09
 PT STATION = 403+50.20

C2
 PI STATION = 405+32.78
 DELTA = 9° 50' 31" (RT)
 DEGREE OF CURVE = 38° 11' 50"
 TANGENT = 12.92
 LENGTH = 25.77
 RADIUS = 150.00
 PC STATION = 405+19.90
 PT STATION = 405+45.67

C3
 PI STATION = 407+88.48
 DELTA = 1° 03' 50" (LT)
 DEGREE OF CURVE = 11° 27' 33"
 TANGENT = 4.64
 LENGTH = 9.29
 RADIUS = 500.00
 PC STATION = 407+83.84
 PT STATION = 407+93.12

LINE TABLE	
LINE	BEARING
L1	S17°14'50"E



Eric A. Kreiner 02/06/23
 Eric A. Kreiner Date
 RPLS No. 5320

- NOTES:
1. THE SURVEY CONTROL INFORMATION HAS BEEN ACCEPTED AND INCORPORATED INTO THIS PS&E WHICH IS SIGNED, SEALED AND DATED BY A TEXAS PROFESSIONAL ENGINEER.
 2. ALL COORDINATES SHOWN HEREON ARE BASED ON THE TEXAS COORDINATE SYSTEM, CENTRAL ZONE (4203), NORTH AMERICAN DATUM OF 1983 (2011 ADJ: EPOCH 2010.00)
 3. THE VERTICAL DATUM FOR THIS PROJECT IS THE NAVD 1988 (CORS 2011), U.S. SURVEY FEET.
 4. ALL COORDINATE VALUES ARE BASED UPON AN AVERAGE OF FOUR 180 EPOCH OBSERVATIONS UTILIZING THE TxDOT VRS NETWORK.
 5. COORDINATES AND DISTANCES ARE U.S. SURVEY FEET, DISPLAYED IN SURFACE VALUES USING THE SURFACE ADJUSTMENT FACTOR 1.00001 (0.99999000009)

PRINT DATE	REVISION DATE
2/6/2023	06/21/2022

CONTROL POINT LEGEND	
	DENOTES PRIMARY CONTROL POINT AS NOTED (3 1/2" ALUMINUM DISK IN CONCRETE)



SAM Surveying and Mapping, LLC. (SAM)
 1341 W. Mockingbird Lane, Suite 400W
 Dallas, Tx 75247 - (214) 631-7888
 FIRM REGISTRATION NO. F-1937
 TBPLS REGISTRATION NO. 10064301

3711 SOUTH MOPAC EXPRESSWAY
 BUILDING ONE, SUITE 350
 AUSTIN, TX 78703
 TEL 512.494.6037 FAX 317.543.0270
 www.structurepoint.com
STRUCTUREPOINT INC.
 TBPE FIRM NO. F-10069

Texas Department of Transportation ©2023
 CR 238 (HCR 207) AT HONEY CREEK
 SURVEY CONTROL INDEX SHEET
 HAMILTON COUNTY, TEXAS

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER
6		CR
STATE	DISTRICT	COUNTY
TEXAS	WACO	HAMILTON
CONTROL	SECTION	JOB SHEET NO.
0909	29	046 21

100% SUBMITTAL



I HEREBY CERTIFY THAT THE HORIZONTAL AND VERTICAL DATA SHOWN HEREON WAS DETERMINED BY A FIELD SURVEY ON JANUARY 25, 2022 UTILIZING THE TXDOT VIRTUAL REFERENCE SYSTEM RTK NETWORK AND IS CORRECTLY SHOWN HEREON.



Eric A. Kreiner 02/06/23

Eric A. Kreiner
Registered Professional Land Surveyor
No. 5320

TBPLS # 10064301	PRINT DATE 2/6/2023	REVISION DATE
------------------	------------------------	---------------

CONTROL POINT NO. 1:
APPROXIMATE LOCATION:

3 1/2" ALUMINUM DISK SET IN CONCRETE STAMPED "CP1", +/- 194 FEET SOUTH OF THE INTERSECTION OF CR 238 AND US 281, 3' EAST OF A BARBED WIRE FENCE, 12' WEST OF WEST EDGE OF PAVING OF CR 238, AND 20' SOUTH OF A UTILITY PEDESTAL.

US SURVEY FEET
NAVD 88 ELEVATION= 1,090.07'
DATE SET: JANUARY 25, 2022
MONUMENT: 3 1/2" ALUMINUM DISK SET IN CONCRETE STAMPED " CP1"
HAMILTON COUNTY SCALE FACTOR: 1.00001
SURFACE ENGLISH CO-ORDS
NORTHING: 10,673,257.161
EASTING: 3,000,182.068
STATE PLANE ENGLISH CO-ORDS
NORTHING: 10,673,150.429
EASTING: 3,000,152.066
ELEVATIONS ARE NAVD 88 BASED UPON TXDOT VRS RTK NETWORK

CONTROL POINT NO. 2:
APPROXIMATE LOCATION:

3 1/2" ALUMINUM DISK SET IN CONCRETE STAMPED "CP2", +/- 499 FEET SOUTH OF THE INTERSECTION OF CR 238 AND US 281, 13' WEST OF WEST EDGE OF PAVING OF CR 238, 40' EAST OF A POWER POLE, AND 69' NORTH OF A TELEPHONE PEDESTAL.

US SURVEY FEET
NAVD 88 ELEVATION= 1,080.29'
DATE SET: JANUARY 25, 2022
MONUMENT: 3 1/2" ALUMINUM DISK SET IN CONCRETE STAMPED " CP2"
HAMILTON COUNTY SCALE FACTOR: 1.00001
SURFACE ENGLISH CO-ORDS
NORTHING: 10,673,001.777
EASTING: 3,000,339.312
STATE PLANE ENGLISH CO-ORDS
NORTHING: 10,672,895.048
EASTING: 3,000,309.309
ELEVATIONS ARE NAVD 88 BASED UPON TXDOT VRS RTK NETWORK

SAM Surveying and Mapping, LLC. (SAM)
1341 W. Mockingbird Lane, Suite 400W
Dallas, Tx 75247 - (214) 631-7888
FIRM REGISTRATION NO. F-1937
TBPLS REGISTRATION NO. 10064301

3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com

STRUCTUREPOINT INC.

TBPE FIRM NO. F-10069



Texas Department of Transportation ©2023

CR 238 (HCR 207) AT HONEY CREEK
PRIMARY HORIZONTAL
AND VERTICAL CONTROL
HAMILTON COUNTY, TEXAS

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	22

REV DATE: 2/6/2023
CSJ: 0909-29-046
FILE LOCATION: \\saminc\dal\PROJECTS\1021066191\04Delivery\Final\2023-02-06_Honey Creek\2020.00072.04.SVY.SCD.dgn

100% SUBMITTAL



I HEREBY CERTIFY THAT THE HORIZONTAL AND VERTICAL DATA SHOWN HEREON WAS DETERMINED BY A FIELD SURVEY ON JANUARY 25, 2022 UTILIZING THE TXDOT VIRTUAL REFERENCE SYSTEM RTK NETWORK AND IS CORRECTLY SHOWN HEREON.



Eric A. Kreiner 02/06/23

Eric A. Kreiner
Registered Professional Land Surveyor
No. 5320

PRINT DATE	REVISION DATE
2/6/2023	

TBPLS # 10064301

SAM Surveying and Mapping, LLC. (SAM)
1341 W. Mockingbird Lane, Suite 400W
Dallas, Tx 75247 - (214) 631-7888
FIRM REGISTRATION NO. F-1937
TBPLS REGISTRATION NO. 10064301

3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com

STRUCTUREPOINT INC.

TBPE FIRM NO. F-10069

Texas Department of Transportation ©2023

CR 238 (HCR 207) AT HONEY CREEK
PRIMARY HORIZONTAL
AND VERTICAL CONTROL
HAMILTON COUNTY, TEXAS

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	23

CONTROL POINT NO. 3:
APPROXIMATE LOCATION:

3 1/2" ALUMINUM DISK SET IN CONCRETE STAMPED "CP3", +/- 0.2 OF A MILE SOUTH OF THE INTERSECTION OF CR 238 AND US 281, 2' WEST OF A BARBED WIRE FENCE, 6' EAST OF EAST EDGE OF PAVING OF CR 238, AND 53' EAST OF A POWER POLE.

US SURVEY FEET
NAVD 88 ELEVATION= 1,078.16'
DATE SET: JANUARY 25, 2022
MONUMENT: 3 1/2" ALUMINUM DISK SET IN CONCRETE STAMPED " CP3"
HAMILTON COUNTY SCALE FACTOR: 1.00001
SURFACE ENGLISH CO-ORDS
NORTHING: 10,672,480.303
EASTING: 3,000,585.180
STATE PLANE ENGLISH CO-ORDS
NORTHING: 10,672,373.579
EASTING: 3,000,555.174
ELEVATIONS ARE NAVD 88 BASED UPON TXDOT VRS RTK NETWORK

REV DATE: 2/6/2023
CSJ: 0909-29-046
FILE LOCATION: \\saminc\dal\PROJECTS\1021066191\04Delivery\Final\2023-02-06_Honey Creek\2023-02-06_SVY_SCD.dgn

CR_238

Beginning chain CR238 description
 Feature: Geom_Centerline

Point CR2381 X 3,000,220.5899 Y 10,673,234.4626 Sta 400+00.00
 Course from CR2381 to PC CR238_1 S 31° 35' 02.74" E Dist 321.0917

Curve Data

Curve CR238_1
 P.I. Station = 403+35.66 X 3,000,396.3894 Y 10,672,948.5268
 Delta = 5° 33' 31.20" (RT)
 Degree = 19° 05' 54.94"
 Tangent = 14.5640
 Length = 29.1051
 Radius = 300.0000
 External = 0.3533
 Long Chord = 29.0937
 Mid. Ord. = 0.3529
 P.C. Station = 403+21.09 X 3,000,388.7615 Y 10,672,960.9335
 P.T. Station = 403+50.20 X 3,000,402.7796 Y 10,672,935.4397
 C.C. = X 3,000,133.1998 Y 10,672,803.8087
 Back = S 31° 35' 02.74" E
 Ahead = S 26° 01' 31.54" E
 Chord Bear = S 28° 48' 17.14" E

Course from PT CR238_1 to PC CR238_2 S 26° 01' 31.54" E Dist 169.7021

Curve Data

Curve CR238_2
 P.I. Station = 405+32.81 X 3,000,482.9065 Y 10,672,771.3400
 Delta = 9° 50' 31.54" (RT)
 Degree = 38° 11' 49.87"
 Tangent = 12.9150
 Length = 25.7665
 Radius = 150.0000
 External = 0.5550
 Long Chord = 25.7349
 Mid. Ord. = 0.5529
 P.C. Station = 405+19.90 X 3,000,477.2398 Y 10,672,782.9455
 P.T. Station = 405+45.67 X 3,000,486.5061 Y 10,672,758.9367
 C.C. = X 3,000,342.4499 Y 10,672,717.1300
 Back = S 26° 01' 31.54" E
 Ahead = S 16° 11' 00.00" E
 Chord Bear = S 21° 06' 15.77" E

Course from PT CR238_2 to PC CR238_3 S 16° 11' 00.00" E Dist 238.1737

Curve Data


Curve CR238_3
 P.I. Station = 407+88.48 X 3,000,554.1819 Y 10,672,525.7421
 Delta = 1° 03' 50.32" (LT)
 Degree = 11° 27' 32.96"
 Tangent = 4.6426
 Length = 9.2849
 Radius = 500.0000
 External = 0.0216
 Long Chord = 9.2848
 Mid. Ord. = 0.0216
 P.C. Station = 407+83.84 X 3,000,552.8879 Y 10,672,530.2007
 P.T. Station = 407+93.12 X 3,000,555.5584 Y 10,672,521.3082
 C.C. = X 3,001,033.0753 Y 10,672,669.5566
 Back = S 16° 11' 00.00" E
 Ahead = S 17° 14' 50.32" E
 Chord Bear = S 16° 42' 55.16" E

Course from PT CR238_3 to CR23811 S 17° 14' 50.32" E Dist 45.8980

Point CR23811 X 3,000,569.1670 Y 10,672,477.4740 Sta 408+39.02

Ending chain CR238 description


PRINT DATE	REVISION DATE
2/8/2023	



JOSE M. SANDOVAL
 PROFESSIONAL ENGINEER
 90593


Jose M. Sandoval
 JOSE M. SANDOVAL
 DATE 2/8/2023

3711 SOUTH MOPAC EXPRESSWAY
 BUILDING ONE, SUITE 350
 AUSTIN, TX 78703
 TEL 512.494.6037 FAX 317.543.0270
 www.structurepoint.com



STRUCTUREPOINT
 INC.

TBPE FIRM NO. F-10069




Texas Department of Transportation ©2023


**CR 238 (HCR 207) AT HONEY CREEK
 HORIZONTAL ALIGNMENT DATA**

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	24

100% SUBMITTAL




ROW DATA			
LOCATION	STATION	CL OFFSET (FT)	
1	402+70.00	22.61	RT
2	403+21.09	39.00	RT
3	403+50.20	39.00	RT
4	405+19.90	39.00	RT
5	405+45.67	39.00	RT
6	406+00.00	39.00	RT
7	406+70.00	22.33	RT
8	406+70.00	17.91	LT
9	406+00.00	39.00	LT
10	405+45.67	39.00	LT
11	405+19.90	39.00	LT
12	403+50.00	39.00	LT
13	403+21.09	39.00	LT
14	402+70.00	20.50	LT



- LEGEND**
- [Grey fill] PROPOSED ROAD
 - [Dark Grey fill] PROPOSED BRIDGE
 - [Stippled pattern] STONE RIPRAP (18 IN)
 - [Hatched pattern] CHANNEL EXCAVATION
 - (A) MTL W-BEAM GD FEN (STL POST)
 - (B) GUARDRAIL END TREATMENT (INSTALL)
 - (C) MBGF TRANS (TL2)
 - (D) MBGF TRANS (NON-SYM)
 - (E) DOWNSTREAM ANCHOR TERMINAL SECTION
 - [Symbol] DEL ASSM (D-SW) SZ (BRF) GF2 (BI)
 - [Symbol] DEL ASSM (D-SW) SZ (BRF) CTB (BI)

PRINT DATE	REVISION DATE
2/13/2023	



J. Sandoval
JOSE M. SANDOVAL
DATE: 2/13/2023

3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com
TBPE FIRM NO. F-10069

STRUCTUREPOINT
INC.




CR 238 (HCR 207) AT HONEY CREEK
PLAN AND PROFILE

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER
6		CR
STATE	DISTRICT	COUNTY
TEXAS	WACO	HAMILTON
CONTROL	SECTION	JOB SHEET NO.
0909	29	046 25



CSJ: 0909-29-046
 FILE LOCATION: P:\2020\0007\090929046\4 - Design\Plan Set\3. Roadway\2020007\204.RD.PP.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/21/2023 3:16:05 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\roadway\BED-14.dgn



- GENERAL NOTES**
- For more detail: See GF(31), SGT()31, GF(31)TR, and GF(31)TL2 standard sheets.
 - Quantities of metal beam guard fence (MBGF) at individual bridge ends are as shown in the plans.
 - Use average daily traffic (ADT) for the current year to determine MBGF length of need in accordance with the Roadway Design Manual unless otherwise specified. Where significant traffic volume growth is anticipated on low volume (0-750 ADT) highways, use length determinations for the higher volume category.
 - MBGF may not be required to shield departure end of bridge unless other obstacles within the horizontal clearance limits or opposing traffic indicate a MBGF consideration.
 - Downstream anchor terminals (DAT) are only for downstream end anchorage use, outside the horizontal clearance area of opposing traffic.
 - Direct connection of MBGF to concrete rails are only for downstream rail connections outside the horizontal clearance area of opposing traffic. (This requires a minimum of three standard line posts plus the DAT terminal, See Detail A)
 - The crown shall be widened to accommodate MBGF. Typically the "front slope" break should be 2'-0" from the back of the MBGF post. This applies to new construction on new alignment or where existing roadway cross section is to be widened to increase roadway width. This does not apply to rehabilitation work where existing roadway crown width is to be retained (See Typical Cross Section at MBGF).
 - For restrictive bridge widths: The MBGF should be properly transitioned from the existing bridge rail to the adjoining MBGF (See MBGF Transition Standards). Metal beam guard fence at these bridge location(s) shall be flared at the rate of 25:1 or flatter, and be of the length necessary to locate the terminal end at the 2 ft. "maximum" offset from the shoulder edge in the approach direction.
 - Transition length and post spacing will vary depending on the transition type. Transition type will be shown elsewhere in the plans.
 - A minimum 25' length of MBGF will be required.



Note: All rail elements shall be lapped in the direction of adjacent traffic.


Texas Department of Transportation Design Division Standard

BRIDGE END DETAILS
 (METAL BEAM GUARD FENCE APPLICATIONS TO RIGID RAILS)


BED-14

FILE: bed14.dgn	DN: TxDOT	CK: AM	DW: BD/VP	CK: CGL
© TxDOT: December 2011	CONT	SECT	JOB	HIGHWAY
REVISED APRIL 2014 SEE (MEMO 0414)	0909	29	046	CR
	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	26	

DATE: 2/8/2023
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\roadway\GF (31) -19.dgn
 DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.




TYPICAL POST PLACEMENT




WOOD BLOCK TO ROUND WOOD POST **ROUTED WOOD BLOCK TO I-BEAM STEEL POST**

- GENERAL NOTES**
1. THE TYPE OF POST (ROUND WOOD POST, RECTANGULAR WOOD POST, OR STEEL POST) WILL BE AS SHOWN IN THE PLANS. THE EXACT POSITION OF MBGF SHALL BE SHOWN IN THE PLANS OR AS DIRECTED BY THE ENGINEER. STEEL POSTS TO BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING."
 2. RAIL ELEMENTS SHALL MEET THE REQUIREMENTS OF ITEM 540, "METAL BEAM GUARD FENCE" EXCEPT AS MODIFIED IN THE PLANS. THE CONTRACTOR MAY FURNISH RAIL ELEMENTS OF 25'-0", OR 12'-6" (NOM.) LENGTHS. RAIL ELEMENTS MAY HAVE SLOTTED HOLES AT 3'-1 1/2" C-C OR 6'-3" C-C. A SPECIAL LENGTH OF RAIL MAY BE MANUFACTURED TO ACCOMMODATE THE DOWNSTREAM ANCHOR TERMINAL (DAT) AND THE TRANSITION SECTIONS OF GUARDRAIL.
 3. BUTTON HEAD "POST BOLTS & NUTS" SHALL MEET THE REQUIREMENTS OF (ASTM A307), AND SHALL BE OF SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND 5/8" WASHER (FWC16d) AND NOT MORE THAN 1" BEYOND IT. TRIM REMAINING BOLT LENGTH TO MEET REQUIRED LENGTH.
 4. FITTINGS (BOLTS, NUTS, AND WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING." FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
 5. CROWN SHALL BE WIDENED TO ACCOMMODATE THE METAL BEAM GUARD FENCE.
 6. THE LATERAL APPROACH TO THE GUARD FENCE, SHALL HAVE A MAXIMUM SLOPE OF 1V:10H.
 7. IF SHOWN ELSEWHERE IN THE PLANS OR AS DIRECTED BY THE ENGINEER, THE GUARD FENCE MAY BE FLARED AT A RATE OF 25:1 OR FLATTER.
 8. UNLESS OTHERWISE SHOWN IN THE PLANS, GUARD FENCE PLACED IN THE VICINITY OF CURBS SHALL BE POSITIONED SO THAT THE FACE OF CURB IS LOCATED DIRECTLY BELOW OR BEHIND THE FACE OF THE RAIL. RAIL PLACED OVER CURBS SHALL BE INSTALLED SO THAT THE POST BOLT IS LOCATED APPROXIMATELY 25 INCHES ABOVE THE GUTTER PAN OR EDGE OF SHOULDER.
 9. APPLICATIONS IN SOLID ROCK ARE ONLY ALLOWED WITH STEEL POSTS. IF SOLID ROCK IS ENCOUNTERED WITHIN 0 TO 18" OF THE FINISHED GRADE, DRILL A 24" DIA. HOLE, 24" INTO THE ROCK. IF SOLID ROCK IS ENCOUNTERED BELOW 18", DRILL A 12" DIA. HOLE, 12" INTO THE ROCK OR TO THE STANDARD EMBEDMENT DEPTH, WHICHEVER MAYBE LESS. ANY EXCESS POST LENGTH, AFTER MEETING THESE DEPTHS, MAY BE FIELD CUT TO ENSURE PROPER GUARDRAIL MOUNTING HEIGHT. BACKFILL WITH COARSE AGGREGATE MATERIAL.
 10. POSTS SHALL NOT BE SET IN CONCRETE, OF ANY DEPTH.
 11. SPECIAL FABRICATION WILL BE REQUIRED AT INSTALLATION LOCATIONS HAVING A CURVATURE OF LESS THAN 150 FT. RADIUS.
 12. UNLESS OTHERWISE SHOWN IN THE PLANS, A COMPOSITE MATERIAL BLOCK THAT MEETS THE REQUIREMENTS OF DMS-7210, "COMPOSITE MATERIAL POSTS AND BLOCKS FOR METAL BEAM GUARD FENCE" MAY BE SUBSTITUTED FOR BLOCKS OF SIMILAR DIMENSIONS. THE CONSTRUCTION DIVISION, TXDOT MAINTAINS A MATERIAL PRODUCER LIST (MPL) FOR PRODUCERS OF MATERIALS CONFORMING TO DMS-7210 ONLY PRODUCERS ON THE MPL MAY FURNISH COMPOSITE MATERIAL BLOCKS.
 - 13.




ELEVATION MID-SPAN RAIL SPLICE

NOTE: ** "WOOD" INDICATES DIMENSIONS FOR BOTH ROUND AND RECTANGULAR WOOD POST SYSTEMS.




ELEVATION 25'-0" (NOM.) W-BEAM SECTION

NOTES: SEE GENERAL NOTE 2 FOR ALLOWABLE RAIL TYPES. SEE RAIL SPLICE DETAIL FOR REQUIRED HARDWARE.



BUTTON HEAD BOLT


NOTE: SEE GENERAL NOTE 3 FOR SPLICE & POST BOLT DETAILS.



MID-SPAN RAIL SPLICE DETAIL

NOTE: GF(31), MID-SPAN RAIL SPLICES ARE REQUIRED WITH 6'-3" POST SPACINGS.

* POST(S) MAY REQUIRE FIELD MODIFICATION TO ENSURE PROPER GUARDRAIL HEIGHT.



LOW FILL CULVERT POST

- NOTE: TWO INSTALLATION OPTIONS.
1. **BOLT-THROUGH OPTION:** REQUIRES A 6" MIN. SLAB THICKNESS. 7/8" DIA (ASTM A449) HEAVY HEX BOLTS WITH TWO HARDENED WASHER EACH AND HEAVY HEX NUTS. NOTE: BOLT LENGTH = SLAB PLUS 2 1/4" MIN.
 2. **EPOXY ANCHOR OPTION:** THIS OPTION MAY ONLY BE USED IF THE CULVERT SLAB IS 9" MIN. THICK. THREADED ANCHOR RODS MUST BE 7/8" DIA. ASTM A449 OR A193 GRADE B7 WITH HEAVY HEX NUT, AND ONE HARDENED WASHER EACH. EMBED ANCHOR RODS 6" WITH HILTI HIT RE 500 EPOXY ADHESIVE. OTHER TYPE III CLASS C EPOXY ADHESIVES MEETING THE REQUIREMENTS OF DMS-6100, "EPOXIES AND ADHESIVES", MAY BE USED IF IT CAN BE DEMONSTRATED THAT THEY MEET OR EXCEED THE STRENGTH OF HILTI HIT RE 500 WITH THE SAME EMBEDMENT DEPTH AND THREADED ROD DIA. FOLLOW THE MANUFACTURER'S REQUIREMENTS FOR INSTALLING EPOXIED THREADED RODS. EXTEND RODS 1/4" MIN. BEYOND NUT.

NOTE: CULVERTS OF 25 FT. OR LESS, SEE GF(31)LS STANDARD FOR "LONG SPAN" OPTION.




**METAL BEAM GUARD FENCE
TL-3 MASH COMPLIANT
GF (31) -19**

FILE: gf3119.dgn	DN: TXDOT	CK: KM	DW: VP	CK: CGL/AG
© TXDOT: NOVEMBER 2019	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	27	

DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.




DATE: 2/8/2023 1:38:16 PM
 FILE: T:\Road_Dept\Department\Team Texas\txdot_cadd_standard\roadway\GF (31) TR TL2-19.dgn



- (5) 7/8" DIA. HEAVY HEX HEAD BOLTS (ASTM A325 OR A449)
 - (10) 1 3/4" O.D. WASHER UNDER EACH HEX BOLT HEAD AND NUT.
 - (5) 7/8" DIA. HEAVY HEX NUTS (ASTM A194 OR A563)
- THRIE-BEAM CONNECTOR TO CONCRETE RAIL

NOTE: HEAVY HEX BOLT LENGTH WILL VARY DEPENDING ON WIDTH CONCRETE RAIL, LEAVE 1" OF BOLT LENGTH PAST THE 7/8" HEX NUT. TRIM AS REQUIRED.

NOTE: CHAMFER REQUIRED ON CONCRETE RAILS THAT EXTEND BEYOND THE FACE OF GUARDRAIL TRANSITION.








- (2) 5/8" BUTTON HEAD POST BOLTS & NUTS: (FBB04)
- (1) 5/8" FLAT WASHER: (FWC14a) UNDER EACH NUT

- (1) 5/8" BUTTON HEAD POST BOLT & NUT: (FBB04)
- (1) 5/8" FLAT WASHER: (FWC14a) UNDER EACH NUT

BRIDGE APPROACH - UPSTREAM: THE SHORT RAIL LAPS OVER THE TERMINAL CONNECTOR. PLATE WASHERS ARE INSTALLED UNDER THE SPLICE NUTS AGAINST INSIDE OF CONNECTOR.

BRIDGE EXIT - DOWNSTREAM: THE TERMINAL CONNECTOR LAPS OVER THE NESTED RAIL. PLATE WASHERS ARE INSTALLED UNDER THE BOLT HEAD AGAINST OUTSIDE OF CONNECTOR.

PLATE WASHER INSTRUCTIONS



NOTE: * "WOOD" INDICATES DIMENSIONS FOR BOTH ROUND AND RECTANGULAR WOOD POST SYSTEMS.


GENERAL NOTES

1. THE TYPE OF POST (ROUND WOOD POST, RECTANGULAR WOOD POST, OR STEEL POST) WILL BE AS SHOWN IN THE PLANS. THE EXACT POSITION OF TRANSITIONS SHALL BE AS SHOWN IN THE PLANS OR AS DIRECTED BY THE ENGINEER. REFER TO GF (31) STANDARD SHEET.
2. RAIL ELEMENT SHALL MEET THE REQUIREMENTS OF ITEM 540, "METAL BEAM GUARD FENCE" EXCEPT AS MODIFIED IN THE PLANS.
3. FITTINGS (BOLTS, NUTS, AND WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING." FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM REQUIRING CONSTRUCTION OF THE TRANSITION.
4. BUTTON HEAD "POST BOLTS & NUTS" SHALL MEET THE REQUIREMENTS OF (ASTM A307), AND SHALL BE OF SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND 5/8" WASHER (FWC16a) AND NOT MORE THAN 1" BEYOND IT. TRIM BOLT LENGTH TO MEET REQUIRED LENGTH.
5. POSTS SHALL NOT BE SET IN CONCRETE, OF ANY DEPTH.
6. CROWN SHALL BE WIDENED TO ACCOMMODATE TRANSITIONS.
7. WHERE SOLID ROCK IS ENCOUNTERED, CONTACT THE DESIGN DIVISION FOR ADDITIONAL GUIDANCE. (512) 416-2678
8. UNLESS OTHERWISE SHOWN IN THE PLANS, A COMPOSITE MATERIAL BLOCK THAT MEETS THE REQUIREMENTS OF DMS-7210, "COMPOSITE MATERIAL POSTS AND BLOCKS FOR METAL BEAM GUARD FENCE" MAY BE SUBSTITUTED FOR BLOCKS OF SIMILAR DIMENSIONS. THE CONSTRUCTION DIVISION, TXDOT, MAINTAINS A MATERIAL PRODUCER LIST (MPL) FOR PRODUCERS OF MATERIALS CONFORMING TO DMS-7210. ONLY PRODUCERS ON THE MPL CAN FURNISH COMPOSITE MATERIAL BLOCKS.
9. REFER TO GF (31) STANDARD SHEET & BRIDGE RAILING DETAILS FOR ADDITIONAL DETAILS.
10. FOR ROUND WOOD POSTS SYSTEMS, ALL ROUND WOOD POSTS SHALL BE 7 1/2" DIA. MINIMUM THROUGHOUT THE TRANSITION.

LOW-SPEED TRANSITION

				Design Division Standard
METAL BEAM GUARD FENCE THRIE-BEAM TRANSITION TL-2 MASH COMPLIANT GF (31) TR TL2-19				
FILE: gf31tr+1219.dgn	DN: TxDOT	CK: KM	DW: VP	CK: CGL/AG
© TXDOT: NOVEMBER 2019		CONT	SECT	JOB
REVISIONS		0909	29	046
DIST	COUNTY	SHEET NO.		
WACO	HAMILTON	28		

DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.



- ### GENERAL NOTES
1. THE DETAIL SHOWN IS THE MINIMUM LENGTH OF NEED (LON) FOR A DOWNSTREAM ANCHOR TERMINAL (DAT) CONNECTED TO A CONCRETE RAIL.
 2. THE RAIL SECTION AT THE END POST IS SUPPORTED BY THE SHELF ANGLE BRACKET. THE RAIL ELEMENT IS NOT ATTACHED TO THE END POST.
 3. THE FOUNDATION TUBES SHALL NOT PROJECT MORE THAN 3 3/4" ABOVE THE FINISHED GRADE.
 4. ALL HARDWARE FOR DAT SHALL BE ASTM A307 UNLESS OTHERWISE SHOWN.
 5. REFER TO GF(31) SHEET FOR TERMINAL CONNECTION DETAILS.







MOW STRIP INSTALLATION

IF A MOW STRIP IS REQUIRED WITH THE DAT INSTALLATION THE LEAVE-OUT AREA AROUND THE STEEL FOUNDATION TUBES AND THE TWO CHANNEL STRUTS MAY BE OMITTED. THIS WILL REQUIRE A FULL POUR AT THE FOUNDATION TUBES.

DOWNSTREAM ANCHOR TERMINAL (DAT)

NOTE: ONLY FOR DOWNSTREAM USE, WHEN LOCATED OUTSIDE THE HORIZONTAL CLEARANCE AREA OF OPPOSING TRAFFIC.

#	(DAT) PARTS LIST	QTY
1	STEEL FOUNDATION TUBE	2
2	DAT TERMINAL POST	2
3	CHANNEL STRUT	2
4	TERMINAL RAIL ELEMENT	1
5	SHELF ANGLE BRACKET	1
6	BCT BEARING PLATE	1
7	BCT POST SLEEVE	1
8	GUARDRAIL ANCHOR BRACKET	1
9	(ROUNDED) W-BEAM END SECTION	1
10	BCT CABLE ANCHOR	1
11	RECESSED NUT, GUARDRAIL	20
12	1 1/4" BUTTON HEAD BOLT	4
13	10" BUTTON HEAD BOLT	2
14	5/8" X 2" HEX HEAD BOLT	8
15	5/8" X 8" HEX HEAD BOLT	4
16	5/8" X 10" HEX HEAD BOLT	2
17	5/8" FLAT WASHER	18




Design Division Standard

METAL BEAM GUARD FENCE (DOWNSTREAM ANCHOR TERMINAL) TL-3 MASH COMPLIANT GF (31) DAT-19

FILE: gf31dat19.dgn	DN: TXDOT	CK: KM	DW: VP	CK: CGL/AG
© TXDOT: NOVEMBER 2019 REVISIONS	CONT: 0909	SECT: 29	JOB: 046	HIGHWAY: CR
	DIST: WACO	COUNTY: HAMILTON	SHEET NO. 29	


DATE: 2/8/2023
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\roadway\SGT (11S)18\sgt.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.







- NOTES:
- ITEM ② COMPOSITE BLOCKOUTS INSTALLED AT LINE POST (9) THRU LINE POST (2).
 - DO NOT INSTALL A BLOCKOUT AT LINE POST (1).

NOTE: RECESSED HEX NUTS FACING TRAFFIC-SIDE SEE DETAIL (C)



NOTE: SECURE THE (TSS) PANEL TO OUTSIDE OF RAIL 2 WITH THE PANEL ARROWS POINTING TOWARDS THE HEAD.



- GENERAL NOTES**
- FOR SPECIFIC INFORMATION REGARDING INSTALLATION AND TECHNICAL GUIDANCE OF THE SYSTEM, CONTACT: LINDSAY TRANSPORTATION SOLUTIONS (LTS) - BARRIER SYSTEMS, INC. AT (707) 374-6800
 - FOR INSTALLATION, REPAIR, & MAINTENANCE REFER TO THE: MAX-TENSION INSTALLATION INSTRUCTION MANUAL. P/N MANMAX REV D (ECN 3516).
 - APPLY HIGH INTENSITY REFLECTIVE SHEETING, "OBJECT MARKER" ON THE FRONT FACE OF THE DEVICE PER MANUFACTURER'S RECOMMENDATIONS. OBJECT MARKER SHALL CONFORM TO THE STANDARDS REQUIRED IN TEXAS MUTCD.
 - FOR POST (LEAVE-OUT) INSTALLATION AND GUIDANCE SEE TXDOT'S LATEST ROADWAY MOW STRIP STANDARD.
 - ALL STEEL COMPONENTS ARE GALVANIZED PER ASTM A123 OR EQUIVALENT UNLESS OTHERWISE STATED.
 - SYSTEM SHOWN USING STEEL WIDE FLANGE POST WITH COMPOSITE BLOCKOUTS.
 - COMPOSITE MATERIAL BLOCKOUT THAT MEETS THE REQUIREMENTS OF DMS-7210, MAY BE SUBSTITUTED FOR BLOCKOUTS SIMILAR DIMENSIONS. SEE CONSTRUCTION DIVISION MATERIAL PRODUCER LIST (MPL) FOR CERTIFIED PRODUCERS.
 - REFER TO INSTALLATION MANUAL FOR SPECIFIC PANEL LAPPING GUIDANCE.
 - IF SOLID ROCK IS ENCOUNTERED SEE THE MANUFACTURER'S INSTALLATION MANUAL FOR INSTALLATION GUIDANCE.
 - POSTS SHALL NOT BE SET IN CONCRETE.
 - A DRIVING CAP WITH A TIMBER OR PLASTIC INSERT SHALL BE USED WHEN DRIVING POST TO PREVENT DAMAGE TO THE GALVANIZING ON TOP OF THE POST.
 - MAX-TENSION SYSTEM SHALL NEVER BE INSTALLED WITHIN A CURVED SECTION OF GUARDRAIL.
 - IF A DELINEATION MARKER IS REQUIRED, MARKER SHALL BE IN ACCORDANCE WITH TEXAS MUTCD.
 - THE SYSTEM IS SHOWN WITH 12'-6" MBGF PANELS, 25'-0" MBGF PANELS ARE ALSO ALLOWED.
 - A MINIMUM OF 12'-6" OF 12GA. MBGF IS REQUIRED IMMEDIATELY DOWNSTREAM OF THE MAX-TENSION SYSTEM.



ITEM#	PART NUMBER	DESCRIPTION	QTY
1	BSI-1610060-00	SOIL ANCHOR - GALVANIZED	1
2	BSI-1610061-00	GROUND STRUT - GALVANIZED	1
3	BSI-1610062-00	MAX-TENSION IMPACT HEAD	1
4	BSI-1610063-00	W6x9 I-BEAM POST 6FT.-GALVANIZED	1
5	BSI-1610064-00	TSS PANEL - TRAFFIC SIDE SLIDER	1
6	BSI-1610065-00	ISS PANEL - INNER SIDE SLIDER	1
7	BSI-1610066-00	TOOTH - GEOMET	1
8	BSI-1610067-00	RSS PLATE - REAR SIDE SLIDER	1
9	B061058	CABLE FRICTION PLATE - HEAD UNIT	1
10	BSI-1610069-00	CABLE ASSEMBLY - MASH X-TENSION	2
11	BSI-1012078-00	X-LITE LINE POST-GALVANIZED	8
12	B090534	8" W-BEAM COMPOSITE-BLOCKOUT XT110	8
13	BSI-4004386	12'-6" W-BEAM GUARD FENCE PANELS 12GA.	4
14	BSI-1102027-00	X-LITE SQUARE WASHER	1
15	BSI-2001886	5/8" X 7" THREAD BOLT HH (GR.5)GEOMET	1
16	BSI-2001885	3/4" X 3" ALL-THREAD BOLT HH (GR.5)GEOMET	4
17	4001115	5/8" X 1 1/4" GUARD FENCE BOLTS (GR.2)MGAL	48
18	2001840	5/8" X 10" GUARD FENCE BOLTS MGAL	8
19	2001636	5/8" WASHER F436 STRUCTURAL MGAL	2
20	4001116	5/8" RECESSED GUARD FENCE NUT (GR.2)MGAL	59
21	BSI-2001888	5/8" X 2" ALL THREAD BOLT (GR.5)GEOMET	1
22	BSI-1701063-00	DELINEATION MOUNTING (BRACKET)	1
23	BSI-2001887	1/4" X 3/4" SCREW SD HH 410SS	7
24	4002051	GUARDRAIL WASHER RECT AASHTO FWRO3	1
25	SEE NOTE BELOW	HIGH INTENSITY REFLECTIVE SHEETING	1
26	4002337	8" W-BEAM TIMBER-BLOCKOUT, PDB01B	8
27	BSI-4004431	25' W-BEAM GUARDRAIL PANEL, 8-SPACE, 12GA.	2
28	MANMAX Rev- (D)	MAX-TENSION INSTALLATION INSTRUCTIONS	1



NOTE: TXDOT GENERIC APPROACH GRADING LAYOUT USED FOR ALL TANGENT TYPE END TREATMENTS.

- * TO BE PROVIDED BY DISTRIBUTOR OR CONTRACTOR.
- ** ALTERNATIVE ITEMS NOT SHOWN. ITEM (26) 8" WOOD-BLOCKOUTS ITEM (27) 25' GUARD FENCE PANELS


NOTE: THIS STANDARD IS A BASIC REPRESENTATION OF THE MAX-TENSION END TERMINAL, IT IS NOT INTENDED TO REPLACE THE PRODUCT DESCRIPTION ASSEMBLY MANUAL.

MAX-TENSION END TERMINAL
MASH - TL-3
SGT (11S) 31-18

FILE: sg11s3118.dgn	DN: TxDOT	CK: KM	DW: TxDOT	CK: CL
© TxDOT: FEBRUARY 2018	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DIST	COUNTY		SHEET NO.	
WACO	HAMILTON		30	

DISCLAIMER: THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.



DATE: 2/8/2023
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standard\roadway\SGT(12S)31-18.dgn




- NOTES:
- ITEM (M) COMPOSITE BLOCKOUTS INSTALLED AT LINE POST (8) THRU LINE POST (3).
 - ITEM (P) WOOD BLOCKOUTS CAN BE USED AS ALTERNATE.

- GENERAL NOTES**
- FOR SPECIFIC INFORMATION REGARDING INSTALLATION AND TECHNICAL GUIDANCE OF THE SYSTEM, CONTACT: ROAD SYSTEMS, INC. (432)263-2435. 3616 OLD HOWARD COUNTY AIRPORT, BIG SPRING, TX 79720
 - FOR INSTALLATION, REPAIR AND MAINTENANCE REFER TO THE: MSKT END TERMINAL, PRODUCT DESCRIPTION ASSEMBLY MANUAL (PUBLICATION-062717).
 - APPLY HIGH INTENSITY REFLECTIVE SHEETING, "OBJECT MARKER" ON THE FRONT FACE OF THE DEVICE PER MANUFACTURER'S RECOMMENDATIONS. OBJECT MARKER SHALL CONFORM TO THE STANDARDS REQUIRED IN TEXAS MUTCD.
 - FOR POST (LEAVE-OUT) INSTALLATION AND GUIDANCE SEE TXDOT'S LATEST ROADWAY MOW STRIP STANDARD.
 - HARDWARE (BOLTS, NUTS, & WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING". FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
 - SYSTEM SHOWN USING STEEL WIDE FLANGE POSTS WITH COMPOSITE BLOCKOUTS.
 - A COMPOSITE MATERIAL BLOCKOUTS THAT MEETS THE REQUIREMENTS OF DMS-7210, MAY BE SUBSTITUTED FOR BLOCKOUTS OF SIMILAR DIMENSIONS. SEE CONSTRUCTION DIVISION MATERIAL PRODUCER LIST (MPL) FOR CERTIFIED PRODUCERS.
 - IF SOLID ROCK IS ENCOUNTERED IN THE AREA OF (POST 1) AND / OR (POST 2) CONTACT THE MANUFACTURER, & REFER TO THE LATEST ROADWAY MBSG STANDARD FOR INSTALLATION GUIDANCE.
 - POSTS SHALL NOT BE SET IN CONCRETE.
 - SYSTEM MUST BE ATTACHED TO STANDARD 31" MBSG.
 - UNDER NO CIRCUMSTANCES SHALL THE GUARDRAIL WITHIN THE MSKT SYSTEM BE CURVED.
 - A FLARE RATE OF UP TO 25:1 MAY BE USED TO PREVENT THE TERMINAL HEAD FROM ENCRANCHING ON THE SHOULDER. THE FLARE MAY BE DECREASED OR ELIMINATED FOR SPECIFIC INSTALLATIONS, IF DIRECTED BY THE ENGINEER.
 - THE SYSTEM IS SHOWN WITH TWO 12'-6" MBSG PANELS, ONE 25'-0" MBSG PANEL IS ALSO ALLOWED IN ITS PLACE.
 - A DRIVING CAP WITH A TIMBER OR PLASTIC INSERT SHALL BE USED WHEN DRIVING POSTS 3-8 TO PREVENT DAMAGE TO THE GALVANIZING ON TOP OF THE POST. SPECIAL DRIVING CAP TO BE USED ON LOWER POSTS 1 & 2 TO PREVENT DAMAGE TO THE WELDED PLATES.

ITEM	QTY	MAIN SYSTEM COMPONENTS	ITEM NUMBERS
A	1	MSKT IMPACT HEAD	MS3000
B	1	W-BEAM GUARDRAIL END SECTION, 12 Ga.	SF1303
C	1	POST 1 - TOP (6" X 6" X 1/8" TUBE)	MTPHP1A
D	1	POST 1 - BOTTOM (6' W6X15)	MTPHP1B
E	1	POST 2 - ASSEMBLY TOP	UHP2A
F	1	POST 2 - ASSEMBLY BOTTOM (6' W6X9)	HP2B
G	1	BEARING PLATE	E750
H	1	CABLE ANCHOR BOX	S760
J	1	BCT CABLE ANCHOR ASSEMBLY	E770
K	1	GROUND STRUT	MS785
L	6	W6X9 OR W6X8.5 STEEL POST	P621
M	6	COMPOSITE BLOCKOUTS	CBSP-14
N	1	W-BEAM MGS RAIL SECTION (9'-4 1/2")	G12025
O	2	W-BEAM MGS RAIL SECTION (12'-6")	G1203A
P	6	WOOD BLOCKOUT 6" X 8" X 14"	P675
Q	1	W-BEAM MGS RAIL SECTION (25'-0")	G1209
SMALL HARDWARE			
a	2	5/16" x 1" HEX BOLT (GRD 5)	B5160104A
b	4	5/16" WASHER	W0516
c	2	5/16" HEX NUT	N0516
d	25	5/8" Dia. x 1 1/4" SPLICE BOLT (POST 2)	B580122
e	2	5/8" Dia. x 9" HEX BOLT (GRD A449)	B580904A
f	3	5/8" WASHER	W050
g	33	5/8" Dia. H.G.R NUT	N050
h	1	3/4" Dia. x 8 1/2" HEX BOLT (GRD A449)	B340854A
j	1	3/4" Dia. HEX NUT	N030
k	2	1 ANCHOR CABLE HEX NUT	N100
l	2	1 ANCHOR CABLE WASHER	W100
m	8	1/2" x 1 1/4" A325 BOLT WITH CAPTIVE WASHER	SB12A
n	8	1/2" STRUCTURAL NUTS	N012A
o	8	1 1/16" O.D. x 3/16" I.D. STRUCTURAL WASHERS	W012A
p	1	BEARING PLATE RETAINER TIE	CT-100ST
q	6	5/8" x 10" H.G.R. BOLT	B581002
r	1	OBJECT MARKER 18" X 18"	E3151



ALTERNATIVE ITEMS NOT SHOWN. * *
 * ITEM (P) 8" WOOD-BLOCKOUT
 * * ITEM (Q) 25' GUARD FENCE PANEL



NOTE: TXDOT GENERIC APPROACH GRADING LAYOUT USED FOR ALL TANGENT TYPE END TREATMENTS.

NOTE: THIS STANDARD IS A BASIC REPRESENTATION OF THE MSKT END TERMINAL, IT IS NOT INTENDED TO REPLACE THE PRODUCT DESCRIPTION ASSEMBLY MANUAL.

Design Division Standard








SINGLE GUARDRAIL TERMINAL

MSKT-MASH-TL-3

SGT (12S) 31-18


FILE: sgt12s3118.dgn	DN: TXDOT	CK: KM	DW: VP	CK: CL
© TXDOT: APRIL 2018	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	31	

DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.



- ### GENERAL NOTES
- FOR SPECIFIC INFORMATION REGARDING INSTALLATION AND TECHNICAL GUIDANCE OF THE SYSTEM, CONTACT: SPIG INDUSTRY, INC. AT 1(267) 644-9510. 14675 INDUSTRIAL PARK RD; BRISTOL, VA 24202
 - FOR INSTALLATION, REPAIR AND MAINTENANCE REFER TO THE MANUFACTURER'S; SGET END TERMINAL, PRODUCT DESCRIPTION ASSEMBLY MANUAL.
 - MANUFACTURER WILL APPLY HIGH INTENSITY REFLECTIVE SHEETING, "OBJECT MARKER" TO THE FACE PLATE OF THE DEVICE PER MANUFACTURER'S RECOMMENDATIONS. THE OBJECT MARKER SHALL CONFORM TO THE STANDARDS REQUIRED IN TEXAS MUTCD.
 - THE NOMINAL HEIGHT OF THE GUARDRAIL BEAM IS 31 INCHES WITH A TOLERANCE OF +/- ONE INCH.
 - FOR POST (LEAVE-OUT) INSTALLATION AND GUIDANCE SEE TXDOT'S LATEST ROADWAY MOW STRIP STANDARD.
 - (POST 2 THROUGH POST 8) ARE MODIFIED STEEL-YIELDING POSTS WITH YIELDING HOLES AT GROUND LEVEL. THERE ARE NO SUBSTITUTE POSTS.
 - POSTS SHALL NOT BE SET IN CONCRETE.
 - IF SOLID ROCK IS ENCOUNTERED FOR ANY OF THE POSTS IN THE SYSTEM, CONTACT THE MANUFACTURER FOR SPECIFIC INSTALLATION GUIDANCE.
 - HARDWARE (BOLTS, NUTS, & WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING". FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
 - A COMPOSITE MATERIAL BLOCKOUT THAT MEETS DMS-7210 REQUIREMENTS MAY BE SUBSTITUTED FOR AN APPROVED WOOD BLOCKOUT. SEE CONSTRUCTION DIVISION MATERIAL PRODUCER LIST (MPL) FOR CERTIFIED PRODUCERS.
 - THE ENTIRE SYSTEM MUST BE INSTALLED IN A STRAIGHT LINE WITHOUT ANY CURVE. HOWEVER, THE SYSTEM CAN BE OFFSET BY TWO FEET AS SHOWN ON THE APPROACH GRADING DETAIL TO HELP OFF-SET THE IMPACT HEAD FROM SHOULDER OF THE ROAD.

ITEM	QTY	MAIN SYSTEM COMPONENTS	ITEM #
A	1	SGET IMPACT HEAD	SIH1A
B	1	MODIFIED GUARDRAIL PANEL 12'-6" 12GA	126SPZGP
B2	1	MODIFIED GUARDRAIL PANEL 9'-4 1/2" 12GA	GP94
C	2	STANDARD GUARDRAIL PANEL 12'-6" 12GA	GP126
D	1	STANDARD GUARDRAIL PANEL 25'-0" 12GA	GP25
E	7	MODIFIED YIELDING I-BEAM POST W6x8.5	YP6MOD
F	6	COMPOSITE BLOCKOUT 6" X 8" X 14"	CBO8
G	6	WOOD BLOCKOUT 6" X 8" X 14"	WB08
H	1	STRUT 3" X 3" X 80" X 1/4" A36 ANGLE	STR80
I	1	FOUNDATION TUBE 6" X 8" X 72" X 3/16"	FNDT6
J	1	WOOD BREAKAWAY POST 5 1/2" X 7 1/2" X 50"	WBRK50
K	1	WOOD STRIKE BLOCK	WSBLK14
L	1	STRIKE PLATE 1/4" A36 BENT PLATE	SPLT8
M	1	REINFORCEMENT PLATE 12 GA. GR55	REPLT17
N	1	GUARDRAIL GRABBER 2 1/2" X 2 1/2" X 16 1/2"	GR17
O	1	BEARING PLATE 8" X 8 5/8" X 5/8" A36	BPLT8
P	1	PIPE SLEEVE 4 1/4" X 2 3/8" O.D. (2 1/8" I.D.)	PSLV4
Q	1	BCT CABLE 3/4" X 81" LENGTH	CBL81
SMALL HARDWARE			
a	1	5/8" X 12" GUARDRAIL BOLT 307A HDG	12GRBLT
b	7	5/8" X 10" GUARDRAIL BOLT 307A HDG	10GRBLT
c	33	5/8" X 1 1/4" GR SPlice BOLTS 307A HDG	1GRBLT
d	3	5/8" FLAT WASHER F436 A325 HDG	58FW436
e	1	5/8" LOCK WASHER HDG	58LW
f	39	5/8" GUARDRAIL HEX NUT HDG	58HN563
g	2	1/2" X 2" STRUT BOLT A325 HDG	2BLT
h	6	1/2" X 1 1/4" PLATE BOLT A325 HDG	125BLT
i	16	1/2" FLAT WASHER F436 A325 HDG	12FWF436
j	8	1/2" LOCK WASHER HDG	12LW
k	8	1/2" HEX NUT A563 HDG	12HN563
l	4	3/8" X 3" HEX LAG SCREW GR5 HDG	38LS
m	4	3/8" FLAT WASHER F436 A325 HDG	38FW844
n	2	1" FLAT WASHER F436 A325 HDG	1FWF436
o	2	1" HEX NUT A563HD HDG	1HN563
p	1	18" TO 24" LONG ZIP TIE RATED 175-200LB	ZPT18
q	1	1 1/2" X 4" SCH-40 PVC PIPE	PSPCR4
r	1	RFID CHIP RATED MIL-STD-810F	RFID810F
s	1	IMPACT HEAD REFLECTIVE SHEETING	RS30M



NOTE: THIS STANDARD IS A BASIC REPRESENTATION OF THE SGET TERMINAL SYSTEM AND IS NOT INTENDED TO REPLACE THE MANUFACTURER'S ASSEMBLY MANUAL.

Texas Department of Transportation
Design Division Standard

SPIG INDUSTRY, LLC SINGLE GUARDRAIL TERMINAL SGET - TL-3 - MASH SGT (15) 31-20

FILE: sg153120.dgn	DN: TXDOT	CK: KM	DW: VP	CK: VP
© TXDOT: APRIL 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	32	

DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or for incorrect results or damages resulting from its use.
 DATE: 2/8/2023 1:38:20 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\signing & striping\txdot standard\20 delin and om.dwg

REFLECTOR UNIT SIZES FOR DELINEATORS AND OBJECT MARKERS				DELINEATORS				D & OM DESCRIPTIVE CODES	
DEVICE	SIZE 1	SIZE 2	SIZE 3	SIZE 4	SINGLE		DOUBLE		
									INSTL DEL ASSM (D-XX)SZ X (XXXX)XXX (XX) NUMBER OF REFLECTORS S = Single D = Double COLOR OF REFLECTORS W = White Y = Yellow R = Red REFLECTOR UNIT SIZE 1 or 2 TYPE OF POST OR DELINEATOR WC = Wing Channel Post YFLX = Yellow Flexible Post WFLX = White Flexible Post TYPE OF MOUNT GND = Embedded (drivable or set in concrete) CTB = Concrete Barrier Mount GF1 or GF2 = Guard Fence Attachment SRF = Surface Mount DIRECTION If Required BI = Bi-Directional BR = Bi-Directional with red on back
SHEETING: Yellow, White or Red Type B or C reflective sheeting				SHEETING: Yellow, White or Red Type B or C Reflective Sheeting					
NOTE: 1. Size 1 and 4 - Direct applied reflective sheeting for use on flexible post (flx). 2. Size 2 and 3 - For use on wing channel (wc) post only. Use approved metal, plastic or fiberglass backplate with 17/64" mounting holes.				POST TYPE: WC, YFLX, WFLX, GND					
				MOUNT TYPE: GND, SRF					

OBJECT MARKERS								
DEVICE	Type 1 (OM-1)		Type 2 (OM-2)			Type 3 (OM-3)		Type 4 (OM-4)
	OM-1	OM-2X	OM-2Y	OM-2Z	OM-3L	OM-3R	OM-3C	OM-4
								NUMBER OF REFLECTORS OR DIRECTION X = 3-Size 2 reflector units (Type 2 only) Y = 1-Size 3 reflector unit (Type 2 only) Z = 3-Size 1 or 1-Size 4 reflector unit(s) (Type 2 only) L = Left Side (Type 3 Object Marker only) R = Right Side (Type 3 Object Marker only) C = Center (Type 3 Object Marker only) TYPE OF POST WC = Wing Channel Post WFLX = White Flexible Post TWT = Thin Walled Tubing TYPE OF MOUNT GND = Embedded (drivable) SRF = Surface Mount WAS = Wedge Anchor Steel WAP = Wedge Anchor Plastic DIRECTION If Required BI = Bi-Directional
SHEETING: Yellow-Type B _{FL} or C _{FL} Sheeting		SHEETING: Yellow - Type B or C Sheeting			SHEETING: Alternating acrylic black and retroreflective yellow - Type B _{FL} or C _{FL} Sheeting		SHEETING: Red -Type B _{FL} or C _{FL} Sheeting	
POST TYPE: TWT		POST TYPE: WC		POST TYPE: WFLX		POST TYPE: TWT		POST TYPE: TWT
MOUNT TYPE: WAS, WAP		MOUNT TYPE: GND		MOUNT TYPE: GND, SRF		MOUNT TYPE: WAS, WAP		MOUNT TYPE: WAS, WAP

DEPARTMENTAL MATERIAL SPECIFICATIONS	
FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES)	DMS-4400
SIGN FACE MATERIALS	DMS-8300
DELINEATORS, OBJECT MARKERS AND BARRIER REFLECTORS	DMS-8600

BARRIER REFLECTORS (BRF)			CHEVRONS				ONE DIRECTION LARGE ARROW		NOTE: Delineator and object marker substrates and sign substrates shall be 0.080" Aluminum sign blank to conform to ASTM B-209 Alloy 6061-T6 or approved alternative.
DEVICE	GF1	GF2	CTB	W1-8		W1-6			
SHEETING: Yellow, White, Red			SIZE (W x L): 18"x 24" (Conventional), 24"x 30" (Conventional Oversize), 30"x 36" (Expressway), 36" x 48" (Freeway)		SIZE (W x L): 48" x 24" (Conventional), 60" x 30" (Expressway & Freeway)				
NOTE: 1. Barrier reflectors shall meet the requirements of DMS 8600. 2. Approved Barrier Reflectors are listed on the "Barrier Reflectors" Material Producer List at: www.txdot.gov.			MOUNTING HEIGHT: 4'-0" or 7'-0"		MOUNTING HEIGHT: 7'-0" Only		MOUNTING HEIGHT: 7'-0"		
NOTE: 1. Reflective sheeting shall have a minimum dimension of 3 inches and minimum surface area of 9 square inches.			NOTE: 1. CHEVRON (W1-8) signs and ONE DIRECTION LARGE ARROW (W1-6) Signs shall be installed per Sign Mounting Details (SMD) Standard Sheets and paid under Item 644 (Small Roadside Sign Assemblies). 2. When there is a need to increase conspicuity, the Texas version of the ONE DIRECTION LARGE ARROW sign (W1-9T) may be used instead of the ONE DIRECTION LARGE ARROW (W1-6).						

Texas Department of Transportation
 Traffic Safety Division Standard

DELINEATOR & OBJECT MARKER MATERIAL DESCRIPTION















D & OM(1)-20

FILE: dom1-20.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-09 3-15	DIST	COUNTY	SHEET NO.	
4-10 7-20	WACO	HAMILTON	33	

20A

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:21 PM
 FILE: T:\Road Department\Team Texas\txdot_cadd_standards\signing & striping\standard 20 object markers.dwg


POST TYPE AND SUPPORT FOUNDATION DETAILS				TYPE OF BARRIER MOUNTS	
WING CHANNEL (WC)	FLEXIBLE POSTS (YFLX, WFLX)		WEDGE ANCHOR SYSTEMS		GUARD FENCE ATTACHMENT
GND	GND	SRF	WAS	WAP	GF1
					
					
	EMBEDDED	SURFACE MOUNT	STEEL	PLASTIC	
NOTES 1. Embedded Wing Channel (WC) post option may be used for Type 2 Object Markers and Delineators only. 2. 1.12 lbs/ft steel per ASTM A 1011 SS Gr. 50, or ASTM A499.			NOTE 1. Install per manufacturer's recommendations.		
NOTES 1. See "Flexible Delineator and Object Marker Posts" Material Producer List for approved devices. 2. Install per manufacturer's recommendations. 3. Post length may vary to meet field conditions. 4. When using yellow delineators with flexible posts to separate opposing direction of travel, such as centerline or median use, the flexible posts shall be yellow.					
TYPES 1,3, AND 4 OBJECT MARKERS AND CHEVRONS		CHEVRONS AND ONE DIRECTION LARGE ARROW SIGN		DELINEATORS AND TYPE 2 OBJECT MARKERS	
					
NOTE Mounting at 4 feet to the bottom of the chevron is permitted for chevrons that will not exceed a height of 6'-6" to the top of the chevron (sizes 24" x 30" and smaller)		NOTE Chevrons 30" x 36" and larger shall be mounted at a height of 7' to the bottom of the chevron. Chevron sign and ONE DIRECTION LARGE ARROW sign (W1-9T) shall be installed per SMD standard sheets and paid under item 644.		NOTE See general notes 1, 2 and 3.	
CONCRETE TRAFFIC BARRIER (CTB)					
					
GENERAL NOTES					
1. Place delineators on a section of roadway at a consistent distance from the edge of pavement. 2. Where a restriction prevents consistent placement from the pavement edge, place the affected object markers in line with the innermost edge of the obstruction. 3. When Type 2 object markers and delineators are more than 8'-0" from the edge of the pavement, it may not be possible to maintain a height of approximately 4'-0". If this is the case, place the object marker or delineator as close to the desired height as possible. 4. Install all delineators, object markers and barrier reflectors in accordance with the manufacturer's recommendation. 5. Barrier reflectors should be installed a minimum of 18 inches above the edge of the pavement surface. 6. Diagonal stripes on Type 3 object markers shall slope down toward the intended travel lane.					
					
DELINATOR & OBJECT MARKER INSTALLATION					
D & OM(2)-20					
FILE: dom2-20.dgn © TxDOT August 2004		DN: TxDOT CONT SECT 0909 29		CK: TxDOT JOB 046	
REVISIONS 10-09 3-15 4-10 7-20		DIST COUNTY WACO HAMILTON		HWY HIGHWAY CR SHEET NO. 34	
20B					

DATE: 2/8/2023 1:38:24 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\signing & striping\txdot standards\20\delin and objm\20\delin and objm.dwg
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

MINIMUM WARNING DEVICES AT CURVES WITH ADVISORY SPEEDS

Amount by which Advisory Speed is less than Posted Speed	Curve Advisory Speed	
	Turn (30 MPH or less)	Curve (35 MPH or more)
5 MPH & 10 MPH	• RPMs	• RPMs
15 MPH & 20 MPH	• RPMs and One Direction Large Arrow sign	• RPMs and Chevrons; or • RPMs and One Direction Large Arrow sign where geometric conditions or roadside obstacles prevent the installation of chevrons.
25 MPH & more	• RPMs and Chevrons; or • RPMs and One Direction Large Arrow sign where geometric conditions or roadside obstacles prevent the installation of chevrons	• RPMs and Chevrons


SUGGESTED SPACING FOR DELINEATORS ON HORIZONTAL CURVES



NOTE

ONE DIRECTION LARGE ARROW (W1-6) sign should be located at approximately and perpendicular to the extension of the centerline of the tangent section of approach lane.

SUGGESTED SPACING FOR CHEVRONS ON HORIZONTAL CURVES



NOTE

At least one chevron pair is installed beyond the point of tangent in tangent section.

DELINEATOR AND CHEVRON SPACING

WHEN DEGREE OF CURVE OR RADIUS IS KNOWN				
Degree of Curve	FEET			
	Radius of Curve	Spacing in Curve	Spacing in Straightaway	Chevron Spacing in Curve
		A	2A	B
1	5730	225	450	—
2	2865	160	320	—
3	1910	130	260	200
4	1433	110	220	160
5	1146	100	200	160
6	955	90	180	160
7	819	85	170	160
8	716	75	150	160
9	637	75	150	120
10	573	70	140	120
11	521	65	130	120
12	478	60	120	120
13	441	60	120	120
14	409	55	110	80
15	382	55	110	80
16	358	55	110	80
19	302	50	100	80
23	249	40	80	80
29	198	35	70	40
38	151	30	60	40
57	101	20	40	40

Curve delineator approach and departure spacing should include 3 delineators spaced at 2A. This spacing should be used during design preparation or when the degree of curve is known.

DELINEATOR AND CHEVRON SPACING

WHEN DEGREE OF CURVE OR RADIUS IS NOT KNOWN			
Advisory Speed (MPH)	Spacing in Curve	Spacing in Straightaway	Chevron Spacing in Curve
	A	2xA	B
65	130	260	200
60	110	220	160
55	100	200	160
50	85	170	160
45	75	150	120
40	70	140	120
35	60	120	120
30	55	110	80
25	50	100	80
20	40	80	80
15	35	70	40

If the degree of curve is not known, delineator spacing may be determined based on the Advisory Speed of the curve. Use the delineator curve spacing for each Advisory Speed (MPH).

DELINEATOR AND OBJECT MARKER APPLICATION AND SPACING

CONDITION	REQUIRED TREATMENT	MINIMUM SPACING
Frwy./Exp. Tangent	RPMs	See PM-series and FPM-series standard sheets
Frwy./Exp. Curve	Single delineators on right side	See delineator spacing table
Frwy/Exp. Ramp	Single delineators on at least one side of ramp (should be on outside of curves) (see Detail 3 on D&OM(4))	100 feet on ramp tangents Use delineator spacing table for ramp curves ("straightway spacing" does not apply to ramp curves)
Acceleration/Deceleration Lane	Double delineators (see Detail 3 on D&OM(4))	100 feet (See Detail 3 on D & OM (4))
Truck Escape Ramp	Single red delineators on both sides	50 feet
Bridge Rail (steel or concrete) and Metal Beam Guard Fence	Bi-Directional Delineators when undivided with one lane each direction Single Delineators when multiple lanes each direction	Equal spacing (100' max) but not less than 3 delineators
Concrete Traffic Barrier (CTB) or Steel Traffic Barrier	Barrier reflectors matching the color of the edge line	Equal spacing 100' max
Cable Barrier	Reflectors matching the color of the edge line	Every 5th cable barrier post (up to 100' max)
Guard Rail Terminus/Impact Head	Divided highway - Object marker on approach end Undivided 2-lane highways - Object marker on approach and departure end	Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM (5) and D & OM (6)
Bridges with no Approach Rail	Type 3 Object Marker (OM-3) at end of rail and 3 single delineators approaching rail	See D & OM(5)
Reduced Width Approaches to Bridge Rail	Type 2 and Type 3 Object Markers (OM-3) and 3 single delineators approaching bridge	Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM (5)
Culverts without MBGF	Type 2 Object Markers	See Detail 2 on D & OM(4)
Crossovers	Double yellow delineators and RPMs	See Detail 1 on D & OM (4)
Pavement Narrowing (lane merge) on Freeways/Expressway	Single delineators adjacent to affected lane for full length of transition	100 feet

NOTES

- Unless indicated otherwise, the delineator or barrier reflector color shall conform to the color of the pavement edge line on the side of the road where the delineators or barrier reflectors are placed.
- Barrier reflectors may be used to replace required delineators.
- Single red delineators may be mounted on the back side of delineator posts for wrong way driver applications

LEGEND	
	Bi-directional Delineator
	Delineator
	Sign

Texas Department of Transportation
Traffic Safety Division Standard


DELINEATOR & OBJECT MARKER PLACEMENT DETAILS

D & OM(3)-20

FILE: dom3-20.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS		090929	046	CR
3-15 8-15	DIST	COUNTY	SHEET NO.	
8-15 7-20	WACO	HAMILTON	35	

20C


**TWO-WAY, TWO LANE ROADWAY
WITH REDUCED WIDTH APPROACH RAIL**



NOTE:

1. Terminal ends require reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end.


**TWO-WAY, TWO LANE ROADWAY
WITH METAL BEAM GUARD FENCE (MBGF)**



NOTE:

1. Terminal ends require reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end.

**TWO-WAY, TWO LANE ROADWAY
BRIDGE WITH NO APPROACH RAIL**



LEGEND

	Bidirectional Delineator
	Delineator
	OM-3
	OM-2
	Terminal End
	Traffic Flow



**DELINEATOR &
OBJECT MARKER
PLACEMENT DETAILS**







D & OM(5)-20

FILE: dom5-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT August 2015	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
7-20	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	36	



DATE: 2/8/2023 1:38:24 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\signing & striping\standards\20e\delin_d_20.dwg
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:25 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\signing & striping\2023\20230208\domvia20.dgn



OBJECT MARKERS SMALLER THAN 3 FT²



- NOTES**
- *1. Spacing should be adjusted to attach through centerline of drum, per attenuator manufacturer's recommendation, or as directed by the Engineer.
 - *2. Mounting should be flush with top of attenuator. Minimum size 96" x 24".


NOTES

- Object Markers shall conform to the Texas MUTCD and meet the color and reflectivity requirement of Department Material Specification DMS 8300. Background shall be yellow reflective sheeting (Type B or C) and Chevron shall be black.
- Object Markers may be fabricated from adhesive backed reflective sheeting applied directly to guardrail end treatment, or applied directly to an "end cap" as per the manufacturer's recommendation. Direct applied sheeting shall provide a smooth surface and have no wrinkles, air bubbles, cuts or tears. A radius at the corners is not required for direct applied sheeting.
- Object Marker size may be reduced to fit smaller devices. Width of alternating black and yellow stripes are typically 6". Object Markers smaller than 3ft may have reduced width stripes of a minimum of 2 1/4".
- Pop rivets, screws, or nuts and bolts may be used to attach object markers and reflectors. Holes, slots or other openings may be cut or drilled through object markers to allow cable or other attachments.
- Object Marker at nose of attenuator is subsidiary to the attenuator.
- See D & OM (1-4) for required barrier reflectors.


<p>DELINEATOR & OBJECT MARKER FOR VEHICLE IMPACT ATTENUATORS</p> <p>D & OM(VIA)-20</p>			
FILE: domvia20.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT
© TXDOT December 1989	CONT	SECT	JOB
REVISIONS		0909 29	046
4-92 8-04	DIST	COUNTY	SHEET NO.
8-95 3-15	WACO	HAMILTON	37
4-98 7-20			
20G			

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd_standards\roadway\WF (2)-10.dgn




SECTION GALVANIZED BARBED WIRE FENCE WITH METAL POSTS
 BRACING DETAIL USED AT ENDS AND GATES
TYPE "C" FENCE
 (See General Note 8)




SECTION GALVANIZED WOVEN WIRE FENCE WITH METAL POSTS
 BRACING DETAIL USED AT ENDS AND GATES
TYPE "D" FENCE
 (See General Note 8)

Note:
 For Steel pipe and
 T-Post requirements.
 (See General Notes 6 & 7)


Metal gate shall consist of 5 panels not less than 4'-4" high and shall be aluminum or galvanized metal and of good quality. Gate and hardware shall meet the approval of the engineer.




DETAIL TYPE 1 GATE




DETAIL TYPE 2 GATE




DETAIL TYPE 3 GATE




CORNER OR PULL POST ASSEMBLY




DETAIL OF FENCE TREATMENT AT STRUCTURES



DETAIL OF STAY (Barbed Wire Fence)



DETAIL OF FENCE SAG



DETAIL OF EYE BOLT


GENERAL NOTES

- Any high point which interferes with the placing of wire mesh shall be excavated to provide a 2 inch clearance.
 - Latches for Type 1 and Type 2 gates shall be good commercial quality and design latch of the spring, fork or chain type. All latches shall be suitable to the gate and shall be approved by the Engineer.
 - Hinges for Type 2 gates shall be a commercial design approved by the Engineer suitable for post and gate.
 - Concrete shall be of the design and consistency approved by the Engineer and shall contain not less than 4 sacks of cement per cubic yard. Concrete footings are to be crowned at the top to shed water.
 - Steel anchor plates shall be of a design and thickness sufficient to prevent turning of the post in firm soil.
 - Steel pipe end posts, corner and pull posts shall be a minimum of 2" Std. pipe (2.375" O.D., 0.154" wall thickness) with a 1/4" Std. pipe brace (1.660" O.D., 0.140" wall thickness), with a 2"x2"x1/4" angle, or other as approved by the Engineer. Fasteners for securing barbed wire or woven wire fence to metal posts shall be a minimum of 11 gauge galvanized steel wire. Tubular posts shall be fitted with water malleable iron caps.
 - If Steel pipe is used for posts and braces, use standard pipe in accordance with ASTM A 53, Class B or A 501. For T-Posts use steel that meets ASTM A 702. Metal line posts shall be not less than 6'-6" in length and shall weigh not less than (1.33 lbs./lin.ft.). These items shall be in accordance with Item 552, "Wire Fence."
 - Barbed Wire shall be in accordance with ASTM A 121, Class 1 Design designation 12-2-4-1 4R or 12-2-5-1 4R, or as approved by the Engineer.
- Woven Wire Fence (Type D) shall be in accordance with ASTM A 116, Class 1 No. 12-1/2 Grade 60 (See Table 1 ASTM A 116) to the height and design shown on the plans, or as approved by the Engineer.
- The location of gates and corner posts will be as indicated elsewhere in these plans.

		Design Division Standard	
BARBED WIRE AND WOVEN WIRE FENCE (STEEL POSTS)			
WF (2)-10			
FILE: wf210.dgn	DN: TxDOT	CK: AM	DW: VP
© TxDOT 1996	CONT	SECT	JOB
REVISIONS	0909	29	046
DIST	COUNTY		SHEET NO.
WACO	HAMILTON		38

REGRESSION METHOD

AREA ID	AREA (AC)	AREA (SQ. MI)	MEAN ANNUAL PRECIPITATION (IN)	MAIN CHANNEL SLOPE (FT/FT)	OMEGA EM PARAMETER	Q - 10 YEARS (CFS)	Q - 100 YEARS (CFS)
DA-1	11794	18.43	33	0.007	-0.106	2,970	7,430




LEGEND

- DRAINAGE AREA
- 20-FT CONTOURS
- DA ID
- DA ACRES

NOTES

1. FLOWS WERE COMPUTED USING OMEGA EM REGRESSION METHOD AS DISCUSSED IN THE TXDOT HYDRAULIC DESIGN MANUAL CH. 4 SEC. 10.
2. CONTOURS ARE SHOWN AT 20' INTERVALS AND WERE OBTAINED FROM THE TNRIS ELEVATION DATA SET.



PRINT DATE	REVISION DATE
2/8/2023	



Fernando Gaytan
2/8/2023

STRUCTUREPOINT
 INC.


3711 SOUTH MOPAC EXPRESSWAY
 BUILDING ONE, SUITE 350
 AUSTIN, TX 78703
 TEL 512.494.6037 FAX 317.543.0270
 www.structurepoint.com

TBPE FIRM NO. F-10069

Texas Department of Transportation ©2023
CR 238 (HCR 207) AT HONEY CREEK DRAINAGE AREA MAP

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	39

REV DATE: 2/8/2023
 CSJ: 0909-29-046
 FILE LOCATION: P:\2020\00072\090929046\4 - Design\Plan Set\5. Drainage\2020.00072.04.DRN.DA.dgn



CROSS SECTION LOCATION MAP

EXISTING CONDITIONS

LOCATION OF STREAM X-SECT	CHANNEL STATION (FT)	Q (CFS)	VEL (FPS)	WSEL (FT)
CONVERGENCE	7956	2970	5.54	1082.34
UPSTREAM	5883	2970	4.66	1069.67
UPSTREAM BRIDGE AT ROW	5750	2970	4.49	1069.5
INSIDE OF BRIDGE	5727	2970	5.1	1069.34
DOWNSTREAM BRIDGE AT ROW	5707	2970	3.98	1069.36
DOWNSTREAM (CONVERGENCE)	5535	2970	3.55	1069.23

FREQUENCY = 10 YEAR

PROPOSED CONDITIONS

LOCATION OF STREAM X-SECT	CHANNEL STATION (FT)	Q (CFS)	VEL (FPS)	WSEL (FT)
CONVERGENCE	7956	2970	5.55	1082.34
UPSTREAM	5883	2970	4.73	1069.59
UPSTREAM BRIDGE AT ROW	5750	2970	4.29	1069.42
INSIDE OF BRIDGE	5727	2970	4.08	1069.43
DOWNSTREAM BRIDGE AT ROW	5707	2970	3.9	1069.37
DOWNSTREAM (CONVERGENCE)	5535	2970	3.55	1069.23

FREQUENCY = 10 YEAR

EXISTING CONDITIONS

LOCATION OF STREAM X-SECT	CHANNEL STATION (FT)	Q (CFS)	VEL (FPS)	WSEL (FT)
CONVERGENCE	7956	7430	6.85	1085.05
UPSTREAM	5883	7430	5.67	1073.74
UPSTREAM BRIDGE AT ROW	5750	7430	7.4	1073.04
INSIDE OF BRIDGE	5727	7430	9.24	1072.34
DOWNSTREAM BRIDGE AT ROW	5707	7430	7.24	1072.44
DOWNSTREAM (CONVERGENCE)	5535	7430	4.96	1072.42


FREQUENCY = 100 YEAR

PROPOSED CONDITIONS

LOCATION OF STREAM X-SECT	CHANNEL STATION (FT)	Q (CFS)	VEL (FPS)	WSEL (FT)
CONVERGENCE	7956	7430	5.55	1082.34
UPSTREAM	5883	7430	6.27	1073.10
UPSTREAM BRIDGE AT ROW	5750	7430	6.56	1072.72
INSIDE OF BRIDGE	5727	7430	6.7	1072.66
DOWNSTREAM BRIDGE AT ROW	5707	7430	6.65	1072.52
DOWNSTREAM (CONVERGENCE)	5535	7430	4.98	1072.42

FREQUENCY = 100 YEAR

PROPOSED LOW CHORD ELEVATION = 1075.22'
(EXISTING LOW CHORD ELEVATION = 1075.86')




TYPICAL STREAM CROSS SECTION & ROAD PROFILE

SCALE: 1" = 100' HORIZONTAL, 1" = 20' VERTICAL


1. HEC-RAS 6.2 USED FOR HYDRAULIC ANALYSIS DESIGN.
2. ALL SECTIONS ARE NORMAL TO STREAMFLOW.
3. ALL ELEMENTS ARE BASED ON NORTH AMERICAN VERTICAL DATUM 88 (NAVD88).
4. NORMAL DEPTH COMPUTATION USED FOR DOWNSTREAM BOUNDARY CONDITION. SLOPE = 0.007 FOR BOTH EXISTING AND PROPOSED CONDITIONS.
5. PROJECT IS LOCATED WITHIN AN UNMAPPED FEMA AREA. THERE IS NO FEMA FIRM PANEL FOR THIS PROJECT

PRINT DATE	REVISION DATE
2/8/2023	



Fernando Gaytan
2/8/2023


3711 SOUTH MOPAC EXPRESSWAY
BUILDING ONE, SUITE 350
AUSTIN, TX 78703
TEL 512.494.6037 FAX 317.543.0270
www.structurepoint.com
TBPE FIRM NO. F-10069



CR 238 (HCR 207) AT HONEY CREEK
HYDRAULIC DATA SHEET

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	40

- GENERAL NOTES:**
- DESIGNED IN ACCORDANCE WITH 2020 AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, 9TH EDITION WITH CURRENT INTERIM REVISIONS.
 - VERIFY ALL DIMENSIONS AND ELEVATIONS PRIOR TO COMMENCING WORK.
 - ALL DIMENSIONS ARE EITHER HORIZONTAL OR VERTICAL AND MUST BE CORRECTED FOR GRADE, CROWN, AND/OR SUPERELEVATION.
 - "H" COLUMN HEIGHTS SHOWN ARE CALCULATED AT THE PROFILE GRADE LINE. ACTUAL COLUMN HEIGHTS SHALL BE MEASURED IN THE FIELD PRIOR TO ORDERING MATERIALS.
 - "D" DENOTES BENTS WITH DOWELS AND SLOTTED HOLES AT ENDS OF EXTERIOR GIRDERS.
 - CONTRACTOR SHALL VERIFY LOCATIONS OF ALL UTILITIES PRIOR TO EXCAVATION AND/OR DRILLING.
 - SEE SOIL BORING LOG SHEETS FOR SOIL PROFILES.
 - SEE ROADWAY DRAWINGS FOR RIPRAP GEOMETRY AND PROPOSED GRADING.
 - SEE STANDARD DRAWINGS FOR FOUNDATION, ABUTMENT, BENT, SLAB AND GIRDER DETAILS.
 - SEE CSAB STANDARD FOR CEMENT STABILIZED ABUTMENT BACKFILL DETAILS.
 - SEE IGSK STANDARD FOR BENT AND ABUTMENT SHEAR KEY DETAILS.



HORIZONTAL CURVE DATA


CURVE 1 (CR238_1)	CURVE 2 (CR238_2)
PI STA = 403+35.66	PI STA = 405+32.81
DELTA = 5° 33' 31.20" (RT)	DELTA = 9° 50' 31.54" (RT)
DEGREE = 19° 05' 54.94"	DEGREE = 38° 11' 49.87"
TANGENT = 14.564'	TANGENT = 12.9150'
LENGTH = 29.1051'	LENGTH = 25.7665'
RADIUS = 300.000'	RADIUS = 150.000'
PC STA = 403+21.09	PC STA = 405+19.90
PT STA = 403+50.20	PT STA = 405+45.67

- EXISTING BRIDGE OVERALL BRIDGE LENGTH = 80'-0". STRUCTURE CONSISTS OF 5 STEEL TRUSS SPANS SUPPORTED BY STEEL CAPS AND COLUMNS ON CONCRETE SPREAD FOOTING FOUNDATIONS.
- PROVIDE 5 RAIL SLOTS EACH SPAN, TYPICAL EACH SIDE.
- REMOVAL OF EXISTING RETAINING WALLS ARE SUBSIDIARY TO THE BRIDGE REMOVAL BID ITEM (TYP).

DESIGN SPEED = MEET OR IMPROVE EXISTING
 FUNCTIONAL CLASS = LOCAL
 ADT (2020) = 66 VPD
 ADT (2041) = 92 VPD
 EXIST NBI: 09-098-0-AA02-38-002
 NEW NBI NO: 09-098-0-AA02-07-001

HL-93 LOADING
 SUPERSTRUCTURE INV/OPR RATINGS: 1.08/1.81

PRINT DATE	REVISION DATE
2/8/2023	



Emily Wason Berver 2/8/2023

P.E. STRUCTURAL CONSULTANTS
 8436 SPICEWOOD SPRINGS ROAD
 AUSTIN, TX 78759
 TEL 512.250.2500
 www.PEStructural.com
 www.HardestyHanover.com

PESC
 A Hardesty & Hanover Company


TBPE FIRM NO. F-3379

Texas Department of Transportation ©2023

CR 238 (HCR 207) AT HONEY CREEK BRIDGE LAYOUT

SHEET 1 OF 2

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	42



EXISTING HYDRAULIC DATA

Q ₁₀ = 2,970 CFS	Q ₁₀₀ = 7,430 CFS
HW ₁₀ = 1,069.50'	HW ₁₀₀ = 1,073.04'
V _{10out} = 5.10 FT/S	V _{100out} = 9.24 FT/S


PROPOSED HYDRAULIC DATA

Q ₁₀ = 2,970 CFS	Q ₁₀₀ = 7,430 CFS
HW ₁₀ = 1,069.42'	HW ₁₀₀ = 1,072.72'
V _{10out} = 4.08 FT/S	V _{100out} = 6.70 FT/S

DRILLED SHAFTS HAVE BEEN DESIGNED USING BOTH END BEARING AND SKIN FRICTION. SHAFTS SHALL BE FOUND AT THE ELEVATIONS SHOWN OR DEEPER AS NECESSARY TO OBTAIN A MINIMUM EMBEDMENT LENGTH INTO HARD LIMESTONE OR SHALE AS SPECIFIED BELOW:

ABUTMENTS = 6 FEET
 INTERIOR BENT = 9 FEET

IGNORE ANY HIGHLY WEATHERED ZONES.



TYPICAL BRIDGE SECTION

N. T. S.

HL-93 LOADING

PRINT DATE	REVISION DATE
2/8/2023	




Emily Wason Berver 2/8/2023



P.E. STRUCTURAL CONSULTANTS
8436 SPICEWOOD SPRINGS ROAD
AUSTIN, TX 78759
TEL 512.250.2500
www.PEStructural.com
www.HardestyHanover.com


TBPE FIRM NO. F-3379



CR 238 (HCR 207) AT HONEY CREEK
BRIDGE LAYOUT

SHEET 2 OF 2

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	43



PRINT DATE	REVISION DATE
2/8/2023	



Emily Wason Berver 2/8/2023

PESC
 A Hardesty & Hanover Company
 P.E. STRUCTURAL CONSULTANTS
 8436 SPICEWOOD SPRINGS ROAD
 AUSTIN, TX 78759
 TEL 512.250.2500
 www.PEStructural.com
 www.HardestyHanover.com
 TBPE FIRM NO. F-3379

Texas Department of Transportation ©2023
 CR 238 (HCR 207) AT HONEY CREEK
 SOIL BORING LOGS

SHEET 1 OF 1

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	44

SUMMARY OF ESTIMATED BRIDGE QUANTITIES

BID ITEM	400 6005	416 6004	420 6013	420 6029	420 6037	422 6001	425 6035	432 6033	450 6054	454 6004	496 6009
BID ITEM DESCRIPTION	CEM STABIL BKFL	DRILL SHAFT (36 IN)	① CL C CONC (ABUT)	① CL C CONC (CAP)	CL C CONC (COLUMN)	REINF CONC SLAB	② PRESTR CONC GIRDER (TX28)	RIPRAP (STONE PROTECTION) (18 IN)	RAIL (TY SSTR) (W/DRAIN SLOTS)	ARMOR JOINT (SEALED)	REMOV STR (BRIDGE 0 - 99 FT LENGTH)
BRIDGE ELEMENT	CY	LF	CY	CY	CY	SF	LF	CY	LF	LF	EA
2 ~ ABUTMENTS	105	93	38.6					862	48.0		
1 ~ INTERIOR BENT		54		11.5	12.0						
1 ~ 140.00' PRESTR CONC I-GIRDER UNIT						3,640	555.92		280.0	46	1
TOTALS	105	147	38.6	11.5	12.0	3,640	555.92	862	328.0	46	1

- ① QUANTITY INCLUDES SHEAR KEY CONCRETE. SEE IGSK STANDARD FOR SHEAR KEY DETAILS.
- ② PAINTING PERMANENT STRUCTURE NUMBER IS SUBSIDIARY TO ITEM 425. SEE GENERAL NOTES.

BEARING SEAT ELEVATIONS

ABUT 1 (FWD)	GIRDER 1 1,075.353	GIRDER 2 1,075.483	GIRDER 3 1,075.480	GIRDER 4 1,075.343
BENT 2 (BK) (FWD)	GIRDER 1 1,075.210 1,075.206	GIRDER 2 1,075.340 1,075.336	GIRDER 3 1,075.336 1,075.332	GIRDER 4 1,075.199 1,075.195
ABUT 3 (BK)	GIRDER 1 1,075.082	GIRDER 2 1,075.212	GIRDER 3 1,075.208	GIRDER 4 1,075.071

PRINT DATE	REVISION DATE
2/8/2023	



Emily Wason Berver 2/8/2023



P.E. STRUCTURAL CONSULTANTS
8436 SPICEWOOD SPRINGS ROAD
AUSTIN, TX 78759
TEL 512.250.2500
www.PEstructural.com
www.HardestyHanover.com

TBPE FIRM NO. F-3379







**CR 238 (HCR 207) AT HONEY CREEK
ESTIMATED QUANTITIES &
BEARING SEAT ELEVATIONS**

SHEET 1 OF 1

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	45

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any drawings to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:32 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girders\AIG-24-15.dgn



- (5) See Span details for "y" value.
- (9) Spacing based on girder type:
 Tx28 ~ 3 spaces at 1'-0" Max
 Tx34 ~ 3 spaces at 1'-0" Max
 Tx40 ~ 4 spaces at 1'-0" Max
 Tx46 ~ 4 spaces at 1'-0" Max
 Tx54 ~ 5 spaces at 1'-0" Max
- (11) Field bend as needed to clear piles.
- (13) Adjust as required to avoid piling.

		Bridge Division Standard	
ABUTMENTS TYPE TX28 THRU TX54 PRESTR CONC I-GIRDERS 24' ROADWAY 15° SKEW AIG-24-15			
FILE: aig02sts-17.dgn	DN: TAR	CK: KCM	DW: JTR
©TxDOT August 2017	CONT	SECT	JOB
REVISIONS	0909	29	046
DIST	COUNTY	SHEET NO.	
WACO	HAMILTON	47	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:33 PM
 FILE: T:\Road_Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-Girders\AIG-24-15.dgn

TABLES OF ESTIMATED QUANTITIES WITH 2:1 HEADER SLOPE (14)


TYPE Tx28 Girders					TYPE Tx34 Girders					TYPE Tx40 Girders					TYPE Tx46 Girders					TYPE Tx54 Girders									
Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight					
A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377					
D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11					
H	8	#6	26'-7"	319	H	8	#6	26'-7"	319	H	10	#6	26'-7"	399	H	10	#6	26'-7"	399	H	12	#6	26'-7"	479					
L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54					
L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54					
S	24	#5	11'-6"	288	S	24	#5	11'-6"	288	S	24	#5	11'-6"	288	S	24	#5	11'-6"	288	S	24	#5	11'-6"	288					
U	4	#6	8'-2"	49	U	4	#6	8'-2"	49	U	4	#6	8'-2"	49	U	4	#6	8'-2"	49	U	4	#6	8'-2"	49					
V	26	#5	11'-4"	307	V	26	#5	12'-4"	334	V	26	#5	13'-4"	362	V	26	#5	14'-4"	389	V	26	#5	15'-8"	425					
wH1	14	#6	9'-5"	198	wH1	14	#6	10'-5"	219	wH1	14	#6	11'-5"	240	wH1	14	#6	12'-5"	261	wH1	14	#6	14'-5"	303					
wH2	20	#6	7'-8"	230	wH2	20	#6	8'-8"	260	wH2	24	#6	9'-8"	348	wH2	24	#6	10'-8"	385	wH2	28	#6	12'-8"	533					
wS	18	#4	7'-10"	94	wS	20	#4	7'-10"	105	wS	22	#4	7'-10"	115	wS	24	#4	7'-10"	126	wS	28	#4	7'-10"	147					
wV	18	#5	11'-4"	213	wV	20	#5	12'-4"	257	wV	22	#5	13'-4"	306	wV	24	#5	14'-4"	359	wV	28	#5	15'-8"	458					
Reinforcing Steel				Lb	3,194	Reinforcing Steel				Lb	3,327	Reinforcing Steel				Lb	3,603	Reinforcing Steel				Lb	3,752	Reinforcing Steel				Lb	4,178
Class "C" Concrete				CY	15.6	Class "C" Concrete				CY	17.0	Class "C" Concrete				CY	18.5	Class "C" Concrete				CY	20.1	Class "C" Concrete				CY	22.9

TABLES OF ESTIMATED QUANTITIES WITH 3:1 HEADER SLOPE (14)

TYPE Tx28 Girders					TYPE Tx34 Girders					TYPE Tx40 Girders					TYPE Tx46 Girders					TYPE Tx54 Girders									
Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight	Bar	No.	Size	Length	Weight					
A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377	A	10	#11	25'-11"	1,377					
D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11	D(7)	2	#9	1'-8"	11					
H	8	#6	26'-7"	319	H	8	#6	26'-7"	319	H	10	#6	26'-7"	399	H	10	#6	26'-7"	399	H	12	#6	26'-7"	479					
L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54	L1	9	#6	4'-0"	54					
L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54	L2	9	#6	4'-0"	54					
S	24	#5	11'-6"	288	S	24	#5	11'-6"	288	S	24	#5	11'-6"	288	S	24	#5	11'-6"	288	S	24	#5	11'-6"	288					
U	4	#6	8'-2"	49	U	4	#6	8'-2"	49	U	4	#6	8'-2"	49	U	4	#6	8'-2"	49	U	4	#6	8'-2"	49					
V	26	#5	11'-4"	307	V	26	#5	12'-4"	334	V	26	#5	13'-4"	362	V	26	#5	14'-4"	389	V	26	#5	15'-8"	425					
wH1	14	#6	13'-5"	282	wH1	14	#6	15'-5"	324	wH1	14	#6	16'-5"	345	wH1	14	#6	18'-5"	387	wH1	14	#6	20'-5"	429					
wH2	20	#6	11'-8"	350	wH2	20	#6	13'-8"	411	wH2	24	#6	14'-8"	529	wH2	24	#6	16'-8"	601	wH2	28	#6	18'-8"	785					
wS	26	#4	7'-10"	136	wS	30	#4	7'-10"	157	wS	32	#4	7'-10"	167	wS	36	#4	7'-10"	188	wS	40	#4	7'-10"	209					
wV	26	#5	11'-4"	307	wV	30	#5	12'-4"	386	wV	32	#5	13'-4"	445	wV	36	#5	14'-4"	538	wV	40	#5	15'-8"	654					
Reinforcing Steel				Lb	3,534	Reinforcing Steel				Lb	3,764	Reinforcing Steel				Lb	4,080	Reinforcing Steel				Lb	4,335	Reinforcing Steel				Lb	4,814
Class "C" Concrete				CY	18.1	Class "C" Concrete				CY	20.4	Class "C" Concrete				CY	22.1	Class "C" Concrete				CY	24.6	Class "C" Concrete				CY	27.7


(7) Omit Dowels D at end of multi-span unit. Adjust reinforcing steel total accordingly.

(14) Quantities shown are for one abutment only (with approach slab). With no approach slab, add 1.0 CY Class "C" concrete and 160 lbs reinforcing steel for 4 additional Bars H.


				Bridge Division Standard	
ABUTMENTS TYPE TX28 THRU TX54 PRESTR CONC I-GIRDERS 24' ROADWAY 15° SKEW AIG-24-15					
FILE:	aig02sts-17.dgn	DN:	TAR	CK:	KCM
REV:	0909 29	DATE:	August 2017	JOB:	046
COUNTY:	WACO	DIST:	HAMILTON	SHEET NO.:	48

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of metric units to U.S. units or for incorrect results or damages resulting from its use.






DATE: 2/8/2023 1:38:33 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\bridge\I-girders\big-24-15.dwg




PLAN



HALF ELEVATION



SECTION A-A



BEARING SEAT DETAIL

(Bearing surface must be clean and free of all loose material before placing bearing pad.)

- ① Quantities shown are based on an "H" value of 36'. For each linear foot variation in "H" value, make the following adjustments:
 Bars V length, 1'-0"
 Bars Z length, 31'-5"
 Reinforcing steel, 165 Lb
 Class "C" conc (col), 0.78 CY
- ② This standard may not be used for "H" heights exceeding 36'. In areas of very soft soil or where scour is anticipated, allowable "H" heights must be evaluated by the Engineer prior to the use of this standard.
- ③ Omit Dowels D at end of multi-span units. Adjust reinforcing steel total accordingly.
- ④ Foundation Loads based on "H" = 36'.
- ⑤ Measured parallel to top of cap cross-slope.

TABLE OF ESTIMATED QUANTITIES ①				
Bar	No.	Size	Length	Weight
A	6	#11	24'- 6"	781
B	4	#11	23'- 0"	489
D ③	4	#9	1'- 8"	23
S	32	#5	13'- 8"	457
T	10	#5	23'- 0"	240
U	2	#5	9'- 8"	20
V	30	#9	38'- 9"	3,953
Z	3	#4	1,154'- 7"	2,314
Reinforcing Steel			Lb	8,277
Class "C" Concrete (Cap)			CY	11.1
Class "C" Concrete (Col)			CY	28.3

FOUNDATION LOADS ④			
Span Average	Drilled Shaft Loads	Pile Load (Tons/Pile)	
		3 Pile Ftg	4 Pile Ftg
Ft	Tons/Shaft		
40	104	38	29
45	112	41	31
50	120	43	33
55	127	46	35
60	135	48	37
65	142	51	39
70	150	53	41
75	157	56	42
80	165	58	44
85	172	61	46
90	179	63	48
95	187	66	50
100	194	68	52
105	202	71	54
110	209	73	55
115	216	75	57
120	224	78	59
125	231	80	61

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications. See Bridge Layout for foundation type, size and length. See Common Foundation Details (FD) standard sheet for all foundation details and notes. See Shear Key Details (IGSK) standard sheet for all shear key details and notes, if applicable. Bent selected must be based on the average span length rounded up to the next 5 ft increment. Details are drawn showing right forward skew. See Bridge Layout for actual skew direction. These bent details may be used with standard SIG-24-15 only.


Cover dimensions are clear dimensions, unless noted otherwise. Reinforcing bar dimensions shown are out-to-out of bar.

MATERIAL NOTES:
 Provide Class C concrete (f'c = 3,600 psi). Provide Class C (HPC) concrete if shown elsewhere in the plans. Provide Grade 60 reinforcing steel. Galvanize dowel bars D. HL93 LOADING


Texas Department of Transportation		Bridge Division Standard	
INTERIOR BENTS			
TYPE TX28 THRU TX54			
PRESTR CONC I-GIRDERS			
24' ROADWAY		15° SKEW	
BIG-24-15			
FILE: big02sts-17.dgn	DN: TAR	CK: SDB	DW: JTR
©TxDOT August 2017	CONTRACT	SECTION	JOB
REVISIONS	0909	29	046
DIST	COUNTY	SHEET NO.	
WACO	HAMILTON	49	

DISCLAIMER:
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 3:33:42 PM
 FILE: T:\Road_Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\SIG-24-15.dgn



PLAN ①



TYPICAL TRANSVERSE SECTION
 (Showing girder type Tx46)

TABLE OF SECTION DEPTHS	
GIRDER TYPE	"Y" AT \bar{C} BRG ③
	Ft/In
Tx28	3'-4"
Tx34	3'-10"
Tx40	4'-4"
Tx46	4'-10"
Tx54	5'-6"

BAR TABLE

BAR	SIZE
A	#4
D	#4
G	#4
H	#4
J	#4
M	#4
OA	#5
P	#4
T	#4

- ① If multi-span units (with slab continuous over interior bents) are indicated on the Bridge Layout, see standard IGCS for adjustment to slab reinforcement and quantities.
- ② Span lengths for Prestressed Concrete I-Girder type:
 Type Tx28 for spans lengths 40,000' thru 75,000'.
 Type Tx34 for spans lengths 40,000' thru 85,000'.
 Type Tx40 for spans lengths 40,000' thru 100,000'.
 Type Tx46 for spans lengths 40,000' thru 115,000'.
 Type Tx54 for spans lengths 40,000' thru 125,000'.
- ③ "Y" value shown is based on theoretical girder camber, dead load deflection from an 8 1/2" concrete slab, a constant roadway grade, and using precast panels (PCP). The Contractor will adjust this value as necessary for any roadway vertical curve.

HL93 LOADING

SHEET 1 OF 2



PRESTRESSED CONCRETE I-GIRDER SPANS (TYPE Tx28 THRU Tx54) 24' ROADWAY 15° SKEW


SIG-24-15

FILE: IG-SIG2415-23.dgn	DN: JMH	CK: NRN	DW: JTR	CK: TAR
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-19: Increased "X" and "Y" Values. 01-23: Removed PCPD reference.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	50	

DATE: 2/8/2023 3:33:43 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\SIG-24-15.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TABLE OF DEAD LOAD DEFLECTIONS

TYPE T _x 28 GIRDERS			TYPE T _x 34 GIRDERS			TYPE T _x 40 GIRDERS			TYPE T _x 46 GIRDERS			TYPE T _x 54 GIRDERS		
SPAN LENGTH	"A"	"B"	SPAN LENGTH	"A"	"B"	SPAN LENGTH	"A"	"B"	SPAN LENGTH	"A"	"B"	SPAN LENGTH	"A"	"B"
Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft	Ft
40	0.007	0.010	40	0.004	0.006	40	0.003	0.004	40	0.002	0.003	40	0.001	0.002
45	0.012	0.017	45	0.007	0.010	45	0.005	0.007	45	0.004	0.005	45	0.002	0.003
50	0.019	0.027	50	0.011	0.016	50	0.007	0.010	50	0.005	0.007	50	0.004	0.005
55	0.028	0.040	55	0.017	0.024	55	0.011	0.016	55	0.008	0.011	55	0.005	0.007
60	0.041	0.057	60	0.024	0.034	60	0.016	0.022	60	0.011	0.015	60	0.007	0.010
65	0.056	0.079	65	0.033	0.047	65	0.022	0.031	65	0.015	0.021	65	0.010	0.014
70	0.077	0.108	70	0.046	0.064	70	0.030	0.042	70	0.021	0.029	70	0.014	0.019
75	0.102	0.143	75	0.061	0.085	75	0.040	0.056	75	0.027	0.038	75	0.018	0.025
			80	0.079	0.111	80	0.052	0.073	80	0.036	0.050	80	0.024	0.033
			85	0.102	0.143	85	0.066	0.093	85	0.046	0.064	85	0.030	0.042
						90	0.084	0.118	90	0.057	0.080	90	0.038	0.053
						95	0.105	0.147	95	0.071	0.100	95	0.047	0.066
						100	0.130	0.182	100	0.088	0.124	100	0.058	0.082
									105	0.108	0.151	105	0.071	0.100
									110	0.130	0.182	110	0.086	0.121
									115	0.156	0.219	115	0.103	0.144
									120			120	0.123	0.172
									125			125	0.145	0.203



DEAD LOAD DEFLECTION DIAGRAM

Calculated deflections shown are due to the concrete slab on interior girders only ($E_c = 5000$ ksi). Adjust values as required for exterior girders and if optional slab forming is used. These values may require field verification.

TABLE OF ESTIMATED QUANTITIES

SPAN LENGTH	REINF CONCRETE SLAB	Prestressed Concrete Girders			TOTAL REINF STEEL ⁵
		ABUT TO INT BT ⁴	INT BT TO INT BT ⁴	ABUT TO ABUT ⁴	
Ft	SF	LF	LF	LF	Lb
40	1,040	157.96	158.00	157.93	2,392
45	1,170	177.96	178.00	177.93	2,691
50	1,300	197.96	198.00	197.93	2,990
55	1,430	217.96	218.00	217.93	3,289
60	1,560	237.96	238.00	237.93	3,588
65	1,690	257.96	258.00	257.93	3,887
70	1,820	277.96	278.00	277.93	4,186
75	1,950	297.96	298.00	297.93	4,485
80	2,080	317.96	318.00	317.93	4,784
85	2,210	337.96	338.00	337.93	5,083
90	2,340	357.96	358.00	357.93	5,382
95	2,470	377.96	378.00	377.93	5,681
100	2,600	397.96	398.00	397.93	5,980
105	2,730	417.96	418.00	417.93	6,279
110	2,860	437.96	438.00	437.93	6,578
115	2,990	457.96	458.00	457.93	6,877
120	3,120	477.96	478.00	477.93	7,176
125	3,250	497.96	498.00	497.93	7,475

- ⁴ Fabricator will adjust lengths for girder slopes as required.
- ⁵ Reinforcing steel weight is calculated using an approximate factor of 2.3 lbs/SF.

MATERIAL NOTES:

Provide Class 5 concrete ($f'_c = 4,000$ psi).
 Provide Class 5 (HPC) concrete if shown elsewhere in the plans.
 Provide Grade 60 reinforcing steel.
 Provide bar laps, where required, as follows:
 Uncoated ~ #4 = 1'-7"
 Epoxy coated ~ #4 = 2'-5"
 Deformed welded wire reinforcement (WWR) (ASTM A1064) of equal size and spacing may be substituted for Bars A, AA, D, OA, P or T unless noted otherwise.

GENERAL NOTES:

Designed according to AASHTO LRFD Bridge Design Specifications.
 Multi-span units, with slab continuous over interior bents, may be formed with the details shown on this sheet and the I-Girder Continuous Slab Detail (IGCS) standard.
 See I-Girder Thickened Slab End Details (IGTS) standard for details and quantity adjustments.
 See Prestressed Concrete Panels (PCP) standard and Prestressed Concrete Panel Fabrication Details (PCP-FAB) standard for panel details not shown.
 See I-Girder Miscellaneous Slab Details (IGMS) standard for miscellaneous details.
 See applicable rail details for rail anchorage in slab.
 See Permanent Metal Deck Forms (PMDf) standard for details and quantity adjustments if this option is used.
 This standard is drawn showing right forward skew.
 See Bridge Layout for actual skew direction.
 This standard does not support the use of transition bents.

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING SHEET 2 OF 2





PRESTRESSED CONCRETE I-GIRDER SPANS (TYPE T_x28 THRU T_x54) 24' ROADWAY 15° SKEW

SIG-24-15


FILE: IG-SIG2415-23.dgn	DN: JMH	CK: NRN	DW: JTR	CK: TAR
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-19: Increased "X" and "Y" Values. 01-23: Removed PCPN() reference.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	51	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/18/2023 1:38:36 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\bridge\Misc\AJ.dgn



- ① Adjust 6" plate height for overlay thicknesses other than the 2" shown. Adjust weight by 1.70 plf for each 1/2" variation in thickness.
- ② Do not paint top 1/2" of plate if using sealed armor joint.
- ③ Set top of backer rod 1" below top of armor plate. Backer rod must be compatible with joint sealant. Use of multiple pieces to create a backer rod cross section is not permitted. Top of backer rod must be convex as shown.
- ④ Blast clean entire contact area between sealant and plate (SSPC-SP10) before installing sealant. Light brush blast and thoroughly clean all dust and debris from concrete surfaces in contact with joint sealant before application of silicone seal.
- ⑤ Use Class 7 joint sealant that conforms to DMS-6310.
- ⑥ Place sealant while ambient temperature is between 55°F and 80°F and is rising.
- ⑦ Armor joint does not include joint sealant or backer rod.
- ⑧ Armor joint (sealed) includes Class 7 joint sealant and backer rod.
- ⑨ Form vertical leg of seal as per the Manufacturer's recommendations. Use Class 4 joint sealant if Class 7 cannot be installed correctly. Install according to Manufacturer's recommendations.
- ⑩ Unless shown otherwise, terminate armor plate at slab break point if break is more than 2'-0" from slab edge.
- ⑪ See "Plans of Armor Plates".
- ⑫ At Fabricator's option, armor plate may extend up to 6" beyond this point for skews through 15°.
- ⑬ Align shipping angle perpendicular to joint.





FABRICATION NOTES:
 Match mark corresponding plate sections and secure together for shipment with shipping angle. Do not use erection bolts.
 Ship armor joints in convenient lengths of 10'-0" Min and 24'-0" Max unless necessary for stage construction or widenings. One shop splice is permitted in each shipping length provided no piece is less than 2'-0" long and sufficient studs are added to limit the stud to shop splice distance to 2" Min and 4" Max.
 Weld studs in accordance with AWS D1.1.
 Use groove welds for all shop and field butt splices. Grind smooth areas in contact with seal. Make all necessary field splice joint preparations in the shop.
 Paint the entire steel section, except as stated in Note 2, with System II or IV primer in accordance with Item 446 "Field Cleaning and Painting Steel." Provide paints in accordance with Item 446.2. Prepare steel and apply paint in accordance with Items 446.4.7.3 and 446.4.7.4.
 Shop drawings for the fabrication of armor joints will not require the Engineer's approval if fabrication is in accordance with the details shown on this standard.

CONSTRUCTION NOTES:
 Secure armor joints in position and place to proper grade and alignment by welding braces to adjacent reinforcing steel, to prestressed beam stirrups, or to anchors cast in concrete diaphragms. Include cost of temporary bracing in the price bid for Armor Joint.
 Remove shipping angle immediately after each joint half is secured in place. Grind smooth, and touch up with organic zinc-rich paint.

GENERAL NOTES:
 Provide armor joints at locations shown on the plans. Provide the seal when "Armor Joint (Sealed)" is noted on the plans. These joint details accommodate a joint movement range of 1 3/8" (3/4" opening movement and 5/8" closure movement). Payment for armor joint, with or without seal, is based on length of armor plate.


WEIGHTS FOR ONE ARMOR JOINT (2 PLATES)	
WITHOUT OVERLAY	16.10 plf
WITH 2" OVERLAY ①	22.90 plf



				Bridge Division Standard	
<h2>ARMOR JOINT DETAILS</h2>					
AJ					
FILE: ajstd01-19.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
REVISONS	0909	29	046	CR	
	DIST	COUNTY	SHEET NO.		
	WACO	HAMILTON	52		


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:37 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\brldge\MI\sc\CSAB.dgn



OPTION 1 ~ PLAN WITH WINGWALLS

Cast-in-place retaining walls similar.




OPTION 1 ~ PLAN WITH MSE RETAINING WALLS


- ① Usual limit of Cement Stabilized Backfill is at end of wingwall. Extend CSB limits as required to maintain a slope no steeper than 1:1 at bottom of backfill.
- ② Bench backfill as shown with 12" (approximate) bench depths.
- ③ Where MSE retaining walls are present, adjust CSB limits to accommodate the select fill zone. See retaining wall details for additional information.
- ④ When distance between select fill zones is less than 5'-0", MSE select fill may be substituted for cement stabilized backfill with approval from the Engineer.
- ⑤ If shown in the plans flowable backfill can be used as a substitute for cement stabilized backfill with the following constraints:
 - a) If flowable backfill is to be placed over MSE backfill then a filter fabric will be placed over the flowable fill; and
 - b) Place flowable fill in lifts not exceeding 2 feet in height, place each successive lift when the previous lift has stiffened/hardened (i.e. has lost its flowability).

GENERAL NOTES:

See the Bridge Layout for selected Option. Option 2 is intended for new construction requiring high plasticity embankment fill with a plasticity index (PI) greater than 30 or pavement built in poor native soil. Poor soils are defined as high plasticity clays or expansive clays. Option 1 is intended for construction only requiring PI controlled embankment fill or excavation in competent soils/rocks in order to construct the abutment. Provide Cement Stabilized Backfill (CSB) meeting the requirements of Item 400, "Excavation and Backfill for Structures", to the limits shown at bridge abutments. If required elsewhere in the plans, provide Flowable Backfill meeting the requirements of Item 401, "Flowable Backfill", to the limits shown at bridge abutments. Details are drawn showing left forward skew. See Bridge Layout for actual skew direction. These details do not apply when Concrete Block retaining walls are used in lieu of wingwalls.



WITHOUT APPROACH SLAB



WITH APPROACH SLAB
 (Showing BAS-C, BAS-A similar.)

SECTION A-A

SHEET 1 OF 2




CEMENT STABILIZED ABUTMENT BACKFILL BRIDGE ABUTMENT

CSAB

FILE: csabste1-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT	REVISIONS	CONTRACT	SECTION	JOB
	0909	29	046	CR
02-20: Added Option 2.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	53	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:38 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\CSAB.dgn




OPTION 2 ~ PLAN WITH WINGWALLS

Cast-in-place retaining walls similar.




OPTION 2 ~ PLAN WITH MSE RETAINING WALLS

- ① Usual limit of Cement Stabilized Backfill is at end of wingwall. Extend CSB limits as required to maintain a slope no steeper than 1:1 at bottom of backfill.
- ② Bench backfill as shown with 12" (approximate) bench depths.
- ③ Where MSE retaining walls are present, adjust CSB limits to accommodate the select fill zone. See retaining wall details for additional information.
- ④ When distance between select fill zones is less than 5'-0", MSE select fill may be substituted for cement stabilized backfill with approval from the Engineer.
- ⑤ If shown in the plans flowable backfill can be used as a substitute for cement stabilized backfill with the following constraints:
 - a). If flowable backfill is to be placed over MSE backfill then a filter fabric will be placed over the MSE backfill prior to placement of the flowable fill; and
 - b). Place flowable fill in lifts not exceeding 2 feet in height, place each successive lift when the previous lift has stiffened/hardened (i.e. has lost its flowability).



WITHOUT APPROACH SLAB



SECTION B-B

WITH APPROACH SLAB
 (Showing BAS-C, BAS-A similar.)

SHEET 2 OF 2




**CEMENT STABILIZED
 ABUTMENT BACKFILL
 BRIDGE ABUTMENT**


CSAB

FILE: csabste1-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT April 2019	CONV	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
02-20: Added Option 2.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	54	


DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




ABUTMENTS, WINGWALLS AND MULTI-DRILLED SHAFT FOOTINGS




INTERIOR BENTS DRILLED SHAFT DIA EQUAL TO COLUMN DIA



INTERIOR BENTS DRILLED SHAFT DIA GREATER THAN COLUMN DIA



OPTIONAL INTERIOR BENT DRILLED SHAFT DETAIL





DRILLED SHAFT SECTIONS

DRILLED SHAFT DETAILS

TABLE OF PILE EMBEDMENT	
Pile Type	Embedment Depth (Ft)
16" Sq Concrete 18" Sq Concrete HP14 Steel HP16 Steel	1'-0"
20" Sq Concrete 24" Sq Concrete HP18 Steel	1'-6"


See Prestressed Concrete Piling (CP) standard for additional details on concrete pile embedment.

ORIENTATION OF STEEL H-PIILING



VERTICAL PILE BATTERED PILE


PILING DETAILS
(Concrete or steel H)



DETAIL "A"

(Showing plan view of a 30° skewed abutment)

- ① #3 spiral at 6" pitch (one and a half flat turns top and bottom).
- ② Min extension into supported element:
#6 Bars = 1'-11"
#7 Bars = 2'-0"
#9 Bars = 2'-3"
- ③ Min lap with column reinf:
#7 Bars = 2'-11"
#9 Bars = 3'-9"
#11 Bars = 4'-8"
- ④ Min extension into supported element:
#6 Bars = 1'-11"
#7 Bars = 2'-3"
#9 Bars = 2'-9"
- ⑤ Drilled shafts may extend to the bottom of bent caps for "H" heights of 6 ft and less (as shown on the Bridge Layout), if approved. This option can only be used when the drilled shaft diameter equals the column diameter. Obtain approval of the forming method above the ground line prior to construction. No adjustments in payment will be made if this option is used.
- ⑥ 1'-0" Min, unless shown otherwise on plans.
- ⑦ Or as shown on plans.




ELEVATION

SECTION A-A

STEEL H-PILE TIP REINFORCEMENT


See Item 407 "Steel Piling" to determine when tip reinforcement is required and for options to the details shown.



SECTION B-B

STEEL H-PILE SPLICE DETAIL

Use when required.



SECTION THRU FLANGE OR WEB

SHEET 1 OF 2

		Bridge Division Standard	
COMMON FOUNDATION DETAILS			
FD			
FILE: fdst01-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
©TxDOT April 2019	CONTRACT	SECTION	JOB
0909	29	046	CR
01-20: Added #11 bars to the FD bars.	DIST	COUNTY	SHEET NO.
	WACO	HAMILTON	55



DATE: FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: FILE:

TABLE OF FOOTING QUANTITIES FOR 30" COLUMNS


ONE 3 PILE FOOTING				
Bar	No.	Size	Length	Weight
F1	11	#4	3'- 2"	23
F2	6	#4	8'- 2"	33
F3	6	#4	6'- 11"	28
F4	8	#9	3'- 2"	86
F5	4	#9	6'- 11"	94
F6	4	#9	8'- 2"	111
FC	12	#4	3'- 6"	28
FD ⁽¹⁰⁾	8	#9	8'- 1"	220
Reinforcing Steel			Lb	623
Class "C" Concrete			CY	4.8
ONE 4 PILE FOOTING				
Bar	No.	Size	Length	Weight
F1	20	#4	7'- 2"	96
F2	16	#8	7'- 2"	306
FC	16	#4	3'- 6"	37
FD ⁽¹⁰⁾	8	#9	8'- 1"	220
Reinforcing Steel			Lb	659
Class "C" Concrete			CY	6.3
ONE 5 PILE FOOTING				
Bar	No.	Size	Length	Weight
F1	20	#4	8'- 2"	109
F2	16	#9	8'- 2"	444
FC	24	#4	3'- 6"	56
FD ⁽¹⁰⁾	8	#9	8'- 1"	220
Reinforcing Steel			Lb	829
Class "C" Concrete			CY	8.0



THREE PILE FOOTING⁽⁸⁾
For 36" Dia and smaller columns.



FOUR PILE FOOTING⁽⁸⁾
For 42" Dia and smaller columns.



FIVE PILE FOOTING⁽⁸⁾
For 42" Dia and smaller columns.

CONSTRUCTION NOTES:

See Bridge Layout for foundation type required. Use these foundation details unless shown otherwise.
 Drive piling under abutment wingwalls to a minimum resistance of 10 Tons/Pile unless shown otherwise.
 Provide Class C Concrete ($f'_c = 3,600$ psi), unless shown otherwise.
 Provide Grade 60 reinforcing steel.
 Galvanize reinforcing if shown elsewhere in the plans.
 Provide bar laps for drilled shaft reinforcing, where required, as follows:
 Uncoated or galvanized (#6) ~ 2'-6"
 Uncoated or galvanized (#7) ~ 2'-11"
 Uncoated or galvanized (#9) ~ 3'-9"

GENERAL NOTES:


Designed according to AASHTO LRFD Bridge Design Specifications.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.

DESIGNER NOTES:

Do not use the drilled shaft details shown on this standard for retaining wall, noise wall, barrier, or sign foundations without structural evaluation.
 Do not use the footings shown on this standard in direct contact with salt water or exposed to salt water spray.
 Maximum allowable pile loads for the footings shown are:

- 72 Tons/Pile with 24" Dia Columns
- 80 Tons/Pile with 30" Dia Columns
- 100 Tons/Pile with 36" Dia Columns
- 120 Tons/Pile with 42" Dia Columns




- ⁽³⁾ Min lap with column reinforcing:
 #7 Bars = 2'-11"
 #9 Bars = 3'-9"
 #11 Bars = 4'-8"
- ⁽⁶⁾ 1'-0" Min, unless shown otherwise on plans.
- ⁽⁷⁾ Or as shown on plans.
- ⁽⁸⁾ See Bridge Layout for type, size and length of piling.
- ⁽⁹⁾ Number and size of FD bars must match column reinforcing. Tie FD bars to the top of the bottom reinforcing mat.
- ⁽¹⁰⁾ Adjust FD quantity, size and weight as needed to match column reinforcing.

COMMON FOUNDATION DETAILS


FD

FILE: fdstoe01-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT April 2019	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
01-20: Added #11 bars to the FD bars.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	56	


DATE: 2/8/2023 3:33:44 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\1-girder\igcs\igcs.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of drawings to other formats or for incorrect results or damages resulting from its use.





PLAN FOR 0° OR 15° SKEW
(Showing 15° skew)



PLAN FOR 30° OR 45° SKEW
(Showing 30° skew)



PLAN FOR 45° SKEW ④
(Showing short span condition.)



SECTION A-A
Bars OA (Top) not shown for clarity.

- ① Top and bottom mats must be continuous through joint.
- ② Maintain a constant slab thickness over the bent.
- ③ 5'-4" as shown on Span Details.
- ④ Use these details when no full slab width bars A and B are shown on Span Details.
- ⑤ Bars OA (Top) at 9" Max spacing between Bars A (Top).
- ⑥ Values in table assume a temperature change of 70° F after erection when calculating thermal movement in one direction (not total).

TABLE OF ⑥ ALLOWABLE UNIT LENGTH

Max Rdwy Grade, Percent	Unit Length Factor
0.00	4.1
1.00	3.9
2.00	3.7
3.00	3.5
4.00	3.3
5.00	3.1

Unit length must not exceed the length of the shortest end span times the Unit Length Factor shown in table or 400', whichever is less.

BAR TABLE

BAR	SIZE
A	#4
B	#4
D	#4
T	#4
OA	#5

The details shown on this sheet are applicable for two and three span units comprised of the same girder type. Units may be comprised of different span lengths. See "Table of Allowable Unit Length".

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 This standard is drawn showing right forward skew. See Bridge Layout for actual skew direction.

CONSTRUCTION NOTES:
 Where multi-span units are indicated on the Bridge Layout, the thickened slab end details and reinforcement shown on IGTS standard (Bars AA, G, H, J, K, and M) and on the Span Details will be omitted where slabs are continuous over interior bents. At these locations, the slab details and reinforcement will be as shown on this sheet or on PCP standard (if using this option).
 Thickened slab end reinforcement and details still apply at expansion joint locations (ends of units).
 See Span Details for remainder of slab reinforcement and details.


MATERIAL NOTES:
 Provide Grade 60 reinforcing steel.
 Provide Class "S" concrete (f'c = 4,000 psi).
 Provide Class "S" (HPC) if shown elsewhere on the plans.
 Provide bar laps, where required, as follows:
 Uncoated ~ #4 = 1'-7"
 Epoxy Coated ~ #4 = 2'-5"

The details shown on this sheet are applicable for use only with the Prestressed Concrete I-Girder Standard Designs shown on standards IGSD-24, IGSD-28, IGSD-30, IGSD-32, IGSD-34, IGSD-38, IGSD-40 and IGSD-44.

HL93 LOADING

Texas Department of Transportation		Bridge Division Standard
CONTINUOUS SLAB DETAILS		
PRESTR CONC I-GIRDER SPANS		
IGCS		
FILE: IG-IGCS-23.dgn	DN: JMH	CK: TxDOT
DN: August 2017	SECT: 0909	JOB: 29
REV: 01-19: Added bubble note 6.	SECT: 046	JOB: CR
REV: 01-23: Added 34' Rdwy.	DIST: WACO	COUNTY: HAMILTON
		SHEET NO: 57

DATE: 2/8/2023 1:38:41 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\IGD.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of drawings to other formats or for incorrect results or damages resulting from its use.




- ① Bundle with Bars R.
- ② Measured along ξ Girder at interior bents; perpendicular to abutment bkwl or inverted-T stem.
- ③ The average of the top and bottom spacing of Bars R cannot exceed the required spacing.
- ④ L/20, but not less than 5'-0" (-0,+2').

GIRDER ELEVATION


- ⑥ Bars P (#6 x 15'-0") required in Tx62 and Tx70 girders. At the fabricator's option bars larger than #6 may be used. When L is less than 50 ft, Bars P are to be the same length as Bars T.
- ⑦ Bars P (#6 x 15'-0") are only required in Tx28, Tx34, Tx40, Tx46, and Tx54 girders when "e" at girder ends exceeds 0.25 x "D". At the fabricator's option bars larger than #6 may be used. When L is less than 50 ft, Bars P are to be the same length as Bars T.
- ⑧ 1 3/8" Clear Cover to Bars S.
- ⑨ Space Bars A at 6" Max for girders requiring overhang bracket hangers. Space at 12" Max for all other girders. Tie to Bars R as necessary. See standard IGMS for "Deck Forming Notes".
- ⑩ Based on 155 pcf total weight of concrete and reinforcing steel.
- ⑪ Smooth trowel finish on the slab overhang side of exterior girder.

GIRDER DIMENSIONS AND SECTION PROPERTIES								
Girder Type	"D"	"B"	"Yt"	"Yb"	Area	"Ix"	"Iy"	Weight (10)
	(in.)	(in.)	(in.)	(in.)	(in. ²)	(in. ⁴)	(in. ⁴)	(plf)
Tx28	28	6	15.02	12.98	585	52,772	40,559	630
Tx34	34	12	18.49	15.51	627	88,355	40,731	675
Tx40	40	18	21.90	18.10	669	134,990	40,902	720
Tx46	46	22	25.90	20.10	761	198,089	46,478	819
Tx54	54	30	30.49	23.51	817	299,740	46,707	880
Tx62	62	37 1/2"	33.72	28.28	910	463,072	57,351	980
Tx70	70	45 1/2"	38.09	31.91	966	628,747	57,579	1,040


GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications. Provide Class H concrete. Provide Grade 60 reinforcing steel. An equal area of deformed Welded Wire Reinforcement (WWR) (ASTM A1064) may be substituted for Bars A, C, R or T unless otherwise noted. It is permissible for bars or strands to come in contact with materials used in forming anchor holes.
 Cover dimensions are clear dimensions, unless noted otherwise. Reinforcing bar dimensions shown are out-to-out of bar.



TYPE Tx62 & Tx70



TYPE Tx46 & Tx54



TYPE Tx28, Tx34 & Tx40

HL93 LOADING SHEET 1 OF 2

Bridge Division Standard


PRESTRESSED CONCRETE I-GIRDER DETAILS

IGD

FILE: igdstds1-19.dgn	DN: TxDOT	CK: JMH	DW: JTR	CK: TAR
©TxDOT August 2017	CONV	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-19: Added Bars C and CH full length for VC <= 20'	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	58	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:42 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\bridge\I-girder\IGD.dwg




PLAN OF GIRDER ENDS ⁽¹²⁾


To control top flange cracking that may occur during form removal, additional top flange reinforcing may be placed as shown in girder ends at the Fabricator's option.




OPTIONAL TOP FLANGE REINFORCING DETAIL




BARS CH (#4)




BARS C (#4)




BARS U (#5)




BARS A (#3)




OPTIONAL WELDED WIRE REINFORCEMENT (WWR) DETAIL



BARS R (#4) ⁽¹⁶⁾



BARS S (#6)



BARS T (#4)

- ⁽¹²⁾ Reinforcing patterns shown are provided as guides to determine reinforcement placement in skewed ends. Place Bars S as close to girder end as cover requirements permit, which may prevent them to be bundled with Bars R.
- ⁽¹³⁾ Bars may be cut or bent at skewed end as required.
- ⁽¹⁴⁾ Increase as necessary for bars at skewed end.
- ⁽¹⁵⁾ No portion of bar less than 10 ft.
- ⁽¹⁶⁾ For Welded Wire Reinforcement (WWR) option, area of Bars R may be reduced in proportion to the increase in reinforcement yield strength over 60 ksi. Yield strength of WWR is limited to 75 ksi.




PRESTRESSED CONCRETE I-GIRDER DETAILS

IGD


FILE: igdstds1-19.dgn	DN: TxDOT	CK: JMH	DW: JTR	CK: TAR
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-19: Added Bars C and CH full length for VC <= 20'	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	59	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 1:38:42 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\igeb.dgn



AT INVERTED-T BENT W/SKEW




AT CONVENTIONAL INTERIOR BENT W/SKEW




AT ABUTMENT W/SKEW


- ① Dowel at doweled girder end [labeled (D) on Bridge Layout]. Required for outside girder only or as shown on substructure details.
- ② For purposes of computing bearing seat elevations, nominal centerline of bearing must be defined as shown. The actual center of bearing pad may vary from this line.
- ③ For transition bents with backwall, girder and elastomeric bearings must receive the same treatment as shown for abutments.
- ④ When angle exceeds 0°, one or both girder ends must be skewed to maintain the clearance between girder ends as shown in view.
- ⑤ See Table of Bearing Pad Dimensions for bearing size. Girder end skew angles in Table not applicable for this situation. Table reflects girder conflicts of this type on radial bents only.



AT INVERTED-T BENT





AT CONVENTIONAL INTERIOR BENT




AT ABUTMENT

GENERAL NOTES:
 These details accommodate skew angles up to 60°. Shop drawings for approval are required. A bearing layout which identifies location and orientation of all bearings must be developed by the bearing fabricator. Permanently mark each bearing in accordance with the bearing layout. A copy of the bearing layout is to be provided to the Engineer. Cost of furnishing and installing elastomeric bearings, including beveled and embedded steel plates, must be included in unit price bid for "Prestressed Concrete Girders".

GIRDER END DETAILS



GIRDER CONFLICT DETAILS



ELASTOMERIC BEARING AND GIRDER END DETAILS PRESTR CONCRETE I-GIRDERS

IGEB



FILE: igebsts1-17.dgn	DN: AEE	CK: JMH	DW: JTR	CK: TxDOT
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DIST	COUNTY		SHEET NO.	
WACO	HAMILTON		60	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 1:38:43 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\igebstd

Girder Type	Abutments	Int Bents	Inv-T Bents
	Face of Bkwl to Face of Cap	Overall Cap Width	Corbel Width
Tx28 thru Tx54	1'-9"	3'-6"	1'-10 1/2"
Tx62 & Tx70	2'-0"	4'-0"	2'-1 1/2"


Bent Type	Girder Type	Bearing Type (13)	Girder End Skew Angle Range	Pad Size Lgth x Wdth	Pad Clip Dimensions	
					"A"	"B"
ABUTMENTS, INVERTED-T AND TRANSITION BENTS WITH BACKWALLS	Tx28, Tx34, Tx40, Tx46 & Tx54	G-1-"N"	0° thru 21°	8" x 21"	---	---
		G-2-"N"	21°+ thru 30°	8" x 21"	1 1/2"	2 1/2"
		G-3-"N"	30°+ thru 45°	9" x 21"	4 1/2"	4 1/2"
		G-4-"N"	45°+ thru 60°	15" Dia	---	---
	Tx62 & Tx70	G-5-"N"	0° thru 21°	9" x 21"	---	---
		G-6-"N"	21°+ thru 30°	9" x 21"	1 1/2"	2 1/2"
		G-7-"N"	30°+ thru 45°	10" x 21"	4 1/2"	4 1/2"
		G-8-"N"	45°+ thru 60°	10" x 21"	7 1/4"	4 1/4"
CONVENTIONAL INTERIOR BENTS	Tx28, Tx34, Tx40, Tx46 & Tx54	---	---	---	---	---
	Tx62 & Tx70	G-5-"N"	0° thru 60°	9" x 21"	---	---
CONVENTIONAL INTERIOR BENTS WITH SKEWED GIRDER ENDS (GIRDER CONFLICTS) (16)	Tx28, Tx34, Tx40, Tx46 & Tx54	G-1-"N"	0° thru 18°	8" x 21"	---	---
		G-2-"N"	18°+ thru 30°	8" x 21"	1 1/2"	2 1/2"
		G-9-"N"	30°+ thru 45°	8" x 21"	3"	3"
		G-10-"N"	45°+ thru 60°	9" x 21"	6"	3 1/2"
	Tx62 & Tx70	G-5-"N"	0° thru 18°	9" x 21"	---	---
		G-5-"N"	18°+ thru 30°	9" x 21"	---	---
		G-11-"N"	30°+ thru 45°	9" x 21"	1 1/2"	1 1/2"
		G-12-"N"	45°+ thru 60°	9" x 21"	3"	1 3/4"



LAMINATED ELASTOMERIC BEARING PAD
(50 DUROMETER)



ROUND BEARINGS FOR SKEWED GIRDER ENDS AT FACE OF INVERTED-T STEM OR FACE OF BKWL



SKEWED GIRDER ENDS AT INT BENTS, FACE OF INVERTED-T STEM OR FACE OF BKWL

SKEWED GIRDER ENDS AT CONVENTIONAL INTERIOR BENTS (NO GIRDER DOWELS)

BEARING PAD PLACEMENT DIAGRAMS

- (2) For purposes of computing bearing seat elevations, nominal centerline of bearing must be defined as shown. The actual center of bearing pad may vary from this line.
- (6) 3" for inverted-T.
- (7) Place centerline pad as near nominal centerline bearing as possible between limits shown.
- (8) Girder end skew angle is equal to 90° minus the girder angle except at some conflicting girders.
- (9) Provide 2" dia hole only at locations required. See Substructure details for location.
- (10) See Table of Bearing Pad Dimensions for dimensions.
- (11) Maximum and minimum layer thicknesses shown are for elastomer only, on tapered layers.
- (12) Locate Permanent Mark here.
- (13) Indicate BEARING TYPE on all pads. For tapered pads, locate BEARING TYPE on the high side. The Fabricator must include the value of "N" (amount of taper in 1/8" increments) in this mark.
 Examples: N=0, (for 0° taper)
 N=1, (for 1/8" taper)
 N=2, (for 1/4" taper)
 (etc.)
 Fabricated pad top surface slope must not vary from plan girder slope by more than (0.0625" / IN) / IN.
- (14) Substructure dimensions must satisfy the minimums provided to accommodate the elastomeric bearings shown on this standard.
- (15) See sheet 3 of 3 for beveled plate use when slopes exceed 5 percent.
- (16) If girder end is skewed for a girder conflict at an interior bent and a beveled sole plate is required, use bearing type for abutments at this location. Location of bearing centerline is to be set as for abutments in this case.

HL93 LOADING SHEET 2 OF 3

Texas Department of Transportation Bridge Division Standard


ELASTOMERIC BEARING AND GIRDER END DETAILS PRESTR CONCRETE I-GIRDERS

IGEB


FILE: igebstd-17.dgn	DN: AEE	CK: JMH	DW: JTR	CK: TxDOT
©TxDOT August 2017	CONTRACT	SECTION	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	61	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or for any errors or omissions in this standard or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 1:38:44 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\igebstd



NORMAL GIRDER END
RECTANGULAR BEARING PAD




SKewed GIRDER END
CLIPPED RECTANGULAR BEARING PAD




SKewed GIRDER END
15" DIA BEARING PAD

PLAN VIEW OF SOLE PLATE DETAILS




SECTION




HOLE DETAIL

- 17 Cut beveled and embedded plates to match girder end skew. Adjust location of screw and stud as shown when necessary.
- 18 Slotted hole is required at doweled girder end locations.

BEVELED PLATE DETAILS



SIDE ELEVATION



END ELEVATION
 Showing normal girder end.

GIRDER DETAILS

SOLE PLATE NOTES:

Provide constant thickness elastomeric bearings with beveled and embedded steel sole plates in accordance with these details when the girder slope exceeds 5 percent or if otherwise required in the plans. Provide for all girders in the span.

On the shop drawings, dimension sole plates to the nearest 1/16" based on required thickness at centerline of bearing and slope of girder. Thickness tolerance variation from the approved shop drawings is 1/16" +/-, except variation from a plane parallel to the theoretical top surface can not exceed 1/16" total. Bearing surface tolerances listed in Item 424 apply to embedded and beveled plates.

Steel plate must conform to ASTM A36, A572 Gr 50, or A709 Gr 36 or Gr 50. Hot dip galvanize both the embedded plate and beveled sole plate after fabrication. Seal weld caps to embedded plate before galvanizing.

When determining if relocation of screw holes and studs are necessary for skewed girder ends, minimum clearance from screw or stud centerline to plate edge is 1.25".

Tap threads in the embedded plate only. Drill and tap prior to galvanizing.

3/4" Dia screws must be electroplated, socket flat head countersunk cap screws conforming to ASTM F835. Electroplating must conform to ASTM B633, SC 2, Type I. Provide screws long enough to maintain a 3/4" minimum embedment into the embedded plate and galvanized cap. Provide galvanized steel caps (16 ga Min) with a nominal 1" inside diameter and deep enough to accommodate the screws, but not less than 1/2" deep or deeper than 1".

Install beveled sole plates prior to shipping girders. Installed screw heads must not protrude below the bottom of the beveled plate.




ELASTOMERIC BEARING AND GIRDER END DETAILS
PRESTR CONCRETE I-GIRDERS

IGEB


FILE: igebsts1-17.dgn	DN: AEE	CK: JMH	DW: JTR	CK: TxDOT
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	62	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or for the use of this standard in other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 1:38:45 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girders\IGMS.dgn




HAUNCH REINFORCING DETAIL



BARS U (#4)




C-I-P DRAIN DETAIL




TYPICAL PART TRANSVERSE SLAB SECTION WITHOUT PCP


Top reinforcing steel not shown for clarity.



TREATMENT AT GIRDER END FOR SKEWED SPANS



TYPE A JOINT DETAIL



DRAIN DETAIL

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 Payment for Type A joint will be as per Item 454, "Bridge Expansion Joints."
 All other items (reinforcing steel, drains, etc.) shown on this sheet are subsidiary to other bid items.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.

DECK FORMWORK NOTES:
 Overhang bracket hangers are limited to a safe working load of 3,600 lbs, applied to and along the axis of a coil rod at 45 degrees from vertical, regardless of higher loads permitted by hanger manufacturers. Do not place a hanger less than 12" from girder end. Space hangers accordingly.


- ① Space Bars U with girder Bars R in all areas where measured haunch exceeds 3 1/2".
- ② Roughen outside of PVC with coarse rasp or equal to ensure bond with cast-in-place concrete.
- ③ Bars B(#4) spaced at 9" Max with 2" end cover. Overhang option, Contractor's may end alternating bars B(#4) at centerline outside girder.
- ④ Provide Grade 60 reinforcing steel. Provide bar laps, where required, as follows:
 Uncoated ~ #4 = 1'-7"
 Epoxy coated ~ #4 = 2'-5"
- ⑤ Class 7 silicone sealant that conforms to DMS-6310. Install when ambient temperature is between 55°F and 85°F and rising. Engineer to determine allowable hours for sealant application.
- ⑥ 1 1/4" backer rod must be compatible with joint sealant. Use of multiple pieces to create a backer rod cross section is not permitted. Top of backer rod must be convex as shown.
- ⑦ The maximum distance between Type A expansion joints is 100'. See Bridge Layout for location of joints.
- ⑧ Drain entrance formed in rail or sidewalk.
- ⑨ Water may not be discharged onto girders.
- ⑩ All drain pipe and fittings to be 4" diameter (Sch 40) PVC. See Item 481 "Pipe for Drains" for pipe, connections and solvent welding. Bend reinforcing steel to clear PVC 1". Drain length and location is as directed by the Engineer. Drains are not permitted over roadways or railroads, or within 10'-0" of bent caps. Degrease outside of exposed PVC, apply acrylic water base primer, then coat with same surface finishing material as used for outside girder face. Variations of the above designs, as required for the type of rail used and its location on the structure, may be installed with the approval and direction of the Engineer.

SHEET 1 OF 2


				Bridge Division Standard	
MISCELLANEOUS SLAB DETAILS PRESTR CONCRETE I-GIRDERS					
IGMS					
FILE: igmsts1-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR	CK: TxDOT	
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0909	29	046	CR	
10-19: Modified Note 7. Type A now a pay item.	DIST	COUNTY	SHEET NO.		
	WACO	HAMILTON	63		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 1:38:45 PM
 FILE: T:\Road_Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girders\IGMS.dgn




SHOWING EXPANSION JOINTS




**SHOWING CONST JTS OR CONTROLLED JTS
 REINFORCEMENT OVER INV-T BENTS**




BARS W (#4)



DRIP BEAD DETAIL



CHAMFER LIMITS DETAIL (15)



CONTROLLED JOINT DETAIL

(Saw-cutting is not allowed)

- (11) See Layout for joint type.
- (12) Dowels DD (#11) spaced at 5 Ft Max. See Inv-T bents for quantity and location.
- (13) Space Bars Y (#4) at 12" Max. Use 2" end cover. Number of Bars Y must satisfy spacing limit. Place parallel to bent.
- (14) Space Bars W at 12" Max (3" from end of cap). Tilt if necessary to maintain cover requirements. Place parallel to longitudinal slab reinforcement.
- (15) See Span details for type of joint and joint locations.

SHEET 2 OF 2



**MISCELLANEOUS
 SLAB DETAILS
 PRESTR CONCRETE I-GIRDERS**

IGMS

FILE: igmsts1-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR	CK: TxDOT
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-19: Modified Note 7. Type A now a pay item.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	64	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 3:33:45 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\bridge\I-girder\IGSD-24.dgn


STRUCTURE	DESIGNED GIRDERS								DEPRESSED STRAND PATTERN	CONCRETE		OPTIONAL DESIGN				LOAD RATING FACTORS						
	SPAN NO.	GIRDER NO.	GIRDER TYPE	PRESTRESSING STRANDS						NO.	TO END (in)	RELEASE STRGTH f'ci (ksi)	MINIMUM 28 DAY COMP STRGTH f'c (ksi)	DESIGN LOAD COMP STRESS (TOP ϵ) (SERVICE I) Fct(ksi)	DESIGN LOAD TENSILE STRESS (BOT ϵ) (SERVICE III) Fcb(ksi)	REQUIRED MINIMUM ULTIMATE MOMENT CAPACITY (STRENGTH I) (kip-ft)	LIVE LOAD DISTRIBUTION FACTOR		STRENGTH I		SERVICE III	
				NON-STD STRAND PATTERN	TOTAL NO.	SIZE (in)	STRGTH fpu (ksi)	"e" $\bar{\epsilon}$ (in)									"e" END (in)	Moment	Shear	Inv	Opr	Inv
Type Tx28 Girders 24' Roadway 8.5" Slab	40	ALL	Tx28		10	0.6	270	10.48	10.48			4.000	5.000	1.055	-1.423	1382	0.670	0.850	1.56	2.02	1.98	
	45	ALL	Tx28		12	0.6	270	10.48	10.48			4.500	5.000	1.332	-1.744	1525	0.650	0.850	1.58	2.05	1.79	
	50	ALL	Tx28		12	0.6	270	10.48	10.48			4.200	5.000	1.645	-2.113	1657	0.630	0.860	1.25	1.62	1.25	
	55	ALL	Tx28		14	0.6	270	10.48	9.62		2	8.5	4.000	5.000	1.969	-2.490	1919	0.610	0.860	1.27	1.64	1.11
	60	ALL	Tx28		18	0.6	270	10.04	7.81		4	14.5	4.000	5.600	2.320	-2.901	2206	0.600	0.870	1.43	1.86	1.14
	65	ALL	Tx28		22	0.6	270	9.75	6.12		4	24.5	4.300	5.900	2.716	-3.337	2486	0.580	0.870	1.55	2.00	1.14
	70	ALL	Tx28		26	0.6	270	9.56	6.48		4	24.5	5.200	6.300	3.131	-3.802	2793	0.570	0.870	1.26	1.89	1.01
	75	ALL	Tx28		28	0.6	270	9.48	6.62		4	24.5	5.600	7.800	3.572	-4.291	3110	0.560	0.880	1.38	1.81	1.08
Type Tx34 Girders 24' Roadway 8.5" Slab	40	ALL	Tx34		10	0.6	270	13.01	13.01			4.000	5.000	0.835	-1.089	1605	0.690	0.830	1.85	2.40	2.60	
	45	ALL	Tx34		10	0.6	270	13.01	13.01			4.500	5.500	1.050	-1.332	1750	0.670	0.840	1.90	2.46	2.42	
	50	ALL	Tx34		12	0.6	270	13.01	13.01			4.000	5.000	1.294	-1.612	1868	0.650	0.840	1.53	1.98	1.81	
	55	ALL	Tx34		12	0.6	270	13.01	13.01			4.000	5.000	1.553	-1.904	1981	0.630	0.840	1.24	1.61	1.33	
	60	ALL	Tx34		14	0.6	270	13.01	12.44		2	6.5	4.000	5.000	1.845	-2.231	2287	0.620	0.850	1.27	1.64	1.22
	65	ALL	Tx34		16	0.6	270	12.76	11.76		4	8.5	4.000	5.000	2.161	-2.579	2605	0.610	0.850	1.25	1.62	1.06
	70	ALL	Tx34		20	0.6	270	12.41	9.61		4	18.5	4.000	5.100	2.461	-2.902	2888	0.590	0.850	1.46	1.89	1.13
	75	ALL	Tx34		24	0.6	270	12.18	7.84		4	30.5	4.300	5.400	2.818	-3.283	3223	0.580	0.860	1.57	2.04	1.15
	80	ALL	Tx34		26	0.6	270	12.09	8.09		4	30.5	4.700	5.700	3.168	-3.660	3554	0.570	0.860	1.39	1.96	1.04
	85	ALL	Tx34		30	0.6	270	11.81	7.81		6	26.5	5.400	6.100	3.567	-4.078	3909	0.560	0.860	1.46	2.00	1.04
Type Tx40 Girders 24' Roadway 8.5" Slab	40	ALL	Tx40		10	0.6	270	15.60	15.60			4.000	5.000	0.697	-0.889	1671	0.720	0.820	2.10	2.73	3.15	
	45	ALL	Tx40		10	0.6	270	15.60	15.60			4.000	5.000	0.873	-1.080	1972	0.690	0.820	1.74	2.26	2.50	
	50	ALL	Tx40		12	0.6	270	15.60	15.60			4.000	5.000	1.065	-1.299	2276	0.670	0.830	1.78	2.31	2.33	
	55	ALL	Tx40		12	0.6	270	15.60	15.60			4.000	5.000	1.283	-1.538	2237	0.650	0.830	1.46	1.90	1.80	
	60	ALL	Tx40		14	0.6	270	15.60	15.60			4.200	5.000	1.522	-1.801	2434	0.640	0.830	1.49	1.93	1.66	
	65	ALL	Tx40		14	0.6	270	15.60	15.60			4.000	5.000	1.780	-2.081	2688	0.630	0.840	1.24	1.60	1.25	
	70	ALL	Tx40		16	0.6	270	15.35	14.85		4	6.5	4.000	5.000	2.035	-2.349	2989	0.610	0.840	1.28	1.65	1.17
	75	ALL	Tx40		18	0.6	270	15.16	14.27		4	8.5	4.000	5.000	2.328	-2.657	3337	0.600	0.840	1.28	1.66	1.05
	80	ALL	Tx40		22	0.6	270	14.87	11.24		4	24.5	4.000	5.000	2.616	-2.961	3681	0.590	0.850	1.47	1.90	1.11
	85	ALL	Tx40		26	0.6	270	14.68	9.76		4	36.5	4.400	5.100	2.930	-3.287	4041	0.580	0.850	1.60	2.08	1.22
	90	ALL	Tx40		28	0.6	270	14.60	10.03		4	36.5	4.800	5.500	3.259	-3.626	4410	0.570	0.850	1.55	2.01	1.07
	95	ALL	Tx40		32	0.6	270	14.23	8.60		6	36.5	5.100	5.800	3.620	-3.991	4799	0.560	0.850	1.62	2.10	1.06
	100	ALL	Tx40		36	0.6	270	13.93	8.93		6	36.5	5.800	6.600	4.006	-4.393	5245	0.560	0.850	1.47	1.94	1.06
Type Tx46 Girders 24' Roadway 8.5" Slab	40	ALL	Tx46		10	0.6	270	17.60	17.60			4.000	5.000	0.613	-0.708	1732	0.740	0.810	2.35	3.05	3.78	
	45	ALL	Tx46		10	0.6	270	17.60	17.60			4.000	5.000	0.768	-0.865	2066	0.720	0.810	1.93	2.50	3.01	
	50	ALL	Tx46		12	0.6	270	17.60	17.60			4.000	5.000	0.937	-1.042	2452	0.700	0.820	1.97	2.55	2.81	
	55	ALL	Tx46		12	0.6	270	17.60	17.60			4.000	5.000	1.127	-1.235	2726	0.680	0.820	1.63	2.11	2.22	
	60	ALL	Tx46		14	0.6	270	17.60	17.60			4.000	5.000	1.332	-1.438	2951	0.660	0.820	1.68	2.18	2.10	
	65	ALL	Tx46		14	0.6	270	17.60	17.60			4.000	5.000	1.557	-1.662	2905	0.650	0.820	1.41	1.82	1.64	
	70	ALL	Tx46		14	0.6	270	17.60	17.60			4.000	5.000	1.798	-1.898	3157	0.640	0.830	1.18	1.52	1.25	
	75	ALL	Tx46		16	0.6	270	17.35	16.85		4	6.5	4.000	5.000	2.050	-2.137	3495	0.620	0.830	1.23	1.59	1.17
	80	ALL	Tx46		18	0.6	270	17.16	16.27		4	8.5	4.000	5.000	2.304	-2.384	3859	0.610	0.830	1.25	1.63	1.09
	85	ALL	Tx46		22	0.6	270	16.88	15.06		4	14.5	4.000	5.000	2.591	-2.656	4249	0.600	0.830	1.46	1.89	1.30
	90	ALL	Tx46		24	0.6	270	16.77	14.10		4	20.5	4.000	5.000	2.870	-2.923	4631	0.590	0.840	1.45	1.88	1.06
	95	ALL	Tx46		28	0.6	270	16.60	11.46		4	40.5	4.200	5.000	3.192	-3.234	5087	0.590	0.840	1.57	2.03	1.08
	100	ALL	Tx46		32	0.6	270	16.23	9.48		6	42.5	4.400	5.000	3.524	-3.542	5513	0.580	0.840	1.65	2.14	1.07
	105	ALL	Tx46		36	0.6	270	15.94	9.94		6	42.5	5.000	5.800	3.856	-3.851	5937	0.570	0.840	1.72	2.23	1.17
110	ALL	Tx46		38	0.6	270	15.81	10.45		6	40.5	5.400	6.300	4.200	-4.169	6370	0.560	0.840	1.67	2.16	1.04	
115	ALL	Tx46		42	0.6	270	15.60	10.75		6	40.5	6.000	7.000	4.584	-4.532	6886	0.560	0.840	1.46	1.96	1.05	

- ① Based on the following allowable stresses (ksi):
 Compression = 0.65 f'ci
 Tension = 0.24 $\sqrt{f'ci}$
 Optional designs must likewise conform.
- ② Portion of full HL93.

DESIGN NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications. Load rated using Load and Resistance Factor Rating according to AASHTO Manual for Bridge Evaluation. Optional designs for girders 120 feet or longer must have a calculated residual camber equal to or greater than that of the designed girder. Prestress losses for the designed girders have been calculated for a relative humidity of 60 percent. Optional designs must likewise conform.

FABRICATION NOTES:
 Provide Class H concrete. Provide Grade 60 reinforcing steel bars. Use low relaxation strands, each pretensioned to 75 percent of fpu. Strand debonding must comply with Item 424.4.2.2.4. Full-length debonded strands are only permitted in positions marked Δ . Double wrap full-length debonded strands in outer most position of each row. When shown on this sheet, the Fabricator has the option of furnishing either the designed girder or an approved optional design. All optional design submittals must be signed, sealed and dated by a Professional Engineer registered in the State of Texas. Seal cracks in girder ends exceeding 0.005" in width as directed by the Engineer. The fabricator is permitted to decrease the spacing of Bars R and S by providing additional bars to help limit crack width provided the decreased spacing results in no less than 1" clear between bars. The fabricator must take an approved corrective action if cracks greater than 0.005" form on a repetitive basis.

DEPRESSED STRAND DESIGNS:
 Locate strands for the designed girder as low as possible on the 2" grid system unless a non-standard strand pattern is indicated. Fill row "2.5", then row "4.5", then row "6.5", etc., beginning each row in the "A" position and working outward until the required number of strands is reached. All strands in the "A" position must be depressed, maintaining the 2" spacing so that, at the girder ends, the upper two strands are in the position shown in the table.



HL93 LOADING SHEET 1 OF 2

Texas Department of Transportation Bridge Division Standard

PRESTRESSED CONCRETE I-GIRDER STANDARD DESIGNS

24' ROADWAY



IGSD-24

FILE: ig01stds-21.dgn	DN: EFC	CK: AJF	DW: EFC	CK: TAR
©TxDOT August 2017	CONV	SECT	JOB	HIGHWAY
10-19: Redesign girders.	0909	29	046	CR
1-21: Added load rating.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	65	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 3:33:46 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girder\IGSD-24.dgn

STRUCTURE	DESIGNED GIRDERS									DEPRESSED STRAND PATTERN		CONCRETE		OPTIONAL DESIGN					LOAD RATING FACTORS			NON-STANDARD STRAND PATTERNS	
	SPAN NO.	GIRDER NO.	GIRDER TYPE	PRESTRESSING STRANDS					NO.			TO END (in)	RELEASE STRGTH f'ci (ksi)	MINIMUM 28 DAY COMP STRGTH f'c (ksi)	DESIGN LOAD COMP STRESS (TOP ϵ) Fct(ksi)	DESIGN LOAD TENSILE STRESS (BOT ϵ) Fcb(ksi)	REQUIRED MINIMUM ULTIMATE MOMENT CAPACITY (STRENGTH I) (kip-ft)	LIVE LOAD DISTRIBUTION FACTOR		STRENGTH I			
				NON-STD STRAND PATTERN	TOTAL NO.	SIZE (in)	STRGTH fpu (ksi)	"e" $\bar{\epsilon}$ (in)		"e" END (in)	Moment							Shear	Inv	Opr	Inv		
Type Tx54 Girders 24' Roadway 8.5" Slab	40	ALL	Tx54		8	0.6	270	21.01	21.01			4.000	5.000	0.511	-0.578	1798	0.770	0.800	2.05	2.66	3.76	<p>① Based on the following allowable stresses (ksi):</p> <p>Compression = 0.65 f'ci</p> <p>Tension = 0.24 $\sqrt{f'ci}$</p> <p>Optional designs must likewise conform.</p> <p>② Portion of full HL93.</p>	
	45	ALL	Tx54		10	0.6	270	21.01	21.01			4.000	5.000	0.636	-0.703	2126	0.740	0.800	2.24	2.90	3.69		
	50	ALL	Tx54		12	0.6	270	21.01	21.01			4.000	5.000	0.781	-0.850	2533	0.720	0.810	1.81	2.35	2.91		
	55	ALL	Tx54		12	0.6	270	21.01	21.01			4.000	5.000	0.938	-1.007	2951	0.700	0.810	1.90	2.46	2.79		
	60	ALL	Tx54		12	0.6	270	21.01	21.01			4.000	5.000	1.108	-1.173	3271	0.680	0.810	1.60	2.07	2.25		
	65	ALL	Tx54		14	0.6	270	21.01	21.01			4.000	5.000	1.285	-1.348	3547	0.670	0.810	1.66	2.16	2.16		
	70	ALL	Tx54		14	0.6	270	21.01	21.01			4.000	5.000	1.482	-1.540	3502	0.660	0.820	1.41	1.82	1.73		
	75	ALL	Tx54		16	0.6	270	20.76	20.26	4	6.5	4.000	5.000	1.689	-1.733	3745	0.640	0.820	1.47	1.91	1.66		
	80	ALL	Tx54		16	0.6	270	20.76	20.76			4.000	5.000	1.912	-1.944	4001	0.630	0.820	1.26	1.63	1.30		
	85	ALL	Tx54		18	0.6	270	20.56	19.67	4	8.5	4.000	5.000	2.148	-2.166	4406	0.620	0.820	1.07	1.39	1.00		
	90	ALL	Tx54		20	0.6	270	20.41	19.21	4	10.5	4.000	5.000	2.379	-2.384	4806	0.610	0.820	1.33	1.73	1.16		
	95	ALL	Tx54		22	0.6	270	20.28	18.46	4	14.5	4.000	5.000	2.639	-2.624	5234	0.600	0.820	1.35	1.75	1.07		
	100	ALL	Tx54		26	0.6	270	20.08	16.39	4	28.5	4.000	5.000	2.896	-2.871	5699	0.600	0.830	1.52	1.97	1.14		
	105	ALL	Tx54		30	0.6	270	19.81	12.21	6	44.5	4.000	5.000	3.180	-3.130	6153	0.590	0.830	1.51	1.96	1.02		
	110	ALL	Tx54		32	0.6	270	19.63	11.38	6	50.5	4.100	5.000	3.477	-3.400	6619	0.580	0.830	1.63	2.12	1.03		
115	ALL	Tx54		36	0.6	270	19.34	12.01	6	50.5	4.700	5.500	3.786	-3.679	7096	0.570	0.830	1.60	2.07	1.00			
120	ALL	Tx54		38	0.6	270	19.22	13.22	6	44.5	5.200	6.100	4.116	-3.985	7646	0.570	0.830	1.65	2.14	1.01			
125	ALL	Tx54		42	0.6	270	19.01	12.72	6	50.5	5.600	6.600	4.415	-4.257	8113	0.560	0.830	1.71	2.24	1.09			
Type Tx62 Girders 24' Roadway 8.5" Slab	60	ALL	Tx62		12	0.6	270	25.78	25.78			4.000	5.000	0.878	-0.986	3525	0.700	0.800	1.81	2.35	2.73		
	65	ALL	Tx62		12	0.6	270	25.78	25.78			4.000	5.000	1.016	-1.133	3847	0.690	0.800	1.89	2.45	2.64		
	70	ALL	Tx62		14	0.6	270	25.78	25.78			4.000	5.000	1.171	-1.293	4173	0.680	0.810	1.61	2.08	2.16		
	75	ALL	Tx62		14	0.6	270	25.78	25.78			4.000	5.000	1.332	-1.455	4132	0.660	0.810	1.68	2.18	2.10		
	80	ALL	Tx62		16	0.6	270	25.53	25.53			4.000	5.000	1.506	-1.633	4429	0.650	0.810	1.45	1.88	1.72		
	85	ALL	Tx62		16	0.6	270	25.53	25.53			4.000	5.000	1.691	-1.819	4610	0.640	0.810	1.24	1.61	1.37		
	90	ALL	Tx62		16	0.6	270	25.53	25.53			4.000	5.000	1.885	-2.013	5051	0.630	0.810	1.29	1.68	1.31		
	95	ALL	Tx62		20	0.6	270	25.18	24.78	4	6.5	4.000	5.000	2.081	-2.209	5493	0.620	0.820	1.11	1.44	1.02		
	100	ALL	Tx62		22	0.6	270	25.05	23.96	4	10.5	4.000	5.000	2.295	-2.420	5959	0.610	0.820	1.16	1.50	1.01		
	105	ALL	Tx62		24	0.6	270	24.94	23.28	4	14.5	4.000	5.000	2.514	-2.642	6475	0.610	0.820	1.37	1.78	1.10		
	110	ALL	Tx62		26	0.6	270	24.85	22.70	4	18.5	4.000	5.000	2.723	-2.850	6936	0.600	0.820	1.39	1.80	1.03		
	115	ALL	Tx62		30	0.6	270	24.58	17.78	6	40.5	4.000	5.000	2.963	-3.083	7440	0.590	0.820	1.56	2.02	1.09		
	120	ALL	Tx62		34	0.6	270	24.25	15.07	6	58.5	4.200	5.000	3.213	-3.325	7957	0.580	0.820	1.55	2.01	1.00		
	125	ALL	Tx62		36	0.6	270	24.11	17.11	6	48.5	4.700	5.600	3.480	-3.591	8551	0.580	0.820	1.64	2.13	1.04		
	130	ALL	Tx62		40	0.6	270	23.88	16.68	6	54.5	5.100	6.100	3.733	-3.836	9072	0.570	0.820	1.52	2.09	1.02		
135	ALL	Tx62		42	0.6	270	23.78	16.35	6	58.5	5.300	6.300	4.002	-4.104	9676	0.570	0.830	1.61	2.18	1.05			



HL93 LOADING SHEET 2 OF 2




**PRESTRESSED CONCRETE
I-GIRDER STANDARD
DESIGNS
24' ROADWAY**

IGSD-24

FILE: ig01stds-21.dgn	DN: EFC	CK: AJF	DW: EFC	CK: TAR
©TxDOT August 2017	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
10-19: Redesign girders. 1-21: Added load rating.	DIST	COUNTY	SHEET NO.	
	WACO	HAMILTON	66	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:48 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\bridge\I-1-girders\IGSK.dgn



PARTIAL PLANS WITH NO SKEW

Showing shear keys on 3'-6" wide caps. 4'-0" caps similar.

PARTIAL PLANS WITH 15° SKEW

Showing shear keys on 3'-6" wide caps. 4'-0" caps similar.


PARTIAL PLANS WITH 30° SKEW

Showing shear keys on 3'-6" wide caps. 4'-0" caps similar.

PARTIAL PLANS WITH 45° SKEW


Showing shear keys on 3'-6" wide caps. 4'-0" caps similar.

- ① Place shear keys on the upstream side of structure between outside girder and next adjacent girder, unless shown otherwise on plans.
- ② UHMW polyethylene wear pad. (Typ)
- ③ Leave a 1/4" gap plus or minus between girder and face of wear pad. Cast wear pad with shear key, smooth side facing girder. Care must be taken to keep concrete from flowing under girder. Slope top of shear keys in accordance with Item 420.4.9, "Treatment and Finishing of Horizontal Surfaces."
- ④ Measure at higher bearing seat elevation forward or back. Dimension based on typical bearing pad and bearing seat. Increase as necessary to maintain 5" overlap.
- ⑤ With No Skew = 1'-8 1/4", measured along cap. With Skew = 1'-8 1/4" * Cos Skew, measured along cap.
- ⑥ With No Skew = 1'-4 1/4", measured along cap. With Skew = 1'-4 1/4" * Cos Skew, measured along cap.
- ⑦ Face of UHMW polyethylene wear pad. Smooth side of pad facing girder.
- ⑧ Abutments = 1/2 Cap width. Interior bents = Cap width.
- ⑨ Abutments = 1/2 Cap width * Cos Skew. Interior bents = Cap width * Cos Skew.




PARTIAL ELEVATION OF ABUTMENT OR INTERIOR BENT CAP

Showing shear key with girder Type Tx46. Other I-Girder types similar.




ELEVATION




PART SECTION


ULTRA HIGH MOLECULAR WEIGHT (UHMW) POLYETHYLENE WEAR PAD DETAILS



BARS M (#5)



BARS Na (#5) (For abutments)



BARS Nb (#5) (For interior bents)

CONSTRUCTION NOTES:
 Provide Class "C" concrete (f'c = 3,600 psi). Provide Class "C" (HPC) if shown elsewhere on the plans.
 Provide Grade 60 reinforcing steel.
 Provide epoxy coated reinforcing steel for shear key if abutment or interior bent reinforcing steel is epoxy coated.
 Provide Ultra High Molecular Weight (UHMW) polyethylene wear pads in accordance with ASTM D6712.


GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications. Details showing skew are drawn showing right forward skew. See Bridge Layout for actual skew direction.
 These details are limited to bridges skewed 45 degrees and less. This standard is only applicable for I-Girders.
 Modify details for bearing conditions, and girder spacing not shown on this standard. Details do not account for sole plate or pedestal bearing seat.
 Include shear key concrete in abutment or bent concrete for payment.
 UHMW polyethylene wear pads are subsidiary to Class "C" concrete.

Cover dimensions are clear dimensions, unless noted otherwise. Reinforcing bar dimensions shown are out-to-out of bar.


		Bridge Division Standard	
SHEAR KEY DETAILS PRESTR CONCRETE I-GIRDERS			
IGSK			
FILE: igskstds-17.dgn	DN: TxDOT	CK: TxDOT	DW: JTR
©TxDOT August 2017	CONTRACT: 0909	SECTION: 29	JOB: 046
REVISIONS	DIST: WACO	COUNTY: HAMILTON	HIGHWAY: CR
			SHEET NO. 67

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or for the use of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:49 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\bridge-I-Girder\IGTS.dwg




PARTIAL PLAN FOR SLABS WITHOUT BREAKBACK



PARTIAL PLAN FOR SLABS WITH BREAKBACK


- 1 End top transverse reinforcing steel at inside Bar G. End bottom transverse reinforcement steel 1'-0" beyond inside Bar G.
- 2 "A" = ("OH" + 2.333' - "B") x Tan ϕ
- 3 Provide clear cover as indicated unless otherwise shown on Span Details.
- 4 Only required on slabs with breakbacks.
- 5 Thickened slab end dimensioned perpendicular to face of bkwl, centerline interior bent or face of inverted-T stem.




GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications. These details are restricted to Prestressed Concrete I-Girder Spans. These details are to be used in conjunction with the Span Details and PCP standard (if prestressed concrete panels are used). When Option 2 from PCP standard is used, provide Bars AA, G, K and OA in the slab.

MATERIAL NOTES:
 Provide Grade 60 reinforcing steel. If slab reinforcing steel is shown on the Slab Details to be epoxy coated, then Bars AA, G, K, H, J, M and OA must be epoxy coated. Provide bar laps, where required, as follows:
 Uncoated ~ #4 = 1'-7"
 Epoxy Coated ~ #4 = 2'-5"

Cover dimensions are clear dimensions, unless noted otherwise. Reinforcing bar dimensions shown are out-to-out of bar.




TYPICAL TRANSVERSE SECTION
 (Showing Prestressed Conc I-Girders at ϕ Brg)




SECTION A-A
 (Showing with 2" and more of haunch)

HL93 LOADING		Texas Department of Transportation		Bridge Division Standard	
THICKENED SLAB END DETAILS					
PRESTRESSED CONCRETE I-GIRDER SPANS					
IGTS					
FILE: igtss1-17.dgn	DN: TxDOT	CK: TxDOT	DW: JTR	CK: TxDOT	
©TxDOT August 2017	CONV	SECT	JOB	HIGHWAY	
REVISIONS	0909	29	046	CR	
DIST	COUNTY		SHEET NO.		
WACO	HAMILTON		68		

DATE: 2/8/2023 1:38:50 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\bridge\I-Girders\MEBR(C).dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of other formats or for incorrect results or damages resulting from its use.




ERECTOR BRACING




FOR ERECTOR BRACING, OPTION 1

(This option is not allowed when slab is formed with PMDF or plywood.)




FOR ERECTOR BRACING, OPTION 2

HORIZONTAL BRACING DETAILS (5)




DETAIL "B"




PLAN

END VIEW



DIAGONAL BRACING DETAILS (5)

(To be used on both ends of the first girder/beam erected in the span in each phase.)



ELEVATION


PLAN

ANGLE BRACE DETAILS

HAULING & ERECTION:
 The Contractor's attention is directed to the possible lateral instability of prestressed concrete girders and beams over 130' long, especially during hauling and erection. The use of the following methods to improve stability is encouraged: Locate lifting devices at the maximum practical distance from girder ends; use external lateral stiffening devices during hauling and erection; lift with vertical lines using two machines; and take care in handling to minimize inertial and impact forces.

ERECTOR BRACING:
 Erection bracing details shown are considered the minimum for fulfilling the bracing requirements of Item 425. Required erection bracing must be placed immediately after erection of each girder and remain in place until additional bracing as required for slab placement is in place. This standard is needed in all cases to meet requirements for Slab Placement Bracing.

PHASED CONSTRUCTION:
 Place erection and slab placement bracing for all girders in a phase as shown in these details. For phases after first, also place erection and slab placement bracing between outer girder of completed phase and adjacent girder of current phase. When the phase construction joint is between girders, top bracing can be omitted.



DETAIL "A"


- 1 If angle shown exceeds 120 degrees, move diagonal brace to other side of girder/beam and place square to girder/beam. This may prevent exterior girder from being erected first.
- 2 Place and weld #5 bars as shown during erection. If forming deck with prestressed panels, bars can be temporarily removed, one at a time, during panel erection. Re-install bar prior to additional panel erection. Bars can rest on panels and be bent down and welded to girder Bars R (See Sheet 2 of 2).
- 3 Clear distance between spacers must not exceed 3'. Nail together with 16d nails.
- 4 Use wedges as necessary to obtain tight fit. Nail wedges to timbers.
- 5 Pressure treated landscape timbers can not be used.
- 6 All hardware used with cable must be able to develop a minimum 25 kips breaking strength. Use thimbles at all loops in cable. Install cable clamps with saddles bearing against the live end and U-bolts bearing against the dead end.
- 7 It is acceptable to tie anchor bolts to cap reinforcement.
- 8 Prior to installing, field bend strap to lay flush on both girders' top flange and slope between flange tips.
- 9 Anchor bolt may be drilled and epoxied in place. Provide 25k minimum pullout. Core drill hole.

SHEET 1 OF 2

				Bridge Division Standard	
MINIMUM ERECTOR AND BRACING REQUIREMENTS PRESTRESSED CONCRETE I-GIRDERS AND I-BEAMS					
MEBR(C)					
FILE: mebcsts1-17.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CK: TxDOT	
©TxDOT August 2017	CONTRACT	SECTION	JOB	HIGHWAY	
REVISIONS	0909	29	046	CR	
	DIST	COUNTY	SHEET NO.		
	WACO	HAMILTON	69		


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any information from other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:50 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\I-girders\MEBR(C).dgn




SLAB PLACEMENT BRACING

TABLE A					
OPTION 1-RIGID BRACING (STEEL STRAP)		OPTION 2-FLEXIBLE BRACING (NO. 5 OVER PCP)			
Girder or Beam Type	Maximum Bracing Spacing		Girder or Beam Type	Maximum Bracing Spacing	
	Slab Overhang less than 4'-0" (11)	Slab Overhang 4'-0" and greater (11)		Slab Overhang less than 4'-0" (11)	Slab Overhang 4'-0" and greater (11)
Tx28	1/4 points	1/4 points	Tx28	1/4 points	1/8 points
Tx34	1/4 points	1/4 points	Tx34	1/4 points	1/8 points
Tx40	1/4 points	1/8 points	Tx40	1/4 points	1/8 points
Tx46	1/4 points	1/8 points	Tx46	1/4 points	1/8 points
Tx54	1/4 points	1/8 points	Tx54	1/4 points	1/8 points
Tx62	1/4 points	1/8 points	Tx62	1/4 points	1/8 points
Tx70	1/4 points	1/8 points	Tx70	1/4 points	1/8 points
A	1/8 points	1/8 points	A	2.0 ft	1.5 ft
B	1/8 points	1/8 points	B	3.0 ft	2.0 ft
C	1/8 points	1/8 points	C	4.5 ft	2.0 ft
IV	1/4 points	1/8 points	IV	1/4 points	4.0 ft
VI	1/4 points	1/8 points	VI	1/4 points	4.0 ft



FOR SLAB PLACEMENT BRACING, OPTION 1 - RIGID


(Showing slab formed with PCP. This option is not allowed when slab is formed with PMDF or plywood.)



FOR SLAB PLACEMENT BRACING, OPTION 2 - FLEXIBLE

(Showing slab formed with PCP.)

HORIZONTAL BRACING DETAILS (5)



DETAIL "B"


- (2) Place and weld #5 bars as shown during erection. If forming deck with prestressed panels, bars can be temporarily removed, one at a time, during panel erection. Re-install bar prior to additional panel erection. Bars can rest on panels and be bent down and welded to girder Bars R.
- (3) Clear distance between spacers must not exceed 3'. Nail together with 16d nails.
- (4) Use wedges as necessary to obtain tight fit. Nail wedges to timbers.
- (5) Pressure treated landscape timbers can not be used.
- (8) Prior to installing, field bend strap to lay flush on both girders' top flange and slope between flange tips.
- (10) Bracing spacing (1/4 and 1/8 points) measured between first and last typical brace location.
- (11) Measure slab overhang from centerline of girder or beam. When overhang varies in span, determine bracing spacing based on largest overhang.

SLAB PLACEMENT BRACING:
 The details for slab placement bracing are considered minimum for fulfilling the requirements of Specification Items 422 and 425. Required slab placement bracing must remain in place until slab concrete has attained a compressive strength of 3000 psi.

GENERAL NOTES:
 Bracing details for spans longer than 150' are not provided. The Contractor must submit proposed bracing details for such conditions to the Engineer for approval prior to erection. Systems equal to or better than those shown may be used provided details of such systems are submitted to and approved by the Engineer prior to erection. Use of these systems or details does not relieve the Contractor of the responsibility for the adequacy of the bracing and the safety of the structure. Removal of bracing for short periods of time to align girders and beams is permissible. All turn-buckles, come-alongs, anchors and other connections must be capable of developing the full strength of the cable shown. Furnish anchor bolts and nuts in accordance with Item 449, "Anchor Bolts".


				Bridge Division Standard	
MINIMUM ERECTION AND BRACING REQUIREMENTS PRESTRESSED CONCRETE I-GIRDERS AND I-BEAMS					
MEBR(C)					
FILE: mebcsts1-17.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
©TxDOT August 2017	CONTRACT	SECTION	JOB	HIGHWAY	
REVISIONS	0909	29	046	CR	
	DIST	COUNTY	SHEET NO.		
	WACO	HAMILTON	70		

DATE: 2/8/2023 1:38:51 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\bridge\MI\sc\PCP\ldg\HL93 Loading\Sheet 1 of 4.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




NORMAL GRADING DETAIL ③

Showing prestressed concrete I-girders.
(Other beam types similar)




SPECIAL GRADING DETAIL FOR CONCRETE BEAMS

Showing prestressed concrete I-girders.
(Other beam types similar)



HAUNCH REINFORCING DETAIL


Showing prestressed concrete I-girders.
(Other beam types similar)



PRESTR CONC I-GIRDERS


WIDTH	HEIGHT ④	
	Min	Max
1" (Min)	1/2"	2"
1 1/4"	1/2"	2 1/2"
1 1/2"	1/2"	3"
1 3/4"	1/2"	3 1/2"
2"	1/2"	4"
2 1/4"	1/2"	4 1/2" ②
2 1/2"	1/2"	5" ②
2 3/4"	1/2"	5 1/2" ②
3" (Max)	1/2"	6" ②

- ① 2" Min for I-girders, 1 1/2" Min for all other beam types.
- ② Allowed for I-girders, not allowed on other beam types.
- ③ To reduce the quantity of cast-in-place concrete, bedding strip thickness may be increased in 1/4" increments. Bedding strips must be comprised of one layer. Bond bedding strips to the beams with an adhesive compatible with bedding strips. Bedding strips over 2.5" high may need to be bonded to panels. The same thickness strip must be used under any one panel edge and the maximum change in thickness between adjacent panels is 1/4". Alternatively, bedding strips may be cut to grade. Panels may be supported by an alternate method, using a commercial product, if approved by the Engineer of Bridge Design, Bridge Division. If bedding strips exceed 6" high for I-Girders, 4" high for all other beam types, use Special Grading Detail for Concrete Beams or submit an alternate method to the Bridge Division for approval.
- ④ Height must not exceed twice the width.
- ⑤ Provide clear cover as indicated unless otherwise shown on Span Details.
- ⑥ See Span Details and Thickened Slab End Details for top slab reinforcement and clear cover. Transverse top slab reinforcement may rest on top of prestressed concrete panels if necessary to maintain clear cover.
- ⑦ Space Bars UP(#4) with Beam Bars R(#4) in all areas where measured haunch exceeds 3 1/2" with I-girders, and 3" for all other beam types. Epoxy coating for Bars UP is not required.
- ⑧ Do not locate construction joints on top of a panel.
- ⑨ Butt adjacent bedding strips together with adhesive. Cut v-notches, approx 1/4" deep, in the top of the bedding strips at 8' o.c..




BARS UP (#4) ⑦

Seal joint between panels when gap exceeds 1/4" with polyurethane sealant or expanding foam sealer. Make seal flush with top of panel.




PANEL JOINTS

(Panel reinforcing not shown for clarity. The gap cannot be considered as a panel fabrication tolerance. Adjust panel placement to minimize joint openings.)



PRESTR CONC I-BEAMS



BEDDING STRIP DETAIL ⑨

CONSTRUCTION NOTES:
 Erected panels must bear uniformly on bedding strips of extruded polystyrene placed along top flange edges. Placing panels to minimize joint openings is recommended. If additional blocking is needed, special grading details for supporting the panels and extra reinforcing between beam and slab will be considered subsidiary to deck construction. Bars U, shown on PCP-FAB, may be bent over or cut off if necessary. Care must be taken to ensure proper cleaning of construction debris and consolidation of concrete material under the edges of the panels. Bedding strips must be placed at beam flange edges so that adequate space is provided for the mortar to flow a minimum of 1 1/2" under the panels as the slab concrete is placed. To allow the proper amount of mortar to flow between beam and panel, the minimum vertical opening must be at least 1/2". Roadway cross-slope reduces the opening available for entry of the mortar. Bedding strips varying in thickness across the beam are therefore required. For clear span between U-beams less than or equal to 18", see Permissible Slab Forming Detail on Miscellaneous Slab Detail sheets, UBMS.

MATERIAL NOTES:
 Provide Grade 60 reinforcing steel in the cast-in-place slab. See Table of Reinforcing Steel for size and spacing of reinforcement. If the top and bottom layer of reinforcing steel is shown on the Span Details to be epoxy coated, then the D, E, P, & Z bars must be epoxy coated. Provide bar Laps, where required, as follows:
 Uncoated ~ #4 = 1'-7"
 Epoxy Coated ~ #4 = 2'-5"


GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications. Panel placement may follow either Option 1 or Option 2 except Option 1 must be used if the skew exceeds 45 degrees. Use of Prestressed Concrete Panels is not permitted for horizontally curved steel plate or tub girders. See Span Details for other possible restrictions on their use. These details are to be used in conjunction with the Span Details, PCP-FAB and other applicable standard drawings. When panel support (bedding strips) deviates from what is shown herein, provide details signed and sealed by a professional Engineer. Any additional reinforcing or concrete required on this standard is considered subsidiary to the bid item "Reinforced Concrete Slab".

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.


HL93 LOADING SHEET 1 OF 4

		Bridge Division Standard	
PRESTRESSED CONCRETE PANELS DECK DETAILS			
PCP			
FILE: pcpstd1-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR
©TxDOT April 2019	CONTRACT: 0909	SECTION: 29	JOB: 046
REVISIONS	DIST: WACO		COUNTY: HAMILTON
			SHEET NO. 71


DATE: 2/8/2023 1:38:52 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\br\ldge\m\sc\pcp\dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




PRESTRESSED CONCRETE I-BEAMS




STEEL BEAMS



PRESTRESSED CONCRETE I-GIRDERS




PRESTRESSED CONCRETE X-BEAMS



NORMAL OVERHANG WITH PRESTR CONC U-BEAMS


TYPICAL PART TRANSVERSE SECTIONS

SLOPED OVERHANG WITH PRESTR CONC U-BEAMS



AT FLARED BEAMS OR GIRDERS


See PCP-FAB standard for Min and Max dimensions based on beam/girder type.




OVER CONC U-BEAMS

PART PLANS OF PANEL PLACEMENT

- 5 Provide clear cover as indicated unless otherwise shown on Span Details.
- 6 See Span Details and Thickened Slab End Details for top slab reinforcement and clear cover. Transverse top slab reinforcement may rest on top of prestressed concrete panels if necessary to maintain clear cover.
- 9 Butt adjacent bedding strips together with adhesive. Cut v-notches, approx 1/4" deep, in the top of the bedding strips at 8' o.c..
- 10 Equally space additional bar if more than 1'-3" Max.
- 11 The actual thickness constructed may exceed the slab thickness shown on the Span Details but the extra thickness may be no more than 2" (1" for prestressed concrete U-beams and steel beams). Bearing seat elevations or finished grade may be adjusted.
- 12 Field adjust Bars Z1(#4) to match actual slope of slab overhangs. Width of slab overhang will vary along span with curved slab edges. Adjust Bar Z1(#4) dimensions to maintain proper cover. Bars Z2(#4) are located at Inverted-Tee stems only.
- 13 Location of concrete placement sequence boundaries and bolted field splices should be considered by the contractor in determining panel limits.




AT INT SUPPORTS OF CONTINUOUS STEEL GIRDERS



PLAN AT SPLICE


(Showing steel beams with flange width transition)

Cut bedding strip to adjust for difference in flange thickness.




ELEVATION AT SPLICE

(Showing steel beams with different flange thickness)



PRESTRESSED CONCRETE SPREAD SLAB BEAMS


Bars P over exterior beams are still required when no overhang is used. In this case, only one Bar D, 2" from slab edge, is required.



BARS Z (#4) (12)


		Bridge Division Standard	
PRESTRESSED CONCRETE PANELS DECK DETAILS			
PCP			
FILE: pcpstd1-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR
REV: April 2019	CONTRACT: 0909	SECTION: 29	JOB: 046
REVISIONS:	DIST: WACO	COUNTY: HAMILTON	SHEET NO: 72

DATE: 2/8/2023 1:38:52 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\bridge\MI\sc\PCP\19.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




AT ALL SPAN ENDS UNLESS NOTED OTHERWISE
 AT INTERIOR BENTS
 AT THICKENED END SLABS

OPTION 1 ~ PLAN OF SLABS WITH NORMAL REINFORCEMENT




AT ALL SPAN ENDS UNLESS NOTED OTHERWISE
 AT INTERIOR BENTS
 AT THICKENED END SLABS

OPTION 1 ~ PLAN OF SLABS WITH SKEWED REINFORCEMENT



AT THICKENED SLAB ENDS FOR PRESTR CONC U-BMS
 AT THICKENED SLAB ENDS FOR PRESTR CONC I-BMS AND STEEL BMS
 AT SLAB CONTINUOUS OVER CONVENTIONAL INTERIOR BENTS FOR ALL SIMPLE SPAN BMS



AT CONVENTIONAL END DIAPHRAGMS FOR STEEL BMS
 AT SLAB OVER ABUTMENT BACKWALL FOR ALL BMS
 AT SLAB CONTINUOUS OVER INVERTED-T BENTS FOR ALL BMS

OPTION 1 ~ ELEVATIONS AT BEAM ENDS

- 6 See Span Details and Thickened Slab End Details for top slab reinforcement and clear cover. Transverse top slab reinforcement may rest on top of prestressed concrete panels if necessary to maintain clear cover.
- 9 Butt adjacent bedding strips together with adhesive. Cut v-notches, approx 1/4" deep, in the top of the bedding strips at 8' o.c.
- 14 Max Spacing as listed unless otherwise shown.
- 15 At connection with cast-in-place slab, extend longitudinal panel reinforcement. See PCP-FAB for details.
- 16 Maintain one Bar E(#4) parallel to panel ends (Typ).
- 17 Bars E(#4) not continuous over beam flanges must overlap beam flange 6" Min.
- 18 Add flared Bars E(#4) (Min Spa = 6", Max Spa = 12") as required at panel ends.
- 19 Where possible, Bars E(#4) may be extended into overhangs to replace Bars P(#4). Bars Z(#4) are required for sloped overhangs with U-Beams.
- 20 See appropriate thickened slab end details for reinforcing and limits of thickened slab end.

TABLE OF REINFORCING STEEL (14)		
BAR	SIZE	Max Spa (in.)
D	#4	9
E	#4	9
P	#4	18
UP	#4	~
Z	#4	18

HL93 LOADING SHEET 3 OF 4



PRESTRESSED CONCRETE PANELS DECK DETAILS

PCP

FILE: pcpstd1-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR	CK: JMH
©TxDOT April 2019	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DIST	COUNTY		SHEET NO.	
WACO	HAMILTON		73	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:53 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\bridge\MI\sc\PCP\ldg\HL93\loading\std\std04.dgn







TABLE OF REINFORCING STEEL (14)		
BAR	SIZE	Max Spa (in.)
D	#4	9
E	#4	9
P	#4	18
UP	#4	~
Z	#4	18




JOINTS (BETWEEN BEAMS/GIRDERS OR AT INV-T STEM)
 For SEJ-A, SEJ-S(0), AJ, and Type A expansion joints only.



CONVENTIONAL INTERIOR BENT
 Panel against panel between beams/girders.



CONVENTIONAL INTERIOR BENT
 Panel against beam/girder end in adjacent span.





INVERTED-T BENT
 Panels against inverted-tee stem

OPTION 2 ~ ELEVATIONS AT BEAM ENDS (6)

ELEVATION EXAMPLE OF END PANEL AND TIMBER BOARD (23)

See "Option 2 ~ Elevation At Beam Ends".

- (6) See Span Details and Thickened Slab End Details for top slab reinforcement and clear cover. Transverse top slab reinforcement may rest on top of prestressed concrete panels if necessary to maintain clear cover.
- (14) Max Spacing as listed unless otherwise shown.
- (21) 1 1/2" Vinyl or plastic joint former at controlled joints (Stress Cap, Zip Strip, Stress Lock, or equal as approved by the Engineer.)
- (22) End panel may be set up to 2" lower to accommodate expansion joint hardware, provided bedding strip is not less than 1/2" thick.
- (23) 3/4" thick redwood timber board, leave in place. Redwood timber board placed flush with top of panel or within 1/4" Max above panel. Place 3/4" pyramid shape chamfer along top of timber board. See "Elevation Example of End Panel and Timber Board". Place straight, within 1/4" of centerline of bent or face of inverted-tee, across bridge width and end board at exterior flange edge of fascia beams/girders. Do not extend into overhang.
- (24) Place panel within 1/2" of 3/4" thick board.
- (25) Permanent galvanized steel sheet form. Removable formwork is acceptable.
- (26) Place end panel within 1/2" of expansion joint opening. End panel cannot encroach on required expansion joint opening.
- (27) Place additional (#4) bar 5'-0" in length between every slab bars T. Center (#4) bar on Joint.
- (28) Place additional (#4) bar continuous 2'-6" beyond each side of Inverted-T Stem between every slab bars T.



OPTION 2 ~ SHOWING MODIFICATION TO BEAM/GIRDER TOP FLANGE FOR SKEWS OVER 5°

Showing I-Bm/I-Girder, U-Bms and Steel Bms similar.

SPECIAL OPTION 2 CONSTRUCTION NOTES:

When Option 2 is chosen bottom mat of thickened slab reinforcing is not required. Use the same top mat as shown on the Thickened Slab End Details sheet.
 Placing panels adjacent to expansion joints and bent centerlines prior to completing interior panel placement is recommended. Saw cutting panels to fit is acceptable when approved by the Engineer. Minimum distance from a saw cut edge to a panel strand is 1 1/2".
 Do not extend the longitudinal panel reinforcement into the cast-in-place slab.
 Top flanges of beams and girders on skewed bridges must be modified as shown on this drawing. The Contractor is responsible for coordinating this modification with the beam fabricator prior to submitting shop drawings for approval.
 Fabricator may optionally skew the whole end. When electing to skew whole end, girder end details and bearing type at conventional interior bent must be changed to use condition at abutment. Fabricator must coordinate change in bearing type, bearing centerline location, and dowel location with Engineer and Contractor. Show appropriate changes on girder and bearing shop drawings.
 Bending of anchor studs of expansion joints shown on standards AJ, SEJ-A and SEJ-S(0) is permissible if necessary to clear top of end panels. The Contractor is responsible for coordinating modifications with the joint fabricator. Submit shop drawings for approval when modifications to expansion joint hardware are made.
 Bedding strips under skewed end panels must conform to the requirements of Item 422 except their minimum compressive strength must be 60 psi.
 Provide Bars AA, G, K and OA from standard IGTS in the slab.

HL93 LOADING SHEET 4 OF 4


Texas Department of Transportation Bridge Division Standard

PRESTRESSED CONCRETE PANELS DECK DETAILS


PCP

FILE: pcpstd1-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR	CK: JMH
REV: 0909 29	CON: 0909 29	SECT: 046	JOB: CR	HIGHWAY: CR
DIST: WACO	COUNTY: HAMILTON	SHEET NO: 74		

DATE: 2/8/2023 1:38:54 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot\cadd\standards\bridge\MI\sc\PCP-FAB.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of drawings to other formats or for incorrect results or damages resulting from its use.



TYPICAL NON-SKEWED PANEL PLAN



TYPICAL SKEWED END PANEL PLAN

(Only to be used with details shown elsewhere in the plans.)


- 1 At connection with cast-in-place slab, extend longitudinal panel reinforcement 1'-0" (+2", -0") past panel end. Alternatively, provide (#3) x 2'-0" dowels at 6" Max Spacing and extend dowels 1'-0" past panel end.
- 2 Four loops required per panel.
- 3 Four loops required per panel. 3/8" or 1/2" strands may be used.
- 4 Normal dimensions must be used on spans with parallel beams. Maximum and Minimum dimensions apply only to spans with flared beams.
- 5 See Normal Grading Detail on PCP standard for lap requirements and bedding strip dimensions. Some laps shown in tables cannot utilize all bedding strip widths.
- 6 One Splice allowed per panel. No more than two sheets of WWR are allowed.
- 7 Provide (#4) bars under transverse reinforcing, 10 Spaces at 4" = 3'-4". Omit for 5 degree (1:12) skew and smaller.
- 8 End Cover 2 1/2" Max, 1" Min.
- 9 Recess strands on indicated panel edge in accordance with Item 424.
- 10 At the fabricator's option, Bars U may be placed parallel to transverse panel reinforcing with horizontal legs in plane of transverse panel reinforcing.
- 11 Use length of indicated panel edge as panel width for purpose of determining type of transverse reinforcing.
- 12 Timber form work permissible this edge.

TABLE A (4) (5)				TABLE B (4) (5)			
Beam Type	Normal (In.)	Min (In.)	Max (In.)	Top Flange Width	Normal (In.)	Min (In.)	Max (In.)
A	3	2 1/2	3 1/2	11" to 12"	2 3/4	2 1/2	2 3/4
B	3	2 1/2	3 1/2	Over 12" to 15"	3 1/4	3	3 1/4
C	4	3	4 1/2	Over 15" to 18"	4	3	4 3/4
IV	6	4	7 1/2	Over 18"	5	3 1/2	6 1/4
VI	6 1/2	4 1/2	8 1/2				
U40 - 54	5 1/2	5 1/2	7				
Tx28-70	6	5	7 1/2				
XB20 - 40	4	3	4 1/2				
XSB12 - 15	4	3	4 1/2				


GENERAL NOTES:
 Provide Class H concrete for panels. Release strength $f'_{ci}=3,500$ psi. Minimum 28 day strength $f'_c=5,000$ psi.
 Provide 3/4" chamfer along bottom edge of panel on beam side. Do not use epoxy-coated reinforcing steel bar or strand in panels. Remove laitance from top panel surface. Finish top of panel to a roughness between a No. 6 and No. 9 concrete surface profile, inclusive, as specified by the International Concrete Repair Institute (ICRI).
 Shop drawings for the fabrication of panels will not require the Engineer's approval if fabrication is in accordance with the details shown on this standard.
 A panel layout which identifies location of each panel must be developed by the Fabricator. Permanently mark each panel in accordance with the panel layout. A copy of the layout is to be provided to the Engineer.

TRANSVERSE PANEL REINFORCEMENT:
 For panel widths over 5', use 3/8" or 1/2" Dia (270k) prestressing strands with a tension of 14.4 kips per strand.
 For panel widths over 3'-6" up to and including 5', use 3/8" or 1/2" Dia (270k) prestressing strands with a tension of 14.4 kip per strand. Optionally, (#4) Grade 60 reinforcing bars may be used in lieu of prestressed strands.
 For panel widths up to 3'-6", use (#4) Grade 60 reinforcing bars (prestressed strands alone are not allowed).
 Place transverse panel reinforcement at panel centroid and space at 6" Max.


LONGITUDINAL PANEL REINFORCEMENT:
 Any of the following options may be used for longitudinal panel reinforcement:
 1. (#3) Grade 60 reinforcing steel at 6" Max Spacing. No splices allowed.
 2. 3/8" Dia prestressing strands at 4 1/2" Max Spacing (unstressed). No splices allowed.
 3. 1/2" Dia prestressing strands at 6" Max Spacing (unstressed). No splices allowed.
 4. Deformed Welded Wire Reinforcement (WWR) (ASTM A1064) providing 0.22 sq in per foot of panel width. Wires larger than D11 not permitted. Provide transverse wires to ensure proper handling of reinforcing. One splice per panel is allowed. See WWR Splice Detail.
 No combination of longitudinal reinforcement options in a panel is allowed. Place longitudinal panel reinforcement above or below transverse panel reinforcement. Must be placed above transverse panel reinforcement for skewed end panels with supplemental (#4) reinforcement.




SECTION A-A
 (Not showing supplemental #4 bars for skewed end panels.)




WELDED WIRE REINFORCEMENT (WWR) SPLICE DETAIL (6)




TYPICAL SECTIONS FOR DETERMINING PANEL WIDTH



TYPICAL SECTIONS FOR DETERMINING PANEL WIDTH



BARS U (#3) (2)




OPTIONAL STRAND FOR BARS U (3)

HL93 LOADING


		Bridge Division Standard	
PRESTRESSED CONCRETE PANEL FABRICATION DETAILS			
PCP-FAB			
FILE: pcpside2-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR
REV: 0909 29	CONTRACT: 0909 29	SECTION: 046	HIGHWAY: CR
DIST: WACO	COUNTY: HAMILTON	SHEET NO. 75	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 3:33:47 PM
 FILE: T:\Road Dept\Department\Team Texas.txdot\cadd\standards\bridge\mi\sc\pmdf\pmdf1-21.dgn




PRESTR CONC I-BEAMS AND I-GIRDERS WITH STIRRUP LOCKS




PRESTR CONC I-BEAMS AND I-GIRDERS WITH WELD ANCHORS




U-BEAMS WITH STIRRUP LOCKS



U-BEAMS WITH WELD ANCHORS




STEEL BEAMS AT COMPRESSION FLANGES




STEEL BEAMS AT TENSION FLANGES

TYPICAL TRANSVERSE SECTIONS




PRECLOSED




ANGLE HEADER

NOTE: This type is to be used for skewed ends only.

TYPES OF END CLOSURES




TYP LONGITUDINAL SLAB SECTION



Note: In spans where PMD forms are used, timber forms must be used at construction joints. Adequate provision must be made to support edge of metal form and to provide anchorage of metal form to slab concrete where joined to wood forms.

SECTION THRU CONSTRUCTION JOINT

FOR PRESTR CONC U-BEAM AND STEEL GIRDER BRIDGES:
 Unless shown elsewhere in the plans, size, spacing, and orientation of bottom mat of slab reinforcement must match the top mat of reinforcing shown on the span details except all bottom mat bars are to be #5. Bottom mat reinforcement and additional concrete is subsidiary to Item 422 "Concrete Superstructures."
FOR PRESTR CONC TX-GIRDER BRIDGES:
 See Miscellaneous Slab Details, Prestr Concrete I-Girders (IGMS) standard sheet for bottom mat reinforcing.



SIDE LAP DETAILS

- Slab thickness minus 5/8" if corrugations match reinforcing bars.
- Welding of form supports to tension flanges will not be permitted. Other methods of providing wind hold down resistance for PMDF in tension flange zones will be considered. At least one layer of sheet metal must be provided between the flange and the weld joint.
- The direction of concrete placement will be such that the upper layer of the form overlap is loaded first.
- See Span details for cover requirements.

GENERAL NOTES:

Steel for Permanent Metal Deck Forms (PMDF) and support angles shall conform to ASTM A653, structural steel (SS), with coating designation G165. Steel must have a minimum yield strength of 33 ksi. Minimum thickness of PMDF is 20 gage and that of support angles and protective angles is 12 gage. Submit two copies of forming plans for PMDF to the Engineer. These plans must show all essential details of proposed form sheets, closures, fasteners, supports, connectors, special conditions and size and location of welds. These plans must clearly show areas of tension flanges for steel beams and provisions for protecting the tension flanges from welding notch effects by inclusion of separating sheet metal or other positive method. These plans must be designed, signed, and sealed by a licensed professional engineer. Department approval of these plans is not required, but the Department reserves the right to require modifications to the plans. The Contractor is responsible for the adequacy of these plans. The details and notes shown on this standard are to be used as a guide in preparation of the forming plans. All material, labor, tools and incidentals necessary to form a bridge deck with Permanent Metal Deck Forms is considered subsidiary to Item 422, "Concrete Superstructures".

DESIGN NOTES:
 As a minimum, PMDF and support angles must be designed for the dead load of the form, reinforcement and concrete plus 50 psf for construction loads. Flexural stresses due to these design loads must not exceed 75 percent of the yield strength of the steel. Allowable stress for weld metal must be 12,400 psi. Maximum deflection under the weight of forms, reinforcement and concrete or 120 psf, whichever is greater, shall not exceed the following:

- 1/180 of the form design span, but not more than 0.50", for design spans of 10' or less.
- 1/240 of the form design span, but not more than 0.75", for design spans greater than 10'.
- 1/240 of the form design span, but not more than 0.75", for all design spans of railroad overpass bridge spans fully or partially over railroad right-of-way, and for all bridge spans of railroad underpass structures.

The form design span must not be less than the clear distance between beam flanges, measured parallel to the form flutes, minus 2".


CONSTRUCTION NOTES:

Form sheets must not be permitted to rest directly on the top of beam flanges. Form sheets must be securely fastened to form supports and must have a minimum bearing length of one inch at each end. Form supports must be placed in direct contact with beam flanges. All attachments must be made by permissible welds, screws, bolts, clips or other means shown on the the forming plans. All sheet metal assembly screws must be installed with torque-limiting devices to prevent stripping. Only welds or bolts must be used to support vertical loads. Welding and welds must be in accordance with the provisions of Item 448, "Structural Field Welding", pertaining to fillet welds. All welds must be made by a qualified welder in accordance with Item 448. All permanently exposed form metal, where the galvanized coating has been damaged, must be thoroughly cleaned and repaired in accordance with Item 445, "Galvanizing". Minor heat discoloration in areas of welds need not be touched up. Flutes must line up uniformly across the entire width of the structure where main reinforcing steel is located in the flute. Construction joints will not be permitted unless shown on the plans. The location of and forming details for any construction joint used must be shown on the forming plans. Forms below a construction joint must be removed after curing of the slab. A sequence for uniform vibration of concrete must be approved by the Engineer prior to concrete placement. Attention must be given to prevent damage to the forms, yet provide proper vibration to prevent voids or honeycomb in the flutes and at headers and/or construction joints.


		Bridge Division Standard	
PERMANENT METAL DECK FORMS			
PMDF			
FILE: pmdfste1-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
CONTRACT: 0909	SECTION: 29	JOB: 046	HIGHWAY: CR
DIST: WACO	COUNTY: HAMILTON	SHEET NO. 76	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 3:33:48 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\MI.sc\PMDF\sc\




AT THICKENED SLAB END FOR U-BEAMS




AT THICKENED SLAB END FOR PRESTRESSED I-BEAMS, I-GIRDERS AND STEEL BEAMS
 Showing I-beam block-out. No block-out for I-girders or steel beams.




SECTION A-A




SHOWING PRESTRESSED CONCRETE I-BEAMS, I-GIRDERS AND U-BEAMS




AT SLAB OVER ABUT BKWL OR INV TEE STEM FOR CONC BEAMS WITHOUT THICKENED SLAB END




AT SLAB OVER INV TEE STEM FOR STEEL BEAMS WITHOUT THICKENED SLAB END




DETAIL "A"




SHOWING STEEL BEAMS



AT CONC END DIAPHRAGM FOR PRESTRESSED I-BEAMS AND STEEL BEAMS



AT END DIAPHRAGM FOR STEEL BEAMS WITHOUT THICKENED SLAB END



DETAIL "B"

WIDENING DETAILS

DETAILS AT ENDS OF BEAMS


- ① Slab thickness minus 3/8" if corrugations match reinforcing bars
- ⑤ Minimum yield stress of 12 gage bars shall be 40 ksi

SHEET 2 OF 2


		Bridge Division Standard	
PERMANENT METAL DECK FORMS			
PMDF			
FILE: pmfste1-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT
©TxDOT April 2019	CONTRACT	SECTION	HIGHWAY
REVISIONS	0909	29	046
02-20: Modified box note by adding steel beams/girders and Subsidiary.	DIST	COUNTY	SHEET NO.
12-21: Updated max deflection for RR.	WACO	HAMILTON	77

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 2/8/2023 1:38:56 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\MI sc\SRR\dgn




PLAN



ELEVATION




SECTION A-A AT CAP



SECTION B-B

Provide toewall when shoulder drain is located adjacent to limits of stone riprap. Omit toewall when thickness of protection riprap is greater than 18".



CAP OPTION A

CAP OPTION B

DETAIL C

① Top of cap to top of riprap dimension varies as directed by the Engineer. Provide 9" Min for beam/slab type bridges and 1'-6" for slab span, box beam, or slab beam bridges.

GENERAL NOTES:
 Refer to Item 432, "Riprap" for stone size and gradation, and construction details. See Layout for limits and thickness of riprap specified.
 See elsewhere in plans for locations and details of shoulder drains.

SHEET 1 OF 2

		Bridge Division Standard	
<h1>STONE RIPRAP</h1>			
<h2>SRR</h2>			
FILE: srrstd1-19.dgn	DN: AES	CK: JGD	DW: BWH
©TxDOT April 2019	CONTRACT: 0909	SECTION: 29	JOB: 046
REVISIONS	DIST: WACO		COUNTY: HAMILTON
	SHEET NO. 78		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 1:38:57 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge\std\std.dgn




FIGURE 1 ~ TYPE R STONE RIPRAP
 dry or grouted




FIGURE 2 ~ TYPE F STONE RIPRAP
 dry or mortared





FIGURE 3 ~ TYPE F STONE RIPRAP
 grouted

- ② Provide bedding material instead of filter fabric if shown elsewhere in plans. See Layout for thickness of bedding material.
- ③ Minimum toe depth is the larger of the maximum scour depth or 2 times the riprap thickness.
- ④ "y" and Height need to be defined. See layout or detail sheet for values if this option is used.
- ⑤ List Stone Protection as size (XX inch) and thickness (YY inch) on the layout.
 Example: Riprap (Stone Protection) XX inch, Thickness = YY inch.



PROTECTION STONE RIPRAP TOE OPTIONS ⑤




FIGURE 4 ~ COMMON STONE RIPRAP
 dry or grouted





FIGURE 5 ~ PROTECTION STONE RIPRAP ⑤

SHEET 2 OF 2


		Bridge Division Standard	
<h1>STONE RIPRAP</h1>			
<h2>SRR</h2>			
FILE: srrside1-19.dgn	DN: AES	CK: JGD	DW: BWH
©TxDOT April 2019 REVISIONS	CONT SECT	JOB	HIGHWAY
	0909 29	046	CR
	DIST	COUNTY	SHEET NO.
	WACO	HAMILTON	79

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 3:33:48 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot_cadd_standards\bridge_rail\img\SSR.dgn




ROADWAY ELEVATION OF RAIL




INTERMEDIATE WALL JOINT DETAIL


Provide at all interior bents without slab expansion joints.



ELEVATION SHOWING TYPICAL REINFORCING PLACEMENT



**SECTION
ELEVATION
TERMINAL CONNECTION DETAILS**



PLAN OF RAIL AT EXPANSION JOINTS

Example showing Slab Expansion Joints without breakbacks.


- ① Terminal Connectors and associated hardware are to be paid for under the Item "Metal Beam Guard Fence". Attach Metal Beam Guard Fence Transitions to the bridge rail and extend along the embankment unless otherwise shown in the plans.
- ② Increase 2" for structures with Overlay.
- ③ Back of rail offset may, with Engineer's approval, be continued to the end of the railing.
- ④ Place 4 additional Bars R(#4) 3'-8" in length inside Bars S(#4) and centered 2'-0" from end of rail when Terminal Connections are required.

SHEET 1 OF 2


		Bridge Division Standard	
<h2>TRAFFIC RAIL SINGLE SLOPE</h2>			
<h3>TYPE SSTR</h3>			
FILE: r1std014-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR
©TxDOT September 2019	CONT	SECT	JOB
REVISIONS	0909	29	046
DIST	COUNTY	SHEET NO.	
WACO	HAMILTON	80	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023 3:33:49 PM
 FILE: T:\Road Dept\Department\Team Texas\txdot cadd standards\Rail\Rail\SSSTR.dgn



ON ABUTMENT WINGWALLS OR CIP RETAINING WALLS



ON BRIDGE SLAB

SECTIONS THRU RAIL


- ② Increase 2" for structures with Overlay.
- ⑤ 5 1/4" when vertical reinforcing has closer clear cover over horizontal reinforcing in abutment wingwalls or retaining walls on traffic side of wall.
- ⑥ As an aid in supporting reinforcement, additional longitudinal bars may be used in the slab with the approval of the Engineer. Such bars must be furnished at the Contractor's expense.
- ⑦ Top longitudinal slab bar may be adjusted laterally 3" plus or minus to tie reinforcing.
- ⑧ No longitudinal wires may be within upper bend.
- ⑨ Bend or cut as required to clear drain slots.
- ⑩ Space U(#4) bars at 4" Max when end region of panel length is less than 6'-0" to side slot drain. Space U(#4) bars at 6" Max when end region of panel length is 6'-0" and greater to side slot drain.

CONSTRUCTION NOTES:
 This railing may be constructed by the slipform process when approved by the Engineer, with equipment approved by the Engineer. Provide sensor control for both line and grade. Tack welding to provide bracing for slipform operations is acceptable. Welding may be performed at a minimum spacing of 3 ft between the cage and the anchorage. It is permissible to weld to bars U, WU and S at any location on the cage. If increased bracing is needed, provide additional anchorage devices and weld in the upper two thirds of the cage. Paint welded areas on epoxy coated and/or galvanized reinforcing with an organic zinc rich paint in accordance with Item 445 "Galvanizing".
 If rail is slipformed, apply a heavy epoxy bead 1" behind toe of traffic side of rail to concrete deck just prior to slip forming. Provide a 3/8" width x 1/4" tall heavy epoxy bead with Type III, Class C or a Type V epoxy.
 The back of railing must be vertical unless otherwise shown in the plans or approved by the Engineer.


MATERIAL NOTES:
 Provide Class "C" concrete. Provide Class "C" (HPC) if required elsewhere.
 Provide Grade 60 reinforcing steel.
 Epoxy coat or galvanize all reinforcing steel if slab bars are epoxy coated or galvanized.
 Deformed Welded Wire Reinforcement (WWR) (ASTM A1064) of equal size and spacing may be substituted for Bars U and WU unless noted otherwise. Deformed WWR (ASTM A1064) may be substituted for Bars R and S, as shown. Combinations of reinforcing steel and WWR or configurations of WWR other than shown are permitted if conditions in the table are satisfied. Provide the same laps as required for reinforcing bars.
 Provide bar laps, where required, as follows:
 Uncoated or galvanized ~ #4 = 1'-7"
 Epoxy coated ~ #4 = 2'-5"

GENERAL NOTES:
 This rail has been successfully evaluated by full-scale crash test to meet MASH TL-4 criteria. This rail can be used for speeds of 50 mph and greater when a TL-3 rated guard fence transition is used. When a TL-2 rated guard fence transition is used, this rail can only be used for speeds of 45 mph and less.
 Do not use this railing on bridges with expansion joints providing more than 5" movement.
 Rail anchorage details shown on this standard may require modification for select structure types. See appropriate details elsewhere in plans for these modifications.
 Shop drawings will not be required for this rail.
 Average weight of railing with no overlay is 376 plf.


Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.




BARS S (#4)




BARS U (#4)



BARS WU (#4)




OPTIONAL WELDED WIRE REINFORCEMENT (WWR)



OPTIONAL SIDE SLOT DRAIN DETAIL

Note: Side Slot Drains may be used where shown elsewhere on the plans or as directed by the Engineer. Drains should not be placed over railroad tracks, lower roadways, or sidewalks. When this rail is used as a separator between a roadway surface and a sidewalk surface, side drain slots will not be permitted.



SECTION THRU OPTIONAL SIDE SLOT DRAIN

DESCRIPTION	LONGITUDINAL WIRES	VERTICAL WIRES
Minimum (Cumulative Total) Wire Area	1.067 Sq In.	0.267 Sq In. per Ft
Minimum	No. of Wires	Spacing
Maximum	8	4"
Maximum	10	8"
Maximum Wire Size Differential	The smaller wire must have an area of 40% or more of the larger wire.	

Texas Department of Transportation
 Bridge Division Standard

TRAFFIC RAIL SINGLE SLOPE

TYPE SSTR

FILE: r1std014-19.dgn	DN: TxDOT	CK: TxDOT	DW: JTR	CK: TxDOT
©TxDOT September 2019	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DIST	COUNTY	SHEET NO.		
WACO	HAMILTON	81		

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with TxDOT policy for projects disturbing less than 1 acre of soil, and not part of a larger common plan of development.

For all projects with any soil disturbing activities, TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office. If no field office is available, then this SWP3 shall be kept at the appropriate TxDOT Area Office.

This SWP3 is consistent with requirements specified in applicable stormwater plans, and the project's environmental permits, issues, and commitments (EPICs).

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

CSJ: 0909-29-046

1.2 PROJECT LIMITS:

From: ON CR 238 (HCR 207) @ HONEY CREEK (MAP 212)

To: _____

1.3 PROJECT COORDINATES:

BEGIN: (Lat) 31°55'48.71"N, (Long) 98°3'54.01"W

END: (Lat) 31°55'43.90"N, (Long) 98°3'51.66"W

1.4 TOTAL PROJECT AREA (Acres): 0.79 AC

1.5 TOTAL AREA TO BE DISTURBED (Acres): 0.28 AC

1.6 NATURE OF CONSTRUCTION ACTIVITY:

EXCAVATION, EMBANKMENT, GRADING OF ROADSIDE DITCHES, CHANNEL SIDE SLOPES AND CONSTRUCTION OF PROPOSED BRIDGE AND APPROACHES.

1.7 MAJOR SOIL TYPES:

Soil Type	Description
LIMESTONE	VERY HARD, LIGHT GRAY AND TAN HIGHLY WEATHERED, INTENSELY FRACTURED, POOR.
SHALE	VERY HARD, GRAY, HIGHLY WEATHER HIGHLY FRACTURED, POOR TO FAIR, INTERBEDDED WITH LIMESTONE AND CLAY AND CALCAREOUS DEPOSITS.

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.3.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures

Other: _____
 Other: _____
 Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Other: _____
- Other: _____
- Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody
HONEY CREEK (MAP 212)	Segment ID 1226J of Brazos River Basin

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Other: _____
- Other: _____

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Other: _____
- Other: _____



STORMWATER POLLUTION PREVENTION PLAN (SWP3) (Less Than 1 Acre)

FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
6				82
STATE	STATE DIST.	COUNTY		
TEXAS	WACO	HAMILTON		
CONT.	SECT.	JOB	HIGHWAY NO.	
0909	29	046	CR	

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: _____
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To
PERMANENT SEEDING	STA. 402+00.00	STA. 407+30.00

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

2.8 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.3 of this SWP3 .

2.9 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.3 of this SWP3.



STORMWATER POLLUTION PREVENTION PLAN (SWP3) (Less Than 1 Acre)

FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
6				83
STATE	STATE DIST.	COUNTY		
TEXAS	WACO	HAMILTON		
CONT.	SECT.	JOB	HIGHWAY NO.	
0909	29	046	CR	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: _____
 FILE: _____

I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

- 1.
2. No Action Required Required Action

Action No.

1. Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000
2. Comply with the SW3P and revise when necessary to control pollution or required by the Engineer.
3. Post Construction Site Notice (CSN) with SW3P information on or near the site, accessible to the public and TCEQ, EPA or other inspectors.
4. When Contractor project specific locations (PSL's) increase disturbed soil area to 5 acres or more, submit NOI to TCEQ and the Engineer.

II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required
- Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
- Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
- Individual 404 Permit Required
- Other Nationwide Permit Required: NWP# _____

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

1. Honey Creek
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

Best Management Practices:

Erosion	Sedimentation	Post-Construction TSS
<input checked="" type="checkbox"/> Temporary Vegetation	<input checked="" type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input checked="" type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	<input type="checkbox"/> Grassy Swales

III. CULTURAL RESOURCES

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

- No Action Required Required Action

Action No.

1. SEE STATEMENT ABOVE
- 2.

IV. VEGETATION RESOURCES

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

- No Action Required Required Action

Action No.

1. SEE STATEMENT ABOVE
2. Vegetation clearing within the project limits/drainage areas must be completed during the non-nesting season September 15 - March 1.
- 3.
- 4.

- No Action Required Required Action

Action No.

1. Comply with Migratory Bird Treaty Act (MBTA)
2. For Eastern Spotted Skunk and Plains Spotted Skunk: Contractors will be advised of potential occurrence in the project area, and to avoid harming the species if encountered, and to avoid unnecessary impacts to dens.
3. For Texas Horned Lizard: Contractors will be advised of potential occurrence in the project area, and to avoid harming the species of encountered. This should include avoiding harvester ant mounds in the selection of Project Specific Locations (PSL's)
- 4.

5. SEE STATEMENT BELOW

If any of the listed species are observed, cease work in the immediate area, do not disturb species or habitat and contact the Engineer immediately. The work may not remove active nests from bridges and other structures during nesting season of the birds associated with the nests. If caves or sinkholes are discovered, cease work in the immediate area, and contact the Engineer immediately.

LIST OF ABBREVIATIONS

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SWP3: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NWP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used.

Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act.

Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- * Dead or distressed vegetation (not identified as normal)
- * Trash piles, drums, canister, barrels, etc.
- * Undesirable smells or odors
- * Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

- Yes No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

- Yes No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

- No Action Required Required Action

Action No.

1. Lead Based Paint: The removal, containment, and disposal process of hazardous materials would comply with applicable federal, state and local laws.


VII. OTHER ENVIRONMENTAL ISSUES



(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required Required Action

Action No.

- 1.
- 2.
- 3.

		Design Division Standard		
<h2 style="margin: 0;">ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS</h2> <h1 style="margin: 0;">EPIC</h1>				
FILE: epic.dgn	DN: TxDOT	CK: RG	DW: VP	CK: AR
©TxDOT: February 2015	CONT	SECT	JOB	HIGHWAY
12-12-2011 (DS) REVISIONS	0909	29	046	CR
05-07-14 ADDED NOTE SECTION IV.	DIST	COUNTY	SHEET NO.	
01-23-2015 SECTION I (CHANGED ITEM 1122 TO ITEM 506, ADDED GRASSY SWALES.	WAC	Hamilton	84	



LEGEND

	TOPSOIL/SEEDING
	SOIL RETENTION BLANKETS (CL 1) (TY B)
	SEDIMENT CONTROL FENCE
	ROCK FILTER DAMS (TY 1)

NOTES

1. LOCATION OF EROSION CONTROL DEVICES ARE APPROXIMATE. ACTUAL LOCATIONS TO BE APPROVED.

PRINT DATE	REVISION DATE
2/13/2023	



3711 SOUTH MOPAC EXPRESSWAY
 BUILDING ONE, SUITE 350
 AUSTIN, TX 78703
 TEL 512.494.6037 FAX 317.543.0270
 www.structurepoint.com

STRUCTUREPOINT
 INC.

TBPE FIRM NO. F-10069

Texas Department of Transportation ©2023


CR 238 (HCR 207) AT HONEY CREEK

SWP3 LAYOUT

FED. RD. DIV. NO.	PROJECT NUMBER	HIGHWAY NUMBER	
6		CR	
STATE	DISTRICT	COUNTY	
TEXAS	WACO	HAMILTON	
CONTROL	SECTION	JOB	SHEET NO.
0909	29	046	85


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE 2/8/2023
 FILE T:\Road_Dept\Department\Team Texas\txdot cadd_standards\erosion control\EC(1)-16.dgn



TEMPORARY SEDIMENT CONTROL FENCE

SCF



HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

SEDIMENT CONTROL FENCE USAGE GUIDELINES

A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT². Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.


LEGEND

Sediment Control Fence

SCF

GENERAL NOTES

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.




VERTICAL TRACKING

				Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING EC(1)-16					
FILE: ec116	DN: TxDOT	CK: KM	DW: VP	DN/CK: LS	
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY	
REVISIONS		0909	29	046	CR
		DIST	COUNTY	SHEET NO.	
		WACO	HAMILTON	86	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 2/8/2023
 FILE: T:\Road Dept\Department Team Texas\txdot cadd standards\erosion control\EC(2)-16.dgn




FILTER DAM AT TOE OF SLOPE

— (RFD1) —




FILTER DAM AT SEDIMENT TRAP

— (RFD1) — OR — (RFD2) —




FILTER DAM AT CHANNEL SECTIONS

— (RFD1) — OR — (RFD2) — OR — (RFD3) —




"V" SHAPE PLAN VIEW




TYPE 4 (SACK GABIONS)


— (RFD4) —



SECTION A-A



PROFILE



SECTION C-C

ROCK FILTER DAM USAGE GUIDELINES

Rock Filter Dams should be constructed downstream from disturbed areas to intercept sediment from overland runoff and/or concentrated flow. The dams should be sized to filter a maximum flow through rate of 60 GPM/FT² of cross sectional area. A 2 year storm frequency may be used to calculate the flow rate.

Type 1 (18" high with no wire mesh) (3" to 6" aggregate): Type 1 may be used at the toe of slopes, around inlets, in small ditches, and at dike or swale outlets. This type of dam is recommended to control erosion from a drainage area of 5 acres or less. Type 1 may not be used in concentrated high velocity flows (approximately 8 Ft/Sec or more) in which aggregate wash out may occur. Sandbags may be used at the embedded foundation (4" deep min.) for better filtering efficiency of low flows if called for on the plans or directed by the Engineer.

Type 2 (18" high with wire mesh) (3" to 6" aggregate): Type 2 may be used in ditches and at dike or swale outlets.

Type 3 (36" high with wire mesh) (4" to 8" aggregate): Type 3 may be used in stream flow and should be secured to the stream bed.

Type 4 (Sack gabions) (3" to 6" aggregate): Type 4 May be used in ditches and smaller channels to form an erosion control dam.

Type 5: Provide rock filter dams as shown on plans.

GENERAL NOTES

1. If shown on the plans or directed by the Engineer, filter dams should be placed near the toe of slopes where erosion is anticipated, upstream and/or downstream at drainage structures, and in roadway ditches and channels to collect sediment.
2. Materials (aggregate, wire mesh, sandbags, etc.) shall be as indicated by the specification for "Rock Filter Dams for Erosion and Sedimentation Control".
3. The rock filter dam dimensions shall be as indicated on the SW3P plans.
4. Side slopes should be 2:1 or flatter. Dams within the safety zone shall have sideslopes of 6:1 or flatter.
5. Maintain a minimum of 1' between top of rock filter dam weir and top of embankment for filter dams at sediment traps.
6. Filter dams should be embedded a minimum of 4" into existing ground.
7. The sediment trap for ponding of sediment laden runoff shall be of the dimensions shown on the plans.
8. Rock filter dam types 2 & 3 shall be secured with 20 gauge galvanized woven wire mesh with 1" diameter hexagonal openings. The aggregate shall be placed on the mesh to the height & slopes specified. The mesh shall be folded at the upstream side over the aggregate and tightly secured to itself on the downstream side using wire ties or hog rings. For in stream use, the mesh should be secured or staked to the stream bed prior to aggregate placement.
9. Sack Gabions should be staked down with 3/4" dia. rebar stakes, and have a double-twisted hexagonal weave with a nominal mesh opening of 2 1/2" x 3 1/4"
10. Flow outlet should be onto a stabilized area (vegetation, rock, etc.).
11. The guidelines shown hereon are suggestions only and may be modified by the Engineer.

PLAN SHEET LEGEND

- Type 1 Rock Filter Dam — (RFD1) —
- Type 2 Rock Filter Dam — (RFD2) —
- Type 3 Rock Filter Dam — (RFD3) —
- Type 4 Rock Filter Dam — (RFD4) —

		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES			
ROCK FILTER DAMS			
EC(2)-16			
FILE: ec216	DN: TxDOT	CK: KM	DW: VP
© TxDOT: JULY 2016	CONT: 0909	SECT: 29	JOB: 046
REVISIONS		DIST: WACO	COUNTY: HAMILTON
			DN/CK: LS HIGHWAY: CR SHEET NO.: 87

BEST MANAGEMENT PRACTICE (BMP) GENERAL NOTES

1. Prior to TxDOT allowing the Contractor to start construction, the Contractor will provide the required storm water and 404 permit documentation and support activities, including but not limited to the following:
 - Provide a list of all chemicals, construction and waste products that will be generated, stored or brought upon TxDOT ROW. The list includes expected construction debris, sanitary wastes, construction chemicals and petroleum products used or generated by the Contractor and sub-contractors. Along with the list, the Contractor will supply a spill prevention plan and clean up procedures that will include each of these chemical products or generated waste.
 - Provide in the construction schedule the necessary line items that will comply with the schedule and planning requirements of the storm water permit.
 - Post the TxDOT storm water permit and any Contractor permits, per permit requirements.
 - Provide copies of storm water permits for Contractor PSL(s). As new PSL(s) may be obtained for the project, provide copies of new or amended permits to TxDOT. The Contractor will not disturb soil without the proper permits.
 - Provide scale drawings of off ROW PSL's within one mile of the project, for field offices, borrow sources, plant sites or other uses.
 - Provide permit information on any Contractor batch plants or concrete crushing plants to be located at a Contractor PSL(s) within one mile of the project limits or boundaries. Copies of the air and water permits are to be provided to TxDOT before materials will be used on the project. No asphalt or concrete batch plants or concrete crushing plants will be located on TxDOT ROW.
 - Provide a letter indicating a Contractor Responsible Person for environmental compliance (CRP) for the project, and maintain a CRP throughout the project duration.
 - Provide all environmental documentation including certification of compliance and EMS training documents/certificates prior to starting work. The Contractor is to provide daily BMP inspection reports that document all field BMPs needing repair or replacement. The Contractor is to clearly document specific BMPs needing repair and location each work day. The Contractor is encouraged to be proactive in fixing BMPs without TxDOT direction.
 - Provide documentation required for Waters of the US, Note #3 and submittals for Item 496 bridge removal. Bridge removal methods submitted will follow all Waters of the US note requirements. The Contractor is not to start construction within the Ordinary High Water Marks of any stream until receiving approval for stream channel construction methods from TxDOT.
 - Provide a written procedure for managing all chemicals and construction items placed in vertical containment structures. Also, provide methods to be used for the treatment, disposal, collection or release of storm water.
 - Provide an estimated date by letter, for the submittal of marked up bridge drawings, indicating out locations for any structural steel requiring cutting or torching of steel, coated with lead containing paints.
2. Place and maintain trash cans and portable sanitary facilities at locations where there is active construction. Worker generated trash and construction debris will be kept from being transported by storm water and will be collected daily from the ground and routinely hauled from the work area.
3. Contractor will provide TxDOT copies of all correspondence with MS4s, TCEQ, EPA, DSHS and Corps of Engineers regarding activities on this project.
4. Contractor to conduct storm water inspections and develop SWPPP documents to support Contractor permits obtained for the project including PSL(s).
5. Contractor will maintain written documentation of locations of all portable sanitary facilities. The Contractor is required to document the location and disposition of all spills and cleanups from portable sanitary facilities.
6. Contractor will not store chemicals on TxDOT ROW, unless chemicals are stored following all environmental and safety regulations. Fuels for construction equipment will not be stored on TxDOT ROW.
7. The Contractor will store fuels and bulk chemicals on Contractor PSL(s) using a secondary containment method, such as double lined tanks and/or free standing containment reservoirs made of plastic or steel designed to hold bulk chemicals or drums.
8. The Contractor will not remove sediment controls without the prior approval of TxDOT, except for a sediment control that may back up water and cause safety or traffic problems.

SCALE = NTS SHEET 1 OF 10

 **Texas Department of Transportation**
Waco District Standard

TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN:	CK:	DW:	CK:
© TxDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	88	

BEST MANAGEMENT PRACTICE (BMP) GENERAL NOTES

9. Any sediment controls removed by the Contractor must be re-installed before the next rainfall event or by the end of day, as approved in advance.
10. Vegetative buffer strips may be used in place of temporary sediment controls such as silt fences and rock filter dams. The amount of disturbed soil area will be limited to 1/3 of an acre or less for a minimum of 50 feet of grassed ditch and 2/3 of an acre of disturbed soil for a minimum of 100 feet of grassed ditch.
11. Construction equipment found to be leaking oil, fuel or coolant will be immediately stopped, the leaking fluid collected and the equipment fixed. Equipment continuing to leak will be removed from the project at no cost to TxDOT. Leaking fluids from equipment will be collected and removed from the project or PSL.
12. Earth berms or mounds typically used to stockpile topsoil and used in place of boundary silt fence will be seeded upon being constructed. Long term use of earth berms or mounds will not be continued without establishing grass on the control.
13. The Contractor will inform TxDOT of new areas where soil will be disturbed to facilitate planning for new sediment controls. Areas of vegetated soil will not be disturbed by the Contractor, unless adequate sediment controls can be installed before the next rainfall event. The Contractor will assist TxDOT in keeping an accurate set of working SWPPP drawings that show the locations of all temporary sediment and erosion controls.
14. The Contractor will maintain an adequate amount of temporary sediment controls on hand at the field office or project staging area for critical SWPPP maintenance, including silt fence (minimum of 200 feet) and rock / fabric for rock filter dams (minimum for 100 feet of Type III dams).

The requirement for BMP rock quantities on hand is waived for small projects for on and off system bridge installations. The Contractor having a BMP Subcontractor does not eliminate the requirement for the Contractor to have the required silt fence and rock on hand, typically stored at the Contractor PSL.
15. Failure of a sub-contractor to complete storm water work on time will require the Contractor to start storm water sediment control work immediately and complete the work with high priority, or be subject to stop work on the entire project.
16. Earth materials on roads as a result of soil tracking will not be allowed to be transported off ROW in storm water. Soil or rock material found on roadways deposited from Contractor equipment will be removed daily.
17. Unless approved, completed concrete curb inlets will not be blocked by sediment controls. The contractor will frequently sweep the completed or partially completed roadway to keep sediment out of drainage pipes.
18. The Contractor will be responsible for proper dust control and will route construction traffic in a manner that minimizes dust generation.
19. Water for dust control will contain no pollutants, but may be non-potable from upland stock ponds. No quantity of water to be used for construction purposes may be taken from a 404 stream, prior to the proper authorizations or permits being obtained by the Contractor.
20. Contractor is to direct workers and sub-contractors to use portable sanitary facilities provided by the Contractor and not to trespass off ROW.
21. Contractor will provide written verification to TxDOT that earth borrow pits and disposal sources meet environmental and regulatory requirements, prior to use. Excavations will meet all OSHA requirements and the current safety guidelines established for TxDOT Quarries and Pits.
22. Boundary silt fences that are terminated down slope, with one end being at the lowest elevation, will be installed with an L - hook to contain sediment. Boundary silt fences that are installed on flat ground will have L-hooks on both ends.
23. Rock filter dams across ditches will be constructed where the rock filter dam ends are embedded within the ditch side slopes and ditch bottom. The top center elevation of the rock filter dam will be at least 6 inches lower than the elevations on the rock filter dam ends.
24. Silt fence will be constructed in a U or V pattern across ditch lines and up the ditch side slope to keep storm water from flowing around the ends of the silt fence. Small silt fences that do not adequately span the ditch and allows storm water around the end(s) will not be used. Where there is adequate space, large U pattern silt fences are preferred to facilitate sediment collection and sediment removal with equipment.
25. Sediment controls (RFDs or silt fences) will be located along road ditches as marked on the SWPPP drawings. Modifications to the sediment control spacing will be adjusted during the project based on sediment control effectiveness. The installation and maintenance of sediment controls at or near outfalls, where storm water leaves TxDOT ROW, takes persistent over ditch line sediment controls.

SCALE = NTS SHEET 2 OF 10

 **Texas Department of Transportation**
Waco District Standard

TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN:	CK:	DW:	CK:
© TxDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY		SHEET NO.
FEB 2015	WACO	HAMILTON		89

BEST MANAGEMENT PRACTICE (BMP) GENERAL NOTES

26. Storm water draining sheet flow over disturbed soil sloped towards the ROW property line, will be intercepted by a boundary silt fence typically installed with L-shaped ends.
27. For ditch grading and shoulder up work, the Contractor is limited during good weather to remove up to one mile (limited to five acres of disturbed soil) of ditch line sediment controls; on one side of the roadway. Outfall controls cannot be removed during this activity. Ditch line controls must be replaced upon completion of work and before the next rain event.
28. Sediment controls damaged by the Contractor, as defined by permit, must be fixed or replaced immediately upon discovery.
29. Notches in silt fences are not typically allowed. Specific silt fences that back up water onto lanes of traffic may be notched if approved.
30. For silt fence maintenance, the Contractor will leave approximately 4 inches of deposited sediment up stream of silt fences and not over excavate around silt fences or rock filter dams.
31. The Contractor will inform TxDOT of new construction areas and where soil is planned to be disturbed. Sediment controls will be installed at outfalls prior to the Contractor beginning soil disturbing activities up slope from the outfall.
32. Water from concrete saw cutting, concrete grinding and concrete coring activities; or fine materials from concrete chipping and salvage will not be allowed to enter storm drains or enter streams.
33. Storm water containing suspended sediment and turbidity needing to be removed from excavations or low areas will be pumped or gravity drained through vegetated buffer strips (50 foot minimum) or placed in ditches with temporary sediment controls, prior to the water being discharged into a stream.
34. Uncontaminated water from natural groundwater seepage, springs, foundations and drains that does not contain suspended sediment or any pollutants may be discharged without storm water controls.
35. Lime or cement if spilled in ditches or outside the defined limits of application is considered a pollutant and will be excavated and removed the same day, to avoid contaminating streams.
36. If located along the project ROW, RAP stockpiles will be located where there is a minimum 100 feet of vegetative buffer strip before storm water will reach a stream. RAP will not be used as a construction material within the Ordinary High Water Marks of a stream channel of a 404 designated stream.
37. If allowed on the project, concrete truck wash out areas will have adequate volume to allow 12 inch freeboard for rain and will be lined with 6 mils of plastic. No concrete will be stored higher than the 12 inch freeboard. Cleaning of truck chutes and equipment does not constitute concrete truck wash out and this activity may be completed at the concrete placement location. Wash out areas will not be located closer than 50 ft from down slope inlets or stream channels.
38. For outfalls near stock ponds closer than 50 foot from disturbed soil at the ROW line, redundant sediment controls will be provided, typically a combination of rock filter dam and a silt fence constructed in line of the flow.
39. Earth stockpiles will utilize silt fence sediment controls, positioned on the low end of the stockpile drainage area with L-hooks or silt fence installed around the entire stockpile.
40. Sediment controls including rock filter dams and silt fences will not be installed across any 404 streams. Sediment controls at 404 streams will be positioned to limit sediment entering the stream from the banks and around structures/culverts, and will allow free flow of storm water to pass through the ROW without being dammed by any sediment controls. Remove loose materials from stream channels prior to each rain event.
41. Sediment controls for non-404 streams may be constructed across the drainage channel in unlimited locations. It is appropriate to use sediment control details typically used for 404 streams for non-404 streams when flow velocities are high. Remove loose material from stream channels prior to each rain event.
42. Incomplete drainage pipe installation across the roadway does not remove the requirement for having sediment controls around the ends of the pipe. To stay within permit requirements, sediment controls should be installed over and around the terminated end and along each side of the banks as soon as construction on the pipe has been completed. Remove loose material from stream channels prior to each rain event.
43. Safety end / headwall construction temporarily will require the removal of part of the sediment control placed over and around the pipe end. Retain in place as much functioning sediment control as possible. Replace the silt fence over and around the top of the pipe, immediately upon concrete placement and form removal. Do not remove culvert sediment controls that cannot be replaced before the next rain event. Sediment control at the ends of culverts must be in place and available for any rain event until the disturbed soil areas are re-vegetated.

SCALE = NTS SHEET 3 OF 10

 **Texas Department of Transportation**
Waco District Standard

TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN:	CK:	DW:	CK:
© TxDOT 2009	CONT	SECT	JOB	HIGHWAY
DEC 2013 FEB 2015	0909	29	046	CR
	DIST	COUNTY		SHEET NO.
	WACO	HAMILTON		90

BEST MANAGEMENT PRACTICE (BMP) GENERAL NOTES

44. Between the Ordinary High Water Marks of a 404 stream channel, the Contractor will disturb only the minimum amount of stream channel that is necessary to complete the work.
45. Rock riprap for erosion control does not replace the requirements to maintain sediment control until vegetation is re-established. Replace sediment controls immediately after installing erosion rock.
46. At the direction of TxDOT, sediment deposited into existing and new culverts will be removed subsidiary to Item 506. Sediment to be removed is either pre-existing material before construction starts or sediment generated as a part of this project.
47. Provide treated 2X4 cross bracing for rectangular inlet silt fence, subsidiary to Item 506.
48. Loose or granular earth materials will not be used to repair silt fence undercuts. Silt fence undercut repairs will be conducted with well compacted soils or the silt fence will be reset in a nearby location.
49. Silt fence steel T posts of approximately 1.25 pounds per foot are allowed at a spacing of 8 feet or less. Silt fence steel T posts between approximately 1.25 pounds per foot and 0.85 pounds per foot are allowed for T post spacing of 5 feet or less.
50. Silt fence to be used to slow the flow of storm water down slopes will be positioned approximately horizontal (on the contour) with L hooks on the ends and limited to approximately 200 feet in length. Multiple sections and levels of silt fence may be required in addition to temporary / permanent erosion control flumes.
51. Soil retention blankets will be installed rolled down the slope with the small dimension side embedded at the top of slope, unless recommended otherwise by the manufacturer. Excess grass, rocks, trash, debris or clods will be removed before seeding and installing soil retention blankets. All installations will be by the manufacturer recommendations. Contractor equipment, including tractor mowers will be kept off areas with soil retention blankets until the grass is established.





SCALE = NTS SHEET 4 OF 10

 **Texas Department of Transportation**
Waco District Standard





TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN:	CK:	DW:	CK:
© TxDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY		SHEET NO.
FEB 2015	WACO	HAMILTON		91

	SEDIMENT CONTROL FENCE
	ROCK FILTER DAM (TY 2)
	ROCK FILTER DAM (TY 3)
	DIRECTION OF FLOW

- NOTES:
- ① EXTEND SILT FENCE SO STORM WATER DOES NOT GO AROUND THE ENDS. USE L-HOOKS ON ENDS AS REQUIRED.
 - ② EXTEND ROCK FILTER DAM SO STORM WATER DOES NOT GO AROUND THE ENDS.







SCALE = NTS SHEET 5 OF 10



TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMLAYOUTS.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	92	



	SEDIMENT CONTROL FENCE
	ROCK FILTER DAM (TY 2)
	ROCK FILTER DAM (TY 3)
	DIRECTION OF FLOW

- NOTES:
- ① PROVIDE OVERLAP OF SILT FENCE WITH ROCK FILTER DAM.
 - ② USE SILT FENCE L-HOOKS ON ENDS TO BLOCK STORM WATER SEDIMENT


SCALE = NTS SHEET 6 OF 10




TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	93	




BEST MANAGEMENT PRACTICE (BMP) #9
STOCKPILE SEDIMENT CONTROL




BEST MANAGEMENT PRACTICE (BMP) #10
FOR 404 OR NON-404 STREAMS ONLY ~
SEDIMENT CONTROL AT PHASED CONSTRUCTION OF BRIDGE CLASS CULVERTS

	SEDIMENT CONTROL FENCE
	ROCK FILTER DAM (TY 2)
	ROCK FILTER DAM (TY 3)
	DIRECTION OF FLOW

- NOTES:
- START SEDIMENT CONTROL AT LOCATION SO ALL STORM WATER WITH SEDIMENT IS COLLECTED
 - ROCK FILTER DAMS OR EARTH/GRASSED EMBANKMENTS CAN BE SUBSTITUTED AS DIRECTED.
 - PROVIDE A SMOOTH TRANSITION FROM THE INVERT ELEVATIONS BETWEEN CULVERTS. REMOVE LOOSE SOIL FROM EXCAVATED AREA BETWEEN CULVERTS.
 - PROVIDE AND INSTALL PNEUMATICALLY PLACED CONCRETE ON THE DITCH BOTTOM AND SIDE SLOPES BETWEEN TEMPORARY TERMINATIONS BETWEEN OLD AND NEW CULVERTS. PNEUMATICALLY PLACED CONCRETE WILL BE PLACED TO THE HEIGHT OF THE LARGEST CULVERT ON THE DITCH SIDE SLOPES; AND TO A LIMIT 10 FEET OUTSIDE THE LOCATION OF BMPS ALONG THE DITCH BOTTOM. CEMENT STABILIZED SAND MAY BE SUBSTITUTED FOR PNEUMATICALLY PLACED CONCRETE, IN AREAS WHERE INSTALLATION WORKS AND AT THE OPTION OF TXDOT.



BEST MANAGEMENT PRACTICE (BMP) #11
BOUNDRY SEDIMENT CONTROL ~ BOTH ENDS OF CONTROL TERMINATED UP SLOPE



BEST MANAGEMENT PRACTICE (BMP) #12
BOUNDRY SEDIMENT CONTROL ~ BOTH ENDS OF CONTROL TERMINATED DOWN SLOPE


SCALE = NTS SHEET 7 OF 10



TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMLAYOUTS.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	94	




BEST MANAGEMENT PRACTICE (BMP) #13

USE OF VEGETATIVE BUFFERS IN PLACE OF TEMPORARY SEDIMENT CONTROLS SUCH AS SILT FENCE AND ROCK FILTER DAMS

	FULLY GRASSED DITCH
	DISTURBED AREA
	DIRECTION OF FLOW
	SEDIMENT CONTROL FENCE

- ① FOR H DIMENSIONS LESS THAN 1.5' SILT FENCE MAY NEED TO BE NOTCHED AS SHOWN IN VIEW A-A. ADD EXTRA POSTS AT NOTCH.
- ② BMP #14 MAY BE USED AT CROSS DRAINAGE STRUCTURES AS DIRECTED.



BEST MANAGEMENT PRACTICE (BMP) #14

NON-404 STREAMS AND DITCHES ONLY ~ SEDIMENT CONTROL AT PARALLEL DRAINAGE STRUCTURE ENTRANCE ②


SCALE = NTS SHEET 8 OF 10




TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	95	




BEST MANAGEMENT PRACTICE (BMP) #15
CONCRETE TRUCK WASHOUT AREA




BEST MANAGEMENT PRACTICE (BMP) #16
PUMPED STORM WATER SEDIMENT CONTROLS ①

	FULLY GRASSED DITCH
	DIRECTION OF FLOW
	SEDIMENT CONTROL FENCE
	ROCK FILTER DAM (TY 2)
	ROCK FILTER DAM (TY 3)

- ① PUMPED STORM WATER FROM AN EXCAVATION AREA SHOULD BE DISCHARGED IN A 50' VEGETATIVE BARRIER OR THROUGH TWO TEMPORARY SEDIMENT CONTROLS BEFORE ENTERING A 404 STREAM.
- ② FOR LANDOWNER STOCKPONDS WITHIN 50' OF THE RIGHT OF WAY LINE, PROVIDE REDUNDANT SEDIMENT CONTROLS AT THE CONVEYANCE OF THE POND. MINIMUM OF TWO SEDIMENT CONTROLS.
- ③ WHEN CONTAINMENT AREA REACHES 1' FREEBOARD, DISCONTINUE WASHOUT PLACEMENT AND REMOVE MATERIAL UPON SOLIDIFICATION.
- ④ EACH TIME SOLIDIFIED MATERIAL IS REMOVED REPLACE PLASTIC SHEETING.



BEST MANAGEMENT PRACTICE (BMP) #17
HORIZONTAL INLET SEDIMENT CONTROL



BEST MANAGEMENT PRACTICE (BMP) #18
LANDOWNER STOCKPOND SEDIMENT CONTROL ②


SCALE = NTS SHEET 9 OF 10

Texas Department of Transportation
Waco District Standard

TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES


TA-BMP

FILE: BMPLAYOUTS.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	96	



	DIRECTION OF FLOW
	SEDIMENT CONTROL FENCE
	ROCK FILTER DAM
	SECURITY FENCING

- ① HAY BALES MAY BE SUBSTITUTED FOR SILT FENCE OVER THE STREAM CROSSING.
- ② CROSSING WILL BE AS PER REQUIREMENTS OF THE WATERS OF THE US GENERAL NOTES.
- ③ INSTALL SILT FENCE SLIGHTLY UP FROM OHW MARK FROM R.O.W. TO R.O.W.
- ④ USE SILT FENCE L-HOOKS ON LEVEL OR DOWN SLOPING ENDS TO BLOCK STORM WATER SEDIMENT
- ⑤ INSTALL LARGE V OR U SHAPED BMP'S FROM ABUTMENT AS SHOWN. IF THERE IS STEEP DITCH CONDITIONS DECREASE SPACING AND CONSIDER RFD'S. ADD ADDITIONAL BMP'S IF GRADE IS STEEP OR IF FLOW IS HIGH.



SCALE = NTS SHEET 10 OF 10

Texas Department of Transportation
Waco District Standard

TYPICAL APPLICATIONS FOR BEST MANAGEMENT PRACTICES

TA-BMP

FILE: BMPLAYOUTS.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT	CK: TXDOT
© TXDOT 2009	CONT	SECT	JOB	HIGHWAY
REVISIONS	0909	29	046	CR
DEC 2013	DIST	COUNTY	SHEET NO.	
FEB 2015	WACO	HAMILTON	97	