

FED. RD. DIV. NO.	PROJECT NO.	SHEET NO.
6	STP 2023(978)HES	1
STATE	STATE DIST.	COUNTY
TEXAS	YKM	FAYETTE, ETC
CONT.	SECT.	JOB
0114	08	036, ETC US 290, ETC

SEE SHEET 2 FOR "INDEX OF SHEETS"

CONTRACTOR: _____
 DATE OF LETTING: _____
 DATE WORK BEGAN: _____
 DATE WORK COMPLETED: _____
 DATE WORK ACCEPTED: _____
 FINAL CONTRACT COST: \$ _____


LIST OF APPROVED FIELD CHANGES:

STATE OF TEXAS

TEXAS DEPARTMENT OF TRANSPORTATION

PLANS OF PROPOSED STATE HIGHWAY IMPROVEMENT

FOR THE CONSTRUCTION OF HAZARD ELIMINATION AND SAFETY
 CONSISTING OF INSTALL MEDIAN BARRIER



DESIGN SPEED: N/A
 HWY FUNCTIONAL CLASS: RURAL PRINCIPAL ARTERIAL

CSJ: 0114-08-036
 HIGHWAY: US 290
 COUNTY: FAYETTE
 LIMITS: FROM WASHINGTON C/L TO LEE C/L
 ADT: 13,532 VPD (2021)
 18,945 VPD (2041)

PROJECT LENGTH	
ROADWAY	= 39,441.60 FT = 7.470 MI
BRIDGES	= 00.00 FT = 0.000 MI
TOTAL	= 39,441.60 FT = 7.470 MI

CSJ: 0266-01-088
 HIGHWAY: SH 71
 COUNTY: FAYETTE
 LIMITS: FROM LA GRANGE CITY LIMITS TO COLORADO C/L
 ADT: 18,659 VPD (2021)
 26,123 VPD (2041)



PROJECT LENGTH	
ROADWAY	= 58,177.58 FT = 11.018 MI
BRIDGES	= 00.00 FT = 0.000 MI
TOTAL	= 58,177.58 FT = 11.018 MI

CSJ: 0266-02-069
 HIGHWAY: SH 71
 COUNTY: COLORADO
 LIMITS: FROM FAYETTE C/L TO MAREK RD
 ADT: 17,150 VPD (2021)
 29,155 VPD (2041)

PROJECT LENGTH	
ROADWAY	= 37,216.57 FT = 7.048 MI
BRIDGES	= 00.00 FT = 0.000 MI
TOTAL	= 37,216.57 FT = 7.048 MI

THIS IS TO CERTIFY THAT THE CONSTRUCTION WORK WAS PERFORMED IN ACCORDANCE WITH THE PLANS, CONTRACT AND LISTED FIELD CHANGES.

_____, P. E. _____
 AREA ENGINEER DATE



SUBMITTED FOR LETTING 04/26/2023
Amanda Anderle Fling, P.E.
 DISTRICT DESIGN ENGINEER

RECOMMENDED FOR LETTING 4/28/2023
 DocuSigned by:
Jeffery Vinklarek, P.E.
 DIRECTOR OF TRANSPORTATION PLANNING AND DEVELOPMENT

APPROVED FOR LETTING 4/28/2023
 DocuSigned by:
Martin C. Horst, P.E.
 DISTRICT ENGINEER

FAYETTE & COLORADO COUNTIES YOAKUM DISTRICT

EXCEPTIONS: NONE
 EQUATIONS: CSJ 0266-01-088
 STA 365+82.89 = STA 149+08.00 (-21,674.89 FT)
 STA 623+24.58 = STA 623+24.26 (+0.32 FT)
 CSJ 0266-02-069
 STA 730+10.56 = STA 730+06.62 (+3.94 FT)
 RAILROAD CROSSINGS: NONE



TEXAS DEPARTMENT OF TRANSPORTATION
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL AID CONSTRUCTION CONTRACTS (FORM FHWA 1273, JULY 2022).

SHEET NO. DESCRIPTION

GENERAL

- 1 TITLE SHEET
- 2 INDEX OF SHEETS
- 3-4 TYPICAL SECTIONS
- 5-7 GENERAL NOTES
- 8 ESTIMATE & QUANTITY SHEET
- 9-12 SUMMARY OF CABLE BARRIER QUANTITIES

TRAFFIC CONTROL

STANDARD SHEETS

- 13-24 BC(1-12)-21
- 25 TCP(2-6)-18
- 26 TCP(5-1)-18
- 27 WZ(RS)-22

ROADWAY

- 28-39 CABLE BARRIER LAYOUT (CSJ 0114-08-036)
- 40-56 CABLE BARRIER LAYOUT (CSJ 0266-01-088)
- 57-67 CABLE BARRIER LAYOUT (CSJ 0266-02-069)
- 68-69 MISCELLANEOUS DETAILS

STANDARD SHEETS

- 70-72 BRIFEN(TL4)-14
- 73 CASS(TL4)-14
- 74 GBRLTR(TL4)-14
- 75-76 NU-CABLE(TL4)-14

SHEET NO. DESCRIPTION

TRAFFIC

STANDARD SHEETS

- 77 D & OM(1)-20


ENVIRONMENTAL

- 78-89 STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)
- 90-107 STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)
- 108-118 STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)
- 119-120 STORMWATER POLLUTION PREVENTION PLAN(SWP3) (CSJ 0114-08-036)
- 121-122 STORMWATER POLLUTION PREVENTION PLAN(SWP3) (CSJ 0266-01-088)
- 123-124 STORMWATER POLLUTION PREVENTION PLAN(SWP3) (CSJ 0266-02-069)
- 125 ENVIRONMENTAL PERMITS, ISSUES & COMMITMENTS

STANDARD SHEETS

- 126 EC(1)-16

PATH: T:\YKMAN\EX\IPS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\DGNI
 FILE: Index_of_Sheets.dgn
 DATE: \$DATE\$



Amanda Anderle Fling, P.E.


04/26/2023

THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ABOVE HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.


INDEX OF SHEETS

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 1 OF 1

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	2



PROPOSED TYPICAL SECTION
US 290 FAYETTE COUNTY
CSJ 0114-08-036
STA 104+00 TO STA 498+41.60




PROPOSED TYPICAL SECTION
SH 71 FAYETTE COUNTY
CSJ 0266-01-088
STA 316+00 TO STA 681+02.37 ①

① EQUATIONS:
 CSJ 0266-01-088
 STA 365+82.89 = STA 149+08.00
 STA 623+24.58 = STA 623+24.26

② SEE "CABLE BARRIER LAYOUT" SHEETS FOR LOCATION OF PROPOSED CABLE BARRIER.

NOTE: CONCRETE MOWSTRIP ON THE ROADSIDE SHALL MATCH THE EXISTING GROUND.



Amanda Anderle Fling, P.E.

04/26/2023


TYPICAL SECTIONS

NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED
 SHEET 1 OF 2

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	3

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE.DGN
 FILE: TYPICAL SECTIONS.dgn
 DATE: \$DATE\$




PROPOSED TYPICAL SECTION
 SH 71 COLORADO COUNTY
 CSJ 0266-02-069
 STA 681+02.37 TO STA 1053+15 ①

① EQUATIONS:
 CSJ: 0266-02-069
 STA 730+10.56 = STA 730+06.62

② SEE "CABLE BARRIER LAYOUT" SHEET FOR LOCATION OF PROPOSED CABLE BARRIER.

NOTE: CONCRETE MOWSTRIP ON THE ROADSIDE SHALL MATCH THE EXISTING GROUND.



Amanda Anderle Fling, P.E.

04/26/2023

TYPICAL SECTIONS

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 2 OF 2

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	4

Project Number:

Sheet: 5

County: FAYETTE, ETC

Control: 0114-08-036, ETC

Highway: US 290, ETC

GENERAL:

Contractor questions on this project are to be addressed to the following individual(s):

Covey Morrow IV Covey.Morrow@txdot.gov

Chase Hermes Chase.Hermes@txdot.gov

Contractor questions will be accepted through email, phone, and in person by the above individuals.

Questions may be submitted via the Letting Pre-Bid Q&A web page. This webpage can be accessed from the Notice to Contractors dashboard located at the following Address:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>

All contractor questions will be reviewed by the Engineer. All questions and any corresponding responses that are generated will be posted through the same Letting Pre-Bid Q&A web page.

The Letting Pre-Bid Q&A web page for each project can be accessed by using the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink for the project you want to view the Q&A for and click on the link in the window that pops up.

All questions submitted that generate a response will be posted through this site. The site is organized by District, Project Type (Construction or Maintenance), Letting Date, CCSJ/Project Name.

The Contractor's attention is directed to the fact that several companies have existing underground gas/oil facilities located within or near the project limits. These companies include Energy Transfer SETPS, DCP Midstream, Magnolia Oil and Gas Operating LLC, and Wink to Webster Pipeline LLC. Excavation and/or construction is prohibited without prior notification to these companies.

Do not work on the roadway before sunrise or after sunset unless otherwise approved.

Leave all traffic lanes open to traffic at night, weekends and holidays unless otherwise approved.

Furnish a certified copy of the legal gross weight of each vehicle hauling materials by weight and certified measurements for all trucks hauling material by volume.

Do not cross the median except at existing crossovers.

Project Number:

Sheet: 5

County: FAYETTE, ETC

Control: 0114-08-036, ETC

Highway: US 290, ETC

Unless otherwise approved, maintain a minimum safety clearance from the edge of the travelway for material stockpiled in proximity of traffic lanes based on the current average traffic count of the particular highway as follows:

0 - 1500 = 16 feet

Over 1500 = 30 feet

In the event the above requirements cannot be met, make arrangements to stockpile material off the right of way.

Do not store equipment or stockpile material in the median overnight unless otherwise approved.

Grade and shape the roadway to the typical section shown in the plans and to a finish profile that is uniform and consistent with the topography as directed.

The Department will provide the cylinder testing machine for this project. Deliver the test specimens to the engineer's curing facilities as directed.

Do not clean out concrete trucks within the right of way.

ITEM 6: CONTROL OF MATERIALS

To comply with the latest provisions of Build America, Buy America Act (BABA Act) of the Bipartisan Infrastructure Law, the contractor must submit a notarized original of the TxDOT Construction Material Buy America Certification Form for all items classified as construction materials. This form is not required for materials classified as a manufactured product.

Refer to the Buy America Material Classification Sheet for clarification on material categorization.

The Buy America Material Classification Sheet is located at the below link.

<https://www.txdot.gov/business/resources/materials/buy-america-material-classification-sheet.html> for clarification on material categorization.

County: FAYETTE, ETC

Control: 0114-08-036, ETC

Highway: US 290, ETC

ITEM 7: LEGAL RELATIONS AND RESPONSIBILITIES

The Department has determined that a USACE Nationwide or Individual Permit is not necessary for the project since all work shall be conducted outside the USACE jurisdictional areas. Any impacts to these jurisdictional areas by the Contractor without a USACE permit will be the responsibility of the Contractor. If the Contractor deems it necessary to impact the USACE jurisdictional areas, then it becomes the Contractor's entire responsibility to consult with the USACE pertaining to the need for a Nationwide or Individual Permit. TXDOT will then hold the Contractor responsible for following all conditions of the approved permit.

No significant traffic generator events identified.

If the contractor proposes work beyond the TxDOT obtained permit limitations, the contractor is responsible for additional costs, delays, and obtaining new or revised permits prior to construction.

ITEM 8: PROSECUTION AND PROGRESS

Provide progress schedule as a Bar Chart.

ITEM 132: EMBANKMENT

Furnish Type C embankment consisting of suitable earth material such as loam, clay or other such material that will form a stable embankment and has a plasticity index of at least 15 but not more than 40. [Requirements may vary for material excavated under Item 110, "Excavation" as directed.](#)

ITEM 150: BLADING

Sprinkling and rolling which may be required during the operation of Item 150 will not be measured or paid for directly, but will be considered subsidiary to this item.

ITEM 432: RIPRAP

Place 1/2 inch expansion joint material between the two concrete areas or structures where riprap is placed against other concrete such as concrete pavement and structures unless otherwise shown on the plans or as directed. This work will not be paid for directly but will be subsidiary to the pertinent items.

County: FAYETTE, ETC

Control: 0114-08-036, ETC

Highway: US 290, ETC

ITEM 502: BARRICADES, SIGNS, AND TRAFFIC HANDLING

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

Law enforcement assistance for this project will be required, as approved, for major traffic control changes and lane closures. Coordinate with local law enforcement and arrange for law enforcement in a marked vehicle as approved by the Engineer. Complete the daily tracking form provided by the department, including all signatures, and submit invoices that agree with the tracking form for payment at the end of each month approved services were provided.

Use WZ(RS)-22 in conjunction with TCP(2-6).

Provide suitable warning lights mounted high enough to be visible from all directions on all construction equipment, including pilot vehicles, and operate warning lights when the equipment is within the right of way. Equip other equipment such as trucks, trailers, autos, etc., with emergency flashers and use emergency flashers while within the work area.

No additional payment will be made for relocating existing sign assemblies to temporary mounts.

Limit the maximum length of any individual work area to 2 miles.

Provide lights to illuminate the flaggers and work area during night time operations. Class 3 garments shall be required for all workers and flaggers during night time work.

ITEM 506: TEMPORARY EROSION, SEDIMENTATION, AND ENVIRONMENTAL CONTROLS

1. See SWP3 plan sheet for total disturbed acreage.
2. The disturbed area in this project, all project locations in the contract, and contractor project specific locations (PSLs), within one (1) mile of the project limits, for the contract will further establish the authorization requirements for storm water discharges.
3. The department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans.

Project Number:

Sheet: 7

County: FAYETTE, ETC

Control: 0114-08-036, ETC

Highway: US 290, ETC

4. Obtain any required authorization from the TCEQ for any contractor PSLs for construction activities on or off right-of-way (ROW).
5. When the total disturbed area for all projects in the contract and PSLs within one (1) mile of the project limits exceeds five (5) acres, provide a copy of the contractor NOI.
6. Provide a signed sketch detailing the location of any contractor's PSLs on ROW or within one (1) mile of the project.

ITEM 543: CABLE BARRIER SYSTEM

Within 15 days of notice to proceed, contractors shall provide correspondence from post and cable supplier on expected delivery date of material. Contractor shall complete all work except the post and cable installation. Time will be suspended when this work is complete. Time will resume when installation of the post and cable begins, or 20 days after receipt of the post and cable material, whichever comes first.

ITEM 6185: TRUCK MOUNTED ATTENUATOR (TMA) AND TRAILER ATTENUATOR (TA)

Shadow vehicle(s) with TMA are set up for stationary and/or mobile operations. The contractor will be responsible for determining if operations will be ongoing at the same time to determine the total number of TMAs needed for the project.



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0114-08-036

DISTRICT Yoakum
HIGHWAY SH 71, US 290

COUNTY Colorado, Fayette

CONTROL SECTION JOB				0114-08-036		0266-01-088		0266-02-069		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00184556		A00184555		A00188481			
COUNTY				Fayette		Fayette		Colorado			
HIGHWAY				US 290		SH 71		SH 71			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL	EST.	FINAL	EST.	FINAL		
	132-6021	EMBANKMENT (VEHICLE)(ORD COMP)(TY C)	CY	21,577.000		9,681.000		588.000		31,846.000	
	150-6002	BLADING	HR	54.000		66.000		34.000		154.000	
	164-6004	BROADCAST SEED (PERM) (RURAL) (CLAY)	AC	6.280		8.030		6.290		20.600	
	164-6010	BROADCAST SEED (TEMP) (WARM)	AC	1.580		2.070		1.600		5.250	
	164-6012	BROADCAST SEED (TEMP) (COOL)	AC	1.580		2.070		1.600		5.250	
	168-6001	VEGETATIVE WATERING	MG	170.780		218.400		171.080		560.260	
	432-6045	RIPRAP (MOW STRIP)(4 IN)	CY	1,691.500		2,156.800		1,693.200		5,541.500	
	500-6001	MOBILIZATION	LS	1.000						1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	8.000						8.000	
	506-6038	TEMP SEDMT CONT FENCE (INSTALL)	LF	1,550.000		2,280.000		1,130.000		4,960.000	
	506-6039	TEMP SEDMT CONT FENCE (REMOVE)	LF	1,550.000		2,280.000		1,130.000		4,960.000	
	543-6002	CABLE BARRIER SYSTEM (TL-4)	LF	31,556.000		40,374.000		32,591.000		104,521.000	
	543-6020	CABLE BARRIER TERMINAL SECTION (TL-4)	EA	54.000		66.000		34.000		154.000	
	771-6002	REPLACE POSTS (TL-4)	EA	100.000		200.000		100.000		400.000	
	771-6004	CABLE SPLICE / TURNBUCKLE (TL-4)	EA	6.000		12.000		6.000		24.000	
	771-6006	REPAIR CONCRETE FOUNDATION (TL-4)	EA	6.000		12.000		6.000		24.000	
	771-6008	REPR OR REPLC CABLE BARR TERM SEC(TL-4)	EA	6.000		12.000		6.000		24.000	
	771-6010	REPLACE CABLE (TL-4)	LF	100.000		200.000		100.000		400.000	
	6185-6002	TMA (STATIONARY)	DAY	54.000		66.000		34.000		154.000	
18		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000						1.000	
		SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000						1.000	
		LAW ENFORCEMENT: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	20.000						20.000	

PATH: T:\KMAN\XPS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290.DGN
 FILE: Summary of Cable Barrier quantities.dgn
 DATE: \$DATE\$

DESCRIPTION	CABLE BARRIER LIMITS (TERMINAL SECTION NOT INCLUDED)		RT/LT OF MEDIAN C/L	**CABLE BARRIER OFFSET FROM EDGE OF TRAVELWAY FT	ITEM 132 EMBANK (VEHICLE) (ORD COMP) (TY C) (CF=1.4) CY	ITEM 150 BLADING ① (EST) HR	ITEM 164 BROADCAST SEED			*ITEM 166 FERTILIZER 500#/AC TON	ITEM 168 VEGETATIVE WATERING 13.6 MG/AC/MO (2 MO) MG	ITEM 432 RIPRAP (MOW STRIP) (4 IN) CY	***ITEM 543 CABLE BARRIER SYSTEM (TL - 4) LF	ITEM 543 CABLE BARRIER TERMINAL SYSTEM (TL - 4) EA	ITEM 771				
	FROM STA	TO STA					(PERM) (RURAL) (CLAY) AC	(TEMP) (WARM) AC	(TEMP) (COOL) AC						REPLACE POSTS (TL - 4) (EST) EA	CABLE SPLICE TURNBUCKLE (TL - 4) (EST) EA	REPAIR CONCRETE FOUNDATION (TL - 4) (EST) EA	REPAIR OR REPLACE CABLE BARRIER TERM SECTION (TL - 4) (EST) EA	REPLACE CABLE (TL - 4) (EST) LF
US 290 0114-08-036 (FAYETTE COUNTY)																			
BEGIN CABLE BARRIER	105+66	122+67	LT	16			0.33	0.08	0.08	0.08	8.98	88.9	1701	2					
NO BARRIER	123+92	134+50																	
X-OVER TO X-OVER	135+75	148+85	LT	16			0.26	0.07	0.07	0.07	7.07	69.6	1310	2					
X-OVER TO X-OVER	151+12	163+85	LT	16			0.25	0.06	0.06	0.06	6.80	67.8	1273	2					
X-OVER TO X-OVER	166+14	180+84	LT	16			0.29	0.07	0.07	0.07	7.89	77.5	1470	2					
X-OVER TO X-OVER	183+15	195+34	LT	16			0.24	0.06	0.06	0.06	6.53	65.1	1219	2					
X-OVER TO X-OVER	197+64	210+83	LT	16			0.26	0.07	0.07	0.07	7.07	70.1	1319	2					
X-OVER TO X-OVER	213+15	226+85	LT	16			0.27	0.07	0.07	0.07	7.34	72.6	1370	2					
X-OVER TO X-OVER	229+16	239+82	LT	16			0.21	0.05	0.05	0.05	5.71	57.6	1066	2					
X-OVER TO X-OVER	242+13	252+84	LT	16			0.22	0.06	0.06	0.06	5.98	57.8	1071	2					
X-OVER TO X-OVER	255+14	265+60	LT	16			0.21	0.05	0.05	0.05	5.71	56.6	1046	2					
X-OVER TO X-OVER	268+13	278+82	LT	16	21577	54	0.21	0.05	0.05	0.05	5.71	57.7	1069	2	100				
X-OVER TO X-OVER	281+22	289+56	LT	16			0.17	0.04	0.04	0.04	4.62	46.1	834	2	6				
X-OVER TO X-OVER	291+89	304+80	LT	16			0.26	0.07	0.07	0.07	7.07	68.7	1291	2	6				
X-OVER TO X-OVER	307+14	317+84	LT	16			0.21	0.05	0.05	0.05	5.71	57.8	1070	2	6				
X-OVER TO X-OVER	320+13	333+82	LT	16			0.27	0.07	0.07	0.07	7.34	72.5	1369	2	6				
X-OVER TO X-OVER	336+15	348+82	LT	16			0.25	0.06	0.06	0.06	6.80	67.5	1267	2	6				
X-OVER TO X-OVER	351+13	366+37	LT	16			0.3	0.08	0.08	0.08	8.16	80.2	1524	2	6				
X-OVER TO X-OVER	368+65	383+73	LT	16			0.3	0.08	0.08	0.08	8.16	79.4	1508	2	6				
X-OVER TO X-OVER	386+20	395+83	LT	16			0.2	0.05	0.05	0.05	5.44	52.5	963	2	6				
X-OVER TO X-OVER	398+18	408+84	LT	16			0.21	0.05	0.05	0.05	5.71	57.6	1066	2	6				
X-OVER TO X-OVER	411+15	421+73	LT	16			0.21	0.05	0.05	0.05	5.71	57.2	1058	2	6				
X-OVER TO X-OVER	424+24	440+67	LT	16			0.32	0.08	0.08	0.08	8.70	86.1	1643	2	6				
X-OVER TO X-OVER	443+15	452+14	LT	16			0.18	0.05	0.05	0.05	4.90	49.3	899	2	6				
X-OVER TO X-OVER	454+71	460+50	LT	16			0.12	0.03	0.03	0.03	3.26	33.5	579	2	6				
X-OVER TO X-OVER	466+24	473+85	LT	16			0.16	0.04	0.04	0.04	4.35	42.5	761	2	6				
X-OVER TO X-OVER	476+35	486+26	LT	16			0.2	0.05	0.05	0.05	5.44	53.9	991	2	6				
X-OVER TO END OF BARRIER	488+95	497+14	LT	16			0.17	0.04	0.04	0.04	4.62	45.4	819	2	6				
CSJ 0114-08-036 TOTAL					21577	54	6.28	1.58	1.58	1.58	170.78	1691.5	31556	54	100				

① LOCATIONS AS DIRECTED BY THE ENGINEER.

* FOR CONTRACTOR'S INFORMATION ONLY
 ** OFFSETS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
 20' OF CLEARANCE REQUIRED BETWEEN CABLE BARRIER AND MBGF/END TREATMENT LOCATIONS.

NOTES:
 1. CABLE BARRIER LENGTHS MAY NEED TO BE ADJUSTED IN THE FIELD DEPENDING ON ANCHOR SECTION TYPE SELECTED. A 50' TERMINAL SECTION LENGTH WAS USED FOR QUANTITY AND STATION CALCULATIONS.
 2. CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS. FIELD VERIFY BEFORE ALL MATERIALS ARE ORDERED.

TMA SUMMARY

LOCATION	ITEM 6185
	TMA(STATIONARY)
	(DAY)
PROJECT LIMITS	54
CSJ 0114-08-036 TOTALS	54

*** REDUCED POST SPACING TO BE INSTALLED ALONG THE FOLLOWING HORIZONTAL CURVES WITHIN STATIONS:

STA 272+66.11 TO STA 289+87.91
 STA 345+83.62 TO STA 350+63.80
 STA 363+10.02 TO STA 370+20.18
 STA 373+96.53 TO STA 378+08.67
 STA 391+22.24 TO STA 395+34.34

SEE "MISCELLANEOUS DETAILS" FOR MORE INFORMATION.

SUMMARY OF CABLE BARRIER QUANTITIES

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	9

CABLE BARRIER SUMMARY

DESCRIPTION	CABLE BARRIER LIMITS (TERMINAL SECTION NOT INCLUDED)		RT/LT OF MEDIAN C/L	**CABLE BARRIER OFFSET FROM EDGE OF TRAVELWAY FT	ITEM 132 EMBANK (VEHICLE) (ORD COMP) (TY C) (CF=1.4) CY (EST)	ITEM 150 BLADING ① HR (EST)	ITEM 164 BROADCAST SEED			*ITEM 166 FERTILIZER 500#/AC TON	ITEM 168 VEGETATIVE WATERING 13.6 MG/AC/MO (2 MO) MG	ITEM 432 RIPRAP (MOW STRIP) (4 IN) CY	***ITEM 543 CABLE BARRIER SYSTEM (TL - 4) LF	ITEM 543 CABLE BARRIER TERMINAL SYSTEM (TL - 4) EA	ITEM 771					
	FROM STA	TO STA					(PERM) (RURAL) (CLAY) AC	(TEMP) (WARM) AC	(TEMP) (COOL) AC						REPLACE POSTS (TL - 4) (EST) EA	CABLE SPLICE TURNBUCKLE (TL - 4) (EST) EA	REPAIR CONCRETE FOUNDATION (TL - 4) (EST) EA	REPAIR OR REPLACE CABLE BARRIER TERM SECTION (TL - 4) (EST) EA	REPLACE CABLE (TL - 4) (EST) LF	
SH 71 0266-01-088 (FAYETTE COUNTY)																				
BEGIN BARRIER TO X-OVER	316+97	326+97	RT	16			0.20	0.05	0.05	0.05	5.44	54.3	1000	2						
X-OVER TO X-OVER	329+68	342+02	RT	16			0.24	0.06	0.06	0.06	6.53	65.9	1234	2						
X-OVER TO X-OVER	344+34	359+12	LT	16			0.29	0.07	0.07	0.07	7.89	77.9	1478	2						
X-OVER TO ROCKY CREEK BRIDGE NO BARRIER	360+50	365+82.89	②																	
ROCKY CREEK BRIDGE NO BARRIER	② 149+08.00	150+90																		
ROCKY CREEK BRIDGE TO X-OVER	151+40	160+40	RT	16			0.18	0.05	0.05	0.05	4.90	49.4	900	2						
X-OVER TO X-OVER	162+80	176+41	RT	16			0.27	0.07	0.07	0.07	7.34	72.1	1361	2						
X-OVER TO X-OVER	178+76	195+55	RT	16			0.33	0.08	0.08	0.08	8.98	87.9	1679	2						
X-OVER TO X-OVER	197+96	208+80	LT	16			0.22	0.06	0.06	0.06	5.98	58.5	1084	2						
X-OVER TO X-OVER	211+20	222+30	LT	16			0.22	0.06	0.06	0.06	5.98	59.8	1110	2						
X-OVER TO X-OVER	224+70	240+60	LT	16			0.31	0.08	0.08	0.08	8.43	83.5	1590	2						
X-OVER TO X-OVER	243+00	252+20	LT	16			0.19	0.05	0.05	0.05	5.17	50.4	920	2						
X-OVER TO X-OVER	254+65	272+30	LT	16			0.34	0.09	0.09	0.09	9.25	92.1	1765	2						
NO BARRIER	273+50	280+20			7658	42									100	6	6	6		100
X-OVER TO BAYLOR CREEK BRIDGE NO BARRIER	280+20	294+69																		
BAYLOR CREEK BRIDGE TO X-OVER	295+19	305+27	LT	16			0.20	0.05	0.05	0.05	5.44	54.7	1008	2						
X-OVER TO X-OVER	307+80	325+79	LT	16			0.35	0.09	0.09	0.09	9.52	93.8	1799	2						
X-OVER TO X-OVER NO BARRIER	327+00	333+84																		
X-OVER TO X-OVER	335+06	347+00	LT	16			0.24	0.06	0.06	0.06	6.53	63.9	1194	2						
X-OVER TO X-OVER NO BARRIER	348+20	355+40																		
X-OVER TO X-OVER	357+08	370+50	LT	16			0.26	0.07	0.07	0.07	7.07	71.2	1342	2						
X-OVER TO CEDAR CREEK BRIDGE	372+90	379+90	RT	16			0.15	0.04	0.04	0.04	4.08	39.5	700	2						
CEDAR CREEK BRIDGE TO X-OVER NO BARRIER	380+40	389+60																		
X-OVER TO X-OVER	390+86	404+35	RT	16			0.27	0.07	0.07	0.07	7.34	71.6	1349	2						
X-OVER TO X-OVER	406+90	422+30	LT	16			0.30	0.08	0.08	0.08	8.16	81.0	1540	2						
X-OVER TO X-OVER	424+70	438+79	RT	16			0.28	0.07	0.07	0.07	7.62	74.5	1409	2						
X-OVER TO X-OVER	441+25	452+10	RT	16			0.22	0.06	0.06	0.06	5.98	58.5	1085	2						
X-OVER TO X-OVER	454+65	461+25	RT	16			0.14	0.04	0.04	0.04	3.81	37.5	660	2						
CSJ 0266-01-088 SHEET TOTAL					7658	42	5.20	1.35	1.35	1.35	141.44	1398	26207	42	100	6	6	6		100

① LOCATIONS AS DIRECTED BY THE ENGINEER.

② EQUATIONS:
CSJ 0266-01-088
STA 365+82.89 = STA 149+08.00
STA 623+24.58 = STA 623+24.26

* FOR CONTRACTOR'S INFORMATION ONLY
** OFFSETS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
20' OF CLEARANCE REQUIRED BETWEEN CABLE BARRIER AND MBGF/END TREATMENT LOCATIONS.

NOTES:
1. CABLE BARRIER LENGTHS MAY NEED TO BE ADJUSTED IN THE FIELD DEPENDING ON ANCHOR SECTION TYPE SELECTED. A 50' TERMINAL SECTION LENGTH WAS USED FOR QUANTITY AND STATION CALCULATIONS.
2. CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS. FIELD VERIFY BEFORE ALL MATERIALS ARE ORDERED.

*** REDUCED POST SPACING TO BE INSTALLED ALONG THE FOLLOWING HORIZONTAL CURVES WITHIN STATIONS:

STA 357+35.30 TO STA 362+97.46
STA 155+76.98 TO STA 183+93.00
STA 191+20.01 TO STA 195+79.99
STA 221+56.57 TO STA 228+43.43
STA 261+31.16 TO STA 293+99.42
STA 305+88.57 TO STA 313+71.47
STA 342+88.71 TO STA 364+02.67
STA 384+13.74 TO STA 394+35.76
STA 401+06.56 TO STA 408+66.80
STA 451+28.52 TO STA 465+97.68
STA 471+68.77 TO STA 480+33.47
STA 515+63.74 TO STA 520+82.64
STA 571+72.17 TO STA 576+44.95
STA 585+53.00 TO STA 591+85.51
STA 617+16.74 TO STA 623+24.72
STA 646+35.08 TO STA 691+37.46

SEE "MISCELLANEOUS DETAILS" FOR MORE INFORMATION.

SUMMARY OF CABLE BARRIER QUANTITIES

 **Texas Department of Transportation**
© 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
ALL RIGHTS RESERVED

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	10

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290.DGN
FILE: Summary of Cable Barrier quantities.dgn
DATE: \$DATE\$

CABLE BARRIER SUMMARY

DESCRIPTION	CABLE BARRIER LIMITS (TERMINAL SECTION NOT INCLUDED)		RT/LT OF MEDIAN C/L	**CABLE BARRIER OFFSET FROM EDGE OF TRAVELWAY FT	ITEM 132 EMBANK (VEHICLE) (ORD COMP) (TY C) (CF=1.4) (EST) CY	ITEM 150 BLADING ① (EST) HR	ITEM 164 BROADCAST SEED			*ITEM 166 FERTILIZER 500#/AC TON	ITEM 168 VEGETATIVE WATERING 13.6 MG/AC/MO (2 MO) MG	ITEM 432 RIPRAP (MOW STRIP) (4 IN) CY	***ITEM 543 CABLE BARRIER SYSTEM (TL - 4) LF	ITEM 543 CABLE BARRIER TERMINAL SYSTEM (TL - 4) EA	ITEM 771					
	FROM STA	TO STA					(PERM) (RURAL) (CLAY) AC	(TEMP) (WARM) AC	(TEMP) (COOL) AC						REPLACE POSTS (TL - 4) (EST) EA	CABLE SPLICE TURNBUCKLE (TL - 4) (EST) EA	REPAIR CONCRETE FOUNDATION (TL - 4) (EST) EA	REPAIR OR REPLACE CABLE BARRIER TERM SECTION (TL - 4) (EST) EA	REPLACE CABLE (TL - 4) (EST) LF	
SH 71 0266-01-088 (FAYETTE COUNTY) (CONTINUED)																				
X-OVER TO X-OVER	463+77	479+00	LT	16			0.30	0.08	0.08	0.08	8.16	80.1	1523	2						
X-OVER TO X-OVER	481+53	497+76	LT	16			0.32	0.08	0.08	0.08	8.70	85.1	1623	2						
X-OVER TO X-OVER	500+20	512+00	LT	16			0.24	0.06	0.06	0.06	6.53	63.2	1180	2						
X-OVER TO X-OVER	516+50	532+35	RT	16			0.31	0.08	0.08	0.08	8.43	83.2	1585	2						
X-OVER TO PETTY'S CREEK	534+90	542+00	RT	16			0.15	0.04	0.04	0.04	4.08	40.0	710	2						
PETTY'S CREEK BRIDGE TO X-OVER NO BARRIER	542+50	551+05																		
X-OVER TO X-OVER	552+28	562+05	RT	16			0.20	0.05	0.05	0.05	5.44	53.2	977	2						
X-OVER TO X-OVER	564+55	575+14	RT	16			0.21	0.05	0.05	0.05	5.71	57.2	1059	2						
X-OVER TO X-OVER	577+65	585+83	RT	16			0.17	0.04	0.04	0.04	4.62	45.3	818	2						
X-OVER TO CITY OF ELLINGER NO BARRIER	587+00	592+74																		
CITY OF ELLINGER TO X-OVER NO BARRIER	619+00	623+05																		
X-OVER TO X-OVER	624+10	634+70	RT	16			0.21	0.05	0.05	0.05	5.71	57.3	1060	2						
X-OVER TO X-OVER	637+22	647+17	RT	16	2023	24	0.20	0.05	0.05	0.05	5.44	54.1	995	2	100	6	6	6	6	100
X-OVER TO X-OVER	649+49	662+73	RT	16			0.26	0.07	0.07	0.07	7.07	70.3	1324	2						
X-OVER TO END OF BARRIER	665+18	678+31	RT	16			0.26	0.07	0.07	0.07	7.07	69.8	1313	2						
CSJ 0266-01-088 SHEET TOTAL					2023	24	2.83	0.72	0.72	0.72	76.96	758.8	14167	24	100	6	6	6	6	100
CSJ 0266-01-088 TOTAL					9681	66	8.03	2.07	2.07	2.07	218.40	2156.8	40374	66	200	12	12	12	12	200

① LOCATIONS AS DIRECTED BY THE ENGINEER.

*** REDUCED POST SPACING TO BE INSTALLED ALONG THE FOLLOWING HORIZONTAL CURVES WITHIN STATIONS:

TMA SUMMARY

LOCATION	ITEM 6185 TMA(STATIONARY) (DAY)
PROJECT LIMITS	66
CSJ 0266-01-088 TOTALS	66

STA 357+35.30 TO STA 362+97.46
 STA 155+76.98 TO STA 183+93.00
 STA 191+20.01 TO STA 195+79.99
 STA 221+56.57 TO STA 228+43.43
 STA 261+31.16 TO STA 293+99.42
 STA 305+88.57 TO STA 313+71.47
 STA 342+88.71 TO STA 364+02.67
 STA 384+13.74 TO STA 394+35.76
 STA 401+06.56 TO STA 408+66.80
 STA 451+28.52 TO STA 465+97.68
 STA 471+68.77 TO STA 480+33.47
 STA 515+63.74 TO STA 520+82.64
 STA 571+72.17 TO STA 576+44.95
 STA 585+53.00 TO STA 591+85.51
 STA 617+16.74 TO STA 623+24.72
 STA 646+35.08 TO STA 691+37.46

* FOR CONTRACTOR'S INFORMATION ONLY
 ** OFFSETS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
 20' OF CLEARANCE REQUIRED BETWEEN CABLE BARRIER AND MBGF/END TREATMENT LOCATIONS.

NOTES:
 1. CABLE BARRIER LENGTHS MAY NEED TO BE ADJUSTED IN THE FIELD DEPENDING ON ANCHOR SECTION TYPE SELECTED. A 50' TERMINAL SECTION LENGTH WAS USED FOR QUANTITY AND STATION CALCULATIONS.
 2. CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS. FIELD VERIFY BEFORE ALL MATERIALS ARE ORDERED.

SUMMARY OF CABLE BARRIER QUANTITIES

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 3 OF 4

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	11

SEE "MISCELLANEOUS DETAILS" FOR MORE INFORMATION.

PATH: T:\KMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE.DGN
 FILE: Summary of Cable Barrier Quantities.dgn
 DATE: \$DATE\$

DESCRIPTION	CABLE BARRIER LIMITS (TERMINAL SECTION NOT INCLUDED)		RT/LT OF MEDIAN C/L	**CABLE BARRIER OFFSET FROM EDGE OF TRAVELWAY FT	ITEM 132 EMBANK (VEHICLE (ORD COMP) (TY C) (CF=1.4) EST CY	ITEM 150 BLADING ① EST HR	ITEM 164 BROADCAST SEED			*ITEM 166 FERTILIZER 500#/AC TON	ITEM 168 VEGETATIVE WATERING 13.6 MG/AC/MO (2 MO) MG	ITEM 432 RIPRAP (MOW STRIP) (4 IN) CY	***ITEM 543 CABLE BARRIER SYSTEM (TL - 4) LF	ITEM 543 CABLE BARRIER TERMINAL SYSTEM (TL - 4) EA	ITEM 771											
	FROM STA	TO STA					(PERM) (RURAL) (CLAY) AC	(TEMP) (WARM) AC	(TEMP) (COOL) AC						REPLACE POSTS (TL - 4) EA	CABLE SPLICE TURNBUCKLE (TL - 4) EA	REPAIR CONCRETE FOUNDATION (TL - 4) EA	REPAIR OR REPLACE CABLE BARRIER TERM SECTION (TL - 4) EA	REPLACE CABLE (TL - 4) LF							
SH 71 0266-02-069 (COLORADO COUNTY)																										
BEGIN BARRIER TO X-OVER	681+25	692+60	RT	16	588	34	0.23	0.06	0.06	0.06	6.26	61.0	1135	2	100	6	6	6	100							
X-OVER TO X-OVER	695+20	710+10	RT	16			0.29	0.07	0.07	0.07	7.89	78.5	1490	2												
X-OVER TO X-OVER NO BARRIER	711+40	717+14																								
X-OVER TO X-OVER	718+44	724+95	LT	16			0.14	0.04	0.04	0.04	3.81	37.1	651	2												
X-OVER TO STATION EQUATION	727+55	730+01.56 ②	LT	16			0.06	0.02	0.02	0.02	1.63	17.1	247	2												
STATION EQUATION TO X-OVER	② 730+06.62	757+70	LT	16			0.53	0.13	0.13	0.13	14.42	141.4	2763	2												
X-OVER TO X-OVER	760+30	804+10	RT	16			0.82	0.21	0.21	0.21	22.30	221.2	4380	2												
X-OVER TO X-OVER	806+70	827+70	RT	16			0.40	0.10	0.10	0.10	10.88	108.6	2100	2												
X-OVER TO X-OVER	830+30	872+60	RT	16			0.80	0.20	0.20	0.20	21.76	213.8	4230	2												
X-OVER TO X-OVER	875+20	899+15	RT	16			0.46	0.12	0.12	0.12	12.51	123.2	2395	2												
X-OVER TO X-OVER	901+75	934+45	RT	16			0.62	0.16	0.16	0.16	16.86	166.4	3270	2												
X-OVER TO X-OVER	937+05	953+50	LT	16			0.32	0.08	0.08	0.08	8.70	86.2	1645	2												
X-OVER TO X-OVER	956+10	978+70	LT	16			0.43	0.11	0.11	0.11	11.70	116.5	2260	2												
X-OVER TO X-OVER	981+30	996+55	RT	16			0.30	0.08	0.08	0.08	8.16	80.2	1525	2												
X-OVER TO X-OVER	999+15	1015+60	RT	16			0.32	0.08	0.08	0.08	8.70	86.2	1645	2												
X-OVER TO X-OVER	1018+20	1027+75	RT	16			0.19	0.05	0.05	0.05	5.17	52.1	955	2												
X-OVER TO X-OVER	1030+35	1041+00	RT	16			0.21	0.05	0.05	0.05	5.71	57.5	1065	2												
X-OVER TO END BARRIER	1043+50	1051+85	LT	16			0.17	0.04	0.04	0.04	4.62	46.2	835	2												
CSJ 0266-02-069 TOTAL							588	34	6.29	1.60	1.60	1.60	171.08	1693.2						32591	34	100	6	6	6	100

*** REDUCED POST SPACING TO BE INSTALLED ALONG THE FOLLOWING HORIZONTAL CURVES WITHIN STATIONS:

STA 646+35.08 TO STA 691+37.46
 STA 711+40.00 TO STA 729+43.86
 STA 966+32.96 TO STA 979+53.60
 STA 983+89.31 TO STA 990+52.51
 STA 1025+27.36 TO STA 1038+48.00

SEE "MISCELLANEOUS DETAILS" FOR MORE INFORMATION.

① LOCATIONS AS DIRECTED BY THE ENGINEER.

② EQUATIONS:
 CSJ 0266-02-069
 STA 730+10.56 = STA 730+06.62

* FOR CONTRACTOR'S INFORMATION ONLY
 ** OFFSETS MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
 20' OF CLEARANCE REQUIRED BETWEEN CABLE BARRIER AND MBGF/END TREATMENT LOCATIONS.

NOTES:
 1. CABLE BARRIER LENGTHS MAY NEED TO BE ADJUSTED IN THE FIELD DEPENDING ON ANCHOR SECTION TYPE SELECTED. A 50' TERMINAL SECTION LENGTH WAS USED FOR QUANTITY AND STATION CALCULATIONS.
 2. CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS. FIELD VERIFY BEFORE ALL MATERIALS ARE ORDERED.

TMA SUMMARY

LOCATION	ITEM 6185 TMA(STATIONARY) (DAY)
PROJECT LIMITS	34
CSJ 0266-02-069 TOTALS	34

SUMMARY OF CABLE BARRIER QUANTITIES

NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 4 OF 4

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	12

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

DATE: \$DATES\$
 FILE: \$FILES\$
 \$TIME\$

WORKER SAFETY NOTES:


1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

1. Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).


<p>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov</p>
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12

		<i>Texas Department of Transportation</i>	Traffic Safety Division Standard
<p>BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS</p> <p>BC (1) - 21</p>			
FILE:	bc-21.dgn	DN:	TxDOT
© TxDOT	November 2002	CK:	TxDOT
REVISIONS	CONT	SECT	JOB
4-03 7-13	0114	08	036, ETC
9-07 8-14	DIST	COUNTY	US 290, ETC
5-10 5-21	YKM	FAYETTE, ETC	SHEET NO.
			13


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPICAL LOCATION OF CROSSROAD SIGNS



- # May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
 - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
 - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
 - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
 - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
 - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

T-INTERSECTION



CSJ LIMITS AT T-INTERSECTION

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING^{1,5,6}

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Spacing "x" Feet (Apprx.)
CW20 ⁴	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"	50	400
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12			55	500 ²
			60	600 ²
			65	700 ²
			70	800 ²
			75	900 ²
			80	1000 ²
			*	* ³


* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

△ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS



When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS



NOTES

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
 - CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
 - Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
 - Contractor will install a regulatory speed limit sign at the end of the work zone.

LEGEND

—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC(2)-21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	YKM	FAYETTE, ETC	14	

DATE: \$DATE\$
FILE: \$FILES\$

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
 - Law enforcement.
 - Flagger stationed next to sign.
 - Portable changeable message sign (PCMS).
 - Low-power (drone) radar transmitter.
 - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES\$
FILE: \$FILES\$
\$TIME\$

SHEET 3 OF 12




BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC (3) - 21

FILE:	bc-21.dgn	DW:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0114	08	036, ETC	US 290, ETC				
9-07	8-14	DIST		COUNTY	SHEET NO.				
7-13	5-21	YKM	FAYETTE, ETC		15				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - Long-term stationary - work that occupies a location more than 3 days.
 - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - Short, duration - work that occupies a location up to 1 hour.
 - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

STOP/SLOW PADDLES

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflective when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

Texas Department of Transportation
Traffic Safety Division Standard


BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC (4) - 21

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	OW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	YKM	FAYETTE, ETC	16	



DATE: \$DATES\$
FILE: \$FILES\$

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act." No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




SKID MOUNTED WOOD SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS





GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE WEBSITE LOCATION.

GENERAL NOTES

1. Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
2. No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
3. When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.

- * See BC(4) for definition of "Work Duration."
- ** Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
- See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CR:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0114	08	036, ETC	US 290, ETC				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	YKM	FAYETTE, ETC	17					

DATE: \$DATES\$
FILE: \$FILES\$

\$TIME\$

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE
ROAD CLOSED AT SH XXX
ROAD CLSD AT FM XXXX
RIGHT X LANES CLOSED
CENTER LANE CLOSED
NIGHT LANE CLOSURES
VARIOUS LANES CLOSED
EXIT CLOSED
MALL DRIVEWAY CLOSED
XXXXXXXX BLVD CLOSED

Other Condition List

FRONTAGE ROAD CLOSED
SHOULDER CLOSED XXX FT
RIGHT LN CLOSED XXX FT
RIGHT X LANES OPEN
DAYTIME LANE CLOSURES
I-XX SOUTH EXIT CLOSED
EXIT XXX CLOSED X MILE
RIGHT LN TO BE CLOSED
X LANES CLOSED TUE - FRI
ROADWORK XXX FT
FLAGGER XXXX FT
RIGHT LN NARROWS XXXX FT
MERGING TRAFFIC XXXX FT
LOOSE GRAVEL XXXX FT
DETOUR X MILE
ROADWORK PAST SH XXXX
BUMP XXXX FT
TRAFFIC SIGNAL XXXX FT
ROAD REPAIRS XXXX FT
LANE NARROWS XXXX FT
TWO-WAY TRAFFIC XX MILE
CONST TRAFFIC XXX FT
UNEVEN LANES XXXX FT
ROUGH ROAD XXXX FT
ROADWORK NEXT FRI-SUN
US XXX EXIT X MILES
LANES SHIFT *

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List

MERGE RIGHT
DETOUR NEXT X EXITS
USE EXIT XXX
STAY ON US XXX SOUTH
TRUCKS USE US XXX N
WATCH FOR TRUCKS
EXPECT DELAYS
REDUCE SPEED XXX FT
USE OTHER ROUTES
STAY IN LANE *

Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXX TO XXXXXXX
US XXX TO FM XXXX

Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

** Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

** See Application Guidelines Note 6.

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy Vehicle	HOV	Tuesday	TUES
Highway	Hwy	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT


Roadway designation # IH-number, US-number, SH-number, FM-number

DATE: \$DATES \$TIME\$ FILE: \$FILES

<h3>BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)</h3>			
<h2>BC (6) - 21</h2>			
FILE:	bc-21.dgn	DN:	TxDOT
©TxDOT	November 2002	CR:	TxDOT
REVISIONS	0114	DW:	TxDOT
9-07	8-14	CON:	08
7-13	5-21	SECT:	036, ETC
		JOB:	US 290, ETC
		DIST:	COUNTY
		YKM:	FAYETTE, ETC
		SHEET NO.:	18


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




CONCRETE TRAFFIC BARRIER (CTB)

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES
 LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

LOW PROFILE CONCRETE BARRIER (LPCB)



DELINEATION OF END TREATMENTS

END TREATMENTS FOR CTB'S USED IN WORK ZONES
 End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS

WARNING LIGHTS


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B_{FL} or C_{FL} Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.



Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.




Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

DATE: \$DATE\$ \$TIME\$ FILE: \$FILE\$

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

ATTENTION
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

FLASHING ARROW BOARDS

SHEET 7 OF 12

TRUCK-MOUNTED ATTENUATORS

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR

BC (7) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0114	08	036, ETC	US 290, ETC				
9-07	8-14	DIST	COUNTY		SHEET NO.				
7-13	5-21	YKM	FAYETTE, ETC		19				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES\$
 FILE: \$FILES\$
 \$TIME\$

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectORIZED space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign
(Maximum Sign Dimension)
Chevron CW1-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer



12" x 24" Vertical Panel
mount with diagonals sloping down towards travel way

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (8) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CR:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0114	08	036, ETC	US 290, ETC				
4-03	8-14	DIST	COUNTY		SHEET NO.				
9-07	5-21	YKM	FAYETTE, ETC		20				
7-13									


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



FIXED

(Rigid or self-righting)


DRIVEABLE



PORTABLE


VERTICAL PANELS (VPs)

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




OPPOSING TRAFFIC LANE DIVIDERS (OTLD)

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS



LONGITUDINAL CHANNELIZING DEVICES (LCD)

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

GENERAL NOTES

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths * *			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS ² / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

* * * Taper lengths have been rounded off.
L=Length of Taper (FT.) W=Width of Offset (FT.)
S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	YKM	FAYETTE, ETC	21	


DATE: \$DATES\$
FILE: \$FILES\$
\$TIME\$

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPE 3 BARRICADES

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL



Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.


TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION



PERSPECTIVE VIEW




PLAN VIEW

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.
42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



TRAFFIC CONTROL FOR MATERIAL STOCKPILES



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (10) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	YKM	FAYETTE, ETC	22	

DATE: \$DATES\$ FILE: \$FILES\$

WORK ZONE PAVEMENT MARKINGS

GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:
 YELLOW - (two amber reflective surfaces with yellow body).
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS


BC(11)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS		0114	08	036, ETC
2-98	9-07	5-21		US 290, ETC
1-02	7-13			
11-02	8-14			
	DIST	COUNTY	SHEET NO.	
	YKM	FAYETTE, ETC	23	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES \$TIME\$
FILE: \$FILES

PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TXDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectORIZED pavement markings.






RAISED PAVEMENT MARKERS

TWO-WAY LEFT TURN LANE


STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS



SOLID LINES




BROKEN LINES



REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC(12)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CK: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
1-97 9-07 5-21	DIST	COUNTY	SHEET NO.	
2-98 7-13	YKM	FAYETTE, ETC	24	
11-02 8-14				


Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: \$DATE\$ \$TIME\$ FILE: \$FILE\$

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: \$DATES\$
 FILE: \$FILES\$
 \$TIME\$



TCP (2-6a)
 ONE LANE CLOSURE



TCP (2-6b)
 LANE CLOSURE NEAR EXIT RAMP



TCP (2-6c)
 LANE CLOSURE NEAR ENTRANCE RAMP

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed * X	Formula L = WS ² / 60	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45		450'	495'	540'	45'	90'	320'	195'
50	L = WS	500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

- GENERAL NOTES**
- Flags attached to signs where shown, are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - Channelizing devices used to close lanes may be supplemented with the Chevron Alignment Sign placed on every other channelizing device. Chevrons may be attached to plastic drums as per BC Standards.
 - Channelizing devices used along the work space or along tangent sections may be supplemented with vertical panels (VP) placed on every other channelizing device. If night time conditions make it difficult to see at least two VPs, the VPs may be placed on each channelizing device.
 - The placement of pavement markings may be omitted on intermediate-term stationary work zones with the approval of the Engineer.
 - Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.




**TRAFFIC CONTROL PLAN
 LANE CLOSURES ON
 DIVIDED HIGHWAYS**

TCP (2-6) - 18

FILE: tcp2-6-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 2-12	YKM	FAYETTE, ETC	25	
1-97 2-18				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATE\$
 FILE: \$FILES\$
 \$TIME\$



TCP (5-1a)

WORK AREA ON SHOULDER



TCP (5-1b)

WORK AREA ON SHOULDER

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	
30	L = WS ² / 60	150'	165'	180'	30'	60'	90'
35		205'	225'	245'	35'	70'	120'
40		265'	295'	320'	40'	80'	155'
45	L = WS	450'	495'	540'	45'	90'	195'
50		500'	550'	600'	50'	100'	240'
55		550'	605'	660'	55'	110'	295'
60		600'	660'	720'	60'	120'	350'
65		650'	715'	780'	65'	130'	410'
70		700'	770'	840'	70'	140'	475'
75		750'	825'	900'	75'	150'	540'
80		800'	880'	960'	80'	160'	615'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	TCP (5-1a)	TCP (5-1b)	TCP (5-1b)	

GENERAL NOTES

1. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the performance or quality of the work. Type 3 barricades or drums may be substituted when workers on foot are no longer present when approved by the Engineer.
2. 28" tall or taller one-piece cones will be allowed only for Short Duration or Short Term stationary operations when workers are present to maintain the devices upright and in proper location. Intermediate Term stationary work areas should use Drums, Vertical Panels or 42" tall two-piece cones.



**TRAFFIC CONTROL PLAN
 SHOULDER WORK FOR
 FREEWAYS / EXPRESSWAYS**

TCP (5-1) - 18


FILE: tcp5-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT February 2012	CONT	SECT	JOB	HIGHWAY
2-18	REVISIONS	0114	08	036, ETC US 290, ETC
	DIST	COUNTY		SHEET NO.
	YKM	FAYETTE, ETC		26

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: \$DATE\$
 FILE: \$FILE\$
 \$TIME\$

Warning sign and rumble strip sequence in opposite direction is same as below.

Flagger to Flagger (Length of Work Area)	ADT	# of Rumble Strip Arrays
1/8 Mile	< 4,500	1
	≥ 4,500	2
1/4 Mile	< 3,500	1
	≥ 3,500	2
1/2 Mile	< 2,600	1
	≥ 2,600	2
1 Mile	< 1,600	1
	≥ 1,600	2
> 1 Mile	N/A	2



RUMBLE STRIPS ON ONE-LANE TWO-WAY APPLICATION



RUMBLE STRIPS FOR LANE CLOSURE ON CONVENTIONAL ROADWAY

GENERAL NOTES

- Each Rumble Strip Array should consist of three rumble strips spaced center to center at the spacing shown in Table 2, placed transverse across the lane at locations shown.
- The CW17-2T "RUMBLE STRIPS AHEAD" sign should be located after the CW20-1D "ROAD WORK AHEAD" sign and spaced as shown. If traffic is observed to be queuing, or is expected to queue beyond the Rumble Strips, the CW17-2T sign and the first Rumble Strip Array may be located upstream of the CW20-1D sign as necessary to provide needed warning.
- Temporary Rumble Strips will be considered subsidiary to Item 502, and shall be a product listed on the Compliant Work Zone Traffic Control Devices.
- Remove Temporary Rumble Strips before removing the advanced warning signs.
- Temporary Rumble Strips should not be used on horizontal curves, loose gravel, soft or bleeding asphalt, heavily rutted pavements or unpaved surfaces.
- Temporary Rumble Strips shall be installed and maintained as per manufacturer's recommendations.
- This standard sheet shall be used in conjunction with other appropriate TCP standard, TMUTCD typical application or project specific detail for the project.
- The one-lane two-way application may utilize a flagger, an Automated Flagger Assistance Device (AFAD) or a Portable Traffic Signal (PTS).
- Replace defective Temporary Rumble Strips as directed by the Engineer.
- Temporary Rumble Strips may be used on freeways or expressways based on engineering judgment and written direction from the Engineer.

Speed	Approximate distance between strips in an array
≤ 40 MPH	10'
> 40 MPH & ≤ 55 MPH	15'
= 60 MPH	20'
≥ 65 MPH	* 35' +

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Panel		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT)
 S=Posted Speed (MPH)

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

◆ Signs are for illustrative purposes only. Signs required may vary depending on the TCP, TMUTCD Typical Application, or project specific details for the project.
 * For posted speeds in excess of 65 MPH, it is recommended that spacing is increased as speed limits increase. Increasing space between rumble strips will improve effectiveness.


Texas Department of Transportation
 Traffic Safety Division Standard

TEMPORARY RUMBLE STRIPS


WZ (RS) - 22

FILE: wzrs22.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2012	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
2-14 1-22	DIST	COUNTY	SHEET NO.	
4-16	YKM	FAYETTE, ETC	27	

PATH: T:\YKMAN\XIP5&E\011408036_ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290_LAYOUT\USE1
 FILE: US290_LAYOUT.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	28

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SHT1_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-3.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023


CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	29

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SHT1_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-6.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	30

PATH: T:\YKMAN\EX\IP5&E\011408036_ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\1AYOUT\TUSEI
 FILE: US290_LAYOUT-9.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION ALL RIGHTS RESERVED SHEET 4 OF 12

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT. 0114	SECT. 08	JOB 036,ETC	HIGHWAY NO. US 290,ETC
STATE TEXAS	DIST. YKM	COUNTY FAYETTE,ETC	SHEET NO. 31

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SHT1_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-12.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0114-08-036)




NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 5 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	32

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-15.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	33

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-18.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0114-08-036)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 7 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	34

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SHT1_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-21.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0114-08-036)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 8 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	35

PATH: T:\YKMAN\EX\PS&E\011408036_ETC_US290_SHT71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-24.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023


CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	36

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUPS\YK\MAN\X\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOU\USE1
 FILE: US290_LAYOUT-27.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023


CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	37

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOU\USE1
 FILE: US290_LAYOUT-30.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE




Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 11 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	38

STA 484+68.58 TO STA 484+90.33
 CENTERLINE STRUCTURE

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SHT1_CABLEBARRIER\PREVIOUS BEFORE COMBINING\011408036_US290\LAYOUT\USE1
 FILE: US290_LAYOUT-33.dgn
 DATE: \$DATE\$



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0114-08-036)

NOT TO SCALE




Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 12 OF 12


NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	39

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-100.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 1 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	40

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-103.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	41

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-106.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 3 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	42

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-109.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	43

PATH: T:\YKMAN\XIP5&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE1
 FILE: BL CL1 - SH710266-01-112.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 5 OF 17

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT. 0114	SECT. 08	JOB 036,ETC	HIGHWAY NO. US 290,ETC
STATE TEXAS	DIST. YKM	COUNTY FAYETTE,ETC	SHEET NO. 44

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE1
 FILE: BL CL1 - SH710266-01-115.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)




NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 6 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	45

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-118.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 7 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	46

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-121.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023


CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 8 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	47

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE1
 FILE: BL CL1 - SH710266-01-124.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023





CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 9 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	48

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE1
 FILE: BL CL1 - SH710266-01-127.dgn
 DATE: \$DATE\$



Amanda Anderle Fling, P.E.

04/26/2023


CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	49

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-130.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO. 6		PROJECT NO.	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	50

SHEET 11 OF 17

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-133.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 12 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	51

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-136.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 13 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	52

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-139.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)


NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 14 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	53

PATH: T:\YKMAN\EX\IP5&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE1
 FILE: BL CL1 - SH710266-01-142.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)




NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 15 OF 17

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	54

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE
 FILE: BL CL1 - SH710266-01-145.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	55

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\026601088CBL_USE1
 FILE: BL CL1 - SH710266-01-148.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-01-088)


NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 17 OF 17

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	56

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTRYLINE\LAYOUI
 FILE: BL CL - SH 71_2.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-02-069)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 1 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	57

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINELAYOUT
 FILE: BL CL - SH 71_5.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	58

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNVTLINE\LAYOUI
 FILE: BL CL - SH 71_8.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023


CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	59

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNVTLINE\LAYOUT
 FILE: BL CL - SH 71_11.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-02-069)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 4 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	60

PATH: T:\YKMAN\XIP5&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINELAYOUT
 FILE: BL CL - SH 71_14.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 5 OF 11

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT. 0114	SECT. 08	JOB 036,ETC	HIGHWAY NO. US 290,ETC
STATE TEXAS	DIST. YKM	COUNTY FAYETTE,ETC	SHEET NO. 61

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINELAYOUT
 FILE: BL CL - SH 71_17.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-02-069)


NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 6 OF 11

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT. 0114	SECT. 08	JOB 036,ETC	HIGHWAY NO. US 290,ETC
STATE TEXAS	DIST. YKM	COUNTY FAYETTE,ETC	SHEET NO. 62

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNVTLINE\LAYOUI
 FILE: BL CL - SH 71_20.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED
 SHEET 7 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	63

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\LAYOUI
 FILE: BL CL - SH 71_23.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 8 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	64

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNVTLINE\LAYOUI
 FILE: BL CL - SH 71_26.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023




CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED SHEET 9 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	65

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINELAYOUT
 FILE: BL CL - SH 71_29.dgn
 DATE: \$DATE\$



NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-02-069)




NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 10 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	66

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNVTYLINELAYOUT
 FILE: BL CL - SH 71_32.dgn
 DATE: \$DATE\$



Amanda Anderle Fling, P.E.

04/26/2023

CABLE BARRIER LAYOUT (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 11 OF 11

NOTE: CABLE BARRIER STATION LIMITS ARE APPROXIMATE AND MAY VARY TO MEET FIELD CONDITIONS.


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	67

CABLE BARRIER RECOMMENDED POST SPACING	
RADIUS (FT)	POST SPACING
650-2500	6' -8"
2501-5500	10'
>5500	AS SHOWN ON DETAILS




* SEE "SUMMARY OF CABLE BARRIER QUANTITIES" FOR OFFSET DISTANCE.

TYPICAL CABLE BARRIER TERMINATION AT CROSSOVERS



CONCRETE RIPRAP PLACEMENT AT OVERHEAD SIGN POSTS



TYPICAL CABLE BARRIER TERMINATION AT BRIDGE ENDS

NOTES:

1. PLACE PROPOSED 4" REINFORCED CONCRETE RIPRAP BETWEEN PROPOSED MOW STRIP & EXIST VEHICLE IMPACT ATTENUATOR FOUNDATIONS, SIGN POST AS SHOWN.
2. PLACE 1/2" PREMOLDED EXPANSION JOINT MATERIAL BETWEEN PROPOSED RIPRAP AND EXIST CONCRETE.
3. SEE "SUMMARY OF CABLE BARRIER QUANTITIES" FOR QUANTITY OF CONCRETE RIPRAP.
4. SURFACE OF PROPOSED CONCRETE RIPRAP SHALL MATCH EXISTING GRADES TO ENSURE POSITIVE DRAINAGE AFTER INSTALLATION.
5. CROSS DRAINAGE STRUCTURES WITH LESS THAN 36 INCHES OF COVER COULD POSE A CONFLICT FOR CABLE BARRIER POST PLACEMENT. ANY UNRESOLVED CONFLICTS SHOULD BE REFERRED BACK TO SUPPLIERS AND APPROVED BY THE ENGINEER. THIS WORK WILL BE CONSIDERED SUBSIDIARY TO ITEM 543.
6. PROVIDE DELINEATORS COMPRISED OF RUBBER COMPOSITE WITH 80% BY VOLUME POST CONSUMER RECYCLED HDPE AND A BRIGHT WHITE PREMIUM U.V. INHIBITED, CO-EXTRUDED HDPT SHELL. THIS WORK WILL BE CONSIDERED SUBSIDIARY TO ITEM 543.



Amanda Anderle Fling, P.E.

04/26/2023

MISCELLANEOUS DETAILS


NOT TO SCALE

Texas Department of Transportation
© 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
ALL RIGHTS RESERVED

SHEET 1 OF 2


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	68

PATH: T:\YKMAN\EXIPS&E\011408036.ETC_US290_SHT1_CABLEBARRIER\011408036_US290\DCGN
 FILE: MISCELLANEOUS DETAILS.dgn
 DATE: \$DATE\$




**TYPICAL RIPRAP DETAIL
 AT MEDIAN DRAINS**

* SEE "SUMMARY OF CABLE BARRIER QUANTITIES"
 FOR OFFSET DISTANCE.



**TYPICAL PLACEMENT DETAIL
 WITHIN V-DITCH**



HALFWAY BETWEEN EACH POST, GROOVE A TRANSVERSE JOINT 0.5" DEEP. IF FOUNDATIONS AND RIPRAP ARE NOT CAST AT THE SAME TIME, ALIGN EXPANSION JOINT MATERIAL AND GROOVE JOINTS WITH EACH POST.

4" REINF CONC RIPRAP (MOW STRIP)
 (FIBER REINF WILL BE ALLOWED AS APPROVED)

MOW STRIP DETAIL



Amanda Anderle Fling, P.E.

04/26/2023

**MISCELLANEOUS
 DETAILS**

NOT TO SCALE



Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 2 OF 2

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	69

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES\$
FILE: \$FILES\$



ROPE TENSION TABLE		
ROPE TEMP (°F)	TENSION (LBS)	TENSION (kN)
0	5700	25.4
5	5550	24.7
10	5400	24.0
15	5250	23.4
20	5100	22.7
25	4950	22.0
30	4800	21.4
35	4650	20.74
40	4500	20.0
45	4350	19.3
50	4200	18.7
55	4050	18.0
60	3900	17.3
65	3750	16.7
70	3600	16.0
75	3450	15.3
80	3300	14.7
85	3150	14.0
90	3000	13.3
95	2850	12.7
100	2700	12.0
105	2550	11.3
110	2400	10.7
115	2250	10.0
120	2100	9.3
125	1950	8.7
130	1800	8.0
135	1650	7.3
140	1500	6.7

GENERAL NOTES:

- BRIFEN DRAWINGS, SPECIFICATIONS, AND PRODUCT MANUAL SHOULD BE REVIEWED PRIOR TO STARTING AN INSTALLATION. FOR ADDITIONAL INFORMATION OR QUESTIONS, CONTACT BRIFEN USA, INC. AT 1-866-427-4336.
- THE BRIFEN WRSF HAS BEEN SUCCESSFULLY TESTED TO NCHRP 350 TL-4 CONDITIONS ON SLOPES 6:1 OR FLATTER AND NCHRP 350 TL-3 CONDITIONS ON SLOPES 4:1 TO 6:1.
- THE POST SPACING SHALL BE DETERMINED BY THE SPECIFYING AGENCY. POST SPACING MAY BE DECREASED TO AVOID OBSTRUCTIONS OR UTILITIES. IN NO EVENT SHALL THE POST SPACING EXCEED 21'-0".
- BRIFEN WRSF SHALL BE PLACED ON A SMOOTH SURFACE, WITHOUT HUMPS, DROP-OFFS, HOLES, ETC THAT WOULD INTERFERE WITH THE STABILITY OF THE ERRANT VEHICLE. GRADING, FILL AND COMPACT MAY BE REQUIRED TO ASSURE THAT ROPES ARE INSTALLED AT THE DESIGN HEIGHT.
- THE WRGT-FL END ANCHOR HAS BEEN SUCCESSFULLY TESTED TO NCHRP 350 TL-3 CONDITIONS. THE LENGTH OF NEED BEGINS 31'-0" FROM THE END ANCHOR. POSTS A THROUGH POST B3, SPACED 6'-6" APART, HAVE WEAKENED CUTS AT THE GROUND THAT SHALL FACE THE ANCHOR.
- ANCHOR AND LINE POST DIMENSIONS AND STEEL REINFORCEMENT WILL BE DETERMINED ON PROJECT SPECIFIC SOIL CLASSIFICATION, PROPERTIES AND TEMPERATURE EXTREMES. CONTACT BRIFEN USA, INC. FOR ADDITIONAL INFORMATION.
- ALL REINFORCEMENT AND CONCRETE FOR THE ANCHORS AND LINE POSTS PROVIDED BY OTHERS.
- REINFORCEMENT AND CONCRETE PROPERTIES SHALL MEET AGENCY SPECIFICATIONS.
- FOR PLACEMENT NEAR GUARDRAIL OR OTHER OBSTACLES CONTACT BRIFEN USA, INC. FOR ADDITIONAL DRAWINGS AND SUPPORT.
- TAPER RATES FOR THE BRIFEN WRSF ARE AS FOLLOWS:
HORIZONTAL: 25:1 MAXIMUM, 50:1 PREFERABLE
VERTICAL: 25:1 MAXIMUM, 50:1 PREFERABLE

* ROPE TENSION: ± 20% AFTER 2-WEEK INTERVAL

SHEET 1 OF 3



**BRIFEN
WIRE ROPE SAFETY FENCE
(TL-4)**


BRIFEN (TL4) - 14

FILE: brifent1414.dgn	DN: TxDOT	CK: RM	DW: VP	CK:
© TxDOT: MARCH 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
	DIST	COUNTY	SHEET NO.	
	YKM	FAYETTE, ETC	70	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES
 FILE: \$FILES

LINE POST ASSEMBLY [Z11]



ELEVATION




PLAN

NOTES SPECIFIC TO LINE POST ASSEMBLY

1. ROPE HEIGHTS SHALL BE $\pm 1"$ TO GROUND LINE.
2. POST SHALL BE $\pm 4"$ FROM VERTICAL PLUMB.
3. POST CAPS SHALL BE USED IF SPECIFIED.
4. REFLECTORS SHALL BE SPACED ACCORDING TO AGENCY SPECIFICATIONS.
5. REFLECTORS CAN BE PLACED ON THE POST CAP OR POST.


ROPE CONNECTION DETAIL




NOTES SPECIFIC TO ROPE CONNECTION DETAIL

1. THE WIRE ROPE TERMINALS SHALL BE THREADED A MINIMUM OF 1-1/2" INTO RIGGING SCREW.
2. AFTER FINAL TENSIONING, THE TERMINALS SHALL BE VISIBLE IN THE INSPECTION HOLES.

SOCKET ASSEMBLY



ELEVATION




PLAN

NOTES SPECIFIC TO CONCRETE FOOTING

1. SIZE OF FOOTING WILL BE DETERMINED BY SOIL CONDITIONS, FOUNDATION TYPE AND PROJECT CONDITIONS.
2. CONCRETE BASED ON AGENCY SPECIFICATIONS.
3. CONCRETE BY OTHERS.
4. REINFORCING RING (BY OTHERS) WILL BE USED ACCORDING TO FOUNDATION SIZE AND TYPE. THE REINFORCING RING MAY BE OMITTED IF THE FOOTING IS PLACED IN A CONTINUOUS CONCRETE MOW STRIP.
5. FOOTING SHALL BE FLUSH WITH THE GROUND LINE, TO A MAXIMUM OF 1 INCH BELOW OR ABOVE GROUND LINE.
6. SOCKET SHALL BE $\pm 2^\circ$ OF VERTICAL PLUMB.

DRIVE SOCKET [Z44]



ELEVATION

SIDE

PLAN

NOTES SPECIFIC TO DRIVE SOCKETS

1. SIZE OF SOIL PLATE WILL BE DETERMINED BY SOIL CONDITIONS AND PROJECT CONDITIONS.
2. THE SOIL PLATE SHALL BE PARALLEL TO ROADWAY AND CAN FACE TOWARD OR AWAY FROM THE TRAVEL LANE.
3. FOOTING SHALL BE FLUSH WITH THE GROUND LINE, TO A MAXIMUM OF 1 INCH BELOW OR ABOVE GROUND LINE.
4. SOCKET SHALL BE $\pm 2^\circ$ OF VERTICAL PLUMB.
5. SOCKETS SHALL BE DRIVEN IN A MANNER TO NOT DISTORT OR DESTROY THE TOP OF SOCKET TO A DEGREE THAT PLACES THE SOCKET OR LINE POST OUT OF CONSTRUCTION TOLERANCES.

GENERAL NOTES:

1. BRIFEN DRAWINGS, SPECIFICATIONS, AND PRODUCT MANUAL SHOULD BE REVIEWED PRIOR TO STARTING AN INSTALLATION. FOR ADDITIONAL INFORMATION OR QUESTIONS, CONTACT BRIFEN USA, INC. 1-866-427-4336.
2. THE BRIFEN WRSF HAS BEEN SUCCESSFULLY TESTED TO NCHRP 350 TL-4 CONDITIONS ON SLOPES 6:1 OR FLATTER AND NCHRP 350 TL-3 CONDITIONS ON SLOPES 4:1 TO 6:1.
3. THE POST SPACING SHALL BE DETERMINED BY THE SPECIFYING AGENCY. POST SPACING MAY BE DECREASED TO AVOID OBSTRUCTIONS OR UTILITIES. IN NO EVENT SHALL THE POST SPACING EXCEED 21'-0".
4. BRIFEN WRSF SHALL BE PLACED ON A SMOOTH SURFACE, WITHOUT HUMPS, DROP-OFFS, HOLES, ETC THAT WOULD INTERFERE WITH THE STABILITY OF THE ERRANT VEHICLE. GRADING, FILL AND COMPACTION MAY BE REQUIRED TO ASSURE THAT ROPES ARE INSTALLED AT THE DESIGN HEIGHT.

SHEET 2 OF 3



BRIFEN
WIRE ROPE SAFETY FENCE
(TL-4)

BRIFEN(TL4) - 14

FILE: brifent1414.dgn	DN: TxDOT	CK: RM	DW: VP	CK:
© TxDOT: MARCH 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
	DIST	COUNTY	SHEET NO.	
	YKM	FAYETTE, ETC	71	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES\$
FILE: \$FILES\$

WRGT-FL END ANCHOR LAYOUT

GENERAL NOTES:




- BRIFEN DRAWINGS, SPECIFICATIONS, AND PRODUCT MANUAL SHOULD BE REVIEWED PRIOR TO STARTING AN INSTALLATION. FOR ADDITIONAL INFORMATION OR QUESTIONS, CONTACT BRIFEN USA, INC. AT 1-866-427-4336.
- THE WRGT-FL END ANCHOR HAS BEEN SUCCESSFULLY TESTED TO NCHRP 350 TL-3 CONDITIONS. THE LENGTH OF NEED BEGINS 31'-0" FROM THE END ANCHOR. POSTS A THROUGH POST B3, SPACED 6'-6" APART, HAVE WEAKENED CUTS AT THE GROUND THAT SHALL FACE THE ANCHOR.
- ANCHOR AND LINE POST DIMENSIONS AND STEEL REINFORCEMENT WILL BE DETERMINED ON PROJECT SPECIFIC SOIL CLASSIFICATION, PROPERTIES AND TEMPERATURE EXTREMES. CONTACT BRIFEN USA, INC. FOR ADDITIONAL INFORMATION.
- ALL REINFORCEMENT AND CONCRETE FOR THE ANCHORS AND LINE POSTS PROVIDED BY OTHERS.
- REINFORCEMENT AND CONCRETE PROPERTIES SHALL MEET AGENCY SPECIFICATIONS.
- FOR PLACEMENT NEAR GUARDRAIL OR OTHER OBSTACLES CONTACT BRIFEN USA, INC. FOR ADDITIONAL DRAWINGS AND SUPPORT.



WRGT-FL POST DETAILS

END ANCHOR DETAILS

END ANCHOR COMPONENTS



NOTES SPECIFIC TO WRGT-FL POST DETAIL

NOTES SPECIFIC TO END ANCHOR DETAIL

- ROPE HEIGHTS SHALL BE $\pm 1"$ TO GROUND LINE.
- POST SHALL BE $\pm 4"$ FROM VERTICAL PLUMB.
- POST CAPS SHALL BE USED IF SPECIFIED.
- REFLECTORS SHALL BE SPACED ACCORDING TO AGENCY SPECIFICATIONS.
- REFLECTORS CAN BE PLACED ON THE POST CAP OR POST.
- Z EXCLUDER (Z41) SHALL BE USED.
- POST A & SOCKET SHALL BE PLACED $79^\circ (\pm 4^\circ)$ TOWARD END ANCHOR FROM THE HORIZONTAL PLANE.
- POST A SOCKET SHALL BE PLACED IN 14" (MIN) CONCRETE FOUNDATION. DEPTH TO BE DETERMINED FROM SOIL CONDITIONS AND PROJECT CONDITIONS.
- FOUNDATIONS FOR POST 2 THRU 4 SHALL BE THE SAME AS THE LINE POST ASSEMBLY'S FOR THE PROJECT.
- WEAKENED CUTS SHALL FACE END ANCHOR.

- THE END ANCHOR ASSEMBLY SHALL BE PLACED 12' (+3', -1') BELOW HORIZONTAL PLANE.
- POST 1 & SOCKET SHALL BE PLACED $79^\circ (\pm 4^\circ)$ TOWARD END ANCHOR FROM THE HORIZONTAL PLANE.
- POST 1 SOCKET SHALL BE PLACED IN 14" (MIN) CONCRETE FOUNDATION. DEPTH TO BE DETERMINED FROM SOIL CONDITIONS AND PROJECT CONDITIONS.

SHEET 3 OF 3



BRIFEN
WIRE ROPE SAFETY FENCE
(TL-4)


BRIFEN(TL4) - 14

FILE: brifentl414.dgn	DN: TxDOT	CK: RM	DW: VP	CK:
© TxDOT: MARCH 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
	DIST	COUNTY	SHEET NO.	
	YKM	FAYETTE, ETC	72	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

Preferred Installation: Locate post #2 away from nearest traffic. System has been successfully tested with opposite installation.





Length-of-Need Cass Cable Terminal (CCT):
Departure Installation: Length-of-Need: 44'-9" (At Post #8)
Approach Installation: Length-of-Need: 19'-9" (12" Post Post #4)




PLAN VIEW



ELEVATION VIEW (TYPICAL LAY-OUT)



CONCRETE FOOTING (IN QUALIFYING MOW STRIP SEE CHART)



- GENERAL NOTES**
- This drawing is a general overview of CASS TL-4 Barrier System. See SS-740 (latest version) for specific details of CASS cable terminal (CCT) and cable safety system (CASS) requirements, proper installation, options and specification.
 - CASS is designed for bi-directional traffic flows and can be installed on either side of the median. Contact Trinity (800-527-6050) or consult the design, installation, or repair manual(s) for additional information.
 - All concrete for CASS footings shall be TxDOT class A. If class A or stronger concrete is utilized for the mowstrip, please see chart below for allowable footing depth and sleeve deviations.
 - All posts shall be socketed unless otherwise specified. All cables shall be pre-stretched unless otherwise specified.
 - For payment see Special Specification "Cable Barrier System".
 - CASS-TL4 shall be installed on shoulders or medians with slopes of 6:1 or flatter without obstructions, depressions, etc. That may significantly affect the stability of an errant vehicle. Grading of site and/or appropriate fill materials may be required. The designer/installer shall "Flatten" or "Round" various topographical inconsistencies that could interfere with the ability of the installer to consistently maintain the design height (in relation to the terrain) of the cables. Please consult manual(s) and / or TxDOT Memo(s) for installations in "Ditch Sections".
 - CASS TL-4 post spacing may be modified to avoid obstacles that conflict with the installation of cass-tl4 line posts or to reduce deflection on radiuses. No post space can exceed the maximum post TxDOT space limit of 20'. Reducing or increasing post spacing affects deflection. CASS TL-4 may be laterally transferred at a rate not to exceed 30:1.
 - Post foundations may be drilled through existing pavement. Please see line post foundation chart for minimum footing requirements in various applications.
 - For aesthetic purposes Trinity recommends all sleeves, driven posts, and lower cable release posts to be installed reasonably plumb (approximately 1/8" per foot).
 - CASS TL-4 shall be installed in well-drained, compacted, NCHRP Report 350 Standard soil. If soil does not meet this classification, if solid rock/concrete is encountered below grade or if soil is susceptible to severe freeze/thaw cycles, please contact Trinity about alternate footing design(s). Trinity suggests the use of "Mow strips" for erosion prevention and ease of maintenance / installation.
 - See the Texas MUTCD for proper "Barrier" Delineation.

MOW STRIP DETAIL*			CONCRETE FOOTING CHART		
MOW STRIP	DEPTH	WIDTH	FOOTING	TUBE SLEEVE	REBAR RING
NONE			30" Min.	27" Min.	YES
HMA	6" Min.	3' Min.	27" Min.	15" Min.	NO
HMA	8" Min.	3' Min.	24" Min.	15" Min.	NO
RC	3" Min.	3' Min.	24" Min.	15" Min.	NO

Chart does not apply to Terminal Posts 1 thru 9.
 * Mow strip or pavement.
 HMA = Hot Mix Asphalt (Not Recycled Asphalt Pavement).
 RC = Reinforced Concrete (TxDOT Class A Minimum).

Trinity Highway Products, LLC.
 2525 Stemmons Freeway
 Dallas, TX 75207
 Phone: (800) 644-7976
 Product: INFO@TRIN.NET

CABLE TENSION CHART

FAHRENHEIT DEGREES	PRE-STRETCHED LB / FORCE
-10	7300
0	7000
10	6600
20	6300
30	6000
40	5600
50	5300
60	5000
70	4600
80	4300
90	4000
100	3600
110	3300
120	3000
130	2700
140	2500
150	2300

Allowable deviation from chart in tangent sections: +800, -200 pounds/force. Cable tension readings are typically higher in curved cable sections.


Design Division Standard

TRINITY CABLE SAFETY SYSTEM (TL-4)
CASS (TL4) - 14

FILE: casst1414.dgn	DN: TxDOT	CK: RM	DW: VP	CK:
©TxDOT: March 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
	DIST	COUNTY	SHEET NO.	
	YKM	FAYETTE, ETC	73	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATES
FILE: \$FILES



- ### GENERAL NOTES
- For additional information contact Gibraltar, Inc. at 1-800-495-8957, 830-798-5444, or see the manufacturer's product manual.
 - All concrete shall be CLASS A.
 - The Cable Barrier System shall be installed on shoulders or on medians with slopes of 6:1 or flatter. If installed on slopes steeper than 6:1 up to 4:1 the TL-4 system performs as a TL-3 and Gibraltar must be contacted for various guidelines related to placement.
 - The Cable Barrier System is accepted by the FHWA Test Level - 4.
 - See the Texas MUTCD for proper "Barrier" delineation.
 - Rock Clause: Where solid rock is encountered:
 - For socketed post, continue digging 12" diameter, 15" deep into rock or the required plan depth, whichever comes first.
 - For driven post, core drill a 4" diameter hole 18" deep into rock or the required plan depth, whichever comes first.
 - For Anchor post, continue digging 24" diameter, 30" deep into rock or the required plan depth, whichever comes first.
 - Tolerances:
 - * LP = 3" out of plumb, at top
 - * Cable height = 1"
 - * Anchor Post = 5" off of Cable Reference Line
 - The Gibraltar cable barrier system shall be installed in NCHRP Report 350 standard compacted soil. Soil must be well drained.
 - All non-welded rebar by others.
 - Minimum recommended line post foundation.
 - Without mowstrip, 36" Deep x 12" diameter foundations with #3 rebar ring x 8" diameter with two #4 rebar vertical bars 30" long
 - With 4" minimum depth hot mix asphalt, 30" deep x 12" diameter foundations with #3 rebar ring x 8" diameter with two #4 rebar vertical bars 30" long.
 - With 3" minimum depth concrete mowstrip, 24" deep x 12" diameter foundations. (No rebar required)
 - Direct drive post 42" deep.

Temperature (°F)	Tension
-10 °F	8000
0 °F	7600
10 °F	7200
20 °F	6800
30 °F	6400
40 °F	6000
50 °F	5600
60 °F	5200
70 °F	4800
80 °F	4400
90 °F	4000
100 °F	3600
110 °F	3200

Deflection	Post Spacing
8'-0"	20 FT
7'-0"	12 FT
6'-8"	10 FT

* Allowable Deviation from Chart +/- 10%


Texas Department of Transportation Design Division Standard

GIBRALTAR CABLE BARRIER SYSTEM (TL-4)


GBRLTR(TL4) - 14

FILE: gbrltr1414.dgn	DN: TxDOT	CK: RM	DW: VP	CK:
©TxDOT: March 2014	CONT: 0114	SECT: 08	JOB: 036, ETC	HIGHWAY: US 290, ETC
REVISIONS		DIST: YKM	COUNTY: FAYETTE, ETC	SHEET NO.: 74

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



STAGGER PLACEMENT OF TURNBUCKLES LINE TO LINE BETWEEN POSTS.
 NOTE: TURNBUCKLES MAY BE SWAGED OR WEDGE FITTINGS.



GENERAL NOTES

- FOR ADDITIONAL INFORMATION CONTACT YOUR DISTRIBUTOR OR NUCOR STEEL MARION, INC. AT (740) 383-4011.
- FOR PAYMENT SEE SPECIAL SPECIFICATION "CABLE BARRIER SYSTEM".
- FOR ADDITIONAL INFORMATION SEE THE MANUFACTURER'S PRODUCT MANUAL.
- THE NU-CABLE SYSTEM IS DESIGNED FOR BI-DIRECTIONAL TRAFFIC FLOWS. SEE THE MANUFACTURER'S PRODUCT MANUAL FOR PLACEMENT ADJACENT TO GUARDRAIL END TREATMENTS.
- THE NU-CABLE SYSTEM SHALL BE INSTALLED ON MEDIANS WITH SLOPES OF 6:1 OR FLATTER WITHOUT OBSTRUCTIONS, DEPRESSIONS, ETC; THAT MAY SIGNIFICANTLY AFFECT THE STABILITY OF AN ERRANT VEHICLE.
- THE NU-CABLE SYSTEM MAY BE INSTALLED ON EITHER SIDE OF THE ROADWAY. Rib-Bak™ CABLE LINE POSTS MAY BE SOCKETED OR DRIVEN DESIGN.
- THE TL-4 FOR 6:1 SLOPES CAN USE 4# / LF POST. SEE TABLE #1 FOR POST SIZE PER SPACING.
- SEE (TABLE 2) FOR TENSION AMOUNT AT SPECIFIC CABLE TEMPERATURE FOR INITIAL INSTALLATION.
- SEE (TABLE 3) FOR TENSION AMOUNT AT SPECIFIC CABLE TEMPERATURE FOR MAINTENANCE.
- FOURTH (LOWEST) CABLE IS NOT OPTIONAL ON THE TL-4 SYSTEM.
- CONSULT YOUR PROJECT PLAN SHEETS AND CABLE BARRIER SPECIFICATIONS FOR DESIRED SOCKET MATERIAL.
- ALL FOUNDATION DESIGNS ARE BASED ON NCHRP 350 STRONG (S1) SOIL. CONSULT THE MANUFACTURER FOR SPECIFIC FOUNDATION DESIGN IF SOIL TYPES DIFFER.

7 TABLE 1

POST SIZE TABLE	
POST SPACING	POST SIZE
0' - 17'-6"	4# / LF X 4' OR 6' POST
17'-6" - 20'	5# / LF X 4' POST

POST SPACING IS PER 8 FOOT DEFLECTION REQUIREMENTS. CONSULT PRODUCT MANUAL IF GREATER DEFLECTION IS PERMISSIBLE.

8 TABLE 2






CABLE TENSION CHART	
INITIAL INSTALL	
F	LBF
120	4624
110	4986
100	5350
90	5713
80	6077
70	6440
60	7167
50	7894
40	8619
30	9346
20	10073
10	10800
0	11525
-10	12252
-20	12979
-30	13706

9 TABLE 3

CABLE TENSION CHART	
MAINTENANCE	
F	LBF
120	4021
110	4336
100	4652
90	4968
80	5284
70	5600
60	6232
50	6864
40	7495
30	8127
20	8759
10	9391
0	10022
-10	10654
-20	11286
-30	11918

LENGTH OF NEED POSTS
MEDIAN CONFIGURATION

INSTALLATION DETAIL
4 CABLE 6:1



SHEET 1 OF 2


Design Division Standard
NU-CABLE BARRIER SYSTEM (TL-4) (4 CABLE)
NU-CABLE (TL4) - 14

FILE:	DN:	CK:	DW:	CK:
© TxDOT:	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
	DIST	COUNTY	SHEET NO.	
	YKM	FAYETTE, ETC	75	


DATE: \$DATE\$
 FILE: \$FILES\$

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: \$DATE\$
FILE: \$FILES\$



SECTION B-B
(CABLE RELEASE POST)



DETAIL A - CRP IN CONCRETE FOOTING
(3000 PSI MIN CONCRETE)







TABLE 4

CRP END TERMINAL CABLE HEIGHTS - TL-4						
	LP 1	LP 2	LP 3	LP 4	LP 5	LP 6
TOP CABLE	34"	34"	34"	34"	34"	34"
UPPER-MIDDLE CABLE	27"	27"	27"	27"	28"	31"
BOTTOM-MIDDLE CABLE	24"	24"	24"	24"	24"	24"
BOTTOM CABLE	15"	15"	15"	15"	15"	15"



① THE OPPOSING END TREATMENTS ON A PARTICULAR RUN ARE MIRRORED IN THEIR LAYOUT.



NU-TEN END TERMINAL SYSTEM

NOTES

1. THE OPPOSING END TREATMENTS ON A PARTICULAR RUN ARE MIRRORED IN THEIR LAYOUT. SYSTEM PAYMENT IS PER EACH (EA). REFER TO PROJECT SPECIFICATIONS FOR ADDITIONAL PAYMENT INFORMATION
2. REFER TO INSTALLATION MANUAL FOR CABLE END ASSEMBLY DETAIL.
3. ALL FOUNDATION DESIGNS ARE BASED ON NCHRP 350 STRONG (S1) SOIL. CONSULT THE MANUFACTURER FOR SPECIFIC FOUNDATION DESIGNS IF SOIL TYPES DIFFER.
4. SEE TABLE 4 CABLE HEIGHTS IN CRP TRANSITION SECTION.

SHEET 2 OF 2



NU-CABLE BARRIER SYSTEM (TL-4) (4 CABLE)

NU-CABLE (TL4) - 14

FILE:	DN:	CK:	DW:	CK:
© TxDOT:	CONT:	SECT:	JOB:	HIGHWAY:
REVISIONS	0114	08	036, ETC	US 290, ETC
	DIST:	COUNTY:	SHEET NO.	
	YKM	FAYETTE, ETC	76	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

REFLECTOR UNIT SIZES FOR DELINEATORS AND OBJECT MARKERS				DELINEATORS				D & OM DESCRIPTIVE CODES	
DEVICE	SIZE 1	SIZE 2	SIZE 3	SIZE 4	DEVICE	SINGLE	DOUBLE	INSTL DEL ASSM (D-XX)SZ X (XXXX)XXX (XX)	
SHEETING	Yellow, White or Red Type B or C reflective sheeting				SHEETING	Yellow, White or Red Type B or C Reflective Sheeting			
NOTE	1. Size 1 and 4 - Direct applied reflective sheeting for use on flexible post (fix). 2. Size 2 and 3 - For use on wing channel (wc) post only. Use approved metal, plastic or fiberglass backplate with 17/64" mounting holes.				POST TYPE	WC	YFLX, WFLX	WC	YFLX, WFLX
					MOUNT TYPE	GND	GND, SRF	GND	GND, SRF

OBJECT MARKERS								INSTL OM ASSM (OM-XX) (XXXX)XXX (XX)		
DEVICE	Type 1 (OM-1)	Type 2 (OM-2)			Type 3 (OM-3)			Type 4 (OM-4)	TYPE OF OBJECT MARKER 1, 2, 3, or 4	
		OM-1	OM-2X	OM-2Y	OM-2Z	OM-3L	OM-3R	OM-3C	OM-4	NUMBER OF REFLECTORS OR DIRECTION X = 3-Size 2 reflector unit (Type 2 only) Y = 1-Size 3 reflector unit (Type 2 only) Z = 3-Size 1 or 1-Size 4 reflector unit(s) (Type 2 only) L = Left Side (Type 3 Object Marker only) R = Right Side (Type 3 Object Marker only) C = Center (Type 3 Object Marker only) TYPE OF POST WC = Wing Channel Post WFLX = White Flexible Post TWT = Thin Walled Tubing TYPE OF MOUNT GND = Embedded (drivable) SRF = Surface Mount WAS = Wedge Anchor Steel WAP = Wedge Anchor Plastic DIRECTION If Required BI = Bi-Directional
SHEETING	Yellow-Type B _{FL} or C _{FL} Sheeting	Yellow - Type B or C Sheeting			Alternating acrylic black and retroreflective yellow - Type B _{FL} or C _{FL} Sheeting			Red -Type B _{FL} or C _{FL} Sheeting	DEPARTMENTAL MATERIAL SPECIFICATIONS FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES) DMS-4400 SIGN FACE MATERIALS DMS-8300 DELINEATORS, OBJECT MARKERS AND BARRIER REFLECTORS DMS-8600	
POST TYPE	TWT	WC	WC	WFLX	TWT			TWT		
MOUNT TYPE	WAS, WAP	GND	GND	GND, SRF	WAS, WAP			WAS, WAP		

BARRIER REFLECTORS (BRF)			CHEVRONS				ONE DIRECTION LARGE ARROW		NOTE: Delineator and object marker substrates and sign substrates shall be 0.080" Aluminum sign blank to conform to ASTM B-290 Alloy 6061-T6 or approved alternative.		
DEVICE	GF1	GF2	CTB	 W1-8				 W1-6			
	1. Barrier reflectors shall meet the requirements of DMS 8600. 2. Approved Barrier Reflectors are listed on the "Barrier Reflectors" Material Producer List at: www.txdot.gov.			SIZE (W x L)	18" x 24" (Conventional)	24" x 30" (Conventional Oversize)	30" x 36" (Expressway)	36" x 48" (Freeway)	SIZE (W x L)	48" x 24" (Conventional)	60" x 30" (Expressway & Freeway)
				MOUNTING HEIGHT	4'-0" or 7'-0"		7'-0" Only	MOUNTING HEIGHT	7'-0"		
				NOTE	1. CHEVRON (W1-8) signs and ONE DIRECTION LARGE ARROW (W1-6) Signs shall be installed per Sign Mounting Details (SMD) Standard Sheets and paid under Item 644 (Small Roadside Sign Assemblies). 2. When there is a need to increase conspicuity, the Texas version of the ONE DIRECTION LARGE ARROW sign (W1-9T) may be used instead of the ONE DIRECTION LARGE ARROW (W1-6).						
SHEETING	Yellow, White, Red										
NOTE	1. Reflective sheeting shall have a minimum dimension of 3 inches and minimum surface area of 9 square inches.										

DATE: \$DATE\$
 TIME: \$TIME\$
 FILE: \$FILE\$

Texas Department of Transportation
 Traffic Safety Division Standard



DELINEATOR & OBJECT MARKER MATERIAL DESCRIPTION

D & OM(1)-20

FILE: dom1-20.dgn	DN: TXDOT	CK: TXDOT	OW: TXDOT	CR: TXDOT
© TXDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS	0114	08	036, ETC	US 290, ETC
10-09 3-15	DIST	COUNTY	SHEET NO.	
4-10 7-20	YKM	FAYETTE, ETC	77	


20A

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_01.dgn
 DATE: \$DATE\$



NOTES:

1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	78


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_02.dgn
 DATE: \$DATE\$



LEGEND

	SILT FENCE
	ID NUMBER
	DIRECTION OF FLOW
	CULVERT
	BRG. CL. CULV. OR BRIDGE
	INLET

- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	79

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_03.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)


NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 3 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	80

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_04.dgn
 DATE: \$DATE\$



LEGEND

	SILT FENCE
	ID NUMBER
	DIRECTION OF FLOW
	CULVERT
	BRG CL CULV OR BRIDGE
	INLET

- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	81


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_05.dgn
 DATE: \$DATE\$



LEGEND

	SILT FENCE
	ID NUMBER
	DIRECTION OF FLOW
	CULVERT
	BRG CL CULV OR BRIDGE
	INLET

- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	82

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_06.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	83

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_07.dgn
 DATE: \$DATE\$



NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED



FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	84

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_08.dgn
 DATE: \$DATE\$



NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE




Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 8 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	85




PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_09.dgn
 DATE: \$DATE\$



LEGEND

	SILT FENCE
	ID NUMBER
	DIRECTION OF FLOW
	CULVERT
	BRG CL CULV OR BRIDGE
	INLET

- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	86

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_10.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023




STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)

NOT TO SCALE

©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	87


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\011408036_US290\SW3P_USE1
 FILE: SW3P_LAYOUT_11.dgn
 DATE: \$DATE\$



LEGEND

	SILT FENCE
	ID NUMBER
	DIRECTION OF FLOW
	CULVERT
	BRG CL CULV OR BRIDGE
	INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)



NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 11 OF 12

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	88

(40)
 STA 484+68.58 TO STA 484+90.33
 CENTERLINE STRUCTURE
 W/INLET



NOTES:
 1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



SW3P SUMMARY


ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
1	STA 111+00	40	40
2	STA 123+92	30	30
3	STA 127+17	30	30
4	STA 134+50	30	30
5	STA 142+87.54	40	40
6	STA 150+00	30	30
7	STA 155+12.38	40	40
8	STA 182+00	30	30
9	STA 184+00.55	40	40
10	STA 191+00	40	40
11	STA 196+50	30	30
12	STA 212+00	30	30
13	STA 213+53.72	40	40
14	STA 227+08.45	40	40
CSJ 0114-08-036 SHEET TOTAL		490	490

SW3P SUMMARY

ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
15	STA 228+00	30	30
16	STA 241+00	30	30
17	STA 253+50	40	40
18	STA 266+19.58	40	40
19	STA 267+00	30	30
20	STA 275+75.40	40	40
21	STA 280+00	30	30
22	STA 289+01.48 TO STA 289+22.52	40	40
23	STA 290+75	30	30
24	STA 300+00	40	40
25	STA 306+00	30	30
26	STA 319+00	30	30
27	STA 334+50	40	40
28	STA 349+50	40	40
CSJ 0114-08-036 SHEET TOTAL		490	490

SW3P SUMMARY

ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
29	STA 365+00	40	40
30	STA 384+50	40	40
31	STA 396+50	40	40
32	STA 410+00	40	40
33	STA 417+26.60	40	40
34	STA 423+50	40	40
35	STA 442+00	30	30
36	STA 450+72.90	40	40
37	STA 461+81	30	30
38	STA 464+50	40	40
39	STA 474+60	40	40
40	STA 484+68.58 TO STA 484+90.33	40	40
41	STA 487+75	30	30
42	STA 490+25	40	40
43	AS APPROVED OR DIRECTED	40	40
CSJ 0114-08-036 SHEET TOTAL		570	570
CSJ 0114-08-036 TOTAL		1550	1550



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0114-08-036)


NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	89

PATH: T:\YKMANNE\XIP56\011408036_ETC_US290_SHT1_CABLEBARRIER\011408036_US290\SW3P_USE\FILE: SW3P_LAYOUT_12.dgn
 DATE: \$DATE\$


PATH: T:\YKMAN\XIP5&E\01.1408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_13.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION ALL RIGHTS RESERVED
 SHEET 1 OF 18

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	90

②
 STA 328+38
 CROSSOVER
 CULVERT

①
 STA 315+75
 BEGIN PROJECT
 CSJ 0266-01-088
 STA 316+00

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71_SW3P_USE1
 FILE: SH71_SW3P_16.dgn
 DATE: \$DATE\$




LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	91

PATH: T:\YKMAN\XIP\SS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_19.dgn
 DATE: \$DATE\$



NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	92


PATH: T:\YKMAN\EX\IPSS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_22.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	93

PATH: T:\YKMAN\XIP5&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_25.dgn
 DATE: \$DATE\$



NOTES:

1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	94


PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_28.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	95

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_31.dgn
 DATE: \$DATE\$




LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023




STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	96

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_34.dgn
 DATE: \$DATE\$



- LEGEND**
- SILT FENCE
 - ID NUMBER
 - DIRECTION OF FLOW
 - CULVERT
 - BRG CL CULV OR BRIDGE
 - INLET
- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	97


PATH: T:\YKMAN\XIP\SS\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_37.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL. CULV OR BRIDGE
- INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	98

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_40.dgn
 DATE: \$DATE\$



NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023





STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE


©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	99

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_43.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)



NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 11 OF 18

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	100

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_46.dgn
 DATE: \$DATE\$



NOTES:
 1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.


04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)


NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	101



PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_49.dgn
 DATE: \$DATE\$



- LEGEND**
- SILT FENCE
 - ID NUMBER
 - DIRECTION OF FLOW
 - CULVERT
 - BRG CL CULV OR BRIDGE
 - INLET
- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)


NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 13 OF 18

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	102

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_52.dgn
 DATE: \$DATE\$




LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL CULV OR BRIDGE
- INLET

NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	103

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_55.dgn
 DATE: \$DATE\$



NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS, AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023





STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	104

PATH: T:\YKMAN\EX\IPS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: SH71_SW3P_58.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)



NOT TO SCALE

Texas Department of Transportation
 © 2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


SHEET 16 OF 18

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET No.
TEXAS	YKM	FAYETTE,ETC	105

PATH: T:\YKMAN\EX\IPSS\011408036.ETC_US290_SHT1_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SHT1\SW3P_USE1
 FILE: SH71_SW3P_61.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-01-088)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 17 OF 18

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	106

SW3P SUMMARY

ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
1	STA 315+75	40	40
2	STA 328+38	30	30
3	STA 332+44	40	40
4	STA 343+40	30	30
5	STA 352+00	40	40
6	STA 360+50	30	30
7	STA 365+82.89 TO STA 150+95 ①	80	80
8	STA 158+48	40	40
9	STA 161+60	30	30
10	STA 176+00	40	40
11	STA 177+60	30	30
12	STA 196+76	30	30
13	STA 206+26.85	40	40
14	STA 210+00	30	30
15	STA 215+61.35	40	40
16	STA 223+50	30	30
17	STA 231+86	40	40
18	STA 241+80	30	30
19	STA 244+85 TO STA 245+07.50	40	40
20	STA 273+50	30	30
21	STA 274+34	40	40
22	STA 280+20	30	30
23	STA 291+40.49 TO STA 293+11	80	80
CSJ 0266-01-088 SHEET TOTAL		890	890

① EQUATION: STA 365+82.89 = STA 149+08.00

SW3P SUMMARY

ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
24	STA 306+50	30	30
25	STA 309+00	40	40
26	STA 333+84	30	30
27	STA 340+32.50	40	40
28	STA 348+20	30	30
29	STA 355+40	30	30
30	STA 363+00	40	40
31	STA 371+70	30	30
32	STA 380+34.50 TO STA 382+34.50	80	80
33	STA 389+60	30	30
34	STA 398+02	40	40
35	STA 405+60	30	30
36	STA 423+50	30	30
37	STA 439+00	40	40
38	STA 452+05	40	40
39	STA 462+55	30	30
40	STA 468+94.37 TO STA 469+50.77	80	80
41	STA 480+40	30	30
42	STA 499+00	30	30
43	STA 503+25	40	40
44	STA 533+00	40	40
45	STA 543+45 TO STA 544+15	80	80
46	STA 551+05	30	30
CSJ 0266-01-088 SHEET TOTAL		920	920

SW3P SUMMARY

ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
47	STA 563+28	30	30
48	STA 571+46	40	40
49	STA 576+38	30	30
50	STA 577+98	40	40
51	STA 587+00	30	30
52	STA 621+35	40	40
53	STA 636+00	30	30
54	STA 640+00	40	40
55	STA 648+60	30	30
56	STA 651+90.04 TO STA 652+40.08	80	80
57	STA 664+00	30	30
	AS APPROVED OR DIRECTED	50	50
CSJ 0266-01-088 SHEET TOTAL		470	470
CSJ 0266-01-088 TOTAL		2280	2280

PATH: T:\YKMAN\EX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\SW3P_USE1
 FILE: BL CL2 - Plan 1.dgn
 DATE: \$DATE\$

**STORM WATER
LAYOUT AND
SUMMARY
(CSJ 0266-01-088)**


NOT TO SCALE



SHEET 18 OF 18

FED. RD. DIV. NO. 6		PROJECT NO.	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	107


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 1.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL. CULV OR BRIDGE
- INLET

- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE




©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	108

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTY\LINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 4.dgn
 DATE: \$DATE\$



- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


**STORM WATER
 LAYOUT AND
 SUMMARY
 (CSJ 0266-02-069)**

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	109

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 7.dgn
 DATE: \$DATE\$



- LEGEND**
- SILT FENCE
 - ID NUMBER
 - DIRECTION OF FLOW
 - CULVERT
 - BRG CL. CULV OR BRIDGE
 - INLET
- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	110

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 10.dgn
 DATE: \$DATE\$



- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



**STORM WATER
LAYOUT AND
SUMMARY
(CSJ 0266-02-069)**

NOT TO SCALE


©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	111

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 13.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	112


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 16.dgn
 DATE: \$DATE\$



LEGEND

	SILT FENCE
	ID NUMBER
	DIRECTION OF FLOW
	CULVERT
	BRG CL. CULV OR BRIDGE
	INLET

- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023


STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	113


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 19.dgn
 DATE: \$DATE\$



LEGEND

- SILT FENCE
- ID NUMBER
- DIRECTION OF FLOW
- CULVERT
- BRG CL. CULV OR BRIDGE
- INLET

- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED


FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	114

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 22.dgn
 DATE: \$DATE\$



NOTES:

- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
- ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)



NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 8 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	115

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 25.dgn
 DATE: \$DATE\$



- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023



STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE


Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	116

PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUP\PS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 28.dgn
 DATE: \$DATE\$



- NOTES:**
1. INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 2. ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.



Amanda Anderle Fling, P.E.

04/26/2023




STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE

©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	117


PATH: \\FS-YKMHQ.dot.state.tx.us\DATA\YK\GROUPS\YK\MANNEX\PS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\SW3P\SW3P_USE1
 FILE: SWLOS - Plan 31.dgn
 DATE: \$DATE\$



- NOTES:**
- INSTALL BMP'S TO CORRESPOND WITH SEQUENCE OF CONSTRUCTION. ADDITIONAL BMP'S MAY BE ADDED TO CORRESPOND WITH CONSTRUCTION ACTIVITIES AS APPROVED OR DIRECTED BY THE ENGINEER.
 - ACTUAL BMP LOCATIONS AND LENGTHS MAY VARY TO MEET FIELD CONDITIONS, AS APPROVED OR DIRECTED BY THE ENGINEER.

SW3P SUMMARY

ID NUM	LOCATION	ITEM 506	
		TEMP SEDMT CONT FENCE INSTALL (LF)	TEMP SEDMT CONT FENCE REMOVE (LF)
1	STA 681+52	40	40
2	STA 691+73.50	40	40
3	STA 694+00	30	30
4	STA 708+37	40	40
5	STA 717+14	30	30
6	STA 726+25	30	30
7	STA 738+30	40	40
8	STA 759+00	30	30
9	STA 772+04.80 TO STA 772+54.84	40	40
10	STA 777+02	40	40
11	STA 799+27.80	40	40
12	STA 827+18	40	40
13	STA 836+36.50	40	40
14	STA 840+11.71 TO STA 840+42.42	40	40
15	STA 869+63	40	40
16	STA 873+90	30	30
17	STA 900+46	30	30
18	STA 916+30	40	40
19	STA 932+15	40	40
20	STA 935+75	30	30
21	STA 952+00.00 TO STA 952+32.67	40	40
22	STA 954+78	30	30
23	STA 975+57.50	40	40
24	STA 980+00	30	30
25	STA 986+74	40	40
26	STA 1008+57	40	40
27	STA 1016+90	30	30
28	STA 1029+05	30	30
29	STA 1041+09	40	40
30	STA 1053+15	30	30
	AS APPROVED OR DIRECTED	50	50
	CSJ 0266-02-069 TOTAL	1130	1130



Amanda Anderle Fling, P.E.

04/26/2023

STORM WATER LAYOUT AND SUMMARY (CSJ 0266-02-069)

NOT TO SCALE

Texas Department of Transportation
 ©2023 BY TEXAS DEPARTMENT OF TRANSPORTATION
 ALL RIGHTS RESERVED

SHEET 11 OF 11

FED. RD. DIV. NO.		PROJECT NO.	
6			
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036,ETC	US 290,ETC
STATE	DIST.	COUNTY	SHEET NO.
TEXAS	YKM	FAYETTE,ETC	118

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with the TPDES Construction General Permit TXR150000 (CGP). The Texas Department of Transportation (TxDOT) ensures that project specifications include adequate best management practices (BMPs) for this project.

For all projects with any soil disturbing activities, TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office. If no field office is available, then this SWP3 shall be kept in the appropriate TxDOT Area Office.

This SWP3 is consistent with requirements specified in applicable stormwater plans and the projects environmental permits, issues, and commitments (EPICs). A copy of the CGP is included in Attachment 2.12 of the SWP3 binder.

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

0114-08-036

1.2 PROJECT LIMITS:

From: LEE C/L

To: WASHINGTON C/L

1.3 PROJECT COORDINATES:

BEGIN: (Lat) 30.1502°(N), (Long) 96.6806°(W)

END: (Lat) 30.1547°(N), (Long) 96.8009°(W)

1.4 TOTAL PROJECT AREA (Acres): 120

1.5 TOTAL AREA TO BE DISTURBED (Acres): 49

1.6 NATURE OF CONSTRUCTION ACTIVITY:

FOR CONSTRUCTION OF HAZARD ELIMINATION AND

SAFETY CONSISTING OF INSTALL MEDIAN BARRIER.

1.7 MAJOR SOIL TYPES:

Soil Type	Description
AROL FINE SANDY LOAM, 1 TO 3% SLOPES	CLAYEY RESIDUUM WEATHERED FROM SANDSTONE AND SILTSTONE MODERATELY WELL DRAINED, HIGH RUNOFF
SHIRO LOAMY FINE SAND, 1 TO 3% SLOPES	RESIDUUM WEATHERED FROM TUFFACEOUS SANDSTONE AND SILTSTONE, WELL DRAINED, HIGH RUNOFF
SINGLETON FINE SANDY LOAM, 1 TO 3% SLOPES	RESIDUUM WEATHERED FROM TUFFACEOUS SANDSTONE AND SILTSTONE, MODERATELY WELL DRAINED, VERY HIGH RUNOFF
STRABER LOAMY FINE SAND, 1 TO 5% SLOPES	CLAYEY RESIDUUM FROM MUDSTONE, MODERATELY WELL DRAINED, MEDIUM RUNOFF
STRABER GRAVELLY LOAMY FINE SAND, 2 TO 5% SLOPES	LOAMY AND CLAYEY FLUVIOMARINE, MODERATELY WELL DRAINED, VERY HIGH RATE OF RUNOFF
TABOR FINE SANDY LOAM, 1 TO 5% SLOPES	LOAMY AND CLAYEY ALLUVIUM, MODERATELY WEE DRAINED, VERY HIGH RATE OF RUNOFF

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.5.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures
- Other: _____
- Other: _____
- Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Other: _____
- Other: _____
- Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody
CUMMINS CREEK	COLORADO RIVER (1402)

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____


1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.14 LOCAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) OPERATOR COORDINATION:

MS4 Entity
N/A

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (CSJ 0114-08-036)



Sheet 1 of 2

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			119
STATE	STATE DIST.	COUNTY	
TEXAS	YKM	FAYETTE, ETC	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036, ETC	US 290, ETC

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: _____
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

Sediment control BMPs requiring design capacity calculations (See SWP3 Attachment 1.3.):

T / P

- Sediment Trap
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Sedimentation Basin
 - Not required (<10 acres disturbed)
 - Required (>10 acres) and implemented.
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Required (>10 acres), but not feasible due to:
 - Available area/Site geometry
 - Site slope/Drainage patterns
 - Site soils/Geotechnical factors
 - Public safety
 - Other: _____

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

2.8 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3 .

2.9 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3.

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (CSJ 0114-08-036)



Sheet 2 of 2
Texas Department of Transportation

FED. RD. DIV. NO. 6	PROJECT NO.		SHEET NO. 120
STATE TEXAS	STATE DIST. YKM	COUNTY FAYETTE, ETC	
CONT. 0114	SECT. 08	JOB 036, ETC	HIGHWAY NO. US 290, ETC

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with the TPDES Construction General Permit TXR150000 (CGP). The Texas Department of Transportation (TxDOT) ensures that project specifications include adequate best management practices (BMPs) for this project.

For all projects with any soil disturbing activities, TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office. If no field office is available, then this SWP3 shall be kept in the appropriate TxDOT Area Office.

This SWP3 is consistent with requirements specified in applicable stormwater plans and the projects environmental permits, issues, and commitments (EPICs). A copy of the CGP is included in Attachment 2.12 of the SWP3 binder.

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

0266-01-088

1.2 PROJECT LIMITS:

From: LA GRANGE CITY LIMITS

To: COLORADO C/L

1.3 PROJECT COORDINATES:

BEGIN: (Lat) 29°55'17.73(N), (Long) 96°52'51.86(W)

END: (Lat) 29°49'16.08(N), (Long) 96°41'33.23(W)

1.4 TOTAL PROJECT AREA (Acres): 105

1.5 TOTAL AREA TO BE DISTURBED (Acres): 31

1.6 NATURE OF CONSTRUCTION ACTIVITY:

FOR CONSTRUCTION OF HAZARD ELIMINATION AND

SAFETY CONSISTING OF INSTALL MEDIAN BARRIER.

1.7 MAJOR SOIL TYPES:

Soil Type	Description
CROCKETT LOAM, 1 TO 3% SLOPES	LOAMY RESIDUUM WEATHERED FROM SHALE OF CRETACEOUS AGE MODERATELY WELL DRAINED, VERY HIGH RUNOFF
STRABER LOAMY FINE SAND, 1 TO 5% SLOPES	CLAYEY RESIDUUM DERIVED FROM MUDSTONE OF THE WILLIS FORMATION MODERATELY WELL DRAINED, MEDIUM RUNOFF
STRABER GRAVELLY LOAMY FINE SAND, 2 TO 5% SLOPES	LOAMY AND CLAYEY FLUVIOMARINE, MODERATELY WELL DRAINED, VERY HIGH RATE OF RUNOFF
STRABER GRAVELLY LOAMY FINE SAND, 5 TO 8% SLOPES	LOAMY AND CLAYEY FLUVIOMARINE, MODERATELY WELL DRAINED, VERY HIGH RATE OF RUNOFF
WILSON CLAY LOAM, 0 TO 1% SLOPES	CLAYEY ALLUVIUM, MODERATELY WELL DRAINED, HIGH RATE OF RUNOFF

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.5.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures
- Other: _____
- Other: _____
- Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Other: _____
- Other: _____
- Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody
CEDAR CREEK	CEDAR CREEK RESERVOIR / LAKE FAYETTE (1402G)

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.14 LOCAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) OPERATOR COORDINATION:

MS4 Entity
N/A

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (CSJ 0266-01-088)



Sheet 1 of 2

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			121
STATE	STATE DIST.	COUNTY	
TEXAS	YKM	FAYETTE, ETC	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036, ETC	US 290, ETC

PATH: T:\KMAN\EXPS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026601088_SH71\DGN_IF_NEEDED\FILE: SWP3.dgn
 DATE: \$DATE\$

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: _____
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

Sediment control BMPs requiring design capacity calculations (See SWP3 Attachment 1.3.):

T / P

- Sediment Trap
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Sedimentation Basin
 - Not required (<10 acres disturbed)
 - Required (>10 acres) and implemented.
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Required (>10 acres), but not feasible due to:
 - Available area/Site geometry
 - Site slope/Drainage patterns
 - Site soils/Geotechnical factors
 - Public safety
 - Other: _____

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

2.8 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3 .

2.9 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3.

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (CSJ 0266-01-088)



Sheet 2 of 2

FED. RD. DIV. NO. 6	PROJECT NO.		SHEET NO. 122
STATE TEXAS	STATE DIST. YKM	COUNTY FAYETTE, ETC	
CONT. 0114	SECT. 08	JOB 036, ETC	HIGHWAY NO. US 290, ETC

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with the TPDES Construction General Permit TXR150000 (CGP). The Texas Department of Transportation (TxDOT) ensures that project specifications include adequate best management practices (BMPs) for this project.

For all projects with any soil disturbing activities, TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office. If no field office is available, then this SWP3 shall be kept in the appropriate TxDOT Area Office.

This SWP3 is consistent with requirements specified in applicable stormwater plans and the projects environmental permits, issues, and commitments (EPICs). A copy of the CGP is included in Attachment 2.12 of the SWP3 binder.

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

0266-02-069

1.2 PROJECT LIMITS:

From: COLORADO C/L

To: MAREK RD

1.3 PROJECT COORDINATES:

BEGIN: (Lat) 29°49'16.08"(N), (Long) 96°41'33.23"(W)

END: (Lat) 29°45'07.64"(N), (Long) 96°36'20.91"(W)

1.4 TOTAL PROJECT AREA (Acres): 100

1.5 TOTAL AREA TO BE DISTURBED (Acres): 32

1.6 NATURE OF CONSTRUCTION ACTIVITY:

FOR CONSTRUCTION OF HAZARD ELIMINATION AND

SAFETY CONSISTING OF INSTALL MEDIAN BARRIER.

1.7 MAJOR SOIL TYPES:

Soil Type	Description
TABOR FINE SANDY LOAM 1 TO 3% SLOPES	LOAMY AND CLAYEY ALLUVIUM MODERATELY WELL DRAINED, VERY HIGH RUNOFF
STRABER VERY GRAVELLY LOAMY FINE SAND, 3 TO 8% SLOPES	LOAMY AND CLAYEY FLUVIOMARINE MODERATELY WELL DRAINED, VERY HIGH RUNOFF
REK EXTREMELY GRAVELLY COARSE SANDY LOAM, 1 TO 3% SLOPES	GRAVELLY SANDY AND CLAYEY FLUVIOMARINE, MODERATELY WELL DRAINED, VERY HIGH RUNOFF
STRABER LOAMY FINE SAND, 1 TO 3% SLOPES	LOAMY AND CLAYEY FLUVIOMARINE, MODERATELY WELL DRAINED, VERY HIGH RUNOFF
STRABER GRAVELLY GRAVELLY LOAMY FINE SAND, 1 TO 3% SLOPES	LOAMY AND CLAYEY FLUVIOMARINE, MODERATELY WELL DRAINED, VERY HIGH RATE OF RUNOFF
TREMONA EXTREMELY GRAVELLY LOAMY SAND, 1 TO 3% SLOPES	SANDY AND CLAYEY FLUVIOMARINE, SOMEWHAT POORLY DRAINED, HIGH RUNOFF

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.5.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures

Other: _____

Other: _____

Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Other: _____
- Other: _____
- Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody
CRIER CREEK	COLORADO RIVER (1402)

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.14 LOCAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) OPERATOR COORDINATION:

MS4 Entity
N/A

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (CSJ 0266-02-069)



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			123
STATE	STATE DIST.	COUNTY	
TEXAS	YKM	FAYETTE, ETC	
CONT.	SECT.	JOB	HIGHWAY NO.
0114	08	036, ETC	US 290, ETC

PATH: T:\YKMAN\EXPS&E\011408036.ETC_US290_SH71_CABLEBARRIER\PREVIOUS BEFORE COMBINING\026602069_SH71_CNTYLINE\DWG\ FILE: SWP3.dgn DATE: \$DATE\$

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: _____
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

Sediment control BMPs requiring design capacity calculations (See SWP3 Attachment 1.3.):

T / P

- Sediment Trap
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Sedimentation Basin
 - Not required (<10 acres disturbed)
 - Required (>10 acres) and implemented.
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Required (>10 acres), but not feasible due to:
 - Available area/Site geometry
 - Site slope/Drainage patterns
 - Site soils/Geotechnical factors
 - Public safety
 - Other: _____

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

2.8 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3 .

2.9 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3.

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (CSJ 0266-02-069)



Sheet 2 of 2

FED. RD. DIV. NO. 6	PROJECT NO.		SHEET NO. 124
STATE TEXAS	STATE DIST. YKM	COUNTY FAYETTE, ETC	
CONT. 0114	SECT. 08	JOB 036, ETC	HIGHWAY NO. US 290, ETC

I. STORMWATER POLLUTION PREVENTION

Texas Pollutant Discharge Elimination System (TPDES) TXR 150000: Stormwater Discharge Permit or Construction General Permit is required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506. If applicable list MS4 operator that may receive discharges from this project. MS4 operator should be notified prior to construction activities.

Prevent stormwater pollution erosion and sedimentation in accordance with TPDES Permit TXR 150000. +

Comply with the SW3P and revise when necessary to control pollution or as required by the Engineer. +

Post Construction Site Notice (CSN) with SW3P information on or near the site, accessible to the public and TCEQ, EPA, or other inspectors.

When Contractor project specific locations (PSL) increase disturbed soil area to 5 acres or more, submit Notice of Intent (NOI) to TCEQ and Engineer. +

MS4 Operator(s): Victoria

No Additional Comments

II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS

United States Army Corps of Engineers (USACE) Permit is required for filling, dredging, excavating or other work in water bodies, rivers, creeks, streams, wetlands or wet areas. The Contractor must adhere to all of the terms and general conditions associated with the following permit(s). If additional work not represented in the plans is required, contact the Engineer immediately.

No USACE Permit Required

Work is authorized by the USACE under a Nationwide Permit _____ without a Pre-Construction Notification (PCN). Project specific permit was not issued by USACE, therefore is not in the plan set.

Work is authorized by the USACE under a Nationwide Permit _____ with a Pre-Construction Notification (PCN). The project specific permit issued by the USACE is included in the plan set.

Work is authorized by the USACE under a Individual Permit (IP). The project specific permit issued by the USACE is included in the plan set.

Work would be authorized by the USACE. The project specific permit issued by the USACE or Nationwide Permit will be provided to the contractor.

United States Coast Guard (USCG) Permit is required for projects that involve the construction or modification (including changes to lighting) of a bridge or causeway across a water body determined to be navigable by the United States Coast Guard (USCG) under Section 9 of the Rivers and Harbors Act. If additional work not represented in the plans is required, contact the Engineer immediately.

No United States Coast Guard (USCG) Coordination Required

United States Coast Guard (USCG) Permit

United States Coast Guard (USCG) Exemption

Best Management Practices +

Erosion	Sedimentation	Post Construction TSS +
<input type="checkbox"/> Temporary Vegetation	<input checked="" type="checkbox"/> Silt Fence	<input checked="" type="checkbox"/> Vegetative Filter Strips +
<input type="checkbox"/> Mulch	<input type="checkbox"/> Rock Filter Dam	<input type="checkbox"/> Vegetation Lined Ditches
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Grassy Swales

No Additional Comments

III. CULTURAL RESOURCES

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the area and contact the Engineer immediately.

No Additional Comments

IV. VEGETATION RESOURCES

Preserve native vegetation to the extent practical. Refer to TxDOT Standard Specifications 162, 164, 192, 193, 506, 730, 751, and 752 in order to comply with requirements for invasive species, beneficial landscaping and tree/brush removal.

No Additional Comments

V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS

If any of the listed species below are observed, cease work in the area, do not disturb species or habitat and contact the Engineer immediately.

The work may not remove active nests (from bridges, structures, or vegetation adjacent to the roadway, etc.) during nesting season (February 15 to October 1). If removal of structures or vegetation is necessary during the nesting season, the Contractor shall conduct a bird survey no more than 3 days in advance of the clearing/demolish start date. All bird surveys shall be conducted by a Field Biologist and adhere to the guidance document "Avoiding Migratory Birds and Handling Potential Violations" found in the TxDOT Environmental Compliance Toolkits at the time of the survey. (See below for Field Biologist and Ornithologist qualifications)

No Additional Comments

VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES

Refer to TxDOT Standard Specifications in the event potentially contaminated materials are observed, such as dead or distressed vegetation, trash disposal areas, drums, canisters, barrels, leaching or seepage of substances, unusual smells or odors, or stained soil, cease work in the area and contact the Engineer immediately.

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)? Yes No


No Additional Comments

VII. ADDITIONAL ENVIRONMENTAL COMMENTS & ISSUES

Comments:


TxDOT has determined that a USACE Nationwide or Individual Permit is not necessary for the project since all work shall be conducted outside the USACE jurisdictional areas. Any impacts to these jurisdictional areas by the contractor without a USACE permit will be the responsibility of the contractor. If the contractor deems it necessary to impact the USACE jurisdictional areas, then it becomes the contractor's entire responsibility to consult with the USACE pertaining to the need for a Nationwide or Individual Permit. TxDOT will then hold the contractor responsible for following all conditions of the approved Permit.

Field Biologist, Ornithologist – a field biologist is defined as an individual qualified to perform field investigations, presence/absence surveys and habitat surveys for protected avian species or species of concern. A mandatory bachelor's degree in biology or a related science is required. At a minimum, the Field Biologist, Ornithologist, shall have completed and reported a minimum of three presence/absence and habitat surveys for protected avian species in the past five years. A minimum of three projects must have been conducted in Texas. Surveys shall have been performed for documentation of species in accordance with a protocol approved by USFWS or TPWD, or following generally accepted methodologies.



		TxDOT Yoakum District	
ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS			
EPIC			
FILE: EPIC Sheet.dgn	DN:	CK:	BW: CK:
© TxDOT: March 2017	CONT SECT	JOB	HIGHWAY
REVISIONS	0114 08	036, ETC	US 290, ETC
UPDATED section V, text and added definition (10/17) ADDED USCG and USACE notes in Section VII (04/18)	DIST	COUNTY	SHEET NO.
	YKM	FAYETTE	125

Version 2.1

DISCLAIMER: This standard is made by TxDOT for any purpose whatsoever. No warranty of any kind is made by TxDOT for any purpose whatsoever. The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



TEMPORARY SEDIMENT CONTROL FENCE



HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

SEDIMENT CONTROL FENCE USAGE GUIDELINES

A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT². Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.


LEGEND

Sediment Control Fence



GENERAL NOTES

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.



VERTICAL TRACKING

				Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING					
EC(1) - 16					
FILE: ec116	DN: TxDOT	CK: KM	DW: VP	DN/CK: LS	
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY	
REVISIONS		0114	08	036, ETC	US 290, ETC
	DIST	COUNTY		SHEET NO.	
	YKM	FAYETTE, ETC		126	

\$DATE\$
\$FILE\$