

100%
SUBMITTAL

INDEX OF SHEETS

SEE SHEET 2 FOR INDEX OF SHEETS

STATE OF TEXAS
DEPARTMENT OF TRANSPORTATION

PLANS OF PROPOSED
STATE HIGHWAY IMPROVEMENT

PROJECT NO. F 2B23 (052)

CSJ: 0579-02-014


NET LENGTH OF ROADWAY = 50,561.22 FT = 9.576 MI.
NET LENGTH OF BRIDGE = 242.11 FT = 0.046 MI.
NET LENGTH OF PROJECT = 50,803.33 FT = 9.622 MI.

FM 512
HUNT COUNTY

LIMITS: FROM SH 34 TO FM 118

FOR THE CONSTRUCTION OF: REHABILITATION OF EXISTING ROAD
CONSISTING OF REWORKING BASE, GEOGRID, FLEXBASE, CEMENT TREATING, 2CST


BEGIN PROJECT
CSJ: 0579-02-014
FM 512
STA: 0+50.00
REF MRK: 220+1.896



END PROJECT
CSJ: 0579-02-014
FM 512
STA: 508+53.33
REF MRK: 232+1.620

EXCEPTIONS: N/A
EQUATIONS: N/A
RAILROAD CROSSINGS: N/A

100% SUBMITTAL



5/24/2023

Charles M. Shine, P.E.

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL-AID CONSTRUCTION CONTRACTS (FORM FHWA 1273, JULY 5, 2022)

© 2023
BY TEXAS DEPARTMENT OF TRANSPORTATION
ALL RIGHTS RESERVED.

FHWA TEXAS DIVISION		SHEET NO.	
		1	
STATE	DISTRICT	COUNTY	
TEXAS	PARIS	HUNT	
CONTROL	SECTION	JOB	HIGHWAY NO.
0579	02	014	FM 512

FUNCTIONAL CLASS = MAJOR COLLECTOR
DESIGN SPEED = 30 MPH
A. D. T. (2023) = 1000
A. D. T. (2043) = 1300

FINAL PLANS

LETTING DATE: _____

DATE CONTRACTOR BEGAN WORK: _____

DATE WORK WAS COMPLETED: _____

DATE WORK WAS ACCEPTED: _____

ORIGINAL CONTRACT WORKING DAYS: _____

USED _____ OF _____ WORKING DAYS

NO. OF CHANGE ORDERS: _____

FINAL CONTRACT COST: _____

PERCENT OVER/UNDER RUN: _____

CONTRACTOR: _____

I CERTIFY THAT THIS PROJECT WAS BUILT IN ACCORDANCE WITH PLANS AND SPECIFICATIONS.

AREA ENGINEER _____ DATE _____

REQUIRED SIGNS SHALL BE IN ACCORDANCE WITH BC (1) - 21 THRU BC (12) - 21 AND THE "TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES".



RECOMMENDED FOR LETTING: 5/26/2023

DocuSigned by: *[Signature]*
18841028B1974ECP&D DIRECTOR

RECOMMENDED FOR LETTING: 5/26/2023

DocuSigned by: *James Atkins ??*
A2C81980FB8844 AREA ENGINEER

APPROVED FOR LETTING: 5/30/2023

DocuSigned by: *Noel Paramanathan*
AFTAF41AFE6049ED DISTRICT ENGINEER

FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\01*GENERAL\FM512*GNNTS.dgn
DATE: 5/24/2023 6:19:44 PM

INDEX OF SHEETS

5/24/2023 6:19:44 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNDX\01-GENERAL\FM512_GNIDX_01.dgn

SHEET NO.	DESCRIPTION	SHEET NO.	DESCRIPTION
GENERAL			
1	TITLE SHEET	** 123	FW-S
2	INDEX OF SHEETS	* 124	PSET-RP
3 - 6	TYPICAL SECTIONS	** 125	PSET-SC
7, 7A - 7G	GENERAL NOTES	** 126	PSET-SP
8, 8A - 8C	ESTIMATE & QUANTITY	** 127	CH-PW-0
9 - 19	QUANTITY SUMMARIES	** 128	PW
TRAFFIC CONTROL PLAN			
20	CONSTRUCTION SEQUENCE NARRATIVE	** 129-130	SCC-3 & 4
21	TRAFFIC CONTROL RAIL RETROFIT LAYOUT	** 131-132	SCC-5 & 6
TRAFFIC CONTROL PLAN STANDARDS			
* 22 - 33	BC(1)-21 THRU BC(12)-21	** 133-134	SCC-7
34	TREATMENT FOR VARIOUS EDGE CONDITIONS	** 135-136	SCC-8
* 35	TCP(1-1)-18	** 137-138	SCC-9
* 36	TCP(1-2)-18	** 139	SCC-MD
* 37	TCP(1-7)-11	* 140	SCP-4
* 38	TCP(2-1)-18	* 141	SCP-5
* 39	TCP(2-2)-18	* 142	SCP-MD
* 40	TCP(2-8)-23	* 143	SETP-PD
* 41	TCP(3-1)-13	* 144	PB
* 42	TCP(3-3)-14	* 145	PJB
* 43	TCP(7-1)-13	* 146	PDD
* 44 - 45	CSB(1)-10	** 147	PBGC
* 46	ABSORB(M)-19	* 148-149	PSL
* 47	SLED-19	** 150-151	SRR
* 48	WZ(RS)-22	SIGNING DETAILS	
* 49	WZ(STPM)-23	152-155	EXISTING SMALL SIGN INVENTORY
* 50	WZ(UL)-13	156-167	SUMMARY OF SMALL SIGNS
ROADWAY DETAILS			
51 - 77	ROADWAY PLAN LAYOUTS	168-170	SIGN DETAILS
78	BRIDGE PLAN LAYOUT	SIGNING STANDARDS	
79 - 81	SUPERELEVATION TABLE	* 171	SMD(GEN)-08
82	MISCELLANEOUS DETAILS	* 172	SMD(SLIP-1)-08
83 - 84	DRIVEWAY DETAILS	* 173	SMD(SLIP-2)-08
85	MAILBOX TURNOUT DETAILS	* 174	SMD(SLIP-3)-08
86	ABUTMENT EROSION REPAIR DETAILS	* 175	TSR(3)-13
87	PILE ENCASMENT DETAILS	* 176	TSR(4)-13
ROADWAY DETAILS STANDARDS			
* 88	TREE TRIMMING & BRUSH REMOVAL	* 177	TSR(5)-13
* 89	TE(HMAC)-11	PAVEMENT MARKINGS & DELINATION STANDARDS	
* 90	MB(1)-21	* 178	D&OM(1)-20
* 91	MB(2)-21	* 179	D&OM(2)-20
* 92	MB(3)-21	* 180	D&OM(3)-20
* 93	MB(4)-21	* 181	D&OM(4)-20
* 94	GF(31)-19	* 182	D&OM(5)-20
* 95 - 96	GF(31)TR TL3-20	* 183	D&OM(VIA)-20
* 97	BED-14	* 184	PM(1)-22
* 98	SGT(12S)31-18	* 185	PM(2)-22
* 99	SGT(15)31-20	* 186	RS(3)-23
100-101	TYPE T131RC	* 187	RS(4)-23
ROADWAY DETAILS STANDARDS			
102	OVERALL DRAINAGE AREA MAP	ENVIRONMENTAL ISSUES	
103	HYDRAULIC DATA COMPUTATIONS	188-189	STORMWATER POLLUTION PREVENTION PLAN (SWP3)
104-119	CULVERT LAYOUTS	190	ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS - EPIC
DRAINAGE DETAILS			
120	BCS	191-216	EROSION CONTROL MEASURES LAYOUTS
** 121	ECD	ENVIRONMENTAL ISSUES STANDARDS	
** 122	FW-0	* 217	EC(1)-16
		* 218	EC(2)-16
		* 219	EC(3)-16
		* 220-222	EC(9)-16



Paul A. Warden, P.E. 5/24/2023

THE STANDARD SHEETS SPECIFICALLY IDENTIFIED BY * HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE SUPERVISION AS BEING APPLICABLE TO THIS PROJECT

_____, P.E. _____
SIGNATURE OF REGISTRANT DATE



Juan E. Trevino-Querra, P.E. 5/24/2023

THE STANDARD SHEETS SPECIFICALLY IDENTIFIED BY ** HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE SUPERVISION AS BEING APPLICABLE TO THIS PROJECT

_____, P.E. _____
SIGNATURE OF REGISTRANT DATE

IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS




FM 512


INDEX OF SHEETS

SHEET 1 OF 1


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	2
CONTROL	SECTION	JOB	
0579	02	014	





FM 512 EXISTING TYPICAL SECTION
STA 0+50.00 TO STA 452+54.00
STA 453+54.00 TO STA 508+53.33



**FM 512 PROPOSED TYPICAL SECTION
HMA OVERLAY**
STA 0+50.00 TO STA 13+50.00



DETAIL AT DRIVEWAY LOCATIONS
STA 0+50.00 TO STA 13+50.00



DETAIL B

SCALE: NTS



Paul A. Warden, P.E. 572412023

IDCUS ENGINEERS PLANNERS MANAGERS
8632 Fredericksburg Rd., Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825




**FM 512
TYPICAL SECTIONS**


SHEET 1 OF 4

			HIGHWAY NO FM 512
STATE TEXAS	DISTRICT PARIS	COUNTY HUNT	SHEET NO 3
CONTROL 0579	SECTION 02	JOB 014	

5/24/2023 6:19:45 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01-GENERAL\FM512_GNTYP_01.dgn




**PROPOSED TYPICAL SECTION
EXISTING ACP AND BASE SCARIFICATION & SUBGRADE WIDENING**
STA 13+50.00 TO STA 452+54.00
STA 453+54.00 TO STA 508+53.33




**PROPOSED TYPICAL SECTION
BASE RESHAPE AND GEOGRID PLACEMENT**
STA 13+50.00 TO STA 452+54.00
STA 453+54.00 TO STA 508+53.33

***WIDTH VARIES AT BRIDGE TRANSITIONS**
23'-3" TO 27'-6" STA 13+50.00 TO STA 14+50.00
27'-6" TO 23'-3" STA 452+04.00 TO STA 452+54.00
23'-3" TO 27'-6" STA 453+54.00 TO STA 454+04.00



DETAIL C



DETAIL D

SCALE: NTS



Paul A. Warden, P.E. 5/24/2023



IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
TYPICAL SECTIONS

SHEET 2 OF 4

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	4
CONTROL	SECTION	JOB	
0579	02	014	



PROPOSED TYPICAL SECTION

STA 13+50.00 TO STA 452+54.00
STA 453+54.00 TO STA 508+53.33

*WIDTH VARIES AT BRIDGE TRANSITIONS
22' TO 26' STA 13+50.00 TO STA 14+50.00
26' TO 24' STA 452+04.00 TO STA 452+54.00
24' TO 26' STA 453+54.00 TO STA 454+04.00

SCALE: NTS



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512




TYPICAL SECTIONS

SHEET 3 OF 4

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	5
CONTROL	SECTION	JOB	
0579	02	014	

5/24/2023 6:19:45 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W42-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01_GENERAL\FM512_GNTYP_01.dgn

5/24/2023 6:19:45 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01_GENERAL\FM512_GNTYP_01.dgn



SCALE: NTS



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
TYPICAL SECTIONS

SHEET 4 OF 4

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	6
CONTROL	SECTION	JOB	
0579	02	014	

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

GENERAL NOTES

General:

Contractor questions on this project are to be addressed to the following individual(s):

Greenville Area Office

James Atkins II, P.E. – James.Atkins@txdot.gov

Willie Bolden II, P.E. - Willie.Bolden@txdot.gov

Contractor questions will be accepted through email, phone, and in person by the above individuals.

Questions may be submitted via the Letting Pre-Bid Q&A web page. This webpage can be accessed from the Notice to Contractors dashboard located at the following Address:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>

All contractor questions will be reviewed by the Engineer. All questions and any corresponding responses that are generated will be posted through the same Letting Pre-Bid Q&A web page.

The Letting Pre-Bid Q&A web page for each project can be accessed by using the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink for the project you want to view the Q&A for and click on the link in the window that pops up.

On Contractor request, earthwork cross sections and construction timelines will be posted to TxDOT's Public FTP at the following Address:

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting%20Responses/>

The site is organized by District, Project Type (Construction or Maintenance), Letting Date, CCSJ/Project Name

Locate equipment a minimum of 30 feet from roadway when possible. Place signs and barricades as approved.

Stockpile sites for construction materials must be approved. Give at least 48 hours notification prior to stockpiling material.

Item 5 Control of the Work:

The responsibility for the construction surveying on this contract will be in accordance with Section 5.9.3, Method C.

Working days will be computed and charged in accordance with Article 8.3.1.4 Standard Work Week.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7

Right and left are determined based upon the forward direction of stationing in the specific control section.

When a precast or cast-in-place concrete element is included in the plans, a precast concrete alternate may be submitted in accordance with "Standard Operating Procedure for Alternate Precast Proposal Submission" found online at <https://www.txdot.gov/inside-txdot/forms-publications/consultants-contractors/publications/bridge.html#design>. Acceptance or denial of an alternate is at the sole discretion of the Engineer. Impacts to the project schedule and any additional costs resulting from the use of alternates are the sole responsibility of the Contractor.

Item 6 Control of Materials:

To comply with the latest provisions of Built America, Buy America Act (BABA Act) of the Bipartisan Infrastructure Law, the contractor must submit a notarized original of the TxDOT Construction Material Buy America Certification Form for all items classified as construction materials. This form is not required for materials classified as a manufactured product.

Refer to the BUY America Classification Sheet for clarification on material categorization.

The buy America Material Classification Sheet is located at the below link.

<https://www.txdot.gov/business/resources/materials/buy-america-material-classification-sheet.html>

Item 7 Legal Relations and Responsibilities:

No significant traffic generator events identified.

Item 8 Prosecution and Progress:

Before beginning work on this project submit in writing, for approval, a plan of construction operations outlining in detail a sequence of work to be followed.

Provide a Bar Chart progress schedule for this project.

This project includes SP 008-003 which allows up to a 90-day delay to begin work on the project to allow for Contractor Mobilization.

SP 008-003 is required to allow for TxDOT to properly staff this project either with in-house or contract forces. This SP also allows the contractor ample time to obtain and schedule resources, material and manpower to ensure continuous prosecution of the work.

Roadway widening operations shall only be allowed on one side of the roadway at a time.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 9 Measurement and Payment:

Items of work for the Monthly Estimate will be cut off on the 25th of each month. Items of work performed after the 25th will be processed and paid on the following month's estimate. Material On Hand (MOH) will cut off on the 20th of each month. Special circumstances will be considered on a case-by-case basis.

Item 100 Preparing Right of Way:

Remove all trees on both sides of roadway to ROW. At cross structures, remove trees to ROW line and within 100' of the structure, parallel to the roadway. Remove underbrush and neatly trim trees and overhanging branches to produce a 60' vertical clear area within the limits of Prep ROW. Remove any trees or underbrush that interferes with any construction operation, including relocation of ditches or other drainage elements. Receive approval of equipment used to trim limbs. A boom axe will not be allowed. Remove all trimmed debris from the ROW or mulch all debris and incorporate into the topsoil on State ROW to the satisfaction of the Engineer.

Item 110 Excavation:

Material below finished subgrade elevation suspected of containing sulfates will be tested in accordance with Tex-145-E by the Department. Treat subgrade material to the required depth and width in accordance with the Soil Sulfates Mitigation General Notes.

Before excavation operations the existing topsoil shall be salvaged in a manner to preserve the vigor of the existing Bermuda grass sod per Item 160.

Item 112 Subgrade Widening:

Limit daily subgrade widening operations to the amount of base widening (proposed depth) that can be completed daily.

All pavement edge drop-offs, at end of day, shall be backfilled in accordance with Edge Treatment Condition I on the "Treatment for Various Edge Conditions" sheet. Backfill material shall be approved by the Engineer.

Item 132 Embankment:

Test potential embankment sources using Tex-145-E to determine the presence and concentration of sulfates. Do not bring soil with greater than 3000 ppm sulfates into project.

Embankment sources containing sulfates that meet specification requirements may be used as fill material provided it is placed with at least one foot of separation from materials to be treated with lime, cement, or other calcium-based stabilizers. When soils are to be placed with less than one foot

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7A

of separation from material to be treated with lime, cement, or other calcium-based stabilizers, process and treat such soils according to the Soil Sulfates Mitigation General Notes.

Excavation pits for project embankment made within 250 feet of State Right of Way must be approved.

Before embankment operations the existing topsoil shall be salvaged in a manner to preserve the vigor of the existing Bermuda grass sod per Item 160.

Item 134 Backfilling Pavement Edges:

The backfill material source shall be approved.

Dirt driveway shaping/construction will be subsidiary to Item 134.

Item 152 Road Grader Work:

Use road grader work to windrow sod (6" depth), construct slopes, construct/repair dirt driveways, prepare driveways for surfacing, grade ditches as necessary to establish drainage and redistribute sod on finished slopes.

Cut ditches to proposed grade in the immediate vicinity of cross drain structures prior to placing Storm Water BMP devices at the early stages of the project.

If excess material is generated under this item, it may be utilized to construct slopes, or wasted as approved.

Item 164 Seeding for Erosion Control, 166 Fertilizer:

Apply fertilizer with a ratio of 3-1-2 (N-P-K) over the areas to be seeded. This work will not be paid for directly, but will be considered subsidiary.

Item 168 Vegetative Watering:

Use water trucks equipped with a sprinkler system adequate to permit coverage of the entire seeded area from the roadbed. This equipment must be available to perform watering throughout the duration of vegetative establishment.

Water all seeded areas the day seed is applied. Thereafter, maintain the seeded areas in a well-watered condition throughout the duration of vegetative establishment.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 247 Flexible Base:

Grading requirements
Tests to be in accordance with TxDOT Standard Test Methods

Item Desc.	Soil Constants			
	Linear Shrinkage	LL	Wet Ball	WBMV (incr. passing #40 sieve)
Item 247 Flex Base	6.0 max.	40 max.	40 max.	20% max.
PERCENT RETAINED ON SIEVE:				
1-3/4"	7/8"	3/8"	No. 4	No. 40
0	10-35	30-50	45-65	70-85

Flexible Base will not contain more than 1% by weight of clay balls.

Place blue top hubs for alignment and elevations of new base at centerline and edge of pavement.

Measure roadway profile smoothness prior to the cover prime or prime course application.

Provide all profile measurements to the Engineer in electronic data files prior to the placement of the prime/cover prime coat using the format specified in Tex-1001-S. The Engineer will use Department software to evaluate longitudinal profiles to determine areas requiring corrective action. Correct 0.1-mi. sections having an average international roughness index (IRI) value greater than 100.0 in. per mile to an IRI value of 100.0 in. per mile or less. The average IRI for the left and right wheel paths will be used to determine acceptance for each 0.1-mi. section. However, the Engineer reserves the right to have the contractor correct isolated imperfections even if the 0.1-mi. section has a passing IRI. This work will be performed at the contractor's expense. Once all corrections have been made, the prime/cover prime coat may be applied.

Re-profile and correct sections that fail to maintain ride quality until placement of the first seal coat, as directed. Correct re-profiled sections until specification requirements are met, as approved. In the spirit of partnering, the department will participate in 50% of an agreed upon cost of repair for any section that has to be subjected to traffic throughout the winter with only a cover prime coat.

Item 251 Reworking Base Courses:

Full depth HMAC patching and stabilized areas of various depths are to be expected and are to be reworked into existing base. Stabilized areas may include but are not limited to cement, fly ash, or asphalt treated base.

Areas with deep asphaltic patching or widening will require processing and relocation operations to incorporate additional flex base to reduce the asphaltic material ration to a 50% maximum by volume. This work will be subsidiary to this Item.

The finished roadway must match existing grades at project limits, highway intersections and

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7B

bridges. In these areas, salvage existing base and remove sufficient subgrade material to construct the full-depth proposed pavement section, according to the transition details shown in the plans. This removal will not be paid for directly, but will be considered subsidiary to the various bid items. Excess subgrade material generated by these transitions may be utilized to construct slopes or wasted as approved by the Engineer.

Item 275 Cement Treatment (Road Mixed):

Microcracking is required where flexible base widths accept full roller width. When temperatures during curing period average below 60 degrees F, perform microcracking operations between 48 and 72 hours.

Subgrade, embankment or backfill suspected of containing sulfates will be tested in accordance with Tex-145-E by the Department. Subgrade, embankment or backfill material within one foot of any area to be treated using cement is subject to the following restriction:

Greater than 7,000 ppm sulfates – Do not treat with any cement or other calcium-based stabilizers. Material within one foot of any area to be treated with cement or other calcium-based stabilizers must be removed or processed as directed.

Item 302 Aggregates for Surface Treatments:

Use unmodified AC or PG for pre-coating aggregate. Emulsion pre-coating will not be allowed.

Use liquid antistripping or other approved antistripping agent complying with the requirements of Item 301 Asphalt Antistripping Agents. The aggregate will be evaluated for moisture susceptibility using test method TEX-530-C.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 316 Surface Treatments:

Unless otherwise permitted by the Engineer in writing, the open season for asphalt placement will be:

May 15- August 31 for AC

Permission to place asphalt outside of the open season may require the contractor to place a fog seal at the contractor's expense.

***Rates For Construction Projects**

First Course

ITEM	APPLICATION	
	Cover Prime	1 st Course
*Asphalt Type	RC-250	AC-20XP
*Asph. Rate (Gal/SY)	0.28	0.46
Aggregate Type	B	B
Aggregate Grade	5	3
Aggr. Rate (CY/SY)	1:140	1:105
Min. Cure Time	14 days **	

Second Course

ITEM	APPLICATION	
	2 nd Course	
*Asphalt Type	AC-20XP	
*Asph. Rate (Gal/SY)	0.36	
Aggregate Type	PB	
Aggregate Grade	4	
Aggr. Rate (CY/SY)	1:120	

* The information above is intended to provide general guidance and as a basis of estimate. Based on the season and weather conditions at the time, the engineer will determine the asphalt type and rates to be used at the time of application.

** Or as approved by the Engineer

Item 354 Planing and Texturing Pavement:

Plane full width by end of work day.

RAP that is not to be used on this project will become the property of TXDOT. Transfer these millings directly into trucks, and transport directly to the stockpile site located at 1600 Joe Ramsey Blvd, Greenville Tx, or as approved. At the end of the project, shape each stockpile for measurement as directed.

Provide a RAP accountability plan that is acceptable to the Area Engineer.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7C

All bridges will be planed down to the existing concrete bridge deck. After planing the existing asphalt off the bridge decks, the bridge decks must be inspected by Justin Ferguson, Bridge Inspector at Paris District Headquarters, to evaluate the current condition of the bridge deck. The inspection must be done before the seal coat/tack coat operation on the bridge decks.

Justin Ferguson
Justin.Ferguson@txdot.gov
(903)-583-9523

Item 400 Excavation and Backfill for Structures:

Excavation and backfill for bridge, culvert and Safety End Treatment construction/installation will be subsidiary to Item 462, 464, 466, and 467.

Pavement markings and RPM replacement will be subsidiary to "Cut and Restore Pavement".

Cut and Restore Pavement: Backfill to top of pipe using HES flowable fill. Use an accelerator that produces a minimum strength of 250 psi in 4 hours. Provide rheofill or equivalent to ensure flowability. Anchor pipes to ensure no movement or displacement by the flowable fill. Furnish paper type cylinder test molds. Place flowable fill from the top of the pipe to within 10" of the existing pavement surface. Place Type B or C HMA from the top of the flowable fill to the existing roadway surface. These items will be subsidiary to this item and will not be paid for directly.

Item 402 Trench Excavation Protection:

Submit a Trench Excavation Protection Plan to the Engineer a minimum of three weeks prior to use. The excavation support plan shall address excavation/protection methods, work sequencing, traffic control, backfill operations, etc.

Item 403 Temporary Special Shoring:

Submit a Temporary Special Shoring Plan to the Engineer a minimum of three weeks prior to use. The excavation support plan shall address excavation/protection methods, work sequencing, traffic control, backfill operations, etc.

Item 432 Riprap:

The Engineer may adjust placement of riprap in the field.

Filter fabric is required for stone riprap.

Removed headwall, wingwall and concrete riprap concrete may be used for stone rip rap. Cut protruding rebar within 2" of concrete surface. Maximum waste concrete cobble size shall match proposed stone rip rap Dmax size.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 451 Railing:

Deliver and Stockpile salvaged bridge rail at TXDOT Area Office located at 3001 IH 30 East, Greenville TX.

Item 462 Concrete Box Culverts and Drains:

Required excavation and backfill will be subsidiary to this Item.

Item 464 Reinforced Concrete Pipe:

Required excavation and backfill will be subsidiary to this Item.

Item 465 Manholes and Inlets:

Required excavation and backfill will be subsidiary to this item.

Item 466 Headwalls and Wingwalls:

Unless shown in plans to obtain from offsite source, obtain headwall and wingwall backfill from ROW and perform grading to shape ditch to headwall/wingwall, per Engineers directions. This work will be subsidiary to this Item.

Required excavation, backfill and pipe saw cutting will be subsidiary to this Item.

Removed headwalls and wingwalls may be broken into riprap size pieces (12" average diameter) for use as stone riprap on the project. Cut protruding steel reinforcement flush with concrete pieces. Broken concrete and riprap must be stored according to the requirements for material stockpiles indicated on the BC standards.

Item 467 Safety End Treatment:

Parallel pipe culverts ~ 30" diameter and smaller require precast SET unless directed by the Engineer to use cast-in-place SETs when precast SETs would project over 3" above surrounding ground surface or when otherwise indicated in the plans. Additional work to install cast in place SETs will be subsidiary to this Item.

Cross pipe culverts ~ 30" diameter and smaller require precast SET unless indicated otherwise in the plans.

Repair damage culvert ends prior to SET installation. Straighten CMP ends by straightening or cutting off damaged ends. Paint cut off ends with zinc paint. Repair minor damaged RCP ends with epoxy mortar. This work will be subsidiary to this Item.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7D

When necessary to close connection gaps, grout precast SETs to culvert ends. Materials, labor and equipment will be subsidiary to this item.

On existing CMP parallel culverts with mitered metal ends, construct concrete cast in place SETs or remove the mitered ends and install precast or cast-in-place SETs. Replace/remove existing mitered metal ends that are not 6:1 or flatter.

Required excavation, backfill and pipe saw cutting will be subsidiary to this Item.

Unless shown in the plans to obtain backfill from offsite source, obtain SET backfill from the Right-of-Way. This work will be subsidiary to this Item.

Placement of concrete Riprap between multiple SETs on multiple barrel culverts will be subsidiary to this Item.

During SET installation, unless indicated otherwise in the plans, match SET flow line grade with the culvert flow line grade.

Removal and disposal of existing headwalls for parallel culverts will be subsidiary to this Item. Removed concrete headwalls and wingwalls may be broken into riprap size pieces (12" average diameter) for use as stone riprap. Cut protruding steel reinforcement. Broken concrete and riprap must be stored according to the requirements for material stockpiles indicated on BC(10)-21.

Item 496 Removing Structure:

The Contractor shall coordinate with the county commissioner for transferring salvageable materials such as beams, piling, and concrete riprap. The Contractor shall dispose of remaining materials.

Item 502 Barricades, Signs and Traffic Handling:

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

The following items will be required for flagger on this project:

1. Flaggers are required to wear a white hard hat while performing flagging operations.
2. Flaggers will be required at the intersection of all State maintained roadways.
3. Flaggers may be required at other high traffic generating intersections as deemed necessary by the Area Engineer.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 502 Barricades, Signs and Traffic Handling (Cont.):

The traffic control plan for this contract consists of the installation and maintenance of warning signs and other traffic control devices shown in the plans, specification data which may be included in the general notes, applicable provisions of the Texas Manual on Uniform Traffic Control Devices (TMUTCD), traffic control plan sheets included in the plans, standard BC sheets and Item 502 of the Standard Specifications.

Do not begin Item 502, Barricades, Signs, and Traffic Handling, on the roadway until both of the following conditions are met:

1. The work schedule is approved.
2. No more than 5 workdays will pass between the beginning of Item 502 and the actual commencement of roadway work bid items.

The final estimate will be withheld until all disturbed areas are covered with at least 70% perennial vegetative cover.

Correct all deficiencies within the time frame noted on the Traffic Control Device Inspection Form 599. Failure to make corrections within time frame specified may result in no payment for this Item for the month of the noted deficiency.

Provide shadow vehicles equipped with Truck Mounted Attenuators (TMA) as shown on Traffic Control Plan (TCP) standards.

Ensure that all travel lanes are open at night.

Provide pilot car during one lane/two-way traffic operations.

Provide Pavement Ends CW8-3 (36x36), Loose Gravel CW8-7 (36x36) and No Center line CW 8-12 (36x36) prior to reworking base material per TMUCTD.

Road closures must be approved by the Engineer. Provide a two-week advance notice to the Engineer prior to desired roadway closure period. Begin display of closure information on PCMBs ten days prior to roadway closure.

The total months of barricades includes the number of working days plus the winterization period.

Portable traffic signals for TCP (2-8)-20 PAR, TCP (2-8)-18 will be subsidiary to this Item.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7E

Item 506 Temporary Erosion, Sedimentation & Environmental Controls:

The Temporary Erosion Control measures for this project will consist of using the following items, as directed:

1. Temporary Silt Fence
2. Rock Filter Dams: All rock filter dams shall be installed with 6:1 slopes regardless of their location on the project. Failure to do so will result in no payment for the dam.
3. Erosion control logs.
4. Construction exits.

Silt fences will remain the property of the Contractor upon completion of the project. The final estimate will not be released until all silt fences have been properly removed, or as directed and 70% establishment of vegetative cover is obtained.

Acquire approval for any change to the location of temporary sediment fence, as shown in the plans, prior to installation. Placement of erosion protection devices may be altered, as directed, to satisfy the requirements of the SW3P.

The pay item to remove rock filter dams will require only a partial removal after 70 percent perennial vegetation has been established and approved. When removing the rock filter dams, leave the lower layer of rock adjacent to the ground in place so as not to disturb the soil. Refer to the SW3P sheet for the total disturbed area for the project.

The disturbed area in this project, all project locations in the Contract, and Contractor project specific locations (PSLs) within one mile of the project limits will further establish the authorization requirements for storm water discharges. The Department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans. Obtain any required authorization from the TCEQ for any Contractor PSLs for construction support activities on or off ROW. When the total area disturbed for all projects in the Contract and PSLs within one mile of the project limits exceeds five acres, provide a copy of the Contractors NOI for PSLs on the ROW (to the appropriate MS4 operator when on an off-system route).

Item 512 Portable Traffic Barrier:

PTB stockpiled at 1100 Hillcrest Drive Sulphur Springs, TX 75482 shall be used in this project. At project completion all Portable Traffic Barriers shall be stockpiled at 1100 Hillcrest Drive Sulphur Springs, TX 75482. All stockpiled Portable Traffic Barriers shall be cleaned to the extent that all loose and foreign material is removed. Any damaged PTB, as determined by the Engineer, and shall become the property of the Contractor.

Inspect PTB before bidding and provide necessary connection hardware as required.

Reflectors shall be placed on all PTB as shown on standard BC(7)-21, throughout stage construction. Expense for this work will be subsidiary to this Item.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 540 Metal Beam Guard Fence:

Reinstall removed MBGF and SGT's on the same day.

MBGF delineation shall be installed within ten (10) working days of the completion of each MBGF section. Concrete mow strip is not considered to be a part of this work.

Item 542 Removing Metal Beam Guard Fence:

Removed re-usable MBGF rail shall be stockpiled at the TXDOT Area Office located at 3001 IH 30 East, Greenville TX.

Item 560 Mailbox Assemblies:

Install new mailboxes unless the property owner chooses to have an existing, compliant mailbox reinstalled. Return all custom non-compliant mailboxes to the property owner.

All new mailboxes furnished and installed by the contractor will display the address number using one inch (1") adhesive back numbering. The color, type, and style of numbering shall be consistent throughout the project.

Install Type 2 Mailbox foundations. Set the mailbox foundations in 12" diameter by 30" deep concrete (Class B) foundations.

Item 644 Small Roadside Sign Support and Assemblies:

Upon removal of sign assemblies, deliver sign faces to TxDOT office at 3001 IH 30 East, Greenville TX. Dispose of foundations, posts, and hardware.

Use the Southern Plains style triangular slip base for all post types.

Once the cover prime is completed, the Paris District Traffic Operations office will field verify the need and spacing of chevrons. If this verification results in fewer materials, the Paris District will purchase the excess signs at invoice price.

Remove the existing city street and county road topper from city and county signs and install on the new city street and county road stop sign assemblies. This work will be subsidiary to Item 644.

Stake proposed sign locations and obtain Engineer's approval of locations prior to placing foundations.

Contact the Engineer to obtain updated curve travel speeds before manufacture of curve speed warning signs.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7F

Item 662 Work Zone Pavement Markings:

Non-removable markings may be paint and beads.

Place flexible reflective roadway tabs in accordance with the current WZ (STPM) prior to seal coat operations. Place tabs to indicate the beginning and ending of no passing zones.

Cut, remove and properly dispose of the upright portions of all work zone tabs prior to acceptance of any roadway. Remove entire tab when located on HMAC or concrete surfaces.

Item 666 Reflectorized Pavement Markings:

No stripe will be placed unless the inspector is present and at least 24 hours advance notice has been given by the Contractor.

Lay out pilot lines for approval 24 hours prior to all final pavement marking applications.

Use equipment with footage counters capable of measuring the linear footage placed. Calibrate counters prior to the beginning of striping operations.

Due to problems in traffic handling, do not place a dash center stripe and edge line at the same time.

Item 3076 Dense-Graded Hot-Mix Asphalt:

All surface mixes are to be SAC A.

RAS is not allowed in surface mixes.

Use a self-propelled wheel mounted MTV capable of receiving mix from the haul trucks, separate from the paver. It shall have a minimum storage capacity of approximately 25 tons. It shall be equipped with a pivoting discharge conveyor and shall completely and thoroughly remix the material prior to placement. The effectiveness of the MTV's remixing ability is subject to the approval of the Engineer. In addition, the paver shall have a surge storage insert with a minimum capacity of 20 tons.

Specify Hot Mix Asphalt Concrete (HMAC) or Warm Mix Asphalt (WMA) at the time of design submittal. After design submittal, continue producing the chosen design unless otherwise approved.

RAP from contractor owned sources may be used if the RAP is fractionated. The course fraction of contractor owned RAP will not be allowed if it consists primarily of siliceous aggregates.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet:

Item 3076 Dense-Graded Hot-Mix Asphalt (Cont.):

A tack coat is required for all overlay areas and for all longitudinal joints unless otherwise directed.

Evaluation of the mixture for moisture susceptibility will be performed by using test method TEX 530-C (boil test) and there shall be no evidence of stripping during design verification or at any time during production.

The maximum nighttime paved surface vertical differential will be limited to two inches. Prevent ponding of water on any travel ways that are exposed to traffic.

Perform all sampling for aggregate quality testing on stockpiles at the HMAC plant. Mixture sampling for QC/QA testing will typically be taken from the truck at the plant; however, the Engineer may direct that a sample be taken at any point or location of mixture during production, delivery, or placement.

Preparation and construction of permanent / temporary transitions, terminations of mix courses and transitions to driveways and intersecting roadways is subsidiary to Item 340. This includes all labor, machinery, materials, and incidentals to complete the work including planing, removal, hauling and stockpiling of materials and necessary clean-up.

Item 3096 Asphalts, Oils, and Emulsions:

Provide 1L (1qt.) clean and dry screw top or friction-lid sampling cans as directed.

Furnish at least one sample of each type of asphalt used on the project for QA/QC purposes.

Item 5001 Geogrid Base Reinforcement:

Install Geogrid with at least a 1 ft. overlap along the longest joint when construction sequencing allows as determined by the Engineer.

Install Geogrid per manufacturer's specifications as well with the following exceptions / inclusions:

1. Cascade Base onto Geogrid using a bulldozer to a depth of at least six inches so that no equipment has direct contact with Geogrid. Raise dozer blade gradually as each lift is pushed out over the Geogrid.
2. Do not operate rubber-tired equipment directly on Geogrid unless allowed by the Engineer. Should operating rubber-tired equipment directly on Geogrid be allowed, operate at no more than 5 mph, do not turn tires on the Geogrid or make sudden stops and starts which causes excessive deformation waves. Keep Geogrid taut and flat. Adjustments to Geogrid installation or construction methods may be directed by the Engineer to minimize deformation waves.

County: Hunt

Control: 0579-02-014

Highway: FM 512

Sheet: 7G

3. Sufficiently compact unbound buffer layer directly above Geogrid to achieve the required density in all subsequently constructed pavement layers.

Item 6001 Portable Changeable Message Board:

Three (3) portable changeable message boards are required for advance warning.

Item 6185 Truck Mounted Attenuators:

Shadow vehicles with truck mounted attenuator (TMA) are required on the traffic control plan and TCP standards for this project. The contractor will be responsible for determining if one or more of these traffic control operations will be ongoing at the same time to determine the total number of TMAs needed for the project.



CONTROLLING PROJECT ID 0579-02-014

DISTRICT Paris
HIGHWAY FM 512

Estimate & Quantity Sheet

COUNTY Hunt

ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL
	100-6002	PREPARING ROW	STA	508.000	
	104-6017	REMOVING CONC (DRIVEWAYS)	SY	102.000	
	104-6028	REMOVING CONC (MISC)	SY	49.300	
	110-6003	EXCAVATION (SPECIAL)	CY	106.600	
	112-6001	SUBGRADE WIDENING (ORD COMP)	STA	494.000	
	132-6019	EMBANKMENT (VEHICLE)(ORD COMP)(TY B)	CY	3,560.000	
	134-6001	BACKFILL (TY A)	STA	507.000	
	152-6001	ROAD GRADER WORK (ORD COMP)	STA	507.000	
	164-6009	BROADCAST SEED (TEMP) (WARM)	SY	45,159.000	
	164-6011	BROADCAST SEED (TEMP) (COOL)	SY	45,159.000	
	164-6015	STRAW/HAY MLCH SEED(PERM)(RURAL)(CLAY)	SY	90,317.000	
	168-6001	VEGETATIVE WATERING	MG	1,084.000	
	216-6001	PROOF ROLLING	HR	30.110	
	247-6124	FL BS (RDWY DEL) (TY A GR 4)	TON	2,049.600	
	247-6242	FL BS (CMP IN PLACE)(TY A GR 4)(9")	SY	143,281.600	
	251-6073	REWRKING BS MATL (TY C)(10")(ORD COMP)	SY	121,239.000	
	275-6001	CEMENT	TON	1,014.980	
	275-6079	CEMENT TREAT (NEW BASE)(7")	SY	143,208.000	
	316-6016	ASPH (AC-20XP)	GAL	118,126.200	
	316-6029	ASPH (RC-250)	GAL	40,098.100	
	316-6126	AGGR(TY-PB GR-4 SAC-A)	CY	1,209.600	
	316-6173	AGGR(TY-B GR-3 SAC-B)	CY	1,363.900	
	316-6177	AGGR(TY-B GR-5 SAC-B)	CY	1,022.900	
	354-6016	PLAN & TEXT CONC PAV(0" TO 1-1/2")	SY	49.000	
	354-6049	PLANE ASPH CONC PAV (6")	SY	2,400.000	
	400-6006	CUT & RESTORING PAV	SY	53.000	
	401-6001	FLOWABLE BACKFILL	CY	87.600	
	402-6001	TRENCH EXCAVATION PROTECTION	LF	54.000	
	403-6001	TEMPORARY SPL SHORING	SF	1,849.000	
	420-6071	CL C CONC (COLLAR)	EA	7.000	
	420-6158	CL C CONC(PILE ENCASEMENT)	LF	45.000	
	429-6007	CONC STR REPAIR (VERTICAL & OVERHEAD)	SF	92.000	
	432-6002	RIPRAP (CONC)(5 IN)	CY	92.000	
	432-6031	RIPRAP (STONE PROTECTION)(12 IN)	CY	185.000	
	432-6045	RIPRAP (MOW STRIP)(4 IN)	CY	254.300	
	438-6004	CLEANING AND SEALING EXIST JOINTS(CL7)	LF	99.000	
	451-6004	RETROFIT RAIL (TY T131RC)	LF	200.000	
	462-6051	CONC BOX CULV (5 FT X 3 FT)(EXTEND)	LF	8.000	
	462-6052	CONC BOX CULV (5 FT X 4 FT)(EXTEND)	LF	2.000	
	462-6055	CONC BOX CULV (6 FT X 4 FT)(EXTEND)	LF	6.000	
	462-6059	CONC BOX CULV (7 FT X 4 FT)(EXTEND)	LF	5.000	

ESTIMATE & QUANTITY



DISTRICT	COUNTY	CCSJ	SHEET
Paris	Hunt	0579-02-014	8



CONTROLLING PROJECT ID 0579-02-014

DISTRICT Paris
HIGHWAY FM 512

Estimate & Quantity Sheet

COUNTY Hunt

ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL
	462-6063	CONC BOX CULV (8 FT X 4 FT)(EXTEND)	LF	10.000	
	462-6066	CONC BOX CULV (8 FT X 7 FT)(EXTEND)	LF	6.000	
	462-6067	CONC BOX CULV (8 FT X 8 FT)(EXTEND)	LF	6.000	
	462-6091	CONC BOX CULV (5FT X 2.5FT)	LF	10.000	
	462-6100	CONC BOX CULV (9 FT X 4 FT)(EXTEND)	LF	5.000	
	464-6001	RC PIPE (CL III)(12 IN)	LF	164.000	
	464-6008	RC PIPE (CL III)(36 IN)	LF	134.000	
	465-6126	INLET (COMPL)(PSL)(FG)(3FTX3FT-3FTX3FT)	EA	1.000	
	466-6099	HEADWALL (CH - PW - 0) (DIA= 30 IN)	EA	2.000	
	466-6101	HEADWALL (CH - PW - 0) (DIA= 36 IN)	EA	2.000	
	466-6150	WINGWALL (FW - 0) (HW=3 FT)	EA	2.000	
	466-6151	WINGWALL (FW - 0) (HW=4 FT)	EA	2.000	
	466-6152	WINGWALL (FW - 0) (HW=5 FT)	EA	4.000	
	466-6155	WINGWALL (FW - 0) (HW=8 FT)	EA	2.000	
	466-6156	WINGWALL (FW - 0) (HW=9 FT)	EA	2.000	
	466-6166	WINGWALL (FW - S) (HW=5 FT)	EA	2.000	
	466-6194	WINGWALL (PW - 2) (HW=5 FT)	EA	4.000	
	467-6326	SET (TY II) (12 IN) (RCP) (6: 1) (P)	EA	59.000	
	467-6341	SET (TY II) (15 IN) (RCP) (6: 1) (P)	EA	4.000	
	467-6363	SET (TY II) (18 IN) (RCP) (6: 1) (P)	EA	116.000	
	467-6395	SET (TY II) (24 IN) (RCP) (6: 1) (P)	EA	20.000	
	467-6417	SET (TY II) (30 IN) (RCP) (3: 1) (C)	EA	2.000	
	467-6423	SET (TY II) (30 IN) (RCP) (6: 1) (P)	EA	18.000	
	467-6448	SET (TY II) (36 IN) (RCP) (3: 1) (C)	EA	2.000	
	467-6454	SET (TY II) (36 IN) (RCP) (6: 1) (P)	EA	2.000	
	480-6001	CLEAN EXIST CULVERTS	EA	103.000	
	496-6004	REMOV STR (SET)	EA	2.000	
	496-6005	REMOV STR (WINGWALL)	EA	18.000	
	496-6007	REMOV STR (PIPE)	LF	743.000	
	500-6001	MOBILIZATION	LS	1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	27.000	
	506-6002	ROCK FILTER DAMS (INSTALL) (TY 2)	LF	1,020.000	
	506-6011	ROCK FILTER DAMS (REMOVE)	LF	1,020.000	
	506-6021	CONSTRUCTION EXITS (INSTALL) (TY 2)	SY	444.000	
	506-6024	CONSTRUCTION EXITS (REMOVE)	SY	444.000	
	506-6038	TEMP SEDMT CONT FENCE (INSTALL)	LF	8,343.000	
	506-6039	TEMP SEDMT CONT FENCE (REMOVE)	LF	8,343.000	
	506-6041	BIODEG EROSN CONT LOGS (INSTL) (12")	LF	20.000	
	510-6003	ONE-WAY TRAF CONT (PORT TRAF SIG)	MO	4.000	
	512-6017	PORT CTB (DES SOURCE)(F-SHAPE)(TY 1)	LF	540.000	
	512-6029	PORT CTB (MOVE)(F-SHAPE)(TY 1)	LF	540.000	

ESTIMATE & QUANTITY



DISTRICT	COUNTY	CCSJ	SHEET
Paris	Hunt	0579-02-014	8A



CONTROLLING PROJECT ID 0579-02-014

DISTRICT Paris
HIGHWAY FM 512

Estimate & Quantity Sheet

COUNTY Hunt

ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL
	512-6041	PORT CTB (STKPL)(F-SHAPE)(TY 1)	LF	540.000	
	530-6003	INTERSECTIONS (SURF TREAT)	SY	1,889.930	
	530-6004	DRIVEWAYS (CONC)	SY	85.000	
	530-6005	DRIVEWAYS (ACP)	SY	1,151.000	
	530-6008	TURNOUTS (ACP)	SY	1,668.000	
	530-6016	DRIVEWAYS (BASE)	SY	1,055.000	
	540-6002	MTL W-BEAM GD FEN (STEEL POST)	LF	2,900.000	
	540-6006	MTL BEAM GD FEN TRANS (THRIE-BEAM)	EA	8.000	
	542-6001	REMOVE METAL BEAM GUARD FENCE	LF	1,050.000	
	542-6005	RM MTL BM GD FEN TRANS (T101)	EA	4.000	
	544-6001	GUARDRAIL END TREATMENT (INSTALL)	EA	20.000	
	544-6003	GUARDRAIL END TREATMENT (REMOVE)	EA	12.000	
	545-6003	CRASH CUSH ATTEN (MOVE & RESET)	EA	2.000	
	545-6005	CRASH CUSH ATTEN (REMOVE)	EA	2.000	
	545-6019	CRASH CUSH ATTEN (INSTL)(S)(N)(TL3)	EA	2.000	
	560-6004	MAILBOX INSTALL-S (TWG-POST) TY 2	EA	58.000	
	560-6005	MAILBOX INSTALL-D (TWG-POST) TY 2	EA	6.000	
	560-6006	MAILBOX INSTALL-M (TWG-POST) TY 2	EA	2.000	
	644-6001	IN SM RD SN SUP&AM TY10BWG(1)SA(P)	EA	239.000	
	644-6004	IN SM RD SN SUP&AM TY10BWG(1)SA(T)	EA	4.000	
	644-6007	IN SM RD SN SUP&AM TY10BWG(1)SA(U)	EA	1.000	
	644-6033	IN SM RD SN SUP&AM TYS80(1)SA(U)	EA	4.000	
	644-6037	IN SM RD SN SUP&AM TYS80(1)SA(U-WC)	EA	7.000	
	644-6076	REMOVE SM RD SN SUP&AM	EA	256.000	
	658-6060	REMOVE DELIN & OBJECT MARKER ASSMS	EA	45.000	
	658-6062	INSTL DEL ASSM (D-SW)SZ 1(BRF)GF2(BI)	EA	31.000	
	658-6073	INSTL OM ASSM (OM-2Y)(WC)GND(BI)	EA	50.000	
	662-6008	WK ZN PAV MRK NON-REMOV (W)6"(SLD)	LF	101,607.000	
	662-6035	WK ZN PAV MRK NON-REMOV (Y)6"(BRK)	LF	8,104.000	
	662-6037	WK ZN PAV MRK NON-REMOV (Y)6"(SLD)	LF	55,991.000	
	662-6050	WK ZN PAV MRK REMOV (REFL) TY II-A-A	EA	1,847.000	
	662-6067	WK ZN PAV MRK REMOV (W)6"(SLD)	LF	3,176.000	
	662-6075	WK ZN PAV MRK REMOV (W)24"(SLD)	LF	22.000	
	662-6098	WK ZN PAV MRK REMOV (Y)6"(SLD)	LF	18,000.000	
	662-6111	WK ZN PAV MRK SHT TERM (TAB)TY Y-2	EA	15,540.000	
	666-6042	REFL PAV MRK TY I (W)12"(SLD)(100MIL)	LF	140.000	
	666-6048	REFL PAV MRK TY I (W)24"(SLD)(100MIL)	LF	42.000	
	666-6099	REF PAV MRK TY I(W)18"(YLD TRI)(100MIL)	EA	4.000	
	666-6343	REF PROF PAV MRK TY I(W)6"(SLD)(100MIL)	LF	101,607.000	
	666-6346	REF PROF PAV MRK TY I(Y)6"(BRK)(100MIL)	LF	8,104.000	
	666-6347	REF PROF PAV MRK TY I(Y)6"(SLD)(100MIL)	LF	55,991.000	

ESTIMATE & QUANTITY



DISTRICT	COUNTY	CCSJ	SHEET
Paris	Hunt	0579-02-014	8B



CONTROLLING PROJECT ID 0579-02-014

DISTRICT Paris
HIGHWAY FM 512

Estimate & Quantity Sheet

COUNTY Hunt

ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL
	672-6009	REFL PAV MRKR TY II-A-A	EA	865.000	
	677-6002	ELIM EXT PAV MRK & MRKS (6")	LF	13,600.000	
	3076-6066	TACK COAT	GAL	269.000	
	3076-6068	D-GR HMA TY-D SAC-A PG64-22(EXEMPT)	TON	350.000	
	5001-6002	GEOGRID BASE REINFORCEMENT (TY II)	SY	151,444.000	
	6001-6002	PORTABLE CHANGEABLE MESSAGE SIGN	EA	3.000	
	6185-6002	TMA (STATIONARY)	DAY	518.000	
	6185-6003	TMA (MOBILE OPERATION)	HR	96.000	
	18	SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000	
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000	
1	464-6003	RC PIPE (CL III)(18 IN)	LF	579.000	
1A	464-6003	RC PIPE (CL III)(18 IN)	LF	235.000	
	4122-6023	THERMO PIPE(18")(PP)(TY S)(TY II)	LF	344.000	
2	464-6005	RC PIPE (CL III)(24 IN)	LF	124.000	
3	464-6007	RC PIPE (CL III)(30 IN)	LF	114.000	
3A	464-6007	RC PIPE (CL III)(30 IN)	LF	60.000	
	4122-6025	THERMO PIPE(30")(PP)(TY S)(TY II)	LF	54.000	
2A	4122-6024	THERMO PIPE(24")(PP)(TY S)(TY II)	LF	124.000	

ESTIMATE & QUANTITY



DISTRICT	COUNTY	CCSJ	SHEET
Paris	Hunt	0579-02-014	8C

SUMMARY OF ROADWAY ITEMS																	
DESCRIPTION						100-6002	112-6001	132-6019	134-6001	152-6001	216-6001	247-6124	247-6242	251-6073	275-6001	275-6079	
STA	TO	STA	LENGTH	EXISTING WIDTH	PROPOSED SURFACE AVERAGE WIDTH	PREPARING ROW	SUBGRADE WIDENING (ORD COMP)	* EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	BACKFILL (TY A)	ROAD GRADER WORK (ORD COMP)	PROOF ROLLING	FL BS (RDWY DEL) (TY A GR 4)	FL BS (CMP IN PLACE) (TY A GR 4) (9")	REWRKING BS MATL (TY C) (10") (ORD COMP)	CEMENT	CEMENT TREAT (NEW BASE) (7")	
						STA	STA	CY	STA	STA	HR	TON	SY	SY	TON	SY	
CSJ: 0579-02-014						LF	LF	LF									
0+50.00	TO	13+50.00	1300.00	22	22	13.0			13.0	13.0							
13+50.00	TO	14+50.00	100.00	22	24	1.0	1.0		1.0	1.0	0.06		267	245	1.89	267	
14+50.00	TO	452+04.00	43754.00	22	26	437.5	437.5	2,961.0	437.5	437.5	26.8		126,921	107,427	899.55	126,921	
452+04.00	TO	452+54.00	50.00	22	25	0.5	0.5	250.0	0.5	0.5	0.03		139	123	0.98	139	
452+54.00	TO	453+54.00	100.00	22	24	1.0											
453+54.00	TO	454+04.00	50.00	22	25	0.5	0.5	213.0	0.5	0.5	0.03		139	123	0.98	139	
454+04.00	TO	508+53.33	5449.33	22	26	54.5	54.5		54.5	54.5	3.15		15,743	13,321	111.58	15,743	
SUPERELEVATION												2,049.60					
MAILBOX TURNOUTS																	
PROJECT TOTAL:						508.0	494.0	3,424.0	507.0	507.0	30.11	2,049.60	143,208	121,239	1,014.98	143,208	

* QUANTITY TO BE USED ON PROPOSED MOW STRIP LOCATIONS. REFER TO MISCELLANEOUS DETAILS SHEET.

SUMMARY OF ROADWAY ITEMS														
DESCRIPTION						316-6029	316-6177	316-6016	316-6173	316-6016	316-6126	3076-6066	3076-6068	5001-6002
STA	TO	STA	LENGTH	EXISTING WIDTH	PROPOSED SURFACE AVERAGE WIDTH	ASPH (RC-250)	AGGR (TY-B GR-5 SAC-B)	ASPH (AC-20XP)	AGGR (TY-B GR-3 SAC-B)	ASPH (AC-20XP)	AGGR (TY-PB GR-4 SAC-A)	TACK COAT	D-GR HMA TY-D SAC-A PG64-22 (EXEM PT)	GEOGRID BASE REINFORCEMENT (TY II)
						GAL	CY	GAL	CY	GAL	CY	GAL	TON	SY
CSJ: 0579-02-014						LF	LF	LF						
0+50.00	TO	13+50.00	1300.00	22	22							269.0	284.0	
13+50.00	TO	14+50.00	100.00	22	24	74.7	1.9	122.7	2.5	96.0	2.2			283
14+50.00	TO	452+04.00	43754.00	22	26	35,537.8	906.6	58,383.5	1,208.8	45,691.4	1,057.7			134,216
452+04.00	TO	452+54.00	50.00	22	25	38.9	1.0	63.9	1.3	50.0	1.2			147
452+54.00	TO	453+54.00	100.00	22	24					96.0	2.2			
453+54.00	TO	454+04.00	50.00	22	25	38.9	1.0	63.9	1.3	50.0	1.2			147
454+04.00	TO	508+53.33	5449.33	22	26	4,407.9	112.4	7,241.6	149.9	5,667.3	131.2		66.0	16,651
SUPERELEVATION													66.0	
MAILBOX TURNOUTS										600.0	14.0			
PROJECT TOTAL:						40,098.1	1,022.9	65,875.5	1,363.9	52,250.7	1,209.6	269.0	350.0	151,444

PRIME COURSE
RC/250 @ 0.28 GAL/SY
GR 5 B @ 1CY / 140SY

FIRST COURSE
AC-20XP @ 0.46 GAL/SY
GR 3 B @ 1CY / 105SY

SECOND COURSE
AC-20XP @ 0.36 GAL/SY
GR 4 PB @ 1CY / 120SY

CEMENT TREATMENT
BASED ON AN ASSUMED DRY COMPACTED UNIT WEIGHT OF 135 LBS/CF @ 2% BY WEIGHT
PROOF ROLLING BASED UPON 5000 SY/HR

FLEX BASE
FL BS (RDWY DEL) (TY A GR 4)
ESTIMATE @ WEIGHT OF 135 LBS/CF

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

 **Texas Department of Transportation**

FM 512

QUANTITIY SUMMARIES

SHEET 1 OF 11

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	9
CONTROL	SECTION	JOB	
0579	02	014	

SUMMARY OF TRAFFIC CONTROL ITEMS																		
DESCRIPTION				510-6003	512-6017	512-6029	512-6041	545-6003	545-6005	545-6019	662-6008	662-6035	662-6037	662-6050	662-6067	662-6075	662-6098	662-6111
				ONE-WAY TRAF CONT (PORT TRAF SIG)	PORT CTB (DES SOURCE) (F-SH APE) (TY 1)	PORT CTB (MOVE) (F-SH APE) (TY 1)	PORT CTB (STKPL) (F-SH APE) (TY 1)	CRASH CUSH ATTEN (MOVE & RESET)	CRASH CUSH ATTEN (REMOVE)	CRASH CUSH ATTEN (INSTL) (S) (N) (TL3)	WK ZN PAV MRK NON-REMOV (W) 6" (SLD)	WK ZN PAV MRK NON-REMOV (Y) 6" (BRK)	WK ZN PAV MRK NON-REMOV (Y) 6" (SLD)	WK ZN PAV MRK REMOV (REFL) TY II-A-A	WK ZN PAV MRK REMOV (W) 6" (SLD)	WK ZN PAV MRK REMOV (W) 24" (SLD)	WK ZN PAV MRK REMOV (Y) 6" (SLD)	WK ZN PAV MRK SHT TERM (TAB) TY Y-2
STA	TO	STA	LENGTH (LF)	MO	LF	LF	LF	EA	EA	EA	LF	LF	LF	EA	LF	LF	LF	EA
CSJ: 0579-02-014																		
0+50	TO	508+53	50,803								101,607	8,104	55,991	1,091				15,540
CULVERT 3				1										300	800		6,000	
CULVERT 7				1										300	800		6,000	
RAYS CREEK NBI: 01-117-0-1097-02-001																		
452+54	TO	453+54	100.00	2	540	540	540	2	2	2				156	1,576	22	6,000	
PROJECT TOTAL				4	540	540	540	2	2	2	101,607	8,104	55,991	1,847	3,176	22	18,000	15,540

* BASED ON THREE APPLICATIONS

SUMMARY OF TRAFFIC CONTROL ITEMS							
DESCRIPTION				677-6002	6001-6002	6185-6002	6185-6003
				ELIM EXT PAV MRK & MRKS (6")	PORTABLE CHANGEABLE MESSAGE SIGN	TMA (STATIONARY)	TMA (MOBILE OPERATION)
STA	TO	STA	LENGTH (LF)	LF	EA	DAY	HR
CSJ: 0579-02-014							
0+50	TO	508+53	50,803		3	518	96
CULVERT 3				6,800			
CULVERT 7				6,800			
RAYS CREEK NBI: 01-117-0-1097-02-001							
452+54	TO	453+54	100.00				
PROJECT TOTAL				13,600	3	518	96

SUMMARY OF BRIDGE ITEMS															
DESCRIPTION				110-6003	247-6242	429-6007	401-6001	420-6158	432-6045	438-6004	540-6002	540-6006	544-6001	451-6004	
				EXCAVATION (SPECIAL)	FL BS (CMP IN PLACE) (TY A GR 4) (9")	CONC STR REPAIR (VERTICAL & OVERHEAD)	FLOWABLE BACKFILL	CL C CONC (PILE ENCASEMENT)	RIPRAP (MOW STRIP) (4 IN)	CLEANING AND SEALING EXIST JOINTS (CL7)	MTL W-BEAM GD FEN (STEEL POST)	MTL BEAM GD FEN TRANS (THRUE-BEAM)	GUARDRAIL END TREATMENT (INSTALL)	RETROFIT RAIL (TY T131RC)	
STA	TO	STA	LENGTH	CY	SY	SF	CY	LF	CY	LF	LF	EA	EA	LF	
CSJ: 0579-02-014															
CULVERT 06 NBI: 01-117-0-0579-02-008															
189+28	TO	189+81	52.90					55.1			750		4		
CULVERT 09 NBI: 01-117-0-0579-02-009															
255+72	TO	255+95	22.46					55.6			550		4		
CULVERT 12 NBI: 01-117-0-0579-02-010															
306+79	TO	307+23	44.82					46.4			550		4		
CULVERT 16 NBI: 01-117-0-0579-02-004															
415+81	TO	416+03	21.93					56.2			700	4	4		
RAYS CREEK NBI: 01-117-0-0579-02-001															
452+54	TO	453+54	100.00	106.6	73.6	12	82.6	45.0	41.0	99	350	4	4	200	
PROJECT TOTAL				106.6	73.6	12	82.6	45.0	254.3	99	2,900	8	20	200	

SUMMARY OF REMOVAL ITEMS								
DESCRIPTION				354-6016	354-6049	542-6001	542-6005	544-6003
				PLAN & TEXT CONC PAV (0" TO 1-1/2")	PLANE ASPH CONC PAV (6")	REMOVE METAL BEAM GUARD FENCE	RM MTL BM GD FEN TRANS (T101)	GUARDRAIL END TREATMENT (REMOVE)
STA	TO	STA	LENGTH	SY	SY	LF	EA	EA
CSJ: 0579-02-014								
0+50	TO	452+54	45204.00	49		700		8
452+54	TO	453+54	100.00		2400	350	4	4
453+54	TO	508+53	5499.33					
PROJECT TOTAL:				49	2,400	1,050	4	12

IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
QUANTITIY SUMMARIES


SHEET 2 OF 11

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	10

5/24/2023 6:19:59 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TXDOT\ProjectData\FM 512 (0579-02-014)\CADD\GEN\01-GENERAL\FM512_GNQT_01.dgn

DRIVEWAY NO.	CL STATION	LT/RT	SURFACE	SUMMARY OF DRIVEWAY ITEMS																		
				L (LENGTH)	W (WIDTH)	R1 (RADIUS)	R2 (RADIUS)	AREA	104-6017	530-6003	530-6004	530-6005	530-6016									
				LT	LF	LF	LF	SF	REMOVING CONC (DRIVEWAYS) SY	INTERSECTIONS (SURF TREAT) SY	DRIVEWAYS (CONC) SY	DRIVEWAYS (ACP) SY	DRIVEWAYS (BASE) SY									
CSJ: 0579-02-014																						
1	0+66.34	RT	GRAVEL	8.00	15.00	8.00	8.00	47.40														
2	1+27.91	RT	GRAVEL	8.00	15.00	8.00	8.00	47.40														
3	1+67.29	LT	GRAVEL	8.00	24.00	15.00	15.00	87.70														
4	1+70.61	RT	CONCRETE	8.00	18.00	8.00	8.00	53.40														
5	2+26.72	RT	CONCRETE	8.00	20.00	8.00	8.00	57.30														
6	2+58.03	RT	DIRT/GRAVEL	8.00	18.00	8.00	8.00	53.30														
S PRESTON ST	3+72.31	LT	HMA	264.00	20.00	40.00	40.00	164.80														
7	5+44.17	RT	CONCRETE	8.00	21.00	10.00	10.00	65.60														
8	5+79.17	LT	DIRT	8.00	12.00	8.00	1.00	34.40														
9	5+94.45	LT	CONCRETE	8.00	48.00	15.00	15.00	124.70														
10	7+03.81	LT	CONCRETE	8.00	20.00	8.00	8.00	56.90														
S MILL ST	7+47.56	LT	HMA	258.90	20.00	20.00	20.00	96.40														
CHERRY ST	8+60.11	RT	HMA	248.90	15.00	20.00	12.00	73.20														
11	9+04.08	RT	ASPHALT	8.00	15.00	8.00	8.00	47.40														
S GREENVILLE ST	9+55.94	LT	HMA	271.90	15.00	12.00	12.00	60.00														
12	11+12.27	LT	HMA	8.00	18.00	8.00	8.00	53.30														
13	11+91.45	LT	HMA	8.00	12.00	15.00	8.00	57.00														
COMMERCE ST	12+14.44	LT	HMA	169.70	20.00	30.00	120.00	1649.73														
14	13+85.46	LT	DIRT	8.00	15.00	8.00	8.00	155.90													17.32	
15	14+66.98	LT	FLEX BASE	8.00	18.00	6.00	6.00	159.40													17.71	
16	16+75.91	RT	BASE	8.00	12.00	8.00	8.00	128.40														14.27
17	17+97.04	LT	BASE	8.00	12.00	8.00	8.00	123.40														13.71
S CHERRY ST	21+50.62	RT	HMA	8.00	15.00	12.00	12.00	466.80		51.87												
18	23+53.35	RT	HMA	8.00	12.00	8.00	8.00	123.40													13.71	
19	23+55.09	LT	BASE	8.00	12.00	8.00	8.00	123.90														13.77
20	25+58.81	LT	GRAVEL	8.00	12.00	8.00	8.00	123.40														13.71
21	33+47.18	RT	DIRT	8.00	18.00	8.00	8.00	171.40														19.04
22	35+32.55	RT	GRAVEL	8.00	12.00	8.00	15.00	154.00														17.11
23	39+06.13	LT	ASPHALT	8.00	12.00	12.00	12.00	157.90													17.54	
24	40+51.29	LT	ASPHALT	8.00	12.00	8.00	8.00	123.40													13.71	
25	41+27.11	LT	ASPHALT	8.00	12.00	8.00	8.00	123.40													13.71	
26	48+00.87	LT	ASPHALT	8.00	18.00	8.00	8.00	171.90													19.10	
27	49+25.81	RT	BASE	8.00	24.00	8.00	8.00	219.40														24.38
28	53+35.98	RT	CONCRETE	8.00	14.00	10.00	10.00	154.60	20.29				17.18									
29	55+24.65	RT	BASE	8.00	12.00	8.00	8.00	123.40														13.71
30	56+94.76	RT	CONCRETE	8.00	11.00	8.00	8.00	101.70	13.74				11.30									
31	57+06.26	RT	DIRT	8.00	12.00	8.00	8.00	109.70														12.19
32	57+52.97	LT	DIRT	8.00	14.00	8.00	8.00	139.40														15.49
33	58+31.16	LT	ASPHALT	8.00	12.00	8.00	8.00	123.40													13.71	
34	58+87.71	RT	DIRT	8.00	12.00	8.00	8.00	123.40														13.71
35	60+09.81	RT	ASPHALT	8.00	12.00	8.00	8.00	123.40													13.71	
36	61+20.09	RT	FLEX BASE	8.00	12.00	8.00	8.00	123.40														13.71
37	66+11.9	LT	FLEX BASE	8.00	18.00	12.00	12.00	203.90														22.66
38	69+14.78	RT	ASPHALT	8.00	15.00	8.00	8.00	147.80													16.42	
CR 4817	71+21.20	RT	ASPHALT	30.00	20.00	30.00	30.00	986.28														
39	72+67.20	LT	FLEX BASE	8.00	12.00	8.00	8.00	123.40														13.71
40	73+77.04	RT	CONCRETE	8.00	10.00	5.00	5.00	90.70	12.30				10.08									
41	77+86.89	LT	FLEX BASE	8.00	12.00	15.00	15.00	184.60														20.51
42	80+34.63	LT	HMA	8.00	12.00	8.00	8.00	125.20														13.91
43	80+81.19	RT	FLEX BASE	8.00	10.00	8.00	8.00	105.80														11.76
44	82+08.17	RT	HMA	8.00	15.00	8.00	8.00	147.10														16.34
45	82+14.28	LT	BASE	8.00	15.00	8.00	8.00	147.60														16.40
46	82+54.75	LT	HMA	8.00	12.00	8.00	8.00	125.90														13.99
47	88+94.17	RT	HMA	8.00	18.00	10.00	10.00	186.60														20.73
48	90+18.38	RT	DIRT	8.00	8.00	10.00	10.00	106.60														11.84
49	91+06.40	LT	FLEX BASE	8.00	15.00	15.00	15.00	209.10														23.23
50	95+98.46	RT	FLEX BASE	8.00	15.00	15.00	15.00	208.60														23.18
CR 4719	98+63.88	LT	FLEX BASE	35.00	22.00	30.00	30.00	1335.51		148.39												
51	107+60.36	LT	FLEX BASE	8.00	10.00	8.00	8.00	107.40														11.93
52	110+33.36	LT	HMA	8.00	15.00	10.00	10.00	162.60														18.07
53	114+55.16	LT	HMA	8.00	15.00	10.00	10.00	162.60														18.07
54	120+08.16	LT	BASE	8.00	15.00	8.00	8.00	147.70														16.41
55	127+89.61	LT	FLEX BASE	8.00	12.00	10.00	10.00	138.60														15.40
56	131+90.53	RT	HMA	8.00	12.00	8.00	8.00	123.40														13.71
57	132+82.53	RT	DIRT	8.00	10.00	8.00	8.00	107.40														11.93
58	138+33.23	LT	FLEX BASE	8.00	15.00	18.00	18.00	239.50														26.61
59	150+19.4	LT	CONCRETE	8.00	26.50	7.00	7.00	233.00	31.78				25.89									
CR 4816	150+71.11	RT	BASE	30.00	18.00	15.00	15.00	583.47					64.83									
60	150+83.56	LT	BASE	8.00	15.00	8.00	8.00	147.40														16.38
61	152+16.75	RT	BASE	8.00	12.00	8.00	8.00	123.40														13.71
62	155+18.7	RT	BASE	8.00	12.00	8.00	8.00	123.40														13.71
63	159+93.02	LT	CONCRETE	8.00	17.33	N/A	15.00	183.00	24.19				20.33									
64	167+72.19	LT	BASE	8.00	24.00	12.00	10.00	234.30														26.03
65	168+69.23	LT	HMA	8.00	15.00	N/A	10.00	141.30														

CONT. NEXT SHEET

IDCUS <small>PLANNERS ENGINEERS MANAGERS</small>			8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825		
 Texas Department of Transportation			© 2023		
FM 512					
QUANTITY SUMMARIES					
SHEET 3 OF 11					
			HIGHWAY NO		
			FM 512		
STATE	DISTRICT	COUNTY	SHEET NO		
TEXAS	PARIS	HUNT		11	
CONTROL	SECTION	JOB			
0579	02	014			

100%
SUBMITTAL

5/24/2023 6:20:00 PM Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNET\01_GENERAL\FM512_GNQT_01.dgn

SUMMARY OF DRIVEWAY ITEMS														
DRIVEWAY NO.	CL STATION	LT/RT	SURFACE	L (LENGTH)	W (WIDTH)	R1 (RADIUS)	R2 (RADIUS)	AREA	104-6017 REMOVING CONC (DRIVEWAYS)	530-6003 INTERSECTIONS (SURF TREAT)	530-6004 DRIVEWAYS (CONC)	530-6005 DRIVEWAYS (ACP)	530-6016 DRIVEWAYS (BASE)	
				LT	LF	LF	LF	SF	SY	SY	SY	SY	SY	
				CSJ: 0579-02-014										
67	179+05.69	RT	BASE	8.00	12.00	10.00	10.00	138.60					15.40	
68	183+65.33	RT	HMA	8.00	10.00	10.00	10.00	121.70				13.52		
69	192+81.28	RT	HMA	8.00	12.00	10.00	10.00	137.20				15.24		
70	195+28.33	LT	HMA	8.00	15.00	8.00	8.00	137.20				15.24		
71	204+22.22	LT	HMA	8.00	18.00	10.00	10.00	186.60				20.73		
72	205+94.22	LT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
73	207+26.05	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
74	207+41.67	LT	GRAVEL	8.00	8.00	8.00	8.00	91.40					10.16	
75	208+73.69	LT	HMA	8.00	12.00	6.00	6.00	111.40				12.38		
76	210+78.8	RT	BASE	8.00	12.00	6.00	6.00	111.40					12.38	
77	224+35.32	LT	HMA	8.00	12.00	8.00	8.00	127.00				14.11		
78	227+52.61	RT	DIRT	8.00	22.00	10.00	10.00	218.40					24.27	
79	231+43.99	LT	BASE	8.00	15.00	10.00	10.00	165.90					18.43	
CR 4727	231+53.76	RT	HMA	40.00	22.00	25.00	25.00	1132.48		125.83				
80	234+64.91	RT	BASE	8.00	12.00	15.00	15.00	184.60					20.51	
81	237+43.83	LT	HMA	8.00	13.00	8.00	8.00	131.70				14.63		
82	239+56.20	RT	BASE	8.00	12.00	15.00	15.00	184.60					20.51	
83	245+59.61	LT	BASE	8.00	12.00	10.00	10.00	138.60					15.40	
CR 4722	247+18.35	LT	BASE	30.00	12.00	25.00	25.00	629.68		69.96				
84	247+85.80	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
85	249+90.65	LT	BASE	8.00	12.00	8.00	8.00	122.20					13.58	
86	250+79.91	RT	BASE	8.00	12.00	8.00	8.00	124.80					13.87	
87	251+73.22	RT	BASE	8.00	20.00	10.00	10.00	205.60					22.84	
88	261+53.67	RT	BASE	8.00	12.00	8.00	8.00	126.60					14.07	
89	265+99.03	LT	BASE	8.00	12.00	8.00	8.00	123.80					13.76	
90	266+16.03	RT	HMA	8.00	12.00	8.00	8.00	122.80				13.64		
91	269+76.23	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
92	270+22.23	RT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
93	275+39.46	LT	BASE	8.00	12.00	10.00	10.00	140.50					15.61	
94	279+18.85	RT	HMA	8.00	12.00	8.00	8.00	124.80				13.87		
95	282+16.99	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
96	284+22.66	RT	BASE	8.00	10.00	5.00	5.00	101.10					11.23	
97	285+28.86	LT	HMA	8.00	12.00	10.00	10.00	141.60				15.73		
98	285+33.86	RT	BASE	8.00	10.00	8.00	8.00	106.30					11.81	
99	286+51.75	LT	HMA	8.00	18.00	8.00	8.00	173.90				19.32		
100	287+27.42	RT	BASE	8.00	12.00	8.00	8.00	146.20					16.24	
101	288+80.62	RT	HMA	8.00	18.00	20.00	20.00	276.70				30.74		
102	292+82.80	RT	HMA	8.00	12.00	8.00	8.00	126.20				14.02		
103	296+83.12	RT	DIRT	8.00	12.00	10.00	10.00	138.60					15.40	
104	300+45.57	LT	HMA	8.00	18.00	5.00	5.00	154.70				17.19		
105	301+45.73	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
106	311+50.10	RT	HMA	78.00	15.00	25.00	25.00	330.00				36.67		
107	315+17.54	LT	HMA	8.00	33.00	8.00	8.00	291.40				32.38		
108	316+17.77	RT	BASE	8.00	12.00	8.00	8.00	123.00					13.67	
109	316+67.47	LT	HMA	8.00	15.00	10.00	10.00	164.60				18.29		
110	317+81.07	LT	HMA	8.00	12.00	5.00	5.00	107.10				11.90		
111	320+19.67	LT	GRAVEL	8.00	12.00	15.00	15.00	184.60					20.51	
112	321+59.20	RT	HMA	8.00	15.00	8.00	8.00	147.40				16.38		
CR 4617	324+43.77	LT	HMA	50.00	22.00	50.00	50.00	2267.36		251.93				
CR 4502	324+50.40	RT	HMA	36.00	18.00	15.00	36.00	1025.57		113.95				
113	325+68.51	LT	DIRT	8.00	8.00	8.00	8.00	90.40					10.04	
114	331+76.64	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
115	332+74.21	LT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
116	333+16.66	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
117	336+93.75	LT	HMA	14.60	20.00	30.00	5.00	331.90				36.88		
118	338+11.57	LT	HMA	10.70	26.00	5.00	30.00	260.00				28.89		
119	339+63.21	LT	HMA	8.00	20.00	18.00	18.00	279.50				31.06		
120	340+80.72	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
121	373+93.46	RT	BASE	8.00	14.00	8.00	8.00	139.40					15.49	
122	375+73.28	RT	BASE	8.00	18.00	15.00	15.00	256.70					28.52	
CR 4600	410+76.52	RT	HMA	30.00	24.00	25.00	25.00	1008.27		112.03				
123	419+95.42	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
124	421+30.66	LT	FLEX BASE	8.00	10.00	8.00	8.00	107.40				11.93		
125	423.41.15	RT	FLEX BASE	8.00	12.00	8.00	8.00	123.40				13.71		
126	424+14.20	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
127	424+88.20	RT	BASE	8.00	10.00	8.00	8.00	107.40					11.93	
CR 4601	428+10.13	LT	HMA	30.00	20.00	100.00	20.00	886.40		98.49				
128	433+36.37	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
129	435+65.19	LT	BASE	8.00	15.00	8.00	8.00	147.40					16.38	
130	443+31.40	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	
131	445+05.69	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
132	447+78.40	RT	HMA	8.00	12.00	8.00	8.00	124.90				13.88		
133	450+23.57	RT	BASE	8.00	12.00	8.00	8.00	123.40					13.71	

CONT. NEXT SHEET

8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

IDCUS
PLANNERS ENGINEERS MANAGERS

© 2023

Texas Department of Transportation

FM 512
QUANTITY SUMMARIES

SHEET 4 OF 11

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	12

5/24/2023 6:20:00 PM Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNET\01_GENERAL\FM512_GNQT_01.dgn

FM512_GNQT_01.dgn

SUMMARY OF DRIVEWAY ITEMS														
DRIVEWAY NO.	CL STATION	LT/RT	SURFACE	L (LENGTH)	W (WIDTH)	R1 (RADIUS)	R2 (RADIUS)	AREA	104-6017	530-6003	530-6004	530-6005	530-6016	
									REMOVING CONC (DRIVEWAYS)	INTERSECTIONS (SURF TREAT)	DRIVEWAYS (CONC)	DRIVEWAYS (ACP)	DRIVEWAYS (BASE)	
									SY	SY	SY	SY	SY	
CSJ: 0579-02-014														
134	461+65.48	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
135	474+72.54	LT	BASE	8.00	12.00	8.00	8.00	123.40						13.71
136	479+98.42	RT	DIRT	8.00	12.00	8.00	8.00	123.40						13.71
137	486+38.42	RT	BASE	8.00	12.00	8.00	8.00	123.40						13.71
138	486+75.42	LT	HMA	8.00	10.00	8.00	8.00	107.40				11.93		
139	487+81.42	LT	HMA	8.00	12.00	8.00	8.00	123.70				13.74		
MUD RD	489+14.52	LT	HMA	20.00	15.00	18.00	18.00	396.20		44.02				
140	490+93.99	LT	HMA	8.00	12.00	8.00	8.00	123.70				13.74		
141	491+15.13	RT	HMA	8.00	12.00	8.00	8.00	123.80				13.76		
142	492+46.02	LT	BASE	8.00	10.00	8.00	8.00	107.40						11.93
143	493+24.59	RT	BASE	8.00	12.00	8.00	8.00	123.40						13.71
144	493+65.59	RT	BASE	8.00	12.00	8.00	8.00	123.40						13.71
145	494+11.47	LT	HMA	8.00	12.00	8.00	8.00	123.40				13.71		
146	494+98.88	LT	HMA	8.00	12.00	8.00	8.00	122.60				13.62		
147	496+01.13	RT	HMA	10.00	18.00	8.00	8.00	172.60				19.18		
148	496+13.84	LT	DIRT/GRAVEL	8.00	16.00	8.00	8.00	154.40						17.16
149	496+55.51	LT	HMA	8.00	15.00	8.00	8.00	146.50				16.28		
150	498+32.25	RT	HMA	8.00	10.00	8.00	8.00	116.30				12.92		
151	499+47.29	LT	FLEX BASE	8.00	28.00	8.00	8.00	251.40				27.93		
152	500+05.29	RT	BASE	8.00	12.00	8.00	8.00	130.80						14.53
153	502+44.97	LT	DIRT	8.00	12.00	8.00	8.00	123.40						13.71
154	504+32.26	RT	BASE	8.00	10.00	8.00	8.00	106.80						11.87
FM 118	507+70.7	RT	HMA	120.00	24.00	100.00	100.00	6291.60		699.07				
PROJECT TOTAL									102	1,889.93	85	1,151	1,055	

5/24/2023 6:20:00 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01_GENERAL\FM512_GNQTY_01.dgn

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825

 **Texas Department of Transportation** © 2023

FM 512
QUANTITIY SUMMARIES

SHEET 5 OF 11			HIGHWAY NO. FM 512
STATE TEXAS	DISTRICT PARIS	COUNTY HUNT	SHEET NO. 13
CONTROL 0579	SECTION 02	JOB 014	

**100%
SUBMITTAL**

5/24/2023 6:20:00 PM Z:\Transportation\TxDOT\PS&E\STATEWIDE 36--9DP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01-GENERAL\FM512_GNQT01.dgn

DRIVEWAY NO.	CL STATION	LT/RT	EXIST PIPE TYPE	EXIST PIPE DIAMETER	SUMMARY OF PARALLEL DRAINAGE ITEMS												ALT BID				
					104-6028	420-6071	464-6001	464-6003	464-6005	464-6007	465-6126	467-6326	467-6341	467-6363	467-6395	467-6423	480-6001	496-6007	4122-6023	4122-6024	4122-6025
					REMOVING CONC (MISC)	CL C CONC (COLLAR)	RC PIPE (CL III) (12 IN)	RC PIPE (CL III) (18 IN)	RC PIPE (CL III) (24 IN)	RC PIPE (CL III) (30 IN)	INLET (COMPL) (PSL) (FG) (3FTX3FT -3FTX3FT)	SET (TY II) (12 IN) (RCP) (6: 1) (P)	SET (TY II) (15 IN) (RCP) (6: 1) (P)	SET (TY II) (18 IN) (RCP) (6: 1) (P)	SET (TY II) (24 IN) (RCP) (6: 1) (P)	SET (TY II) (30 IN) (RCP) (6: 1) (P)	CLEAN EXIST CULVERTS	REMOV STR (PIPE)	THERMO PIPE (18") (PP) (TY S) (TY II)	THERMO PIPE (24") (PP) (TY S) (TY II)	THERMO PIPE (30") (PP) (TY S) (TY II)
IN	EA	LF	LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	LF	LF	LF	LF	LF				
CSJ: 0579-02-014																					
S PRESTON ST	3+72.31	LT	RCP	18			3						2			1					
7	5+44.17	RT	RCP	12									2			1					
S GREENVILLE ST	9+55.94	LT	RCP	18												1					
12	11+12.27	LT	CMP	12			24											24			
* 13	11+91.45	LT	CMP	12		2	7			1	1					1					
* COMMERCE ST	12+14.44	LT	RCP	18				6						1							
14	13+85.46	LT	CMP	12		1	24				2					1					
15	14+66.98	LT	RCP	18				8					2			1		3			
16	16+75.91	RT	RCP	18				8					1			1		3			
17	17+97.04	LT	CMP	18									2			1					
S CHERRY ST	21+50.62	RT	RCP	18				12						2		1		3			
18	23+53.35	RT	RCP	12							2					1					
19	23+55.09	LT	RCP	12							2					1					
20	25+58.81	LT	CMP	12														24			
23	39+06.13	LT	CMP	18		1		24					2			1		4			
24	40+51.29	LT	RCP	18				16					2			1		6			
25	41+27.11	LT	RCP	18				36					2					6			
26	48+00.87	LT	CMP	18				24					1								
27	49+25.81	RT	CMP	18																	
28	53+35.98	RT	RCP	12				28													
29	55+24.65	RT	RCP	12			4				2					1		3			
30	56+94.76	RT	RCP	12			11				2					1		8			
31	57+06.26	RT	CMP	12							2					1					
32	57+52.97	LT	RCP	12			4				2					1		3			
33	58+31.16	LT	CMP	18				26						2		1		2			
34	58+87.71	RT	RCP	18									2			1					
35	60+09.81	RT	RCP	12							2					1					
36	61+20.09	RT	CMP	18									2			1					
37	66+11.9	LT	CMP	12		1	24				2					1					
38	69+14.78	RT	CMP	18												1					
CR 4817	71+21.20	RT	CMP	18		1		6						2				3			
39	72+67.20	LT	RCP	12			18				2							16			
40	73+77.04	RT	CMP	18												1					
41	77+86.89	LT	CMP	18												1					
42	80+34.63	LT	CMP	12							2					1					
43	80+81.19	RT	RCP	18				4								1		3			
44	82+08.17	RT	RCP	12							2					1					
45	82+14.28	LT	CMP	12							2					1					
46	82+54.75	LT	CMP	12							2					1					
47	88+94.17	RT	CMP	18																	
49	91+06.40	LT	CMP	24																	
50	95+98.46	RT	CMP	18																	
51	107+60.36	LT	RCP	18				4					2			1		3			
52	110+33.36	LT	CMP	18				24.00					2			1					
53	114+55.16	LT	CMP	18																	
54	120+08.16	LT	CMP	18									2			1					
55	127+89.61	LT	CMP	18									2			1					
56	131+90.53	RT	CMP	18									2			1					
57	132+82.53	RT	RCP	18				4					2			1		3			
58	138+33.23	LT	CMP	18									2			1					
59	150+19.4	LT	CMP	18									2			1					
CR 4816	150+71.11	RT	CMP	18									2			1					
60	150+83.56	LT	CMP	18									2			1					
61	152+16.75	RT	CMP	18									2			1					
62	155+18.7	RT	CMP	18				4					2			1		3			
66	171+80.23	LT	CMP	18									2			1					
67	179+05.69	RT	CMP	18									2			1					
68	183+65.33	RT	RCP	12			4						2			1		3			
69	192+81.28	RT	RCP	12									2			1					
70	195+28.33	LT	CMP	18																	
71	204+22.22	LT	CMP	15									2			1					
72	205+94.22	LT	CMP	12									2			1					
75	208+73.69	LT	CMP	12									2			1					
76	210+78.8	RT	RCP	12				24					2			1		16			
77	224+35.32	LT	RCP	18				4					2			1		3			
81	237+43.83	LT	CMP	24											2						
82	239+56.20	RT	CMP	18																	
83	245+59.61	LT	CMP	12									2			1		3			
84	247+85.80	RT	CMP	12														20			
85	249+90.65	LT	CMP	12				24					2					22			
86	250+79.91	RT	RCP	12									2			1		2			
87	251+73.22	RT	CMP	18																	
88	261+53.67	RT	CMP	12				24					2					24			
89	265+99.03	LT	CMP	18				24					2					24			
90	266+16.03	RT	CMP	18				24					2					20			

* REFER TO DETAIL A

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS

Texas Department of Transportation © 2023


FM 512			
QUANTITIY SUMMARIES			
SHEET 6 OF 11			
STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	14

CONT. NEXT SHEET

100%
SUBMITTAL

5/24/2023 6:20:00 PM
Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNO\01_GENERAL\FM512_GNOQTY_01.dgn

DRIVEWAY NO.	CL STATION	LT/RT	EXIST PIPE TYPE	EXIST PIPE DIAMETER	SUMMARY OF PARALLEL DRAINAGE ITEMS															ALT BID																	
					104-6028	420-6071	464-6001	464-6003	464-6005	464-6007	465-6126	467-6326	467-6341	467-6363	467-6395	467-6423	480-6001	496-6007	4122-6023	4122-6024	4122-6025																
					REMOVING CONC (MISC)	CL C CONC (COLLAR)	RC PIPE (CL III) (12 IN)	RC PIPE (CL III) (18 IN)	RC PIPE (CL III) (24 IN)	RC PIPE (CL III) (30 IN)	INLET (COMPL) (PSL) (FG) (3FTX3FT -3FTX3FT)	SET (TY II) (12 IN) (RCP) (6: 1) (P)	SET (TY II) (15 IN) (RCP) (6: 1) (P)	SET (TY II) (18 IN) (RCP) (6: 1) (P)	SET (TY II) (24 IN) (RCP) (6: 1) (P)	SET (TY II) (30 IN) (RCP) (6: 1) (P)	CLEAN EXIST CULVERTS	REMOV STR (PIPE)	THERMO PIPE (18") (PP) (TY S) (TY II)	THERMO PIPE (24") (PP) (TY S) (TY II)	THERMO PIPE (30") (PP) (TY S) (TY II)																
IN	SY	EA	LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA																				
93	275+39.46	LT	CMP	18												2																					
95	282+16.99	RT	CMP	12													2																				
96	284+22.66	RT	CMP	12															20																		
98	285+33.86	RT	RCP	12							4																										
99	286+51.75	LT	CMP	18																																	
100	287+27.42	RT	CMP	12																																	
102	292+82.80	RT	CMP	18																																	
105	301+45.73	RT	CMP	12																																	
107	315+17.54	LT	CMP	24																																	
108	316+17.77	RT	CMP	2-30																																	
109	316+67.47	LT	RCP	24																																	
110	317+81.07	LT	CMP	18																																	
112	321+59.20	RT	RCP	30	9.3																																
CR 4502	324+50.40	RT	RCP	30								10																									
114	331+76.64	LT	CMP	12																																	
121	373+93.46	RT	RCP	30																																	
CR 4600	410+76.52	RT	RCP	24																																	
123	419+95.42	LT	CMP	12																																	
124	421+30.66	LT	CMP	12																																	
125	423.41.15	RT	CMP	18																																	
126	424+14.20	RT	CMP	18																																	
127	424+88.20	RT	CMP	18																																	
128	433+36.37	RT	CMP	15																																	
129	435+65.19	LT	CMP	18																																	
130	443+31.40	RT	CMP	24																																	
131	445+05.69	LT	RCP	18																																	
132	447+78.40	RT	CMP	18																																	
133	450+23.57	RT	CMP	18																																	
134	461+65.48	LT	RCP	30																																	
135	474+72.54	LT	CMP	18																																	
137	486+38.42	RT	CMP	18																																	
138	486+75.42	LT	RCP	18																																	
139	487+81.42	LT	CMP	24																																	
140	490+93.99	LT	RCP	12																																	
142	492+46.02	LT	RCP	24																																	
143	493+24.59	RT	RCP	18																																	
144	493+65.59	RT	RCP	18																																	
145	494+11.47	LT	RCP	24																																	
146	494+98.88	LT	RCP	18																																	
147	496+01.13	RT	RCP	18																																	
148	496+13.84	LT	RCP	30																																	
149	496+55.51	LT	CMP	30																																	
150	498+32.25	RT	CMP	24																																	
151	499+47.29	LT	CMP	18																																	
152	500+05.29	RT	CMP	18																																	
153	502+44.97	LT	RCP	2-24																																	
154	504+32.26	RT	RCP	18																																	
PROJECT TOTAL					9.3	7	164	579	124	72	1	59	4	116	20	18	89	534				344	124	54													



CULVERT DETAIL A
AT FM 512 AND COMMERCE ST

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx, 78240
(210) 448-1800
FIRM # F-6825
PLANNERS ENGINEERS MANAGERS

 **Texas Department of Transportation**

FM 512
QUANTITY SUMMARIES


SHEET 7 OF 11

STATE			DISTRICT	COUNTY		HIGHWAY NO.
TEXAS			PARIS	HUNT		FM 512
CONTROL		SECTION	JOB		SHEET NO.	15
0579	02		014			

5/24/2023 6:20:01 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W42-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01_GENERAL\FM512_GNQT_01.dgn


SUMMARY OF MAILBOXES							(SEE NOTE 1)	
LOCATION	LT/RT	NUMBER OF BOXES	560-6004	560-6005	560-6006	530-6008	316-6404	316-6405
			MAILBOX INSTALL-S (TWG-POST) TY 2	MAILBOX INSTALL-D (TWG-POST) TY 2	MAILBOX INSTALL-M (TWG-POST) TY 2	TURNOUTS (ACP)	AGGR (TY-PB GR-4 OR TY-PL GR-4 SAC-A)	ASPH (AC-20-5TR OR AC-20XP)
STA			EA	EA	EA	SY	CY	GAL
CSJ: 0579-02-014								
6+57	LT	1	1			29.3	0.2	10.5
13+98	LT	1	1			21.3	0.2	7.7
23+38	LT	1	1			21.3	0.2	7.7
35+42	LT	1	1			29.3	0.2	10.6
38+87	LT	1	1			21.3	0.2	7.7
41+40	LT	1	1			21.3	0.2	7.7
48+15	LT	1	1			21.3	0.2	7.7
53+49	LT	1	1			29.3	0.2	10.6
56+72	LT	1	1			29.3	0.2	10.6
58+11	LT	1	1			21.3	0.2	7.7
60+34	LT	1	1			29.3	0.2	10.6
61+34	LT	1	1			29.3	0.2	10.6
65+88	LT	1	1			21.3	0.2	7.7
69+41	LT	1	1			29.3	0.2	10.6
77+65	LT	1	1			21.3	0.2	7.7
80+15	LT	1	1			21.2	0.2	7.6
82+40	LT	2		1		21.3	0.2	7.7
90+83	LT	1	1			21.3	0.2	7.7
95+69	LT	1	1			28.8	0.2	10.4
110+48	LT	1	1			21.3	0.2	7.7
114+70	LT	1	1			21.3	0.2	7.7
128+02	LT	1	1			21.3	0.2	7.7
152+10	LT	1	1			29.3	0.2	10.6
154+86	LT	1	1			29.3	0.2	10.6
159+70	LT	1	1			21.3	0.2	7.7
168+82	LT	1	1			21.3	0.2	7.7
195+11	LT	2		1		21.2	0.2	7.6
208+52	LT	1	1			21.3	0.2	7.7
234+68	LT	1	1			29.4	0.2	10.6
237+59	LT	1	1			21.3	0.2	7.7
239+56	LT	1	1			29.4	0.2	10.6
245+38	LT	1	1			21.3	0.2	7.7
247+86	LT	1	1			29.3	0.2	10.6
252+30	LT	1	1			30.0	0.2	10.8
261+18	LT	1	1			28.8	0.2	10.4
266+17	LT	2		1		21.3	0.2	7.7
269+68	LT	1	1			29.3	0.2	10.6
278+87	LT	1	1			30.0	0.2	10.8
281+59	LT	1	1			29.3	0.2	10.6
285+44	LT	1	1			21.2	0.2	7.6
287+47	LT	1	1			28.8	0.2	10.4
288+95	LT	4			1	28.8	0.2	10.4
292+81	LT	1	1			28.8	0.2	10.4
300+22	LT	1	1			21.3	0.2	7.7
301+62	LT	1	1			29.3	0.2	10.6
311+45	LT	3			1	29.3	0.2	10.6
316+37	LT	2		1		21.2	0.2	7.6
317+93	LT	1	1			21.2	0.2	7.6
319+98	LT	1	1			21.3	0.2	7.7
321+82	LT	1	1			28.2	0.2	10.2
331+92	LT	1	1			21.3	0.2	7.7
340+98	LT	1	1			21.3	0.2	7.7
420+08	LT	1	1			21.3	0.2	7.7
423+70	LT	1	1			29.3	0.2	10.6
424+96	LT	1	1			29.3	0.2	10.6
427+66	LT	1	1			21.9	0.2	7.9
433+39	LT	1	1			29.3	0.2	10.6
444+86	LT	1	1			21.3	0.2	7.7
450+17	LT	1	1			29.3	0.2	10.6
474+83	LT	1	1			21.3	0.2	7.7
487+94	LT	1	1			21.3	0.2	7.7
490+73	LT	2		1		21.3	0.2	7.7
493+91	LT	1	1			21.3	0.2	7.7
494+78	LT	1	1			21.3	0.2	7.7
495+94	LT	2		1		29.8	0.2	10.7
496+68	LT	1	1			21.5	0.2	7.7
498+29						29.8	0.2	10.7
PROJECT TOTAL			58	6	2	1,668	14	600

NOTE:
1. APPLY SECOND COURSE SURFACE TREATMENT TO MAILBOX TURNOUTS.



IDCUS
PLANNERS ENGINEERS MANAGERS

8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



Texas Department of Transportation

FM 512

QUANTITIY SUMMARIES

SHEET 8 OF 11
HIGHWAY NO
FM 512

STATE	DISTRICT	COUNTY	16
TEXAS	PARIS	HUNT	
CONTROL	SECTION	JOB	
0579	02	014	

SUMMARY OF DRAINAGE ITEMS		104-6028	132-6019	400-6006	401-6001	402-6001	403-6001	429-6007	432-6002	432-6031	462-6051	462-6052	462-6055	462-6059	462-6063	462-6066	462-6067	462-6091	462-6100	464-6007	464-6008	
DESCRIPTION		REMOVING CONC (MISC)	EMBANKMENT (VEHICLE) (OR) (TY B)	CUT & RESTORING PAV	FLOWABLE BACKFILL	TRENCH EXCAVATION PROTECTION	TEMPORARY SPL SHORING	CONC STR REPAIR (VERTICAL & OVERHEAD)	RIPRAP (CONC) (5 IN)	RIPRAP (STONE PROTECTIO N) (12 IN)	CONC BOX CULV (5 FT X 3 FT) (EXTEND)	CONC BOX CULV (5 FT X 4 FT) (EXTEND)	CONC BOX CULV (6 FT X 4 FT) (EXTEND)	CONC BOX CULV (7 FT X 4 FT) (EXTEND)	CONC BOX CULV (8 FT X 4 FT) (EXTEND)	CONC BOX CULV (8 FT X 7 FT) (EXTEND)	CONC BOX CULV (8 FT X 8 FT) (EXTEND)	CONC BOX CULV (5FT X 2.5FT)	CONC BOX CULV (9 FT X 4 FT) (EXTEND)	RC PIPE (CL III) (30 IN)	RC PIPE (CL III) (36 IN)	
CULVERT NO.	STA	SY	CY	SY	CY	LF	SF	SF	CY	CY	LF	LF	LF	LF	LF	LF	LF	LF	LF	LF	LF	
CSJ: 0579-02-014																						
CULVERT 1	30+70.25		4	12.2		22				18											42	
CULVERT 2	44+89.85		5				50		6		8											
CULVERT 3	76+57.36		4				99		9	13.5				6								
CULVERT 4	94+41.83		4	15		10																42
CULVERT 5	162+95.74		7				80		4.6	17								10				
CULVERT 7	228+99.24		6				160		27	44							6					
CULVERT 8	231+94.15		3				70		8.4	13			2									
CULVERT 9	255+83.82																					
CULVERT 10	257+32.72		30				130		22.2								6					
CULVERT 11	295+16.99		14							18												
CULVERT 12	307+00.86																					
CULVERT 13	312+88.60		10				100		15.2							10						
CULVERT 14	370+06.67		27	26		22				48												80
CULVERT 15	375+20.36		10																			12
CULVERT 16	415+92.00	40	7		5			80		13												
CULVERT 17	456+79.07		2					568						5								
CULVERT 18	484+24.53		3					592												5		
PROJECT TOTAL		40	136	53	5	54	1,849	80	92	185	8	2	6	5	10	6	6	10	5	42	134	

SUMMARY OF DRAINAGE ITEMS		466-6099	466-6101	466-6150	466-6151	466-6152	466-6155	466-6156	466-6166	466-6194	467-6417	467-6448	467-6454	480-6001	496-6004	496-6005	496-6007	
DESCRIPTION		HEADWALL (CH - PW - O) (DIA= 30 IN)	HEADWALL (CH - PW - O) (DIA= 36 IN)	WINGWALL (FW - O) (HW=3 FT)	WINGWALL (FW - O) (HW=4 FT)	WINGWALL (FW - O) (HW=5 FT)	WINGWALL (FW - O) (HW=8 FT)	WINGWALL (FW - O) (HW=9 FT)	WINGWALL (FW - S) (HW=5 FT)	WINGWALL (PW - 2) (HW=5 FT)	SET (TY II) (30 IN) (RCP) (3: 1) (C)	SET (TY II) (36 IN) (RCP) (3: 1) (C)	SET (TY II) (36 IN) (RCP) (6: 1) (P)	CLEAN EXIST CULVERTS	REMOV STR (SET)	REMOV STR (WINGWALL)	REMOV STR (PIPE)	
CULVERT NO.	STA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF	
CSJ: 0579-02-014																		
CULVERT 1	30+70.25										2						43	
CULVERT 2	44+89.85				2									1		2		
CULVERT 3	76+57.36					2								1		2		
CULVERT 4	94+41.83											2					50	
CULVERT 5	162+95.74			2										1		2		
CULVERT 7	228+99.24							2						1		2		
CULVERT 8	231+94.15					2								1		2		
CULVERT 9	255+83.82													1				
CULVERT 10	257+32.72						2							1		2		
CULVERT 11	295+16.99	2												1			16	
CULVERT 12	307+00.86													1				
CULVERT 13	312+88.60								2					1		2		
CULVERT 14	370+06.67		2														100	
CULVERT 15	375+20.36												2	1	2			
CULVERT 16	415+92.00													1				
CULVERT 17	456+79.07									2				1		2		
CULVERT 18	484+24.53									2				1		2		
PROJECT TOTAL		2	2	2	2	4	2	2	2	4	2	2	2	14	2	18	209	

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

 **Texas Department of Transportation** © 2023

FM 512
QUANTITY SUMMARIES

SHEET 9 OF 11

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	17

5/24/2023 6:20:01 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01_GENERAL\FM512_GNQT_01.dgn

SUMMARY OF PAVEMENT MARKINGS										
DESCRIPTION				666-6042	666-6048	666-6099	666-6343	666-6346	666-6347	672-6009
				REFL PAV MRK TY I (W)12" (SLD) (100MIL)	REFL PAV MRK TY I (W)24" (SLD) (100MIL)	REF PAV MRK TY I (W)18" (YLD TRI) (100MIL)	REF PROF PAV MRK TY I (W)6" (SLD) (100MIL)	REF PROF PAV MRK TY I (Y)6" (BRK) (100MIL)	REF PROF PAV MRK TY I (Y)6" (SLD) (100MIL)	REFL PAV MRKR TY II-A-A
STA	TO	STA	LENGTH	LF	LF	EA	LF	LF	LF	EA
CSJ: 0579-02-014										
0+50	TO	15+00	1450				2,900		2,900	36
15+00	TO	23+39	839				1,677	210	839	10
23+39	TO	35+29	1190				2,381	298		15
35+29	TO	44+00	871				1,742	218	871	11
44+00	TO	45+50	150				300	38		2
45+50	TO	66+26	2076				4,153	519	2,076	26
66+26	TO	72+00	574				1,147	143		7
72+00	TO	80+79	879				1,758	220	879	11
80+79	TO	102+96	2217				4,435		4,435	55
102+96	TO	111+49	853				1,705	213	853	11
111+49	TO	172+50	6101				12,203	1,525		76
172+50	TO	181+31	881				1,762	220	881	11
181+31	TO	195+00	1369				2,738		2,738	34
195+00	TO	204+25	925				1,849	231	925	12
204+25	TO	208+63	438				877	110		5
208+63	TO	217+44	881				1,762	220	881	11
217+44	TO	232+14	1470				2,941		2,941	37
232+14	TO	238+34	620				1,239	155	620	8
238+34	TO	240+22	188				377	47		2
240+22	TO	249+20	898				1,797	225	898	11
249+20	TO	295+14	4594				9,187		9,187	115
295+14	TO	304+00	886				1,772	222	886	11
304+00	TO	306+66	266				532	67		3
306+66	TO	313+26	660				1,319	165	660	8
313+26	TO	315+18	192				384	48		2
315+18	TO	338+12	2294				4,588		4,588	57
338+12	TO	347+13	901				1,803	225	901	11
347+13	TO	360+63	1350				2,700	338		17
360+63	TO	363+76	313				626	78	313	4
363+76	TO	386+33	2257	140	12	4	4,513		4,513	56
386+33	TO	395+17	884				1,769	221	884	11
395+17	TO	402+67	750				1,500	188		9
402+67	TO	407+42	475				949	119	475	6
407+42	TO	411+72	430				860		860	11
411+72	TO	426+38	1466				2,932	367	1,466	18
426+38	TO	429+96	358				716		716	9
429+96	TO	435+65	569				1,138	142	569	7
435+65	TO	439+15	350				700	88		4
439+15	TO	446+60	745				1,490	186	745	9
446+60	TO	448+50	190				380		380	5
448+50	TO	456+67	817				1,634	204	817	10
456+67	TO	458+17	150				300	38		2
458+17	TO	467+50	933				1,866	233	933	12
467+50	TO	482+51	1500				3,000	375		19
482+51	TO	490+94	843				1,687	211	843	11
490+94	TO	508+53	1759		30		3,519		3,519	44
PROJECT TOTAL				140	42	4	101,607	8,104	55,991	865

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS

 **Texas Department of Transportation**

© 2023

FM 512
QUANTITIY SUMMARIES

SHEET 10 OF 11

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	18
CONTROL	SECTION	JOB	
0579	02	014	

SUMMARY OF SIGNING ITEMS												
DESCRIPTION				644-6001	644-6004	644-6007	644-6037	644-6033	644-6076	658-6060	658-6073	658-6062
				IN SM RD SN SUP&AM TY10BWG (1) SA (P)	IN SM RD SN SUP&AM TY10BWG (1) SA (T)	IN SM RD SN SUP&AM TY10BWG (1) SA (U)	IN SM RD SN SUP&AM TYS80 (1) SA (U -WC)	IN SM RD SN SUP&AM TYS80 (1) SA (U)	REMOVE SM RD SN SUP&AM	REMOVE DELIN & OBJECT MARKER ASSMS	IN STL OM ASSM (OM-2Y) (WC) G ND (BI)	IN STL DEL ASSM (D-SW) SZ 1 (BRF) GF 2 (BI)
STA	TO	STA	LENGTH	EA	EA	EA	EA	EA	EA	EA	EA	EA
CSJ: 0579-02-014												
0+50	TO	508+53	50,803	239	4	1	7	4	256	45	50	31
PROJECT TOTAL				239	4	1	7	4	256	45	50	31

SUMMARY OF SWPPP ITEMS															
DESCRIPTION				164-6009	164-6011	164-6015	168-6001	506-6002	506-6011	506-6021	506-6024	506-6038	506-6039	506-6041	FERTILIZER 3-1-2 *
				BROADCAST SEED (TEMP) (WARM)	BROADCAST SEED (TEMP) (COOL)	STRAW/HAY MLCH SEED (PERM) (R URAL) (CLAY)	** VEGETATIVE WATERING	ROCK FILTER DAMS (INSTALL) (TY 2)	ROCK FILTER DAMS (REMOVE)	CONSTRUCTION EXITS (INSTALL) (TY 2)	CONSTRUCTION EXITS (REMOVE)	TEMP SEDMT CONT FENCE (INSTALL)	TEMP SEDMT CONT FENCE (REMOVE)	BIODEG EROSN CONT LOGS (IN STL) (12")	
STA	TO	STA	LENGTH	SY	SY	SY	MG	LF	LF	SY	SY	LF	LF	LF	LBS
CSJ: 0579-02-014															
0+50	TO	508+53	50,803	45,159	45,159	90,317	1,084	1,020	1,020	444	444	8,343	8,343	20	8,887.2
PROJECT TOTAL				45,159	45,159	90,317	1,084	1,020	1,020	444	444	8,343	8,343	20	8,887.2

* FOR CONTRACTOR INFORMATION ONLY: 2 CYCLES AT 50 LBS. NITROGEN PER ACRE AT 21-7-14 (NPK) ANALYSIS = 0.0492 LBS/SY/CYCLE

** VEGETATIVE WATERING BASED ON 2 APPLICATIONS AT A RATE OF 0.003 MG/SY/CYCLE

5/24/2023 6:20:01 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\01_GENERAL\FM512_GNQT_01.dgn

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS

 **Texas Department of Transportation**


© 2023

FM 512

QUANTITIY SUMMARIES


SHEET 11 OF 11

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	19
CONTROL	SECTION	JOB	
0579	02	014	




**PHASE IV ~ A
DAYTIME OPERATIONS**

* REFER TO "TREATMENT FOR VARIOUS EDGE CONDITIONS" STANDARD



**PHASE IV ~ B
DAYTIME OPERATIONS**



NIGHT TIME TRAFFIC FLOW

PHASE I ~ INITIAL TRAFFIC CONTROL

INSTALL PROJECT LIMIT TRAFFIC CONTROL DEVICES (TCD) PER THE BC STANDARD SHEETS. UTILIZE THE APPLICABLE TCP(2-1)-18 OR TCP(2-2b)-18 LAYOUT FOR RCD INSTALLATION.

PROVIDE PAVEMENT ENDS CW8-3 (36X36), LOOSE GRAVEL CW8-7 (36X36) AND NO CENTER LINE CW 8-12 (36X36), SHOULDER DROP OFF W8-9AT (36X36) SIGNS AS DIRECTED BY THE ENGINEER.

PHASE II ~ EROSION CONTROL

INSTALL EROSION CONTROL DEVICES UTILIZING THE APPLICABLE TCP(2-1)-18 LAYOUT OR TCP(2-2b)-18.

PHASE III ~ CULVERT WORK (CROSS AND PARALLEL CULVERTS)

PERFORM OFF-PAVEMENT CULVERT OPERATIONS UTILIZING THE APPLICABLE TCP(2-1)-18.

PERFORM ON-PAVEMENT CULVERT OPERATIONS UTILIZING TCP(2-2b)-18.

PERFORM OFF-PAVEMENT BOX CULVERT EXTENSIONS UTILIZING TCP(2-2b)-18.

PERFORM BOX CULVERT #3 AND #7 EXTENSIONS WORK UTILIZING TCP(2-8b)-23.

REFER TO BC(10)-21 FOR ADDITIONAL DETAILS WHEN WORK IS NOT IN PROGRESS.

CULVERT WORK MAY PROCEED CONCURRENTLY WITH ROADWAY REHABILITATION WHEN APPROVED BY THE ENGINEER. ADHERE TO THE WORKSHEET FOR EDGE CONDITION TREATMENT TYPES.

PHASE IV ~ ROADWAY REHABILITATION

REFER TO THE TRAFFIC CONTROL PLAN (TCP) TYPICAL SECTIONS FOR CONSTRUCTION WORK AREA AND TRAFFIC FLOW. PERFORM OPERATIONS TO FULL WIDTH BY END OF EACH WORK DAY.

PERFORM PAVEMENT REHABILITATION OPERATIONS UP TO COVERED PRIME UTILIZING TCP(2-2b)-18 AND PLACE WORK ZONE PAVEMENT MARKING UTILIZING TCP (3-1)-13

INSTALL BRIDGE RAIL RETRO-FIT, AND MBGF PRIOR TO WIDENING UTILIZING "TCP RETRO-FIT RAIL LAYOUT" SHEET.

LIMIT ROADWAY REHABILITATION OPERATIONS TO ONE MILE SECTIONS. PRIOR TO ADVANCEMENT TO THE NEXT SECTION, ALL BACKFILLING AND TEMPORARY SEEDING MUST BE COMPLETED AND THE SECTION BE APPROVED BY THE ENGINEER. ADHERE TO THE WORKSHEET FOR EDGE CONDITION TREATMENT TYPES.

PHASE V ~ FINAL PAVEMENT MARKINGS

PLACE TWO COURSE SURFACE TREATMENT UTILIZING TCP(2-2b)-18 AND FINAL PAVEMENT MARKINGS/MARKERS UTILIZING TCP (3-1)-13 AND TCP (3-3)-14 RESPECTIVELY.

PHASE VI ~ SIGN AND SEEDING OPERATIONS

PERFORM SIGN INSTALATION AND SEEDING UTILIZING TCP(2-1)-18.

PHASE VII ~ PROJECT CLEAN UP

REMOVE EROSION CONTROL DEVICES, CONSTRUCTION DEBRIS AND WASTE MATERIAL UTILIZING TCP(2-1)-18.

NOTES:

PRIOR TO A SPECIFIC CONSTRUCTION OPERATION, THE TRAFFIC CONTROL STANDARD SPECIFIED FOR THE CONSTRUCTION PHASE IN THIS NARRATIVE MUST BE EVALUATED THOROUGHLY FOR APPROPRIATENESS.

ALL TRAFFIC CONTROL OPERATIONS MUST ADHERE TO THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) AND THE APPLICABLE TRAFFIC CONTROL STANDARDS. CONSTRUCTION PHASE ORDER MAY BE VARIED WHEN APPROVED BY THE ENGINEER. SUBMIT A WORK AND TRAFFIC CONTROL SEQUENCE PLAN TO THE ENGINEER FOR APPROVAL. ENSURE THAT BOTH TRAVEL LANES ARE OPEN AT NIGHT. PROVIDE ACCESS TO PRIVATE PROPERTY AND PUBLIC ROADS AT ALL TIMES. PROVIDE PILOT CAR DURING ONE LANE/TWO WAY TRAFFIC OPERATIONS. ROAD CLOSURES MUST BE APPROVED BY THE ENGINEER.



Paul A. Warden, P.E. 579412023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS




**FM 512
CONSTRUCTION SEQUENCE
NARRATIVE**


SHEET 1 OF 1

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	20
CONTROL	SECTION	JOB	
0579	02	014	


5/30/2023 10:17:09 AM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\02_TRAFFIC\FM512_TCP_LAYOUT_01.dgn



TRAFFIC CONTROL FOR BRIDGE RAIL RETROFIT WORK



SECTION A-A
STA 452+54.00 TO STA 453+54.00
(MIRROR IMAGE FOR OPPOSITE SIDE OF BRIDGE WORK)
(N. T. S.)



SUMMARY OF PORTABLE CONCRETE TRAFFIC BARRIER LOCATION							
LOCATIONS				L		CCA	
STA	TO	STA	LENGTH	BEG STA	END STA	LENGTH (FT)	EA
452+54	TO	453+54	100.00	450+34	455+74	540	2

NOT TO SCALE

Paul A. Warden P.E. 5/30/2023

IDCUS
PLANNERS ENGINEERS MANAGERS

8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

© 2023

Texas Department of Transportation

FM 512
**TRAFFIC CONTROL
RAIL RETROFIT LAYOUT**

SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	21

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:02 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\02_TRAFF_CONTROL\STDETAILS\bc-21.dgn

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY NOTES:

1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

1. Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).

<p>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov</p>
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS) "
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS




**BARRICADE AND CONSTRUCTION
 GENERAL NOTES
 AND REQUIREMENTS**

BC (1) -21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CR:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0579	02	014	FM 512				
4-03	7-13	DIST	COUNTY		SHEET NO.				
9-07	8-14	5-10	5-21	PARIS	HUNT	22			


DATE: 5/24/2023 6:20:03 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Parish\ProjectData\FM 512 (05179-02-014)\CADD\GN\02_TRAF_CONTS\STDDETAILS\bc-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPICAL LOCATION OF CROSSROAD SIGNS



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
 - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
 - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
 - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
 - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
 - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

T-INTERSECTION



CSJ LIMITS AT T-INTERSECTION

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING^{1,5,6}

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Spacing "x" Feet (Apprx.)
CW20 ⁴	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25			50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"	55	500 ²
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" x 48"	48" x 48"	60	600 ²
			65	700 ²
			70	800 ²
			75	900 ²
			80	1000 ²
			*	* ³


* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

△ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS



When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS



NOTES

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
 - ** CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
 - ◇ Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
 - ◇◇ Contractor will install a regulatory speed limit sign at the end of the work zone.

LEGEND	
—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



BARRICADE AND CONSTRUCTION PROJECT LIMIT


BC(2)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	PARIS	HUNT	23	

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
 - Law enforcement.
 - Flagger stationed next to sign.
 - Portable changeable message sign (PCMS).
 - Low-power (drone) radar transmitter.
 - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:03 PM
FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\02_TRAFFIC\STDETAILS\bc-21.dgn

SHEET 3 OF 12



BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT


BC (3) - 21

FILE:	bc-21.dgn	DW:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0579	02	014	FM 512				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	PARIS	HUNT	24					

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:03 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (05179-02-014)\CADD\GNV02_TRAF_CONT\STDDETAILS\bc-21.dgn


TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS




Attachment to wooden supports will be by bolts and nuts or screws. Use TxDOT's or manufacturer's recommended procedures for attaching sign substrates to other types of sign supports

Nails shall NOT be allowed.
 Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.

Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

STOP/SLOW PADDLES

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflective when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRs standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - Long-term stationary - work that occupies a location more than 3 days.
 - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - Short, duration - work that occupies a location up to 1 hour.
 - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes).

SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS

- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.


BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC (4) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CR:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0579	02	014	FM 512				
9-07	8-14	DIST		COUNTY	SHEET NO.				
7-13	5-21	PARIS		HUNT	25				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:03 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\02\TRAF_CONTS\STDDETAILS\bc-21.dgn




SKID MOUNTED WOOD SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS




GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

GENERAL NOTES

- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
 - No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
 - When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.
- * See BC(4) for definition of "Work Duration."
 - ** Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
 - See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	OW:	TxDOT	CR:	TxDOT
©TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0579	02	014	FM 512				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	PARIS	HUNT	26					

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLRS
High-Occupancy Vehicle	HOV	Tuesday	TUES
Highway	Hwy	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT

Roadway designation # IH-number, US-number, SH-number, FM-number

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT
RIGHT X LANES CLOSED	RIGHT X LANES OPEN
CENTER LANE CLOSED	DAYTIME LANE CLOSURES
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE
EXIT CLOSED	RIGHT LN TO BE CLOSED
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI
XXXXXXXXX BLVD CLOSED	

Other Condition List

ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT *

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List

MERGE RIGHT	FORM X LINES RIGHT
DETOUR NEXT X EXITS	USE XXXXX RD EXIT
USE EXIT XXX	USE EXIT I-XX NORTH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N
TRUCKS USE US XXX N	WATCH FOR TRUCKS
WATCH FOR TRUCKS	EXPECT DELAYS
EXPECT DELAYS	PREPARE TO STOP
REDUCE SPEED XXX FT	END SHOULDER USE
USE OTHER ROUTES	WATCH FOR WORKERS
STAY IN LANE	*

Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXXX TO XXXXXXX
US XXX TO FM XXXX

Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

** Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

** See Application Guidelines Note 6.

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

SHEET 6 OF 12

Texas Department of Transportation		Traffic Safety Division Standard	
BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)			
BC (6) - 21			
FILE:	bc-21.dgn	DN:	TxDOT
©TxDOT	November 2002	CONT:	SECT:
REVISIONS	0579	02	014
9-07	8-14	DIST:	COUNTY:
7-13	5-21	PARIS	HUNT
			SHEET NO. 27


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:04 PM
FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNV\02_TRAFFIC_CONTENT\DETAILS\bc-21.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:04 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAF_CONTS\STDDETAILS\bc-21.dgn

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.



CONCRETE TRAFFIC BARRIER (CTB)


- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES

LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

LOW PROFILE CONCRETE BARRIER (LPCB)




DELINEATION OF END TREATMENTS


END TREATMENTS FOR CTB'S USED IN WORK ZONES

End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS



Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

WARNING LIGHTS

- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B_{FL} or C_{FL} Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

ATTENTION
 Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

FLASHING ARROW BOARDS

SHEET 7 OF 12

TRUCK-MOUNTED ATTENUATORS

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.

Texas Department of Transportation
Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR

BC (7) -21

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		0579 02	014	FM 512
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	PARIS	HUNT	28	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:04 PM FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DPS101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\02_TRAF_CONTS\STDETAILS\bc-21.dgn

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectORIZED space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign
(Maximum Sign Dimension)
Chevron CW1-8, Opposing Traffic Lane
Divider, Driveway sign D70a, Keep Right
R4 series or other signs as approved
by Engineer



12" x 24"
Vertical Panel
mount with diagonals
sloping down towards
travel way

Plywood, Aluminum or Metal sign
substrates shall NOT be used on
plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every third drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (8) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	OW:	TxDOT	CR:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0579	02	014	FM 512				
4-03	8-14	DIST	COUNTY	SHEET NO.					
9-07	5-21	PARIS	HUNT	29					
7-13									


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:04 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-9IDP5101\WA2-TxDOT\Parish\ProjectData\FM 512 (0579-02-01-4)\CADD\DETAILS\BC-21.dgn



FIXED
(Rigid or self-righting)


DRIVEABLE



PORTABLE


VERTICAL PANELS (VPs)

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




OPPOSING TRAFFIC LANE DIVIDERS (OTLD)

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS



LONGITUDINAL CHANNELIZING DEVICES (LCD)

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

GENERAL NOTES

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths * *			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

* * *Taper lengths have been rounded off.
 L=Length of Taper (FT.) W=Width of Offset (FT.)
 S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	PARIS	HUNT	30	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:05 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN02_TRAFFIC_CONTROL\STDETAILS\bc-21.dgn


TYPE 3 BARRICADES

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL



Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.


TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION



PERSPECTIVE VIEW




PLAN VIEW

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.
 42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



TRAFFIC CONTROL FOR MATERIAL STOCKPILES

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (10) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
©TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	PARIS	HUNT	31	

WORK ZONE PAVEMENT MARKINGS

GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:
 YELLOW - (two amber reflective surfaces with yellow body).
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

BC(11)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
	0579	02	014	FM 512
REVISIONS	DIST	COUNTY	SHEET NO.	
2-98 9-07 5-21				
1-02 7-13				
11-02 8-14	PARIS	HUNT		32


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:05 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\02\TRAF_CON\STDDETAILS\bc-21.dgn


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:05 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\02_IRAF_CONTS\STDDETAILS\bc-21.dgn

PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TxDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectorized pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectorized pavement markings.




RAISED PAVEMENT MARKERS

EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectorized pavement markings.




RAISED PAVEMENT MARKERS

LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectorized pavement markings.





RAISED PAVEMENT MARKERS

TWO-WAY LEFT TURN LANE


STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS




SOLID LINES



(FOR LEFT TURN CHANNELIZING LINE OR CHANNELIZING LINE USED TO DISCOURAGE LANE CHANGING.)




BROKEN LINES



REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12

Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."

Texas Department of Transportation
 Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC (12) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CK: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
1-97 9-07 5-21				
2-98 7-13	DIST	COUNTY		SHEET NO.
11-02 8-14	PARIS	HUNT		33

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



DATE: 5/24/2023 6:20:05 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE_36-91DPS101\WA2-TxDOT_Paris\ProjectData\FM 512 (05179-02-014)\CADD\GN\02_TRAFF_CONC\STDETAILS\edgecon-21.dgn

DEFINITION OF TREATMENT ZONES FOR VARIOUS EDGE CONDITIONS



Edge Height (D) in Inches versus Lateral Clearance (Y) in Feet





Edge Condition I
S = (3:1) (or flatter)



Edge Condition II
S = ((2.99):1) to (1:1)



Edge Condition III
S is steeper than (1:1)



FACTORS CONSIDERED IN THE GUIDELINES:


- The "Edge Condition" is the slope (S) of the drop-off (H:V). The "Edge Height" is the depth of the drop-off "D".
- Distance "X" is to be the maximum practical under job conditions. Two feet minimum for high speed conditions. Distance "Y" is the lateral clearance from edge of travel lane to edge of dropoff. Distance "Z" does not have a minimum.
- In addition to the factors considered in the guidelines, each construction zone drop-off situation should be analyzed individually, taking into account other variables, such as: traffic mix, posted speed in the construction zone, horizontal curvature, and the practicality of the treatment options.
- The conditions for indicating the use of positive or protective barriers are given by Zone-5 and Figure-1. Traffic barriers are primarily applicable for high speed conditions. Urban areas with speeds of 30 mph or less may have a lesser need for signing, delineation, and barriers. Right-angled edges, however, with "D" greater than 2 inches and located within a lateral offset of 6 feet, may indicate a higher level of treatment.
- If the distance "Y" must be less than 3 feet, the use of a positive barrier may not be feasible. In such a case, consider either: 1) narrowing the lanes to a desired 11 to 12 feet or 10 foot minimum (see CW20-8 sign), or 2) provide an edge slope such as Edge Condition I.

Zone	Treatment Types Guidelines:
①	No treatment
②	CW 8-11 "Uneven Lanes" signs.
③	CW 8-9a Shoulder Drop-Off" or CW 8-11 signs plus vertical panels.
④	CW8-9a or CW 8-11, signs plus drums. Where restricted space precludes the use of drums, use vertical panels. An edge slope to that of the proferred Edge Condition I.
⑤	Check indications (Figure-1) for positive barrier. Where positive barrier is not indicated, the treatment shown above for Zone-4 may be used after consideration of other applicable factors.

Edge Condition Notes:

- Edge Condition I: Most vehicles are able to traverse an edge condition with a slope rate of (3 to 1) or flatter. The slope must be constructed with a compacted material capable of supporting vehicles.
- Edge Condition II: Most vehicles are able to traverse an edge condition with a slope between (2.99 to 1) and (1 to 1) so long as "D" does not exceed 5 inches. Under-carriage drag on most automobiles will occur when "D" exceeds 6 inches. As "D" exceeds 24 inches, the possibility for rollover is greater in most vehicles.
- Edge Condition III: When slopes are greater than (1 to 1) and where "D" is greater than 2 inches, a more difficult control factor may exist for some vehicles, if not properly treated. For example, where "D" is greater than 2 inches and up to 24 inches different types of vehicles may experience different steering control at different edge heights. Automobiles might experience more steering control differential when "D" is greater than 2 inches and up to 5 inches. Trucks, particularly those with high loads, have more steering control differential when "D" is greater than 5 inches and up to 24 inches. When "D" exceeds 24 inches, the possibility of rollover is greater for most vehicles.
- Milling or overlay operations that result in Edge Condition III should not be in place without appropriate warning treatments, and these conditions should not be left in place for extended periods of time.

FIGURE-1: CONDITIONS INDICATING USE OF POSITIVE BARRIER FOR ZONE 5 ([hatched box])




- $E = ADT \times T$
Where ADT is that portion of the average daily traffic volume traveling within 20 feet (generally two adjacent lanes) of the edge dropoff condition; and, T is the duration time in years of the dropoff condition.
- Figure-1 provides a practical approach to the use of positive barriers for the protection of vehicles from pavement drop-offs. Other factors, such as the presence of heavy machinery, construction workers, or the mix and volume of traffic may make the use of positive barriers appropriate, even when the edge condition alone may not justify the use of a barrier.
- An approved end treatment should be provided for any positive barrier end located within the clear zone.

These guidelines apply to temporary traffic control areas or work zones where continuous pavement edges or drop-offs exists parallel and adjacent to a lane used by traffic. The edge conditions may be present between shoulders and travel lanes, between adjacent or opposing travel lanes, or at intermediate points across the width of the paved surface. Due to the variability in construction operations, tolerances in the variables may be allowed by the engineer. These guidelines do not apply to short term operations. These guidelines do not constitute a rigid standard or policy; rather, they are guidance to be used in conjunction with engineering judgement. These guidelines may be updated on the Design Division's on-line manuals.

Engineer's Seal Date <u>5/24/2023</u>	 TREATMENT FOR VARIOUS EDGE CONDITIONS
FILE: edgecon.dgn DN: CK: DW: CK: © TxDOT August 2000 CONT SECT JOB HIGHWAY REVISIONS 0579 02 014 FM 512 03-01 DIST COUNTY SHEET NO. 08-01 PARIS HUNT 34 9-21	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:06 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAFF_CONTROL\DETAILS\tcp1-1-18.dgn




TCP (1-1a)

WORK SPACE NEAR SHOULDER
 Conventional Roads



TCP (1-1b)

WORK SPACE ON SHOULDER
 Conventional Roads



TCP (1-1c)

WORK VEHICLES ON SHOULDER
 Conventional Roads

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES**
- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - Inactive work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
 - See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
 - CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.



TRAFFIC CONTROL PLAN
CONVENTIONAL ROAD
SHOULDER WORK


TCP (1-1) - 18

FILE: tcp1-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 2-12	PARIS	HUNT	35	
1-97 2-18				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:06 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-9\IDP5101\WA2-TXDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\02_TRAFF_CONTROL\DETAILS\tcp1-2-18.dgn


Warning Sign Sequence in Opposite Direction Same as Below



Channelizing devices separate work space from traveled way



TCP (1-2a)
ONE LANE TWO-WAY CONTROL WITH YIELD SIGNS
 (Less than 2000 ADT - See note 7)



TCP (1-2b)
ONE LANE TWO-WAY CONTROL WITH FLAGGERS

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed * X	Formula L = WS ² / 60	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45		450'	495'	540'	45'	90'	320'	195'	360'
50	L = WS	500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

GENERAL NOTES

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
- Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or R1-2 "YIELD" sign is less than 1500 feet.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.

TCP (1-2a)

- R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
- R1-2 "YIELD" sign with R1-2aP "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.



TCP (1-2b)

- Flaggers should use two-way radios or other methods of communication to control traffic.
- Length of work space should be based on the ability of flaggers to communicate.
- If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
- Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the Engineer.
- Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

		Traffic Operations Division Standard	
TRAFFIC CONTROL PLAN			
ONE-LANE TWO-WAY			
TRAFFIC CONTROL			
TCP (1-2) - 18			
FILE: tcp1-2-18.dgn	DN:	CK:	DW: CK:
© TxDOT December 1985	CON: 0579	SECT: 02	JOB: 014 HIGHWAY: FM 512
REVISIONS: 4-90 4-98 2-94 2-12 1-97 2-18	DIST: PARIS	COUNTY: HUNT	SHEET NO.: 36

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:06 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-9\IDP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\02*TRAF#CONTSTD\DETAILS\tcp1-7.dgn



NOTE: FORM 6(09)-19(E) - Pilot Vehicles using Temporary Traffic Signals - TxDOT, must be filled out each day this preliminary standard is used.

LEGEND			
	Sign		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Temporary or Portable Traffic Signal		Portable Changeable Message Sign (PCMS)
	Flag		Traffic Flow


Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
		✓		

GENERAL NOTES

- Unless otherwise stated in the plans, flags attached to signs are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or, for routine maintenance work, when approved by the Engineer.
- The BE PREPARED TO STOP sign may be installed after the ONE LANE ROAD AHEAD sign, but proper sign spacing shall be maintained.
- ROAD WORK AHEAD sign may be repeated if the visibility of the work zone is less than 1500'.
- If pilot car is used to guide vehicles through traffic control zone, vehicle shall have an identification name displayed and "PILOT CAR, FOLLOW ME" (G20-4) sign or message board mounted in a conspicuous position on rear.
- Channelizing devices are recommended for all applications. Devices may be offset as needed for Maintenance operations.
- See "Recommended Work Zone Settings" chart in the control box for preset programming.
- A temporary STOP line may be used in conjunction with "Stop here on Red" (R10-6).
- Proper alignment of overhead signal with on-coming lane should be ensured.
- A Shadow Vehicle with TMA should be used anytime it can be positioned approximately 30 to 100' in advance of workers exposed to traffic without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.



1.5" Radius, 0.625" Border, 0.375" Indent, Black on White;
 [WAIT FOR] D; [PILOT CAR] D;
 (Must be mounted at 7' height)

Texas Department of Transportation
Traffic Operations Division Standard




**TRAFFIC CONTROL PLAN
 SHORT TERM
 TEMPORARY SIGNALS
 PRELIMINARY STANDARD**

TCP (1-7) - 11

FILE: tcp1-7.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	37	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:07 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAFFIC_CONTROL\TCP2-1-18.dgn



LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	✓

- GENERAL NOTES**
- Flags attached to signs where shown, are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated in the plans, or for routine maintenance work, when approved by the Engineer.
 - Stockpiled material should be placed a minimum of 30 feet from nearest traveled way.
 - Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.
 - See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
 - Inactive work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
 - CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.

Texas Department of Transportation Traffic Operations Division Standard


**TRAFFIC CONTROL PLAN
 CONVENTIONAL ROAD
 SHOULDER WORK**

TCP (2-1) - 18


FILE: tcp2-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 2-12	PARIS	HUNT	38	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:07 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-9\IDP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAFF_CONTROL\DETAILS\tcp2-2-18.dgn



TCP (2-2a)
 2-LANE ROADWAY WITHOUT PAVED SHOULDERS
 ONE LANE TWO-WAY
 CONTROL WITH YIELD SIGNS
 (Less than 2000 ADT - See Note 9)



TCP (2-2b)
 2-LANE ROADWAY WITHOUT PAVED SHOULDERS
 ONE LANE TWO-WAY
 CONTROL WITH FLAGGERS

LEGEND

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	575'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓	✓	

GENERAL NOTES

- Flags attached to signs where shown, are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4 "ONE LANE ROAD XXX FT" sign, but proper sign spacing shall be maintained.
 - Flaggers should use two-way radios or other methods of communication to control traffic.
 - Length of work space should be based on the ability of flaggers to communicate.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.
- TCP (2-2a)**
- The R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work space should be no longer than one half city block. In rural areas, roadways with less than 2000 ADT, work space should be no longer than 400 feet.
 - The R1-2aP "YIELD TO ONCOMING TRAFFIC" sign shall be placed on a support at a 7 foot minimum mounting height.
- TCP (2-2b)**
- Channelizing devices on the center line may be omitted when a pilot car is leading traffic and approved by the Engineer.
 - If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain stopping sight distance to the flagger and a queue of stopped vehicles. (See table above).
 - Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

Texas Department of Transportation


TRAFFIC CONTROL PLAN
ONE-LANE TWO-WAY
TRAFFIC CONTROL

TCP (2-2) - 18


FILE: tcp2-2-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
8-95 3-03	DIST	COUNTY	SHEET NO.	
1-97 2-12	PARIS	HUNT	39	
4-98 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:07 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-9IDP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAFFIC_CONTROL\DETAILS\TCP2-8-23.dgn



TCP (2-8a)
ONE LANE TWO-WAY
TRAFFIC CONTROL WITH YIELD SIGNS
 (Less Than 2000 ADT-See Note 5)



TCP (2-8b)
ONE LANE TWO-WAY
TRAFFIC CONTROL WITH TRAFFIC SIGNAL

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Sign		Traffic Flow
	Flag		Flagger
	Raised Pavement Markers Ty II-AA		Temporary or Portable Traffic Signal

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

GENERAL NOTES

- Flags attached to signs where shown are REQUIRED.
 - When this TCP is used at a location which does not involve a bridge, a 48" x 48" CW20-4D "ONE LANE ROAD AHEAD" signs should be used in lieu of the CW5-3 "ONE LANE BRIDGE" signs. The CW13-1P Advisory Speed Plaque is required with either warning sign.
 - Raised pavement markers shall be placed 40 feet c-c on centerline between DO NOT PASS signs and stop or yield lines.
 - For intermediate term situations, when it is not feasible to remove and restore pavement markings, the channelization must be made dominant by using a very close spacing. This is especially important in locations of conflicting information, such as where traffic is directed over a double yellow centerline. In such locations a maximum channelizing device spacing of 20 feet is recommended. The 20 foot channelizing device spacing recommendation is intended for the area of conflicting information and not the entire work zone.
- TCP (2-8a)**
- Traffic control by CW3-2 "YIELD AHEAD" symbol signs for one lane two-way traffic control operations should be limited to work spaces less than 400 feet long and roadways with less than 2000 ADT. Otherwise, portable traffic signals should be used.
 - If power is available, a flashing beacon should be attached to the CW3-2 "YIELD AHEAD" symbol sign for emphasis.
 - The R1-2 "YIELD" and R1-2aP "TO ONCOMING TRAFFIC" signs and other regulatory signs shall be installed at 7 foot minimum mounting height.
- TCP (2-8b)**
- A list of approved Portable Traffic Signals can be found in the "Compliant Work Zone Traffic Control Devices" list.
 - Portable traffic signals should be located to provide adequate stopping sight distance for approaching motorist (See table above).

Texas Department of Transportation
 Traffic Safety Division Standard


TRAFFIC CONTROL PLAN LONG TERM ONE-LANE TWO-WAY CONTROL

TCP (2-8) -23


FILE: tcp2-8-23.dgn	DN:	CK:	DW:	CK:
© TxDOT April 2023	CONT	SECT	JOB	HIGHWAY
12-85 4-98 2-18	0579	02	014	FM 512
8-95 3-03 4-23	DIST	COUNTY	SHEET NO.	
1-97 2-12	PARIS	HUNT	40	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:08 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DPS101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAFFIC_CONTROL\DETAILS\tcp3-1.dgn



TCP (3-1a)
UNDIVIDED MULTILANE ROADWAY




TRAIL/SHADOW VEHICLE A
 with RIGHT Directional display Flashing Arrow Board

LEGEND			
*	Trail Vehicle	ARROW BOARD DISPLAY	
**	Shadow Vehicle		
***	Work Vehicle		RIGHT Directional
	Heavy Work Vehicle		LEFT Directional
	Truck Mounted Attenuator (TMA)		Double Arrow
	Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)


TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

GENERAL NOTES


- TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used the WORK vehicle must be equipped with an arrow board. The Engineer will determine if the LEAD VEHICLE and/or TRAIL VEHICLE are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
- Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
- "X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY" (CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
- On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the rearmost protection vehicle.




TCP (3-1b)
TWO-WAY ROADWAY WITH PAVED SHOULDERS



TRAIL/SHADOW VEHICLE B
 with Flashing Arrow Board in CAUTION display



TCP (3-1c)
TWO-WAY ROADWAY WITHOUT PAVED SHOULDERS



STRIPING FOR TMA

Texas Department of Transportation
 Traffic Operations Division Standard


**TRAFFIC CONTROL PLAN
 MOBILE OPERATIONS
 UNDIVIDED HIGHWAYS**

TCP (3-1) - 13


FILE: tcp3-1.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	PARIS	HUNT	41	
1-97				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:08 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAFFIC_CONTROL\DETAILS\tcp3-3.dgn




TCP (3-3a)
TWO LANE HIGHWAY WITH PAVED SHOULDERS
(WORK ON TRAVEL LANE)




TCP (3-3b)
TWO LANE HIGHWAY WITHOUT PAVED SHOULDERS
(WORK ON TRAVEL LANE)




TCP (3-3c)
DIVIDED MULTILANE HIGHWAY




TCP (3-3d)
UNDIVIDED MULTILANE HIGHWAY




TRAIL/SHADOW VEHICLE A
 with RIGHT Directional display
 Flashing Arrow Board



TRAIL/SHADOW VEHICLE B
 with Flashing Arrow Board
 in Caution Mode



ADVANCE WARNING VEHICLE



STRIPING FOR TMA

LEGEND			
* Trail Vehicle		ARROW BOARD DISPLAY	
** Shadow Vehicle			
*** Work Vehicle		RIGHT	Directional
Heavy Work Vehicle		LEFT	Directional
Truck Mounted Attenuator (TMA)		DOUBLE	Arrow
Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)	

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

GENERAL NOTES

1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used on two way roads the WORK vehicle must have an arrow board. For divided roadways, the arrow board on the WORK vehicle is optional based on the type of work being performed. The Engineer will determine if the LEAD vehicle and/or TRAIL vehicle are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating, or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE, ADVANCE WARNING and TRAIL VEHICLE are required.
4. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
5. Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
6. Each vehicle shall have two-way radio communication capability.
7. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
8. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
9. X VEHICLE CONVOY (CW21-10cT) or WORK CONVOY (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" x 48" diamond shaped WORK CONVOY (CW21-10T) or X VEHICLE CONVOY (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The X VEHICLE CONVOY sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
10. For divided highways with two or three lanes in one direction, the appropriate LEFT LANE CLOSED (CW20-5bTL), RIGHT LANE CLOSED (CW20-5bTR), or CENTER LANE CLOSED (CW20-5dT) sign should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board may be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
11. A double arrow shall not be displayed on the arrow board on the Advance Warning Vehicle.
12. For divided highways with three or four lanes in each direction, use TCP(3-2).
13. Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
14. The Advance Warning Vehicle may straddle the edgeline when Shoulder width makes it necessary.
15. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a DO NOT PASS (R4-1) sign should be placed on the back of the rearmost protection vehicle.


Traffic Operations Division Standard

TRAFFIC CONTROL PLAN
MOBILE OPERATIONS
RAISED PAVEMENT
MARKER INSTALLATION/REMOVAL
TCP (3-3) - 14

FILE: tcp3-3.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CK: TxDOT
© TxDOT September 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	PARIS	HUNT	42	
1-97 7-14				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or the accuracy of the information contained herein.

DATE: 5/24/2023 6:20:09 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\Project\Signs\Traffic Control Details.dgn



NOTE
 Signing shown for one direction of travel only.

NO PASSING ZONES ON TWO-LANE TWO-WAY ROADS



TABS ON CENTERLINES OF TWO-LANE TWO-WAY ROADS
 For seal coat, micro-surface or similar operations

"DO NOT PASS" SIGN (R4-1) and NO-PASSING ZONES

- A. Prior to the beginning of construction, all currently striped no-passing zones shall be signed with the DO NOT PASS (R4-1) signs and PASS WITH CARE (R4-2) signs placed at the beginning and end of each zone for each direction of travel except as otherwise provided herein. Signs marking these individual no-passing zones need not be covered prior to construction if the signs supplement the existing pavement markings.
- B. At the discretion of the Engineer, in areas of numerous no-passing zones, several zones may be combined as a single zone. If passing is to be prohibited over one or more lengthy sections, a DO NOT PASS sign and a NEXT XX MILES (R20-1TP) plaque may be used at the beginning of such zones. The DO NOT PASS sign and the NEXT XX MILES plaque should be repeated every mile to the end of the no-passing zone. In areas where there is considerable distance between no-passing zones, the end of the no-passing zone may be signed with a PASS WITH CARE sign and a NEXT XX MILES plaque.
- C. Depending on traffic volumes and length of sections, it may be desirable to prohibit passing throughout the project to prevent damage to windshield and lights. The DO NOT PASS sign and NEXT XX MILES plaque should be used and repeated as often as necessary for this purpose. Where several existing zones are to be combined into one individual no-passing zone, the sign at the beginning of the zone should be covered until the surfacing operation has passed this location so as not to have the DO NOT PASS sign conflict with the existing pavement markings. Also, unless one days operation completes the entire length of such combined zones, appropriate DO NOT PASS and PASS WITH CARE signs should be placed at the beginning and end of the no-passing zones where the surfacing operation has stopped for the day.
- D. R4-1 and R4-2 are to remain in place until standard pavement markings are installed.

"NO CENTER LINE" SIGN (CW8-12)

- A. Center line markings are yellow pavement markings that delineate the separation of travel lanes that have opposite directions of travel on a roadway. Divided highways do not typically have center line markings.
- B. At the time construction activity obliterates the existing center line markings (low volume roads may not have an existing centerline), a NO CENTER LINE (CW8-12) sign should be erected at the beginning of the work area, at approximately 2 mile intervals within the work area, beyond major intersections and other locations deemed necessary by the Engineer.
- C. The NO CENTER LINE signs are to remain in place until standard pavement markings are installed.

"LOOSE GRAVEL" SIGN (CW8-7)

- A. When construction begins, a LOOSE GRAVEL (CW8-7) sign should be erected at each end of the work area and repeated at intervals of approximately 2 miles in rural areas and closer in urban areas.
- B. The LOOSE GRAVEL signs are to remain in place until the condition no longer exists.

PAVEMENT MARKINGS

- A. Temporary markings for surfacing projects shall be Temporary Flexible-reflective Roadway Marker Tabs unless otherwise approved by the Engineer. Tabs are to be installed to provide true alignment for striping crews or as directed by the Engineer. Tabs will be placed at the spacing indicated. Tabs should be applied to the pavement no more than two (2) days before the surfacing is applied. After the surfacing is rolled and swept, the cover over the reflective strip shall be removed.
- B. Tabs shall not be used to simulate edge lines.
- C. Tab placement for overlay/inlay operations shall be as shown on the WZ(STPM) standard sheet.

COORDINATION OF SIGN LOCATIONS

- A. The location of warning signs at the beginning and end of a work area are to be coordinated with other signing typically shown on the Barricade and Construction Standards for project limits to ensure adequate sign spacing.
- B. Where possible the ROAD WORK AHEAD (CW20-1D), LOOSE GRAVEL (CW8-7), and NO CENTER LINE (CW8-12) signs should be placed in the sequence shown following the OBEY WARNING SIGNS STATE LAW (R20-3T) and the TRAFFIC FINES DOUBLE (R20-5T) sign, and one "X" sign spacing prior to the CONTRACTOR (G20-6T) sign typically located at or near the limits of surfacing. LOOSE GRAVEL and NO CENTER LINE signs will then be repeated as described above.

Posted Speed *	Minimum Sign Spacing "X" Distance
30	120'
35	160'
40	240'
45	320'
50	400'
55	500'
60	600'
65	700'
70	800'
75	900'

* Conventional Roads Only

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

GENERAL NOTES

1. The traffic control devices detailed on this sheet will be furnished and erected as directed by the Engineer on sections of roadway where tabs must be placed prior to the surfacing operation which will cover or obliterate the existing pavement markings.
2. The devices shown on this sheet are to be used to supplement those required by the BC Standards or others required elsewhere in the plans.
3. Signs shall be erected as detailed on the BC Standards or the Compliant Work Zone Traffic Control Devices List (CWZTCD) on supports approved for Long-Term / Intermediate-Term Work Zone Sign Supports.
4. When surfacing operations take place on divided highways, freeways or expressways, the size of diamond shaped construction warning signs shall be 48" x 48".
5. Signs on divided highways, freeways and expressways will be placed on both right and left sides of the roadway based on roadway conditions as directed by the Engineer.




TRAFFIC CONTROL DETAILS FOR SURFACING OPERATIONS


TCP(7-1)-13

FILE: tcp7-1.dgn	DW: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT March 1991	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-92 4-98	DIST	COUNTY	SHEET NO.	
1-97 7-13	PARIS	HUNT	43	


DATE: 5/24/2023 6:20:09 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TXDOT\Parish\ProjectData\FM 512 (0579-02-014)\CADD\DN\02_TRAF_CONTS\DETAILS\csb110 (2).dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




End View Precast Barrier
 See sheet 2 of 3 for Joint connection Type X




Reinforcement for Precast (CSB) Concrete Safety Barrier (Type 1)
 Showing reinforcement for Joint Type X




DEFORMED BAR ANCHOR DETAILS
 Two (2) Bars required per assembly. Eight (8) required per joint.




UPPER CONNECTION PIPE DETAILS
 One (1) Steel Pipe required per Upper Assembly. Two (2) required per joint.




LOWER CONNECTION PIPE DETAILS
 One (1) Steel Pipe required per Lower Assembly. Two (2) required per joint.




TYPE X JOINT INSTALLATION DETAIL
 Barrier reinforcing and Type X Joint Leave-Out dimensions not shown for clarity.



CONNECTION PLATE DETAILS
 One (1) Plate required per assembly. Four (4) required per joint. All steel fittings for joint Type X shall be galvanized after fabrication in accordance with Item 445.




BARRIER PLAN AT END JOINTS




Welded Wire Reinforcement (WWR) Option for Bars R and S3
(WWR) General Notes

1. Deformed Welded Wire Reinforcement (WWR) shall conform to ASTM A497.
2. Welded wire cage may be cut or bent to accommodate the Type X joint connection and drainage slots, as directed by the Engineer.
3. All reinforcement shall comply with Item 440, "Reinforcing Steel."
4. Combinations of reinforcing steel and WWR will be permitted, as directed by the Engineer. The dimension from the end of the barrier section to the first wire shall not exceed 3".




CONNECTION BOLT OR THREADED ROD DETAIL
 Two (2) Threaded Rods (or Equivalent Hex Hd. Bolts) (w/ Two (2) PL 3/8 x 3 x 3 Plate Washers & Two (2) Std Hex Nuts) required per joint.



ISOMETRIC OF TYPICAL WELDED ASSEMBLY
 Four (4) [2 Upper & 2 Lower] Assemblies required per joint.

Weight of one Precast 30 ft. (CSB) segment = Approx. 6.5 Tons or 440 lbs per ft.



Concrete Safety Barrier

* When 1" ACP is "not" used as lateral support for permanent barrier placement. A permissible method of attaining the equivalent lateral support may be used. See CSB(6) sheet.


GENERAL NOTES

1. Concrete shall be Class H with a minimum compressive strength of 3,600 psi.
2. Where used, rebar reinforcement shall be Grade 60 and conform to ASTM A615.
3. Precast barrier length shall be 30 ft. unless otherwise specified on the plans.
4. All precast barrier edges shall have a 3/4 inch chamfer or tool radius.
5. All concrete, reinforcement, joint connection systems, grout etc. as shown, are considered as part of the barrier payment.
6. All steel assemblies for joint shall be galvanized after fabrication in accordance with Item 445, "Galvanizing."
7. Regardless of the method of handling, barrier lifting points shall be approx. 7.5 feet from the ends of the barrier. Lifting devices and attachments to barrier sections shall be approved by the Engineer.
8. Surface finishing and grouting (where required) shall be two parts sand one part cement with enough water to make the mixture plastic. Grouting shall be done in a manner that will assure a smooth surface. Surface finishing shall be considered subsidiary to the various bid items involved.
9. Conduit trough when required shall be shown elsewhere on the plans, or as directed by the Engineer.


		Design Division Standard	
CONCRETE SAFETY BARRIER (F-SHAPE)			
PRECAST BARRIER (TYPE 1)			
CSB(1)-10			
FILE: csb110.dgn	DN: TxDOT	CK: AM	DW: BD
©TxDOT December 2010	CONT: 0579	SECT: 02	JOB: 014
REVISIONS	DIST: PARIS	COUNTY: HUNT	SHEET NO.: 44

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:09 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91\DP5101\WAZ-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\02_TRAF_CONTS\DETAILS\csb110 (2).dgn



END VIEW (CSB) QUICK-BOLT
 QUICK-BOLT POCKET LOCATIONS




ELEVATION (CSB) QUICK-BOLT
 See Manufacturer's shop drawing for additional details




ELEVATION VIEW SHOWING JOINT CONNECTION
"QUICK-BOLT"

Joint Connection (Type Q)




TOP VIEW
PRECAST (CSB) WITH J-J HOOKS
 See Manufacturer's shop drawing for additional details



END VIEW
J-J HOOK CONNECTION

Joint Connection (Type J)



VIEW FROM ABOVE
J-J HOOK CONNECTION

Proprietary Joint Connections (CSB)

Two proprietary joint connections are acceptable as alternates to the (Type X) connection shown, here on. These joint connections types are:




J-J Hooks by Easi-Set Industries, (800)547-4045
 Quick-Bolt by Bexar Concrete, (210)497-3773

If one of these connection systems are exclusively specified in the plans, prior approval for sole source use must be obtained. Details of the connection components and barrier reinforcement for these systems, will be shown on the manufacturer's shop drawing(s) furnished to the Engineer.

SHEET 2 OF 2

		Design Division Standard	
CONCRETE SAFETY BARRIER (F-SHAPE) PRECAST BARRIER (TYPE 1) CSB(1)-10			
FILE: csb110.dgn	DN: TxDOT	CK: AM	DW: BD
© TxDOT December 2010	CONT SECT	JOB	HIGHWAY
REVISIONS	0579 02	014	FM 512
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	45	


DATE: 5/24/2023
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT Proj\Proj\ProjData\FM 512 (0579-02-014)\CADD\GN\02_TRAF_CONT\STDETAILS\absorbm19 (1).dgn
 DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.



THE ABSORB-M IS A NON-REDIRECTIVE, GATING, CRASH CUSHION DESIGNED TO MEET THE LATEST TL-3 & TL-2 MASH REQUIREMENTS.
 THE SYSTEM IS DESIGNED TO ACCOMMODATE A VARIETY OF F-SHAPE AND SINGLE SLOPE CONCRETE BARRIERS. CONTACT THE MANUFACTURER FOR GUIDANCE REGARDING OTHER ALLOWABLE SHAPES.

TEST LEVEL	NUMBER OF ELEMENTS	EFFECTIVE LENGTH	MAXIMUM LENGTH
TL-2	2	14' - 7 3/4"	17' - 4"
TL-3	3	20' - 11 3/4"	23' - 8"

NOTE: CROSS SLOPES OF UP TO 8% (OR 1:12 SLOPE) CAN BE ACCOMMODATED WITH STANDARD HARDWARE SHOWN WITHIN THE INSTRUCTIONS MANUAL. FOR SLOPES WITH EXCESS OF 8% (OR 1:12) CONTACT, LINDSAY TRANSPORTATION SOLUTIONS.



NOTE: APPLY A HIGH REFLECTIVE DECAL TO THE NOSE PLATE. DELINEATION DECAL ORIENTATION IS SHOWN ON THE CONSTRUCTION PLAN SET AND SHALL BE IN ACCORDANCE WITH THE TEXAS MUTCD FOR (TRAFFIC CONTROL DEVICES). DECALS ARE AVAILABLE FOR TRAFFIC FLOW ON THE LEFT-SIDE, BOTH -SIDES AND RIGHT-SIDE.

- ### GENERAL NOTES
- FOR SPECIFIC INFORMATION REGARDING THE INSTALLATION AND TECHNICAL GUIDANCE, CONTACT: LINDSAY TRANSPORTATION SOLUTIONS (LTS) - BARRIER SYSTEMS, INC. AT (707) 374-6800. 180 RIVER ROAD, RIO VISTA, CA 94571
 - THE ABSORB-M SYSTEM IS ONLY APPROVED FOR USE IN (TEMPORARY WORK ZONE) LOCATIONS.
 - THE ABSORB-M IS A WATER FILLED NON-REDIRECTIVE, GATING CRASH CUSHION THAT DOES NOT NEED TO BE ATTACHED TO A FOUNDATION AND CAN BE INSTALLED ON TOP OF CONCRETE, ASPHALT, OR ANY SURFACE CAPABLE OF BEARING THE WEIGHT OF THE SYSTEM.
 - MAXIMUM PERMISSIBLE CROSS-SLOPE IS 8%.
 - THE INSTALLATION AREA SHOULD BE FREE FROM CURBS, ELEVATED OBJECTS, OR DEPRESSIONS.
 - THE ABSORB-M SHOULD BE LOCATED APPROXIMATELY PARALLEL WITH THE BARRIER.
 - THE USE OF THE ABSORB-M IS RESTRICTED TO A BARRIER HEIGHT OF UP TO 42 INCHES.
 - DO NOT ADD WATER TO FRONT ELEMENT (TL-2 OR TL-3 UNIT).

BILL OF MATERIALS (BOM) ABSORB-M TL-3 & TL-2 SYSTEMS			QTY	QTY
ITEM #	PART NUMBER	PART DESCRIPTION	TL-2 SYSTEM	TL-3 SYSTEM
1	BSI-1809036-00	TRANSITION - (GALV)	1	1
2	BSI-1808002-00	PRE-ASSEMBLED ABSORBING (ELEMENTS)	2	3
3	BSI-4004598	FILL CAPS	8	12
4	BSI-4004599	DRAIN PLUGS	2	3
5	BSI-1809053-00	TENSION STRAP - (GALV)	8	12
6	BSI-2001998	C-SCR FH 3/8-16 X 1 1/2 GR5 PLT	8	12
7	BSI-2001999	C-SCR FH 3/8-16 X 1 GR5 PLT	8	12
8	BSI-1809035-00	MIDNOSE - (GALV)	1	1
9	BSI-1808014-00	NOSE PLATE	1	1
10	BSI-1809037-00	TRANSITION STRAP (LEFT-HAND) - (GALV)	1	1
11	BSI-1809038-00	TRANSITION STRAP (RIGHT-HAND) - (GALV)	1	1
12	BSI-1808005-00	PIN ASSEMBLY	8	10
13	BSI-2002001	ANC MECH 5/8-11X5 (GALV)	6	6
14	ABSORB-M	INSTALLATION AND INSTRUCTIONS MANUAL	1	1

* COMPONENTS PRE-ASSEMBLED WITH ELEMENT ASSEMBLY


NOTE: THIS STANDARD IS A BASIC REPRESENTATION OF THE ABSORB-M, IT IS NOT INTENDED TO REPLACE THE INSTALLATION INSTRUCTIONS MANUAL.

SACRIFICIAL


		Design Division Standard	
LINDSAY TRANSPORTATION SOLUTIONS CRASH CUSHION (MASH TL-3 & TL-2) TEMPORARY - WORK ZONE ABSORB (M) - 19			
FILE: absorbm19	DN: TxDOT	CK: KM	DW: VP
© TXDOT: JULY 2019	CONT SECT	JOB	HIGHWAY
REVISIONS	0579 02	014	FM 512
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	46	

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\02_TRAF_CONTS\DETAILS\sled19.dgn




PLAN VIEW



ELEVATION VIEW

GENERAL NOTES

1. REFER TO THE INSTALLATION MANUAL FOR SPECIFIC SYSTEM ASSEMBLY AND MODULE ORIENTATION. FOR ADDITIONAL INFORMATION, CONTACT TRAFFIX, INC. AT (949) 361-5663.
2. THE SLED SYSTEM IS A MASH APPROVED TEST LEVEL 3 (TL-3) CRASH CUSHION APPROVED FOR USE IN TEMPORARY WORK ZONES. THE SLED SYSTEM IS A NON-REDIRECTIVE, GATING CRASH CUSHION THAT DOES NOT NEED TO BE ATTACHED TO THE GROUND AND CAN BE INSTALLED ON CONCRETE, ASPHALT, GRAVEL OR COMPACTED SOIL.
3. MAXIMUM PERMISSIBLE CROSS SLOPE IS 8° (DEGREES) (14%).
4. THE INSTALLATION AREA SHOULD BE FREE FROM CURBS, ELEVATED OBJECTS, OR DEPRESSIONS.
5. THE SLED SYSTEM CAN BE ATTACHED TO:
 - CONCRETE BARRIER, TEMPORARY OR PERMANENT, 45" MAXIMUM HEIGHT
 - STEEL BARRIER
 - PLASTIC BARRIER
 - CONCRETE BRIDGE ABUTMENTS
 - W-BEAM GUARD RAIL
 - THRIE BEAM GUARD RAIL




NOTE:
SEE INSTALLATION MANUAL FOR CUSTOMIZED DELINEATION NOSE SHEETING FOR DECAL PLACEMENT.

TEST LEVEL	NUMBER OF SECONDARY MODULES	SYSTEM LENGTH
TL-3	3	25' 3"

BILL OF MATERIAL		
PART NUMBER	DESCRIPTION	QTY: TL-3
45131	TRANSITION FRAME, GALVANIZED	1
45150	TRANSITION PANEL, GALVANIZED	2
45147-CP	TRANSITION SHORT DROP PIN W/ KEEPER PIN, GALVANIZED	2
45148-CP	TRANSITION LONG DROP PIN W/ KEEPER PIN, GALVANIZED	1
45050	ANCHOR BOLTS	9
12060	WASHER, 3/4" ID X 2" OD	9
45044-Y	SLED YELLOW WATER FILLED MODULE	3
45044-YH	SLED YELLOW "NO FILL" MODULE	1
45044-S	CIS (CONTAINMENT IMPACT SLED), GALVANIZED	1
45043-CP	T-PIN W/ KEEPER PIN	4
18009-B-I	FILL CAP W/ "DRIVE BY" FLOAT INDICATOR	3
45033-RC-B	DRAIN PLUG	3
45032-DPT	DRAIN PLUG REMOVAL TOOL	1

TRANSITION OPTIONS
SLED TRANSITION TO CONCRETE TRAFFIC BARRIER (TEMPORARY OR PERMANENT)
SLED TRANSITION TO STEEL TRAFFIC BARRIER (CONTACT MFG FOR PROPER TRANSITION)
SLED TRANSITION TO PLASTIC TRAFFIC BARRIER (CONTACT MFG FOR PROPER TRANSITION)
SLED TRANSITION TO W-BEAM OR THRIE BEAM GUARD RAIL (CONTACT MFG FOR PROPER TRANSITION)
SLED TRANSITION TO CONCRETE BRIDGE ABUTMENT



SLED TRANSITION COMPONENTS FOR ATTACHMENT TO CMB

NOTE:
SEE MANUFACTURER'S INSTALLATION MANUAL FOR FURTHER DETAILS.

NOTE:
THIS STANDARD IS A BASIC REPRESENTATION OF THE SLED, IT IS NOT INTENDED TO REPLACE THE INSTALLATION INSTRUCTIONS MANUAL.

SACRIFICIAL

Design Division Standard

SLED
 CRASH CUSHION
 TL-3 MASH COMPLIANT
 (TEMPORARY, WORK ZONE)
 SLED-19


FILE: sled19.dgn	DN: TxDOT	CK: KM	DW: VP	CK:
© TxDOT: DECEMBER 2019	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
DIST	COUNTY	SHEET NO.		
PARIS	HUNT	47		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:10 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DPS101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\02_TRAF_CONT\STDETAILS\wzrs22.dgn

Warning sign and rumble strip sequence in opposite direction is same as below.

Flagger to Flagger (Length of Work Area)	ADT	# of Rumble Strip Arrays
1/8 Mile	< 4,500	1
	≥ 4,500	2
1/4 Mile	< 3,500	1
	≥ 3,500	2
1/2 Mile	< 2,600	1
	≥ 2,600	2
1 Mile	< 1,600	1
	≥ 1,600	2
> 1 Mile	N/A	2



RUMBLE STRIPS ON ONE-LANE TWO-WAY APPLICATION



RUMBLE STRIPS FOR LANE CLOSURE ON CONVENTIONAL ROADWAY

GENERAL NOTES

- Each Rumble Strip Array should consist of three rumble strips spaced center to center at the spacing shown in Table 2, placed transverse across the lane at locations shown.
- The CW17-2T "RUMBLE STRIPS AHEAD" sign should be located after the CW20-1D "ROAD WORK AHEAD" sign and spaced as shown. If traffic is observed to be queuing, or is expected to queue beyond the Rumble Strips, the CW17-2T sign and the first Rumble Strip Array may be located upstream of the CW20-1D sign as necessary to provide needed warning.
- Temporary Rumble Strips will be considered subsidiary to Item 502, and shall be a product listed on the Compliant Work Zone Traffic Control Devices.
- Remove Temporary Rumble Strips before removing the advanced warning signs.
- Temporary Rumble Strips should not be used on horizontal curves, loose gravel, soft or bleeding asphalt, heavily rutted pavements or unpaved surfaces.
- Temporary Rumble Strips shall be installed and maintained as per manufacturer's recommendations.
- This standard sheet shall be used in conjunction with other appropriate TCP standard, TMUTCD typical application or project specific detail for the project.
- The one-lane two-way application may utilize a flagger, an Automated Flagger Assistance Device (AFAD) or a Portable Traffic Signal (PTS).
- Replace defective Temporary Rumble Strips as directed by the Engineer.
- Temporary Rumble Strips may be used on freeways or expressways based on engineering judgment and written direction from the Engineer.

Speed	Approximate distance between strips in an array
≤ 40 MPH	10'
> 40 MPH & ≤ 55 MPH	15'
= 60 MPH	20'
≥ 65 MPH	* 35' +

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Panel		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT)
 S=Posted Speed (MPH)

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

◆ Signs are for illustrative purposes only. Signs required may vary depending on the TCP, TMUTCD Typical Application, or project specific details for the project.

* For posted speeds in excess of 65 MPH, it is recommended that spacing is increased as speed limits increase. Increasing space between rumble strips will improve effectiveness.

Texas Department of Transportation
 Traffic Safety Division Standard

TEMPORARY RUMBLE STRIPS


WZ (RS) - 22

FILE: wzrs22.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2012	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
2-14 1-22	DIST	COUNTY	SHEET NO.	
4-16	PARIS	HUNT	48	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:11 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\G2\TRAFFIC\STPM\WZ(STPM)-23.dgn

WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS





NOTES:

- Short term pavement markings may be prefabricated markings (stick down tape) or temporary flexible reflective roadway marker tabs unless otherwise specified elsewhere in plans.
- Short term pavement markings shall NOT be used to simulate edge lines.
- Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.
- Temporary flexible-reflective roadway marker tabs will require normal maintenance replacement when used on roadways with an ADT per lane of up to 7500 vehicles with no more than 10% truck mix. When roadways exceed these values, additional maintenance replacement of devices should be planned.
- No segment of roadway open to traffic shall remain without permanent pavement markings for a period greater than 14 calendar days. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
- For two lane, two-way roadways, DO NOT PASS signs shall be erected to mark the beginning of sections where passing is prohibited and PASS WITH CARE signs shall be erected to mark the beginning of sections where passing is permitted. Signs shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and may be used to indicate the limits of no-passing zones for up to 14 calendar days. Permanent pavement markings should then be placed.
- For low volume two lane, two-way roadways of 4000 ADT or less, no-passing lines may be omitted when approved by the Engineer. DO NOT PASS and PASS WITH CARE signs shall be erected (see note 6).
- For exit gores where a lane is being dropped place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are not allowed for this purpose.

TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS (TABS)

- Temporary flexible-reflective roadway marker tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
- Tabs shall meet requirements of Departmental Material Specification DMS-8242.
- When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
- No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 3.

WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS



If raised pavement markers are used to supplement REMOVABLE short term markings, the markers shall be applied to the top of the tape at the approximate mid length of the tape. This allows an easier removal of raised markers and tape.

PREFABRICATED PAVEMENT MARKINGS

- Temporary Removable Prefabricated Pavement Markings shall meet the requirements of DMS-8241.
- Non-removable Prefabricated Pavement Markings shall meet the requirements of either DMS-8240 "Permanent Prefabricated Pavement Markings" or DMS-8243 "Temporary Construction-Grade Prefabricated Pavement Markings."

RAISED PAVEMENT MARKERS

- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and DMS-4200.

DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)

- DMSs referenced above can be found along with embedded links to their respective MPLs at the following website:

http://www.txdot.gov/business/contractors_consultants/material_specifications/default.htm







WORK ZONE SHORT TERM PAVEMENT MARKINGS

WZ(STPM)-23

FILE:	wzstpm-23.dgn	DN:		CK:		DW:		CK:	
© TxDOT	February 2023	CONT:	0579	SECT:	02	JOB:	014	HIGHWAY:	FM 512
REVISIONS:	4-92 7-13 1-97 2-23 3-03	DIST:	PARIS	COUNTY:	HUNT	SHEET NO.:			49

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:11 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\02_TRAFFIC_CONTROL\STDETAILS\wzul-13.dgn



DEPARTMENTAL MATERIAL SPECIFICATIONS	
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY (REMOVABLE) PREFABRICATED PAVEMENT MARKINGS	DMS-8241
SIGN FACE MATERIALS	DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B _{FL} OR TYPE C _{FL} SHEETING
BLACK	LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING

GENERAL NOTES

- If spalling or holes occur, ROUGH ROAD (CW8-8) signs should be placed in advance of the condition and be repeated every two miles where the condition persists.
- UNEVEN LANES (CW8-11) signs shall be installed in advance of the condition and repeated every mile. Signs installed along the uneven lane condition may be supplemented with the NEXT XX MILES (CW7-3aP) plaque or Advisory Speed (CW13-1P) plaque.
- NO CENTER LINE (CW8-12) signs and temporary pavement markings as per the WZ(STPM) standard shall be installed if yellow centerlines separating two way traffic are obscured or obliterated. Repeat NO CENTER LINE signs every two miles where the center line markings are not in place. The signs and markings shall remain in place until permanent pavement markings are installed.
- Signs shall be spaced at the distances recommended as per BC standards.
- Additional signs may be required as directed by the Engineer. Signs shall remain in place until final surface is applied. Signs shall be considered subsidiary to Item 502 "BARRICADES, SIGNS AND TRAFFIC HANDLING."
- Signs shall be fabricated and mounted on supports as shown on the BC standards and/or listed on the "Compliant Work Zone Traffic Control Devices" list.
- Short term markings shall not be used to simulate edge lines.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition.

TABLE 1		
Edge Condition	Edge Height (D)	* Warning Devices
①	Less than or equal to: 1/4" (maximum-planing) 1/2" (typical-overlay)	Sign: CW8-11
②	Less than or equal to 3"	Sign: CW8-11
③	Distance "D" may be a maximum of 3" if uneven lanes with edge condition 2 or 3 are open to traffic after work operations cease. Uneven lanes should not be open to traffic when "D" is greater than 3".	

TRAFFIC CONTROL DURING PLANING, OVERLAY AND LEVELING OPERATIONS ARE SHOWN ELSEWHERE IN THE PLANS.


MINIMUM WARNING SIGN SIZE	
Conventional roads	36" x 36"
Freeways/expressways, divided roadways	48" x 48"



SIGNING FOR UNEVEN LANES

WZ (UL) - 13

FILE:	wzul-13.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	April 1992	CONT	SECT	JOB	HIGHWAY				
REVISIONS	0579 02	014	FM 512						
8-95 2-98 7-13	DIST	COUNTY	SHEET NO.						
1-97 3-03	PARIS	HUNT	50						




LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
 PLANNERS ENGINEERS MANAGERS



FM 512
ROADWAY PLAN LAYOUT

SHEET 1 OF 27


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	51



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:**
1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
ROADWAY PLAN LAYOUT

SHEET 2 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	52
CONTROL	SECTION	JOB	
0579	02	014	




LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




FM 512

ROADWAY PLAN LAYOUT

SHEET 3 OF 27




			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	53
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:**
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS




FM 512

ROADWAY PLAN LAYOUT

SHEET 4 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	54
CONTROL	SECTION	JOB	
0579	02	014	




PI STATION = 80+76.97
 DELTA = 13° 48' 00.00" (LT)
 DEGREE OF CURVE = 5° 14' 00.07"
 TANGENT = 132.49
 LENGTH = 263.69
 RADIUS = 1,094.82
 PC STATION = 79+44.48
 PT STATION = 82+08.17

PI STATION = 85+14.28
 DELTA = 14° 06' 00.00" (RT)
 DEGREE OF CURVE = 5° 08' 31.54"
 TANGENT = 137.80
 LENGTH = 274.21
 RADIUS = 1,114.25
 PC STATION = 83+76.48
 PT STATION = 86+50.69

LEGEND


- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



PI STATION = 93+58.49
 DELTA = 43° 36' 00.00" (LT)
 DEGREE OF CURVE = 10° 00' 00.00"
 TANGENT = 229.17
 LENGTH = 436.00
 RADIUS = 572.96
 PC STATION = 91+29.33
 PT STATION = 95+65.33

CULVERT 04
 1-36"x50' CMP
 STA 91+41.83
 (REFER TO CULVERT LAYOUT SHEETS)



Paul A. Warden, P.E. 579110023

IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
 PLANNERS ENGINEERS MANAGERS




**FM 512
ROADWAY PLAN LAYOUT**

SHEET 5 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	55
CONTROL	SECTION	JOB	
0579	02	014	


5/24/2023 6:20:14 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\03-ROADWAY\FM512_RD_PPM_06.dgn




LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:
1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023




IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 6 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	56
CONTROL	SECTION	JOB	
0579	02	014	




LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579410023



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 7 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	57
CONTROL	SECTION	JOB	
0579	02	014	





LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**




SHEET 8 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	58
CONTROL	SECTION	JOB	
0579	02	014	



- LEGEND**
- PROPOSED SMALL SIGN ASSEM & NUMBER
 - EXIST SMALL SIGN ASSEM TO BE REMOVED
 - DIRECTION OF TRAFFIC FLOW
 - DRIVEWAY NUMBER
 - MAIL BOX
 - PLANE ASPH (0"-1.5")

- NOTES:**
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825


PLANNERS ENGINEERS MANAGERS



FM 512
ROADWAY PLAN LAYOUT

SHEET 9 OF 27

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	59





LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 10 OF 27

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	60




END 1-6" YELLOW SOLID
1-6" YELLOW BROKEN
BEGIN 1-6" YELLOW BROKEN
FM 512
STA 204+25.00

END 1-6" YELLOW BROKEN
BEGIN 1-6" YELLOW SOLID
1-6" YELLOW BROKEN
FM 512
STA 208+63.00



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:**
1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



PI STATION = 216+74.04
DELTA = 16° 47' 00.00" (RT)
DEGREE OF CURVE = 11° 55' 00.00"
TANGENT = 70.93
LENGTH = 140.84
RADIUS = 480.80
PC STATION = 216+03.11
PT STATION = 217+43.95






IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 11 OF 27

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	61



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
ROADWAY PLAN LAYOUT

SHEET 12 OF 27


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	62



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:**
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.




IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 13 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	63
CONTROL	SECTION	JOB	
0579	02	014	



PI STATION = 261+76.51
 DELTA = 43° 41' 00.00" (LT)
 DEGREE OF CURVE = 10° 00' 00.00"
 TANGENT = 229.65
 LENGTH = 436.83
 RADIUS = 572.96
 PC STATION = 259+46.86
 PT STATION = 263+83.70


PI STATION = 276+11.67
 DELTA = 90° 24' 00.00" (RT)
 DEGREE OF CURVE = 10° 00' 00.00"
 TANGENT = 576.97
 LENGTH = 904.00
 RADIUS = 572.96
 PC STATION = 270+34.70
 PT STATION = 279+38.70

LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd.
 Suite 200
 San Antonio, Tx. 78240
 (210) 448-1800
 FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 14 OF 27


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	64
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
 PLANNERS ENGINEERS MANAGERS © 2023



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 15 OF 27



STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	65



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023



IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
ROADWAY PLAN LAYOUT

SHEET 16 OF 27


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	66



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579110023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 17 OF 27

			HIGHWAY NO FM 512
STATE TEXAS	DISTRICT PARIS	COUNTY HUNT	SHEET NO 67
CONTROL 0579	SECTION 02	JOB 014	





LEGEND

- XX PROPOSED SMALL SIGN ASSEM & NUMBER
- XX EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRWY #XX DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
ROADWAY PLAN LAYOUT

SHEET 18 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	68
CONTROL	SECTION	JOB	
0579	02	014	





LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 5/24/2023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 19 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	69
CONTROL	SECTION	JOB	
0579	02	014	




LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 5/24/2023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 20 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	70
CONTROL	SECTION	JOB	
0579	02	014	





LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS









FM 512
ROADWAY PLAN LAYOUT

SHEET 21 OF 27



			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	71
CONTROL	SECTION	JOB	
0579	02	014	

LEGEND

-  XX PROPOSED SMALL SIGN ASSEM & NUMBER
-  XX EXIST SMALL SIGN ASSEM TO BE REMOVED
-  DIRECTION OF TRAFFIC FLOW
-  DRWY #XX DRIVEWAY NUMBER
-  MAIL BOX
-  PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825





FM 512

ROADWAY PLAN LAYOUT

SHEET 22 OF 27

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	72
CONTROL	SECTION	JOB	
0579	02	014	







LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 23 OF 27



STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	73



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:**
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.




IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 24 OF 27

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	74




LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 579412023



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 25 OF 27



			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	75
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
ROADWAY PLAN LAYOUT**

SHEET 26 OF 27

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	76

PI STATION = 503+79.67
 DELTA = 14° 12' 00.00" (LT)
 DEGREE OF CURVE = 6° 00' 00.00"
 TANGENT = 118.94
 LENGTH = 236.67
 RADIUS = 954.93
 PC STATION = 502+60.73
 PT STATION = 504+97.39



PI STATION = 509+77.61
 DELTA = 91° 24' 00.00" (LT)
 DEGREE OF CURVE = 18° 00' 00.00"
 TANGENT = 326.18
 LENGTH = 507.78
 RADIUS = 318.31
 PC STATION = 506+51.43
 PT STATION = 511+59.20

LEGEND

- PROPOSED SMALL SIGN ASSEM & NUMBER
- EXIST SMALL SIGN ASSEM TO BE REMOVED
- DIRECTION OF TRAFFIC FLOW
- DRIVEWAY NUMBER
- MAIL BOX
- PLANE ASPH (0"-1.5")

NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. FOR DRIVEWAY DETAIL REFER TO DRIVEWAY SUMMARY SHEET.



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
 Suite 200
 San Antonio, Tx. 78240
 (210) 448-1800
 FIRM # F-6825

© 2023
Texas Department of Transportation

**FM 512
ROADWAY PLAN LAYOUT**

SHEET 27 OF 27


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	77
CONTROL	SECTION	JOB	
0579	02	014	



NOTES:

1. ALL EXISTING RAIL DRILLED HOLES NOT INCORPORATED WITHIN T131RC RAIL SHALL BE FILLED WITH NON-SHRINK GROUT.
2. BRIDGE SKEW: 45 DEGREE RFS.

5/24/2023 6:20:21 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\03-ROADWAY\FM512_BRG_PL_01.dgn



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




FM 512
BRIDGE PLAN LAYOUT
AT RAYS CREEK
NBI: 01-117-0-0579-02-001

SHEET 1 OF 1			HIGHWAY NO FM 512
STATE TEXAS	DISTRICT PARIS	COUNTY HUNT	SHEET NO 78
CONTROL 0579	SECTION 02	JOB 014	


NOTES: CONTRACTOR IS TO CONFIRM EXISTING SUPERELEVATION SLOPE AND NOTIFY AREA ENGINEER BEFORE ROADWAY REHABILITATION STARTS.

EXCESS MATERIAL GENERATED IS PROPERTY OF CONTRACTOR.




PROPOSED SUPERELEVATION TABLE					ITEM 247-6124	ITEM 3076-6068
STATION	SHOULDER CROSS SLOPE LEFT (%)	TRAVEL LANE CROSS SLOPE LEFT (%)	TRAVEL LANE CROSS SLOPE RIGHT (%)	SHOULDER CROSS SLOPE RIGHT (%)	FL BS (RDWY DEL) (TY A GR4) TON	D-GR HMA TY-D SAC-A PG64-22 (EXEMPT)
BEGIN PROJECT	> 2.00	2.00	-2.00	-2.00		
10+45.00 END NC						
SUPERELEVATION TRANSITION						
11+54.00 BEGIN FS	> -5.90	-5.90	-5.90	-5.90		66.0
12+66.00 END FS						
SUPERELEVATION TRANSITION						
13+75.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
78+21.00 END NC						
SUPERELEVATION TRANSITION						
79+97.00 BEGIN FS	> 6.00	6.00	6.00	6.00	46.8	
81+16.00 END FS						
SUPERELEVATION TRANSITION						
82+92.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
82+92.00 END NC						
SUPERELEVATION TRANSITION						
84+68.00 BEGIN FS	> -6.00	-6.00	-6.00	-6.00	58.1	
85+98.00 END FS						
SUPERELEVATION TRANSITION						
87+74.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
90+07.00 END NC						
SUPERELEVATION TRANSITION						
91+60.00 BEGIN FS	> 5.90	5.90	5.90	5.90	80.3	
95+35.00 END FS						
SUPERELEVATION TRANSITION						
96+88.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
97+40.00 END NC						
SUPERELEVATION TRANSITION						
98+93.00 BEGIN FS	> -5.90	-5.90	-5.90	-5.90	0.0	
102+79.00 END FS						
SUPERELEVATION TRANSITION						
104+32.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
182+97.00 END NC						
SUPERELEVATION TRANSITION						
184+58.61 BEGIN FS	> 5.80	5.80	5.80	5.80	261.0	
193+02.66 END FS						
SUPERELEVATION TRANSITION						
194+65.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
214+92.00 END NC						
SUPERELEVATION TRANSITION						
216+31.00 BEGIN FS	> -5.80	-5.80	-5.80	-5.80	50.3	
217+16.00 END FS						
SUPERELEVATION TRANSITION						
218+55.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
227+41.00 END NC						
SUPERELEVATION TRANSITION						
228+98.00 BEGIN FS	> 5.10	5.10	5.10	5.10	144.2	
233+24.00 END FS						
SUPERELEVATION TRANSITION						
234+81.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
247+80.00 END NC						
SUPERELEVATION TRANSITION						
249+33.00 BEGIN FS	> -5.90	-5.90	-5.90	-5.90	73.4	
253+12.00 END FS						
SUPERELEVATION TRANSITION						
254+65.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
258+24.00 END NC						
SUPERELEVATION TRANSITION						
259+77.00 BEGIN FS	> 5.90	5.90	5.90	5.90	53.6	
263+53.00 END FS						
SUPERELEVATION TRANSITION						
265+06.00 BEGIN NC	> 2.00	2.00	-2.00	-2.00		
CONT. NEXT SHEET						

NC = NORMAL CROWN
FS = FULL SUPERELEVATION
RC = REVERSE CROWN



5/24/2023 6:20:21 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\03-ROADWAY\FM512_RD_SUP_01.dgn



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS




**FM 512
SUPERELEVATION
TABLE**

SHEET 1 OF 3

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	79


NOTES: CONTRACTOR IS TO CONFIRM EXISTING SUPERELEVATION SLOPE AND NOTIFY AREA ENGINEER BEFORE ROADWAY REHABILITATION STARTS.

EXCESS MATERIAL GENERATED IS PROPERTY OF CONTRACTOR.



PROPOSED SUPERELEVATION TABLE						ITEM 247-6124	ITEM 3076-6068
STATION		SHOULDER CROSS SLOPE LEFT (%)	TRAVEL LANE CROSS SLOPE LEFT (%)	TRAVEL LANE CROSS SLOPE RIGHT (%)	SHOULDER CROSS SLOPE RIGHT (%)	FL BS (RDWY DEL) (TY A GR4) TON	D-GR HMA TY-D SAC-A PG64-22 (EXEMPT)
CONT.	269+12.00	END NC	2.00	2.00	-2.00		
SUPERELEVATION TRANSITION							
	270+65.00	BEGIN FS	> -5.90	-5.90	-5.90	127.6	
	279+08.00	END FS					
SUPERELEVATION TRANSITION							
	280+61.00	BEGIN NC	> 2.00	2.00	-2.00		
	283+34.00	END NC					
SUPERELEVATION TRANSITION							
	284+87.00	BEGIN FS	> 5.90	5.90	5.90	126.5	
	293+31.00	END FS					
SUPERELEVATION TRANSITION							
	294+84.00	BEGIN NC	> 2.00	2.00	-2.00		
	312+04.00	END NC					
SUPERELEVATION TRANSITION							
	313+78.00	BEGIN FS	> -5.90	-5.90	-5.90	71.9	
	313+82.00	END FS					
SUPERELEVATION TRANSITION							
	315+56.00	BEGIN NC	> 2.00	2.00	-2.00		
	315+56.00	END NC					
SUPERELEVATION TRANSITION							
	317+19.00	BEGIN FS	> 5.40	5.40	5.40	0.0	
	318+05.00	END FS					
SUPERELEVATION TRANSITION							
	319+68.00	BEGIN NC	> 2.00	2.00	-2.00		
	323+21.00	END NC					
SUPERELEVATION TRANSITION							
	324+74.00	BEGIN FS	> -5.90	-5.90	-5.90	87.0	
	326+20.00	END FS					
SUPERELEVATION TRANSITION							
	327+73.00	BEGIN NC	> 2.00	2.00	-2.00		
	333+16.00	END NC					
SUPERELEVATION TRANSITION							
	334+43.00	BEGIN FS	> -5.70	-5.70	-5.70	201.8	
	338+92.00	END FS					
SUPERELEVATION TRANSITION							
	340+19.00	BEGIN NC	> 2.00	2.00	-2.00		
	363+02.00	END NC					
SUPERELEVATION TRANSITION							
	364+29.00	BEGIN FS	> 5.70	5.70	5.70	101.3	
	368+77.00	END FS					
SUPERELEVATION TRANSITION							
	370+04.00	BEGIN NC	> 2.00	2.00	-2.00		
	406+40.00	END NC					
SUPERELEVATION TRANSITION							
	407+67.00	BEGIN FS	> 5.70	5.70	5.70	106.5	
	412+16.00	END FS					
SUPERELEVATION TRANSITION							
	413+43.00	BEGIN NC	> 2.00	2.00	-2.00		
	425+05.00	END NC					
SUPERELEVATION TRANSITION							
	426+32.00	BEGIN FS	> -5.70	-5.70	-5.70	72.0	
	429+41.00	END FS					
SUPERELEVATION TRANSITION							
	430+68.00	BEGIN NC	> 2.00	2.00	-2.00		
	445+36.00	END NC					
SUPERELEVATION TRANSITION							
	446+91.00	BEGIN FS	> -6.00	-6.00	-6.00	53.4	
	448+55.00	END FS					
SUPERELEVATION TRANSITION							
	450+10.00	BEGIN NC	> 2.00	2.00	-2.00		
CONT. NEXT SHEET							

NC = NORMAL CROWN
FS = FULL SUPERELEVATION
RC = REVERSE CROWN



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825




FM 512
**SUPERELEVATION
TABLE**

SHEET 2 OF 3

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	80


NOTES: CONTRACTOR IS TO CONFIRM EXISTING SUPERELEVATION SLOPE AND NOTIFY AREA ENGINEER BEFORE ROADWAY REHABILITATION STARTS.

EXCESS MATERIAL GENERATED IS PROPERTY OF CONTRACTOR.



PROPOSED SUPERELEVATION TABLE						ITEM 247-6124	ITEM 3076-6068
STATION	SHOULDER CROSS SLOPE LEFT (%)	TRAVEL LANE CROSS SLOPE LEFT (%)	TRAVEL LANE CROSS SLOPE RIGHT (%)	SHOULDER CROSS SLOPE RIGHT (%)	FL BS (RDWY DEL) (TY A GR4) TON	D-GR HMA TY-D SAC-A PG64-22 (EXEMPT)	
CONT. 486+95.00	END NC	2.00	2.00	-2.00	-2.00		
SUPERELEVATION TRANSITION							
487+83.00	BEGIN FS	> 4.00	4.00	4.00	4.00	63.1	
490+86.00	END FS						
SUPERELEVATION TRANSITION							
491+74.00	BEGIN NC	> 2.00	2.00	-2.00	-2.00		
493+58.00	END NC						
SUPERELEVATION TRANSITION							
495+20.00	BEGIN FS	> -5.80	-5.80	-5.80	-5.80	214.8	
498+40.00	END FS						
SUPERELEVATION TRANSITION							
500+02.00	BEGIN NC	> 2.00	2.00	-2.00	-2.00		
501+39.00	END NC						
SUPERELEVATION TRANSITION							
503+13.00	BEGIN FS	> 5.90	5.90	5.90	5.90	56.0	
504+00.00	END FS						
SUPERELEVATION TRANSITION							
505+74.00	BEGIN NC	> 2.00	2.00	-2.00	-2.00		
505+74.00	END NC						
SUPERELEVATION TRANSITION							
507+01.00	BEGIN FS	> 5.70	5.70	5.70	5.70	0.0	
511+34.00	END FS						
SUPERELEVATION TRANSITION							
512+61.00	BEGIN NC	> 2.00	2.00	-2.00	-2.00		
END PROJECT							
TOTAL						2,049.6	66.0

NC = NORMAL CROWN
FS = FULL SUPERELEVATION
RC = REVERSE CROWN



5/24/2023 6:20:21 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\03-ROADWAY\FM512_RD_SUP_01.dgn



Paul A. Warden, P.E. 572412023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
SUPERELEVATION
TABLE**


SHEET 3 OF 3

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	81
CONTROL	SECTION	JOB	
0579	02	014	




TRANSITION TO PROJECT LIMITS/HMA OVERLAY

TRANSITION RATIO IS 1":50'




TRANSITION AT BRIDGE

TRANSITION RATIO IS 1":50'



SUMMARY OF ROADWAY ITEMS							132-6019
DESCRIPTION							EMBANKMENT (VEHICLE) (ORD COMP) (TY B)
BEGIN MOW STRIP STA	TO	END MOW STRIP STA	LT/RT	LENGTH	AREA	"L"	
FM 512							CY
187+33.69	TO	189+27.14	LT	193	6.0	8.0	42
186+04.00	TO	189+28.30	RT	324	14.9	11.9	179
189+81.99	TO	193+29.40	LT	347	31.4	19.4	404
189+80.65	TO	191+79.59	RT	199	10.6	12.8	78
252+86.24	TO	258+70.11	LT	584	6.5	6.8	140
253+00.25	TO	258+86.99	RT	587	13.4	9.8	290
305+32.77	TO	306+93.83	LT	161	13.8	10.4	82
303+89.78	TO	306+60.66	RT	271	17.4	16.6	174
307+40.90	TO	310+18.28	LT	277	46.6	24.2	478
307+07.82	TO	308+75.29	RT	167	17.2	13.5	106
413+31.41	TO	415+80.41	LT	249	12.8	11.1	117
412+31.71	TO	415+80.27	RT	349	36.4	17.9	469
416+03.74	TO	419+52.75	LT	349	17.2	13.0	222
416+03.70	TO	418+52.70	RT	249	19.6	12.0	180
450+93.06	TO	452+42.00	LT	149	15.3	10.0	84
450+30.18	TO	452+66.00	RT	236	19.1	11.4	166
453+42.00	TO	456+16.00	LT	274	16.8	12.0	170
453+66.00	TO	455+14.94	RT	149	7.9	13.7	43
FM 512 TOTAL							3,424

- USE CLASS 7 JOINT SEALANT IN ACCORDANCE WITH DMS-6310, "JOINT SEALANTS AND FILTERS." PREPARE JOINT AND SEAL IN ACCORDANCE WITH ITEM 438 "CLEANING AND SEALING JOINTS."
- PROVIDE BACKER ROD 25% LARGER THAN JOINT OPENING AND COMPATIBLE WITH THE SEALANT. USE OF MULTIPLE PIECES TO CREATE A BACKER ROD CROSS SECTION IS NOT PERMITTED. TOP OF BACKER ROD MUST BE CONVEX AS SHOWN.



JOINT DETAIL

CONTRACTOR SHALL FIELD VERIFY EXISTING DIMENSION PRIOR TO ORDERING MATERIALS

GENERAL NOTES:

CLEANING EXISTING JOINT OPENING (FULL DEPTH) OF ALL DEBRIS, PROVIDING AND REPLACING BACKER ROD, SAW-CUTTING ASPHALT OVERLAY, AND SEALING JOINT IS PAID FOR BY ITEM 438, "CLEANING AND SEALING JOINTS" AND MEASURED BY THE LINEAR FOOT. OBTAIN APPROVAL FOR ALL TOOLS, EQUIPMENT, MATERIALS AND TECHNIQUES PROPOSED TO CLEAN AND SEAL THE JOINT. PROVIDE CLASS 7 JOINT SEALANT IN ACCORDANCE WITH DMS-6310, "JOINT SEALANTS AND FILTERS" FOR JOINTS IN ASPHALT OVERLAY. EXTEND SEALANT UP INTO RAIL OR CURB 3 INCHES ON LOW SIDE OR SIDES OF DECK. IF THE CLASS 7 JOINT SEALANT CANNOT BE EFFECTIVELY PLACED IN THE VERTICAL POSITION, A CLASS 4 JOINT SEALANT COMPATIBLE WITH THE CLASS 7 JOINT SEALANT IS ALLOWED FOR THE EXTENSION OF THE SEAL INTO THE CURB OR RAIL. PREPARE SURFACES WHERE SEALANT IS TO BE PLACED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.

PROCEDURE FOR CLEANING AND SEALING EXISTING CONCRETE GIRDER JOINT WITH SILICONE SEAL:

- CLEAN JOINT OPENING OF ALL EXISTING EXPANSION MATERIALS/DEVICES, DIRT, AND ALL OTHER DELETERIOUS MATERIALS IN ACCORDANCE WITH ITEM 438, "CLEANING AND SEALING JOINTS." CLEAN JOINT OUT FULL DEPTH OF THE JOINT.
- OBTAIN APPROVAL OF CLEANED JOINT PRIOR TO PROCEEDING WITH JOINT SEALING OPERATION.
- FILL VOID WITH EXTRUDED POLYSTYRENE FOAM.
- PLACE BACKER ROD INTO JOINT OPENING 1" BELOW THE TOP OF CONCRETE.
- SEAL THE JOINT OPENING WITH A CLASS 7 JOINT SEALANT. RECESS SEAL 1/2" BELOW TOP OF CONCRETE IN TRAVEL LANES AND 1/4" BELOW TOP OF CONCRETE IN SHOULDERS.



Paul A. Warden, P.E. 579412023

IDCUS PLANNERS ENGINEERS MANAGERS
8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825



FM 512


MISCELLANEOUS DETAILS

SHEET 1 OF 1

STATE			HIGHWAY NO
TEXAS			FM 512
DISTRICT			SHEET NO
PARIS			82
COUNTY			
HUNT			
CONTROL SECTION			
JOB			
0579 02 014			


DRIVEWAY BASE SURFACE

N. T. S.




DRIVEWAY ACP SURFACE


N. T. S.



SECTION A-A:




SECTION B-B:



NOTES:

1. THIS WORK WILL BE MEASURED AND PAID FOR AS: "DRIVEWAYS (BASE)".
2. DIMENSIONS W, L, R1 AND R2 ARE PROVIDED IN QUANTITY SUMMARY FOR DRIVEWAYS.

SECTION B-B:




HOT MIX WEDGE

N. T. S.

NOTES:

1. THIS WORK WILL BE MEASURED AND PAID FOR AS: "DRIVEWAYS (ACP)".
2. DIMENSIONS W, L, R1 AND R2 ARE PROVIDED IN QUANTITY SUMMARY FOR DRIVEWAYS.
3. DIMENSION W DOES NOT REPRESENT THE AVERAGE WIDTH OF WEDGE AREA TO BE PAID.
4. HMA WILL BE TY C UNLESS OTHERWISE APPROVED BY THE ENGINEER.



Paul A. Warden, P.E. 572412023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512


DRIVEWAY DETAILS

SHEET 1 OF 2


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	83
CONTROL	SECTION	JOB	
0579	02	014	

INTERSECTION (SURF TREAT)

N. T. S.



SECTION C-C:




NOTES:


1. THIS WORK WILL BE MEASURED AND PAID FOR AS: "INTERSECTION (SURF TREAT)".
2. DIMENSIONS W, L, R1 AND R2 ARE PROVIDED IN QUANTITY SUMMARY FOR DRIVEWAYS.
3. DIMENSION W DOES NOT REPRESENT THE AVERAGE WIDTH OF WEDGE AREA TO BE PAID.

CONCRETE DRIVEWAY


N. T. S.



SECTION D-D:




SECTION E-E:



TIE-BAR DETAIL

TIE-BAR DETAIL

N. T. S.



NOTES:

1. THIS WORK WILL BE MEASURED AND PAID FOR AS: DRIVEWAYS (CONC).
2. DIMENSIONS W,L,R1 AND R2 ARE PROVIDED IN QUANTITY SUMMARY FOR DRIVEWAYS.



Paul A. Warden, P.E. 579412023


IDCUS PLANNERS ENGINEERS MANAGERS
8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240
(210) 448-1800 FIRM # F-6825



**FM 512
DRIVEWAY DETAILS**

SHEET 2 OF 2

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	84
CONTROL	SECTION	JOB	
0579	02	014	



Paul A. Warden, P.E. 5/24/2023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825





FM 512
MAILBOX TURNOUT DETAILS

SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	85



ABUTMENT QUANTITIES					
LOCATION	STA	"Y"	110-6003	247-6242	401-6001
			EXCAVATION (SPECIAL)	FL BS (CMP IN PLACE) (TY A GR 4) (9")	FLOWABLE BACKFILL
			FT	SY	CY
RAYS CREEK	452+54.00	2	106.6	73.6	82.6
TOTAL			106.6	73.6	82.6



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS




FM 512
ABUTMENT EROSION REPAIR DETAILS

- NOTES:
1. IT IS THE CONTRACTOR'S RESPONSABILITY TO VERIFY ALL DIMENSIONS AND ELEVATION PRIOR TO COMMENCING ANY CONSTRUCTION.

SHEET 1 OF 1			HIGHWAY NO. FM 512
STATE TEXAS	DISTRICT PARIS	COUNTY HUNT	SHEET NO. 86
CONTROL 0579	SECTION 02	JOB 014	

DATE: 5/24/2023
 FILE: Z:\Transportation\DOT\PS&E\STATEWIDE_36-9\IDP5101\WA2-TXDOT_Paris\ProjectData\FM 512 (0579-02-01-4)\CADD\GN\03_ROADWAY\FM512_RD_PED_01.dgn




TYPICAL BENT ELEVATION
 (Looking upstation)

TABLE OF PILE ENCASEMENT LENGTHS			
Bent	Pile	Length of Pile Encasement (ft)	Bent Total (ft)
2	1	5	15
	2	5	
	3	5	
3	1	5	15
	2	5	
	3	5	
4	1	5	15
	2	5	
	3	5	
Total			45

- PILE ENCASEMENT PROCEDURE:**
- 1) Verify channel line elevations and report to the Engineer for possible adjustments.
 - 2) Submit a concrete mix design and procedures for casting the encasements for approval.
 - 3) Clean mud, grease, loose rust, and paint off the section of H-piling to be encased with hand tools and high pressure water.
 - 4) Place and secure the steel reinforcement and install formwork.
 - 5) Place the concrete in the encasement per approved procedures and in accordance with Item 420, "Concrete Substructures."
 - 6) Leave forms in-place for at least 48 hours.


- PAINTING NOTES:**
- 1) Clean the area to be painted with hand tools and high pressure water blasting.
 - 2) Apply a minimum of 4.0 mils DFT coating conforming to DMS-8105 as shown.
 - 3) Allow coating to cure a minimum of 24 hours prior to placing concrete.

- GENERAL NOTES:**
- Verify dimensions for steel H-piling encasements and ground elevations. Pile Encasement Length may be adjusted by the Engineer based on actual channel and ground line elevations.
- Existing conditions may be under water. Contractor is responsible for dewatering. Payment for dewatering is subsidiary to Item 420, "Concrete Substructures." The Contractor may submit a plan that adequately demonstrates the ability to perform the repairs without dewatering to the Engineer for approval. If approved, dewatering may be waived.
- Obtain approval for the mix design and the construction procedures before beginning work.
- If underwater placement is approved, concrete mix should be designed for underwater placement and may require the use of anti-washout admixtures.
- Provide concrete for the H-piling encasement capable of attaining an average concrete compressive strength of 3,000 psi within 24 hours and consisting of coarse aggregate grades not greater than No. 5 (3/4"). Provide a concrete mix with 2 gallons of corrosion inhibitor per CY.
- Pile encasement will be paid for per the unit bid price for each linear foot of encasement, per Item 420, "Concrete Substructures." Payment for collars is subsidiary to Item 420, "Concrete Substructures." Provide Grade 60 reinforcing steel.




ELEVATION OF PILE ENCASEMENT

- 1 See Table of Pile Encasement Lengths.
- 2 Field adjust encasement length based on actual conditions.
- 3 Seal gap with Class 4 or Class 7 joint sealant (DMS-6310).
- 4 Apply System I-A overcoat (or alternate coating system, as specified) per Item 446, "Field Cleaning and Painting Steel" to an area covering 3" above and 3" below the top of concrete encasement as shown. Refer to Painting Notes for more information. Payment for this work is subsidiary to Item 420, "Concrete Substructures."




ROUND ENCASEMENT




SQUARE ENCASEMENT

SECTION A-A




BAR C (#4)

Arrange Bar C pairs to provide 1'-0" opening on opposite faces:




BAR S (#4)




5/24/2023

Jerome A. Quintero


<h2>PILE ENCASEMENT DETAILS</h2>			
<p>NBI: 01-117-0-0579-02-001</p>			
FILE: WD-PED-22.dgn	DWG: 0579 02	CK: 014	CHK: FM 512
©TXDOT August 2022	CONT: 0579 02	SECT: 014	HIGHWAY: FM 512
REVISIONS	DIST: PARIS	COUNTY: HUNT	SHEET NO.: 87



BRUSH REMOVAL




BRUSH REMOVAL UNDER BRIDGE AND IN CHANNEL




STEPS 1, 2 AND 3 APPLY WHEN REMOVING LIMBS 2" IN DIAMETER OR LARGER.

TREE TRIMMING



TREE REMOVAL
SPECIFIC LOCATION SPECIFIED IN PLANS



Paul A. Warden, P.E. 5/24/2023

FM 512
TREE TRIMMING &
BRUSH REMOVAL

© 2023


STATE OF TEXAS
PAUL A. WARDEN
101319
LICENSED PROFESSIONAL ENGINEER

TEXAS
Department
of Transportation

CONT	SECT	JOB	HIGHWAY
0579	02	014	FM 512
DIST		COUNTY	SHEET NO.
PARIS		HUNT	88


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-01-4)\CADD\DGN\03_ROADWAY\StdDetail\stehmac11.dgn



*** SEE TYPICAL SECTION FOR ROADSIDE DETAILS


CONDITION - 1
 THIN HMAC SURFACES OR HMAC OVERLAY
 WITH THICKNESS OF 2.5" OR LESS



** EXISTING ROADSIDE EMBANKMENT TO BE GRADED TO PRODUCE A SMOOTH LEVEL SURFACE FOR PLACEMENT OF TAPERED EDGE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.


*** SEE TYPICAL SECTION FOR ROADSIDE DETAILS

CONDITION - 2
 OVERLAY OF EXISTING PAVEMENT
 HMAC THICKNESS 2.5" TO 5"



*** SEE TYPICAL SECTION FOR ROADSIDE DETAILS

CONDITION - 3
 NEW OR RECONSTRUCTED PAVEMENT
 HMAC THICKNESS 2.5" TO 5"



*** SEE TYPICAL SECTION FOR ROADSIDE DETAILS

CONDITION - 4
 NEW OR RECONSTRUCTED PAVEMENT
 HMAC THICKNESS 5" OR GREATER

GENERAL NOTES


- UNLESS OTHERWISE SHOWN IN THE PLANS, A VERTICAL EDGE IS PERMISSIBLE FOR HMAC PLACED GREATER THAN 5" BELOW THE EDGE OF PAVEMENT AND FOR THICKNESS OF HMAC LESS THAN 2.5".
- FOR FURTHER INFORMATION REGARDING THE ROADSIDE AND PAVEMENT DETAILS, SEE TYPICAL SECTIONS.
- PAYMENT FOR TAPERED EDGE WILL BE IN ACCORDANCE WITH APPLICABLE ITEMS IN THE CONTRACT.
- THE SLOPE OF THE TAPERED EDGE SHALL BE 1.75H:1V OR FLATTER.
- THE TAPERED EDGE SHALL BE PRODUCED BY USE OF A SCREED ATTACHMENT CAPABLE OF PRODUCING A SMOOTH COMPACTED SURFACE. ADDITIONAL COMPACTING EFFORT BEHIND THE SCREED IS NOT REQUIRED.

(NOT TO SCALE)


					Design Division Standard
TAPERED EDGE DETAILS HMAC PAVEMENT					
TE (HMAC) - 11					
FILE: tehmac11.dgn	DN: TxDOT	CK: RL	DW: KB	CK:	
© TxDOT January 2011	CONT	SECT	JOB	HIGHWAY	
REVISIONS		0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.		
	PARIS	HUNT	89		

DATE: 5/24/2023 6:20:25 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TXDOT\Part1s\ProjectData\FM 512 (0579-02-014)\CADD\DN\03_ROADWAY\StdDetail\sm-b-21(1).dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPE 1 - MULTIPLE



TYPE 4 - MULTIPLE




MAILBOX SIZES

MAILBOX SIZE	TYPICAL DIMENSIONS			MAX **
	LENGTH	WIDTH	HEIGHT	WEIGHT
SMALL	19 1/2"	6"	7"	6 LBS
MEDIUM	22 1/2" *	8" *	11 1/2" *	8 LBS
LARGE	23 1/2"	11 1/2"	13 1/2"	11 LBS
EXTRA LARGE	18"	14"	12"	13 LBS
LOCKABLE	18"	11 1/2"	15"	23 LBS


- GENERAL NOTES:**
- Dimensions shown (length, width, and height) are typical, not maximums. However, anytime a medium size mailbox is mounted on a single/double mount or on the outside position on a multi mount, the dimensions shown are maximums.
 - Mailboxes shall be made of light weight sheet metal or light weight plastic. Heavy steel, cast iron or decorative mailboxes shall not be used on the state highway system.
- * See Note 1.
** Excluding Molded Plastic on 4 X 4 Post

TYPICAL INSTALLATION MEASUREMENTS




NOTE:
Mailbox installations in sidewalk areas shall be in accordance with the latest TxDOT Design Standard sheets PED-Pedestrian Facilities Curb Ramps.


TYPE 2 and 4 - SINGLE/DOUBLE





TYPE 3 - SINGLE/DOUBLE




PLACEMENT OF EMERGENCY LOCATION NUMBER



- NOTES:**
- Location numbers are provided by homeowner. Minimum size 1" height.
 - Location number is typically placed on the mailbox in a contrasting color.
 - Black numbers may be placed on the Type 2 object marker if the numbers cannot be placed on the mailbox.
 - Alternatively, a green or blue plate with white numbers attached may be mounted below the object marker. Other contrasting color configuration, as approved, may be used.
 - See 3 of 4 for Foundation details.
 - See 4 of 4 for Hardware details.



TYPE 5



SHEET 1 OF 4



MAILBOX MOUNTING AND ASSEMBLY


MB(1)-21

FILE: MB-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT March 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
2/2005	11/2009	4/2015		
6/2005	1/2011			
11/2006	7/2014			
	DIST	COUNTY		SHEET NO.
	PARIS	HUNT		90


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:26 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\03_ROADWAY\StdDetail\mb-21(1).dgn


TYPE 1 - MULTI LOCKABLE AND XL MAILBOX



TYPE 2/4 - SINGLE LOCKABLE MAILBOX




TYPE 2/4 - SINGLE XL MAILBOX




NOTE:
 Follow same configuration when mounting an XL mailbox on a Type 4 multi post.


TYPE 1 MULTI - LOCKABLE ARCHITECTURAL (LA)



TYPE 1 MULTI - XL MAILBOX



TYPE 3 - XL MAILBOX MOUNTING



SHEET 2 OF 4


		Maintenance Division Standard	
<p>XL AND LOCKABLE ARCHITECTURAL MAILBOX ASSEMBLY</p> <p>MB (2) - 21</p>			
FILE: MB-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT March 2004	CONT	SECT	JOB
2/2005	0579	02	014
6/2005	DIST	COUNTY	SHEET NO.
11/2006	PARIS	HUNT	91

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:26 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNN\03_ROADWAY\StdDetail\smb-21(1).dgn

TYPE 1 - SUPPORT/FOUNDATION

Thin Wall Tube w/ V-LOC Anchorage




TYPE 3 - SUPPORT/FOUNDATION




NOTES:

1. Attach Object Marker (OM) facing direction of traffic.
2. OM will also be required on opposite side if installed on a 2-Lane, 2-Way roadway.

TYPE 5 - SUPPORT/FOUNDATION



TYPE 6 - TEMPORARY MAILBOX SUPPORT




Plastic Drum NIGP: 55093383655
 Rubber Collar NIGP: 55093387102

NOTES:

1. Place on approved plastic drum as shown in the Compliant Work Zone Traffic Control Devices (CWZTCD).
2. Existing attachment hardware shall be used unless damaged. Damaged hardware shall be replaced.


TYPE 2 - SUPPORT/FOUNDATION

Thin Wall Steel Tube w/Wedge Anchor System



TYPE 4 - SUPPORT/FOUNDATION

Whitecoated steel post NIGP: 45057561107
 Multiple post NIGP: 45057257409
 Recycled Rubber post (RR) NIGP: 45057561057



GENERAL NOTES:

1. Erect post plumb or vertical.
2. When galvanized part is required galvanize in accordance with Item 445.
3. Use a concrete footing as shown or when directed. Concrete footing will be required when soils do not hold the support/foundations in a stable condition, only on Type 1, Type 2, and Type 4

SHEET 3 OF 4



MAILBOX SUPPORT AND FOUNDATION

















MB (3) - 21

FILE: MB-21.dgn	DN:	CK:	DW:	CK:
© TxDOT March 2004	CONT	SECT	JOB	HIGHWAY
2/2005	0579	02	014	FM 512
6/2005	DIST	COUNTY	SHEET NO.	
11/2006	PARIS	HUNT	92	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:26 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT\Par\is\ProjectData\FM 512 (05179-02-014)\CADD\GNN\03_ROADWAY\StdDetail\is\mb-21(1).dgn

TYPE	TYPE 1	TYPE 2	TYPE 3	TYPE 4	TYPE 5	TYPE 6
Configuration	Multiple	Single or Double	Single or Double	Single	Double	Multiple
Mailbox Size NIGP #	Outside Position: S or M Inside Position: S, M, L, XL, or LA	Single: S, M, L, XL, or LA Double: SS, SM, MM	Single: S, M, L, or XL Double: SS, SM, MM	S, M, L, XL, or LA	SS, SM, or MM	Outside Position: S or M Inside Position: S, M, L, or XL
Mailbox Post NIGP #	45057255254 (Galvanized Multiple)	45057561404 (Thin Walled Govanize)	57044325108 (Wing Channel Post)	45057561107 (Thin walled white powder coated) 45057561057 (Recycled Rubber Post: S or M only)	45057561107 (Thin Walled White Powder Coated)	45057257409 (White Powder Coated Multiple)
Post and Mailbox Hardware NIGP #	45057259009 (Wedge) 45057256500 (V-Wing Socket) 45057253002 (Bracket Extension) 45057252251 (Mailbox Bracket) 45057258001 (Part A Angle Bracket x2) 45057250255 (Plate Washer for XL/LA x2) 45057250263 (L-Bracket for XL x4)	80130598701 (Wedge) 80130238407 (Wedge Anchor) 45057253002 (Bracket Extension) 45057252343 (Double MB Bracket) 45057252350 (S. Mailbox Bracket) 45057252251 (Mailbox Bracket) 45057250255 (Plate Washer for XL/LA x2) 45057250263 (L-Bracket for XL x4)	45057541653 (Type 3 Double Mailbox Bracket) 45057252251 (Mailbox Bracket) 45057253002 (Bracket Extension) 45057258001 (Part A Angle Bracket) 45057258027 (Part B Angle Bracket) 45057250255 (Plate Washer for XL x2) 45057250263 (L-Bracket for XL x4)	55083571053 (Wedge) 55083571004 (Socket) 45057252350 (Single Mailbox Bracket) 45057253002 (Bracket Extension) 45057250255 (Plate Washer for XL/LA x2) 45057250263 (L-Bracket for XL x4)	55083571053 (Wedge) 55083571004 (Socket) 45057253002 (Bracket Extension) 45057252343 (Double Mount Bracket) 45057252251 (Mailbox Bracket x2)	55083571053 (Wedge) 55083571004 (Socket) 45057253002 (Bracket Extension) 45057252350 (Single Mount Bracket) 45057250255 (Plate Washer for XL x2) 45057250263 (L-Bracket for XL x4)
Foundation Used	Class B Concrete (Required for LA Mailboxes)	Class B Concrete (Required for LA Mailboxes)	None	Class B Concrete (not used with recycled rubber post, required for LA Mailboxes)	Class B Concrete (not required)	Class B Concrete

 NIGP: 45057250263 L-Bracket x4 for XL sized mailboxes	 NIGP: 45057252343 Double Mailbox Bracket For Type 2 and Type 4 double mount	 NIGP: 45057252350 Single Mailbox Bracket For Type 2 single and for Type 4 single and multi mount	 NIGP: 45057258001 Part "A" Angle Bracket For Type 1 multi (2 per mailbox) and Type 3 single and double
 NIGP: 45057251055 Type 6 Angle Bracket (2 per mailbox)	 NIGP: 45057252251 Mailbox Bracket For Type 1 multi and any double mount (use 2)	 NIGP: 45057253002 Bracket Extension Use 1 for a medium Mailbox Use 2 for a Large Mailbox	 NIGP: 45057258027 Part "B" Angle Bracket For Type 3 single and double
 NIGP: 80130598701 Wedge for Type 2	 NIGP: 45057250255 Plate Washer for Architecural and XL Mailboxes	 NIGP: 45057541653 Type 3 double mailbox bracket	 NIGP: 55083571053 Type 4 Mailbox Wedge
 NIGP: 55083571004 Type 4 Mailbox Socket	 NIGP: 80130238407 Type 2 Wedge Anchor	 NIGP: 45057259009 Wedge for Type 1 V-wing Socket	 NIGP: 45057256500 V-wing Socket for Type 1 Foundation

NIGP #	OBJECT MARKERS AND CONFORMABLE SHEETING
55008311759	Type 2 OM 4"x4" (3 Needed) for Type 3 Wing Channel Post
55008312906	Type 2 OM 6"x12" (1 needed) for Type 3 Wing Channel Post
80149872006	12" Conformable Reflective Yellow Sheeting for Flexible Posts

NOTES:

- Type 2 object marker in accordance with Traffic Engineering Standard Delineators & Object Markers.
- A light weight receptacle for newspaper delivery can be attached to mailbox posts if the receptacle does not touch the mailbox, present a hazard to traffic or delivery of the mail, extend beyond the front of the mailbox, or display advertising, except the publication title.

BID CODES FOR CONTRACTS

MB-(X) ASSM TY (XXX) (X)

Type of Mailbox _____

S = Single
D = Double
M = Multiple
MP = Molded Plastic


Type of Post _____

WC = Winged Channel Post
RR = Recycled Rubber
TWW = Thin Walled White Tubing
TWG = Thin Walled Galvanized Tubing
TIM = Timber


Type of Foundation _____

Ty 1 = V-Loc
Ty 2 = Wedge Anchor Steel System
Ty 3 = Winged Channel post
Ty 4 = Wedge Anchor Plastic System
Ty 5 = 4 X 4 Post


SHEET 4 OF 4

 Texas Department of Transportation		Maintenance Division Standard
NIGP PARTS LIST AND COMPATIBILITY		
MB(4)-21		
FILE: MB-21.dgn	DN: TxDOT	CK: TxDOT
© TxDOT March 2004	CONT SECT	JOB
2/2005 11/2009 4/2015	0579 02	014
6/2005 1/2011	DIST	COUNTY
11/2006 7/2014	PARIS	HUNT
		SHEET NO.
		93


DATE: 5/24/2023
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP510\WAZ-TXDOT\Projects\ProjectData\FM 512 (0579-02-01-4)\CADD\GN\03-ROADWAY\StdDetail\sgf3119 (1).dgn
 DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.




TYPICAL POST PLACEMENT



WOOD BLOCK TO ROUND WOOD POST




WOOD BLOCK TO RECTANGULAR WOOD POST




ROUTED WOOD BLOCK TO I-BEAM STEEL POST

- GENERAL NOTES**
1. THE TYPE OF POST (ROUND WOOD POST, RECTANGULAR WOOD POST, OR STEEL POST) WILL BE AS SHOWN IN THE PLANS. THE EXACT POSITION OF MBGF SHALL BE SHOWN IN THE PLANS OR AS DIRECTED BY THE ENGINEER. STEEL POSTS TO BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING."
 2. RAIL ELEMENTS SHALL MEET THE REQUIREMENTS OF ITEM 540, "METAL BEAM GUARD FENCE" EXCEPT AS MODIFIED IN THE PLANS. THE CONTRACTOR MAY FURNISH RAIL ELEMENTS OF 25'-0", OR 12'-6" (NOM.) LENGTHS. RAIL ELEMENTS MAY HAVE SLOTTED HOLES AT 3'-1 1/2" C-C OR 6'-3" C-C. A SPECIAL LENGTH OF RAIL MAY BE MANUFACTURED TO ACCOMMODATE THE DOWNSTREAM ANCHOR TERMINAL (DAT) AND THE TRANSITION SECTIONS OF GUARDRAIL.
 3. BUTTON HEAD "POST BOLTS & NUTS" SHALL MEET THE REQUIREMENTS OF (ASTM A307), AND SHALL BE OF SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND 5/8" WASHER (FWC16G) AND NOT MORE THAN 1" BEYOND IT. TRIM REMAINING BOLT LENGTH TO MEET REQUIRED LENGTH.
 4. FITTINGS (BOLTS, NUTS, AND WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING." FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
 5. CROWN SHALL BE WIDENED TO ACCOMMODATE THE METAL BEAM GUARD FENCE.
 6. THE LATERAL APPROACH TO THE GUARD FENCE, SHALL HAVE A MAXIMUM SLOPE OF 1V:10H.
 7. IF SHOWN ELSEWHERE IN THE PLANS OR AS DIRECTED BY THE ENGINEER, THE GUARD FENCE MAY BE FLARED AT A RATE OF 25:1 OR FLATTER.
 8. UNLESS OTHERWISE SHOWN IN THE PLANS, GUARD FENCE PLACED IN THE VICINITY OF CURBS SHALL BE POSITIONED SO THAT THE FACE OF CURB IS LOCATED DIRECTLY BELOW OR BEHIND THE FACE OF THE RAIL. RAIL PLACED OVER CURBS SHALL BE INSTALLED SO THAT THE POST BOLT IS LOCATED APPROXIMATELY 25 INCHES ABOVE THE GUTTER PAN OR EDGE OF SHOULDER.
 9. APPLICATIONS IN SOLID ROCK ARE ONLY ALLOWED WITH STEEL POSTS. IF SOLID ROCK IS ENCOUNTERED WITHIN 0 TO 18" OF THE FINISHED GRADE, DRILL A 24" DIA. HOLE, 24" INTO THE ROCK. IF SOLID ROCK IS ENCOUNTERED BELOW 18", DRILL A 12" DIA. HOLE, 12" INTO THE ROCK OR TO THE STANDARD EMBEDMENT DEPTH, WHICHEVER MAYBE LESS. ANY EXCESS POST LENGTH, AFTER MEETING THESE DEPTHS, MAY BE FIELD CUT TO ENSURE PROPER GUARDRAIL MOUNTING HEIGHT. BACKFILL WITH COARSE AGGREGATE MATERIAL.
 10. POSTS SHALL NOT BE SET IN CONCRETE, OF ANY DEPTH.
 11. SPECIAL FABRICATION WILL BE REQUIRED AT INSTALLATION LOCATIONS HAVING A CURVATURE OF LESS THAN 150 FT. RADIUS.
 12. UNLESS OTHERWISE SHOWN IN THE PLANS, A COMPOSITE MATERIAL BLOCK THAT MEETS THE REQUIREMENTS OF DMS-7210, "COMPOSITE MATERIAL POSTS AND BLOCKS FOR METAL BEAM GUARD FENCE" MAY BE SUBSTITUTED FOR BLOCKS OF SIMILAR DIMENSIONS. THE CONSTRUCTION DIVISION, TXDOT MAINTAINS A MATERIAL PRODUCER LIST (MPL) FOR PRODUCERS OF MATERIALS CONFORMING TO DMS-7210 ONLY PRODUCERS ON THE MPL MAY FURNISH COMPOSITE MATERIAL BLOCKS.
 13. FOR THE LOW FILL CULVERT OPTION, POSTS LOCATED PARTIALLY OR WHOLLY BETWEEN PRECAST BOX CULVERT UNITS, THE USE OF A CAST-IN-PLACE CONCRETE CLOSURE BETWEEN BOXES IS REQUIRED. THE LENGTH OF THE CAST-IN-PLACE CONCRETE CLOSURE SHALL ACCOMMODATE THE PLACEMENT OF THE LOW FILL CULVERT OPTION. SEE CONCRETE CLOSURE DETAILS ON BRIDGE STANDARD SCP-MD.
 14. GUARDRAIL HEIGHT MEASUREMENT: WHEN THE GUARDRAIL IS LOCATED ABOVE PAVEMENT, MEASURE THE HEIGHT FROM THE PAVEMENT TO THE TOP OF THE W-BEAM RAIL. WHEN THE GUARDRAIL IS LOCATED UP TO 2 FT. OFF OF THE EDGE OF PAVEMENT OR FOR A PAVEMENT OVERLAY, USE A 10-FOOT STRAIGHTEDGE TO EXTEND THE PAVEMENT/SHOULDER SLOPE TO THE BACK OF RAIL, MEASURE FROM THE BOTTOM OF STRAIGHTEDGE TO THE TOP OF RAIL. FOR GUARDRAIL LOCATED DOWN A 10:1 SLOPE, MEASURE FROM THE NOMINAL TERRAIN.




ELEVATION MID-SPAN RAIL SPLICE

SHOWING A 25'-0" SECTION OF W-BEAM RAIL. (SEE GENERAL NOTE 2)




ELEVATION 25'-0" (NOM.) W-BEAM SECTION

NOTES: SEE GENERAL NOTE 2 FOR ALLOWABLE RAIL TYPES. SEE RAIL SPLICE DETAIL FOR REQUIRED HARDWARE.



BUTTON HEAD BOLT

NOTE: SEE GENERAL NOTE 3 FOR SPLICE & POST BOLT DETAILS.




MID-SPAN RAIL SPLICE DETAIL

NOTE: GF(31), MID-SPAN RAIL SPLICES ARE REQUIRED WITH 6'-3" POST SPACINGS.

* POST(S) MAY REQUIRE FIELD MODIFICATION TO ENSURE PROPER GUARDRAIL HEIGHT.

12" x 12" x 1/4" (ASTM A36) STEEL BOTTOM PLATE WITH 1" DIA. HOLES REQUIRED WITH BOLT-THROUGH INSTALLATION.

LOW FILL CULVERT POST




NOTE: TWO INSTALLATION OPTIONS.

1. **BOLT-THROUGH OPTION:** REQUIRES A 6" MIN. SLAB THICKNESS. 7/8" DIA (ASTM A449) HEAVY HEX BOLTS WITH TWO HARDENED WASHER EACH AND HEAVY HEX NUTS. NOTE: BOLT LENGTH = SLAB PLUS 2 1/4" MIN.
2. **EPOXY ANCHOR OPTION:** THIS OPTION MAY ONLY BE USED IF THE CULVERT SLAB IS 9" MIN. THICK. THREADED ANCHOR RODS MUST BE 7/8" DIA. ASTM A449 OR A193 GRADE B7 WITH HEAVY HEX NUT, AND ONE HARDENED WASHER EACH. EMBED ANCHOR RODS 6" WITH HILTI HIT RE 500 EPOXY ADHESIVE. OTHER TYPE III CLASS C EPOXY ADHESIVES MEETING THE REQUIREMENTS OF DMS-6100, "EPOXIES AND ADHESIVES", MAY BE USED IF IT CAN BE DEMONSTRATED THAT THEY MEET OR EXCEED THE STRENGTH OF HILTI HIT RE 500 WITH THE SAME EMBEDMENT DEPTH AND THREADED ROD DIA. FOLLOW THE MANUFACTURER'S REQUIREMENTS FOR INSTALLING EPOXIED THREADED RODS. EXTEND RODS 1/4" MIN. BEYOND NUT.

NOTE: CULVERTS OF 25 FT. OR LESS, SEE GF(31)LS STANDARD FOR "LONG SPAN" OPTION.

				Design Division Standard
METAL BEAM GUARD FENCE TL-3 MASH COMPLIANT GF(31)-19				
FILE: g3119.dgn	DN: TXDOT	CK: KM	DW: VP	CK: CGL/AG
© TXDOT: NOVEMBER 2019	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARTS	HUNT	94	





DATE: 5/24/2023
 FILE: Z:\Transportation\TXDOT\STATEWIDE\36-91DP5101\WA2-TXDOT\ProjectData\FM 512 (0579-02-014)\CADD\GN\03-ROADWAY\StdDetail\sgf31tr+1320 (2).dgn
 DISCLAIMER: THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.



- (5) 1" DIA. HOLES.
- (5) 7/8" DIA. HEAVY HEX HEAD BOLTS (FACING TRAFFIC SIDE) (ASTM F3125 GR A325 OR A449).
- (10) 1 3/4" O.D. WASHER UNDER EACH HEX BOLT HEAD AND NUT.
- (5) 7/8" DIA. HEAVY HEX NUTS (ASTM A194 OR A563).


NOTE: HEAVY HEX BOLT LENGTH WILL VARY DEPENDING ON WIDTH CONCRETE RAIL, LEAVE 1" OF BOLT LENGTH PAST THE 7/8" HEX NUT. TRIM AS REQUIRED.

NOTE: CURB IS A REQUIRED COMPONENT FOR THE TRANSITION TO FUNCTION PROPERLY. SEE GENERAL NOTES: 2-4 AND 16-17.




BRIDGE APPROACH - UPSTREAM: THE NESTED RAIL LAPS OVER THE TERMINAL CONNECTOR. PLATE WASHERS ARE INSTALLED UNDER THE SPLICE NUTS AGAINST INSIDE OF CONNECTOR.

BRIDGE EXIT - DOWNSTREAM: THE TERMINAL CONNECTOR LAPS OVER THE NESTED RAIL. PLATE WASHERS ARE INSTALLED UNDER THE BOLT HEAD AGAINST OUTSIDE OF CONNECTOR.



THRIE-BEAM TERMINAL - CURB TABLE	
PRECAST CURB FULL LENGTH EQUALS 12' - 2"	
THE PRECAST CURB MAY BE FORMED INTO TWO SECTIONS.	
CURB (1) LENGTH	5' - 8"
CURB (2) LENGTH	6' - 6"
TAPER CURB (2) TO A HEIGHT OF 4" AT POST 7	
CONNECTING PRECAST CURB SECTIONS (1) & (2):	
FORM OR CORE	1" DIA. HOLE 9" LONG INTO EACH CURB END.
USE	(1) #5 GR.60 REBAR 18" LONG TO CONNECT BOTH CURBS.
SECURING PRECAST OR CAST-IN-PLACE TO FINISHED GRADE *:	
FORM OR CORE	(4) 1" DIA. HOLES, SEE PLAN AND ELEVATION VIEWS FOR HOLE LOCATIONS. DRIVE (4) #5 GR.60 REBAR STAKES 18" LONG INTO THE GROUND AND 1/2" BELOW TOP OF CURB.
FILL HOLES WITH APPROVED GROUT MIXTURE.	



* NOTES: NOT NEEDED FOR CAST-IN-PLACE. SEE TYPE II CURB DETAIL FOR REBAR AND COVER REQUIREMENTS. PERCUSSION DRILLING IS NOT PERMITTED WITH: TYPE II CURB, BRIDGE RAIL OR CONCRETE TRAFFIC RAIL.

NOTE: ** "WOOD" INDICATES DIMENSIONS FOR BOTH ROUND AND RECTANGULAR WOOD POST SYSTEMS.

GENERAL NOTES


1. CONTACT THE DESIGN DIVISION FOR DRAINAGE CUT OUT OPTIONS NEEDED WITHIN THE CURB SECTION OF THE THRIE-BEAM TRANSITION. (512) 416-2678
2. CONCRETE CURB MAY BE CAST-IN-PLACE OR PRECAST AS SHOWN ON THIS SHEET. WHEN USED IN CONJUNCTION WITH THE THRIE-BEAM TRANSITIONS, CURB SHALL BE TYPE II (5- 3/4" HEIGHT); SEE CURRENT CCGG STANDARD SHEET FOR FURTHER DETAILS. IF OTHER CURB HEIGHTS ARE SHOWN IN THE PLANS IN CONJUNCTION WITH THE TRANSITION, THE CURB HEIGHT MAY BE FROM 4" TO 8" WITH A RELATIVELY VERTICAL FACE. CONCRETE CURB SHALL BE CONTINUOUS TO THE SEVENTH POST UNLESS OTHERWISE SHOWN IN THE PLANS. SEE GENERAL NOTE:17 FOR CIRCUMSTANCES WHERE CURB CONTINUES PAST POST 7.
3. CONCRETE CURB TYPE II SUBSIDIARY TO "METAL BEAM GUARD FENCE TRANSITION". IF NO ADDITIONAL CURB IS INDICATED BEYOND THE TRANSITION, THEN ANY CURB HEIGHT GREATER THAN 4" WILL BE TAPERED DOWN BEGINNING AT THE LAST 7 FT. POST TO A MAXIMUM HEIGHT OF 4" AT POST 7. IF SHOWN ELSEWHERE IN THE PLANS, ADDITIONAL CURB UNDERNEATH GUARDRAIL WILL BE PAID FOR BY THE LINEAR FOOT.
4. UNLESS OTHERWISE SHOWN IN THE PLANS, TRANSITIONS SHALL BE PLACED WITH THE BLOCKOUT FACE IN FRONT OF OR DIRECTLY ABOVE THE CURB FACE. SEE SECTION A-A.
5. FOR ROUND WOOD POST SYSTEMS, ALL ROUND WOOD POSTS SHALL BE 7 1/2" DIA. MINIMUM THROUGHOUT THE THRIE-BEAM TRANSITION.
6. THE TYPE OF POST (ROUND WOOD POST, RECTANGULAR WOOD POST OR STEEL POST) WILL BE AS SHOWN IN THE PLANS. REFER TO GF (31) STANDARD SHEET.
7. THE POST LENGTH SHALL BE MARKED ON ALL 7' - 0" LONG POSTS BY THE MANUFACTURER. THE MARK SHALL BE LOCATED WITHIN THE TOP 1 FT. REGION OF THE POST, AT LEAST 5/8" IN HEIGHT, AND VISIBLE AFTER INSTALLATION. WOODEN POSTS SHALL BE MARKED WITH A BRAND, AND STEEL POSTS WITH A STENCIL BEFORE GALVANIZING.
8. POSTS SHALL NOT BE SET IN CONCRETE, OF ANY DEPTH.
9. RAIL ELEMENTS SHALL MEET THE REQUIREMENTS OF ITEM 540, "METAL BEAM GUARD FENCE" EXCEPT AS MODIFIED ON THE PLANS. THE THRIE-BEAM TERMINAL CONNECTOR AND THE THRIE-BEAM TRANSITION TO W-BEAM SHALL BE OF THE SAME MATERIAL, BUT SHALL NOT BE LESS THAN 10 GAUGE. CONTRACTOR SHALL VERIFY THAT THE LOCATIONS OF BOLT HOLES MATCH THOSE IN THE THRIE-BEAM TERMINAL CONNECTOR PRIOR TO ORDERING MATERIALS.
10. BUTTON HEAD "POST BOLTS & NUTS" SHALL MEET THE REQUIREMENTS OF (ASTM A307), AND SHALL BE OF SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND 5/8" WASHER (FWC16G) AND NOT MORE THAN 1" BEYOND IT. TRIM REMAINING BOLT LENGTH TO MEET REQUIRED LENGTH.
11. FITTINGS (BOLTS, NUTS, AND WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING". FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
12. CROWN SHALL BE WIDENED TO ACCOMMODATE TRANSITIONS.
13. WHERE SOLID ROCK IS ENCOUNTERED, CONTACT THE DESIGN DIVISION FOR ADDITIONAL GUIDANCE. (512) 416-2678
14. UNLESS OTHERWISE SHOWN IN THE PLANS, A COMPOSITE MATERIAL BLOCK THAT MEETS THE REQUIREMENTS OF DMS-7210, "COMPOSITE MATERIAL POSTS AND BLOCKS FOR METAL BEAM GUARD FENCE" MAY BE SUBSTITUTED FOR BLOCKS OF SIMILAR DIMENSIONS. TXDOT'S MATERIALS AND TESTS DIVISION MAINTAINS A MATERIAL PRODUCER LIST (MPL) FOR PRODUCERS OF MATERIALS CONFORMING TO DMS-7210. ONLY PRODUCERS ON THE MPL CAN FURNISH COMPOSITE MATERIAL BLOCKS.
15. REFER TO GF (31) STANDARD SHEET & BRIDGE RAILING DETAILS FOR ADDITIONAL DETAILS.
16. THE INSTALLATION OF THE TYPE II CURB IS CRITICAL FOR THE PERFORMANCE OF THE THRIE-BEAM TRANSITION SYSTEM. THE CURB PREVENTS (VEHICLE WHEEL SNAGGING) AT THE CONCRETE RAIL AND IS REQUIRED TO MEET MASH CRASH TEST CRITERIA.
17. IF CURB EXTENDS BEYOND POST 7, 25' OF NESTED W-BEAM GUARDRAIL SHALL BE INSTALLED BEYOND THE PAY LIMITS OF THRIE-BEAM TRANSITION SECTION, (SEE SHT.2). PAYMENT FOR THIS 25' SECTION WILL BE BY LINEAR FOOT, PAY ITEM "0540 6XXX MTL W-BEAM GD FEN (NESTED) (TIM POST)" OR "540 6XXX MTL W-BEAM GD FEN (NESTED) (STEEL POST)" AS APPLICABLE FOR POST TYPE. SEE SHT.2 FOR ADDITIONAL INFORMATION.

**HIGH-SPEED TRANSITION
SHEET 1 OF 2**


		<i>Design Division Standard</i>	
METAL BEAM GUARD FENCE THRIE-BEAM TRANSITION TL-3 MASH COMPLIANT			
GF (31) TR TL3-20			
FILE: g31tr+1320.dgn	DN: TXDOT	CK: KM	DW: VP
©TXDOT: NOVEMBER 2020	CONT	SECT	JOB
REVISIONS	0579	02	014
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	95

DATE: 5/24/2023
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-91\DP5101\WAZ-TXDOT_Paris\ProjectData\FM 512 (0579-02-01-4)\CADD\GN\03_ROADWAY\StdDetail\1s\gf31tr+1320 (2).dgn
 DISCLAIMER: THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.


REQUIRED ALTERNATIVE FOR CONTINUOUS CURB EXTENDING PAST POST 7 (SEE SHT. 1 GENERAL NOTE 17)



ELEVATION VIEW



SECTION D-D



THREE BEAM TRANSITION BLOCKOUT DETAILS




HIGH-SPEED TRANSITION

SHEET 2 OF 2



		<i>Design Division Standard</i>	
METAL BEAM GUARD FENCE THREE-BEAM TRANSITION TL-3 MASH COMPLIANT GF (31) TR TL3-20			
FILE: gf31tr+1320.dgn	DN: TXDOT	CK: KM	DW: KM
©TXDOT: NOVEMBER 2020	CONT	SECT	JOB
REVISIONS		0579	02
		014	FM 512
		DIST	COUNTY
		PARIS	HUNT
		SHEET NO.	
		96	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:33 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\03_ROADWAY\StdDetail\sbbed14 (1).dgn



- GENERAL NOTES**
- For more detail: See GF(31), SGT()31, GF(31)TR, and GF(31)TL2 standard sheets.
 - Quantities of metal beam guard fence (MBGF) at individual bridge ends are as shown in the plans.
 - Use average daily traffic (ADT) for the current year to determine MBGF length of need in accordance with the Roadway Design Manual unless otherwise specified. Where significant traffic volume growth is anticipated on low volume (0-750 ADT) highways, use length determinations for the higher volume category.
 - MBGF may not be required to shield departure end of bridge unless other obstacles within the horizontal clearance limits or opposing traffic indicate a MBGF consideration.
 - Downstream anchor terminals (DAT) are only for downstream end anchorage use, outside the horizontal clearance area of opposing traffic.
 - Direct connection of MBGF to concrete rails are only for downstream rail connections outside the horizontal clearance area of opposing traffic. (This requires a minimum of three standard line posts plus the DAT terminal, See Detail A)
 - The crown shall be widened to accommodate MBGF. Typically the "front slope" break should be 2'-0" from the back of the MBGF post. This applies to new construction on new alignment or where existing roadway cross section is to be widened to increase roadway width. This does not apply to rehabilitation work where existing roadway crown width is to be retained (See Typical Cross Section at MBGF).
 - For restrictive bridge widths: The MBGF should be properly transitioned from the existing bridge rail to the adjoining MBGF (See MBGF Transition Standards). Metal beam guard fence at these bridge location(s) shall be flared at the rate of 25:1 or flatter, and be of the length necessary to locate the terminal end at the 2 ft. "maximum" offset from the shoulder edge in the approach direction.
 - Transition length and post spacing will vary depending on the transition type. Transition type will be shown elsewhere in the plans.
 - A minimum 25' length of MBGF will be required.



Note: All rail elements shall be lapped in the direction of adjacent traffic.


Texas Department of Transportation Design Division Standard

BRIDGE END DETAILS
(METAL BEAM GUARD FENCE APPLICATIONS TO RIGID RAILS)

BED-14



FILE: bed14.dgn	DN: TxDOT	CK: AM	DW: BD/VP	CK: CGL
© TxDOT: December 2011	CONT	SECT	JOB	HIGHWAY
REVISED APRIL 2014 SEE (MEMO 0414)	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	97	

DISCLAIMER: THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-91\DP5101\WA2-TXDOT\Par\is\ProjectData\FM 512 (0579-02-014)\CADD\GN\03-ROADWAY\StdDetail\1s\sgt12s3118 (1).dgn




- GENERAL NOTES**
- FOR SPECIFIC INFORMATION REGARDING INSTALLATION AND TECHNICAL GUIDANCE OF THE SYSTEM, CONTACT: ROAD SYSTEMS, INC. (432)263-2435. 3616 OLD HOWARD COUNTY AIRPORT, BIG SPRING, TX 79720
 - FOR INSTALLATION, REPAIR AND MAINTENANCE REFER TO THE: MSKT END TERMINAL, PRODUCT DESCRIPTION ASSEMBLY MANUAL (PUBLICATION-062717).
 - APPLY HIGH INTENSITY REFLECTIVE SHEETING, "OBJECT MARKER" ON THE FRONT FACE OF THE DEVICE PER MANUFACTURER'S RECOMMENDATIONS. OBJECT MARKER SHALL CONFORM TO THE STANDARDS REQUIRED IN TEXAS MUTCD.
 - FOR POST (LEAVE-OUT) INSTALLATION AND GUIDANCE SEE TXDOT'S LATEST ROADWAY MOW STRIP STANDARD.
 - HARDWARE (BOLTS, NUTS, & WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING". FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
 - SYSTEM SHOWN USING STEEL WIDE FLANGE POSTS WITH COMPOSITE BLOCKOUTS.
 - A COMPOSITE MATERIAL BLOCKOUTS THAT MEETS THE REQUIREMENTS OF DMS-7210, MAY BE SUBSTITUTED FOR BLOCKOUTS OF SIMILAR DIMENSIONS. SEE CONSTRUCTION DIVISION MATERIAL PRODUCER LIST (MPL) FOR CERTIFIED PRODUCERS.
 - IF SOLID ROCK IS ENCOUNTERED IN THE AREA OF (POST 1) AND / OR (POST 2) CONTACT THE MANUFACTURER, & REFER TO THE LATEST ROADWAY MBSG STANDARD FOR INSTALLATION GUIDANCE.
 - POSTS SHALL NOT BE SET IN CONCRETE.
 - SYSTEM MUST BE ATTACHED TO STANDARD 31" MBSG.
 - UNDER NO CIRCUMSTANCES SHALL THE GUARDRAIL WITHIN THE MSKT SYSTEM BE CURVED.
 - A FLARE RATE OF UP TO 25:1 MAY BE USED TO PREVENT THE TERMINAL HEAD FROM ENCRANCHING ON THE SHOULDER. THE FLARE MAY BE DECREASED OR ELIMINATED FOR SPECIFIC INSTALLATIONS, IF DIRECTED BY THE ENGINEER.
 - THE SYSTEM IS SHOWN WITH TWO 12'-6" MBSG PANELS, ONE 25'-0" MBSG PANEL IS ALSO ALLOWED IN ITS PLACE.
 - A DRIVING CAP WITH A TIMBER OR PLASTIC INSERT SHALL BE USED WHEN DRIVING POSTS 3-8 TO PREVENT DAMAGE TO THE GALVANIZING ON TOP OF THE POST. SPECIAL DRIVING CAP TO BE USED ON LOWER POSTS 1 & 2 TO PREVENT DAMAGE TO THE WELDED PLATES.

ITEM	QTY	MAIN SYSTEM COMPONENTS	ITEM NUMBERS
A	1	MSKT IMPACT HEAD	MS3000
B	1	W-BEAM GUARDRAIL END SECTION, 12 Go.	SF1303
C	1	POST 1 - TOP (6" X 6" X 1/8" TUBE)	MTPHP1A
D	1	POST 1 - BOTTOM (6' W6X15)	MTPHP1B
E	1	POST 2 - ASSEMBLY TOP	UHP2A
F	1	POST 2 - ASSEMBLY BOTTOM (6' W6X9)	HP2B
G	1	BEARING PLATE	E750
H	1	CABLE ANCHOR BOX	S760
J	1	BCT CABLE ANCHOR ASSEMBLY	E770
K	1	GROUND STRUT	MS785
L	6	W6X9 OR W6X8.5 STEEL POST	P621
M	6	COMPOSITE BLOCKOUTS	CBSP-14
N	1	W-BEAM MGS RAIL SECTION (9'-4 1/2")	G12025
O	2	W-BEAM MGS RAIL SECTION (12'-6")	G1203A
P	6	WOOD BLOCKOUT 6" X 8" X 14"	P675
Q	1	W-BEAM MGS RAIL SECTION (25'-0")	G1209
SMALL HARDWARE			
a	2	5/8" x 1" HEX BOLT (GRD 5)	B5160104A
b	4	5/8" WASHER	W0516
c	2	5/8" HEX NUT	N0516
d	25	5/8" Dia. x 1 1/4" SPLICE BOLT (POST 2)	B580122
e	2	5/8" Dia. x 9" HEX BOLT (GRD A449)	B580904A
f	3	5/8" WASHER	W050
g	33	5/8" Dia. H.G.R NUT	N050
h	1	3/4" Dia. x 8 1/2" HEX BOLT (GRD A449)	B340854A
j	1	3/4" Dia. HEX NUT	N030
k	2	1 ANCHOR CABLE HEX NUT	N100
l	2	1 ANCHOR CABLE WASHER	W100
m	8	1/2" x 1 1/4" A325 BOLT WITH CAPTIVE WASHER	SB12A
n	8	1/2" STRUCTURAL NUTS	N012A
o	8	1 1/8" O.D. x 3/8" I.D. STRUCTURAL WASHERS	W012A
p	1	BEARING PLATE RETAINER TIE	CT-100ST
q	6	5/8" x 10" H.G.R. BOLT	B581002
r	1	OBJECT MARKER 18" X 18"	E3151



NOTE: TXDOT GENERIC APPROACH GRADING LAYOUT USED FOR ALL TANGENT TYPE END TREATMENTS.

NOTE: THIS STANDARD IS A BASIC REPRESENTATION OF THE MSKT END TERMINAL, IT IS NOT INTENDED TO REPLACE THE PRODUCT DESCRIPTION ASSEMBLY MANUAL.


Design Division Standard


SINGLE GUARDRAIL TERMINAL

MSKT-MASH-TL-3

SGT (12S) 31-18

FILE: sgt12s3118.dgn	DN: TXDOT	CK: KM	DW: VP	CK: CL
© TXDOT: APRIL 2018	CONT SECT	JOB	HIGHWAY	
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY		SHEET NO.
	PARIS	HUNT		98






DATE: 5/24/2023
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TXDOT_Par1s\ProjectData\FM 512 (0579-02-014)\CADD\GNV03-ROADWAY\StdDetail\1513120 (1).dgn
 DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY TXDOT FOR ANY PURPOSE WHATSOEVER. TXDOT ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.



- ### GENERAL NOTES
- FOR SPECIFIC INFORMATION REGARDING INSTALLATION AND TECHNICAL GUIDANCE OF THE SYSTEM, CONTACT: SPIG INDUSTRY, INC. AT 1(267) 644-9510. 14675 INDUSTRIAL PARK RD; BRISTOL, VA 24202
 - FOR INSTALLATION, REPAIR AND MAINTENANCE REFER TO THE MANUFACTURER'S; SGET END TERMINAL, PRODUCT DESCRIPTION ASSEMBLY MANUAL.
 - MANUFACTURER WILL APPLY HIGH INTENSITY REFLECTIVE SHEETING, "OBJECT MARKER" TO THE FACE PLATE OF THE DEVICE PER MANUFACTURER'S RECOMMENDATIONS. THE OBJECT MARKER SHALL CONFORM TO THE STANDARDS REQUIRED IN TEXAS MUTCD.
 - THE NOMINAL HEIGHT OF THE GUARDRAIL BEAM IS 31 INCHES WITH A TOLERANCE OF +/- ONE INCH.
 - FOR POST (LEAVE-OUT) INSTALLATION AND GUIDANCE SEE TXDOT'S LATEST ROADWAY MOW STRIP STANDARD.
 - (POST 2 THROUGH POST 8) ARE MODIFIED STEEL-YIELDING POSTS WITH YIELDING HOLES AT GROUND LEVEL. THERE ARE NO SUBSTITUTE POSTS.
 - POSTS SHALL NOT BE SET IN CONCRETE.
 - IF SOLID ROCK IS ENCOUNTERED FOR ANY OF THE POSTS IN THE SYSTEM, CONTACT THE MANUFACTURER FOR SPECIFIC INSTALLATION GUIDANCE.
 - HARDWARE (BOLTS, NUTS, & WASHERS) SHALL BE GALVANIZED IN ACCORDANCE WITH ITEM 445, "GALVANIZING". FITTINGS SHALL BE SUBSIDIARY TO THE BID ITEM.
 - A COMPOSITE MATERIAL BLOCKOUT THAT MEETS DMS-7210 REQUIREMENTS MAY BE SUBSTITUTED FOR AN APPROVED WOOD BLOCKOUT. SEE CONSTRUCTION DIVISION MATERIAL PRODUCER LIST (MPL) FOR CERTIFIED PRODUCERS.
 - THE ENTIRE SYSTEM MUST BE INSTALLED IN A STRAIGHT LINE WITHOUT ANY CURVE. HOWEVER, THE SYSTEM CAN BE OFFSET BY TWO FEET AS SHOWN ON THE APPROACH GRADING DETAIL TO HELP OFF-SET THE IMPACT HEAD FROM SHOULDER OF THE ROAD.

ITEM	QTY	MAIN SYSTEM COMPONENTS	ITEM #
A	1	SGET IMPACT HEAD	SIH1A
B	1	MODIFIED GUARDRAIL PANEL 12'-6" 12GA	126SPZGP
B2	1	MODIFIED GUARDRAIL PANEL 9'-4 1/2" 12GA	GP94
C	2	STANDARD GUARDRAIL PANEL 12'-6" 12GA	GP126
D	1	STANDARD GUARDRAIL PANEL 25'-0" 12GA	GP25
E	7	MODIFIED YIELDING I-BEAM POST W6x8.5	YP6MOD
F	6	COMPOSITE BLOCKOUT 6" X 8" X 14"	CBO8
G	6	WOOD BLOCKOUT 6" X 8" X 14"	WB08
H	1	STRUT 3" X 3" X 80" X 1/4" A36 ANGLE	STR80
I	1	FOUNDATION TUBE 6" X 8" X 72" X 3/16"	FNDT6
J	1	WOOD BREAKAWAY POST 5 1/2" X 7 1/2" X 50"	WBRK50
K	1	WOOD STRIKE BLOCK	WSBLK14
L	1	STRIKE PLATE 1/4" A36 BENT PLATE	SPLT8
M	1	REINFORCEMENT PLATE 12 GA. GR55	REPLT17
N	1	GUARDRAIL GRABBER 2 1/2" X 2 1/2" X 16 1/2"	GGR17
O	1	BEARING PLATE 8" X 8 5/8" X 5/8" A36	BPLT8
P	1	PIPE SLEEVE 4 1/4" X 2 3/8" O.D. (2 1/8" I.D.)	PSLV4
Q	1	BCT CABLE 3/4" X 81" LENGTH	CBL81

ITEM	QTY	SMALL HARDWARE	ITEM #
a	1	5/8" X 12" GUARDRAIL BOLT 307A HDG	12GRBLT
b	7	5/8" X 10" GUARDRAIL BOLT 307A HDG	10GRBLT
c	33	5/8" X 1 1/4" GR SPlice BOLTS 307A HDG	1GRBLT
d	3	5/8" FLAT WASHER F436 A325 HDG	58FW436
e	1	5/8" LOCK WASHER HDG	58LW
f	39	5/8" GUARDRAIL HEX NUT HDG	58HN563
g	2	1/2" X 2" STRUT BOLT A325 HDG	2BLT
h	6	1/2" X 1 1/4" PLATE BOLT A325 HDG	125BLT
i	16	1/2" FLAT WASHER F436 A325 HDG	12FWF436
j	8	1/2" LOCK WASHER HDG	12LW
k	8	1/2" HEX NUT A563 HDG	12HN563
l	4	3/8" X 3" HEX LAG SCREW GR5 HDG	38LS
m	4	3/8" FLAT WASHER F436 A325 HDG	38FW844
n	2	1" FLAT WASHER F436 A325 HDG	1FWF436
o	2	1" HEX NUT A563DH HDG	1HN563
p	1	18" TO 24" LONG ZIP TIE RATED 175-200LB	ZPT18
q	1	1 1/2" X 4" SCH-40 PVC PIPE	PSPCR4
r	1	RFID CHIP RATED MIL-STD-810F	RFID810F
s	1	IMPACT HEAD REFLECTIVE SHEETING	RS30M





NOTE: THIS STANDARD IS A BASIC REPRESENTATION OF THE SGET TERMINAL SYSTEM AND IS NOT INTENDED TO REPLACE THE MANUFACTURER'S ASSEMBLY MANUAL.

Design Division Standard





SPIG INDUSTRY, LLC
SINGLE GUARDRAIL TERMINAL
SGET - TL-3 - MASH
SGT (15) 31-20

FILE: sg153120.dgn	DN: TXDOT	CK: KM	DW: VP	CK: VP
© TXDOT: APRIL 2020	CONT: 0579	SECT: 02	JOB: 014	HIGHWAY: FM 512
REVISIONS	DIST: PARIS	COUNTY: HUNT	SHEET NO. 99	

DATE: 5/24/2023 6:20:34 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DPS101\WA2-TXDOT\Proj\cadd\03-ROADWAY\StdDetail\std034-19.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



RETROFIT WITH FLARED WING
 (Showing 9" high and 8" wide curbs, higher and wider curbs similar)




ANGLE SHOE DETAILS
 Angle Shoe shown is detailed for one side only, other side similar. For other side shoe must be built for opposite hand.

- 1 Post length = Top of rail elevation minus bottom of drilled shaft elevation.
- 2 Terminal Connectors and associated hardware are to be paid for under the Item "Metal Beam Guard Fence". The appropriate Metal Beam Guard Fence Transitions or Downstream Anchor Terminal must be attached to the bridge rail and extended along the embankment.
- 3 Top HSS can be shorter than bottom HSS 5/8" plus or minus.
- 4 Match existing bridge curb height.
- 5 Cast transition curb 1'-0" into soil or top of concrete approach slab. Remove any asphaltic concrete or mow strip if present.
- 6 Match existing bridge curb face on traffic side of transition curb. Transition curb 6" x 1'-6" taper will remain vertical.
- 7 Showing first post for a TL-3 rated guard fence transition. First post for a TL-2 rated guard fence transition or a guard fence downstream anchor terminal is 4'-4 3/4".
- 8 HSS Transition Sections must have one soil mounted end post embedded in an unreinforced, Class "C" concrete drilled shaft as shown, and a minimum of one curb mounted post per transition section.
- 9 HSS Panel Sections must have a minimum of three posts and a maximum of eight posts per panel section.
- 10 HSS Expansion Joint or L HSS Splice Joint as required.
- 11 Use 9" minimum for both expansion joints and construction/controlled joints.
- 12 HSS 6 x 6 x 1/4 (ASTM A1085 or A500 Gr C).
- 15 Remove all existing structure area from top of existing curb. Cut and grind flush all existing reinforcing extending from top of existing curb and paint ends with two coats of zinc-rich paint conforming to the Item "Galvanizing".
- 16 When post is mounted to the transition curb on flared wings as shown, transition curb must be supported laterally by the existing wingwall/curb.


SHEET 1 OF 2

		Bridge Division Standard	
RETROFIT GUIDE FOR T131RC RAIL ON CURBS			
TYPE T131RC			
FILE: rstd034-19.dgn	DN: TXDOT	CK: JMH	DW: JTR
©TXDOT September 2019	CONT	SECT	JOB
REVISIONS	0579	02	014
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	100




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:35 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-9\DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\03_ROADWAY\StdDetail\std034-19.dgn



SECTION A-A OF 18" HIGH CURBS

(Showing example of 8" Min width curb, wider curbs similar)



18" HIGH CURB BASE PLATE DETAIL

- ⑫ HSS 6 x 6 x 1/4 (ASTM A1085 or A500 Gr C).
- ⑬ 1 3/4" Bolt Projection (Typ).
- ⑭ See "Material Notes" for anchor Bolt information.
- ⑮ Remove existing railing (including posts), cut and grind anchor bolts flush and paint ends with two coats of zinc-rich paint conforming to the Item "Galvanizing".
- ⑯ See elsewhere in plans for dimensions (curb width and height, slab and overlay thickness). Slope of curb may differ from what is shown. Adjust base plate as necessary to conform to curb face geometry.





5/24/2023

SHEET 2 OF 2

		Bridge Division Standard	
RETROFIT GUIDE FOR T131RC RAIL ON CURBS			
TYPE T131RC			
FILE: rstd034-19.dgn	DN: TxDOT	CK: JMH	DW: JTR
REVISIONS	CONT	SECT	JOB
0579	02	014	FM 512
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	101	

BEGIN PROJECT
CSJ: 0579-02-014
STA 0+50.00



Rational Q Values									
Drainage Area	Precipitation Area	AREA (AC)	Tc (min)	C	I - 10YR	I - 100YR	Q - 10YR	Q - 25YR	Q - 100YR
					Existing Conditions				
C1	HUNT	20.77	24.3	0.40	4.40	6.37	36.55	43.20	52.92
C2	HUNT	20.75	30.0	0.35	3.93	5.70	28.54	33.70	41.39
C3	HUNT	105.25	41.8	0.35	3.24	4.73	119.36	141.46	174.24
C4	HUNT	29.57	24.8	0.35	4.37	6.31	45.23	53.30	65.30
C5	HUNT	37.82	73.2	0.36	2.27	3.33	30.91	36.62	45.34
C7	HUNT	147.49	122.0	0.35	1.59	2.37	82.08	98.08	122.34
C8	HUNT	82.72	116.3	0.35	1.65	2.45	47.77	57.03	70.93
C9	HUNT	311.38	102.9	0.35	NRCS Method		255.90	356.70	518.80
C10	HUNT	129.30	107.8	0.35	1.74	2.58	78.75	93.68	116.76
C11	HUNT	130.43	132.2	0.35	1.51	2.24	68.93	82.17	102.26
C13	HUNT	50.38	41.3	0.37	3.26	4.76	60.77	71.96	88.73
C14	HUNT	72.46	40.8	0.37	3.29	4.79	88.21	104.30	128.43
C15	HUNT	49.87	45.8	0.37	3.06	4.48	56.47	66.98	82.67
C17	HUNT	462.85	100.0	0.37	NRCS Method		153.80	320.90	641.50
C18	HUNT	327.20	95.4	0.37	NRCS Method		115.30	244.30	492.60



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512

OVERALL DRAINAGE AREA MAP

SHEET 1 OF 1

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	TEXAS	HUNT	102
CONTROL	SECTION	JOB	
0579	02	014	

NOTES:
DESIGN OF DRAINAGE FACILITIES BASED UPON THE TXDOT HYDRAULIC DESIGN MANUAL, SEPTEMBER 2019.
DRAINAGE AREAS DETERMINED BY SURVEY DATA, USGS TOPOGRAPHIC MAPS, DIGITAL ELEVATION MODELS, AS-BUILT PLANS AND FIELD OBSERVATIONS.

STRUCTURE INLET STA	DRAINAGE AREA IDENTIFIER	AREA (AC)	HYDRAULIC CONDITION	STRUCTURE DESCRIPTION	STRUCTURE MANNINGS "n"	STRUCTURE SLOPE (FT/FT)	ENTRANCE / EXIT TYPE		FLOOD FREQUENCY	FLOW (Q) (CFS)	HEADWATER ELEV (FT)	TAILWATER ELEV (FT)	TAILWATER VELOCITY (FT/S)	FLOW OVER ROADWAY (CFS)	ROADWAY ELEV OVERTOP (FT)
							LEFT	RIGHT							
30+70.25	DA 1	20.77	EXISTING	1-30" x 43' CMP	0.022	0.0277	LEFT	PROJ	10 YEAR	36.55	670.22	666.20	4.50	0.00	670.26
			RIGHT	PROJ	100 YEAR	52.92	670.5	666.39	4.98	14.05					
			PROPOSED	1-30" x 42' RCP	0.012	0.015	LEFT	PSET-SC	10 YEAR	36.55	669.71	666.17	4.50	0.00	670.93
			RIGHT	PSET-SC	100 YEAR	52.92	671.07	666.36	4.95	6.26					
44+89.85	DA 2	20.75	EXISTING	1-5'x3' x 33' SBC	0.012	0.0179	LEFT	FW-0	10 YEAR	28.54	654.61	653.05	4.02	0.00	657.47
			RIGHT	FW-0	100 YEAR	41.39	655.08	653.21	4.49	0.00					
			PROPOSED	1-5'x3' x 41' SBC	0.012	0.0178	LEFT	FW-0	10 YEAR	28.54	654.51	652.98	4.02	0.00	658.14
			RIGHT	FW-0	100 YEAR	41.39	654.95	653.14	4.49	0.00					
76+57.36	DA 3	105.25	EXISTING	1-6'x4' x 33' SBC	0.012	0.0066	RIGHT	FW-0	10 YEAR	119.36	634.98	632.30	6.00	0.00	636.53
			LEFT	FW-0	100 YEAR	174.24	636.29	632.61	6.66	0.00					
			PROPOSED	1-6'x4' x 39' SBC	0.012	0.0187	RIGHT	FW-0	10 YEAR	119.36	634.66	632.27	6.00	0.00	637.20
			LEFT	FW-0	100 YEAR	174.24	635.84	632.58	6.66	0.00					
94+41.83	DA 4	29.57	EXISTING	1-36" x 50' CMP	0.022	0.0034	RIGHT	PROJ	10 YEAR	45.23	630.26	627.47	4.74	0.00	631.06
			LEFT	PROJ	100 YEAR	65.30	631.22	627.68	5.24	7.30					
			PROPOSED	1-36" x 42' RCP	0.012	0.0049	RIGHT	PSET-SC	10 YEAR	45.23	630.28	627.43	4.74	0.00	631.73
			LEFT	PSET-SC	100 YEAR	65.30	631.80	627.64	5.24	2.03					
162+95.74	DA 5	37.82	EXISTING	1-5'x2.5' x 33' SBC	0.012	0.0176	LEFT	FW-0	10 YEAR	30.91	578.47	576.86	4.12	0.00	657.47
			RIGHT	FW-0	100 YEAR	45.34	578.98	577.03	4.61	0.00					
			PROPOSED	1-5'x2.5' x 43' SBC	0.012	0.0177	LEFT	FW-0	10 YEAR	30.91	578.37	576.75	4.12	0.00	658.14
			RIGHT	FW-0	100 YEAR	45.34	578.85	576.92	4.61	0.00					
228+99.24	DA 7	147.49	EXISTING	1-8'x8' x 34.5' SBC	0.012	0.0032	LEFT	FW-0	10 YEAR	82.08	573.89	572.24	5.13	0.00	581.10
			RIGHT	FW-0	100 YEAR	122.34	574.67	572.48	5.80	0.00					
			PROPOSED	1-8'x8' x 40.5' SBC	0.012	0.0032	LEFT	FW-0	10 YEAR	82.08	573.63	572.23	5.13	0.00	581.77
			RIGHT	FW-0	100 YEAR	122.34	574.33	572.47	5.80	0.00					
231+94.15	DA 8	82.72	EXISTING	1-5'x4' x 39' SBC	0.012	0.00692	LEFT	FW-0	10 YEAR	47.77	578.59	576.85	4.68	0.00	581.17
			RIGHT	FW-0	100 YEAR	70.93	579.3	577.06	5.24	0.00					
			PROPOSED	1-5'x4' x 39' SBC	0.012	0.00692	LEFT	FW-0	10 YEAR	47.77	578.35	576.86	4.68	0.00	581.84
			RIGHT	FW-0	100 YEAR	70.93	579.01	577.07	5.24	0.00					
255+83.82	DA 9	311.38	EXISTING	2-8.5'x8' x 79' MBC	0.012	0.0027	LEFT	FW-S	10 YEAR	255.90	577.2	575.58	7.27	0.00	586.56
			RIGHT	FW-S	100 YEAR	518.80	579.18	576.39	8.81	0.00					
			PROPOSED	2-8.5'x8' x 79' MBC	0.012	0.0027	LEFT	N/A	10 YEAR	255.90	577.2	575.58	7.27	0.00	587.23
			RIGHT	N/A	100 YEAR	518.80	579.18	576.39	8.81	0.00					
257+32.72	DA 10	129.30	EXISTING	1-8'x7' x 52.6' SBC	0.012	0.038	RIGHT	FW-0	10 YEAR	78.75	578.45	575.12	5.20	0.00	586.48
			LEFT	FW-0	100 YEAR	116.76	579.16	575.37	5.84	0.00					
			PROPOSED	1-8'x7' x 58.6' SBC	0.012	0.038	RIGHT	FW-0	10 YEAR	78.75	578.35	575.02	5.20	0.00	587.15
			LEFT	FW-0	100 YEAR	116.76	578.99	575.27	5.84	0.00					
295+16.99	DA 11	130.43	EXISTING	2-30" x 56' RCP	0.012	0.0034	RIGHT	PROJ	10 YEAR	68.93	581.11	578.44	5.20	0.00	583.51
			LEFT	PROJ	100 YEAR	102.26	583.46	578.70	5.80	0.00					
			PROPOSED	2-30" x 48' RCP	0.012	0.0034	RIGHT	CH-PW-0	10 YEAR	68.93	581.09	578.44	5.20	0.00	584.18
			LEFT	CH-PW-0	100 YEAR	102.26	583.44	578.70	5.80	0.00					
312+88.60	DA 13	50.38	EXISTING	1-8'x4' x 47' SBC	0.012	0.0239	LEFT	FW-S	10 YEAR	60.77	580.28	578.04	4.81	0.00	584.06
			RIGHT	FW-S	100 YEAR	88.73	580.85	578.25	5.39	0.00					
			PROPOSED	1-8'x4' x 57' SBC	0.012	0.0239	LEFT	FW-S	10 YEAR	60.77	579.98	577.99	4.81	0.00	584.73
			RIGHT	FW-S	100 YEAR	88.73	580.53	578.20	5.39	0.00					
370+06.67	DA 14	72.46	EXISTING	2-36" x 50' CMP	0.022	0.0076	LEFT	PROJ	10 YEAR	88.21	584.77	582.13	5.57	0.00	585.56
			RIGHT	PROJ	100 YEAR	128.43	585.8	582.40	6.18	13.90					
			PROPOSED	2-36" x 40' RCP	0.012	0.015	LEFT	CH-PW-0	10 YEAR	88.21	584.62	581.77	5.57	0.00	586.23
			RIGHT	CH-PW-0	100 YEAR	128.43	586.27	582.04	6.18	0.80					
375+20.36	DA 15	49.87	EXISTING	1-36" x 116.5' RCP	0.012	0.0075	LEFT	PSET-SC	10 YEAR	56.47	594.84	590.60	5.04	0.00	594.85
			RIGHT	PSET-SC	100 YEAR	82.67	595.18	590.84	5.58	22.46					
			PROPOSED	1-36" x 128.5' RCP	0.012	0.0075	LEFT	PSET-SC	10 YEAR	56.47	594.85	590.51	5.04	0.00	595.52
			RIGHT	PSET-SC	100 YEAR	82.67	595.79	590.75	5.58	16.35					
456+79.07	DA 17	462.85	EXISTING	1-7'x4' x 35.5' SBC	0.012	0.0078	RIGHT	PW-2	10 YEAR	153.80	564.11	561.23	6.38	0.00	568.09
			LEFT	PW-2	100 YEAR	641.50	569.83	562.81	9.38	278.42					
			PROPOSED	1-7'x4' x 40.5' SBC	0.012	0.0078	RIGHT	PW-2	10 YEAR	153.80	564.17	561.25	6.38	0.00	568.76
			LEFT	PW-2	100 YEAR	641.50	569.31	562.83	9.38	294.00					
484+24.53	DA 18	327.20	EXISTING	1-9'x3.5' x 36' SBC	0.012	0.0084	RIGHT	PW-2	10 YEAR	115.30	558.66	556.69	5.65	0.00	563.65
			LEFT	PW-2	100 YEAR	492.60	564.56	558.04	8.47	105.99					
			PROPOSED	1-9'x3.5' x 41' SBC	0.012	0.0084	RIGHT	PW-2	10 YEAR	115.30	558.73	556.61	5.65	0.00	564.32
			LEFT	PW-2	100 YEAR	492.60	564.60	557.96	8.47	106.76					



IDCUS  8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825





FM 512

HYDRAULIC DATA COMPUTATIONS

SHEET 1 OF 1

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	103
CONTROL	SECTION	JOB	
0579	02	014	

5/24/2023 6:20:37 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W42-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\05_DRAINAGE\CULVERT SHEETS\FM512_DRCULV_01.dgn




NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES

ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	4
402 6001	TRENCH EXCAVATION PROTECTION	LF	22
432 6031	RIPRAP (STONE PROTECTION) (12IN)	CY	18
464 6007	RC PIPE (CL III) (30 IN)	LF	42
467 6417	SET (TY II) (30 IN) (RCP) (3:1) (C)	EA	2
496 6007	REMOV STR (PIPE)	LF	43
400 6006	CUT & RESTORING PAV	SY	12.2



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
CULVERT LAYOUT 01
STA 30+70.25

SHEET 1 OF 1


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	104

STANDARDS: PSET-SC, SRR

ELEVATION
CULVERT 01
CL FM 512 STA 30+70.25
EXIST 1 - 30" X 43' CMP TO BE REPLACED
PROP 1 - 30" X 42' RCP W/PSET-SC


**100%
SUBMITTAL**

5/24/2023 6:20:38 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\DWG\05_DRAINAGE\CULVERT SHEETS\FM512_DRCULV_02.dgn



- NOTES:**
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.


ESTIMATED QUANTITIES				
ITEM	DESCRIPTION	UNIT	QTY	
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	5	
403 6001	TEMPORARY SPL SHORING	SF	50	
432 6002	RIPRAP (CONC) (5 IN)	CY	6	
462 6051	CONC BOX CULV (5 FT X 3 FT) (EXTEND)	LF	8	
466 6151	WINGWALL (FW - O) (HW=4 FT)	EA	2	
480 6001	CLEAN EXIST CULVERTS	EA	1	
496 6005	REMOV STR (WINGWALL)	EA	2	



ELEVATION

CULVERT 02
 Q FM 512 STA 44+89.85
 EXIST 1 - 5' X 3' X 33' SBC TO BE EXTENDED
 PROP RIGHT EXTEND 4' W/FW-0
 PROP LEFT EXTEND 4' W/FW-0

STANDARDS: FW-0, SCC-3 & 4, SCC-MD



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
 Suite 200
 San Antonio, Tx. 78240
 (210) 448-1800
 FIRM # F-6825






FM 512

**CULVERT LAYOUT 02
 STA 44+89.85**


SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	105




- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES			
ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	4
403 6001	TEMPORARY SPL SHORING	SF	99
432 6002	RIPRAP (CONC) (5 IN)	CY	9
432 6031	RIPRAP (STONE PROTECTION) (12 IN)	CY	13.5
462 6055	CONC BOX CULV (6 FT X 4 FT) (EXTEND)	LF	6
466 6152	WINGWALL (FW - 0) (HW=5 FT)	EA	2
480 6001	CLEAN EXIST CULVERTS	EA	1
496 6005	REMOV STR (WINGWALL)	EA	2



STANDARDS: FW-0, SCC-3 & 4, SCC-MD, SRR





IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
 PLANNERS ENGINEERS MANAGERS



FM 512
CULVERT LAYOUT 03
 STA 76+57.36

SHEET 1 OF 1			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	106
CONTROL	SECTION	JOB	
0579	02	014	

EXIST. R.O.W. -----




NOTES:

1. HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
2. CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES

ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	4
402 6001	TRENCH EXCAVATION PROTECTION	LF	10
464 6008	RC PIPE (CL III) (36 IN)	LF	42
467 6448	SET (TY II) (36 IN) (RCP) (3:1) (C)	EA	2
496 6007	REMOV STR (PIPE)	LF	50
400 6006	CUT & RESTORE PAV	SY	15



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825




FM 512
CULVERT LAYOUT 04
STA 94+41.83

SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	107

ELEVATION
CULVERT 04
CL FM 512 STA 94+41.83
EXIST 1 - 36" X 50' CMP TO BE REPLACED
PROP 1 - 36" X 42' RCP W/PSET-SC

STANDARDS: PSET-SC




NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES

ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	7
403 6001	TEMPORARY SPL SHORING	SF	80
432 6002	RIPRAP (CONC) (5 IN)	CY	4.6
432 6031	RIPRAP (STONE PROTECTION) (12 IN)	CY	17
462 6091	CONC BOX CULV (5FT X 2.5FT) (EXTEND)	LF	10
466 6150	WINGWALL (FW - O) (HW=3 FT)	EA	2
480 6001	CLEAN EXIST CULVERTS	EA	1
496 6005	REMOV STR (WINGWALL)	EA	2



ELEVATION

CULVERT 05
 CL FM 512 STA 162+95.74
 EXIST 1 - 5' X 2.5' X 33' SBC TO BE EXTENDED
 PROP RIGHT EXTEND 4' W/FW-O
 PROP LEFT EXTEND 6' W/FW-O

STANDARDS: FW-O, SCC-5 & 6, SCC-MD, SRR



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
 Suite 200
 San Antonio, Tx. 78240
 (210) 448-1800
 FIRM # F-6825



FM 512



CULVERT LAYOUT 05
 STA 162+95.74

SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	108



100%
SUBMITTAL

5/24/2023 6:20:39 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\05_DRAINAGE\CULVERT SHEETS\FM512_DRCLV_07.dgn



- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES			
ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	6
403 6001	TEMPORARY SPL SHORING	SF	160
432 6002	RIPRAP (CONC) (5 IN)	CY	27
432 6031	RIPRAP (STONE PROTECTION) (12 IN)	CY	44
462 6067	CONC BOX CULV (8 FT X 8 FT) (EXTEND)	LF	6
466 6156	WINGWALL (FW - 0) (HW=9 FT)	EA	2
480 6001	CLEAN EXIST CULVERTS	EA	1
496 6005	REMOV STR (WINGWALL)	EA	2




IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
CULVERT LAYOUT 07
STA 228+99.24


SHEET 1 OF 1			
STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	109



NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES			
ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	3
403 6001	TEMPORARY SPL SHORING	SF	70
432 6002	RIPRAP (CONC) (5 IN)	CY	8.4
432 6031	RIPRAP (STONE PROTECTION) (12 IN)	CY	13
462 6052	CONC BOX CULV (5 FT X 4 FT) (EXTEND)	LF	2
466 6152	WINGWALL (FW - 0) (HW=5 FT)	EA	2
480 6001	CLEAN EXIST CULVERTS	EA	1
496 6005	REMOV STR (WINGWALL)	EA	2



Juan E. Trevino-Guerra
141908
5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
CULVERT LAYOUT 08
STA 231+94.15




SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	110

STANDARDS: FW-0, SCC-5 & 6, SCC-MD, SRR


ELEVATION
CULVERT 08
CL FM 512 STA 231+94.15
EXIST 1 - 5' X 4' X 39' SBC TO BE EXTENDED
PROP RIGHT BREAKBACK 2', ADD W/FW-0
PROP LEFT EXTEND 2' W/FW-0

5/24/2023 6:20:40 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\05_DRAINAGE\CULVERT SHEETS\FM512_DRCLUV_10.dgn



- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES			
ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	30
403 6001	TEMPORARY SPL SHORING	SF	130
432 6002	RIPRAP (CONC) (5 IN)	CY	22.2
462 6066	CONC BOX CULV (8 FT X 7 FT) (EXTEND)	LF	6
466 6155	WINGWALL (FW - 0) (HW=8 FT)	EA	2
480 6001	CLEAN EXIST CULVERTS	EA	1
496 6005	REMOV STR (WINGWALL)	EA	2





IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



FM 512
CULVERT LAYOUT 10
STA 257+32.72


SHEET 1 OF 1

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	111




- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES				
ITEM	DESCRIPTION	UNIT	QTY	
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	14	
432 6031	RIPRAP (STONE PROTECTION) (12 IN)	CY	18	
466 6099	HEADWALL (CH-PW-0) (DIA=30IN)	EA	2	
480 6001	CLEAN EXIST CULVERTS	EA	1	
496 6007	REMOV STR (PIPE)	LF	16	



ELEVATION
 CULVERT 11
 C FM 512 STA 295+16.99
 EXIST 2 - 30" X 56' RCP
 PROP RIGHT REMOVE 4', ADD W/CH-PW-0
 PROP LEFT REMOVE 4', ADD W/CH-PW-0

STANDARDS: CH-PW-0, SRR





IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
 PLANNERS ENGINEERS MANAGERS



FM 512
CULVERT LAYOUT 11
 STA 295+16.99

SHEET 1 OF 1


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	112



NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES				
ITEM	DESCRIPTION	UNIT	QTY	
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	10	
403 6001	TEMPORARY SPECIAL SHORING	SF	100	
432 6002	RIPRAP (CONC) (5 IN)	CY	15.2	
462 6063	CONC BOX CULV (8 FT X 4 FT) (EXTEND)	LF	10	
466 6166	WINGWALL (FW - S) (HW=5 FT)	EA	2	
480 6001	CLEAN EXIST CULVERTS	EA	1	
496 6005	REMOV STR (WINGWALL)	EA	2	



ELEVATION

CULVERT 13
 Q FM 512 STA 312+88.60
 EXIST 1 - 8' X 4' X 47' SBC TO BE EXTENDED
 PROP RIGHT EXTEND 2' W/FW-S
 PROP LEFT EXTEND 8' W/FW-S

STANDARDS: FW-S, SCC-8, SCC-MD





JUAN E. TREVINO-GUERRA
 141908
 LICENSED PROFESSIONAL ENGINEER
 5/24/2023

IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
 PLANNERS ENGINEERS MANAGERS




FM 512
CULVERT LAYOUT 13
 STA 312+88.60

SHEET 1 OF 1				HIGHWAY NO
				FM 512
STATE	DISTRICT	COUNTY	SHEET NO	
TEXAS	PARIS	HUNT	113	
CONTROL	SECTION	JOB		
0579	02	014		



- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES			
ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	27
400 6006	CUT & RESTORING PAV	SY	26
402 6001	TRENCH EXCAVATION PROTECTION	LF	22
432 6031	RIPRAP (STONE PROTECTION) (12IN)	CY	48
464 6008	RC PIPE (CL III) (36 IN)	LF	80
466 6101	HEADWALL (CH-PW-0) (DIA=36IN)	EA	2
496 6007	REMOV STR (PIPE)	LF	100





JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512
CULVERT LAYOUT 14
STA 370+06.67

SHEET 1 OF 1			HIGHWAY NO FM 512
STATE TEXAS	DISTRICT PARIS	COUNTY HUNT	SHEET NO 114
CONTROL 0579	SECTION 02	JOB 014	




NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES

ITEM	DESCRIPTION	UNIT	QTY
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	3
467 6454	SET (TY II) (36 IN) (RCP) (6:1) (P)	EA	1
480 6001	CLEAN EXIST CULVERTS	EA	1
496 6004	REMOV STR (SET)	EA	1



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512

CULVERT LAYOUT 15
STA 375+20.36

SHEET 1 OF 2




STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	115

STANDARDS: PSET-SC

ELEVATION
CULVERT 15
C FM 512 STA 375+20.36
EXIST 1 - 36" X 70.5' RMP TO BE EXTENDED
PROP LEFT PSET-SC


MATCH LINE A

MATCH LINE A



- NOTES:
- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
 - CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES				
ITEM	DESCRIPTION	UNIT	QTY	
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	7	
464 6008	RC PIPE (CL III) (36 IN)	LF	12	
467 6454	SET (TY II) (36 IN) (RCP) (6:1) (P)	EA	1	
496 6004	REMOV STR (SET)	EA	1	



ELEVATION

CULVERT 15
 C FM 512 STA 375+20.36
 EXIST 1 - 36" X 70.5' RCP TO BE EXTENDED
 PROP RIGHT EXTEND 12' W/PSET-SC

STANDARDS: PSET-SC



Juan E. Trevino-Guerra
 5/24/2023

IDCUS 8632 Fredericksburg Rd.
 Suite 200
 San Antonio, Tx. 78240
 (210) 448-1800
 FIRM # F-6825





FM 512
CULVERT LAYOUT 15
 STA 375+20.36

SHEET 2 OF 2

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	116


5/24/2023 6:20:41 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DRG\05_DRAINAGE\CULVERT SHEETS\FM512_DR_BG-CULV_16.dgn



NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.
- 2' DEEP FLOWABLE FILL AROUND AND UNDER THE APRON THEN FILL WITH DIRT (EMBANKMENT)
- TYPICAL 8 SF OF CONCRETE SPALLING REPAIR ON EACH END OF EACH BARREL.

ESTIMATED QUANTITIES			
ITEM	DESCRIPTION	UNIT	QTY
104 6028	REMOVING CONC (MISC)	SY	40
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	7
401 6001	FLOWABLE BACKFILL	CY	5
429 6007	CONC STR REPAIR (VERTICAL & OVERHEAD)	SF	80
432 6031	RIPRAP (STONE PROTECTION) (12IN)	CY	13
480 6001	CLEAN EXIST CULVERTS	EA	1



Paul A. Warden, P.E. 579412023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825





FM 512
CULVERT LAYOUT 16
BRIDGE CLASS
STA 415+92.00
NBI: 01-117-0-0579-02-004

SHEET 1 OF 1			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	117
CONTROL	SECTION	JOB	
0579	02	014	

STANDARDS: SRR

100%
SUBMITTAL



5/24/2023 6:20:42 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\WA2-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\05_DRAINAGE\CULVERT SHEETS\FM512_DRCLUV_17.dgn



NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES				
ITEM	DESCRIPTION	UNIT	QTY	
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	2	
403 6001	TEMPORARY SPL SHORING	SF	568	
462 6059	CONC BOX CULV (7 FT X 4 FT) (EXTEND)	LF	5	
466 6194	WINGWALL (PW - 2) (HW=5 FT)	EA	2	
480 6001	CLEAN EXIST CULVERTS	EA	1	
496 6005	REMOV STR (WINGWALL)	EA	2	



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825




FM 512
CULVERT LAYOUT 17
STA 456+79.07

SHEET 1 OF 1			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	118
CONTROL	SECTION	JOB	
0579	02	014	

STANDARDS: PW, SCC-7, SCC-MD, ECD


ELEVATION
CULVERT 17
C FM 512 STA 456+79.07
EXIST 1 - 7' X 4' X 35.5' SBC TO BE EXTENDED
PROP RIGHT EXTEND 3' W/PW-2
PROP LEFT EXTEND 2' W/PW-2



NOTES:

- HORIZONTAL ALIGNMENT DATA IS FOR INFORMATION ONLY. MATCH EXISTING ROADWAY.
- CONTRACTOR TO FIELD VERIFY ELEVATIONS AND CONSTRUCT PROPOSED STRUCTURES TO ALLOW PROPER DRAINAGE FLOW.

ESTIMATED QUANTITIES				
ITEM	DESCRIPTION	UNIT	QTY	
132 6019	EMBANKMENT (VEHICLE) (ORD COMP) (TY B)	CY	3	
403 6001	TEMPORARY SPL SHORING	SF	592	
462 6100	CONC BOX CULV (9 FT X 4 FT) (EXTEND)	LF	5	
466 6194	WINGWALL (PW - 2) (HW=5 FT)	EA	2	
480 6001	CLEAN EXIST CULVERTS	EA	1	
496 6005	REMOV STR (WINGWALL)	EA	2	



JTG
5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512
CULVERT LAYOUT 18
STA 484+24.53

SHEET 1 OF 1				HIGHWAY NO
				FM 512
STATE	DISTRICT	COUNTY	SHEET NO	
TEXAS	PARIS	HUNT	119	
CONTROL	SECTION	JOB		
0579	02	014		

STANDARDS: PW, SCC-9, SCC-MD, ECD

ELEVATION
CULVERT 18
CL FM 512 STA 484+24.53
EXIST 1 - 9' X 4' X 36' SBC TO BE EXTENDED
PROP RIGHT EXTEND 3' W/PW-2
PROP LEFT EXTEND 2' W/PW-2

DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:42 PM
FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WAZ-TxDOT-Par1.s\Project\DOT\FM 512 (0579-02-014)\CADD\05_DRA\IMAGE\STANDARD\01-20.dgn

Culvert Station and/or Creek Name followed by applicable end (Lt, Rt or Both)	Description of Box Culvert No. Spans ~ Span X Height	Max Fill Height (Ft)	Applicable Box Culvert Standard (4)	Applicable Wingwall or End Treatment Standard	Skew Angle (0°, 15°, 30° or 45°)	Side Slope or Channel Slope Ratio (SL:1)	T Culvert Top Slab Thickness (In)	U Culvert Wall Thickness (In)	C Estimated Curb Height (Ft)	Hw Height of Wingwall (Ft) (1)	A Curb to End of Wingwall (Ft)	B Offset of End of Wingwall (Ft)	Lw Length of Longest Wingwall (Ft)	Ltw Culvert Toewall Length (Ft)	Atw Anchor Toewall Length (Ft)	Riprap Apron (CY)	Class "C" Conc (Curb) (CY) (2)	Class "C" Conc (Wingwall) (CY) (3)	Total Wingwall Area (SF)
CULVERT 02 - STA 44+89.85 (BOTH)	1 ~ 5' x 3'	4'	SCC-5&6	FW-0	0	4:1	8"	7"	0.7	3.917	14.333	8.275	16.551	N/A	N/A	6.0	0.2	9.4	140
CULVERT 03 - STA 76+57.36 (BOTH)	1 ~ 6' x 4'	5'	SCC-5&6	FW-0	0	4:1	8"	7"	0.7	4.917	18.333	10.585	21.170	N/A	N/A	9.0	0.2	14.6	222
CULVERT 05 - STA 162+95.74 (BOTH)	1 ~ 5' x 2.5'	3.5'	SCC-5&6	FW-0	0	4:1	8"	7"	0.7	3.417	12.333	7.121	14.241	N/A	N/A	4.6	0.2	7.8	106
CULVERT 07 - STA 228+99.24 (BOTH)	1 ~ 8' x 8'	9'	SCC-8	FW-0	0	4:1	8"	7"	0.7	8.917	34.333	19.822	39.645	N/A	N/A	27.0	0.4	42.4	734
CULVERT 08 - STA 231+94.15 (BOTH)	1 ~ 5' x 4'	5'	SCC-5&6	FW-0	0	4:1	8"	7"	0.8	4.917	18.333	10.585	21.170	N/A	N/A	8.4	0.2	14.6	222
CULVERT 10 - STA 257+32.72 (BOTH)	1 ~ 8' x 7'	8'	SCC-8	FW-0	0	4:1	8"	7"	0.8	7.917	30.333	17.513	35.026	N/A	N/A	22.2	0.4	34.0	288
CULVERT 13 - STA 312+88.60 (BOTH)	1 ~ 8' x 4'	5'	SCC-7	FW-S	45	4:1	8"	7"	0.8	4.917	18.333	31.754	36.667	N/A	N/A	15.2	0.4	18.8	332
CULVERT 17 - STA 456+79.07 (BOTH)	1 ~ 7' x 4'	5'	SCC-7	PW-2	0	4:1	8"	7"	2.9	5.167	N/A	N/A	16.667	8.167	N/A	0.0	0.4	23.0	332
CULVERT 18 - STA 484+24.53 (BOTH)	1 ~ 9' x 4'	5'	SCC-9	PW-2	0	4:1	8"	7"	2.9	5.167	N/A	N/A	16.667	10.167	N/A	0.0	0.4	23.4	332

NOTES:

Skew = 0° on SW-0, FW-0, SETB-CD, SETB-SW-0, and SETB-FW-0 standard sheets; 30° maximum for safety end treatment

SL:1 = Horizontal : 1 Vertical

- Side slope at culvert for flared or straight wingwalls.
- Channel slope for parallel wingwalls.
- Slope must be 3:1 or flatter for safety end treatments.

T = Box culvert top slab thickness. Dimension can be found on the applicable box culvert standard sheet.

U = Box culvert wall thickness. Dimension can be found on the applicable box culvert standard sheet.

C = Curb height

See applicable wing or end treatment standard sheets for calculations of Hw, A, B, Lw, Ltw, Atw, and Total Wingwall Area.

Hw = Height of wingwall

A = Distance from face of curb to end of wingwall (not applicable to parallel or straight wingwalls)

B = Offset of end of wingwall (not applicable to parallel or straight wingwalls)

Lw = Length of longest wingwall.

Ltw = Length of culvert toewall (not applicable when using riprap apron)

Atw = Length of anchor toewall (applicable to safety end treatment only)

Total Wingwall Area = Wingwall area in sq. ft. for two wingwalls (one structure end) if Lt or Rt. Area for four wingwalls (two structure ends) if Both.


- Round the wall heights shown to the nearest foot for bidding purposes.
- Concrete volume shown is for box culvert curb only. For curbs using the Box Culvert Rail Mounting Details (RAC) standard sheet quantities shown must be increased by a factor of 2.25. If Class S concrete is required for the top slab of the culvert, also provide Class S concrete for the curb. Curb concrete is considered part of the Box Culvert for payment.
- Concrete volume shown is total of wings, footings, culvert toewall (if any), anchor toewalls (if any) and wingwall toewalls. Riprap aprons, culverts, and curb quantities are not included.
- Regardless of the type of culvert shown on this sheet, the Contractor has the option of furnishing cast-in-place or precast culverts unless otherwise shown elsewhere on the plans. If the Contractor elects to provide culverts of a different type than those shown on this sheet, it is the Contractor's responsibility to make the necessary adjustments to the dimensions and quantities shown.



				Bridge Division Standard	
<h2>BOX CULVERT SUPPLEMENT</h2> <h3>WINGS AND END TREATMENTS</h3>					
BCS					
FILE:	bcstde1-20.dgn	DN:	TxDOT	CK:	TxDOT
©TxDOT	February 2020	CON:	0579	SECT:	02
REVISIONS		JOB:	014	HIGHWAY:	FM 512
		DIST:	PARIS	COUNTY:	HUNT
				SHEET NO.:	120


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:42 PM
 FILE: Z:\Transportation\on\Txdot\PS&E\STATEWIDE\36-9\DP5101\WAZ-TxDOT\Par1.s\Project\DOT\PS&E\STATEWIDE_36-9\DP5101\WAZ-TxDOT\Par1.s\2\ecdstde1-20.dgn




TYPICAL SECTION


Used for curbs over 1'-0" to 5'-0"




BARS V (#5)
Spaced at 12" Max



BARS L (#5)
Spaced at 12" Max



OPTIONAL BARS L (#5)
Spaced at 12" Max



BARS U (#4)
Spaced at 12" Max

- ① "C" is equal to the culvert top slab thickness. For precast boxes with slabs less than 8" thick, see SCP-MD standard for additional details.
- ② Adjust normal culvert slab bars as necessary to clear obstructions.
- ③ Place bars L as shown. Tilt hook as necessary to maintain cover.
- ④ Place normal culvert curb bars H(#4) as shown. Adjust as necessary to clear obstructions.
- ⑤ Additional bars H(#4) as required to maintain 12" Max spacing.
- ⑥ Replace normal culvert curb bars K with one bar U and two bars V as shown spaced at 12" Max. Adjust length of bars V as necessary to maintain clear cover.
- ⑦ Optional bars L are to be used only for precast box culverts with 3'-0" closure pour.
- ⑧ Quantities shown are for Contractor's information only. Quantities are per linear foot of curb length. The value in table can be interpolated for intermediate values of curb height, "C". Quantity includes bars K (when applicable).

TABLE OF ESTIMATED CURB QUANTITIES ⑧		
Curb Height "C"	Conc (CY/LF)	Reinf Steel (Lb/LF)
1'-0"	0.037	10.4
1'-6"	0.056	14.5
2'-0"	0.074	15.6
2'-6"	0.093	18.0
3'-0"	0.111	19.0
3'-6"	0.130	21.3
4'-0"	0.148	22.4
4'-6"	0.167	24.8
5'-0"	0.185	25.9

CONSTRUCTION NOTES:
 Adjust reinforcing steel as necessary to provide 1/4" cover.
 For vehicle safety, top of the curb must not project more than 3" above the finished grade.

MATERIAL NOTES:
 Provide Grade 60 reinforcing steel.
 Provide galvanized reinforcing steel if required elsewhere in the plans.
 Provide Class "C" concrete (f'c = 3,600 psi) minimum for curbs.
 Provide bar laps, where required, as follows:
 · Uncoated or galvanized ~ #4 = 1'-8" Min

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 These extended curb details have sufficient strength to allow for future retrofit of Type T631 or T631LS railing. These details are suitable for use with PR11, PR22 and PR3 type rails. These details are not suitable for the mounting of other rail types. For new construction using T631 or T631LS railing, use the T631-CM standard.
 This Curb is considered as part of the Box Culvert for payment.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.



EXTENDED CURB DETAILS
 FOR BOX CULVERTS WITH CURBS OVER 1'-0" TO 5'-0" TALL

ECD

FILE: ecdstde1-20.dgn	DN: GAF	CK: TxDOT	DW: TxDOT	CK: GAF
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	121	

DATE: 5/24/2023 6:20:43 PM
 FILE: Z:\Transportation\on\TXDOT\PS&E\STATEWIDE\36-9\DP5101\WA2-TXDOT-Par\s\Projec+D+o\FM_512_(0579-02-014)\CADD\GN\05_DRAINAGE\ST+d\Det\i.s.(3).fw-0stde-20.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TABLE OF DIMENSIONS AND REINFORCING STEEL
(Wings for one structure end)

Maximum Wingwall Height Hw	Dimensions				Variable Reinforcing				Estimated Quantities per ft of wing length (2-wings) ⁽³⁾	
	W	X	Y	Z	Bars J1		Bars J2			
					Size	Spa	Size	Spa		
2'-6"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	33.73	0.248
3'-0"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	37.07	0.261
3'-6"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	37.74	0.273
4'-0"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	38.41	0.285
4'-6"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	41.75	0.330
5'-0"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	45.09	0.343
5'-6"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	45.75	0.355
6'-0"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	46.42	0.367
7'-0"	3'-8"	1'-9"	1'-3"	7"	#4	1'-0"	#4	1'-0"	52.77	0.414
8'-0"	4'-2"	2'-0"	1'-6"	8"	#5	1'-0"	#4	1'-0"	60.19	0.486
9'-0"	4'-8"	2'-3"	1'-9"	8"	#4	6"	#4	6"	81.49	0.535
10'-0"	5'-2"	2'-6"	2'-0"	8"	#5	6"	#4	6"	97.25	0.584
11'-0"	5'-8"	2'-9"	2'-3"	8"	#6	6"	#5	6"	133.65	0.634
12'-0"	6'-2"	3'-0"	2'-6"	9"	#7	6"	#5	6"	162.29	0.721
13'-0"	6'-8"	3'-3"	2'-9"	11"	#7	6"	#5	6"	178.80	0.856
14'-0"	7'-2"	3'-6"	3'-0"	1'-0"	#8	6"	#5	6"	216.78	0.959
15'-0"	7'-8"	4'-0"	3'-0"	1'-1"	#9	6"	#6	6"	283.06	1.068
16'-0"	8'-2"	4'-6"	3'-0"	1'-3"	#9	6"	#6	6"	297.02	1.234

TABLE OF WINGWALL REINFORCING
(2-wings)

Bar	Size	No.	Spa
D	#5	~	1'-0"
E	#4	~	1'-0"
F	#4	~	1'-0"
G	#6	4	~
M	#4	4	~
P	#4	~	1'-0"
R	#5	6	~
V	#4	~	1'-0"

TABLE OF ESTIMATED CULVERT TOEWALL QUANTITIES

Bar	Size	No.	Spa
L	#4	~	1'-6"
Q	#4	1	~
Reinf (Lb/Ft)			2.45
Conc (CY/Ft)			0.037

WING DIMENSION FORMULAS:

(All values are in feet.)

$Hw = H + T + C - 0.250'$
 $A = (Hw - 0.333') (SL)$
 $B = (A) \text{ tangent } (30^\circ)$
 $Lw = (A) + \text{cosine } (30^\circ)$


For cast-in-place culverts:
 $Ltw = (N) (S) + (N + 1) (U)$

For precast culverts:
 $Ltw = (N) (2U + S) + (N - 1) (0.5')$


Total wingwall area (two wings - SF) = $(Hw + 0.333') (Lw)$

Hw = Height of wingwall
 SL:1 = Side slope ratio (horizontal:1 vertical)
 Lw = Length of wingwall
 Ltw = Culvert toewall length
 N = Number of culvert spans


See applicable box culvert standard sheet for H, S, T, and U values.




BARS D




BARS R




BARS J1




BARS V



BARS L




BARS J2




INSIDE ELEVATION

(Showing reinforcing. Culvert and culvert toewall reinforcing not shown for clarity.)




PLAN

(Showing dimensions.)




SECTION A-A




WINGWALL

CORNER DETAILS

(Culvert and culvert toewall reinforcing not shown for clarity.)



FOOTING AND TOEWALL



SECTION B-B

(5)

- 1 Extend Bars P 3'-0" minimum into bottom slab of box culvert.
- 2 Adjust as necessary to maintain 1 #2" clear cover and 4" minimum between bars.
- 3 Quantities shown are based on an average wing height for two wings (one structure end). To determine total quantities for two wings, multiply the tabulated values by Lw.
- 4 Recommended values of side slope are: 2:1, 3:1, 4:1, and 6:1.
- 5 When shown elsewhere on the plans, construct 5" deep concrete riprap. Payment for riprap is as required by Item 432, "Riprap". Unless otherwise shown on the plans or directed by the Engineer, provide a 6" wide by 1'-6" deep reinforced concrete toewall along all edges of the riprap adjacent to natural ground; reinforce the toewall by extending typical riprap reinforcing into the toewall; and extend construction joints or grooved joints oriented in the direction of flow across the full distance of the riprap at intervals of approximately 20'. When such riprap is provided, the culvert toewall shown in SECTION B-B will not be required.
- 6 At Contractor's option, culvert toewall may be ended flush with wingwall toewall. Adjust reinforcing as needed.
- 7 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Box Culvert Rail Mounting Details (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- 8 For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade.
 Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.

MATERIAL NOTES:

Provide Class C concrete (fc=3,600 psi).
 Provide Grade 60 reinforcing steel.
 Provide galvanized reinforcing steel if required elsewhere in the plans.
 In riprap concrete synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing unless noted otherwise.

GENERAL NOTES:

Designed according to AASHTO LRFD Bridge Design Specifications.
 When structure is founded on solid rock, depth of toewalls for culverts and wingwalls may be reduced or eliminated as directed by the Engineer.
 See Box Culvert Supplement (BCS) standard sheet for additional dimensions and information.
 The quantities for concrete and reinforcing steel resulting from the formulas given on this sheet are for Contractor's information only.

Cover dimensions are clear dimensions, unless noted otherwise. Reinforcing dimensions are out-to-out of bars.

				Bridge Division Standard	
CONCRETE WINGWALLS WITH FLARED WINGS FOR 0° SKEW BOX CULVERTS					
FW-0					
FILE:	fw-0stde-20.dgn	DN:	GAF	CK:	CAT
©/TxDOT	February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS		0579	02	014	FM 512
		DIST	COUNTY	SHEET NO.	
		PARIS	HUNT	122	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:43 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DPS101\WA2-TxDOT\Projects\DOT\PS&E\STATEWIDE_36-91DPS101\WA2-TxDOT\Drawings\DWG\05-DRAWING\ASST-dwg.dgn

TABLE OF DIMENSIONS AND REINFORCING STEEL (Wings for one structure end)										
Maximum Wingwall Height Hw	Dimensions				Variable Reinforcing				Estimated Quantities per ft of wing length (2-wings)	
	W	X	Y	Z	Bars J1		Bars J2		Reinf (Lb/Ft)	Conc (CY/Ft)
2'-6"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	33.73	0.248
3'-0"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	37.07	0.261
3'-6"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	37.74	0.273
4'-0"	2'-5"	1'-0"	9"	7"	#4	1'-0"	#4	1'-0"	38.41	0.285
4'-6"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	41.75	0.330
5'-0"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	45.09	0.343
5'-6"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	45.75	0.355
6'-0"	3'-2"	1'-6"	1'-0"	7"	#4	1'-0"	#4	1'-0"	46.42	0.367
7'-0"	3'-8"	1'-9"	1'-3"	7"	#4	1'-0"	#4	1'-0"	52.77	0.414
8'-0"	4'-2"	2'-0"	1'-6"	8"	#5	1'-0"	#4	1'-0"	60.19	0.486
9'-0"	4'-8"	2'-3"	1'-9"	8"	#4	6"	#4	6"	81.49	0.535
10'-0"	5'-2"	2'-6"	2'-0"	8"	#5	6"	#4	6"	97.25	0.584
11'-0"	5'-8"	2'-9"	2'-3"	8"	#6	6"	#5	6"	133.65	0.634
12'-0"	6'-2"	3'-0"	2'-6"	9"	#7	6"	#5	6"	162.29	0.721
13'-0"	6'-8"	3'-3"	2'-9"	11"	#7	6"	#5	6"	178.80	0.856
14'-0"	7'-2"	3'-6"	3'-0"	1'-0"	#8	6"	#5	6"	216.78	0.959
15'-0"	7'-8"	4'-0"	3'-0"	1'-1"	#9	6"	#6	6"	283.06	1.068
16'-0"	8'-2"	4'-6"	3'-0"	1'-3"	#9	6"	#6	6"	297.02	1.234

TABLE OF WINGWALL REINFORCING (2-wings)			
Bar	Size	No.	Spa
DL	#5	~	1'-0"
DS	#5	~	1'-0"
E	#4	~	1'-0"
F	#4	~	1'-0"
G	#6	4	~
M	#4	4	~
P	#4	~	1'-0"
RS	#5	3	~
RL	#5	3	~
V	#4	~	1'-0"

TABLE OF ESTIMATED CULVERT TOEWALL QUANTITIES			
Bar	Size	No.	Spa
L	#4	~	1'-6"
Q	#4	1	~
Reinf (Lb/Ft)			2.45
Conc (CY/Ft)			0.037

WING DIMENSION FORMULAS:
 (All values are in feet.)
 $H_w = H + T + C - 0.250'$
 $A = (H_w - 0.333')(SL)$
 $B = (A) [\tan(\theta + 15^\circ)]$
 $L_w = (A) + [\cos(\theta + 15^\circ)]$


For cast-in-place culverts:
 $L_{tw} = [(N)(S) + (N + 1)(U)] + \cosine \theta$

For precast culverts:
 $L_{tw} = [(N)(2U + S) + (N - 1)(0.5')] + \cosine \theta$








Total wingwall area (two wings ~ FW) = $0.5 (H_w + 0.333') (L_w + A)$

Hw = Height of wingwall
 SL:1 = Side slope ratio (horizontal:1 vertical)
 A = Length of short wingwalls
 Lw = Length of long wingwall
 Lt看 = Culvert toewall length
 N = Number of culvert spans
 θ = Culvert skew

See applicable box culvert standard sheet for H, S, T, and U values.



- Extend Bars P 3'-0" minimum into bottom slab of box culvert.
- Adjust as necessary to maintain 1 #2" clear cover and 4" minimum between bars.
- Quantities shown are based on an average wing height for two wings (one structure end). To determine total quantities for two wings, multiply the tabulated values by 0.5 x (A + Lw).
- Recommended values of side slope are: 2:1, 3:1, 4:1, and 6:1.
- When shown elsewhere on the plans, construct 5" deep concrete riprap. Payment for riprap is as required by Item 432, "Riprap". Unless otherwise shown on the plans or directed by the Engineer, provide a 6" wide by 1'-6" deep reinforced concrete toewall along all edges of the riprap adjacent to natural ground; reinforce the toewall by extending typical riprap reinforcing into the toewall; and extend construction joints or grooved joints oriented in the direction of flow across the full distance of the riprap at intervals of approximately 20'. When such riprap is provided, the culvert toewall shown in SECTION B-B will not be required.
- At Contractor's option, culvert toewall may be ended flush with wingwall toewall. Adjust reinforcing as needed.
- Applicable values of skew are: 15°, 30°, and 45°.
- Typical wingwall angle for all skews.
- 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Box Culvert Rail Mounting Details (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade.
 Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional information will be allowed for this work.



MATERIAL NOTES:
 Provide Class C concrete (f'c=3,600 psi).
 Provide Grade 60 reinforcing steel.
 Provide galvanized reinforcing steel if required elsewhere in the plans.
 In riprap concrete, synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 When structure is founded on solid rock, depth of toewalls for culverts and wingwalls may be reduced or eliminated as directed by the Engineer.
 See Box Culvert Supplement (BCS) standard sheet for additional dimensions and information.
 The quantities for concrete and reinforcing steel resulting from the formulas given on this sheet are for Contractor's information only.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing dimensions are out-to-out of bars.

Bridge Division Standard


CONCRETE WINGWALLS WITH FLARED WINGS FOR SKEWED BOX CULVERTS

FW-S

FILE: fw-sside-20.dgn	DN: GAF	CK: CAT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
DIST	COUNTY	SHEET NO.		
PARIS	HUNT	123		


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:44 PM
FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-9\IDP5101\WA2-TxDOT\Project\DOT\512 (0579-02-014)\CADD\DN\05_DRAINAGE\StdDet\015\psetrps-20 (2).dgn




PLAN VIEW - 12" THRU 24"

(Showing spigot end connection.)




LONGITUDINAL ELEVATION - 12" THRU 24"

(Showing spigot end connection.)




SECTION A-A




MULTIPLE PIPE INSTALLATION

- Slope as shown elsewhere in the plans. Slope of 6:1 or flatter is required for vehicle safety.
- Provide cement stabilized bedding and backfill in accordance with the Item, "Excavation and Backfill for Structures". Bedding and backfill is considered subsidiary to the Item 467, "Safety End Treatment". When concrete riprap is specified around the safety end treatment, backfill as directed by Engineer.
- Fill the top 4" of void between precast end treatments with concrete riprap. Concrete riprap is considered subsidiary to the Item 467, "Safety End Treatment".
- Adjust clear distance between pipes to provide for the minimum distance between safety end treatments.
- Safety pipe runners are required for multiple pipe culverts with more than two pipes.




INSTALLATION DETAIL FOR SAFETY PIPE RUNNERS

(If required)



OPTION A



OPTION B

END DETAILS FOR INSTALLATION OF SAFETY PIPE RUNNERS

(If required)

REQUIREMENTS FOR CULVERT PIPES AND SAFETY PIPE RUNNERS

Pipe I.D.	Min Wall Thickness	Min O.D.	Min O.D. at Tapered End	Min Reinf Requirements (sq. in. per ft. of Pipe)	Max Slope	Min Length of Unit	Pipe Runner Requirements		Required Pipe Runner Sizes		
							Single Pipe	Multiple Pipe	Nominal Dia	O.D.	I.D.
12"	2"	16"	16"	0.07 Circ.	6:1	4' - 0"	No	(5)	3" STD	3.500"	3.068"
15"	2 1/4"	19 1/2"	19"	0.07 Circ.	6:1	5' - 8"	No	(5)	3" STD	3.500"	3.068"
18"	2 1/2"	23"	21 1/2"	0.07 Circ.	6:1	7' - 3"	No	(5)	3" STD	3.500"	3.068"
24"	3"	30"	27"	0.07 Circ.	6:1	10' - 6"	No	(5)	3" STD	3.500"	3.068"
30"	3 1/2"	37"	31"	0.18 Circ.	6:1	12' - 1"	No	Yes	4" STD	4.500"	4.026"
36"	4"	44"	36"	0.19 Ellip.	6:1	15' - 4"	Yes	Yes	4" STD	4.500"	4.026"
42"	4 1/2"	51"	41 1/2"	0.23 Ellip.	6:1	18' - 7"	Yes	Yes	4" STD	4.500"	4.026"

MATERIAL NOTES:

Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.
Provide pipe runners meeting the requirements of ASTM A53 (Type E or S, Gr B), ASTM A500 Gr B, or API 5LX52.
Galvanize steel components except reinforcing steel after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.


GENERAL NOTES:

Precast safety end treatment for reinforced concrete pipe (RCP) may be used for TYPE II end treatment as specified in Item 467, "Safety End Treatment".
When precast safety end treatment is used as a Contractor's alternate to mitered RCP, riprap will not be required unless noted otherwise on the plans.
Manufacture precast concrete end sections in accordance with Item 464, "Reinforced Concrete Pipe" and in accordance with ASTM Specification C-76, Class III, Wall B for circular pipe.
Provide precast concrete end sections with a spigot or bell end for compatibility to upstream or downstream end conditions with sufficient annular space to allow for grout, mortar, cold applied asphalt joint compound or pre-formed plastic gasket material.
Methods of lifting shall be provided by the manufacturer for ease of loading, unloading and installation.
Pipe runners are designed for a traversing load of 10,000 Lbs at yield as recommended by Research Report 280-2F, "Safety Treatment of Roadside Parallel-Drainage Structures", Texas Transportation Institute, March 1981.

				Bridge Division Standard	
PRECAST SAFETY END TREATMENT TYPE II ~ PARALLEL DRAINAGE PSET-RP					
FILE: psetrps-20.dgn	DN: RLW	CK: KLR	DW: JTR	CK: GAF	
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0579	02	014	FM 512	
	DIST	COUNTY	SHEET NO.		
	PARIS	HUNT	124		


REQUIREMENTS FOR CULVERT PIPES AND SAFETY PIPE RUNNERS

Pipe I.D.	RCP Wall "B" Thickness	TP Wall Thickness (8)	"D" (1)	Slope	Min Length of Unit	Single Pipe		Multiple Pipes	
						Skew	Pipe Runners Required	Skew	Pipe Runners Required
12"	2"	1.15"	17.00"	3:1	2' - 11"	≤ 45°	No	≤ 45°	No
				4:1	3' - 6"				
				6:1	4' - 9"				
15"	2 1/4"	1.30"	20.50"	3:1	3' - 8"	≤ 45°	No	≤ 45°	No
				4:1	4' - 7"				
				6:1	6' - 5"				
18"	2 1/2"	1.60"	24.00"	3:1	4' - 6"	≤ 45°	No	≤ 45°	No
				4:1	5' - 8"				
				6:1	8' - 0"				
24"	3"	1.95"	31.00"	3:1	6' - 2"	≤ 45°	No	= 30°	No
				4:1	7' - 10"				
				6:1	11' - 3"				
30"	3 1/2"	2.65"	38.50"	3:1	7' - 10"	= 15°	No	= 15°	No
				4:1	10' - 1"				
				6:1	14' - 8"				
36"	4"	2.75"	45.50"	3:1	9' - 5"	= 0°	No	≥ 0°	Yes
				4:1	12' - 3"				
				6:1	17' - 11"				
42"	4 1/2"	2.7"	52.50"	3:1	11' - 1"	≥ 0°	Yes	≥ 0°	Yes
				4:1	14' - 5"				
				6:1	21' - 2"				



PLAN

(Showing bell end connection.)



LONGITUDINAL ELEVATION

(Showing bell end connection.)

SAFETY PIPE RUNNER DIMENSIONS

Max Safety Pipe Runner Length	Required Pipe Runner Size		
	Pipe Size	Pipe O.D.	Pipe I.D.
11' - 2"	3" STD	3.500"	3.068"
15' - 6"	3 1/2" STD	4.000"	3.548"
20' - 10"	4" STD	4.500"	4.026"
35' - 4"	5" STD	5.563"	5.047"

- 1 Dimension "D" is based on reinforced concrete pipe (RCP) meeting the requirements of ASTM C-76, Class III, (RCP Wall "B" thickness). Adjust "D" for any other wall thickness used. For thermoplastic pipe (TP) take into account the annular space requirements for grouted connections.
- 2 Slope as shown elsewhere in plans. Slope of 3:1 or flatter is required for vehicle safety.
- 3 Toewall to be used only when dimension is shown elsewhere in the plans.
- 4 Fill the top 4" of void between precast end treatments with concrete riprap. Concrete riprap is considered subsidiary to the Item 467, "Safety End Treatment".
- 5 Adjust clear distance between pipes to provide for the minimum distance between safety end treatments.
- 6 Measured along slope.
- 7 Provide cement stabilized bedding and backfill in accordance with the Item 400, "Excavation and Backfill for Structures". Bedding and backfill is considered subsidiary to the Item 467, "Safety End Treatment". When concrete riprap is specified around the safety end treatment, backfill as directed by Engineer.
- 8 Thermoplastic pipe wall thickness may vary. Adjust accordingly. Thermoplastic pipe requires the safety end treatments to have a bell end for grouted connections.

GENERAL NOTES:

Precast safety end treatment for reinforced concrete pipe (RCP), and thermoplastic pipe (TP) may be used for TYPE II end treatment as specified in Item "Safety End Treatment".

When precast safety end treatment is used as a Contractor's alternate to mitered RCP, riprap will not be required unless noted otherwise on the plans.

Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.

Manufacture this product in accordance with Item 467, "Safety End Treatment" except as noted below:

A. Provide minimum reinforcing of #4 at 6" (Grade 40) or #4 at 9" (Grade 60) each way or 6"x6" - D12 x D12 or 5"x5" - D10 x D10 welded wire reinforcement (WWR).

B. For precast (steel formed) sections, provide Class "C" concrete (f_c = 3,600 psi).


At the option and expense of the Contractor, the next larger size of safety end treatment may be furnished as long as the "D" dimension cast is that of the required size of pipe.

Pipe runners are designed for a traversing load of 1,800 Lbs at yield as recommended by Research Report 280-1, "Safety Treatment of Roadside Cross-Drainage Structures", Texas Transportation Institute, March 1981.

Provide safety pipe runners, cross pipes, pipe support posts, and pipe stubs meeting the requirements of ASTM A53 (Type E or S, Grade B), ASTM A500 (Grade B), or API 5LX52.


Galvanize all steel components except reinforcing steel after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.

Connect RCP using the Optional Joint for RCP detail shown or in accordance with Item 464 "Reinforced Concrete Pipe". Connect TP by grouting. See Pipe and Box Grouted Connections (PBGC) standard for grouted connections with TP and precast safety end treatment.




END DETAIL FOR INSTALLATION OF SAFETY PIPE RUNNERS

(If required)



OPTIONAL JOINT FOR RCP

(Showing joint between RCP and precast safety end treatment)




OPTION A


DETAIL A

OPTION B


(If required)




MULTIPLE PIPE INSTALLATION



OPTION WITH SQUARE BOTTOM



OPTION WITH INVERT BOTTOM



INSTALLATION DETAIL FOR SAFETY PIPE RUNNERS

(If required)

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practices Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:44 PM
FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Proj\cadd\PS&E\STATEWIDE_36-91DP5101.dgn


Bridge Division Standard

PRECAST SAFETY END TREATMENT TYPE II ~ CROSS DRAINAGE

PSET-SC


FILE: psetscs-21.dgn	DN: RLW	CK: KLR	DW: JTR	CK: GAF
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS 12-21: Added 42" TP	0579	02	014	FM 512
DIST	COUNTY	SHEET NO.		
PARIS	HUNT			125

DATE: 5/24/2023 6:20:44 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TXDOT\Project\DOT\PS&E\STATEWIDE\05_DRAINAGE\STANDARD\17_Psetspss-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




PLAN

(Showing bell end connection.)




LONGITUDINAL ELEVATION

(Showing bell end connection.)




INSTALLATION DETAIL FOR SAFETY PIPE RUNNERS

(If required)




OPTION A




OPTION B

END DETAILS FOR INSTALLATION OF SAFETY PIPE RUNNERS

(If required)




MULTIPLE PIPE INSTALLATION




OPTION WITH SQUARE BOTTOM

SECTION A-A



OPTION WITH INVERT BOTTOM



OPTIONAL JOINT FOR RCP

(Showing joint between RCP and precast safety end treatment.)

REQUIREMENTS FOR CULVERT PIPES AND SAFETY PIPE RUNNERS

Pipe I.D.	RCP Wall "B" Thickness	TP Wall Thickness (7)	"D" (1)	Slope	Min Length	Pipe Runners Required		Required Pipe Runner Size		
						Single Pipe	Multiple Pipe	Nominal Dia.	O.D.	I.D.
12"	2"	1.15"	17.00"	6:1	4' - 9"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
15"	2 1/4"	1.30"	20.50"	6:1	6' - 5"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
18"	2 1/2"	1.60"	24.00"	6:1	8' - 0"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
24"	3"	1.95"	31.00"	6:1	11' - 3"	No	Yes, for > 2 pipes	3" STD	3.500"	3.068"
30"	3 1/2"	2.65"	38.50"	6:1	14' - 8"	No	Yes	4" STD	4.500"	4.026"
36"	4"	2.75"	45.50"	6:1	17' - 11"	Yes	Yes	4" STD	4.500"	4.026"
42"	4 1/2"	2.7"	52.50"	6:1	21' - 2"	Yes	Yes	4" STD	4.500"	4.026"

- Dimension "D" is based on reinforced concrete pipe (RCP) meeting the requirements of ASTM C-76, Class III, (RCP Wall "B" thickness). Adjust "D" for any other wall thickness used. For thermoplastic pipe (TP) take into account the annular space requirements for grouted connections.
- Slope as shown elsewhere in the plans. Slope of 6:1 or flatter is required for vehicle safety.
- Toewall to be used only when dimension is shown elsewhere in the plans.
- Fill the top 4" of void between precast end treatments with concrete riprap. Concrete riprap is considered subsidiary to the Item 467, "Safety End Treatment".
- Adjust clear distance between pipes to provide for the minimum distance between safety end treatments.
- Provide cement stabilized bedding and backfill in accordance with the Item 400, "Excavation and Backfill for Structures". Bedding and backfill is considered subsidiary to the Item 467, "Safety End Treatment". When concrete riprap is specified around the safety end treatment, backfill as directed by Engineer.
- Thermoplastic pipe wall thickness may vary. Adjust accordingly. Thermoplastic pipe requires the safety end treatments to have a bell end for grouted connections.

GENERAL NOTES:

Precast safety end treatment for reinforced concrete pipe (RCP), and thermoplastic pipe (TP) may be used for TYPE II end treatment as specified in Item "Safety End Treatment".

When precast safety end treatment is used as a Contractor's alternate to mitered RCP, riprap will not be required unless noted otherwise on the plans.

Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.

Manufacture this product in accordance with Item 467, "Safety End Treatment" except as noted below:

A. Provide minimum reinforcing of #4 at 6" (Grade 40) or #4 at 9" (Grade 60) each way or 6"x6" - D12 x D12 or 5"x5" - D10 x D10 welded wire reinforcement (WWR).

B. For precast (steel formed) sections, provide Class "C" concrete (f_c = 3,600 psi).

At the option and expense of the Contractor the next larger size of safety end treatment may be furnished; as long as the "D" dimension cast is that of the required size of pipe.

Pipe runners are designed for a traversing load of 10,000 Lbs at yield as recommended by Research Report 280-2F, "Safety Treatment of Roadside Parallel-Drainage Structures", Texas Transportation Institute, March 1981.

Provide pipe runners meeting the requirements of ASTM A53 (Type E or S, Grade B), ASTM A500 (Grade B), or API 5LX52.

Galvanize all steel components except reinforcing steel after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.

Connect RCP using the Optional Joint for RCP detail shown or in accordance with Item 464, "Reinforced Concrete Pipe". Connect TP by grouting. See Pipe and Box Grouted Connections (PBGC) standard for grouted connections with TP and precast safety end treatment.

Bridge Division Standard

PRECAST SAFETY END TREATMENT TYPE II ~ PARALLEL DRAINAGE

PSET-SP

FILE: psetspss-21.dgn	DN: RLW	CK: KLR	DW: JTR	CK: GAF
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
12-21: Added 42" TP	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	126	



TABLE OF VARIABLE DIMENSIONS AND QUANTITIES FOR ONE HEADWALL

5


Slope	Dia of Pipe (D)	Values for One Pipe			Values To Be Added for Each Add'l Pipe		
		W	Reinf (Lbs) (1)	Conc (CY) (2)	W	Reinf (Lbs) (1)	Conc (CY) (2)
2:1	12"	9' - 0"	122	1.1	1' - 9"	15	0.2
	15"	10' - 3"	136	1.3	2' - 2"	16	0.2
	18"	11' - 6"	163	1.5	2' - 8"	19	0.3
	21"	12' - 9"	200	1.8	3' - 1"	31	0.4
	24"	14' - 0"	217	2.1	3' - 7"	34	0.4
	27"	15' - 3"	254	2.4	3' - 11"	37	0.5
	30"	16' - 6"	272	2.7	4' - 4"	40	0.6
	33"	17' - 9"	314	3.1	4' - 8"	43	0.6
	36"	19' - 0"	371	3.9	5' - 1"	46	0.8
	42"	21' - 6"	442	4.9	5' - 10"	52	1.0
	48"	25' - 0"	569	6.4	6' - 7"	59	1.3
	54"	27' - 6"	701	7.5	7' - 6"	82	1.6
60"	30' - 0"	794	8.8	8' - 3"	90	1.8	
66"	32' - 6"	894	10.2	8' - 9"	96	2.0	
72"	35' - 0"	1,055	11.7	9' - 4"	103	2.3	
3:1	12"	13' - 0"	175	1.6	1' - 9"	14	0.2
	15"	14' - 9"	193	1.9	2' - 2"	17	0.2
	18"	16' - 6"	228	2.2	2' - 8"	19	0.3
	21"	18' - 3"	299	2.6	3' - 1"	31	0.4
	24"	20' - 0"	323	3.0	3' - 7"	33	0.4
	27"	21' - 9"	371	3.5	3' - 11"	37	0.5
	30"	23' - 6"	415	4.0	4' - 4"	40	0.5
	33"	25' - 3"	469	4.6	4' - 8"	43	0.6
	36"	27' - 0"	556	5.7	5' - 1"	46	0.8
	42"	30' - 6"	675	7.1	5' - 10"	52	1.0
	48"	35' - 6"	837	9.2	6' - 7"	59	1.3
	54"	39' - 0"	1,015	11.0	7' - 6"	84	1.6
60"	42' - 6"	1,171	12.9	8' - 3"	91	1.8	
66"	46' - 0"	1,298	14.9	8' - 9"	98	2.0	
72"	49' - 6"	1,561	17.1	9' - 4"	103	2.3	
4:1	12"	17' - 0"	229	2.0	1' - 9"	15	0.2
	15"	19' - 3"	266	2.4	2' - 2"	17	0.2
	18"	21' - 6"	308	2.9	2' - 8"	19	0.3
	21"	23' - 9"	382	3.5	3' - 1"	31	0.3
	24"	26' - 0"	430	3.9	3' - 7"	34	0.4
	27"	28' - 3"	486	4.7	3' - 11"	37	0.5
	30"	30' - 6"	539	5.2	4' - 4"	40	0.6
	33"	32' - 9"	603	6.0	4' - 8"	42	0.6
	36"	35' - 0"	738	7.5	5' - 1"	47	0.8
	42"	39' - 6"	881	9.3	5' - 10"	52	1.0
	48"	46' - 0"	1,102	12.1	6' - 7"	61	1.3
	54"	50' - 6"	1,364	14.4	7' - 6"	84	1.6
60"	55' - 0"	1,547	16.9	8' - 3"	91	1.8	
66"	59' - 6"	1,741	19.5	8' - 9"	98	2.0	
72"	64' - 0"	2,077	22.4	9' - 4"	102	2.3	
6:1	12"	25' - 0"	336	3.0	1' - 9"	14	0.2
	15"	28' - 3"	384	3.6	2' - 2"	17	0.2
	18"	31' - 6"	452	4.2	2' - 8"	19	0.3
	21"	34' - 9"	581	5.1	3' - 1"	31	0.4
	24"	38' - 0"	644	5.8	3' - 7"	34	0.4
	27"	41' - 3"	737	6.9	3' - 11"	37	0.5
	30"	44' - 6"	807	7.7	4' - 4"	39	0.6
	33"	47' - 9"	912	8.9	4' - 8"	44	0.6
	36"	51' - 0"	1,108	11.0	5' - 1"	48	0.8
	42"	57' - 6"	1,318	13.7	5' - 10"	54	1.0
	48"	67' - 0"	1,682	17.9	6' - 7"	59	1.3
	54"	73' - 6"	2,072	21.3	7' - 6"	83	1.6
60"	80' - 0"	2,351	24.9	8' - 3"	89	1.8	
66"	86' - 6"	2,643	28.9	8' - 9"	96	2.0	
72"	93' - 0"	3,121	33.1	9' - 4"	101	2.3	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:45 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-9\IDP510\WAZ-TxDOT\Par\1.s\chpw0ste-20.dgn



ELEVATION



PLAN OF NON-SKEWED PIPES



SECTION AT CENTER OF PIPE

- 1 Total quantities include one 3'-1" lap for bars over 60' in length.
- 2 Quantities shown are for concrete pipe and will increase slightly for metal pipe installations.
- 3 Indicated slope is perpendicular to centerline pipe or pipes.
- 4 For vehicle safety, construct curbs no more than 3" above finished grade. Reduce curb heights, if necessary, to meet these requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- 5 Dimensions shown are usual and maximum.
- 6 Quantities shown are for one structure end only (one headwall).

TABLE OF CONSTANT DIMENSIONS

Dia of Pipe (D)	G	K (5)	H	T	E
12"	0' - 9"	1' - 0"	2' - 8"	0' - 9"	1' - 9"
15"	0' - 11"	1' - 0"	2' - 11"	0' - 9"	1' - 9"
18"	1' - 2"	1' - 0"	3' - 2"	0' - 9"	1' - 9"
21"	1' - 4"	1' - 0"	3' - 5"	0' - 9"	2' - 0"
24"	1' - 7"	1' - 0"	3' - 8"	0' - 9"	2' - 0"
27"	1' - 8"	1' - 0"	3' - 11"	0' - 9"	2' - 3"
30"	1' - 10"	1' - 0"	4' - 2"	0' - 9"	2' - 3"
33"	1' - 11"	1' - 0"	4' - 5"	0' - 9"	2' - 6"
36"	2' - 1"	1' - 0"	4' - 8"	1' - 0"	2' - 6"
42"	2' - 4"	1' - 0"	5' - 2"	1' - 0"	2' - 9"
48"	2' - 7"	1' - 3"	5' - 11"	1' - 0"	3' - 0"
54"	3' - 0"	1' - 3"	6' - 5"	1' - 0"	3' - 3"
60"	3' - 3"	1' - 3"	6' - 11"	1' - 0"	3' - 6"
66"	3' - 3"	1' - 3"	7' - 5"	1' - 0"	3' - 9"
72"	3' - 4"	1' - 3"	7' - 11"	1' - 0"	4' - 0"

TABLE OF REINFORCING STEEL

Bar	Size	Spa	No.
A1	#5	~	2
A2	#5	1' - 6"	~
E	#5	~	2
F	#5	1' - 0"	~

MATERIAL NOTES:
 Provide Grade 60 reinforcing steel.
 Provide Class C concrete (f_c = 3,600 psi).

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 Do not mount bridge rails of any type directly to these culvert headwalls.
 This standard may not be used for wall heights, H, exceeding the values shown.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing dimensions are out-to-out of bars.

Bridge Division Standard

CONCRETE HEADWALLS WITH PARALLEL WINGS FOR NON-SKEWED PIPE CULVERTS

CH-PW-0

FILE: chpw0ste-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	127	

TABLE OF DIMENSIONS AND REINFORCING STEEL
(Wings for one structure end)




Maximum Wingwall Height Hw	Dimensions				Variable Reinforcing				Estimated Quantities per ft of wing (2-wings) ④	Estimated Quantities per ft of Toewall (1-toewall)		
	W	X	Y	Z	Bars J1		Bars J2					
					Size	Spa	Size	Spa				
2'-6"	2'-10"	10"	1'-0"	7"	#4	1'-0"	#4	1'-0"	48.64	0.406	6.85	0.071
2'-9"	2'-10"	10"	1'-0"	7"	#4	1'-0"	#4	1'-0"	49.31	0.424	6.85	0.071
3'-0"	2'-10"	10"	1'-0"	7"	#4	1'-0"	#4	1'-0"	49.98	0.444	6.85	0.071
3'-3"	2'-10"	10"	1'-0"	7"	#4	1'-0"	#4	1'-0"	53.32	0.462	6.85	0.071
3'-6"	2'-10"	10"	1'-0"	7"	#4	1'-0"	#4	1'-0"	53.98	0.480	6.85	0.071
4'-0"	3'-2"	1'-2"	1'-0"	7"	#4	1'-0"	#4	1'-0"	55.77	0.532	6.85	0.071
4'-6"	3'-2"	1'-2"	1'-0"	7"	#4	1'-0"	#4	1'-0"	59.77	0.568	6.85	0.071
5'-0"	3'-9"	1'-7"	1'-2"	7"	#4	1'-0"	#4	1'-0"	63.45	0.632	6.96	0.075
5'-6"	3'-9"	1'-7"	1'-2"	7"	#4	1'-0"	#4	1'-0"	67.46	0.668	6.96	0.075
6'-0"	4'-4"	2'-0"	1'-4"	7"	#5	1'-0"	#5	1'-0"	80.67	0.730	7.07	0.078
6'-6"	4'-4"	2'-0"	1'-4"	7"	#5	1'-0"	#5	1'-0"	85.05	0.768	7.07	0.078
7'-0"	5'-0"	2'-3"	1'-9"	8"	#5	1'-0"	#5	1'-0"	92.15	0.864	8.07	0.093
7'-6"	5'-0"	2'-3"	1'-9"	8"	#5	1'-0"	#5	1'-0"	96.54	0.902	8.07	0.093
8'-0"	5'-6"	2'-8"	1'-10"	8"	#5	6"	#5	6"	139.04	0.962	8.13	0.095
8'-6"	5'-6"	2'-8"	1'-10"	8"	#5	6"	#5	6"	144.47	1.000	8.13	0.095
9'-6"	6'-0"	2'-10"	2'-2"	9"	#5	6"	#5	6"	156.93	1.136	8.41	0.110
10'-6"	6'-5"	3'-0"	2'-5"	9"	#6	6"	#5	6"	196.27	1.234	8.57	0.117
11'-6"	7'-2"	3'-6"	2'-8"	11"	#6	6"	#6	6"	230.13	1.438	9.52	0.140
12'-6"	7'-8"	3'-9"	2'-11"	1'-0"	#7	6"	#6	6"	283.41	1.592	9.74	0.157
13'-6"	8'-2"	4'-0"	3'-2"	1'-2"	#8	6"	#6	6"	348.72	1.804	10.02	0.186
14'-6"	8'-10"	4'-5"	3'-5"	1'-4"	#9	6"	#6	6"	432.94	2.046	10.30	0.218
15'-6"	9'-6"	4'-10"	3'-8"	1'-6"	#9	6"	#7	6"	489.52	2.302	11.24	0.253
16'-0"	9'-11"	5'-0"	3'-11"	1'-7"	#9	6"	#7	6"	505.72	2.448	11.47	0.279

TABLE OF WINGWALL REINFORCING
(2-wings)

Bar	Size	No.	Spa
D1	#6	~	1'-0"
D2	#6	~	1'-0"
E1	#4	~	1'-0"
F	#4	~	1'-0"
G	#6	~	8"
M1	#4	4	~
P	#4	~	1'-0"
V	#4	~	1'-0"

TABLE OF TOEWALL REINFORCING

Bar	Size	No.	Spa
J3	#4	~	1'-0"
M2	#4	2	~
E2	#4	~	1'-0"



WING DIMENSION FORMULAS:
(All values are in feet.)

Hw = H + T + C
Lw = (Hw) (SL) + cosine (θ) for Type PW-1
= (Hw - 1') (SL) + cosine (θ) for Type PW-2 and Hw 4'
= (Hw - 0.5') (SL) + cosine (θ) for Type PW-2 and Hw 4'








For cast-in-place culverts:
Ltw = [(N) (S) + (N + 1) (U)] + cosine (θ)

For precast culverts:
Ltw = [(N) (2 U + S) + (N - 1) (0.5')] + cosine (θ)
Total Wingwall Area (two wings ~ SF)
= (2)(Hw)(Lw) for Type PW-1
= (2)(Hw)(Lw) - 6 SF for Type PW-2 and Hw 4'
= (2)(Hw)(Lw) - 1.5 SF for Type PW-2 and Hw 4'

Hw = Height of wingwall
Lw = Length of wingwall
Ltw = Culvert toewall length
N = Number of culvert spans
SL:1 = Channel slope ratio. (horizontal: 1 vertical, usual value is 2:1)
θ = Culvert skew

See applicable box culvert standard sheet for S, H, T, and U values.

- Skew = 0°
- At discharge end, chamfer may be 3/4" minimum.
- For 15° skew ~ 1"
For 30° skew ~ 2"
For 45° skew ~ 3"
- Quantities shown are for two Type PW-1 wings. Adjust concrete volume for Type PW-2 wings. To determine estimated quantities for two wings, multiply the tabulated values by Lw. Quantities shown do not include weight of Bars D.
- Provide weepholes for Hw = 5'-0" and greater. Fill around weepholes with coarse gravel.
- Extend Bars E2 1'-6" minimum into the wingwall footing.
- Lap Bars M1 1'-6" minimum with Bars M2.
- Place Bars G as shown, equally spaced at 8" maximum. Provide at least two pairs of Bars G per wing.
- 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0, refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Box Culvert Rail Mounting Details (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade.
Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- 1'-0" typical, 2'-3" when the Box Culvert Rail Mounting Details (RAC) standard sheet is referred to elsewhere in the plans.
- 3'-0" for Hw < 4'.
- 6" for Hw < 4'.



DESIGNER NOTES:
Type PW-1 can be used for all applications and must be used if railing is to be mounted to the wingwall. Type PW-2 can only be used for applications without a railing mounted to the wingwall.

MATERIAL NOTES:
Provide Class C concrete (f'c=3,600 psi).
Provide Grade 60 reinforcing steel.
Provide galvanized reinforcing steel if required elsewhere in the plans.


GENERAL NOTES:
Designed in accordance with AASHTO LRFD Bridge Design Specifications.
Depth of toewalls for wingwalls and culverts may be reduced or eliminated when founded on solid rock, when directed by the Engineer.
See Box Culvert Supplement (BCS) standard sheet for wingwall type and additional dimensions and information. Quantities for concrete and reinforcing steel resulting from the formulas given on this sheet are for the Contractor's information only.

Cover dimensions are clear dimensions, unless noted otherwise.
Reinforcing dimensions are out-to-out of bars.


Texas Department of Transportation		Bridge Division Standard	
CONCRETE WINGWALLS WITH PARALLEL WINGS FOR BOX CULVERTS TYPES PW-1 AND PW-2			
PW			
FILE: pwstde01-20.dgn	DN: GAF	CK: CAT	DW: TXDOT
©TXDOT February 2020	CONT SECT	JOB	HIGHWAY
REVISIONS	0579 02	014	FM 512
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	128	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
DATE: 5/24/2023 6:20:45 PM
FILE: Z:\Transportation\WAZ-9\DP5101\WAZ-9\STATEWIDE_36-9\DP5101\WAZ-9\STATEWIDE_36-9\PROJECT\DOT\FM_512_0579-02-014\X\CADD\DCN\05_DRAINAGE\ST-dDet\GIS_8\pwstde01-20.dgn


DATE: 5/24/2023 6:20:46 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TXDOT\Projec+D+o\FM 512 (0579-02-014)\CADD\GN\05_DRAINAGE\stdet+ci (9) scc34ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




TYPICAL SECTION




PLAN OF REINF STEEL




SECTION THRU CURB



BARS C



BARS D



BARS K (#4)
(Spa = 1'-0" Max)
(Length = 4'-2")

- ① 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Rail Anchorage Curb (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- ② For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade.
 Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- ③ For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.
- ④ 1'-0" typical. 2'-3" when the Rail Anchorage Curb (RAC) standard sheet is referred to elsewhere in the plans.

The Contractor may replace Bars B, C, D, E, F1, F2, M, Y, and/or Z with deformed welded wire reinforcement (WWR) meeting the requirements of ASTM A1064. The area of required reinforcement may be reduced by the ratio of 60 ksi / 70 ksi. Spacing of WWR is limited to 4" Min and 18" Max. When required, provide lap splices in the WWR of the same length required for the equivalent bar size, rounded up for wire sizes between conventional bar sizes. The lap length required for WWR is never less than the lap length required for uncoated #4 bars.

Example conversion: Replacing No. 6 Gr 60 at 6" Spacing with WWR.
 Required WWR = (0.44 sq. in. per 0.5 ft.) x (60 ksi / 70 ksi) = 0.755 sq. in. per ft.
 If D30.6 wire is used to meet the 0.755 sq. in. per ft. requirement in this example, the required spacing = (0.306 sq. in.) / (0.755 sq. in. per ft.) x (12 in. per ft.) = 4.86" Max spacing. Required lap length for the provided D30.6 wire is 2'-1" (the same minimum lap length required for uncoated #5 bars, as listed under MATERIAL NOTES).

CONSTRUCTION NOTES:

- Do not use permanent forms.
- Chamfer the bottom edge of the top slab 3" at the entrance.
- Optionally, raise construction joints shown at the flow line by a maximum of 6". If this option is taken, Bars M may be cut off or raised, Bars C and D may be reversed.

MATERIAL NOTES:

- Provide Grade 60 reinforcing steel.
- Provide galvanized reinforcing steel if required elsewhere in the plans.
- Provide Class C concrete (f'c = 3,600 psi) for culvert barrel and curb, with the following exceptions: provide Class S concrete (f'c = 4,000 psi) for top slabs of:
 - culverts with overlay,
 - culverts with 1-to-2 course surface treatment, or
 - culverts with the top slab as the final riding surface.
- Provide bar laps, where required, as follows:
 - Uncoated or galvanized ~ #4 = 1'-8" Min
 - Uncoated or galvanized ~ #5 = 2'-1" Min

GENERAL NOTES:

- Designed according to AASHTO LRFD Bridge Design Specifications for the range of fill heights shown.
- See the Single Box Culverts Cast-In-Place Miscellaneous Detail (SCC-MD) standard sheet for details pertaining to skewed ends, angle sections, and lengthening.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.

HL93 LOADING

SHEET 1 OF 2

Bridge Division Standard

**SINGLE BOX CULVERTS
CAST-IN-PLACE
0' TO 30' FILL**

SCC-3 & 4

FILE: scc34ste-21.dgn	DN: TBE	CK: BMP	DW: TXDOT	CK: TXDOT
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	129	

DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:46 PM
FILE: Z:\Transportation\TxDOT\STATEWIDE\36-9IDP5101\WAZ-TxDOT\Paris\Project\DOT\PS&E\STATEWIDE_36-9IDP5101\WAZ-TxDOT\Paris\Project\DOT\PS&E\STATEWIDE_36-9IDP5101.dgn

SECTION DIMENSIONS				⑤ FILL HEIGHT	BILLS OF REINFORCING STEEL (For Box Length = 40 feet)																								QUANTITIES														
					Bars B				Bars C				Bars D				Bars M ~ #4			Bars F1 ~ #4 at 18" Spa			Bars F2 ~ #4 at 18" Spa		Bars H 4 ~ #4		Bars K		Per Foot of Barrel		Curb		Total										
					S	H	T	U	No.	Size	Spa	Length	Weight	No.	Size	Spa	Length	Weight	" X "	" Y "	No.	Size	Spa	Length	Weight	" Y "	" Z "	No.	Spa	Length	Weight	No.	Length	Wt	No.	Length	Weight	Length	Wt	No.	Wt	Conc (CY)	Reinf (Lb)
3' - 0"	2' - 0"	8"	7"	30'	108	#5	9"	3' - 11"	441	108	#4	9"	5' - 4"	385	2' - 6"	2' - 10"	108	#4	9"	5' - 1"	367	2' - 10"	2' - 3"	108	9"	2' - 0"	144	3	39' - 9"	80	19	39' - 9"	505	3' - 11"	10	10	28	0.292	48.1	0.3	38	12.0	1,960
3' - 0"	3' - 0"	8"	7"	30'	108	#5	9"	3' - 11"	441	108	#4	9"	6' - 4"	457	3' - 6"	2' - 10"	108	#4	9"	5' - 1"	367	2' - 10"	2' - 3"	108	9"	3' - 0"	216	3	39' - 9"	80	23	39' - 9"	611	3' - 11"	10	10	28	0.335	54.3	0.3	38	13.7	2,210
4' - 0"	2' - 0"	8"	7"	30'	108	#5	9"	4' - 11"	554	162	#4	6"	5' - 8"	613	2' - 6"	3' - 2"	162	#4	6"	5' - 5"	586	3' - 2"	2' - 3"	108	9"	2' - 0"	144	3	39' - 9"	80	21	39' - 9"	558	4' - 11"	13	12	33	0.342	63.4	0.4	46	14.1	2,581
4' - 0"	3' - 0"	8"	7"	30'	108	#5	9"	4' - 11"	554	162	#4	6"	6' - 8"	721	3' - 6"	3' - 2"	162	#4	6"	5' - 5"	586	3' - 2"	2' - 3"	108	9"	3' - 0"	216	3	39' - 9"	80	25	39' - 9"	664	4' - 11"	13	12	33	0.385	70.5	0.4	46	15.8	2,867
4' - 0"	4' - 0"	8"	7"	30'	108	#5	9"	4' - 11"	554	162	#4	6"	7' - 8"	830	4' - 6"	3' - 2"	162	#4	6"	5' - 5"	586	3' - 2"	2' - 3"	108	9"	4' - 0"	289	3	39' - 9"	80	25	39' - 9"	664	4' - 11"	13	12	33	0.428	75.1	0.4	46	17.5	3,049

⑤ For direct traffic culverts (fill height ≤ 2 ft.), identify the required box size and select the option with the minimum fill height.




**SINGLE BOX CULVERTS
CAST-IN-PLACE
0' TO 30' FILL**


SCC-3 & 4

FILE: scc34ste-21.dgn	DN: TBE	CK: BMP	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	130	


DATE: 5/24/2023 6:20:46 PM
 FILE: Z:\Transportation\TXDOT\STATEWIDE\36-91DP5101\WAZ-TXDOT\Paris\Project\Drawings\SCC56ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




TYPICAL SECTION



PLAN OF REINF STEEL



SECTION THRU CURB



- ① 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Rail Anchorage Curb (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- ② For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade. Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- ③ For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.
- ④ 1'-0" typical. 2'-3" when the Rail Anchorage Curb (RAC) standard sheet is referred to elsewhere in the plans.

The Contractor may replace Bars B, C, D, E, F1, F2, M, Y, and/or Z with deformed welded wire reinforcement (WWR) meeting the requirements of ASTM A1064. The area of required reinforcement may be reduced by the ratio of 60 ksi / 70 ksi. Spacing of WWR is limited to 4" Min and 18" Max. When required, provide lap splices in the WWR of the same length required for the equivalent bar size, rounded up for wire sizes between conventional bar sizes. The lap length required for WWR is never less than the lap length required for uncoated #4 bars.

Example conversion: Replacing No. 6 Gr 60 at 6" Spacing with WWR.
 Required WWR = (0.44 sq. in. per 0.5 ft.) x (60 ksi / 70 ksi) = 0.755 sq. in. per ft.
 If D30.6 wire is used to meet the 0.755 sq. in. per ft. requirement in this example, the required spacing = (0.306 sq. in.) / (0.755 sq. in. per ft.) x (12 in. per ft.) = 4.86" Max spacing. Required lap length for the provided D30.6 wire is 2'-1" (the same minimum lap length required for uncoated #5 bars, as listed under MATERIAL NOTES).

CONSTRUCTION NOTES:

- Do not use permanent forms.
- Chamfer the bottom edge of the top slab 3" at the entrance.
- Optionally, raise construction joints shown at the flow line by a maximum of 6". If this option is taken, Bars M may be cut off or raised, Bars C and D may be reversed.

MATERIAL NOTES:

- Provide Grade 60 reinforcing steel.
- Provide galvanized reinforcing steel if required elsewhere in the plans.
- Provide Class C concrete (f_c = 3,600 psi) for culvert barrel and curb, with the following exceptions: provide Class S concrete (f_c = 4,000 psi) for top slabs of:
 - culverts with overlay,
 - culverts with 1-to-2 course surface treatment, or
 - culverts with the top slab as the final riding surface.
- Provide bar laps, where required, as follows:
 - Uncoated or galvanized ~ #4 = 1'-8" Min
 - Uncoated or galvanized ~ #5 = 2'-1" Min
 - Uncoated or galvanized ~ #6 = 2'-6" Min

GENERAL NOTES:

- Designed according to AASHTO LRFD Bridge Design Specifications for the range of fill heights shown.
- See the Single Box Culverts Cast-In-Place Miscellaneous Detail (SCC-MD) standard sheet for details pertaining to skewed ends, angle sections, and lengthening.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.




**SINGLE BOX CULVERTS
 CAST-IN-PLACE
 0' TO 30' FILL**


SCC-5 & 6

FILE: scc56ste-21.dgn	DN: TBE	CK: BMP	DW: TXDOT	CK: TXDOT
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	131	


DATE: 5/24/2023 6:20:47 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9\DP5101\WAZ-TXDOT\Paris\SCC07ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of units or for the accuracy of the information contained herein.




TYPICAL SECTION




PLAN OF REINF STEEL




SECTION THRU CURB



BARS C



BARS D



BARS K (#4)
(Spa = 1'-0" Max)
(Length = 4'-2")

- ① 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Rail Anchorage Curb (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- ② For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade. Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- ③ For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.
- ④ 1'-0" typical. 2'-3" when the Rail Anchorage Curb (RAC) standard sheet is referred to elsewhere in the plans.

The Contractor may replace Bars B, C, D, E, F1, F2, M, Y, and/or Z with deformed welded wire reinforcement (WWR) meeting the requirements of ASTM A1064. The area of required reinforcement may be reduced by the ratio of 60 ksi / 70 ksi. Spacing of WWR is limited to 4" Min and 18" Max. When required, provide lap splices in the WWR of the same length required for the equivalent bar size, never less than the lap length required for uncoated #4 bars.

Example conversion: Replacing No. 6 Gr 60 at 6" Spacing with WWR.
 Required WWR = (0.44 sq. in. per 0.5 ft.) x (60 ksi / 70 ksi) = 0.755 sq. in. per ft.
 If D30.6 wire is used to meet the 0.755 sq. in. per ft. requirement in this example, the required spacing = (0.306 sq. in.) / (0.755 sq. in. per ft.) x (12 in. per ft.) = 4.86" Max spacing. Required lap length for the provided D30.6 wire is 2'-1" (the same minimum lap length required for uncoated #5 bars, as listed under MATERIAL NOTES).

CONSTRUCTION NOTES:

- Do not use permanent forms.
- Chamfer the bottom edge of the top slab 3" at the entrance.
- Optionally, raise construction joints shown at the flow line by a maximum of 6". If this option is taken, Bars M may be cut off or raised, Bars C and D may be reversed.

MATERIAL NOTES:

- Provide Grade 60 reinforcing steel.
- Provide galvanized reinforcing steel if required elsewhere in the plans.
- Provide Class C concrete (f'c = 3,600 psi) for culvert barrel and curb, with the following exceptions: provide Class S concrete (f'c = 4,000 psi) for top slabs of:
 - culverts with overlay,
 - culverts with 1-to-2 course surface treatment, or
 - culverts with the top slab as the final riding surface.
- Provide bar laps, where required, as follows:
 - Uncoated or galvanized ~ #4 = 1'-8" Min
 - Uncoated or galvanized ~ #5 = 2'-1" Min
 - Uncoated or galvanized ~ #6 = 2'-6" Min

GENERAL NOTES:

- Designed according to AASHTO LRFD Bridge Design Specifications for the range of fill heights shown.
- See the Single Box Culverts Cast-In-Place Miscellaneous Detail (SCC-MD) standard sheet for details pertaining to skewed ends, angle sections, and lengthening.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.

HL93 LOADING

SHEET 1 OF 2



**SINGLE BOX CULVERTS
CAST-IN-PLACE
0' TO 30' FILL**

SCC-7

FILE: scc07ste-21.dgn	DN: TBE	CK: BMP	DWR: TXDOT	CK: TXDOT
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	133	


DATE: 5/24/2023 6:20:47 PM
 FILE: Z:\Transportation\DOT\PS&E\STATEWIDE\36-9\DP5101\WAZ-TXDOT\Par1.s\PS&E\STATEWIDE\SCC07ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units.

SECTION DIMENSIONS				FILL HEIGHT	BILLS OF REINFORCING STEEL (For Box Length = 40 feet)																									QUANTITIES													
					Bars B					Bars C					Bars D					Bars M ~ #4				Bars F1 ~ #4 at 18" Spa			Bars F2 ~ #4 at 18" Spa		Bars H 4 ~ #4		Bars K		Per Foot of Barrel		Curb		Total						
					S	H	T	U	No.	Size	Spa	Length	Weight	No.	Size	Spa	Length	Weight	" X "	" Y "	No.	Size	Spa	Length	Weight	" Y "	" Z "	No.	Spa	Length	Weight	No.	Length	Wt	No.	Length	Weight	Length	Wt	No.	Wt	Conc (CY)	Reinf (Lb)
7' - 0"	3' - 0"	8"	7"	16'	108	#6	9"	7' - 11"	1,284	162	#5	6"	7' - 11"	1,338	3' - 6"	4' - 5"	162	#5	6"	7' - 1"	1,197	4' - 5"	2' - 8"	108	9"	3' - 0"	216	5	39' - 9"	133	31	39' - 9"	823	7' - 11"	21	18	50	0.533	124.8	0.6	71	21.9	5,062
7' - 0"	3' - 0"	9"	7"	20'	108	#6	9"	7' - 11"	1,284	162	#5	6"	8' - 0"	1,352	3' - 7"	4' - 5"	162	#5	6"	7' - 2"	1,211	4' - 5"	2' - 9"	108	9"	3' - 0"	216	5	39' - 9"	133	31	39' - 9"	823	7' - 11"	21	18	50	0.583	125.5	0.6	71	23.9	5,090
7' - 0"	3' - 0"	10"	8"	23'	108	#6	9"	8' - 1"	1,311	162	#5	6"	8' - 2"	1,380	3' - 8"	4' - 6"	162	#5	6"	7' - 4"	1,239	4' - 6"	2' - 10"	82	12"	3' - 0"	164	5	39' - 9"	133	31	39' - 9"	823	8' - 1"	22	20	56	0.663	126.3	0.6	78	27.1	5,128
7' - 0"	3' - 0"	11"	8"	30'	108	#6	9"	8' - 1"	1,311	162	#5	6"	8' - 3"	1,394	3' - 9"	4' - 6"	162	#5	6"	7' - 5"	1,253	4' - 6"	2' - 11"	82	12"	3' - 0"	164	5	39' - 9"	133	31	39' - 9"	823	8' - 1"	22	20	56	0.714	127.0	0.6	78	29.2	5,156
7' - 0"	4' - 0"	8"	7"	16'	108	#6	9"	7' - 11"	1,284	162	#5	6"	8' - 11"	1,507	4' - 6"	4' - 5"	162	#5	6"	7' - 1"	1,197	4' - 5"	2' - 8"	108	9"	4' - 0"	289	5	39' - 9"	133	31	39' - 9"	823	7' - 11"	21	18	50	0.576	130.8	0.6	71	23.6	5,304
7' - 0"	4' - 0"	9"	7"	20'	108	#6	9"	7' - 11"	1,284	162	#5	6"	9' - 0"	1,521	4' - 7"	4' - 5"	162	#5	6"	7' - 2"	1,211	4' - 5"	2' - 9"	108	9"	4' - 0"	289	5	39' - 9"	133	31	39' - 9"	823	7' - 11"	21	18	50	0.627	131.5	0.6	71	25.7	5,332
7' - 0"	4' - 0"	10"	8"	23'	108	#6	9"	8' - 1"	1,311	162	#5	6"	9' - 2"	1,549	4' - 8"	4' - 6"	162	#5	6"	7' - 4"	1,239	4' - 6"	2' - 10"	82	12"	4' - 0"	219	5	39' - 9"	133	31	39' - 9"	823	8' - 1"	22	20	56	0.712	131.9	0.6	78	29.1	5,352
7' - 0"	4' - 0"	11"	8"	30'	162	#6	6"	8' - 1"	1,967	162	#5	6"	9' - 3"	1,563	4' - 9"	4' - 6"	162	#5	6"	7' - 5"	1,253	4' - 6"	2' - 11"	82	12"	4' - 0"	219	5	39' - 9"	133	31	39' - 9"	823	8' - 1"	22	20	56	0.763	149.0	0.6	78	31.1	6,036
7' - 0"	5' - 0"	8"	7"	16'	108	#6	9"	7' - 11"	1,284	162	#5	6"	9' - 11"	1,676	5' - 6"	4' - 5"	162	#5	6"	7' - 1"	1,197	4' - 5"	2' - 8"	108	9"	5' - 0"	361	5	39' - 9"	133	35	39' - 9"	929	7' - 11"	21	18	50	0.619	139.5	0.6	71	25.4	5,651
7' - 0"	5' - 0"	9"	7"	20'	108	#6	9"	7' - 11"	1,284	162	#5	6"	10' - 0"	1,690	5' - 7"	4' - 5"	162	#5	6"	7' - 2"	1,211	4' - 5"	2' - 9"	108	9"	5' - 0"	361	5	39' - 9"	133	35	39' - 9"	929	7' - 11"	21	18	50	0.670	140.2	0.6	71	27.4	5,679
7' - 0"	5' - 0"	10"	8"	23'	108	#6	9"	8' - 1"	1,311	162	#5	6"	10' - 2"	1,718	5' - 8"	4' - 6"	162	#5	6"	7' - 4"	1,239	4' - 6"	2' - 10"	82	12"	5' - 0"	274	5	39' - 9"	133	35	39' - 9"	929	8' - 1"	22	20	56	0.761	140.1	0.6	78	31.1	5,682
7' - 0"	5' - 0"	11"	8"	30'	162	#6	6"	8' - 1"	1,967	162	#5	6"	10' - 3"	1,732	5' - 9"	4' - 6"	162	#5	6"	7' - 5"	1,253	4' - 6"	2' - 11"	82	12"	5' - 0"	274	5	39' - 9"	133	35	39' - 9"	929	8' - 1"	22	20	56	0.813	157.2	0.6	78	33.1	6,366
7' - 0"	6' - 0"	8"	7"	16'	108	#6	9"	7' - 11"	1,284	162	#5	6"	10' - 11"	1,845	6' - 6"	4' - 5"	162	#5	6"	7' - 1"	1,197	4' - 5"	2' - 8"	108	9"	6' - 0"	433	5	39' - 9"	133	39	39' - 9"	1,036	7' - 11"	21	18	50	0.663	148.2	0.6	71	27.1	5,999
7' - 0"	6' - 0"	9"	7"	20'	108	#6	9"	7' - 11"	1,284	162	#5	6"	11' - 0"	1,859	6' - 7"	4' - 5"	162	#5	6"	7' - 2"	1,211	4' - 5"	2' - 9"	108	9"	6' - 0"	433	5	39' - 9"	133	39	39' - 9"	1,036	7' - 11"	21	18	50	0.713	148.9	0.6	71	29.1	6,027
7' - 0"	6' - 0"	10"	8"	23'	108	#6	9"	8' - 1"	1,311	162	#5	6"	11' - 2"	1,887	6' - 8"	4' - 6"	162	#5	6"	7' - 4"	1,239	4' - 6"	2' - 10"	82	12"	6' - 0"	329	5	39' - 9"	133	39	39' - 9"	1,036	8' - 1"	22	20	56	0.811	148.4	0.6	78	33.1	6,013
7' - 0"	6' - 0"	11"	8"	30'	162	#6	6"	8' - 1"	1,967	162	#5	6"	11' - 3"	1,901	6' - 9"	4' - 6"	162	#5	6"	7' - 5"	1,253	4' - 6"	2' - 11"	82	12"	6' - 0"	329	5	39' - 9"	133	39	39' - 9"	1,036	8' - 1"	22	20	56	0.862	165.5	0.6	78	35.1	6,697
7' - 0"	7' - 0"	8"	7"	16'	108	#6	9"	7' - 11"	1,284	162	#5	6"	11' - 11"	2,014	7' - 6"	4' - 5"	162	#5	6"	7' - 1"	1,197	4' - 5"	2' - 8"	108	9"	7' - 0"	505	5	39' - 9"	133	39	39' - 9"	1,036	7' - 11"	21	18	50	0.706	154.2	0.6	71	28.8	6,240
7' - 0"	7' - 0"	9"	7"	20'	108	#6	9"	7' - 11"	1,284	162	#5	6"	12' - 0"	2,028	7' - 7"	4' - 5"	162	#5	6"	7' - 2"	1,211	4' - 5"	2' - 9"	108	9"	7' - 0"	505	5	39' - 9"	133	39	39' - 9"	1,036	7' - 11"	21	18	50	0.756	154.9	0.6	71	30.8	6,268
7' - 0"	7' - 0"	10"	8"	23'	108	#6	9"	8' - 1"	1,311	162	#5	6"	12' - 2"	2,056	7' - 8"	4' - 6"	162	#5	6"	7' - 4"	1,239	4' - 6"	2' - 10"	108	9"	7' - 0"	505	5	39' - 9"	133	39	39' - 9"	1,036	8' - 1"	22	20	56	0.860	157.0	0.6	78	35.0	6,358
7' - 0"	7' - 0"	11"	8"	30'	162	#6	6"	8' - 1"	1,967	162	#5	6"	12' - 3"	2,070	7' - 9"	4' - 6"	162	#5	6"	7' - 5"	1,253	4' - 6"	2' - 11"	108	9"	7' - 0"	505	5	39' - 9"	133	39	39' - 9"	1,036	8' - 1"	22	20	56	0.912	174.1	0.6	78	37.1	7,042


5 For direct traffic culverts (fill height ≤ 2 ft.), identify the required box size and select the option with the minimum fill height.

				Bridge Division Standard	
SINGLE BOX CULVERTS CAST-IN-PLACE 0' TO 30' FILL					
SCC-7					
FILE: scc07ste-21.dgn	DN: TBE	CK: BMP	DWR: TXDOT	CK: TXDOT	
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0579	02	014	FM 512	
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.		
	PARIS	HUNT	134		


DATE: 5/24/2023 6:20:48 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9\DP5101\WAZ-TXDOT\Par1.s.P&E\SCC08ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of units or for the accuracy of the information contained herein.




TYPICAL SECTION




PLAN OF REINF STEEL




SECTION THRU CURB



BARS C



BARS D



BARS K (#4)
(Spa = 1'-0" Max)
(Length = 4'-2")

- ① 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Rail Anchorage Curb (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- ② For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade.
 Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- ③ For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.
- ④ 1'-0" typical. 2'-3" when the Rail Anchorage Curb (RAC) standard sheet is referred to elsewhere in the plans.

The Contractor may replace Bars B, C, D, E, F1, F2, M, Y, and/or Z with deformed welded wire reinforcement (WWR) meeting the requirements of ASTM A1064. The area of required reinforcement may be reduced by the ratio of 60 ksi / 70 ksi. Spacing of WWR is limited to 4" Min and 18" Max. When required, provide lap splices in the WWR of the same length required for the equivalent bar size, rounded up for wire sizes between conventional bar sizes. The lap length required for WWR is never less than the lap length required for uncoated #4 bars.

Example conversion: Replacing No. 6 Gr 60 at 6" Spacing with WWR.
 Required WWR = (0.44 sq. in. per 0.5 ft.) x (60 ksi / 70 ksi) = 0.755 sq. in. per ft.
 If D30.6 wire is used to meet the 0.755 sq. in. per ft. requirement in this example, the required spacing = (0.306 sq. in.) / (0.755 sq. in. per ft.) x (12 in. per ft.) = 4.86" Max spacing. Required lap length for the provided D30.6 wire is 2'-1" (the same minimum lap length required for uncoated #5 bars, as listed under MATERIAL NOTES).

CONSTRUCTION NOTES:

- Do not use permanent forms.
- Chamfer the bottom edge of the top slab 3" at the entrance.
- Optionally, raise construction joints shown at the flow line by a maximum of 6". If this option is taken, Bars M may be cut off or raised, Bars C and D may be reversed.

MATERIAL NOTES:

- Provide Grade 60 reinforcing steel.
- Provide galvanized reinforcing steel if required elsewhere in the plans.
- Provide Class C concrete (f_c = 3,600 psi) for culvert barrel and curb, with the following exceptions: provide Class S concrete (f_c = 4,000 psi) for top slabs of:
 - culverts with overlay,
 - culverts with 1-to-2 course surface treatment, or
 - culverts with the top slab as the final riding surface.
- Provide bar laps, where required, as follows:
 - Uncoated or galvanized ~ #4 = 1'-8" Min
 - Uncoated or galvanized ~ #5 = 2'-1" Min
 - Uncoated or galvanized ~ #6 = 2'-6" Min

GENERAL NOTES:

- Designed according to AASHTO LRFD Bridge Design Specifications for the range of fill heights shown.
- See the Single Box Culverts Cast-In-Place Miscellaneous Detail (SCC-MD) standard sheet for details pertaining to skewed ends, angle sections, and lengthening.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.

HL93 LOADING

SHEET 1 OF 2



**SINGLE BOX CULVERTS
 CAST-IN-PLACE
 0' TO 30' FILL**

SCC-8


FILE: scc08ste-21.dgn	DN: TBE	CK: BMP	DW: TXDOT	CK: TXDOT
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	135	

DATE: 5/24/2023 6:20:48 PM
 FILE: Z:\Transportation\DOT\STATEWIDE\36-91DP5101\WAZ-TXDOT\Paris\HL93\SCC8ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of units or the accuracy of the information provided herein.


SECTION DIMENSIONS				FILL HEIGHT	BILLS OF REINFORCING STEEL (For Box Length = 40 feet)																											QUANTITIES											
					Bars B					Bars C					Bars D					Bars M ~ #4				Bars F1 ~ #4 at 18" Spa			Bars F2 ~ #4 at 18" Spa			Bars H 4 ~ #4		Bars K		Per Foot of Barrel		Curb		Total					
					S	H	T	U	No.	Size	Spa	Length	Weight	No.	Size	Spa	Length	Weight	" X "	" Y "	No.	Size	Spa	Length	Weight	" Y "	" Z "	No.	Spa	Length	Weight	No.	Length	Wt	No.	Length	Weight	Length	Wt	No.	Wt	Conc (CY)	Reinf (Lb)
8' - 0"	3' - 0"	8"	7"	13'	162	#6	6"	8' - 11"	2,170	108	#6	9"	8' - 8"	1,406	3' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	3' - 0"	216	6	39' - 9"	159	32	39' - 9"	850	8' - 11"	24	20	56	0.582	153.5	0.7	80	24.0	6,219
8' - 0"	3' - 0"	8"	7"	16'	162	#6	6"	8' - 11"	2,170	108	#6	9"	8' - 8"	1,406	3' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	3' - 0"	216	6	39' - 9"	159	32	39' - 9"	850	8' - 11"	24	20	56	0.582	153.5	0.7	80	24.0	6,219
8' - 0"	3' - 0"	10"	8"	20'	162	#6	6"	9' - 1"	2,210	108	#6	9"	8' - 10"	1,433	3' - 8"	5' - 2"	108	#6	9"	8' - 5"	1,365	5' - 2"	3' - 3"	82	12"	3' - 0"	164	6	39' - 9"	159	32	39' - 9"	850	9' - 1"	24	22	61	0.724	154.5	0.7	85	29.6	6,266
8' - 0"	3' - 0"	11"	8"	23'	162	#6	6"	9' - 1"	2,210	108	#6	9"	8' - 11"	1,446	3' - 9"	5' - 2"	108	#6	9"	8' - 6"	1,379	5' - 2"	3' - 4"	82	12"	3' - 0"	164	6	39' - 9"	159	32	39' - 9"	850	9' - 1"	24	22	61	0.782	155.2	0.7	85	32.0	6,293
8' - 0"	3' - 0"	13"	9"	30'	162	#6	6"	9' - 3"	2,251	108	#6	9"	9' - 2"	1,487	3' - 11"	5' - 3"	108	#6	9"	8' - 9"	1,419	5' - 3"	3' - 6"	108	9"	3' - 0"	216	6	39' - 9"	159	32	39' - 9"	850	9' - 3"	25	22	61	0.929	159.6	0.7	86	37.9	6,468
8' - 0"	4' - 0"	8"	7"	13'	162	#6	6"	8' - 11"	2,170	108	#6	9"	9' - 8"	1,568	4' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	4' - 0"	289	6	39' - 9"	159	32	39' - 9"	850	8' - 11"	24	20	56	0.626	159.4	0.7	80	25.7	6,454
8' - 0"	4' - 0"	8"	7"	16'	162	#6	6"	8' - 11"	2,170	108	#6	9"	9' - 8"	1,568	4' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	4' - 0"	289	6	39' - 9"	159	32	39' - 9"	850	8' - 11"	24	20	56	0.626	159.4	0.7	80	25.7	6,454
8' - 0"	4' - 0"	10"	8"	20'	162	#6	6"	9' - 1"	2,210	108	#6	9"	9' - 10"	1,595	4' - 8"	5' - 2"	108	#6	9"	8' - 5"	1,365	5' - 2"	3' - 3"	82	12"	4' - 0"	219	6	39' - 9"	159	32	39' - 9"	850	9' - 1"	24	22	61	0.774	160.0	0.7	85	31.6	6,483
8' - 0"	4' - 0"	11"	8"	23'	162	#6	6"	9' - 1"	2,210	108	#6	9"	9' - 11"	1,609	4' - 9"	5' - 2"	108	#6	9"	8' - 6"	1,379	5' - 2"	3' - 4"	82	12"	4' - 0"	219	6	39' - 9"	159	32	39' - 9"	850	9' - 1"	24	22	61	0.831	160.7	0.7	85	33.9	6,511
8' - 0"	4' - 0"	13"	9"	30'	162	#6	6"	9' - 3"	2,251	108	#6	9"	10' - 2"	1,649	4' - 11"	5' - 3"	108	#6	9"	8' - 9"	1,419	5' - 3"	3' - 6"	108	9"	4' - 0"	289	6	39' - 9"	159	32	39' - 9"	850	9' - 3"	25	22	61	0.985	165.4	0.7	86	40.1	6,703
8' - 0"	5' - 0"	8"	7"	13'	162	#6	6"	8' - 11"	2,170	108	#6	9"	10' - 8"	1,730	5' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	5' - 0"	361	6	39' - 9"	159	36	39' - 9"	956	8' - 11"	24	20	56	0.669	167.9	0.7	80	27.4	6,794
8' - 0"	5' - 0"	8"	7"	16'	162	#6	6"	8' - 11"	2,170	108	#6	9"	10' - 8"	1,730	5' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	5' - 0"	361	6	39' - 9"	159	36	39' - 9"	956	8' - 11"	24	20	56	0.669	167.9	0.7	80	27.4	6,794
8' - 0"	5' - 0"	10"	8"	20'	162	#6	6"	9' - 1"	2,210	108	#6	9"	10' - 10"	1,757	5' - 8"	5' - 2"	108	#6	9"	8' - 5"	1,365	5' - 2"	3' - 3"	82	12"	5' - 0"	274	6	39' - 9"	159	36	39' - 9"	956	9' - 1"	24	22	61	0.823	168.0	0.7	85	33.6	6,806
8' - 0"	5' - 0"	11"	8"	23'	162	#6	6"	9' - 1"	2,210	108	#6	9"	10' - 11"	1,771	5' - 9"	5' - 2"	108	#6	9"	8' - 6"	1,379	5' - 2"	3' - 4"	82	12"	5' - 0"	274	6	39' - 9"	159	36	39' - 9"	956	9' - 1"	24	22	61	0.881	168.7	0.7	85	35.9	6,834
8' - 0"	5' - 0"	13"	9"	30'	162	#6	6"	9' - 3"	2,251	108	#6	9"	11' - 2"	1,811	5' - 11"	5' - 3"	108	#6	9"	8' - 9"	1,419	5' - 3"	3' - 6"	108	9"	5' - 0"	361	6	39' - 9"	159	36	39' - 9"	956	9' - 3"	25	22	61	1.040	173.9	0.7	86	42.3	7,043
8' - 0"	6' - 0"	8"	7"	13'	162	#6	6"	8' - 11"	2,170	108	#6	9"	11' - 8"	1,893	6' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	6' - 0"	433	6	39' - 9"	159	40	39' - 9"	1,062	8' - 11"	24	20	56	0.712	176.4	0.7	80	29.2	7,135
8' - 0"	6' - 0"	8"	7"	16'	162	#6	6"	8' - 11"	2,170	108	#6	9"	11' - 8"	1,893	6' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	6' - 0"	433	6	39' - 9"	159	40	39' - 9"	1,062	8' - 11"	24	20	56	0.712	176.4	0.7	80	29.2	7,135
8' - 0"	6' - 0"	10"	8"	20'	162	#6	6"	9' - 1"	2,210	108	#6	9"	11' - 10"	1,920	6' - 8"	5' - 2"	108	#6	9"	8' - 5"	1,365	5' - 2"	3' - 3"	82	12"	6' - 0"	329	6	39' - 9"	159	40	39' - 9"	1,062	9' - 1"	24	22	61	0.872	176.1	0.7	85	35.6	7,130
8' - 0"	6' - 0"	11"	8"	23'	162	#6	6"	9' - 1"	2,210	108	#6	9"	11' - 11"	1,933	6' - 9"	5' - 2"	108	#6	9"	8' - 6"	1,379	5' - 2"	3' - 4"	82	12"	6' - 0"	329	6	39' - 9"	159	40	39' - 9"	1,062	9' - 1"	24	22	61	0.930	176.8	0.7	85	37.9	7,157
8' - 0"	6' - 0"	13"	9"	30'	162	#6	6"	9' - 3"	2,251	108	#6	9"	12' - 2"	1,974	6' - 11"	5' - 3"	108	#6	9"	8' - 9"	1,419	5' - 3"	3' - 6"	108	9"	6' - 0"	433	6	39' - 9"	159	40	39' - 9"	1,062	9' - 3"	25	22	61	1.096	182.5	0.7	86	44.5	7,384
8' - 0"	7' - 0"	8"	7"	13'	162	#6	6"	8' - 11"	2,170	108	#6	9"	12' - 8"	2,055	7' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	7' - 0"	505	6	39' - 9"	159	40	39' - 9"	1,062	8' - 11"	24	20	56	0.755	182.2	0.7	80	30.9	7,369
8' - 0"	7' - 0"	8"	7"	16'	162	#6	6"	8' - 11"	2,170	162	#6	6"	12' - 8"	3,082	7' - 6"	5' - 2"	162	#6	6"	8' - 3"	2,007	5' - 2"	3' - 1"	108	9"	7' - 0"	505	6	39' - 9"	159	40	39' - 9"	1,062	8' - 11"	24	20	56	0.755	224.6	0.7	80	30.9	9,065
8' - 0"	7' - 0"	10"	8"	20'	162	#6	6"	9' - 1"	2,210	162	#6	6"	12' - 10"	3,123	7' - 8"	5' - 2"	162	#6	6"	8' - 5"	2,048	5' - 2"	3' - 3"	82	12"	7' - 0"	383	6	39' - 9"	159	40	39' - 9"	1,062	9' - 1"	24	22	61	0.922	224.6	0.7	85	37.6	9,070
8' - 0"	7' - 0"	11"	8"	23'	162	#6	6"	9' - 1"	2,210	162	#6	6"	12' - 11"	3,143	7' - 9"	5' - 2"	162	#6	6"	8' - 6"	2,068	5' - 2"	3' - 4"	82	12"	7' - 0"	383	6	39' - 9"	159	40	39' - 9"	1,062	9' - 1"	24	22	61	0.979	225.6	0.7	85	39.8	9,110
8' - 0"	7' - 0"	13"	9"	30'	162	#6	6"	9' - 3"	2,251	162	#6	6"	13' - 2"	3,204	7' - 11"	5' - 3"	162	#6	6"	8' - 9"	2,129	5' - 3"	3' - 6"	108	9"	7' - 0"	505	6	39' - 9"	159	40	39' - 9"	1,062	9' - 3"	25	22	61	1.151	232.8	0.7	86	46.7	9,396
8' - 0"	8' - 0"	8"	7"	13'	162	#6	6"	8' - 11"	2,170	108	#6	9"	13' - 8"	2,217	8' - 6"	5' - 2"	108	#6	9"	8' - 3"	1,338	5' - 2"	3' - 1"	108	9"	8' - 0"	577	6	39' - 9"	159	44	39' - 9"	1,168	8' - 11"	24	20	56	0.798	190.7	0.7	80	32.6	7,709
8' - 0"	8' - 0"	8"	7"	16'	162	#6	6"	8' - 11"	2,170	162	#6	6"	13' - 8"	3,325	8' - 6"	5' - 2"	162	#6	6"	8' - 3"	2,007	5' - 2"	3' - 1"	108	9"	8' - 0"	577	6	39' - 9"	159	44	39' - 9"	1,168	8' - 11"	24	20	56	0.798	235.2	0.7	80	32.6	9,486
8' - 0"	8' - 0"	10"	8"	20'	162	#6	6"	9' - 1"	2,210	162	#6	6"	13' - 10"	3,366	8' - 8"	5' - 2"	162	#6	6"	8' - 5"	2,048	5' - 2"	3' - 3"	108	9"	8' - 0"	577	6	39' - 9"	159	44	39' - 9"	1,168	9' - 1"	24	22	61	0.971	238.2	0.7	85	39.5	9,613
8' - 0"	8' - 0"	11"	8"	23'	162	#6	6"	9' - 1"	2,210	162	#6	6"	13' - 11"	3,386	8' - 9"	5' - 2"	162	#6	6"	8' - 6"	2,068	5' - 2"	3' - 4"	162	6"	8' - 0"	866	6	39' - 9"	159	44	39' - 9"	1,168	9' - 1"	24	22	61	1.029	246.4	0.7	85	41.8	9,942
8' - 0"	8' - 0"	13"	9"	30'	162	#6	6"	9' - 3"	2,251	162	#6	6"	14' - 2"	3,447	8' - 11"	5' - 3"	162	#6	6"	8' - 9"	2,129	5' - 3"	3' - 6"	162	6"	8' - 0"	866	6	39' - 9"	159	44	39' - 9"	1,168	9' - 3"	25	22	61	1.207	250.5	0.7	86	49.0	10,106

⑤ For direct traffic culverts (fill height ≤ 2 ft.), identify the required box size and select the option with the minimum fill height.


DATE: 5/24/2023 6:20:48 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9\DP5101\WAZ-TXDOT\Par1.s\PS&E\STATEWIDE\SCC-9\SCC-9.ste-21.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of units or for the accuracy of the information provided.




TYPICAL SECTION




PLAN OF REINF STEEL




SECTION THRU CURB



BARS C



BARS D



BARS K (#4)
(Spa = 1'-0" Max)
(Length = 4'-2")

- ① 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail or curbs taller than 1'-0", refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Rail Anchorage Curb (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- ② For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade. Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- ③ For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.
- ④ 1'-0" typical. 2'-3" when the Rail Anchorage Curb (RAC) standard sheet is referred to elsewhere in the plans.

The Contractor may replace Bars B, C, D, E, F1, F2, M, Y, and/or Z with deformed welded wire reinforcement (WWR) meeting the requirements of ASTM A1064. The area of required reinforcement may be reduced by the ratio of 60 ksi / 70 ksi. Spacing of WWR is limited to 4" Min and 18" Max. When required, provide lap splices in the WWR of the same length required for the equivalent bar size, rounded up for wire sizes between conventional bar sizes. The lap length required for WWR is never less than the lap length required for uncoated #4 bars.

Example conversion: Replacing No. 6 Gr 60 at 6" Spacing with WWR.
 Required WWR = (0.44 sq. in. per 0.5 ft.) x (60 ksi / 70 ksi) = 0.755 sq. in. per ft.
 If D30.6 wire is used to meet the 0.755 sq. in. per ft. requirement in this example, the required spacing = (0.306 sq. in.) / (0.755 sq. in. per ft.) x (12 in. per ft.) = 4.86" Max spacing. Required lap length for the provided D30.6 wire is 2'-1" (the same minimum lap length required for uncoated #5 bars, as listed under MATERIAL NOTES).

CONSTRUCTION NOTES:

- Do not use permanent forms.
- Chamfer the bottom edge of the top slab 3" at the entrance.
- Optionally, raise construction joints shown at the flow line by a maximum of 6". If this option is taken, Bars M may be cut off or raised, Bars C and D may be reversed.

MATERIAL NOTES:

- Provide Grade 60 reinforcing steel.
- Provide galvanized reinforcing steel if required elsewhere in the plans.
- Provide Class C concrete (f'c = 3,600 psi) for culvert barrel and curb, with the following exceptions: provide Class S concrete (f'c = 4,000 psi) for top slabs of:
 - culverts with overlay,
 - culverts with 1-to-2 course surface treatment, or
 - culverts with the top slab as the final riding surface.
- Provide bar laps, where required, as follows:
 - Uncoated or galvanized ~ #4 = 1'-8" Min
 - Uncoated or galvanized ~ #5 = 2'-1" Min
 - Uncoated or galvanized ~ #6 = 2'-6" Min

GENERAL NOTES:

- Designed according to AASHTO LRFD Bridge Design Specifications for the range of fill heights shown.
- See the Single Box Culverts Cast-In-Place Miscellaneous Detail (SCC-MD) standard sheet for details pertaining to skewed ends, angle sections, and lengthening.

Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bar dimensions shown are out-to-out of bar.

HL93 LOADING SHEET 1 OF 2



**SINGLE BOX CULVERTS
CAST-IN-PLACE
0' TO 30' FILL**


SCC-9

FILE: scc09ste-20.dgn	DN: TBE	CK: BMP	DW: TXDOT	CK: TXDOT
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	137	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or for the accuracy of the information provided. For more information, please contact the Texas Department of Transportation, 1100 West St. De Witt, TX 76734. (512) 437-7000. FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT_Par1.s\13-SCC09ste-21.dgn DATE: 5/24/2023 6:20:49 PM

SECTION DIMENSIONS				FILL HEIGHT	BILLS OF REINFORCING STEEL (For Box Length = 40 feet)																										QUANTITIES												
					Bars B						Bars C						Bars D						Bars M ~ #4				Bars F1 ~ #4 at 18" Spa			Bars F2 ~ #4 at 18" Spa			Bars H 4 ~ #4		Bars K		Per Foot of Barrel		Curb		Total		
					S	H	T	U	No.	Size	Spa	Length	Weight	No.	Size	Spa	Length	Weight	" X "	" Y "	No.	Size	Spa	Length	Weight	" Y "	" Z "	No.	Spa	Length	Wt	No.	Length	Wt	No.	Length	Weight	Length	Wt	No.	Wt	Conc (CY)	Reinf (Lb)
9' - 0"	4' - 0"	8"	7"	10'	162	#6	6"	9' - 11"	2,413	108	#6	9"	10' - 0"	1,622	4' - 6"	5' - 6"	108	#6	9"	8' - 7"	1,392	5' - 6"	3' - 1"	108	9"	4' - 0"	289	7	39' - 9"	186	35	39' - 9"	929	9' - 11"	26	22	61	0.675	170.8	0.8	87	27.8	6,918

⑤ For direct traffic culverts (fill height ≤ 2 ft.), identify the required box size and select the option with the minimum fill height.



TEXAS DEPARTMENT OF TRANSPORTATION

SINGLE BOX CULVERTS
CAST-IN-PLACE
0' TO 30' FILL








SCC-9

FILE: scc09ste-21.dgn	DN: TBE	CR: BMP	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
04/2021 Updated X values.	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	138	

Bridge Division Standard

DATE: 5/24/2023 6:20:49 PM
 FILE: Z:\Transportation\on\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT\Project\DOT\QFM_512_0579-02-014\CADD\DN\05_DRAINAGE\StdDet\01_S\scmdste-20.dgn

DISCLAIMER:
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



① For skewed box culverts with less than 2'-0" of fill, break back the top slab to provide a 1'-10" minimum lap of the existing longitudinal bars with the longitudinal bars in the extension.
 For non-skewed box culverts with less than 2'-0" of fill and for skewed or non-skewed culverts with a fill depth of 2'-0" or greater, break back the top slab to provide a 1'-10" minimum lap of the existing longitudinal bars with the longitudinal bars in the extension. Alternatively, if the box is non-skewed, embed #6 anchor bars with a Type III, C, D, E, or F anchor adhesive into the existing walls, top and bottom slab at 1'-6" center-to-center spacing. Minimum embedment depth is 8". Anchor adhesive chosen must be able to achieve a basic bond strength in tension, Nba, of 26.4 kips. Submit signed and sealed calculations or the manufacturer's published literature showing the proposed anchor adhesive's ability to develop this load to the Engineer for approval prior to use. Anchor installation, including hole size, drilling, and clean out, must be in accordance with Item 450, "Railing." Test adhesive anchors in accordance with Item 450.3.3, "Tests." Test 3 anchors per 100 anchors installed.
 Break back wings and apron as necessary to install the extension. Clean and extend the exposed wingwall and apron reinforcing into the extension. When lengthening existing box culverts with dimensions different than current standard dimensions, form horizontal and vertical transitions as directed by the Engineer. Match bottom slabs to maintain an uninterrupted flow line. Field bend existing and new reinforcing into transitions and maintain specified cover requirements. For top slabs of culverts with overlay, with 1-to-2 course surface treatment, or with the top slab as the final riding surface, adjust the "H" dimension to provide a smooth riding surface.

- ② When the spacing between Bars B becomes less than half of the normal spacing, cut bars to avoid conflict.
- ③ The length of Bars B vary in the skewed end sections.
- ④ $[One\ half\ of\ overall\ width] \times [tangent\ of\ the\ skew\ angle]$
- ⑤ Place Bars F1 and F2 continuously through the angle section. Bend Bars F1 and F2 to remain parallel to the walls of the box culvert.
- ⑥ When necessary to avoid conflict in acute corners, shorten the slab extension leg of Bars C and Bars D to a minimum of 1'-6" for skews of 30° thru 45°.
- ⑦ At the Contractor's option, for skews of 15° or less, place Bars B, C, and D parallel to the skewed end while maintaining spacing along centerline of box. Increase lengths of Bars B shown on the Single Box Culverts Cast-In-Place (SCC) standards sheets to accommodate the skew.

CONSTRUCTION NOTES:
 Do not use permanent forms.
 When required, lap Bars H 1'-8" for uncoated or galvanized bars.
 Provide a minimum of 1 1/2" clear cover.

MATERIAL NOTES:
 Provide Grade 60 reinforcing steel.
 Provide galvanized reinforcing steel, if required elsewhere in the plans.
 Provide Class C concrete ($f'_c = 3,600$ psi) with these exceptions:
 provide Class S concrete ($f'_c = 4,000$ psi) for top slabs of culverts with overlay, with 1-to-2 course surface treatment, or with the top slab as the final riding surface.

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 Refer to Single Box Culverts Cast-in-Place (SCC) standard sheets for details of straight sections of culvert.
 For skewed sections and angle sections, refer to Single Box Culverts Cast-in-Place (SCC) standard sheets for slab and wall dimensions, bar sizes, maximum bar spacing, and any other details not shown.
 For skewed ends with curbs, adjust length of Bars H, number of Bars K, curb concrete volume, and reinforcing steel weight by dividing the values shown on the culvert Single Box Culverts Cast-In-Place (SCC) standard sheets by the cosine of the skew angle.

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING


		Bridge Division Standard	
SINGLE BOX CULVERTS CAST-IN-PLACE MISCELLANEOUS DETAILS			
SCC-MD			
FILE: scmdste-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
©TxDOT February 2020	CONT	SECT	JOB
REVISIONS	0579	02	014
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	139

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:50 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT\Paris\Project\DOT\OVM_512_05179-02-014\NCADD\DCN\05_DRAINAGE\AS1.dwg (14) scp04sts-20.dgn

BOX DATA


SECTION DIMENSIONS					Fill Height (ft.)	M (Min) (in.)	REINFORCING (sq. in. / ft.) ^②								① Lift Weight (tons)
S (ft.)	H (ft.)	TT (in.)	TB (in.)	TS (in.)			AS1	AS2	AS3	AS4	AS5	AS7	AS8		
4	2	7.5	6	5	< 2	-	0.18	0.27	0.15	0.12	0.18	0.18	0.14	4.5	
4	2	5	5	5	2 < 3	38	0.18	0.19	0.17	0.12	-	-	-	3.6	
4	2	5	5	5	3 - 5	38	0.13	0.13	0.13	0.12	-	-	-	3.6	
4	2	5	5	5	10	38	0.12	0.12	0.12	0.12	-	-	-	3.6	
4	2	5	5	5	15	38	0.14	0.16	0.16	0.12	-	-	-	3.6	
4	2	5	5	5	20	38	0.18	0.20	0.21	0.12	-	-	-	3.6	
4	2	5	5	5	25	38	0.23	0.25	0.25	0.12	-	-	-	3.6	
4	2	5	5	5	30	38	0.28	0.30	0.30	0.12	-	-	-	3.6	
4	3	7.5	6	5	< 2	-	0.18	0.31	0.18	0.12	0.18	0.18	0.14	5.0	
4	3	5	5	5	2 < 3	38	0.15	0.23	0.20	0.12	-	-	-	4.1	
4	3	5	5	5	3 - 5	38	0.12	0.16	0.16	0.12	-	-	-	4.1	
4	3	5	5	5	10	38	0.12	0.14	0.14	0.12	-	-	-	4.1	
4	3	5	5	5	15	38	0.12	0.18	0.18	0.12	-	-	-	4.1	
4	3	5	5	5	20	38	0.14	0.23	0.24	0.12	-	-	-	4.1	
4	3	5	5	5	25	38	0.17	0.29	0.29	0.12	-	-	-	4.1	
4	3	5	5	5	30	38	0.21	0.35	0.35	0.12	-	-	-	4.1	
4	4	7.5	6	5	< 2	-	0.18	0.33	0.20	0.12	0.18	0.18	0.14	5.5	
4	4	5	5	5	2 < 3	38	0.12	0.26	0.23	0.12	-	-	-	4.6	
4	4	5	5	5	3 - 5	38	0.12	0.18	0.18	0.12	-	-	-	4.6	
4	4	5	5	5	10	38	0.12	0.15	0.15	0.12	-	-	-	4.6	
4	4	5	5	5	15	38	0.12	0.19	0.20	0.12	-	-	-	4.6	
4	4	5	5	5	20	38	0.12	0.25	0.25	0.12	-	-	-	4.6	
4	4	5	5	5	25	38	0.14	0.31	0.31	0.12	-	-	-	4.6	
4	4	5	5	5	30	38	0.17	0.37	0.37	0.12	-	-	-	4.6	



FILL HEIGHT 2 FT AND GREATER



FILL HEIGHT LESS THAN 2 FT



SECTION A-A
(Showing top and bottom slab joint reinforcement.)

MATERIAL NOTES:
 Provide 0.03 sq. in./ft. minimum longitudinal reinforcement at each face in slabs and walls. This minimum requirement may be met by the transverse wires when wire mesh reinforcement is used.
 Provide Class H concrete (f'c = 5,000 psi).

GENERAL NOTES:
 Designs shown conform to ASTM C1577. Refer to ASTM C1577 for information or details not shown.
 See Box Culverts Precast Miscellaneous Details (SCP-MD) standard sheet for details and notes not shown.
 In lieu of furnishing the designs shown on this sheet, the contractor may furnish an alternate design that is equal to or exceeds the box design for the design fill height in the table. Submit shop plans for alternate designs in accordance with Item "Precast Concrete Structural Members (Fabrication)".

① For box length = 8'-0"
 ② AS1 thru AS4, AS7 and AS8 are minimum required areas of reinforcement per linear foot of box length. AS5 is minimum required area of reinforcement per linear foot of box width.

HL93 LOADING

Bridge Division Standard

SINGLE BOX CULVERTS PRECAST 4'-0" SPAN

SCP-4


FILE: scp04sts-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
DIST	COUNTY	SHEET NO.		
PARIS	HUNT	140		

DATE: 5/24/2023 6:20:50 PM
 FILE: Z:\Transportation\DOT\STATEWIDE\36-91DPS101\WAZ-TXDOT\Par1s\Project\DOT\512 (0579-02-014)\CADD\DCN\05_DRAINAGE\ST-dDet\01.s\15) scp05sts-20 (1) .dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


BOX DATA

SECTION DIMENSIONS					Fill Height (ft.)	M (Min) (in.)	REINFORCING (sq. in. / ft.) ^②								① Lift Weight (tons)
S (ft.)	H (ft.)	TT (in.)	TB (in.)	TS (in.)			AS1	AS2	AS3	AS4	AS5	AS7	AS8		
5	2	8	7	6	< 2	-	0.19	0.27	0.18	0.14	0.19	0.19	0.17	6.0	
5	2	6	6	6	2 < 3	44	0.22	0.20	0.16	0.14	-	-	-	5.1	
5	2	6	6	6	3 - 5	44	0.16	0.14	0.14	0.14	-	-	-	5.1	
5	2	6	6	6	10	36	0.15	0.14	0.14	0.14	-	-	-	5.1	
5	2	6	6	6	15	36	0.20	0.18	0.18	0.14	-	-	-	5.1	
5	2	6	6	6	20	36	0.26	0.23	0.24	0.14	-	-	-	5.1	
5	2	6	6	6	25	36	0.33	0.29	0.29	0.14	-	-	-	5.1	
5	2	6	6	6	30	36	0.39	0.34	0.35	0.14	-	-	-	5.1	
5	3	8	7	6	< 2	-	0.19	0.31	0.21	0.14	0.19	0.19	0.17	6.6	
5	3	6	6	6	2 < 3	45	0.18	0.24	0.19	0.14	-	-	-	5.7	
5	3	6	6	6	3 - 5	36	0.14	0.17	0.16	0.14	-	-	-	5.7	
5	3	6	6	6	10	36	0.14	0.16	0.17	0.14	-	-	-	5.7	
5	3	6	6	6	15	35	0.16	0.21	0.22	0.14	-	-	-	5.7	
5	3	6	6	6	20	35	0.21	0.27	0.28	0.14	-	-	-	5.7	
5	3	6	6	6	25	35	0.26	0.34	0.34	0.14	-	-	-	5.7	
5	3	6	6	6	30	35	0.31	0.41	0.41	0.14	-	-	-	5.7	
5	4	8	7	6	< 2	-	0.19	0.33	0.24	0.14	0.19	0.19	0.17	7.2	
5	4	6	6	6	2 < 3	45	0.16	0.27	0.22	0.14	-	-	-	6.3	
5	4	6	6	6	3 - 5	45	0.14	0.19	0.18	0.14	-	-	-	6.3	
5	4	6	6	6	10	36	0.14	0.18	0.18	0.14	-	-	-	6.3	
5	4	6	6	6	15	35	0.14	0.23	0.24	0.14	-	-	-	6.3	
5	4	6	6	6	20	35	0.17	0.30	0.31	0.14	-	-	-	6.3	
5	4	6	6	6	25	35	0.21	0.37	0.38	0.14	-	-	-	6.3	
5	4	6	6	6	30	35	0.25	0.44	0.45	0.14	-	-	-	6.3	
5	5	8	7	6	< 2	-	0.19	0.35	0.26	0.14	0.19	0.19	0.17	7.8	
5	5	6	6	6	2 < 3	45	0.14	0.29	0.24	0.14	-	-	-	6.9	
5	5	6	6	6	3 - 5	45	0.14	0.21	0.20	0.14	-	-	-	6.9	
5	5	6	6	6	10	45	0.14	0.19	0.20	0.14	-	-	-	6.9	
5	5	6	6	6	15	36	0.14	0.24	0.25	0.14	-	-	-	6.9	
5	5	6	6	6	20	35	0.15	0.31	0.32	0.14	-	-	-	6.9	
5	5	6	6	6	25	35	0.18	0.38	0.39	0.14	-	-	-	6.9	
5	5	6	6	6	30	35	0.21	0.46	0.47	0.14	-	-	-	6.9	


① For box length = 8'-0"
 ② AS1 thru AS4, AS7 and AS8 are minimum required areas of reinforcement per linear foot of box length. AS5 is minimum required area of reinforcement per linear foot of box width.



FILL HEIGHT 2 FT AND GREATER



FILL HEIGHT LESS THAN 2 FT



SECTION A-A
 (Showing top and bottom slab joint reinforcement.)


MATERIAL NOTES:
 Provide 0.03 sq. in./ft. minimum longitudinal reinforcement at each face in slabs and walls. This minimum requirement may be met by the transverse wires when wire mesh reinforcement is used.
 Provide Class H concrete (f_c = 5,000 psi).

GENERAL NOTES:
 Designs shown conform to ASTM C1577. Refer to ASTM C1577 for information or details not shown.
 See Box Culverts Precast Miscellaneous Details (SCP-MD) standard sheet for details and notes not shown.
 In lieu of furnishing the designs shown on this sheet, the contractor may furnish an alternate design that is equal to or exceeds the box design for the design fill height in the table. Submit shop plans for alternate designs in accordance with Item "Precast Concrete Structural Members (Fabrication)".


HL93 LOADING

		<i>Bridge Division Standard</i>	
SINGLE BOX CULVERTS PRECAST			
5'-0" SPAN			
SCP-5			
FILE: scp05sts-20.dgn	DN: TxDOT	CR: TxDOT	DW: TxDOT
©TxDOT February 2020	CONT	SECT	JOB
REVISIONS	0579	02	014
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	141	


DATE: 5/24/2023 6:20:51 PM
 FILE: Z:\Transportation\on\TxDOT\PS&E\STATEWIDE_36-9\IDP5101\WAZ-TxDOT_Par1.s\Project\DOT\VF 512 (0579-02-014)\CADD\DN\05_DRAINAGE\StdDet\0116\scpmdsts-20 (2).dgn
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




MULTIPLE UNIT PLACEMENT



SECTION B-B




DETAIL "A"




WINGWALL CONNECTION

(Also applies to safety end treatment.)




SECTION THRU TOP SLABS LESS THAN 8"




SECTION THRU CURB

QUANTITIES PER FOOT OF CURB (10)	
Reinforcing Steel	4.12 Lb
Concrete	0.037 CY



BARS C (#4)
(Spa = 1'-0" Max)




BARS K (#4)
(Spa = 1'-0" Max)
(Length = 4'-2")

- 0" Min to 5'-0" Max. Estimated curb heights are shown elsewhere in the plans. For structures with pedestrian rail, bicycle rail, or curbs taller than 1'-0, refer to the Extended Curb Details (ECD) standard sheet. For structures with T631 or T631LS bridge rail, refer to the Mounting Details for T631 & T631LS Rails (T631-CM) standard sheet. Refer to the Box Culvert Rail Mounting Details (RAC) standard sheet for structures with bridge rail other than T631 or T631LS.
- For curbs less than 1'-0" high, tilt Bars K or reduce bar height as necessary to maintain cover. For curbs less than 3" high, Bars K may be omitted.
- Extend curb, wingwall, or safety end treatment reinforcing into concrete closure. Bend or trim, as necessary, any reinforcing that does not fit into closure area.
- Provide a 3'-0" Min cast-in-place concrete closure. Break back boxes in the field or cast boxes short. Provide bands of reinforcing in the closure that are the same size and spacing as in the precast box section. Provide #4 longitudinal reinforcement spaced at 12 inches Max within the closure. Except where shown otherwise, construct the cast-in-place closure flush with the inside and outside faces of the precast box section.
- For multiple unit placements, adjust the length of the closure for the interior walls as necessary. Provide a 3'-0" Min cast-in-place closure in the top slab, bottom slab, and exterior wall. See Section B-B detail when interior walls are cast full length.
- Extend precast box reinforcing a minimum of 1'-0" into concrete closure (Typ).
- Place bands of reinforcing matching the inside and outside face reinforcing in the gaps of the top and bottom slabs. Place a band matching the outside face reinforcing of the wall in the gaps of the walls (placed in the outside face only). Tack weld the bands to the exposed reinforcing at each point of contact.
- For vehicle safety, the following requirements must be met:
 - For structures without bridge rail, construct curbs no more than 3" above finished grade.
 - For structures with bridge rail, construct curbs flush with finished grade. Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work.
- Cement stabilized backfill between boxes is considered part of the box culvert for payment.
- All curb concrete and reinforcing is considered part of the box culvert for payment.
- Any additional concrete and reinforcing required for the closures will be considered subsidiary to the box culvert for payment.
- 1'-0" typical. 2'-3" when the Box Culvert Rail Mounting Details (RAC) standard sheet is referred to elsewhere in the plans.
- For multiple unit placement with overlay, with 1 to 2 course surface treatment, or with the top slab as the final riding surface, provide wall closure as shown in Detail "A".
- This dimension may be increased with approval of the Engineer to allow the precast boxes to be tunneled or jacked in accordance with Item 476, "Jacking, Boring, or Tunneling Pipe or Box". No payment will be made for any additional material in the gap between adjacent boxes.


MATERIAL NOTES:
 Provide Grade 60 reinforcing steel.
 Provide ASTM A1064 welded wire reinforcement.
 Provide Class C concrete (f_c = 3,600 psi) for the closures.
 Provide cement stabilized backfill meeting the requirements of Item 400, "Excavation and Backfill for Structures."
 Any additional concrete required for the closures will be considered subsidiary to the box culvert.

GENERAL NOTES:
 Designed according to AASHTO LRFD Bridge Design Specifications.
 Refer to the Single Box Culverts Precast (SCP) standard sheets for details and notes not shown.
 Chamfer the bottom edge of the top slab closure 3 inches at culvert closure ends.


Cover dimensions are clear dimensions, unless noted otherwise.
 Reinforcing bars dimensions are out-to-out of bars.



ANGLE DETAIL



SECTION A-A




PLAN OF SKEWED ENDS

(Showing multi-box placement.)

HL93 LOADING

		<i>Bridge Division Standard</i>	
BOX CULVERTS PRECAST MISCELLANEOUS DETAILS			
SCP-MD			
FILE: scpmdsts-20.dgn	DN: GAF	CK: LMW	DW: BWH/TxDOT
©TxDOT February 2020	CONT	SECT	JOB
REVISIONS	0579	02	014
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	142


DATE: 5/24/2023 6:20:51 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TXDOT_Par1.s\Project\DOT\QFM_512_0579-02-014\CADD\DN\05_DRAINAGE\SETPD\01.dgn
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




NOTE: All cross pipes, calculations, and dimensions are based on the pipe culverts mitered as shown in this detail. Alternate styles of mitered ends will require that appropriate adjustments be made to the values presented on this standard.

SIDE ELEVATION OF TYPICAL PIPE CULVERT MITER

(Showing corrugated metal pipe (CMP) culvert. Details at reinforced concrete pipe (RCP) culvert are similar.)




ISOMETRIC VIEW OF TYPICAL INSTALLATION




SIDE ELEVATION OF CAST-IN-PLACE CONCRETE


(Showing reinforced concrete pipe (RCP) culvert. Details at corrugated metal pipe (CMP) culvert are similar.)



PIPE WITH BOLTED ANCHOR




PIPE WITH ANCHOR BARS




SECTION C-C

CROSS PIPE DETAILS


Limits of riprap (to be included with SET for payment)



SHOWING TYPICAL PIPE CULVERT AND RIPRAP




SHOWING CROSS PIPE WITH ANCHOR BAR




SHOWING CROSS PIPE WITH BOLTED ANCHOR

SECTION A-A



DETAIL "A"

(Showing invert with corrugated metal pipe (CMP) culvert. Reinforced concrete pipe (RCP) culvert details are similar. Cross pipes not shown for clarity.)



SECTION B-B

(Cross pipes not shown for clarity.)

CROSS PIPE LENGTHS, REQUIRED PIPE SIZES, AND RIPRAP QUANTITIES

Nominal Culvert I.D.	Conc Riprap (CY) (6)	Pipe Culvert Spa ~ G	Single Barrel ~ Q1	Multi-Barrel ~ Q1	Q2	Conditions for Use of Cross Pipes	Cross Pipe Sizes
12"	0.6	0' - 9"	N/A	2' - 1"	1' - 9"	3 or more pipe culverts	3" Std (3.500" O.D.)
15"	0.7	0' - 11"	N/A	2' - 5"	2' - 2"		
18"	0.8	1' - 2"	N/A	2' - 10"	2' - 8"		
21"	0.9	1' - 4"	N/A	3' - 2"	3' - 1"		
24"	0.9	1' - 7"	N/A	3' - 6"	3' - 7"	3 or more pipe culverts	3 1/2" Std (4.000" O.D.)
27"	1.0	1' - 8"	N/A	3' - 10"	3' - 11"		
30"	1.1	1' - 10"	N/A	4' - 2"	4' - 4"	2 or more pipe culverts	3 1/2" Std (4.000" O.D.)
33"	1.2	1' - 11"	4' - 2"	4' - 5"	4' - 8"		
36"	1.3	2' - 1"	4' - 5"	4' - 9"	5' - 1"	All pipe culverts	4" Std (4.500" O.D.)
42"	1.5	2' - 4"	4' - 11"	5' - 5"	5' - 10"		
48"	1.7	2' - 7"	5' - 5"	6' - 0"	6' - 7"	All pipe culverts	5" Std (5.563" O.D.)
54"	2.0	3' - 0"	5' - 11"	6' - 9"	7' - 6"		
60"	2.2	3' - 3"	6' - 5"	7' - 4"	8' - 3"		
66"	2.4	3' - 3"	6' - 11"	7' - 10"	8' - 9"		
72"	2.7	3' - 4"	7' - 5"	8' - 5"	9' - 4"		

- The proper installation of the first cross pipe is critical for vehicle safety. Place the top of the first cross pipe no more than 6" above the flow line.
- Provide cross pipes, except the first bottom pipe, of the size shown in the table. Provide a 3 1/2" standard pipe (4" O.D.) for the first bottom pipe.
- Install the third cross pipe from the bottom of the culvert using a bolted connection. Ensure that riprap concrete does not flow into the cross pipe so as to permit disassembly of the bolted connection to allow cleanout access. At the Contractor's option, install all other cross pipes using the bolted connection details.
- Match cross slope as shown elsewhere in the plans. Cross slope of 6:1 or flatter is required for vehicle safety.
- Riprap placed beyond the limits shown will be paid for as concrete riprap in accordance with Item 432, "Riprap".
- Quantities shown are for one end of one reinforced concrete pipe (RCP) culvert. For multiple pipe culverts or for corrugated metal pipe (CMP) culverts, quantities will need to be adjusted. Riprap quantities are for contractor's information only.

MATERIAL NOTES:

Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise. Provide cross pipes that meet the requirements of ASTM A53 (Type E or S, Gr B), ASTM A500 (Gr B), or API 5LX52. Provide ASTM A307 bolts and nuts. Galvanize all steel components, except concrete reinforcing, after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.

GENERAL NOTES:

Cross pipes are designed for a traversing load of 10,000 pounds at yield as recommended by Research Report 280-2F, "Safety Treatment of Roadside Parallel-Drainage Structures", Texas Transportation Institute, March 1981. Safety end treatments (SET) shown herein are intended for use in those installations where out of control vehicles are likely to traverse the openings approximately perpendicular to the cross pipes. Construct concrete riprap and all necessary inverts in accordance with the requirements of Item 432, "Riprap". Payment for riprap and toewall is included in the Price Bid for each Safety End Treatment.

Bridge Division Standard






SAFETY END TREATMENT
FOR 12" DIA TO 72" DIA
PIPE CULVERTS
TYPE II ~ PARALLEL DRAINAGE

SETP-PD

FILE: setppdse-20.dgn	DN: GAF	CK: CAT	DW: JRP	CK: GAF
©TXDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	143	

DATE: 5/24/2023 6:20:51 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-9\IDP5101\WAZ-TXDOT_Par1.s\Project\DOT\Q\FM_512_0579-02-014\CADD\DN\05_DRAINAGE\StdDet\ci1.s\18)prest01-20_01.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



- FABRICATION NOTES:**
1. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
 2. Provide Grade 60 reinforcing steel or equivalent area of WWR.
 3. Provide typical clear cover of 1 1/2" to reinforcing steel at interior or exterior walls.
 4. Walls or slabs with a thickness of 8" or greater require shrinkage and temperature reinforcing steel. Provide steel area = 0.11 in²/ft each way.
 5. No substitution is allowed for vertical and horizontal #4 bars in corners.
 6. Manufacture base and risers to nearest 3" increment.
 7. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is 3/4".
 8. Provide lifting devices in conformance with Manufacturer's recommendations.
 9. See sheet PDD for sizes, dimensions, and reinforcing steel not shown.

- INSTALLATION NOTES:**
1. If required elsewhere. Inverts (benching) to be provided by Contractor. Concrete or mortar used for invert is subsidiary to specified inlet or manhole.
 2. Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or 1/2 the joint depth, whichever is greater.
 3. Do not grout rubber gasket joints without Manufacturer's recommendation.
 4. For rigid pipe, cut hole in thin wall panel (KO) 4" Max, 2" Min larger than pipe OD.
 5. For flexible pipe, consult boot/seal Manufacturer's specification for placement tolerance and hole size. Center pipe in hole and install boot/seal per Manufacturer's specification.


- GENERAL NOTES:**
1. Precast Base consists of base slab, base unit, risers (as required), reducing slab (as required), and reduced risers (as required). See sheet PDD for sizes.
 2. Designed according to ASTM C913.
 3. Payment for precast base is subsidiary to the specified inlet, per Item 465, "Junction Boxes, Manholes, and Inlets."

Cover dimensions are clear dimensions, unless noted otherwise.


HL93 LOADING

		Bridge Division Standard	
PRECAST BASE			
PB			
FILE: prest01-20.dgn	DN: TXDOT	CK: TXDOT	DW: TXDOT
©TXDOT February 2020	CONT	SECT	JOB
REVISIONS	0579	02	014
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	144	


DATE: 5/24/2023 6:20:52 PM
 FILE: Z:\Transportation\DOT\STATEWIDE_36-91\DP5101\WAZ-TxDOT_Paris\Project\DOT\FM_512_0579-02-014\CADD\05_DRAINAGE\Std\01.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




DETAIL "B"



PLAN VIEW



SECTION A-A



PIPE CONNECTION DETAIL

Connect pipes within 7° of normal to PJB wall. If necessary, use pipe elbow or curved approach alignment to stay within this limit.

FABRICATION NOTES:

1. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
2. Provide Grade 60 reinforcing steel or equivalent area of WWWR.
3. Provide typical clear cover of 1 1/2" to reinforcing steel at interior or exterior walls.
4. Walls or slabs with a thickness of 8" or greater require shrinkage and temperature reinforcing steel. Provide steel area = 0.11 in²/ft each way.
5. No substitution is allowed for vertical and horizontal #4 bars in corners.
6. Manufacture base and risers to nearest 3" increment.
7. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is 3/4".
8. Provide lifting devices in conformance with Manufacturer's recommendations.
9. See sheet PDD for sizes, dimensions, and reinforcing steel not shown.
10. Provide hole in below grade slab only when PJB is installed with inlet type POD.

INSTALLATION NOTES:

1. Inverts (benching) to be provided by Contractor. Concrete or mortar used for invert is subsidiary to junction box.
2. Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or 1/2 the joint depth, whichever is greater.
3. Do not grout rubber gasket joints without Manufacturer's recommendation.
4. For rigid pipe, cut hole in thin wall panel (KO) 4" Max, 2" Min larger than pipe OD.
5. For flexible pipe, consult boot/seal Manufacturer's specification for placement tolerance and hole size. Center pipe in hole and install boot/seal per Manufacturer's specification.

GENERAL NOTES:

1. Precast Junction Box consists of base slab, base unit, risers (as required), and below grade slab. See sheet PDD for sizes.
2. Designed according to ASTM C913.
3. Payment for junction box is per Item 465 "Junction Boxes, Manholes, and Inlets" by type and size.

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING



PRECAST JUNCTION BOX

PJB

FILE: presto09-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	145	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:52 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WAZ-TxDOT_Paris\Project\DOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\Project\DOT\PS&E\STATEWIDE_36-91DP5101.dgn

Size	MAXDEPTH = 15 ft. to top of BASE SLAB											MAXDEPTH = 25 ft. to top of BASE SLAB											Min Height (See Gen Note 3)	Max HOLE DIA (See Fab Note 2)	Max KO DIA (See Fab Note 2)
	Base Slab			Base Unit or Riser Walls			Below Grade Slab (w/PJB) Reducing Slab (w/PB)					Base Slab			Base Unit or Riser Walls			Below Grade Slab (w/PJB) Reducing Slab (w/PB)							
	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Reduced Riser Size	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness	Reduced Riser Size	Short Span Reinf Steel Area	Long Span Reinf Steel Area	Thickness					
X x Y	Ashort	Along	BS	Bshort	Blong	W	RWSxRWL or ID	Dshort	Dlong	TS	Ashort	Along	BS	Bshort	Blong	W	RWSxRWL or ID	Dshort	Dlong	TS	BH MIN	HOLE DIA	KODIA		
ft.	in ² /ft	in ² /ft	in.	in ² /ft	in ² /ft	in.	ft. **	in ² /ft	in ² /ft	in.	in ² /ft	in ² /ft	in.	in ² /ft	in ² /ft	in.	ft. **	in ² /ft	in ² /ft	in.	ft.	in.	in.		
Precast Junction Box (PJB)																									
3x3	0.23	0.23	6	0.19	0.19	6	N/A	0.37	0.37	9	0.29	0.29	6	0.24	0.24	6	N/A	0.37	0.37	9	3.5	36	36		
4x4	0.29	0.29	6	0.24	0.24	6	N/A	0.41	0.41	9	0.47	0.47	6	0.38	0.38	6	N/A	0.41	0.41	9	4.5	48	48		
3x5	0.29	0.18	6	0.19	0.35	6	N/A	0.48	0.48	9	0.39	0.18	6	0.23	0.59	6	N/A	0.48	0.48	9	3.5	36/60	36/60		
4x5	0.36	0.18	6	0.22	0.34	6	N/A	0.42	0.42	9	0.53	0.26	6	0.39	0.59	6	N/A	0.42	0.42	9	4.5	48/60	48/60		
5x5	0.36	0.36	6	0.34	0.34	6	N/A	0.43	0.43	9	0.62	0.62	6	0.59	0.59	6	N/A	0.43	0.43	9	5.5	60	60		
5x6	0.27	0.27	9	0.34	0.45	6	N/A	0.48	0.48	9	0.47	0.45	9	0.38	0.54	8	N/A	0.48	0.48	9	5.5	60/72	60/72		
6x6	0.27	0.27	9	0.45	0.45	6	N/A	0.56	0.56	9	0.52	0.52	9	0.54	0.54	8	N/A	0.56	0.56	9	6.5	72	72		
8x8	0.46	0.46	9	0.51	0.51	8	N/A	0.45	0.45	12	0.87	0.87	9	0.59	0.59	10	N/A	0.45	0.45	12	8.5	96	72		
Precast Base (PB)																									
3x3	0.23	0.23	6	0.19	0.19	6	N/A	N/A	N/A	N/A	0.29	0.29	6	0.24	0.24	6	N/A	N/A	N/A	N/A	3.5	36	36		
4x4	0.29	0.29	6	0.24	0.24	6	N/A	N/A	N/A	N/A	0.47	0.47	6	0.38	0.38	6	N/A	N/A	N/A	N/A	4.5	48	48		
3x5	0.29	0.18	6	0.19	0.35	6	3x3	0.30	0.34	9	0.39	0.18	6	0.23	0.59	6	3x3	0.40	0.40	9	3.5	36/60	36/60		
4x5	0.36	0.18	6	0.22	0.34	6	3x3	0.30	0.30	9	0.53	0.26	6	0.39	0.59	6	3x3	0.46	0.37	9	4.5	48/60	48/60		
4x5	0.36	0.18	6	0.22	0.34	6	4x4	0.30	0.30	9	0.53	0.26	6	0.39	0.59	6	4x4	0.39	0.39	9	4.5	48/60	48/60		
4x5	0.36	0.18	6	0.22	0.34	6	48"	0.39	0.39	9	0.53	0.26	6	0.39	0.59	6	48"	0.47	0.47	9	4.5	48/60	48/60		
4x5	0.36	0.18	6	0.22	0.34	6	3x5	0.33	0.40	9	0.53	0.26	6	0.39	0.59	6	3x5	0.48	0.48	9	4.5	48/60	48/60		
5x5	0.36	0.36	6	0.34	0.34	6	3x3	0.34	0.34	9	0.62	0.62	6	0.59	0.59	6	3x3	0.53	0.53	9	5.5	60	60		
5x5	0.36	0.36	6	0.34	0.34	6	4x4	0.36	0.36	9	0.62	0.62	6	0.59	0.59	6	4x4	0.64	0.64	9	5.5	60	60		
5x5	0.38	0.38	6	0.34	0.34	6	48"	0.36	0.36	9	0.62	0.62	6	0.59	0.59	6	48"	0.64	0.64	9	5.5	60	60		
5x5	0.36	0.36	6	0.34	0.34	6	3x5	0.34	0.40	9	0.62	0.62	6	0.59	0.59	6	3x5	0.53	0.53	9	5.5	60	60		
5x6	0.31	0.31	9	0.34	0.45	6	3x3	0.34	0.34	9	0.47	0.45	9	0.38	0.54	8	3x3	0.61	0.50	9	5.5	60/72	60/72		
5x6	0.27	0.27	9	0.34	0.45	6	4x4	0.36	0.45	9	0.47	0.45	9	0.38	0.54	8	4x4	0.74	0.57	9	5.5	60/72	60/72		
5x6	0.29	0.29	9	0.34	0.45	6	48"	0.36	0.45	9	0.47	0.45	9	0.38	0.54	8	48"	0.74	0.57	9	5.5	60/72	60/72		
5x6	0.29	0.29	9	0.34	0.45	6	3x5	0.45	0.45	9	0.47	0.45	9	0.38	0.54	8	3x5	0.61	0.61	9	5.5	60/72	60/72		
6x6	0.29	0.29	9	0.45	0.45	6	3x3	0.41	0.41	9	0.52	0.52	9	0.54	0.54	8	3x3	0.74	0.74	9	6.5	72	72		
6x6	0.27	0.27	9	0.45	0.45	6	4x4	0.45	0.45	9	0.52	0.52	9	0.54	0.54	8	4x4	0.87	0.87	9	6.5	72	72		
6x6	0.29	0.29	9	0.45	0.45	6	48"	0.45	0.45	9	0.52	0.52	9	0.54	0.54	8	48"	0.87	0.87	9	6.5	72	72		
6x6	0.29	0.29	9	0.45	0.45	6	3x5	0.45	0.45	9	0.52	0.52	9	0.54	0.54	8	3x5	0.87	0.87	9	6.5	72	72		
8x8	0.52	0.52	9	0.51	0.51	8	3x3	0.61	0.61	12	0.91	0.91	9	0.70	0.70	10	3x3	0.85	0.85	12	8.5	96	72		
8x8	0.52	0.52	9	0.51	0.51	8	4x4	0.70	0.70	12	0.87	0.87	9	0.70	0.70	10	4x4	1.01	1.01	12	8.5	96	72		
8x8	0.52	0.52	9	0.51	0.51	8	48"	0.70	0.70	12	0.87	0.87	9	0.70	0.70	10	48"	1.01	1.01	12	8.5	96	72		
8x8	0.52	0.52	9	0.51	0.51	8	3x5	0.70	0.85	12	0.87	0.87	9	0.70	0.70	10	3x5	1.01	1.01	12	8.5	96	72		

** Unless otherwise indicated.

FABRICATION NOTES:

- Maximum spacing of reinforcement is 8".
- At manufacturer's option, provide cast or cored holes or thin wall panels (KO) to the maximum diameter shown for each. When no penetration is required, it is acceptable to provide a wall with no sectional reduction.

GENERAL NOTES:


- Precast Junction Box consists of base slab, base unit, risers (as required), and below grade slab. See sheet PJB for details.
- Precast Base consists of base slab, base unit, risers (as required), reducing slab (as required), and reduced risers (as required). See sheet PB for details.
- Min Height shown is for stock base units. Use stock base units whenever practical. Smaller height base units can be used in special installation circumstances, when noted elsewhere in the plans. Absolute minimum height of base units is 2'-6".

HL93 LOADING

		Bridge Division Standard	
DESIGN DATA FOR PRECAST BASE AND JUNCTION BOX			
PDD			
FILE: prest10-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
©TxDOT February 2020	CONT	SECT	HIGHWAY
REVISIONS	0579	02	014 FM 512
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	146	


DATE: 5/24/2023 6:20:52 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-9\DP5101\W42-TXDOT_Par1.s\Pre-Design\Drawings\PS&E\STANDARD-20 (1) .dgn

DISCLAIMER:
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any drawings or specifications from any other source.




PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
 PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF PLAN




PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
 PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF PLAN




PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
 PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF ELEVATION



PRECAST ROUND MANHOLE (PRM) WITH THROUGH-HOLE
 PRECAST BASE (PB) OR PRECAST JUNCTION BOX (PJB) WITH THIN-WALL KNOCK-OUT

TYPICAL HALF ELEVATION



TYPICAL PARTIAL ELEVATION OF PRECAST SAFETY END TREATMENTS

Showing square PSET for parallel drainage, cross drainage shown similar.

① Completely fill the void between the precast structure and the connecting pipe or box with cementitious grouts and mortars in accordance with DMS-4675 "Cementitious Grouts and Mortars for Miscellaneous Application".

CONSTRUCTION NOTES:

- Do not grout rubber gasket joints without Manufacturer's recommendations.
- Do not use bricks, masonry blocks, native stone, or similar materials in conjunction with grouted connections when filling void spaces around pipes or box culverts.

MATERIAL NOTES:

- Provide grouted connections in accordance with DMS-4675 "Cementitious Grouts and Mortars for Miscellaneous Application".


GENERAL NOTES:

- See applicable standards for notes and details not shown:
 - Precast Base (PB)
 - Precast Junction Box (PJB)
 - Precast Round Manhole (PRM)
 - Precast Safety End Treatments C/D Square (PSET-SC)
 - Precast Safety End Treatments P/D Square (PSET-SP)
- Provide Concrete Box Culverts in accordance with Item 462 "Concrete Box Culverts and Drains".
- Provide Reinforced Concrete Pipe (RCP) in accordance with Item 464 "Reinforced Concrete Pipe".
- Provide Thermoplastic Pipe (TP) in accordance with Special Specification Thermoplastic Pipe.
- Payment for grouted connections is considered subsidiary to other bid items.


				Bridge Division Standard	
PIPE AND BOX GROUTED CONNECTIONS FOR PRECAST STRUCTURES					
PBGC					
FILE: pbgcsld1-20.dgn	DN: TxDOT	CK: TAR	DW: JTR	CK: TAR	
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0579	02	014	FM 512	
	DIST	COUNTY	SHEET NO.		
	PARIS	HUNT	147		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:20:53 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE_36-91\DP5101\WAZ-TxDOT_Paris\Projec+D+o\FM_512_(0579-02-014)\CADD\DGN\05_DRAINAGE\Std+D+o\i.s.(21)prest05-20.dgn




ELEVATION VIEW




ELEVATION VIEW




ELEVATION VIEW




ELEVATION VIEW




STYLE 'FG'




STYLE 'SFG'
ELEVATION VIEW




PLAN VIEW
NO OPENINGS
STYLE 'SL'




PLAN VIEW
SHIP LOOSE RING & COVER
STYLE 'RH'




PLAN VIEW
32" DIA CAST-IN RING & COVER
STYLE 'RC'




PLAN VIEW
32" DIA CAST-IN RING & GRATE
STYLE 'RG'




ELEVATION VIEW




ELEVATION VIEW



PLAN VIEW
CAST-IN FRAME & GRATE
STYLES 'FG' & 'SFG'



PLAN VIEW
SHIP LOOSE FRAME & GRATE
STYLE 'SH'



PLAN VIEW
EXPOSED REBAR
STYLE 'S1'

① Matches inside face of wall of precast base or riser below inlet.


HL93 LOADING		SHEET 1 OF 2	
			Bridge Division Standard
PRECAST SLAB LID			
PSL			
FILE: prest05-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
©TxDOT February 2020	CONT: 0579	SECT: 02	JOB: 014
REVISIONS	DIST: PARIS		COUNTY: HUNT
	HIGHWAY: FM 512		SHEET NO.: 148

DATE: 5/24/2023 6:20:53 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-9\IDP5101\WAZ-TXDOT_Paris\Project\DOT\FM_512_0519-02-014\CADD\DN\05_DRAINAGE\Std\Detail\prest05-20.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

Style	Size (X x Y)	W ⁽²⁾	A x B (nominal)	Short Span Reinf Steel Area	Long Span Reinf Steel Area
SL	3'x3'	6"	n/a	0.37 in ² /ft	0.37 in ² /ft
RH,RC,RG,SH,S1,FG	3'x3'	6"	3'x3' or 32" Dia	0.37 in ² /ft	0.37 in ² /ft
SFG	3'x3'	6"	3'x3'	0.32 in ² /ft	0.32 in ² /ft
SL	4'x4'	6"	n/a	0.34 in ² /ft	0.34 in ² /ft
RH,RC,RG,SH,S1,FG	4'x4'	6"	3'x3' or 32" Dia	0.41 in ² /ft	0.41 in ² /ft
SH,S1,FG	4'x4'	6"	4'x4'	0.41 in ² /ft	0.41 in ² /ft
SFG	4'x4'	6"	4'x4'	0.32 in ² /ft	0.32 in ² /ft
SL	3'x5'	6"	n/a	0.39 in ² /ft	0.39 in ² /ft
RH,RC,RG,SH,S1,FG	3'x5'	6"	3'x3' or 32" Dia	0.48 in ² /ft	0.48 in ² /ft
SH,S1,FG	3'x5'	6"	3'x5'	0.48 in ² /ft	0.48 in ² /ft
SFG	3'x5'	6"	3'x5'	0.32 in ² /ft	0.32 in ² /ft
SL	4'x5'	6"	n/a	0.42 in ² /ft	0.42 in ² /ft
RH,RC,RG,SH,S1,FG	4'x5'	6"	3'x3' or 32" Dia	0.42 in ² /ft	0.42 in ² /ft
SH,S1,FG	4'x5'	6"	4'x4'	0.63 in ² /ft	0.63 in ² /ft
SH,S1,FG	4'x5'	6"	3'x5'	0.66 in ² /ft	0.66 in ² /ft
SL	5'x5'	6"	n/a	0.36 in ² /ft	0.36 in ² /ft
RH,RC,RG,SH,S1,FG	5'x5'	6"	3'x3' or 32" Dia	0.43 in ² /ft	0.43 in ² /ft
SH,S1,FG	5'x5'	6"	4'x4'	0.63 in ² /ft	0.63 in ² /ft
SH,S1,FG	5'x5'	6"	3'x5'	0.63 in ² /ft	0.63 in ² /ft
SL	5'x6'	6"/8"	n/a	0.48 in ² /ft	0.48 in ² /ft
RH,RC,RG,SH,S1,FG	5'x6'	6"/8"	3'x3' or 32" Dia	0.48 in ² /ft	0.48 in ² /ft
SH,S1,FG	5'x6'	6"/8"	4'x4'	0.60 in ² /ft	0.60 in ² /ft
SH,S1,FG	5'x6'	6"/8"	3'x5'	0.60 in ² /ft	0.60 in ² /ft
SL	6'x6'	6"/8"	n/a	0.43 in ² /ft	0.43 in ² /ft
RH,RC,RG,SH,S1,FG	6'x6'	6"/8"	3'x3' or 32" Dia	0.56 in ² /ft	0.56 in ² /ft
SH,S1,FG	6'x6'	6"/8"	4'x4'	0.56 in ² /ft	0.56 in ² /ft
SH,S1,FG	6'x6'	6"/8"	3'x5'	0.59 in ² /ft	0.59 in ² /ft
SL	8'x8'	8"/10"	n/a	0.45 in ² /ft	0.45 in ² /ft
RH,RC,RG,SH,S1,FG	8'x8'	8"/10"	3'x3' or 32" Dia	0.45 in ² /ft	0.45 in ² /ft
SH,S1,FG	8'x8'	8"/10"	4'x4'	0.45 in ² /ft	0.45 in ² /ft
SH,S1,FG	8'x8'	8"/10"	3'x5'	0.45 in ² /ft	0.45 in ² /ft

⁽²⁾ See sheet PDD for corresponding wall thickness (W) of base unit or riser.

Construct cast-in-place reinforced concrete apron, when shown elsewhere in plans. Use Class "A" concrete. Apron is subsidiary to PSL. Apron is 1'-6" Min width around precast zone drain.



DETAIL "A"

(Reinforcing not shown for clarity)
 When an apron is to be cast around PSL, use detail above to create an apron ledge on all 4 sides.

FABRICATION NOTES:

1. Locate penetration (Style 'RH'), ring and cover (Style 'RC'), ring and grate (Style 'RG'), and frame and grate (Style 'FG') in a corner. Only one penetration is allowed per slab lid.
2. Provide Class "H" concrete in accordance with Item 421 and having a minimum compressive strength of 5,000 psi.
3. Provide Grade 60 reinforcing steel or equivalent area of WWR.
4. Provide clear cover of 3/4" to reinforcing from lower outside shoulder of slab for structural reinforcement, and 2" from top of slab for shrinkage and temperature reinforcement. Place short span reinforcing closest to surface.
5. Slabs with a thickness of 8" or greater require shrinkage and temperature reinforcing. Provide steel area = 0.11 in²/ft each way.
6. No substitution is allowed for diagonal #4 bars around openings.
7. Design tongue and groove joints for full closure on both shoulders. Minimum spigot depth is 3/4".
8. Provide lifting devices in conformance with Manufacturer's recommendations.

INSTALLATION NOTES:

1. Precast slab lids are intended for direct traffic and may be placed in roadway.
2. Seal tongue and groove joints with preformed or bulk mastic in conformance with Manufacturer's recommendations. Tongue and groove joints may be grouted no more than 1" between each section, or 1/2 the joint depth, whichever is greater.
3. Do not grout rubber gasket joints without Manufacturer's recommendation.
4. Initial installation of grade adjustment rings for Styles 'RH' and 'SH' is limited to 1'-0" Max as shown.
5. Grade adjustment rings for Styles 'RH' and 'SH' may be increased to 2'-0" Max when future construction affects final grade of structure. Make adjustments greater than 2'-0" with additional risers. Adjustments can be made up to Max depth shown on sheet PDD. Structure must be evaluated if Max depth will be exceeded.
6. Orient long dimension of grate slots perpendicular to traffic, unless noted otherwise on plans.

GENERAL NOTES:

1. Designed according to ASTM C913.
2. Payment for lid is per Item 465, "Junction Boxes, Manholes, and Inlets" by type, style, size, and opening size (when applicable).

Cover dimensions are clear dimensions, unless noted otherwise.

HL93 LOADING SHEET 2 OF 2



PRECAST SLAB LID

PSL

FILE: prest05-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT February 2020	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	149	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:20:54 PM
 FILE: Z:\Transportation\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM_512_(0579-02-014)\CADD\DN\05_DRAINAGE\StdDetail-19.dgn




FIGURE 1 ~ TYPE R STONE RIPRAP
dry or grouted




FIGURE 2 ~ TYPE F STONE RIPRAP
dry or mortared




FIGURE 3 ~ TYPE F STONE RIPRAP
grouted




FIGURE 4 ~ COMMON STONE RIPRAP
dry or grouted





FIGURE 5 ~ PROTECTION STONE RIPRAP

- ② Provide bedding material instead of filter fabric if shown elsewhere in plans. See Layout for thickness of bedding material.
- ③ Minimum toe depth is the larger of the maximum scour depth or 2 times the riprap thickness.
- ④ "Y" and Height need to be defined. See layout or detail sheet for values if this option is used.
- ⑤ List Stone Protection as size (XX inch) and thickness (YY inch) on the layout.
Example: Riprap (Stone Protection) XX inch, Thickness = YY inch.



PROTECTION STONE RIPRAP TOE OPTIONS

SHEET 2 OF 2

		Bridge Division Standard	
<h2>STONE RIPRAP</h2>			
<h3>SRR</h3>			
FILE: srrstd1-19.dgn	DN: AES	CK: JGD	DW: BWH
©TxDOT	APR 2019	CONTRACT: 0579	SECTION: 02
REVISIONS:		JOB: 014	HIGHWAY: FM 512
		DIST: PARIS	COUNTY: HUNT
			SHEET NO.: 151

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
1	1	SOUTH/TEXAS 34/ARROW UP/NORTH/TEXAS 34/ARROW RIGHT	X
1	2	WEIGHT/LIMIT/GROSS/58420/LBS	X
1	3	STOP	X
1	4	SOUTH/FARM ROAD 512/224	X
1	5	ARROW UP GREENVILLE/HONEY GROVE ARROW RIGHT	X
1	6	STOP	X
1	7	ARROW RIGHT (SYMBOL)/20 MPH	X
1	8	STOP	X
1	9	E CROCKETT ST/S GREENVILLE ST/STOP	X
1	10	SPEED LIMIT 35	X
1	11	CHEVRON/CHEVRON	X
1	12	CHEVRON/CHEVRON	X
1	13	STOP	X
1	14	ARROW RIGHT/ARROW LEFT	X
1	15	CHEVRON/CHEVRON	X
1	16	CHEVRON/CHEVRON	X
1	17	ABERFOYLE 7/COMMERCE 18	X
1	18	JCT/TEXAS 37	X
1	19	ARROW LEFT (SYMBOL)/20 MPH	X
2	1	SPEED LIMIT 55	X
2	2	SPEED LIMIT 35	X
3	1	WOLFE CITY/CITY LIMIT/POP 1412	X
3	2	SPEED LIMIT 55	X
3	3	SPEED LIMIT 50	X
3	4	SPEED LIMIT 50 AHEAD (SYMBOL)	X
4	1	CO RD/4817/ARROW RIGHT	X
4	2	HUNT COUNTY/4817/STOP	X
4	3	MULTIPLE CURVE LEFT (SYMBOL)/40 MPH	X
4	4	CO RD/4817/ARROW LEFT	X

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
5	1	CHEVRON/CHEVRON	X
5	2	CHEVRON/CHEVRON	X
5	3	CHEVRON/CHEVRON	X
5	4	CHEVRON/CHEVRON	X
5	5	CHEVRON/CHEVRON	X
5	6	CHEVRON/CHEVRON	X
5	7	CHEVRON/CHEVRON	X
5	8	CHEVRON/CHEVRON	X
5	9	CHEVRON/CHEVRON	X
5	10	CHEVRON/CHEVRON	X
5	11	CHEVRON/CHEVRON	X
5	12	CHEVRON/CHEVRON	X
5	13	CHEVRON/CHEVRON	X
5	14	CHEVRON/CHEVRON	X
5	15	CO RD/4719/ARROW LEFT	X
5	16	CHEVRON/CHEVRON	X
5	17	CHEVRON/CHEVRON	X
5	18	CHEVRON/CHEVRON	X
5	19	CHEVRON/CHEVRON	X
5	20	HUNT COUNTY/4719/STOP	X
6	1	CHEVRON/CHEVRON	X
6	2	CHEVRON/CHEVRON	X
6	3	CHEVRON/CHEVRON	X
6	4	CHEVRON/CHEVRON	X
6	5	CO RD/4719/ARROW RIGHT	X
6	6	CHEVRON/CHEVRON	X
6	7	CHEVRON/CHEVRON	X
6	8	CHEVRON/CHEVRON	X
6	9	FARM ROAD 512/226	X
6	10	MULTIPLE CURVE LEFT (SYMBOL)/40 MPH	X
8	1	HUNTY COUNTY 4816	
8	2	STOP	X
8	3	CO RD/4816/ARROW LEFT	X
9	1	CURVE LEFT (SYMBOL)/45 MPH	X

PAGE TOTAL: 63



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
EXISTING SMALL SIGN INVENTORY


SHEET 1 OF 4

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	152

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
10	1	CHEVRON/CHEVRON	X
10	2	BRIDGE/MAY ICE IN/COLD/WEATHER	X
10	3	CHEVRON/CHEVRON	X
10	4	CHEVRON/CHEVRON	X
10	5	CHEVRON/CHEVRON	X
10	6	CHEVRON/CHEVRON	X
10	7	TURKEY/CREEK	X
10	8	CHEVRON/CHEVRON	X
10	9	CHEVRON/CHEVRON	X
10	10	CHEVRON/CHEVRON	X
10	11	CHEVRON/CHEVRON	X
10	12	CHEVRON/CHEVRON	X
11	1	CURVE RIGHT (SYMBOL)/45 MPH	X
11	2	CURVE RIGHT (SYMBOL)/45 MPH	X
11	3	FARM ROAD 512/228	X
11	4	PASS WITH CARE	X
12	1	CURVE LEFT (SYMBOL)/50 MPH	X
12	2	CURVE LEFT (SYMBOL)/50 MPH	X
12	3	CO RD/4727/ARROW RIGHT	X
12	4	HUNT COUNTY/4727/STOP	X
12	5	PASS WITH CARE	X
12	6	CO RD/4727/ARROW LEFT	X
12	7	DO NOT PASS	X
13	1	CURVE RIGHT (SYMBOL)/50 MPH	X
13	2	DOUBLE CURVE RIGHT (SYMBOL)/40 MPH	X
13	3	DO NOT PASS	X
13	4	CO RD/4722/ARROW LEFT	X
13	5	BUS STOP AHEAD	X
13	6	HUNT COUNTY/4722/STOP	X
13	7	CHEVRON/CHEVRON	X
13	8	PASS WITH CARE	X
13	9	CHEVRON/CHEVRON	X
13	10	CHEVRON/CHEVRON	X
13	11	CHEVRON/CHEVRON	X
13	12	CHEVRON/CHEVRON	X
13	13	CHEVRON/CHEVRON	X
13	14	CHEVRON/CHEVRON	X

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
14	1	CHEVRON/CHEVRON	X
14	2	ADOPT A/HIGHWAY/NEXT 2 MILES/ABERFOYLE/BAPTIST/CHURCH	X
14	3	CHEVRON/CHEVRON	X
14	4	CHEVRON/CHEVRON	X
14	5	CHEVRON/CHEVRON	X
14	6	DOUBLE CURVE RIGHT (SYMBOL)/40 MPH	X
14	7	DOUBLE CURVE RIGHT (SYMBOL)/40 MPH	X
14	8	CHEVRON/CHEVRON	X
14	9	CHEVRON/CHEVRON	X
14	10	CHEVRON/CHEVRON	X
14	11	CHEVRON/CHEVRON	X
14	12	CHEVRON/CHEVRON	X
14	13	CHEVRON/CHEVRON	X
14	14	CHEVRON/CHEVRON	X
15	1	CHEVRON/CHEVRON	X
15	2	CHEVRON/CHEVRON	X
15	3	CHEVRON/CHEVRON	X
15	4	CHEVRON/CHEVRON	X
15	5	CHEVRON/CHEVRON	X
15	6	CHEVRON/CHEVRON	X
15	7	CHEVRON/CHEVRON	X
15	8	CHEVRON/CHEVRON	X
15	9	CHEVRON/CHEVRON	X
15	10	CHEVRON/CHEVRON	X
15	11	PASS WITH CARE	X
15	12	SPEED LIMIT 55	X
15	13	ABERFOYLE	X
16	1	DOUBLE CURVE RIGHT (SYMBOL)/40 MPH	X
16	2	DO NOT PASS	X
16	3	DOUBLE CURVE RIGHT (SYMBOL)/50 MPH	X
16	4	DO NOT PASS	X
16	5	GARDNER LN/STOP	X
16	6	PASS WITH CARE	X

PAGE TOTAL: 70



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512

EXISTING SMALL SIGN INVENTORY


SHEET 2 OF 4

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	153
CONTROL	SECTION	JOB	
0579	02	014	

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
17	1	CO RD/ARROW LEFT 4617/4502 ARROW RIGHT	X
17	2	HUNT COUNTY/4617/STOP	X
17	3	HUNT COUNTY/4502/STOP	X
17	4	CO RD/ARROW LEFT 4502/4617 ARROW RIGHT	X
17	5	ARROW RIGHT (SYMBOL)/35 MPH	X
17	6	DOUBLE CURVE LEFT (SYMBOL)/50 MPH	X
17	7	CHEVRON/CHEVRON	X
17	8	CHEVRON/CHEVRON	X
17	9	CHEVRON/CHEVRON	X
17	10	CHEVRON/CHEVRON	X
17	11	CHEVRON/CHEVRON	X
17	12	CHEVRON/CHEVRON	X
17	13	CHEVRON/CHEVRON	X
18	1	CHEVRON/CHEVRON	X
18	2	PASS WITH CARE	X
18	3	CHEVRON/CHEVRON	X
18	4	CHEVRON/CHEVRON	X
18	5	DO NOT PASS	X
18	6	ARROW LEFT (SYMBOL)/30 MPH	X
18	7	DO NOT PASS	X
18	8	JCT/FARM ROAD 512	X
19	1	CHEVRON/CHEVRON	X
19	2	PASS WITH CARE	X
19	3	CHEVRON/CHEVRON	X
19	4	CHEVRON/CHEVRON	X
19	5	SPEED LIMIT 55	X
19	6	CHEVRON/CHEVRON	X
19	7	CHEVRON/CHEVRON	X
19	8	CHEVRON/CHEVRON	X
19	9	ARROW UP FAIRLIE/SOUTH SULPHER ARROW RIGHT	X
20	1	FARM ROAD 512	X
20	2	CHEVRON/CHEVRON	X
20	3	ADOPT A/HIGHWAY/NEXT 2 MILES/ABERFOYLE/BAPTIST/CHURCH	X
20	4	DO NOT PASS	X
20	5	EAST/FARM ROAD 2655/ARROW UP/SOUTH/FARM ROAD 512/ARROW RIGHT	X
20	6	ARROW RIGHT (SYMBOL)/30 MPH	X
20	7	ARROW LEFT RIGHT	X
20	8	NORTH/FARM ROAD 512/ARROW LEFT/EAST/FARM ROAD 2655/ARROW RIGHT	X
20	9	STOP	X
20	10	YIELD	X

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
21	1	DO NOT PASS	X
21	2	FARM ROAD 512	X
21	3	SPEED LIMIT 55	X
21	4	STOP AHEAD (SYMBOL)	X
21	5	PASS WITH CARE	X
21	6	JCT/FARM ROAD 2655	X
21	7	DO NOT PASS	X
22	1	ARROW LEFT (SYMBOL)/35 MPH	X
22	2	DO NOT PASS	X
22	3	CHEVRON/CHEVRON	X
22	4	CO RD/4600/ARROW RIGHT	X
22	5	PASS WITH CARE	X
22	6	CHEVRON/CHEVRON	X
22	7	ARROW LEFT/CHEVRON	X
22	8	CHEVRON/CHEVRON	X
22	9	HUNT COUNTY/4600/STOP	X
22	10	WESLEY CHAPEL/CEMETERY/ARROW LEFT/WESLEY CHAPEL/CEMETERY/ARROW RIGHT	X
22	11	CHEVRON/ARROW LEFT	X
22	12	PASS WITH CARE	X
22	13	CHEVRON/CHEVRON	X
22	14	CHEVRON/CHEVRON	X
22	15	CO RD/4600/ARROW LEFT	X
22	16	WEIGHT/LIMIT/GROSS/58420/LBS	X
22	17	WEIGHT/LIMIT/GROSS/58420/LBS	X
22	18	ARROW RIGHT (SYMBOL)/35 MPH	X
23	1	DO NOT PASS	X
23	2	DO NOT PASS	X
23	3	ARROW RIGHT (SYMBOL)/30 MPH	X
23	4	FARM ROAD 512/232	X
23	5	CO RD/4601/ARROW LEFT	X
23	6	CHEVRON/CHEVRON	X
23	7	CHEVRON/CHEVRON	X
23	8	PASS WITH CARE	X
23	9	CHEVRON/CHEVRON	X
23	10	ARROW LEFT/CHEVRON	X
23	11	HUNT COUNTY/4601/STOP	X
23	12	CHEVRON/ARROW LEFT	X
23	13	PASS WITH CARE	X
23	14	CHEVRON/CHEVRON	X
23	15	DO NOT PASS	X

PAGE TOTAL: 80



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

PLANNERS ENGINEERS MANAGERS



FM 512
EXISTING SMALL SIGN INVENTORY

SHEET 3 OF 4

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	154
CONTROL	SECTION	JOB	
0579	02	014	

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
23	16	ARROW LEFT (SYMBOL)/30 MPH	X
24	1	ARROW RIGHT (SYMBOL)/40 MPH	X
24	2	DO NOT PASS	X
24	3	BRIDGE/MAY ICE IN/COLD/WEATHER	X
24	4	CHEVRON/CHEVRON	X
24	5	PASS WITH CARE	X
24	6	CHEVRON/CHEVRON	X
24	7	CHEVRON/CHEVRON	X
24	8	CHEVRON/CHEVRON	X
24	9	CHEVRON/CHEVRON	X
24	10	SCHOOL/BUS STOP/AHEAD	X
24	11	ARROW LEFT (SYMBOL)/40 MPH	X
24	12	DO NOT PASS	X
24	13	DO NOT PASS	X
25	1	BRIDGE/MAY ICE IN/COLD/WEATHER	X
25	2	SOUTH SULPHUR	X
26	1	MULTIPLE CURVE LEFT (SYMBOL)/35 MPH	X
26	2	DO NOT PASS	X
26	3	CO RD/4507/ARROW LEFT	X
26	4	CHEVRON/CHEVRON	X
26	5	CHEVRON/CHEVRON	X
26	6	HUNT COUNTY/4507/STOP	X
26	7	CHEVRON/CHEVRON	X
26	8	JCT/FARM ROAD 118	X
26	9	CHEVRON/CHEVRON	X
26	10	PASS WITH CARE	X
26	11	CHEVRON/CHEVRON	X
26	12	CO RD/4507/ARROW RIGHT	X
26	13	CHEVRON/CHEVRON	X
26	14	CHEVRON/CHEVRON	X
26	15	CHEVRON/CHEVRON	X
26	16	CHEVRON/CHEVRON	X
27	1	SPEED LIMIT 55	X
27	2	CHEVRON/CHEVRON	X
27	3	CHEVRON/CHEVRON	X
27	4	NORTH/FARM ROAD 512	X
27	5	CHEVRON/CHEVRON	X
27	6	CHEVRON/CHEVRON	X
27	7	CHEVRON/CHEVRON	X
27	8	CHEVRON/CHEVRON	X

PLAN SHEET NO.	SIGN NO.	SIGN	REMOVE
27	9	SOUTH/FARM ROAD 512/ARROW UP/SOUTH/FARM ROAD 118/ARROW RIGHT	X
27	10	ARROW LEFT RIGHT	X
27	11	STOP/CROSS TRAFFIC/DOES NOT STOP	X
PAGE TOTAL: 43			
PROJECT TOTALS: 256			



Paul A. Warden, P.E. 5/24/2023

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825

 **Texas Department of Transportation** © 2023

**FM 512
EXISTING SMALL SIGN INVENTORY**

SHEET 4 OF 4

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	155
CONTROL	SECTION	JOB	
0579	02	014	

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
0+63 LT	1	M3-3 M1-6T M6-3 M3-1 M1-6T M6-1R	SOUTH TEXAS 34 ARROW UP NORTH TEXAS 34 ARROW RIGHT	24 x 12 24 x 24 21 x 15 24 x 12 24 x 24 21 x 15	X		S80	1	SA	U		
3+18 RT	2	R12-1T	WEIGHT/LIMIT/GROSS/58420/LBS	24 x 36	X		10BWG	1	SA	P		
3+51 LT	3	R1-1	STOP	30 x 30	X		10BWG	1	SA	P		
5+98 RT	4	M3-3 M1-6F D10-7aT	SOUTH FARM ROAD 512 224	24 x 12 24 x 24 3 x 10	X		10BWG	1	SA	P		
7+23 LT	5	D1-2	ARROW UP/GREENVILLE/HONEY GROVE/ARROW RIGHT	108 x 30	X		S80	1	SA	U	WC	
7+30 LT	6	R1-1	STOP	30 x 30	X		10BWG	1	SA	P		
8+72 RT	7	R1-1	STOP	30 x 30	X		10BWG	1	SA	P		
9+40 LT	8	* * R1-1	E/CROCKETT/ST S/GREENVILLE/ST STOP	30 x 30	X		10BWG	1	SA	P		
9+66 RT	9	R2-1	SPEED LIMIT 35	30 x 36	X		10BWG	1	SA	P		
10+32 RT	10	W1-1R W13-1P	RIGHT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
11+32 LT	11	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
11+70 LT	12	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
11+96 LT	13	R1-1	STOP	30 x 30	X		10BWG	1	SA	P		
12+30 LT	14	W1-6R W1-6L	ARROW RIGHT ARROW LEFT	36 x 18 36 x 18	X		10BWG	1	SA	U		
12+47 LT	15	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
12+87 LT	16	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
14+10 RT	17	W1-1L W13-1P	LEFT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
15+13 RT	18	D2-2	ABERFOYLE 7/COMMERCE 18	90 x 30	X		S80	1	SA	U	WC	
17+12 LT	19	M2-1 M1-6T	JCT TEXAS 34	21 x 15 24 x 24	X		10BWG	1	SA	P		
21+62 RT	20	R1-1	STOP	30 x 30	X		10BWG	1	SA	P		
21+77 RT	21	R2-1	SPEED LIMIT 50	30 x 36	X		10BWG	1	SA	P		
21+79 LT	22	R2-1	SPEED LIMIT 35	30 x 36	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD (GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 1 OF 12



SUMMARY OF SMALL SIGNS


SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	156	

DATE: 5/24/2023 6:20:55 PM
 FILE: Z:\transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\08_TRAFFIC\slums16.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80							1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S	
39+52 RT	23	R2-1	SPEED LIMIT 55	30 x 36	X		10BWG	1	SA	P		
39+52 LT	24	I-2aT	WOLFE CITY/CITY LIMIT/POP 1390	60 x 24	X		10BWG	1	SA	T		
39+55 LT	25	R2-1	SPEED LIMIT 50	30 x 36	X		10BWG	1	SA	P		
42+50 LT	26	W3-5	SPEED LIMIT 50 AHEAD (SYMBOL)	36 x 36	X		10BWG	1	SA	P		
68+91 RT	27	D20-1TR	CO RD/4817/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
71+44 RT	28	* R1-1	HUNT/COUNTY/4817 STOP	30 x 30	X		10BWG	1	SA	P		
73+31 LT	29	D20-1TL	CO RD/4817/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
78+15 RT	30	W1-5L W13-1P	S-CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
79+44 RT	31	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
80+72 RT	32	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
81+87 RT	33	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
83+76 LT	34	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
84+67 LT	35	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
85+58 LT	36	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
86+50 LT	37	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
91+29 RT	38	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
92+33 RT	39	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
93+37 RT	40	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
94+38 RT	41	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
95+65 RT	42	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
96+40 RT	43	D20-1TL	CO RD/4719/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
98+28 LT	44	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topover signs installed on new stop sign post. Subsidiary to item 644.

SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	157	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DPS101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
98+47 LT	45	* R1-1	HUNT/COUNTY/4719 STOP	30 x 30	X		10BWG	1	SA	P		
99+74 LT	46	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
100+80 LT	47	D20-1TR	CO RD/4719/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
100+86 LT	48	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
101+98 LT	49	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
103+10 LT	50	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
104+37 LT	51	M1-6F D10-7aT	FARM ROAD 512 226	24 x 24 3 x 10	X		10BWG	1	SA	P		
105+40 LT	52	W1-5L W13-1P	S-CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
148+61 RT	53	D20-1TR	CO RD/4816/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
150+90 RT	54	* R1-1	HUNT/COUNTY/4816 STOP	30 x 30	X		10BWG	1	SA	P		
152+81 LT	55	D20-1TL	CO RD/4816/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
176+20 RT	56	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
183+00 RT	57	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
184+55 RT	58	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
184+98 RT	59	W8-13aT	BRIDGE/MAY ICE IN/COLD/WEATHER	36 x 36	X		10BWG	1	SA	P		
186+10 RT	60	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
187+65 RT	61	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
189+20 RT	62	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
190+05 LT	63	I-3	TURKEY/CREEK	18 x VAR	X		10BWG	1	SA	P		
190+75 RT	64	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
192+30 RT	65	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
193+85 RT	66	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 3 OF 12

Texas Department of Transportation

Traffic Operations Division Standard

SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	158	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80							1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S	
194+11 LT	67	W8-13aT	BRIDGE/MAY ICE IN/COLD/WEATHER	36 x 36	X		10BWG	1	SA	P		
195+40 RT	68	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
197+00 RT	69	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
199+25 LT	70	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
211+41 RT	71	M1-6F D10-7aT	FARM ROAD 512 228	24 x 24 3 x 10	X		10BWG	1	SA	P		
214+00 RT	72	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
217+34 LT	73	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
218+50 LT	74	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
229+25 RT	75	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
229+43 RT	76	D20-1TR	CO RD/4727/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
231+80 RT	77	* R1-1	HUNT/COUNTY/4727 STOP	30 x 30	X		10BWG	1	SA	P		
232+13 RT	78	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
233+20 LT	79	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
233+65 LT	80	D20-1TL	CO RD/4727/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
238+56 LT	81	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
240+20 RT	82	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
244+32 LT	83	S3-1T	SCHOOL BUS STOP AHEAD	36 x 36	X		10BWG	1	SA	P		
242+74 RT	84	D20-1TL	CO RD/4722/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
246+86 LT	85	* R1-1	HUNT/COUNTY/4722 STOP	30 x 30	X		10BWG	1	SA	P		
247+00 RT	86	W1-4R W13-1P	DOUBLE-CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
249+02 LT	87	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
249+16 LT	88	D20-1TR	CO RD/4722/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
249+26 LT	89	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topover signs installed on new stop sign post. Subsidiary to item 644.

SHEET 4 OF 12



SUMMARY OF SMALL SIGNS


SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	159	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512_0579-02-014\XCADD\GNN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80							1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S	
250+12 LT	90	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
251+22 LT	91	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
252+32 LT	92	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
253+42 LT	93	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
259+47 RT	94	W1-8L	CHEVRON LEFT	18 x 24	X		10BWG	1	SA	P		
		W1-8R	CHEVRON RIGHT	18 x 24								
260+56 RT	95	W1-8L	CHEVRON LEFT	18 x 24	X		10BWG	1	SA	P		
		W1-8R	CHEVRON RIGHT	18 x 24								
260+85 RT	96	D14-4T	ADOPT A HIGHWAY NEXT 2 MILES ABERFOYLE BAPTIST CHURCH	48 x 48	X		10BWG	1	SA	P		
261+68 RT	97	W1-8L	CHEVRON LEFT	18 x 24	X		10BWG	1	SA	P		
		W1-8R	CHEVRON RIGHT	18 x 24								
262+74 RT	98	W1-8L	CHEVRON LEFT	18 x 24	X		10BWG	1	SA	P		
		W1-8R	CHEVRON RIGHT	18 x 24								
263+84 RT	99	W1-8L	CHEVRON LEFT	18 x 24	X		10BWG	1	SA	P		
		W1-8R	CHEVRON RIGHT	18 x 24								
265+10 LT	100	W1-4R	DOUBLE-CURVE RIGHT (SYMBOL)	36 x 36	X		10BWG	1	SA	P		
		W13-1P	XX MPH	18 x 18								
269+05 RT	101	W1-4R	DOUBLE-CURVE RIGHT (SYMBOL)	36 x 36	X		10BWG	1	SA	P		
		W13-1P	XX MPH	18 x 18								
270+34 LT	102	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
271+47 LT	103	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
272+60 LT	104	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
273+73 LT	105	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
274+86 LT	106	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
275+99 LT	107	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
277+12 LT	108	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								
278+25 LT	109	W1-8R	CHEVRON RIGHT	18 x 24	X		10BWG	1	SA	P		
		W1-8L	CHEVRON LEFT	18 x 24								



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 5 OF 12

Traffic Operations Division Standard

SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	160	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023 6:20:56 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
279+39 LT	110	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
284+56 RT	111	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
285+69 RT	112	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
286+82 RT	113	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
287+95 RT	114	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
289+10 RT	115	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
290+21 RT	116	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
291+34 RT	117	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
292+47 RT	118	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
293+61 RT	119	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
301+12 LT	120	W1-4R W13-1P	DOUBLE-CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
295+96 RT	121	R4-2	PASS WITH CARE	18 x 24	X			1	SA	P		
296+91 RT	122	R2-1	SPEED LIMIT 55	30 x 36	X			1	SA	P		
298+81 RT	123	I-2cT	ABERFOYLE	60 x 12	X			1	SA	T		
304+34 LT	124	R4-1	DO NOT PASS	18 x 24	X			1	SA	P		
307+27 RT	125	R4-1	DO NOT PASS	18 x 24	X			1	SA	P		
311+83 RT	126	D3-1 R1-1	GARDNER LN STOP	VAR x VAR 30 x 30	X			1	SA	P		
312+20 RT	127	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
313+87 LT	128	R4-2	PASS WITH CARE	18 x 24	X			1	SA	P		
316+10 LT	129	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
322+33 RT	130	D20-5T (L,R)	CO RD/4617/ARROW LEFT 4502/ARROW RIGHT	24 x 42	X			1	SA	P		
323+00 RT	131	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 6 OF 12

Texas Department of Transportation
Traffic Operations Division Standard

SUMMARY OF SMALL SIGNS


SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	161	

DATE: 5/24/2023
 TIME: 6:20:57 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNN\08_TRAFFIC\sums16.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
323+80 LT	132	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
324+16 LT	133	* R1-1	HUNT/COUNTY/4617 STOP	30 x 30	X			1	SA	P		
324+76 RT	134	* R1-1	HUNT/COUNTY/4502 STOP	30 x 30	X			1	SA	P		
325+31 LT	135	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
326+51 LT	136	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
326+61 LT	137	D20-5T(L,R)	CO RD/4502/ARROW LEFT 4617/ARROW RIGHT	24 x 42	X			1	SA	P		
327+80 LT	138	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
332+65 RT	139	W1-1R W13-1P	RIGHT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
334+17 LT	140	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
335+17 LT	141	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
336+17 LT	142	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
337+00 LT	143	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
338+17 LT	144	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
339+17 LT	145	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
339+19 RT	146	R4-2	PASS WITH CARE	18 x 24	X			1	SA	P		
341+20 LT	147	W1-2L W13-1P	LEFT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
343+95 LT	148	R4-1	DO NOT PASS	18 x 24	X			1	SA	P		
349+09 LT	149	I-2cT	ABERFOYLE	60 x 12	X			1	SA	T		
356+80 RT	150	R4-1	DO NOT PASS	18 x 24	X			1	SA	P		
358+38 RT	151	M2-1 M1-6F	JCT FARM ROAD 2653	21 x 15 24 x 24	X			1	SA	P		
361+76 RT	152	W1-2L W13-1P	LEFT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topover signs installed on new stop sign post. Subsidiary to item 644.

SHEET 7 OF 12



SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	162	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM_512_0579-02-014\CAD\OGN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
363+07 RT	153	M3-3 M1-6F M5-1R	SOUTH FARM ROAD 512 ARROW RIGHT	24 x 12 24 x 24 21 x 15	X		10BWG	1	SA	P		
363+54 LT	154	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
363+76 RT	155	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
364+53 RT	156	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
365+30 RT	157	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
366+07 RT	158	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
366+84 RT	159	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
367+61 RT	160	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
368+00 RT	161	D1-2	ARROW UP FARLIE/SOUTH SULPHER ARROW RIGHT	114 x 30	X		S80	1	SA	U	WC	
368+38 RT	162	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
368+92 LT	163	R2-1	SPEED LIMIT 55	30 x 36	X		10BWG	1	SA	P		
369+17 RT	164	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
371+17 LT	165	W1-1R W13-1P	RIGHT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
371+31 LT	166	D14-4T	ADOPT A HIGHWAY NEXT 2 MILES ABERFOYLE BAPTIST CHURCH	48 x 48	X		10BWG	1	SA	P		
372+17 LT	167	M1-6F	FARM ROAD 512	24 x 24	X		10BWG	1	SA	P		
372+91 LT	168	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
374+40 RT	169	M3-2 M1-6F M6-3 M3-3 M1-6F M6-1R	EAST FARM ROAD 2655 ARROW UP SOUTH FARM ROAD 512 ARROW RIGHT	24 x 12 24 x 24 21 x 15 24 x 12 24 x 24 21 x 15	X		S80	1	SA	U		
374+92 LT	170	W1-7T	ARROW LEFT-RIGHT	96 x 36	X		S80	1	SA	U	WC	
374+99 LT	171	M3-1 M1-6F M6-1L M3-2 M1-6F M6-1R	NORTH FARM ROAD 512 ARROW LEFT EAST FARM ROAD 2655 ARROW RIGHT	24 x 12 24 x 24 21 x 15 24 x 12 24 x 24 21 x 15	X		S80	1	SA	U		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD (GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 8 OF 12

Texas Department of Transportation
Traffic Operations Division Standard

SUMMARY OF SMALL SIGNS


SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	163	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
375+19 LT	172	R1-1 W4-4P	STOP CROSS TRAFFIC/DOES NOT STOP	36 x 36 24 x 12	X		10BWG	1	SA	P		
375+46 LT	173	R1-2	YIELD	36 x 36 x 36	X		10BWG	1	SA	P		
378+00 RT	174	M1-6F	FARM ROAD 512	24 x 24	X		10BWG	1	SA	P		
379+25 RT	175	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
381+25 RT	176	R2-1	SPEED LIMIT 55	30 x 36	X		10BWG	1	SA	P		
382+63 LT	177	D1-2	ARROW LEFT ABERFOYLE/FARLIE ARROW RIGHT	90 x 30	X		S80	1	SA	U	WC	
385+10 LT	178	W3-1	STOP AHEAD (SYMBOL)	36 x 36	X		10BWG	1	SA	P		
386+18 RT	179	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
388+30 LT	180	M3-1 M1-6F M5-1L	NORTH FARM ROAD 512 ARROW LEFT	24 x 12 24 x 24 21 x 15	X		10BWG	1	SA	P		
391+48 LT	181	M2-1 M1-6F	JCT FARM ROAD 2653	21 x 15 24 x 24	X		10BWG	1	SA	P		
395+24 LT	182	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
402+54 RT	183	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
405+40 RT	184	W1-1R W13-1P	LEFT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
406+82 LT	185	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
407+42 RT	186	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
408+13 RT	187	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
408+63 RT	188	D20-1TR	CO RD/4600/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
408+84 RT	189	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
409+55 RT	190	W1-6L W1-8R	ARROW LEFT CHEVRON RIGHT	18 x 36 18 x 24	X		10BWG	1	SA	P		
410+26 RT	191	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X		10BWG	1	SA	P		
410+88 RT	192	* R1-1	HUNT/COUNTY/4600 STOP	30 x 30	X		10BWG	1	SA	P		
411+02 LT	193	D3-3bTR D3-3bTL	WESLEY CHAPEL/CEMETERY/ARROW RIGHT WESLEY CHAPEL/CEMETERY/ARROW LEFT	78 x 36 78 x 36	X		S80	1	SA	U	WC	
411+10 RT	194	W1-8L W1-6R	CHEVRON LEFT ARROW RIGHT	18 x 24 18 x 36	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 9 OF 12



SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	164	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512_0579-02-014\CADD\GEN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80							1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S	
411+63 RT	195	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
411+76 RT	196	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 36 18 x 24	X		10BWG	1	SA	P		
412+41 RT	197	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 36 18 x 24	X		10BWG	1	SA	P		
413+00 LT	198	D20-1TL	CO RD/4600/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
414+45 LT	199	W1-1R W13-1P	RIGHT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
414+85 RT	200	R12-1T	WEIGHT/LIMIT/GROSS/58420/LBS	24 x 36	X		10BWG	1	SA	P		
416+99 LT	201	R12-1T	WEIGHT/LIMIT/GROSS/58420/LBS	24 x 36	X		10BWG	1	SA	P		
419+16 RT	202	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
419+18 LT	203	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
422+00 RT	204	W1-1R W13-1P	RIGHT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
423+01 RT	205	M1-6F D10-7aT	FARM ROAD 512 232	24 x 24 3 x 10	X		10BWG	1	SA	P		
425+80 RT	206	D20-1TL	CO RD/4601/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
426+07 LT	207	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
426+19 LT	208	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
426+79 LT	209	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
427+51 LT	210	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
428+05 LT	211	* R1-1	HUNT/COUNTY/4601 STOP	30 x 30	X		10BWG	1	SA	P		
428+37 LT	212	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
428+95 LT	213	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
429+66 LT	214	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
429+96 RT	215	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
430+67 LT	216	D20-1TR	CO RD/4601/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
431+70 LT	217	W1-1L W13-1P	LEFT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 10 OF 12



SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
©TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	165	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM_512_0579-02-014\CAD\08\TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
435+36 LT	218	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
439+14 RT	219	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
445+30 RT	220	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
445+98 LT	221	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
446+60 LT	222	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
447+72 LT	223	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
448+20 RT	224	W8-13aT	BRIDGE/MAY ICE IN/COLD/WEATHER	36 x 36	X		10BWG	1	SA	P		
448+86 LT	225	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
450+00 LT	226	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
451+24 RT	227	W5-2	NARROW BRIDGE	36 x 36	X		10BWG	1	SA	P		
454+79 LT	228	S3-1T	SCHOOL BUS STOP AHEAD	36 x 36	X		10BWG	1	SA	P		
455+79 LT	229	W5-2	NARROW BRIDGE	36 x 36	X		10BWG	1	SA	P		
457+60 LT	230	W8-13aT	BRIDGE/MAY ICE IN/COLD/WEATHER	36 x 36	X		10BWG	1	SA	P		
457+79 LT	231	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
458+28 RT	232	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
474+10 RT	233	I-2cT	SOUTH/SULPHER	54 x 24	X		10BWG	1	SA	T		
481+61 RT	234	R4-1	DO NOT PASS	18 x 24	X		10BWG	1	SA	P		
487+00 RT	235	D20-1TL	CO RD/4507/ARROW LEFT	24 x 24	X		10BWG	1	SA	P		
488+91 LT	236	* R1-1	HUNT/COUNTY/4507 STOP	30 x 30	X		10BWG	1	SA	P		
490+06 RT	237	M2-1 M1-6F	JCT FARM ROAD 118	21 x 15 24 x 24	X		10BWG	1	SA	P		
490+38 LT	238	R4-2	PASS WITH CARE	18 x 24	X		10BWG	1	SA	P		
491+20 LT	239	D20-1TR	CO RD/4507/ARROW RIGHT	24 x 24	X		10BWG	1	SA	P		
493+80 RT	240	W1-2R W13-1P	CURVE RIGHT (SYMBOL) XX MPH	36 x 36 18 x 18	X		10BWG	1	SA	P		
494+87 LT	241	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		
496+15 LT	242	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X		10BWG	1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SHEET 11 OF 12



SUMMARY OF SMALL SIGNS

SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	166	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNGN\08_TRAFFIC\sums16.dgn

SUMMARY OF SMALL SIGNS

STATION	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A)	EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)				BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)	
							POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION		
										PREFABRICATED		1EXT or 2EXT = # of Ext
							FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	P = "Plain" T = "T" U = "U"	BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels	TY = TYPE TY N TY S
497+43 LT	243	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
498+72 LT	244	W1-8R W1-8L	CHEVRON RIGHT CHEVRON LEFT	18 x 24 18 x 24	X			1	SA	P		
499+75 LT	245	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
500+75 LT	246	R2-1	SPEED LIMIT 55	30 x 36	X			1	SA	P		
501+50 RT	247	W1-2L W13-1P	CURVE LEFT (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
504+00 LT	248	M3-1 M1-6F	NORTH FARM ROAD 512	21 x 15 24 x 24	X			1	SA	P		
501+50 RT	249	W1-1L W13-1P	LEFT TURN (SYMBOL) XX MPH	36 x 36 18 x 18	X			1	SA	P		
506+05 RT	250	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
506+86 RT	251	W1-8L W1-8R	CHEVRON LEFT CHEVRON RIGHT	18 x 24 18 x 24	X			1	SA	P		
506+88 RT	252	M3-3 M1-6F M6-3 M3-1 M1-6F M6-1R	SOUTH FARM ROAD 512 ARROW UP SOUTH FARM ROAD 118 ARROW RIGHT	24 x 12 24 x 24 21 x 15 24 x 12 24 x 24 21 x 15	X			1	SA	U		
507+56 LT	253	W1-7T	ARROW LEFT-RIGHT	96 x 36	X			1	SA	U	WC	
507+73 LT	254	M1-6F M6-4	FARM ROAD 512 ARROW LEFT-RIGHT	24 x 24 21 x 15	X			1	SA	P		
508+05 RT	255	R1-1 W4-4P	STOP CROSS TRAFFIC/DOES NOT STOP	36 x 36 24 x 12	X			1	SA	P		



Paul A. Warden, P.E. 5/24/2023

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>


- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD (GEN).
- * Existing city/county road topper signs installed on new stop sign post. Subsidiary to item 644.

SUMMARY OF SMALL SIGNS


SOSS

FILE: slums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-16	DIST	COUNTY	SHEET NO.	
8-16	PARIS	HUNT	167	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023 6:20:58 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GNN\08_TRAFFIC\sums16.dgn




D1-2 8in UP-RT;
1.875" Radius, 0.750" Border, White on Green;
Standard Arrow Custom 10.000" X 7.125" 90"; "Greenville", ClearviewHwy-3-W;
1.875" Radius, 0.750" Border, White on Green;
"Honey Grove", ClearviewHwy-3-W; Standard Arrow Custom 12.000" X 7.125" 0°;




D2-2 8in;
1.875" Radius, 0.750" Border, White on Green;
"Aberfoyle", ClearviewHwy-3-W; "7", ClearviewHwy-3-W;
1.875" Radius, 0.750" Border, White on Green;
"Commerce", ClearviewHwy-3-W; "18", ClearviewHwy-3-W;




I-2aT 6in;
1.500" Radius, 0.750" Border, White on Green;
"Wolfe City", ClearviewHwy-5-W-R; "CITY LIMIT", ClearviewHwy-3-W;
"POP 1412", ClearviewHwy-3-W;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4817", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4817", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4719", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4719", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4816", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4816", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




I-3 5in;
1.500" Radius, 0.500" Border, White on Green;
"Turkey", ClearviewHwy-3-W;
"Creek", ClearviewHwy-3-W;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4727", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;



D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4727", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4722", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4722", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;



D14-4T-2_48x48;
3.000" Radius, 1.000" Border, White on Blue;
"ADOPT A", ClearviewHwy-1-W;
"HIGHWAY", ClearviewHwy-1-W;
"NEXT 2 MILES", ClearviewHwy-1-W;
3.000" Radius, 1.000" Border, White on Blue;
"ABERFOYLE", ClearviewHwy-1-W;
"BAPTIST", ClearviewHwy-1-W;
"CHURCH", ClearviewHwy-1-W;



I-2cT 6in;
1.500" Radius, 0.500" Border, White on Green;
"Aberfoyle", ClearviewHwy-5-W-R;



5/24/2023
Charles M. Shine, P.E.



IDCUS PLANNERS ENGINEERS MANAGERS
8632 Fredericksburg Rd., Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825





FM 512
SIGN DETAILS

SHEET 1 OF 3


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	168




D20-5T_24x42;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4617", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;
"4502", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




D20-5T_24x42;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4502", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;
"4617", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




I-2cT 6in;
1.500" Radius, 0.500" Border, White on Green;
"Aberfoyle", ClearviewHwy-5-W-R;



D1-2 8in LT-RT;
1.875" Radius, 0.750" Border, White on Green;
Standard Arrow Custom 12.000" X 7.125" 180°; "Aberfoyle", ClearviewHwy-3-W;
1.875" Radius, 0.750" Border, White on Green;
"Fairlie", ClearviewHwy-3-W; Standard Arrow Custom 12.000" X 7.125" 0°;




D1-2 8in UP-RT;
1.875" Radius, 0.750" Border, White on Green;
Standard Arrow Custom 10.000" X 7.125" 90°; "Farlie", ClearviewHwy-3-W;
1.875" Radius, 0.750" Border, White on Green;
"South Sulphur", ClearviewHwy-3-W; Standard Arrow Custom 12.000" X 7.125" 0°;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4600", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




D14-4T-2_48x48;
3.000" Radius, 1.000" Border, White on Blue;
"ADOPT A", ClearviewHwy-1-W;
"HIGHWAY", ClearviewHwy-1-W;
"NEXT 2 MILES", ClearviewHwy-1-W;
3.000" Radius, 1.000" Border, White on Blue;
"ABERFOYLE", ClearviewHwy-1-W;
"BAPTIST", ClearviewHwy-1-W;
"CHURCH", ClearviewHwy-1-W;



D3-3bTR_VARx36;
2.250" Radius, 0.750" Border, White on Green;
"WESLEY CHAPEL", ClearviewHwy-3-W; "CEMETERY", ClearviewHwy-3-W;
Standard Arrow Custom 20.000" X 6.125" 0°;



D3-3bTL_VARx36;
2.250" Radius, 0.750" Border, White on Green;
"WESLEY CHAPEL", ClearviewHwy-3-W; "CEMETERY", ClearviewHwy-3-W;
Standard Arrow Custom 20.000" X 6.125" 180°;



5/24/2023

Charles M. Shine, P.E.


IDCUS PLANNERS ENGINEERS MANAGERS
8632 Fredericksburg Rd., Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825




FM 512
SIGN DETAILS

SHEET 2 OF 3


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	169
CONTROL	SECTION	JOB	
0579	02	014	




D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4600", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4601", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;




D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4601", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;




I-2cT 6in;
1.500" Radius, 0.500" Border, White on Green;
"SOUTH", ClearviewHwy-5-W-R;
"SULPHUR", ClearviewHwy-5-W-R;



D20-1TL_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4507", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 180°;



D20-1TR_24x24;
1.500" Radius, 0.750" Border, White on Green;
"CO RD", ClearviewHwy-3-W;
"4507", ClearviewHwy-3-W;
Standard Arrow Custom 14.000" X 6.125" 0°;



5/24/2023

Charles M. Shine, P.E.

IDCUS  8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825

 **Texas Department of Transportation** © 2023

FM 512
SIGN DETAILS

SHEET 3 OF 3

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	170
CONTROL	SECTION	JOB	
0579	02	014	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:01 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08*TRAFFIC\StdDetail\smngen.dgn

SIGN SUPPORT DESCRIPTIVE CODES

(Descriptive Codes correspond to project estimate and quantities sheets)

SM RD SGN ASSM TY XXXXX(X)XX(X-XXXX)

Post Type

FRP = Fiberglass Reinforced Plastic Pipe (see SMD(FRP))
 TWT = Thin-Walled Tubing (see SMD(TWT))
 10BWG = 10 BWG Tubing (see SMD(SLIP-1) to (SLIP-3))
 S80 = Schedule 80 Pipe (see SMD(SLIP-1) to (SLIP-3))

Number of Posts (1 or 2)


Anchor Type

UA = Universal Anchor - Concreted (see SMD(FRP) and (TWT))
 UB = Universal Anchor - Bolted down (see SMD(FRP) and (TWT))
 WS = Wedge Anchor Steel - (see SMD(TWT))
 WP = Wedge Anchor Plastic (see SMD(TWT))
 SA = Slipbase - Concreted (see SMD(SLIP-1) to (SLIP-3))
 SB = Slipbase - Bolted Down (see SMD(SLIP-1) to (SLIP-3))

Sign Mounting Designation

P = Prefab. "Plain" (see SMD(SLIP-1) to (SLIP-3), (TWT), (FRP))
 T = Prefab. "T" (see SMD(SLIP-1) to (SLIP-3), (TWT))
 U = Prefab. "U" (see SMD(SLIP-1) to (SLIP-3))
 IF REQUIRED
 1EXT or 2EXT = Number of Extensions (see SMD(SLIP-1) to (SLIP-3), (TWT))
 BM = Extruded Wind Beam (see SMD(SLIP-1) to (SLIP-3))
 WC = 1.12 #/ft Wing Channel (see SMD(SLIP-1) to (SLIP-3))
 EXAL = Extruded Aluminum Sign Panels (see SMD(SLIP-3))


REQUIRED CLEARANCE FOR BREAKAWAY SUPPORT



To avoid vehicle undercarriage snagging, any substantial remains of a breakaway support, when it is broken away, should not project more than 4 inches above a 60-inch chord (i.e., typical space between wheel paths).


SIGN LOCATION

PAVED SHOULDERS



LESS THAN 6 FT. WIDE


When the shoulder is 6 ft. or less in width, the sign must be placed at least 12 ft. from the edge of the travel lane.



GREATER THAN 6 FT. WIDE


When the shoulder is greater than 6 ft in width, the sign must be placed at least 6 ft. from the edge of the shoulder.

T-INTERSECTION




When this sign is needed at the end of a two-lane, two way roadway, the right edge of the sign should be in line with the centerline of the roadway. Place as close to ROW as practical.


No more than 2 sign posts should be located within a 7 ft. circle.



BEHIND BARRIER




BEHIND GUARDRAIL



BEHIND CONCRETE BARRIER

**Sign clearance based on distance required for proper guard rail or concrete barrier performance.

TYPICAL SIGN ATTACHMENT DETAIL




Bolts used to mount sign panels to the clamp are 5/16-18 UNC galvanized square head with nut, nylon washer, flat washer and lock washer. The bolt length is 1 inch for aluminum.

When two sign clamps are used to mount signs back-to-back, use a 5/16-18 UNC galvanized hex head per ASTM A307 with nut and helical-spring lock washer. The approximate bolt lengths for various post sizes and sign clamp types are given in the table at right. The bolt length may need to be adjusted depending upon field conditions.

Sign clamps may be either the specific size clamp or the universal clamp.


Pipe Diameter	Approximate Bolt Length	
	Specific Clamp	Universal Clamp
2" nominal	3"	3 or 3 1/2"
2 1/2" nominal	3 or 3 1/2"	3 1/2 or 4"
3" nominal	3 1/2 or 4"	4 1/2"

SIGNS WITH PLAQUES




When a supplemental plaque or secondary sign is used, the 7 ft sign height is measured to the bottom of the supplemental plaque or secondary sign.

CURB & GUTTER OR RAISED ISLAND



RESTRICTED RIGHT-OF-WAY (When 6 ft min. is not possible.)



Right-of-way restrictions may be created by rocks, water, vegetation, forest, buildings, a narrow island, or other factors.

In situations where a lateral restriction prevents the minimum horizontal clearance from the edge of the travel lane, signs should be placed as far from the travel lane as practical.

*** Post may be shorter if protected by guardrail or if Engineer determines the post could not be hit due to extreme slope.




SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS GENERAL NOTES & DETAILS

SMD (GEN) -08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0579	02	014	FM 512
		DIST	COUNTY		SHEET NO.
		PARIS	HUNT		171

TRIANGULAR SLIPBASE INSTALLATION GENERAL REQUIREMENTS



NOTE

There are various devices approved for the Triangular Slipbase System. Please reference the Material Producer List for approved slip base systems. http://www.txdot.gov/business/producer_list.htm The devices shall be installed per manufacturers' recommendations. Installation procedures shall be provided to the Engineer by Contractor.

GENERAL NOTES:

- Slip base shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to approval of the TxDOT Traffic Standards Engineer.
- Material used as post with this system shall conform to the following specifications:
 - 10 BWG Tubing (2.875" outside diameter)
 - 0.134" nominal wall thickness
 - Seamless or electric-resistance welded steel tubing or pipe
 - Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008
 - Other steels may be used if they meet the following:
 - 55,000 PSI minimum yield strength
 - 70,000 PSI minimum tensile strength
 - 20% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.122" to 0.138"
 - Outside diameter (uncoated) shall be within the range of 2.867" to 2.883"
 - Galvanization per ASTM A123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833.
 - Schedule 80 Pipe (2.875" outside diameter)
 - 0.276" nominal wall thickness
 - Steel tubing per ASTM A500 Gr C
 - Other seamless or electric-resistance welded steel tubing or pipe with equivalent outside diameter and wall thickness may be used if they meet the following:
 - 46,000 PSI minimum yield strength
 - 62,000 PSI minimum tensile strength
 - 21% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.248" to 0.304"
 - Outside diameter (uncoated) shall be within the range of 2.855" to 2.895"
 - Galvanization per ASTM A123
- See the Traffic Operations Division website for detailed drawings of sign clamps and Texas Universal Triangular Slipbase System components. The website address is: <http://www.txdot.gov/publications/traffic.htm>
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.

ASSEMBLY PROCEDURE


Foundation

- Prepare 12-inch diameter by 42-inch deep hole. If solid rock is encountered, the depth of the foundation may be reduced such that it is embedded a minimum of 18 inches into the solid rock.
- The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor-driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class A.
- Push the pipe end of the slip base stub into the center of the concrete. Rotate the stub back and forth while pushing it down into the concrete to assure good contact between the concrete and stub. Continue to work the stub into the concrete until it is between 2 to 4 inches above the ground.
- Plumb the stub. Allow a minimum of 4 days to set, unless otherwise directed by the Engineer.
- The triangular slipbase system is multidirectional and is designed to release when struck from any direction.

Support

- Cut support so that the bottom of the sign will be 7 to 7.5 feet above the edge of the travelway (i.e., edge of the closest lane) when slip plate is below the edge of pavement or 7 to 7.5 feet above slip plate when the slip plate is above the edge of the travelway. The cut shall be plumb and straight.
- Attach sign to support using connections shown. When multiple signs are installed on the same support, ensure the minimum clearance between each sign is maintained. See SMD(SLIP-2) for clearances based on sign types.

CONCRETE ANCHOR



Concrete anchor consists of 5/8" diameter stud bolt with UNC series bolt threads on the upper end. Heavy hex nut per ASTM A563, and hardened washer per ASTM F436. The stud bolt shall have a minimum yield and ultimate tensile strength of 50 and 75 KSI, respectively. Nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." Adhesive type anchors shall have stud bolts installed with Type III epoxy per DMS-6100, "Epoxyes and Adhesives." Adhesive anchors may be loaded after adequate epoxy cure time per the manufacturer's recommendations. Top of bolt shall extend at least flush with top of the nut when installed. The anchor, when installed in 4000 psi normal-weight concrete with a 5 1/2" minimum embedment, shall have a minimum allowable tension and shear of 3900 and 3100 psi, respectively.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:02 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE_36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DN\08*TRAFFIC\StdDetail\iss\smas1.dgn

















SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

SMD(SLIP-1)-08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0579	02	014	FM 512
		DIST	COUNTY	SHEET NO.	
		PARIS	HUNT	172	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:02 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0519-02-014)\CADD\GN\08*TRAFFIC\StdDetail\1.smsd2.dgn



All dimensions are in english unless detailed otherwise.

SM RD SGN ASSM TY XXXX(1)XX(T) (* - See Note 12)

GENERAL NOTES:

1. SIGN SUPPORT # OF POSTS MAX. SIGN AREA

10 BWG	1	16 SF
10 BWG	2	32 SF
Sch 80	1	32 SF
Sch 80	2	64 SF
2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
3. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
4. Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
10. Additional route markers may be added vertically, provided the total sign area does not exceed the maximum allowable amount per Note 1.
11. Additional sign clamp required on the "T-bracket" post for 24 inch height signs. Place the clamp 3 inches above bottom of sign when possible.
12. Post open ends shall be fitted with Friction Caps.
13. Sign blanks shall be the sizes and shapes shown on the plans.

REQUIRED SUPPORT		
SIGN DESCRIPTION	SUPPORT	
Regulatory	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
Warning	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)
	48x60-inch signs	TY S80(1)XX(T)
	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)
	48x60-inch signs	TY S80(1)XX(T)
	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)
48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)	
Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)	

Friction caps may be manufactured from hot rolled or cold rolled steel sheets. The minimum sheet metal thickness shall be 24 gauge for all cap sizes. The rim edges shall be reasonably straight and smooth. Caps shall be sized and formed in such a manner as to produce a drive-on friction fit and have no tendency to rock when seated on the pipe. The depth shall be sufficient to give positive protection against entrance of rainwater. They shall be free of sharp creases or indentations and show no evidence of metal fracture. Caps shall have an electrodeposited coating of zinc in accordance with the requirements of ASTM B633 Class FE/ZN 8.






SIGN MOUNTING DETAILS
 SMALL ROADSIDE SIGNS
 TRIANGULAR SLIPBASE SYSTEM
 SMD(SLIP-2)-08



© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0579	02	014	FM 512
		DIST	COUNTY	SHEET NO.	
		PARIS	HUNT	173	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:21:02 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE_36-9IDP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08*TRAFFIC\StdDetail\smas3.dgn




Splices shall only be allowed behind the sign substrate.




Typical Sign Mount
 SM RD SGN ASSM TY S80(2)XX(IP-EXAL)
 * Additional stiffener placed at approximate center of signs when sign width is greater than 10'.



Detail E




Detail A



Detail D

EXTRUDED ALUMINUM SIGN WITH T BRACKET



Extruded Aluminum Sign With T Bracket

Use Extruded Alum. Windbeam as stiffeners See SMD (2-1) for additional details
 See Detail E for clamp installation

GENERAL NOTES:

- | SIGN SUPPORT | # OF POSTS | MAX. SIGN AREA |
|--------------|------------|----------------|
| 10 BWG | 1 | 16 SF |
| 10 BWG | 2 | 32 SF |
| Sch 80 | 1 | 32 SF |
| Sch 80 | 2 | 64 SF |
- The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
- Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
- Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
- For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
- When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
- Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
- Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
- Sign blanks shall be the sizes and shapes shown on the plans.
- Additional sign clamp required on the "T-bracket" post for 24 inch high signs. Place the clamp 3 inches above bottom of sign when possible.
- Post open ends shall be fitted with Friction Caps.

		REQUIRED SUPPORT	
		SIGN DESCRIPTION	SUPPORT
Regulatory	48-inch STOP sign (R1-1)		TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	60-inch YIELD sign (R1-2)		TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	48x16-inch ONE-WAY sign (R6-1)		TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	36x48, 48x36, and 48x48-inch signs		TY 10BWG(1)XX(T)
Warning	48x60-inch signs		TY S80(1)XX(T)
	48x48-inch signs (diamond or square)		TY 10BWG(1)XX(T)
	48x60-inch signs		TY S80(1)XX(T)
	48-inch Advance School X-ing sign (S1-1)		TY 10BWG(1)XX(T)
	48-inch School X-ing sign (S2-1)		TY 10BWG(1)XX(T)
	Large Arrow sign (W1-6 & W1-7)		TY 10BWG(1)XX(T)



**SIGN MOUNTING DETAILS
 SMALL ROADSIDE SIGNS
 TRIANGULAR SLIPBASE SYSTEM
 SMD(SLIP-3)-08**




© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0579	02	014	FM 512
		DIST	COUNTY		SHEET NO.
		PARIS	HUNT		174

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:03 PM
 FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail\tsr3-13.dgn

REQUIREMENTS FOR INDEPENDENT MOUNTED ROUTE SIGNS



SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	WHITE	TYPE A SHEETING
BACKGROUND	ALL OTHERS	TYPE B OR C SHEETING
LEGEND & BORDERS	WHITE	TYPE A SHEETING
LEGEND & BORDERS	BLACK	ACRYLIC NON-REFLECTIVE FILM
LEGEND & BORDERS	ALL OTHERS	TYPE B or C SHEETING



TYPICAL EXAMPLES

REQUIREMENTS FOR BLUE, BROWN & GREEN D AND I SERIES GUIDE SIGNS

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	ALL	TYPE B OR C SHEETING
LEGEND & BORDERS	WHITE	TYPE D SHEETING
LEGEND, SYMBOLS & BORDERS	ALL OTHERS	TYPE B OR C SHEETING



TYPICAL EXAMPLES

GENERAL NOTES

- Signs to be furnished shall be as detailed elsewhere in the plans and/or as shown on sign tabulation sheet. Standard sign designs and arrow dimensions can be found in the "Standard Highway Sign Designs for Texas" (SHSD).
- White legend shall use the Clearview Alphabet. The following Clearview fonts shall be used to replace the existing white Federal Highway Administration (FHWA) Standard Highway Alphabets, when not specified in the SHSD, or in the plans.

B	CV-1W
C	CV-2W
D	CV-3W
E	CV-4W
Emod	CV-5WR
F	CV-6W

- Route sign legend (ie. IH, US, SH and FM shields) shall use the Federal Highway Administration (FHWA) Standard Highway Alphabets B, C, D, E, Emod or F).
- Lateral spacing between letters and numerals shall conform with the SHSD, and any approved changes thereto. Lateral spacing of legend shall provide a balanced appearance when spacing is not shown.
- Independent mounted route sign with white or colored legend and borders shall be applied by screening process with transparent color ink, transparent colored overlay film to white background sheeting or cut-out white sheeting to colored background sheeting, or combination thereof. White legend, symbols and borders on all other signs shall be cut-out white sheeting applied to colored background sheeting.
- Information regarding borders and radii for signs is found in the "Standard Highway Sign Designs for Texas". Dimensions shown and described for borders and corner radii on parent sign are nominal. Borders may vary in width as much as 1/2 inch. Corner radii above 3 inches may vary in width as much as 1 inch. Borders and corner radii within a parent sign must be of matching widths. The sign area outside the corner radius should be trimmed or rounded.
- Sign substrate shall be any material that meets the Departmental Material Specification requirements of DMS-7110 or approved alternative.
- Mounting details of roadside signs are shown in the "SMD series" Standard Plan Sheets.

DEPARTMENTAL MATERIAL SPECIFICATIONS	
ALUMINUM SIGN BLANKS	DMS-7110
SIGN FACE MATERIALS	DMS-8300

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080
7.5 to 15	0.100
Greater than 15	0.125

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>



TYPICAL SIGN REQUIREMENTS

TSR(3) - 13


FILE:	tsr3-13.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
©TxDOT	October 2003	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0579	02	014	FM 512				
12-03	7-13	DIST	COUNTY	SHEET NO.					
9-08		PARIS	HUNT	175					

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:03 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail\tsr4-13.dgn

REQUIREMENTS FOR RED BACKGROUND REGULATORY SIGNS

(STOP, YIELD, DO NOT ENTER AND WRONG WAY SIGNS)



REQUIREMENTS FOR FOUR SPECIFIC SIGNS ONLY

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	WHITE	TYPE B OR C SHEETING
LEGEND & BORDERS	WHITE	TYPE B OR C SHEETING
LEGEND	RED	TYPE B OR C SHEETING

REQUIREMENTS FOR WHITE BACKGROUND REGULATORY SIGNS


(EXCLUDING STOP, YIELD, DO NOT ENTER AND WRONG WAY SIGNS)



TYPICAL EXAMPLES

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	WHITE	TYPE A SHEETING
BACKGROUND	ALL OTHERS	TYPE B OR C SHEETING
LEGEND, BORDERS AND SYMBOLS	BLACK	ACRYLIC NON-REFLECTIVE FILM
LEGEND, BORDERS AND SYMBOLS	ALL OTHER	TYPE B OR C SHEETING

REQUIREMENTS FOR WARNING SIGNS



TYPICAL EXAMPLES

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	FLOURESCENT YELLOW	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDERS	BLACK	ACRYLIC NON-REFLECTIVE FILM
LEGEND & SYMBOLS	ALL OTHER	TYPE B OR C SHEETING

REQUIREMENTS FOR SCHOOL SIGNS



TYPICAL EXAMPLES

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	WHITE	TYPE A SHEETING
BACKGROUND	FLOURESCENT YELLOW GREEN	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND, BORDERS AND SYMBOLS	BLACK	ACRYLIC NON-REFLECTIVE FILM
SYMBOLS	RED	TYPE B OR C SHEETING

GENERAL NOTES

- Signs to be furnished shall be as detailed elsewhere in the plans and/or as shown on sign tabulation sheet. Standard sign designs and arrow dimensions can be found in the "Standard Highway Sign Designs for Texas" (SHSD).
- Sign legend shall use the Federal Highway Administration (FHWA) Standard Highway Alphabets (B, C, D, E, Emod or F).
- Lateral spacing between letters and numerals shall conform with the SHSD, and any approved changes thereto. Lateral spacing of legend shall provide a balanced appearance when spacing is not shown.
- Black legend and borders shall be applied by screening process or cut-out acrylic non-reflective black film to background sheeting, or combination thereof.
- White legend and borders shall be applied by screening process with transparent colored ink, transparent colored overlay film to white background sheeting or cut-out white sheeting to colored background sheeting, or combination thereof.
- Colored legend shall be applied by screening process with transparent colored ink, transparent colored overlay film or colored sheeting to background sheeting, or combination thereof.
- Sign substrate shall be any material that meets the Departmental Material Specification requirements of DMS-7110 or approved alternative.
- Mounting details for roadside mounted signs are shown in the "SMD series" Standard Plan Sheets.

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080
7.5 to 15	0.100
Greater than 15	0.125


DEPARTMENTAL MATERIAL SPECIFICATIONS	
ALUMINUM SIGN BLANKS	DMS-7110
SIGN FACE MATERIALS	DMS-8300

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>


				<i>Traffic Operations Division Standard</i>	
<h2>TYPICAL SIGN REQUIREMENTS</h2>					
<h3>TSR(4) - 13</h3>					
FILE:	tsr4-13.dgn	DN:	TxDOT	CK:	TxDOT
© TxDOT	October 2003	CONT	SECT	JOB	HIGHWAY
REVISIONS		0579	02	014	FM 512
12-03	7-13	DIST	COUNTY	SHEET NO.	
9-08		PARIS	HUNT	176	

ARROW DETAILS


for Large Ground-Mounted and Overhead Guide Signs




Type A




Type B



E-3



E-4



Down Arrow

TYPE	LETTER SIZE	USE
A-1	10.67" U/L and 10" Caps	Single Lane Exits
A-2	13.33" U/L and 12" Caps	
A-3	16" & 20" U/L	
B-1	10.67" U/L and 10" Caps	Multiple Lane Exits
B-2	13.33" U/L and 12" Caps	
B-3	16" & 20" U/L	


CODE	USED ON SIGN NO.
E-3	E5-1aT
E-4	E5-1bT

NOTE

Arrow dimensions are shown in the "Standard Highway Sign Designs for Texas" manual.


The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

SIGN BLANK PUNCHING DETAILS FOR ATTACHMENTS WHEN SPECIFIED TO BE TYPE A ALUMINUM SIGNS (FOR MOUNTING TO GUIDE SIGN FACE)




INTERSTATE ROUTE MARKERS

A	C	D	E
36	21	15	1 1/2
48	28	20	1 3/4




U.S. ROUTE MARKERS

Sign Size	"Y"
24x24	2
30x24	3
36x36	3
45x36	4
48x48	4
60x48	5




STATE ROUTE MARKERS

No. of Digits	W	X
4	24	4
4	36	5
4	48	6
3	24	3
3	36	4
3	48	5



EXIT ONLY PANEL


MOUNTING DETAILS OF ATTACHMENTS TO GUIDE SIGN FACE ("EXIT ONLY" AND "LEFT EXIT" PANELS, ROUTE MARKERS AND OTHER ATTACHMENTS)




DIRECT APPLIED ATTACHMENT

NOTE:

- Sheeting for legend, symbols, and borders must be cut at panel joints.
- Direct applied attachment signs will be subsidiary to "Aluminum Signs" or "Fiberglass Signs".



SCREW ATTACHMENT




NUT/BOLT ATTACHMENT


NOTE:

Furnish Type A aluminum sign attachments only when specified in the plans. These signs will be paid for under "Aluminum Signs".

ARROW DETAILS for Destination Signs (Type D)



Standard arrow to be used with 6 inch letters.



Standard arrow to be used with 8 inch letters.



TYPICAL SIGN REQUIREMENTS

TSR (5) - 13

FILE: tsr5-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT October 2003	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
12-03 7-13	DIST	COUNTY	SHEET NO.	
9-08	PARIS	HUNT	177	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:03 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail\tsr5-13.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:04 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DPS101\WA2-TxDOT\Par1s\ProjectData\FM 512 (05179-02-014)\CADD\GN\08_TRAFFIC\StdDetail\dom1-20.dgn

REFLECTOR UNIT SIZES FOR DELINEATORS AND OBJECT MARKERS				DELINEATORS				D & OM DESCRIPTIVE CODES	
DEVICE	SIZE 1	SIZE 2	SIZE 3	SIZE 4	DEVICE	SINGLE	DOUBLE	INSTL DEL ASSM (D-XX)SZ X (XXXX)XXX (XX)	
SHEETING	Yellow, White or Red Type B or C reflective sheeting				SHEETING	Yellow, White or Red Type B or C Reflective Sheeting			
NOTE	1. Size 1 and 4 - Direct applied reflective sheeting for use on flexible post (flx). 2. Size 2 and 3 - For use on wing channel (wc) post only. Use approved metal, plastic or fiberglass backplate with 17/64" mounting holes.				POST TYPE	WC	YFLX, WFLX	WC	YFLX, WFLX
					MOUNT TYPE	GND	GND, SRF	GND	GND, SRF

OBJECT MARKERS								D & OM DESCRIPTIVE CODES		
DEVICE	Type 1 (OM-1)	Type 2 (OM-2)			Type 3 (OM-3)			Type 4 (OM-4)	INSTL OM ASSM (OM-XX) (XXXX)XXX (XX)	
		OM-1	OM-2X	OM-2Y	OM-2Z	OM-3L	OM-3R	OM-3C	OM-4	TYPE OF OBJECT MARKER 1, 2, 3, or 4 NUMBER OF REFLECTORS OR DIRECTION X = 3-Size 2 reflector units (Type 2 only) Y = 1-Size 3 reflector unit (Type 2 only) Z = 3-Size 1 or 1-Size 4 reflector unit(s) (Type 2 only) L = Left Side (Type 3 Object Marker only) R = Right Side (Type 3 Object Marker only) C = Center (Type 3 Object Marker only) TYPE OF POST WC = Wing Channel Post WFLX = White Flexible Post TWT = Thin Walled Tubing TYPE OF MOUNT GND = Embedded (drivable) SRF = Surface Mount WAS = Wedge Anchor Steel WAP = Wedge Anchor Plastic DIRECTION If Required BI = Bi-Directional
SHEETING	Yellow-Type B _{FL} or C _{FL} Sheeting	Yellow - Type B or C Sheeting			Alternating acrylic black and retroreflective yellow - Type B _{FL} or C _{FL} Sheeting			Red -Type B _{FL} or C _{FL} Sheeting	DEPARTMENTAL MATERIAL SPECIFICATIONS	
POST TYPE	TWT	WC	WC	WFLX	TWT			TWT	FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES) DMS-4400	
MOUNT TYPE	WAS, WAP	GND	GND	GND, SRF	WAS, WAP			WAS, WAP	SIGN FACE MATERIALS DMS-8300	
									DELINEATORS, OBJECT MARKERS AND BARRIER REFLECTORS DMS-8600	

BARRIER REFLECTORS (BRF)			CHEVRONS				ONE DIRECTION LARGE ARROW		NOTE:		
DEVICE	GF1	GF2	CTB	 W1-8				 W1-6		Delineator and object marker substrates and sign substrates shall be 0.080" Aluminum sign blank to conform to ASTM B-209 Alloy 6061-T6 or approved alternative.	
SHEETING	Yellow, White, Red			SIZE (W x L)	18"x 24" (Conventional)	24"x 30" (Conventional Oversize)	30"x 36" (Expressway)	36" x 48" (Freeway)	SIZE (W x L)	48" x 24" (Conventional)	60" x 30" (Expressway & Freeway)
NOTE	1. Barrier reflectors shall meet the requirements of DMS 8600. 2. Approved Barrier Reflectors are listed on the "Barrier Reflectors" Material Producer List at: www.txdot.gov.			MOUNTING HEIGHT	4'-0" or 7'-0"		7'-0" Only	MOUNTING HEIGHT	7'-0"		 DELINEATOR & OBJECT MARKER MATERIAL DESCRIPTION D & OM(1)-20
	1. Reflective sheeting shall have a minimum dimension of 3 inches and minimum surface area of 9 square inches.			NOTE	1. CHEVRON (W1-8) signs and ONE DIRECTION LARGE ARROW (W1-6) Signs shall be installed per Sign Mounting Details (SMD) Standard Sheets and paid under Item 644 (Small Roadside Sign Assemblies). 2. When there is a need to increase conspicuity, the Texas version of the ONE DIRECTION LARGE ARROW sign (W1-9T) may be used instead of the ONE DIRECTION LARGE ARROW (W1-6).						Traffic Safety Division Standard

FILE: dom1-20.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
© TxDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
10-09 3-15	DIST	COUNTY	SHEET NO.	
4-10 7-20	PARIS	HUNT	178	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:04 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DPS101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\08_TRAFFIC\StdDetail\1s\dom2-20.dgn

POST TYPE AND SUPPORT FOUNDATION DETAILS				TYPE OF BARRIER MOUNTS		
WING CHANNEL (WC)	FLEXIBLE POSTS (YFLX, WFLX)		WEDGE ANCHOR SYSTEMS		GUARD FENCE ATTACHMENT	
GND	GND	SRF	WAS	WAP	GF 1	
	EMBEDDED	SURFACE MOUNT	STEEL	PLASTIC	GF 2	
NOTES 1. Embedded Wing Channel (WC) post option may be used for Type 2 Object Markers and Delineators only. 2. 1.12 lbs/ft steel per ASTM A 1011 SS Gr. 50, or ASTM A499.		NOTES 1. See "Flexible Delineator and Object Marker Posts" Material Producer List for approved devices. 2. Install per manufacturer's recommendations. 3. Post length may vary to meet field conditions. 4. When using yellow delineators with flexible posts to separate opposing direction of travel, such as centerline or median use, the flexible posts shall be yellow.		NOTE 1. Install per manufacturer's recommendations.		
CONCRETE TRAFFIC BARRIER (CTB)						
GENERAL NOTES						
1. Place delineators on a section of roadway at a consistent distance from the edge of pavement. 2. Where a restriction prevents consistent placement from the pavement edge, place the affected object markers in line with the innermost edge of the obstruction. 3. When Type 2 object markers and delineators are more than 8'-0" from the edge of the pavement, it may not be possible to maintain a height of approximately 4'-0". If this is the case, place the object marker or delineator as close to the desired height as possible. 4. Install all delineators, object markers and barrier reflectors in accordance with the manufacturer's recommendation. 5. Barrier reflectors should be installed a minimum of 18 inches above the edge of the pavement surface. 6. Diagonal stripes on Type 3 object markers shall slope down toward the intended travel lane.						
TYPES 1,3, AND 4 OBJECT MARKERS AND CHEVRONS		CHEVRONS AND ONE DIRECTION LARGE ARROW SIGN		DELINEATORS AND TYPE 2 OBJECT MARKERS		
NOTE Mounting at 4 feet to the bottom of the chevron is permitted for chevrons that will not exceed a height of 6'-6" to the top of the chevron (sizes 24" x 30" and smaller)		NOTE Chevrons 30" x 36" and larger shall be mounted at a height of 7' to the bottom of the chevron. Chevron sign and ONE DIRECTION LARGE ARROW sign (W1-9T) shall be installed per SMD standard sheets and paid under item 644.		2'-0" to 8'-0" or in front of object being marked See general notes 1, 2 and 3.		

Texas Department of Transportation
Traffic Safety Division Standard

DELINEATOR & OBJECT MARKER INSTALLATION

D & OM(2)-20


FILE: dom2-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
10-09 3-15	DIST	COUNTY	SHEET NO.	
4-10 7-20	PARIS	HUNT	179	

DATE: 5/24/2023 6:21:04 PM
 FILE: Z:\Transportation\TXDOT\PS&E\STATEWIDE_36-91DPS101\WA2-TXDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail\dom3-20.dgn
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

MINIMUM WARNING DEVICES AT CURVES WITH ADVISORY SPEEDS

Amount by which Advisory Speed is less than Posted Speed	Curve Advisory Speed	
	Turn (30 MPH or less)	Curve (35 MPH or more)
5 MPH & 10 MPH	● RPMs	● RPMs
15 MPH & 20 MPH	● RPMs and One Direction Large Arrow sign	● RPMs and Chevrons; or ● RPMs and One Direction Large Arrow sign where geometric conditions or roadside obstacles prevent the installation of chevrons.
25 MPH & more	● RPMs and Chevrons; or ● RPMs and One Direction Large Arrow sign where geometric conditions or roadside obstacles prevent the installation of chevrons	● RPMs and Chevrons


SUGGESTED SPACING FOR DELINEATORS ON HORIZONTAL CURVES



NOTE

ONE DIRECTION LARGE ARROW (W1-6) sign should be located at approximately and perpendicular to the extension of the centerline of the tangent section of approach lane.

SUGGESTED SPACING FOR CHEVRONS ON HORIZONTAL CURVES



NOTE

At least one chevron pair is installed beyond the point of tangent in tangent section.

DELINEATOR AND CHEVRON SPACING

WHEN DEGREE OF CURVE OR RADIUS IS KNOWN				
Degree of Curve	FEET			
	Radius of Curve	Spacing in Curve	Spacing in Straightaway	Chevron Spacing in Curve
		A	2A	B
1	5730	225	450	—
2	2865	160	320	—
3	1910	130	260	200
4	1433	110	220	160
5	1146	100	200	160
6	955	90	180	160
7	819	85	170	160
8	716	75	150	160
9	637	75	150	120
10	573	70	140	120
11	521	65	130	120
12	478	60	120	120
13	441	60	120	120
14	409	55	110	80
15	382	55	110	80
16	358	55	110	80
19	302	50	100	80
23	249	40	80	80
29	198	35	70	40
38	151	30	60	40
57	101	20	40	40

Curve delineator approach and departure spacing should include 3 delineators spaced at 2A. This spacing should be used during design preparation or when the degree of curve is known.

DELINEATOR AND CHEVRON SPACING

WHEN DEGREE OF CURVE OR RADIUS IS NOT KNOWN			
Advisory Speed (MPH)	Spacing in Curve	Spacing in Straightaway	Chevron Spacing in Curve
	A	2xA	B
65	130	260	200
60	110	220	160
55	100	200	160
50	85	170	160
45	75	150	120
40	70	140	120
35	60	120	120
30	55	110	80
25	50	100	80
20	40	80	80
15	35	70	40

If the degree of curve is not known, delineator spacing may be determined based on the Advisory Speed of the curve. Use the delineator curve spacing for each Advisory Speed (MPH).

DELINEATOR AND OBJECT MARKER APPLICATION AND SPACING

CONDITION	REQUIRED TREATMENT	MINIMUM SPACING
Frwy./Exp. Tangent	RPMs	See PM-series and FPM-series standard sheets
Frwy./Exp. Curve	Single delineators on right side	See delineator spacing table
Frwy/Exp. Ramp	Single delineators on at least one side of ramp (should be on outside of curves) (see Detail 3 on D&OM(4))	100 feet on ramp tangents Use delineator spacing table for ramp curves ("straightway spacing" does not apply to ramp curves)
Acceleration/Deceleration Lane	Double delineators (see Detail 3 on D&OM(4))	100 feet (See Detail 3 on D & OM (4))
Truck Escape Ramp	Single red delineators on both sides	50 feet
Bridge Rail (steel or concrete) and Metal Beam Guard Fence	Bi-Directional Delineators when undivided with one lane each direction Single Delineators when multiple lanes each direction	Equal spacing (100' max) but not less than 3 delineators
Concrete Traffic Barrier (CTB) or Steel Traffic Barrier	Barrier reflectors matching the color of the edge line	Equal spacing 100' max
Cable Barrier	Reflectors matching the color of the edge line	Every 5th cable barrier post (up to 100' max)
Guard Rail Terminus/Impact Head	Divided highway - Object marker on approach end Undivided 2-lane highways - Object marker on approach and departure end	Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM (5) and D & OM (6)
Bridges with no Approach Rail	Type 3 Object Marker (OM-3) at end of rail and 3 single delineators approaching rail	See D & OM(5)
Reduced Width Approaches to Bridge Rail	Type 2 and Type 3 Object Markers (OM-3) and 3 single delineators approaching bridge	Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM (5)
Culverts without MBGF	Type 2 Object Markers	See Detail 2 on D & OM(4)
Crossovers	Double yellow delineators and RPMs	See Detail 1 on D & OM (4)
Pavement Narrowing (lane merge) on Freeways/Expressway	Single delineators adjacent to affected lane for full length of transition	100 feet

NOTES

- Unless indicated otherwise, the delineator or barrier reflector color shall conform to the color of the pavement edge line on the side of the road where the delineators or barrier reflectors are placed.
- Barrier reflectors may be used to replace required delineators.
- Single red delineators may be mounted on the back side of delineator posts for wrong way driver applications

LEGEND	
	Bi-directional Delineator
	Delineator
	Sign

Texas Department of Transportation
Traffic Safety Division Standard

DELINEATOR & OBJECT MARKER PLACEMENT DETAILS


D & OM(3)-20

FILE: dom3-20.dgn	DN: TXDOT	CK: TXDOT	OW: TXDOT	CR: TXDOT
© TXDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS		0579 02	014	FM 512
3-15 8-15	DIST	COUNTY	SHEET NO.	
8-15 7-20	PARIS	HUNT	180	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023 6:21:05 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\08_TRAFFIC\StdDetail\dom4-20.dgn

CROSSOVERS




DETAIL 1

FOR CULVERTS WITHOUT MBGF




DETAIL 2

FREEWAY DELINEATION FOR RAMPS AND ACCELERATION/DECELERATION LANES




DETAIL 3

TYPICAL APPLICATION OF DEAD END BARRICADE



DETAIL 4

TYPICAL DEAD END BARRICADE INSTALLATION



NOTES

- Barricade striping shall be red and white reflective sheeting for all permanent road closures.
- Barricade striping is red and white sloping toward the center of the roadway.
- Type 3 Barricade Supports should be anchored to soil or pavement as described in compliant Work Zone Traffic Control Devices List, section D.2.f and D.2.g.

DETAIL 5

LEGEND	
	Bidirectional Delineator
	Delineator
	OM-3
	Barricade
	Sign
	OM-2
	Double Delineator




DELINEATOR & OBJECT MARKER PLACEMENT DETAILS

D & OM(4) -20

FILE: dom4-20.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
© TxDOT August 2004	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
3-15	DIST	COUNTY	SHEET NO.	
7-20	PARIS	HUNT	181	


**TWO-WAY, TWO LANE ROADWAY
WITH REDUCED WIDTH APPROACH RAIL**



NOTE:

1. Terminal ends require reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end.


**TWO-WAY, TWO LANE ROADWAY
WITH METAL BEAM GUARD FENCE (MBGF)**



NOTE:

1. Terminal ends require reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end.

**TWO-WAY, TWO LANE ROADWAY
BRIDGE WITH NO APPROACH RAIL**



LEGEND

	Bidirectional Delineator
	Delineator
	OM-3
	OM-2
	Terminal End
	Traffic Flow



**DELINEATOR &
OBJECT MARKER
PLACEMENT DETAILS**

D & OM(5) - 20








FILE: dom5-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
©TxDOT August 2015	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
7-20	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	182	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:05 PM
FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail\dom5-20.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:05 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail\domvia-20.dgn




OBJECT MARKERS SMALLER THAN 3 FT²

NOTES

- Object Markers shall conform to the Texas MUTCD and meet the color and reflectivity requirement of Department Material Specification DMS 8300. Background shall be yellow reflective sheeting (Type B or C) and Chevron shall be black.
- Object Markers may be fabricated from adhesive backed reflective sheeting applied directly to guardrail end treatment, or applied directly to an "end cap" as per the manufacturer's recommendation. Direct applied sheeting shall provide a smooth surface and have no wrinkles, air bubbles, cuts or tears. A radius at the corners is not required for direct applied sheeting.
- Object Marker size may be reduced to fit smaller devices. Width of alternating black and yellow stripes are typically 6". Object Markers smaller than 3ft may have reduced width stripes of a minimum of 2 1/4".
- Pop rivets, screws, or nuts and bolts may be used to attach object markers and reflectors. Holes, slots or other openings may be cut or drilled through object markers to allow cable or other attachments.
- Object Marker at nose of attenuator is subsidiary to the attenuator.
- See D & OM (1-4) for required barrier reflectors.


NOTES

- Spacing should be adjusted to attach through centerline of drum, per attenuator manufacturer's recommendation, or as directed by the Engineer.
- Mounting should be flush with top of attenuator. Minimum size 96" x 24".




DELINEATOR & OBJECT MARKER FOR VEHICLE IMPACT ATTENUATORS D & OM(VIA) -20			
FILE: domvia20.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT
© TxDOT December 1989	CONT	SECT	JOB
REVISIONS		0579 02	014
4-92 8-04	DIST	COUNTY	SHEET NO.
8-95 3-15	PARIS	HUNT	183
4-98 7-20			
20G			

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 DATE: 5/24/2023 6:21:05 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\GN\08_TRAFFIC\StdDetail.s\pml-22.dgn



**EDGE LINE AND LANE LINES
ONE-WAY ROADWAY
WITH OR WITHOUT SHOULDERS**




**TYPICAL TWO-LANE, TWO-WAY PAVEMENT
MARKINGS THROUGH INTERSECTIONS**


- GENERAL NOTES**
- Edge line striping shall be as shown in the plans or as directed by the Engineer. The edge line should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement raveling or other conditions. Edge lines are not required in curb and gutter sections of roadways.
 - The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the center of edge line to the center of edge line of a two lane roadway.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




**CENTERLINE AND LANE LINES
FOUR LANE TWO-WAY ROADWAY
WITH OR WITHOUT SHOULDERS**




* 2" minimum for restripe projects when approved by the Engineer.
 ** 8" minimum for restripe projects when approved by the Engineer.




**TYPICAL MULTI-LANE, TWO-WAY PAVEMENT
MARKINGS THROUGH INTERSECTIONS**



**TWO LANE TWO-WAY ROADWAY
WITH OR WITHOUT SHOULDERS**




* 2" minimum for restripe projects when approved by the Engineer.



YIELD LINES

For posted speed on road being marked equal to or greater than 45 MPH.




NOTE: Traveled way is exclusive of shoulder widths. Refer to General Note 2 for additional details.

**GUIDE FOR PLACEMENT OF STOP LINES,
EDGE LINE & CENTERLINE**
Based on Traveled Way and Pavement Widths for Undivided Roadways

NOTES

- Where divided highways are separated by median widths of 30 feet or more, median openings shall be signed as two separate intersections. Each median opening has two width measurements, with one measurement for each approach. The narrow median width will be the controlling width to determine if signs are required. Yield signs are the typical intersection control. Stop signs and stop bars are optional as determined by the Engineer.
- Install median striping (double yellow centerlines and stop lines/yield lines) when a 50' or greater median centerline can be placed. Stop lines shall only be used with stop signs. Yield lines shall only be used with yield signs.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.



FOUR LANE DIVIDED ROADWAY CROSSOVERS

Texas Department of Transportation
 Traffic Safety Division Standard

**TYPICAL STANDARD
PAVEMENT MARKINGS**


PM(1) - 22

FILE: pml-22.dgn	DN:	CK:	DW:	CK:
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
11-78 8-00 6-20	DIST	COUNTY	SHEET NO.	
8-95 3-03 12-22	PARIS	HUNT	184	
5-00 2-12				


22A

REFLECTIVE RAISED PAVEMENT MARKERS FOR VEHICLE POSITIONING GUIDANCE


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DPS101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\08_TRAFFIC\StdDetail\15\pm2-22.dgn



CENTERLINE FOR ALL TWO LANE TWO-WAY ROADWAYS




**CENTERLINE & LANE LINES
FOR FOUR LANE TWO-WAY ROADWAYS**




DETAIL "A"

DETAIL "B"

DETAIL "C"




CENTERLINE AND LANE LINES FOR TWO-WAY LEFT TURN LANE




LANE LINES FOR ONE-WAY ROADWAY (NON-FREEWAY FACILITIES)

Raised pavement markers Type II-C-R shall have clear face toward normal traffic and red face toward wrong-way traffic.
 See Note 3.



CENTER OR EDGE LINE (see note 1)


BROKEN LANE LINE



**REFLECTORIZED PROFILE
PATTERN DETAIL**

USING REFLECTIVE PROFILE PAVEMENT MARKINGS

6" EDGE LINE, 6" CENTERLINE
OR 6" LANE LINE



A quick field check for the thickness of base line and profile marking is approximately equal to a stack of 5 quarters to a maximum height of 7 quarters.

NOTES


1. Edge lines should typically be 6" wide and the materials shall be specified in the plans.
2. Profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.

GENERAL NOTES


1. All raised pavement markers placed along broken lines shall be placed in line with and midway between the stripes.
2. On concrete pavements the raised pavement markers should be placed to one side of the longitudinal joints.
3. Use raised pavement marker Type I-C with undivided roadways, flush medians and two way left turn lanes. Use raised pavement marker Type II-C-R with divided highways and raised medians.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



Type I (Top View)



Type II (Top View)



SECTION A

RAISED PAVEMENT MARKERS



**POSITION GUIDANCE USING
RAISED MARKERS
REFLECTORIZED PROFILE
MARKINGS
PM(2) - 22**


FILE: pm2-22.dgn	DN:	CK:	DW:	CK:
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
4-77 8-00 6-20	DIST	COUNTY	SHEET NO.	
4-92 2-10 12-22	PARIS	HUNT	185	
5-00 2-12				

DATE: 5/24/2023 6:21:06 PM
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91DPS101\WA2-TxDOT_Paris\ProjectData\FM 512 (0579-02-014)\CADD\08_TRAFFIC\StdDetail\15\pm2-22.dgn


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:06 PM
FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT\Paris\ProjectData\FM 512 (0579-02-01-14)\CADD\DCN\08_TRAFF IC\StdDetail\rs(3)-23.dgn

MULTILANE UNDIVIDED HIGHWAY WITH SHOULDER



CENTERLINE RUMBLE STRIPS



GENERAL NOTES


1. This standard sheet provides guidelines for installing centerline rumble strips on multilane undivided highways.
2. Centerline and edge line rumble strips or profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.
3. Milled rumble strips are preferred when adequate pavement depth is available. If pavement thickness is less than 2 inches, milled rumble strips shall not be used. Rumble strips shall not be milled or depressed into bridge decks.
4. See dimensions for milled rumble strips. Other shapes and dimensions may be used if approved by the Traffic Safety Division.
5. Breaks in milled centerline rumble strips shall occur at least 50 feet and no more than 150 feet in advance of bridges, railroad crossing, intersections or driveways with high usage of large trucks.
6. Use standard sheet PM(2) for positioning, dimensioning, and spacing of all reflective raised pavement markers, pavement markings and profile markings.
7. Consideration should be given to noise levels when centerline rumble strips are to be installed near residential areas, schools, churches, etc. A 3/8 inch deep (minimum) milled rumble strip may be considered in these areas.
8. Pavement markings must be applied over milled centerline rumble strips for normal centerline spacing. For wider medians, specify in the plans the exact placement of the rumble strips. Place the rumble strips under each centerline marking or centered in the middle of the median.

WHEN INSTALLING CENTERLINE RUMBLE STRIPS:


9. Raised rumble strips consisting of non-reflective raised traffic buttons may be used. Non-reflective raised traffic buttons can be affixed to asphalt or concrete with bitumen or adhesives, as per manufacturer's recommendations.
10. When using non-reflective raised traffic buttons as a centerline rumble strip, the button shall be placed adjacent to the pavement marking delineating the centerline. The color of the button should be yellow for a continuous no passing roadway. The button will be paid for under Item 672, "Raised Pavement Markers." Non-reflective traffic buttons must meet the requirements of DMS-4300.
11. Consideration shall be given to bicyclists. See RS(6).

WHEN INSTALLING EDGE LINE RUMBLE STRIPS WITH OR WITHOUT CENTERLINE RUMBLE STRIPS ON UNDIVIDED HIGHWAYS:

12. See standard sheet RS(2).



Texas Department of Transportation



Traffic Safety Division Standard

CENTERLINE RUMBLE STRIPS ON MULTILANE UNDIVIDED HIGHWAYS


RS(3)-23

FILE: rs(3)-23.dgn	DWG: TxDOT	CHK: TxDOT	DES: TxDOT	CRK: TxDOT
© TxDOT	January 2023	CONT	SECT	JOB
		0579	02	014
10-13	REVISIONS			HIGHWAY
1-23				FM 512
	DIST		COUNTY	SHEET NO.
	PARIS		HUNT	186


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023 6:21:06 PM
FILE: Z:\Transportation\TxDOT\STATEWIDE\36-91DP5101\WA2-TxDOT\Projects\DOT\PS&E\STATEWIDE_36-91DP5101\WA2-TxDOT\PS&E\STATEWIDE_36-91DP5101\TRAFFIC\StdDetail\rs(4)-23.dgn


TWO LANE TWO-WAY HIGHWAYS




CENTERLINE RUMBLE STRIPS




PROFILE VIEW




PROFILE VIEW



PROFILE VIEW




PROFILE VIEW




PLAN VIEW
OPTION 1

MILLED CENTERLINE RUMBLE STRIPS




PLAN VIEW
OPTION 2

RAISED CENTERLINE RUMBLE STRIPS



PLAN VIEW
OPTION 3

PREFORMED THERMOPLASTIC RUMBLE STRIPS



PLAN VIEW
OPTION 4

PROFILE CENTERLINE MARKINGS AND PREFORMED THERMOPLASTIC RUMBLE STRIPS

GENERAL NOTES

1. This standard sheet provides guidelines for installing centerline rumble strips on two-lane highways with or without shoulders.
2. Centerline and edge line rumble strips or profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.
3. Milled rumble strips are preferred when adequate pavement depth is available. If pavement thickness is less than 2 inches, milled rumble strips shall not be used. Rumble strips shall not be milled or depressed into bridge decks.
4. See dimensions for milled rumble strips. Other shapes and dimensions may be used if approved by the Traffic Safety Division.
5. Breaks in milled centerline rumble strips shall occur at least 50 feet and no more than 150 feet in advance of bridges, railroad crossings, intersections or driveways with high usage of large trucks.
6. Use standard sheet PM(2) for positioning, dimensioning, and spacing of all reflective raised pavement markers, pavement markings and profile markings.
7. Consideration should be given to noise levels when centerline rumble strips are to be installed near residential areas, schools, churches, etc. A 3/8 inch deep (minimum) milled rumble strip may be considered in these areas.
8. Pavement markings must be applied over milled centerline rumble strips.

WHEN INSTALLING CENTERLINE RUMBLE STRIPS:

9. Raised rumble strips consisting of non-reflective raised traffic buttons may be used. Non-reflective raised traffic buttons can be affixed to asphalt or concrete with bitumen or adhesives, as per manufacturer's recommendations.
10. When using non-reflective raised traffic buttons as a centerline rumble strip, the button shall be placed adjacent to the pavement marking delineating the centerline. The buttons will be paid for under Item 672, "Raised Pavement Markers." Non-reflective traffic buttons must meet the requirements of DMS-4300.
11. The color of the button should be yellow for a continuous no passing roadway. Black buttons should be used in areas where passing is allowed.
12. Consideration shall be given to bicyclists. See RS(6).

WHEN INSTALLING EDGE LINE RUMBLE STRIPS WITH OR WITHOUT CENTERLINE RUMBLE STRIPS ON UNDIVIDED HIGHWAYS:

13. See standard sheet RS(2).

<p>CENTERLINE RUMBLE STRIPS ON TWO LANE TWO-WAY HIGHWAYS RS(4)-23</p>			
FILE: rs(4)-23.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT	January 2023	CONT	SECT
REVISIONS	0579	02	014
10-13 1-23	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	187

5/24/2023 6:21:07 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Par1s\ProjectData\FM 512 (0579-02-014)\CADD\DGN\09-ENVIRONMENTAL\swp3b22.dgn

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with the TPDES Construction General Permit TXR150000 (CGP). The Texas Department of Transportation (TxDOT) ensures that project specifications include adequate best management practices (BMPs) for this project.

For all projects with any soil disturbing activities, TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office. If no field office is available, then this SWP3 shall be kept in the appropriate TxDOT Area Office.

This SWP3 is consistent with requirements specified in applicable stormwater plans and the projects environmental permits, issues, and commitments (EPICs). A copy of the CGP is included in Attachment 2.12 of the SWP3 binder.

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

0579-02-014

1.2 PROJECT LIMITS:

From: SH 34

To: FM 118

1.3 PROJECT COORDINATES:

BEGIN: (Lat) 33.362623, (Long) -96.070109

END: (Lat) 33.265105, (Long) -96.009922

1.4 TOTAL PROJECT AREA (Acres): 104.86

1.5 TOTAL AREA TO BE DISTURBED (Acres): 45.55

1.6 NATURE OF CONSTRUCTION ACTIVITY:

RECONSTRUCTION OF EXISTING ROADWAY CONSISTING OF REWORKING BASE, GEOGRID, FLEXBASE, SURFACE TREATMENTS AND STRUCTURES

1.7 MAJOR SOIL TYPES:

Soil Type	Description
CROCKETT LOAM	1 TO 3 PERCENT SLOPES, ERODED
LESON CLAY	1 TO 3 PERCENT SLOPES
WILSON SILT LOAM	0 TO 1 PERCENT SLOPES

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.5.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures
- Other: _____
- Other: _____
- Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Other: _____
- Other: _____
- Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody
OYSTER CREEK TO UPPER SULPHUR RIVER	CLASSIFIED IMPAIRED SEGMENT 0306
TURKEY CREEK TO UPPER SULPHUR RIVER	CLASSIFIED IMPAIRED SEGMENT 0306
RAYS CREEK TO UPPER SULPHUR RIVER	CLASSIFIED IMPAIRED SEGMENT 0306

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____
- Other: _____
- Other: _____

1.14 LOCAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) OPERATOR COORDINATION:

MS4 Entity



Paul A. Warden, P.E. 5/24/2023

STORMWATER POLLUTION PREVENTION PLAN (SWP3)



Sheet 1 of 2

FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
				188
STATE	STATE DIST.	COUNTY		
TEXAS	PARIS	HUNT		
CONT.	SECT.	JOB	HIGHWAY NO.	
0579	02	014	FM 512	

5/24/2023 6:21:07 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Par1s\ProjectData\FM 512 (0579-02-014)\CADD\DCN\09-ENVIRONMENTAL\swp3b22.dgn

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: _____
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

Sediment control BMPs requiring design capacity calculations (See SWP3 Attachment 1.3.):

T / P

- Sediment Trap
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Sedimentation Basin
 - Not required (<10 acres disturbed)
 - Required (>10 acres) and implemented.
 - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
 - 3,600 cubic feet of storage per acre drained
- Required (>10 acres), but not feasible due to:
 - Available area/Site geometry
 - Site slope/Drainage patterns
 - Site soils/Geotechnical factors
 - Public safety
 - Other: _____

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To
PERMANENT SEEDING	0+50	508+53

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To
BETWEEN ROW AND WINDROWED TOPSOIL BERM	0+50	508+53

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

2.8 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3 .

2.9 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3.



Paul A. Warden, P.E. 5/24/2023

STORMWATER POLLUTION PREVENTION PLAN (SWP3)



Sheet 2 of 2

Texas Department of Transportation

FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
				189
STATE	STATE DIST.	COUNTY		
TEXAS	PARIS	HUNT		
CONT.	SECT.	JOB	HIGHWAY NO.	
0579	02	014	FM 512	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\APS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Part1\ProjectData\FM 512 (0579-02-014)\CADD\09-ENVIRONMENTAL\epic.dgn

I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

-
- No Action Required Required Action

Action No.

- Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000
- Comply with the SW3P and revise when necessary to control pollution or required by the Engineer.
- Post Construction Site Notice (CSN) with SW3P information on or near the site, accessible to the public and TCEQ, EPA or other inspectors.
- When Contractor project specific locations (PSL's) increase disturbed soil area to 5 acres or more, submit NOI to TCEQ and the Engineer.

II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required
- Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
- Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
- Individual 404 Permit Required
- Other Nationwide Permit Required: NWP# _____

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

-
-
-
-

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

Best Management Practices:

Erosion	Sedimentation	Post-Construction TSS
<input checked="" type="checkbox"/> Temporary Vegetation	<input checked="" type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input checked="" type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input checked="" type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	<input type="checkbox"/> Grassy Swales

III. CULTURAL RESOURCES

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

- No Action Required Required Action

Action No.

-
-
-
-

IV. VEGETATION RESOURCES

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

- No Action Required Required Action

Action No.

-
-
-
-

V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.

- No Action Required Required Action

Action No.

-
-
-
-

If any of the listed species are observed, cease work in the immediate area, do not disturb species or habitat and contact the Engineer immediately. The work may not remove active nests from bridges and other structures during nesting season of the birds associated with the nests. If caves or sinkholes are discovered, cease work in the immediate area, and contact the Engineer immediately.

LIST OF ABBREVIATIONS

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SW3P: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NWP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used. Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act. Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- * Dead or distressed vegetation (not identified as normal)
- * Trash piles, drums, canister, barrels, etc.
- * Undesirable smells or odors
- * Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

- Yes No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

- Yes No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

- No Action Required Required Action

Action No.

-
-
-


VII. OTHER ENVIRONMENTAL ISSUES


(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required Required Action

Action No.


-
-
-

		Design Division Standard		
<h2 style="margin: 0;">ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS</h2> <h1 style="margin: 0;">EPIC</h1>				
FILE: epic.dgn	DN: TxDOT	CK: RG	DW: VP	CK: AR
©TxDOT: February 2015	CONT	SECT	JOB	HIGHWAY
12-12-2011 (DS) REVISIONS	0579	02	014	FM 512
05-07-14 ADDED NOTE SECTION IV.	DIST	COUNTY	SHEET NO.	
01-23-2015 SECTION I (CHANGED ITEM 1122 TO ITEM 506, ADDED GRASSY SWALES.	PARIS	HUNT	190	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM





IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512
**EROSION CONTROL
MEASURES LAYOUT**


SHEET 1 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	191



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 579412023


IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



FM 512
EROSION CONTROL MEASURES LAYOUT


SHEET 2 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	192
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
EROSION CONTROL
MEASURES LAYOUT


SHEET 3 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	193
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
EROSION CONTROL
MEASURES LAYOUT



SHEET 4 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	194
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 5 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	195
CONTROL	SECTION	JOB	
0579	02	014	



- LEGEND:**
- SEDIMENT CONTROL FENCE EST. @ 15 LF
 - ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - EROSION CONTROL LOGS EST. @ 10 LF
 - WATER FLOW DIRECTION
 - CULVERT
 - BERM





IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
EROSION CONTROL
MEASURES LAYOUT**


SHEET 6 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	196
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
EROSION CONTROL MEASURES LAYOUT


SHEET 7 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	197
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
EROSION CONTROL
MEASURES LAYOUT**


SHEET 8 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	198



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




**FM 512
EROSION CONTROL
MEASURES LAYOUT**


SHEET 9 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	199
CONTROL	SECTION	JOB	
0579	02	014	

5/24/2023 6:21:17 PM Z:\Transportation\TXDOT\PS&E\STATEWIDE\36-9IDP5101\W42-TXDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\09_ENVIRONMENTAL\FM512_EN_SW3P_10.dgn



- LEGEND:**
- SCF SEDIMENT CONTROL FENCE EST. @ 15 LF
 - RFD2 ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - ECL EROSION CONTROL LOGS EST. @ 10 LF
 - ← WATER FLOW DIRECTION
 - CULVERT
 - BERM




IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
EROSION CONTROL
MEASURES LAYOUT**



SHEET 10 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	200
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023





IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
EROSION CONTROL MEASURES LAYOUT

SHEET 11 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	201
CONTROL	SECTION	JOB	
0579	02	014	



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 12 OF 26




STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	202

MATCH LINE STA 239+00

MATCH LINE STA 249+00



- LEGEND:**
- (SCF)— SEDIMENT CONTROL FENCE EST. @ 15 LF
 - (RFD2)— ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - (ECL)— EROSION CONTROL LOGS EST. @ 10 LF
 - ← WATER FLOW DIRECTION
 - - - - - CULVERT
 - ===== BERM




IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
EROSION CONTROL
MEASURES LAYOUT**



SHEET 13 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	203



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




FM 512
EROSION CONTROL
MEASURES LAYOUT

SHEET 14 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	204
CONTROL	SECTION	JOB	
0579	02	014	



- LEGEND:**
- SCF SEDIMENT CONTROL FENCE EST. @ 15 LF
 - RFD2 ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - ECL EROSION CONTROL LOGS EST. @ 10 LF
 - ← WATER FLOW DIRECTION
 - CULVERT
 - BERM






IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
(210) 448-1800
FIRM # F-6825



**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 15 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	205






IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 16 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	206




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825





FM 512
EROSION CONTROL
MEASURES LAYOUT

SHEET 17 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	207
CONTROL	SECTION	JOB	
0579	02	014	



- LEGEND:**
- SCF SEDIMENT CONTROL FENCE EST. @ 15 LF
 - RFDZ ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - ECL EROSION CONTROL LOGS EST. @ 10 LF
 - ← WATER FLOW DIRECTION
 - CULVERT
 - == BERM



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 18 OF 26


STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	208

MATCH LINE STA 359+00

MATCH LINE STA 369+00



MATCH LINE STA 369+00

MATCH LINE STA 379+00



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM




IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




FM 512
**EROSION CONTROL
MEASURES LAYOUT**

SHEET 19 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	209



- LEGEND:**
- SEDIMENT CONTROL FENCE EST. @ 15 LF
 - ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - EROSION CONTROL LOGS EST. @ 10 LF
 - WATER FLOW DIRECTION
 - CULVERT
 - BERM



IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825






**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 20 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	210
CONTROL	SECTION	JOB	
0579	02	014	

- LEGEND:**
- SCF SEDIMENT CONTROL FENCE EST. @ 15 LF
 - RFD2 ROCK FILTER DAM (TY-2) EST. @ 15 LF
 - ECL EROSION CONTROL LOGS EST. @ 10 LF
 - ← WATER FLOW DIRECTION
 - CULVERT
 - BERM





IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
EROSION CONTROL
MEASURES LAYOUT**


SHEET 21 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	211



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM







IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 22 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	212
CONTROL	SECTION	JOB	
0579	02	014	



Paul A. Warden, P.E. 5/24/2023


IDCUS 8632 Fredericksburg Rd. Suite 200 San Antonio, Tx. 78240 (210) 448-1800 FIRM # F-6825
PLANNERS ENGINEERS MANAGERS



**FM 512
EROSION CONTROL
MEASURES LAYOUT**


SHEET 23 OF 26

STATE	DISTRICT	COUNTY	HIGHWAY NO
TEXAS	PARIS	HUNT	FM 512
CONTROL	SECTION	JOB	SHEET NO
0579	02	014	213



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM





IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825



FM 512
EROSION CONTROL
MEASURES LAYOUT


SHEET 24 OF 26

			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	214
CONTROL	SECTION	JOB	
0579	02	014	



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




**FM 512
EROSION CONTROL
MEASURES LAYOUT**

SHEET 25 OF 26


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	215
CONTROL	SECTION	JOB	
0579	02	014	

MATCH LINE STA 499+00



LEGEND:

- SEDIMENT CONTROL FENCE EST. @ 15 LF
- ROCK FILTER DAM (TY-2) EST. @ 15 LF
- EROSION CONTROL LOGS EST. @ 10 LF
- WATER FLOW DIRECTION
- CULVERT
- BERM



Paul A. Warden, P.E. 5/24/2023

IDCUS 8632 Fredericksburg Rd.
Suite 200
San Antonio, Tx. 78240
PLANNERS ENGINEERS MANAGERS (210) 448-1800
FIRM # F-6825




FM 512
EROSION CONTROL MEASURES LAYOUT

SHEET 26 OF 26


			HIGHWAY NO
			FM 512
STATE	DISTRICT	COUNTY	SHEET NO
TEXAS	PARIS	HUNT	216
CONTROL	SECTION	JOB	
0579	02	014	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WAZ-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\DGN\09_ENVIRONMENTAL\StdDetail\ec116.dgn



TEMPORARY SEDIMENT CONTROL FENCE
 SCF




HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

SEDIMENT CONTROL FENCE USAGE GUIDELINES


A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT². Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.



GENERAL NOTES


1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.



				Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING					
EC(1) - 16					
FILE: ec116	DN: TxDOT	CK: KM	DW: VP	DN/CK: LS	
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0579	02	014	FM 512	
	DIST	COUNTY	SHEET NO.		
	PARIS	HUNT	217		


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Parish\ProjectData\FM 512 (0579-02-014)\CADD\GDN\09-ENVIRONMENTAL\StdDetail\ec216.dgn




FILTER DAM AT TOE OF SLOPE


RFD1




PLAN VIEW



"V" SHAPE PLAN VIEW




SECTION B-B




TYPE 4 (SACK GABIONS)

RFD4




SECTION A-A




FILTER DAM AT SEDIMENT TRAP

RFD1 OR RFD2



PROFILE



SECTION C-C

ROCK FILTER DAM USAGE GUIDELINES

Rock Filter Dams should be constructed downstream from disturbed areas to intercept sediment from overland runoff and/or concentrated flow. The dams should be sized to filter a maximum flow through rate of 60 GPM/FT² of cross sectional area. A 2 year storm frequency may be used to calculate the flow rate.


Type 1 (18" high with no wire mesh) (3" to 6" aggregate): Type 1 may be used at the toe of slopes, around inlets, in small ditches, and at dike or swale outlets. This type of dam is recommended to control erosion from a drainage area of 5 acres or less. Type 1 may not be used in concentrated high velocity flows (approximately 8 Ft/Sec or more) in which aggregate wash out may occur. Sandbags may be used at the embedded foundation (4" deep min.) for better filtering efficiency of low flows if called for on the plans or directed by the Engineer.

Type 2 (18" high with wire mesh) (3" to 6" aggregate): Type 2 may be used in ditches and at dike or swale outlets.

Type 3 (36" high with wire mesh) (4" to 8" aggregate): Type 3 may be used in stream flow and should be secured to the stream bed.

Type 4 (Sack gabions) (3" to 6" aggregate): Type 4 May be used in ditches and smaller channels to form an erosion control dam.

Type 5: Provide rock filter dams as shown on plans.



FILTER DAM AT CHANNEL SECTIONS

RFD1 OR RFD2 OR RFD3

GENERAL NOTES

1. If shown on the plans or directed by the Engineer, filter dams should be placed near the toe of slopes where erosion is anticipated, upstream and/or downstream at drainage structures, and in roadway ditches and channels to collect sediment.
2. Materials (aggregate, wire mesh, sandbags, etc.) shall be as indicated by the specification for "Rock Filter Dams for Erosion and Sedimentation Control".
3. The rock filter dam dimensions shall be as indicated on the SW3P plans.
4. Side slopes should be 2:1 or flatter. Dams within the safety zone shall have sideslopes of 6:1 or flatter.
5. Maintain a minimum of 1' between top of rock filter dam weir and top of embankment for filter dams at sediment traps.
6. Filter dams should be embedded a minimum of 4" into existing ground.
7. The sediment trap for ponding of sediment laden runoff shall be of the dimensions shown on the plans.
8. Rock filter dam types 2 & 3 shall be secured with 20 gauge galvanized woven wire mesh with 1" diameter hexagonal openings. The aggregate shall be placed on the mesh to the height & slopes specified. The mesh shall be folded at the upstream side over the aggregate and tightly secured to itself on the downstream side using wire ties or hog rings. For in stream use, the mesh should be secured or staked to the stream bed prior to aggregate placement.
9. Sack Gabions should be staked down with 3/4" dia. rebar stakes, and have a double-twisted hexagonal weave with a nominal mesh opening of 2 1/2" x 3 1/4".
10. Flow outlet should be onto a stabilized area (vegetation, rock, etc.).
11. The guidelines shown hereon are suggestions only and may be modified by the Engineer.


PLAN SHEET LEGEND

- Type 1 Rock Filter Dam — RFD1 —
- Type 2 Rock Filter Dam — RFD2 —
- Type 3 Rock Filter Dam — RFD3 —
- Type 4 Rock Filter Dam — RFD4 —


		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES ROCK FILTER DAMS EC(2) - 16			
FILE: ec216	DN: TxDOT	CK: KM	DW: VP
© TxDOT: JULY 2016	CONT	SECT	JOB
REVISIONS	0579	02	014
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	218

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE_36-91\DP5101\WAZ-TxDOT_Paris\ProjectData\FM 512 (0579-02-01-4)\CADD\09_ENVIRONMENTAL\StdDetail\ec316.dgn



PLAN VIEW




ELEVATION VIEW


CONSTRUCTION EXIT (TYPE 1)
 ROCK CONSTRUCTION (LONG TERM)

GENERAL NOTES (TYPE 1)

- The length of the type 1 construction exit shall be as indicated on the plans, but not less than 50'.
- The coarse aggregate should be open graded with a size of 4" to 8".
- The approach transitions should be no steeper than 6:1 and constructed as directed by the Engineer.
- The construction exit foundation course shall be flexible base, bituminous concrete, portland cement concrete or other materials approved by the Engineer.
- The construction exit shall be graded to allow drainage to a sediment trapping device.
- The guidelines shown hereon are suggestions only and may be modified by the Engineer.
- Construct exits with a width of at least 14 ft. for one-way and 20 ft. for two-way traffic for the full width of the exit, or as directed by the engineer.



PLAN VIEW




ELEVATION VIEW


CONSTRUCTION EXIT (TYPE 2)
 TIMBER CONSTRUCTION (LONG TERM)

GENERAL NOTES (TYPE 2)

- The length of the type 2 construction exit shall be as indicated on the plans, but not less than 50'.
- The treated timber planks shall be attached to the railroad ties with 1/2" X 6" min. lag bolts. Other fasteners may be used as approved by the Engineer.
- The treated timber planks shall be #2 grade min., and should be free from large and loose knots.
- The approach transitions shall be no steeper than 6:1 and constructed as directed by the Engineer.
- The construction exit foundation course shall be flexible base, bituminous concrete, portland cement concrete or other material as approved by the Engineer.
- The construction exit should be graded to allow drainage to a sediment trapping device.
- The guidelines shown hereon are suggestions only and may be modified by the Engineer.
- Construct exits with a width of at least 14 ft. for one-way and 20 ft. for two-way traffic for the full width of the exit, or as directed by the engineer.



PLAN VIEW



SECTION A-A

CONSTRUCTION EXIT (TYPE 3)
 SHORT TERM


GENERAL NOTES (TYPE 3)

- The length of the type 3 construction exit shall be as shown on the plans, or as directed by the Engineer.
- The type 3 construction exit may be constructed from open graded crushed stone with a size of two to four inches spread a min. of 4" thick to the limits shown on the plans.
- The treated timber planks shall be #2 grade min., and should be free from large and loose knots.
- The guidelines shown hereon are suggestions only and may be modified by the Engineer.


		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES CONSTRUCTION EXITS EC(3)-16			
FILE: ec316	DN: TxDOT	CK: KM	DW: VP
© TxDOT: JULY 2016	CONT	SECT	JOB
REVISIONS	0579	02	014
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	219

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\09-ENVIRONMENTAL\StdDetail\ec916.dgn




PLAN VIEW



PLAN VIEW




PLAN VIEW



SECTION A-A

EROSION CONTROL LOG DAM


CL-D



SECTION B-B

EROSION CONTROL LOG AT BACK OF CURB


CL-BOC



SECTION C-C


EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY

CL-ROW



DIAMETER MEASUREMENTS OF EROSION CONTROL LOGS SPECIFIED IN PLANS

- LEGEND**
- CL-D EROSION CONTROL LOG DAM
 - CL-BOC EROSION CONTROL LOG AT BACK OF CURB
 - CL-ROW EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY
 - CL-SST EROSION CONTROL LOGS ON SLOPES STAKE AND TRENCHING ANCHORING
 - CL-SSL EROSION CONTROL LOGS ON SLOPES STAKE AND LASHING ANCHORING
 - CL-DI EROSION CONTROL LOG AT DROP INLET
 - CL-CI EROSION CONTROL LOG AT CURB INLET
 - CL-GI EROSION CONTROL LOG AT CURB & GRATE INLET



REBAR STAKE DETAIL

SEDIMENT BASIN & TRAP USAGE GUIDELINES

An erosion control log sediment trap may be used to filter sediment out of runoff draining from an unstabilized area.

Log Traps: The drainage area for a sediment trap should not exceed 5 acres. The trap capacity should be 1800 CF/Acre (0.5" over the drainage area).

Control logs should be placed in the following locations:

1. Within drainage ditches spaced as needed or min. 500' on center
2. Immediately preceding ditch inlets or drain inlets
3. Just before the drainage enters a water course
4. Just before the drainage leaves the right of way
5. Just before the drainage leaves the construction limits where drainage flows away from the project.

The logs should be cleaned when the sediment has accumulated to a depth of 1/2 the log diameter.

Cleaning and removal of accumulated sediment deposits is incidental and will not be paid for separately.

SHEET 1 OF 3


Design Division Standard

TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES
 EROSION CONTROL LOG
 EC (9) - 16

FILE: ec916	DN: TxDOT	CK: KM	DW: LS/PT	CK: LS
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY
REVISIONS	0579	02	014	FM 512
	DIST	COUNTY	SHEET NO.	
	PARIS	HUNT	220	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE\36-91DP5101\WA2-TxDOT\Part1s\ProjectData\FM 512 (0579-02-014)\CADD\GDN\09-ENVIRONMENTAL\StdDetail\ec916.dgn



**EROSION CONTROL LOGS ON SLOPES
 STAKE AND TRENCHING ANCHORING**


CL-SST



END SECTION RAP DETAIL


SLOPE	LOG DIAMETER			
	6"	8"	12"	18"
1:1 OR STEEPER	5'	10'	15'	20'
2:1	10'	20'	30'	40'
3:1	15'	30'	45'	60'
4:1 OR FLATTER	20'	40'	60'	80'

* ADJUSTMENTS CAN BE MADE FOR SOIL TYPE:
 SOFT, LOAMY SOILS-ADJUST ROWS CLOSER TOGETHER;
 HARD, ROCKY SOILS- ADJUST ROWS FARTHER APART





**EROSION CONTROL LOGS ON SLOPES
 STAKE AND LASHING ANCHORING**

CL-SSL




STAKE AND TRENCHING ANCHORING DETAIL

CL-SST




STAKE AND LASHING ANCHORING DETAIL

CL-SSL



TRENCH DEPTH TABLE	
LOG DIAMETER	DEPTH
6"	2"
8"	3"
12"	4"
18"	5"




STAKE NOTCH DETAIL

SHEET 2 OF 3

		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16			
FILE: ec116	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CONT SECT	JOB	HIGHWAY
REVISIONS	0579 02	014	FM 512
	DIST	COUNTY	SHEET NO.
	PARIS	HUNT	221


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 5/24/2023
 FILE: Z:\Transportation\TxDOT\PS&E\STATEWIDE 36-91DP5101\WA2-TxDOT Paris\ProjectData\FM 512 (0579-02-014)\CADD\09-ENVIRONMENTAL\StdDetail\ec916.dgn




EROSION CONTROL LOG AT DROP INLET

CL-DI



EROSION CONTROL LOG AT CURB INLET


CL-CI



EROSION CONTROL LOG AT CURB INLET


CL-CI

NOTE:
 EROSION CONTROL LOGS USED AT CURB INLETS SHOULD ONLY BE USED IF THEY WILL NOT IMPEDE TRAFFIC OR FLOOD THE ROADWAY OR WHEN THE STORM SEWER SYSTEM IS NOT FULLY FUNCTIONAL.



EROSION CONTROL LOG AT CURB & GRADE INLET

CL-GI



		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16			
FILE: ec916	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CONT	SECT	JOB
REVISIONS	0579	02	014
DIST	COUNTY	SHEET NO.	
PARIS	HUNT	222	