

STATE OF TEXAS  
DEPARTMENT OF TRANSPORTATION

DESIGN SPEED = 30 MPH

ADT (YR 2023) = 650 VPD  
ADT (YR 2043) = 830 VPD

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6	C912-34-185		1
STATE	DIST.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72

INDEX OF SHEETS


SHEET NO. DESCRIPTION  
SEE SHEET 2 FOR INDEX OF SHEETS

PLANS OF PROPOSED  
STATE HIGHWAY IMPROVEMENT

FORT BEND COUNTY  
PARK ROAD 72  
LIMITS: IN BRAZOS BEND STATE PARK  
PROJECT: C 912-34-185  
CONTROL 0912-34-185


FOR THE CONSTRUCTION OF MISCELLANEOUS WORK  
CONSISTING OF MILLING, 1.5IN ACP OVERLAY AND PAVEMENT MARKINGS

LOCATION	ROADWAY LENGTH	BRIDGE LENGTH	TOTAL LENGTH
PARK ENTRANCE/EXIT	572.24 FT = 0.108 MI	0.00 FT / 0.000 MI	572.24 FT = 0.108 MI
PARK ROAD 72	14,423.68 FT = 2.732 MI	0.00 FT / 0.000 MI	14,423.68 FT = 2.732 MI
BURR OAK CAMPGROUND	3,068.01 FT = 0.581 MI	0.00 FT / 0.000 MI	3,078.47 FT = 0.581 MI
RED BUCKEYE CAMPGROUND	3,774.45 FT = 0.715 MI	0.00 FT / 0.000 MI	3,774.45 FT = 0.715 MI
SHELTER CAMPGROUND	1,139.59 FT = 0.216 MI	0.00 FT / 0.000 MI	1,139.59 FT = 0.216 MI
MAINTENANCE ROAD	747.05 FT = 0.141 MI	0.00 FT / 0.000 MI	747.05 FT = 0.141 MI
TOTAL			23,735.48 FT = 4.500 MI



VICINITY MAP  
N. T. S.

FUNCTIONAL CLASSIFICATION: RURAL MINOR COLLECTOR



BEGIN PROJECT  
PARK ENTRANCE  
STA 127+72.29  
PARK EXIT  
STA 128+00.00  
CSJ 0912-34-185  
REF MARK = 666+0.384  
MP = 1.524

PARK ENTRANCE/EXIT

END  
PARK ROAD 72  
STA 280+34.81  
REF MARK = 668+1.294  
MP = 4.322

BEGIN  
PARK ROAD 72  
STA 136+11.13

PARK RD 72

NOT TO SCALE

END:  
PARK ENTRANCE  
STA 130+27.21  
PARK EXIT  
STA 131+17.42

EXCEPTIONS: NONE  
EQUATIONS: NONE  
RR CROSSING: NONE

MAINTENANCE ROAD

END  
MAINTENANCE ROAD  
STA 17+47.05

BEGIN  
MAINTENANCE ROAD  
STA 10+00.00

BURR OAK CAMPING AREA - STA 10+10.46 TO STA 40+78.47  
RED BUCKEYE CAMPING AREA - STA 10+00.00 TO STA 47+74+45  
SHELTER CAMPING AREA - STA 10+00.00 TO STA 21+39.59

6/9/2023

DocuSigned by:  
*Scott D. Smith*  
TEXAS PARKS & WILDLIFE DEPARTMENT

SUBMITTED FOR LETTING: 6/11/2023

DocuSigned by:  
*Carlos M. Zepeda, Jr., P.E.*  
AREA ENGINEER

APPROVED FOR LETTING: 6/29/2023

DocuSigned by:  
*Larry W. Blackburn, P.E.*  
FOR DISTRICT ENGINEER

COUNTY: FORT BEND PROJ. NO. C912-34-185  
HWY. NO. VARIOUS LETTING DATE SEPTEMBER 2023  
DATE ACCEPTED

TDLR INSPECTION REQUIRED  
TDLR NO. **TABS2023020607**

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND THE SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED SPECIAL LABOR PROVISION FOR STATE PROJECTS: SP000---008.

- GENERAL**
- 1 TITLE SHEET
  - 2 PR 72 INDEX OF SHEETS
  - 3-5 TYPICAL SECTION
  - 6 GENERAL NOTES
  - 7 ,7A ESTIMATE AND QUANTITY SHEET
  - 8-9 SUMMARY SHEETS
  - 10 SUMMARY OF SMALL SIGNS SOSS

- TRAFFIC CONTROL PLAN**
- 11 TRAFFIC CONTROL NARRATIVE
  - 12-13 TRAFFIC CONTROL TYPICAL SECTION


- TRAFFIC CONTROL PLAN STANDARDS**
- \* 14 BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS BC(1)-21
  - \* 15 BARRICADE AND CONSTRUCTION PROJECT LIMIT BC(2)-21
  - \* 16 BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT BC(3)-21
  - \* 17 BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES BC(4)-21
  - \* 18 BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT BC(5)-21
  - \* 19 BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS) BC(6)-21
  - \* 20 BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR BC(7)-21
  - \* 21 BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES BC(8)-21
  - \* 22 BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES BC(9)-21
  - \* 23 BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES BC(10)-21
  - \* 24 BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS BC(11)-21
  - \* 25 BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS BC(12)-21
  - \* 26 TRAFFIC CONTROL PLAN ONE-LANE TWO WAY TRAFFIC CONTROL TCP(1-2)-18
  - \* 27 TRAFFIC CONTROL PLAN LONG TERM ONE-LANE TWO-WAY CONTROL TCP(2-8)-18
  - \* 28 TRAFFIC CONTROL PLAN MOBILE OPERATIONS UNDIVIDED HIGHWAYS TCP(3-1)-13
  - \* 29 TRAFFIC CONTROL PLAN MOBILE OPERATIONS RAISED PAVEMENT MARKER INSTALLATION REMOVAL TCP(3-3)-14
  - \* 30 WORK ZONE "GIVE US A BRAKE" SIGNS WZ(BRK)-13
  - \* 31 WORK ZONE SHORT TERM PAVEMENT MARKINGS WZ(STPM)-13
  - \* 32 TRAFFIC CONTROL PLAN TYPICAL DETAILS WZ(TD)-17
  - \* 33 SIGNING FOR UNEVEN LANES WZ(UL)-13

- ROADWAY DETAILS**
- 34-39 HORIZONTAL ALIGNMENT DATA SHEET
  - 40-42 PR 72 HORIZONTAL ALIGNMENT LAYOUT SHEET
  - 43 CAMPING AREA HORIZONTAL ALIGNMENT LAYOUT SHEET
  - 44-54 PR 72 PLAN SHEET
  - 55-57 PR 72 MISCELLANEOUS DETAIL
  - 58 PAVEMENT MARKINGS AND SIGNING FOR ACCESIBLE PARKING PM(AP)-21

- ROADWAY STANDARDS**
- \* 59 TAPERED EDGE DETAILS HMAC PAVEMENT TE (HMAC)-11
  - \* 60 TYPICAL STANDARD PAVEMENT MARKINGS PM(1)-22
  - \* 61 POSITION GUIDANCE USING RAISED MARKERS REFLECTORIZED PROFILE MARKINGS PM(2)-22
  - \* 62 CROSSWALK PAVEMENT MARKINGS PM(4)-22A
  - \* 63 SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS GENERAL NOTES & DETAILS SMD(GEN)-08
  - \* 64 SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM SMD(SLIP-1)-08
  - \* 65 SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM SMD(SLIP-2)-08
  - \* 66 SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM SMD(SLIP-3)-08

- ENVIRONMENTAL ISSUES**
- 67 ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS EPIC
  - 68-69 FM 723 STORMWATER POLLUTION PREVENTION PLAN (SWP3)

- ENVIRONMENTAL ISSUES STANDARDS**
- \* 70 TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING EC(1)-16
  - \* 71 TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES ROCK FILTER DAMS EC(2)-16




THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ABOVE, HAVE BEEN ISSUED BY ME AND ARE APPLICABLE TO THE PROJECT.

*Glenn Lazaro, P.E.* 07/01/2023  
 GLENN C. LAZARO DATE

## PR 72 INDEX OF SHEETS




FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
6				2
STATE	STATE DIST. NO.	COUNTY		
TEXAS	HOU	FORT BEND		
CONT.	SECT.	JOB	HIGHWAY NO.	
0912	34	185	PR 72	



**EXISTING TYPICAL SECTION**


PARK ENTRANCE - STA 127+72.39 TO STA 130+27.21  
 PARK EXIT - STA 128+00.00 TO STA 131+17.42  
 PARK ROAD 72 - STA 136+11.13 TO STA 280+34.81



**PROPOSED TYPICAL SECTION**

PARK ROAD 72 - STA 136+11.13 TO STA 280+34.81

\* MATCH EXISTING SLOPE




*Glenn Lazaro, P.E.*  
 09/01/2023

**TYPICAL SECTIONS**  
 SHEET 1 OF 3



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			3
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72




**PROPOSED TYPICAL SECTION**

PARK ENTRANCE - STA 127+72.39 TO STA 130+27.21

PARK EXIT - STA 128+00.00 TO STA 131+17.42

\* MATCH EXISTING SLOPE




*Glenn Lazaro, P.E.*  
07/01/2023

**TYPICAL SECTIONS**  
SHEET 2 OF 3



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			4
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72





**PROPOSED TYPICAL SECTION**


BURR OAK CAMPING AREA - STA 10+10.46 TO STA 40+78.47  
 RED BUCKEYE CAMPING AREA - STA 10+00.00 TO STA 47+74+45  
 SHELTER CAMPING AREA - STA 10+00.00 TO STA 21+39.59  
 MAINTENANCE ROAD - STA 10+00.00 TO STA 17+47.05

\* MATCH EXISTING SLOPE



*Glenn Lazaro, P.E.*  
 07/01/2023

**TYPICAL SECTIONS**  
 SHEET 3 OF 3



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			5
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72

**County:** Fort Bend

**Control:** 0912-34-185

**Highway:** Park Road 72

**General:**

Area Engineer contact information for this project follows:

(Carlos Zepeda, Jr., 281-238-7900, and carlos.zepeda@txdot.gov)  
(Daniel Dvorak, 281-238-7900, and daniel.dvorak@txdot.gov)

Submit any questions about this project via the Letting Pre-Bid Q&A web page, located at:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>

The Letting Pre-Bid Q&A web page for each project can be accessed by scrolling or filtering the dashboard using the controls on the left side to navigate to the project. Hover over the blue hyperlink of the project to view the Q&A and click on the link in the window that pops up.

All relevant project documentation, including Contract Time Determinations and cross-sections will continue to be provided on the following FTP site:

[Index of /pub/txdot-info/Pre-Letting Responses/Houston District \(state.tx.us\) or](Index of /pub/txdot-info/Pre-Letting Responses/Houston District (state.tx.us) or)

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting%20Responses/Houston%20District/>

Unless otherwise shown on the plans, RAP generated by this project will become the property of the Contractor for use in the current construction project or in future projects.

If fixed features require, the governing slopes shown may vary between the limits shown and to the extent determined by the Engineer.

Superelevate the curves to match the existing surface.

Notify the Engineer immediately if discrepancies are discovered in the horizontal control or the benchmark data.

The following standard detail sheets are modified:

**Modified Standards**

PAVEMENT MARKINGSANDSIGNJNGFORACCESIBLE PARKING PM(AP)-21 MOD

References to manufacturer's trade name or catalog numbers are for the purpose of identification only. Similar materials from other manufacturers are permitted if they are of equal quality, comply with the specifications for this project, and are approved, except for roadway illumination, electrical, and traffic signal items.

**County:** Fort Bend

**Control:** 0912-34-185

**Highway:** Park Road 72

The cost for materials, labor, and incidentals to provide for traffic across the roadway and for ingress and egress to private property in accordance with Section 7.2.4 of the standard specifications is subsidiary to the various bid items. Restore access roadways to their original condition upon completing construction.

Grade street intersections and median openings for surface drainage.

If a foundation is to be placed where a riprap surface or an asphalt concrete surface presently exists, use caution in breaking out the existing surface for placement. Break out no greater area than is required to place the foundation. After placing the foundation, wrap the periphery with 0.5 in. pre-molded mastic expansion joint. Then replace the remaining portion of the broken out surface with Class A or Class C concrete or cold mix asphalt concrete to the exact slope, pattern, and thickness of the existing riprap or asphalt. Payment for breaking out the existing surface, wrapping the foundation, and replacing the surface is subsidiary to the various bid items.

The lengths of the posts for ground mounted signs and the tower legs for the overhead sign supports are approximate. Verify the lengths before ordering these materials to meet the existing field conditions and to conform to the minimum sign mounting heights shown in the plans.

Furnish aluminum Type A signs instead of plywood signs for signs shown on the Summary of Small Signs sheet.

Stencil the National Bridge Inventory (NBI) number on each existing bridge shown on these plans. The NBI number is shown above the title block for each bridge layout.

Clearly mark or highlight on the shop drawings, the items being furnished for this project. Submit required shop drawings in accordance with the shop drawing distribution list shown in the note for Item 5 for review and distribution.

**General: Roadway Illumination and Electrical**

For roadway illumination and electrical items, use materials from pre-qualified producers as shown on the Construction Division (CST) of the Department's material producers list. Check the latest link on the Department's website for this list. The category/item is "Roadway Illumination and Electrical Supplies." No substitutions will be allowed for materials found on this list.

Perform electrical work in conformance with the National Electrical Code (NEC) and the Department's standard sheets.

**General: Site Management**

Mow the grass and weeds within the project limits a maximum of 3 times a year as directed. This work is subsidiary to the various bid items.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

Mark stations every 100 ft. and maintain the markings for the project duration. Remove the station markings at the completion of the project. This work is subsidiary to the various bid items.

Do not mix or store materials, or store or repair equipment, on top of concrete pavement or bridge decks unless authorized by the Engineer. Permission will be granted to store materials on surfaces if no damage or discoloration will result.

Assume ownership of debris and dispose of at an approved location. Do not dispose of debris on private property unless approved in writing by the District Engineer.

Control the dust caused by construction operations. For sweeping the base material in preparation for laying asphalt and for sweeping the finished concrete pavement, use one of the following types of sweepers or approved equal:

**Tricycle Type**

Wayne Series 900  
Elgin White Wing  
Elgin Pelican

**Truck Type - 4 Wheel**

M-B Cruiser II  
Wayne Model 945  
Mobile TE-3  
Mobile TE-4  
Murphy 4042

**General: Traffic Control and Construction**

Schedule construction operations such that preparing individual items of work follows in close sequence to constructing storm drains in order to provide as little inconvenience as practical to the businesses and residents along the project.

Schedule work so that the base placement operations follow the subgrade work as closely as practical to reduce the hazard to the traveling public and to prevent undue delay caused by wet weather.

This project requires extensive grading operations in an environmentally sensitive area.

If relocating mailboxes, place them with the post firmly in the ground at nearby locations. Upon completing the project, the Engineer will locate the final mailbox placement. Perform this work in accordance with the requirements of the Item, "Mailbox Assemblies," except for measurement and payment. This work is subsidiary to the various bid items.

If fences cross construction easements shown on the plans and work is required beyond the fences, remove and replace the fences as directed. This work and the materials are subsidiary to the various bid items.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

When design details are not shown on the plans, provide signs and arrows conforming to the latest "Standard Highway Sign Designs for Texas" manual.

**General: Utilities**

Consider the locations of underground utilities depicted in the plans as approximate and employ responsible care to avoid damaging utility facilities. Depending upon scope and magnitude of planned construction activities, advanced field confirmation by the utility owner or operator may be prudent. Where possible, protect and preserve permanent signs, markers, and designations of underground facilities.

If the Contractor damages or causes damage (breaks, leaks, nicks, dents, gouges, etc.) to the utility, contact the utility facility owner or operator immediately.

At least 72 hours before starting work, make arrangements for locating existing Department-owned above ground and underground fiber optic, communications, power, illumination, and traffic signal cabling and conduit. Do this by calling the Department's Houston District Traffic Signal Operations Office at 713-802-5662, or by e-mailing the Department's Houston District Traffic Signal Operations Office at: [HOU-LocateRequest@txdot.gov](mailto:HOU-LocateRequest@txdot.gov), to schedule marking of underground lines on the ground. Use caution if working in these areas to avoid damaging or interfering with existing facilities.

Notify the Engineer at least 48 hours before constructing junction boxes at storm drain and utility intersections.

Install or remove poles and luminaires located near overhead or underground electrical lines using established industry and utility safety practices. Consult the appropriate utility company before beginning such work.

If overhead or underground power lines need to be de-energized, contact the electrical service provider to perform this work. Costs associated with de-energizing the power lines or other protective measures required are at no expense to the Department.

If working near power lines, comply with the appropriate sections of Texas State Law and Federal Regulations relating to the type of work involved.

Perform electrical work in conformance with the National Electrical Code (NEC) and Department's standard sheets.

Before beginning any underground work, notify the City of Houston's Chief Inspector, Public Works and Engineering, to establish the locations of any existing electrical systems for lighting facilities within the limits of this project.

County: Fort Bend

Control: 0912-34-185

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

Highway: Park Road 72

**Item 5: Control of Work**

The cross-section data provided above is for non-construction purposes only and it is the responsibility of the prospective bidder to validate the data with the appropriate plans, specifications, and estimates for the projects.

Submit shop drawings electronically for the fabrication of items as documented in Table below. Information and requirements for electronic submittals can be viewed in the "Guide to Electronic Shop Drawing Submittal" which can be accessed through the following web link, [ftp://ftp.dot.state.tx.us/pub/txdot-info/library/pubs/bus/bridge/e\\_submit\\_guide.pdf](ftp://ftp.dot.state.tx.us/pub/txdot-info/library/pubs/bus/bridge/e_submit_guide.pdf). References to 11 in. x 17 in. sheets in individual specifications for structural items imply electronic CAD sheets.

**Table 1**

**2014 Construction Specification Required Shop/Working Drawing Submittals - TxDOT Generated Plans**

Spec Item No.'s	Product	Submittal Required	Approval Required (Y/N)	Contractor/Fabricator P.E. Seal Required	Reviewing Party	Shop or Working Drawing (Note 1)
7.16.1&.2	Construction Load Analyses	Y	Y	Y	B	WD
400	Excavation and Backfill for Structures (cofferdams)	Y	N	Y	A	WD
403	Temporary Special Shoring	Y	N	Y	C	WD
420	Formwork/Falsework	Y	N	Y	A	WD
423	Retaining Walls, (calcs req'd.)	Y	Y	Y	C	SD
425	Optional Design Calculations (Prstrs Bms)	Y	Y	Y	B	SD
425	Prestr Concr Sheet Piling	Y	Y	N	B	SD
425	Prestr Concr Beams	Y	Y	N	B	SD
425	Prestr Concr Bent	Y	Y	N	B	SD
426	Post Tension Details	Y	Y	N	B	SD
434	Elastomeric Bearing Pads (All)	Y	Y	N	B	SD
441	Bridge Protective Assembly	Y	Y	N	B	SD
441	Misc Steel (various steel assemblies)	Y	Y	N	B	SD
441	Steel Pedestals (bridge raising)	Y	Y	N	B	SD
441	Steel Bearings	Y	Y	N	B	SD
441	Steel Bent	Y	Y	N	B	SD
441	Steel Diaphragms	Y	Y	N	B	SD
441	Steel Finger Joint	Y	Y	N	B	SD
441	Steel Plate Girder	Y	Y	N	B	SD
441	Steel Tub-Girders	Y	Y	N	B	SD
441	Erection Plans, including Falsework	Y	N	Y	A	WD
449	Sign Structure Anchor Bolts	Y	Y	N	T	SD
450	Railing	Y	Y	N	A	SD
462	Concrete Box Culvert	Y	Y	N	C	SD
462	Concrete Box Culvert (Alternate Designs Only, calcs req'd.)	Y	Y	Y	B	SD
464	Reinforced Concrete Pipe (Jack and Bore only; ONLY when	Y	Y	Y	A	SD

	requested)					
465	Pre-cast Junction Boxes, Grates, and Inlets	Y	Y	N	A	SD
465	Pre-cast Junction Boxes, Grates, and Inlets (Alternate Designs Only, calcs req'd.)	Y	Y	Y	B	SD
466	Pre-cast Headwalls and Wingwalls	Y	Y	N	A	SD
467	Pre-cast Safety End Treatments	Y	Y	N	A	SD
495	Raising Existing Structure (calcs req'd.)	Y	Y	Y	B	SD
610	Roadway Illumination Supports (Non-Standard only, calcs req'd.)	Y	Y	Y	BRG	SD
613	High Mast Illumination Poles (Non-standard only, calcs req'd.)	Y	Y	Y	BRG	SD
627	Treated Timber Poles	Y	Y	N	T	SD
644	Special Non-Standard Supports (Bridge Mounts, Barrier Mounts, Etc.)	Y	Y	Y	T	SD
647	Large Roadside Sign Supports	Y	Y	Y	T	SD
650	Cantilever Sign Structure Supports - Alternate Design Calcs.	Y	Y	Y	T	SD
650	Sign Structures	Y	Y	N	T	SD
680	Installation of Highway Traffic Signals	Y	Y	N	T	SD
682	Vehicle and Pedestrian Signal Heads	Y	Y	N	T	SD
684	Traffic Signal Cables	Y	Y	N	T	SD
685	Roadside Flashing Beacon Assemblies	Y	Y	N	T	SD
686	Traffic Signal Pole Assemblies (Steel) (Non-Standard only)	Y	Y	Y	T	SD
687	Pedestal Pole Assemblies	Y	Y	N	T	SD
688	Detectors	Y	Y	N	A	SD
784	Repairing Steel Bridge Members	Y	Y	Y	B	WD
SS	Prestr Concr Crown Span	Y	Y	N	B	SD
SS	Sound Barrier Walls	Y	Y	Y	A	SD
SS	Camera Poles	Y	Y	Y	TMS	SD
SS	Pedestrian Bridge (Calcs req'd.)	Y	Y	Y	B	SD
SS	Screw-In Type Anchor Foundations	Y	Y	N	T	SD
SS	Fiber Optic/Communication Cable	Y	Y	N	TMS	SD
SS	Spread Spectrum Radios for Signals	Y	Y	N	T	SD
SS	VIVDS System for Signals	Y	Y	N	T	SD
SS	CTMS Equipment	Y	Y	N	TMS	SD

Notes:

- Document flow for Working Drawings differs from Shop Drawings in that Working Drawings must be submitted to the Engineer rather than the Engineer of Record and they are for the information of the Engineer only; an approval stamp and distribution to all project offices is not required.

**Key to Reviewing Party**

A - Area Office

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

Area Office	Email Address
Brazoria Area Office	<a href="mailto:HOU-BRZAShpDrwgs@txdot.gov">HOU-BRZAShpDrwgs@txdot.gov</a>
Fort Bend Area Office	<a href="mailto:HOU-FBAShpDrwgs@txdot.gov">HOU-FBAShpDrwgs@txdot.gov</a>
Galveston Area Office	<a href="mailto:HOU-GALVAShpDrwgs@txdot.gov">HOU-GALVAShpDrwgs@txdot.gov</a>
Montgomery Area Office	<a href="mailto:HOU-MONTAShpDrwgs@txdot.gov">HOU-MONTAShpDrwgs@txdot.gov</a>
North Harris Area Office	<a href="mailto:HOU-NHAShpDrwgs@txdot.gov">HOU-NHAShpDrwgs@txdot.gov</a>
Southeast Area Office	<a href="mailto:HOU-SEHAShpDrwgs@txdot.gov">HOU-SEHAShpDrwgs@txdot.gov</a>
Traffic Systems Construction Office	<a href="mailto:HOU-TSCShpDrwgs@txdot.gov">HOU-TSCShpDrwgs@txdot.gov</a>
West/Central Harris Area Office	<a href="mailto:HOU-WWCHAOShpDrwgs@txdot.gov">HOU-WWCHAOShpDrwgs@txdot.gov</a>
B - Houston Bridge Engineer	
Bridge Design (Houston TxDOT)	<a href="mailto:HOU-BrgShpDrwgs@txdot.gov">HOU-BrgShpDrwgs@txdot.gov</a>
BRG - Austin Bridge Division	
Bridge Design (Austin TxDOT)	<a href="mailto:BRG_ShopPlanReview@txdot.gov">BRG_ShopPlanReview@txdot.gov</a>
C - Construction Office	
Construction	<a href="mailto:HOU-ConstrShpDrwgs@txdot.gov">HOU-ConstrShpDrwgs@txdot.gov</a>
Laboratory	<a href="mailto:HOU-LabShpDrwgs@txdot.gov">HOU-LabShpDrwgs@txdot.gov</a>
T - Traffic Engineer	
Traffic Operations	<a href="mailto:HOU-TrfShpDrwgs@txdot.gov">HOU-TrfShpDrwgs@txdot.gov</a>
TMS – Traffic Management System	
Computerized Traffic Management Systems (CTMS)	<a href="mailto:HOU-CTMSShpDrwgs@txdot.gov">HOU-CTMSShpDrwgs@txdot.gov</a>

**Item 7: Legal Relations and Responsibilities**

Do not initiate activities in a Project Specific Location (PSL), associated with a U.S. Army Corps of Engineers (USACE) permit area, that have not been previously evaluated by the USACE as part of the permit review of this project. Such activities include those pertaining to, but are not limited to, haul roads, equipment staging areas, borrow and disposal sites. Associated defined here means materials are delivered to or from the PSL. The permit area includes the waters of the U.S. or associated wetlands affected by activities associated with this project. Special restrictions may be required for such work. Assume responsibility for consultations with the USACE regarding activities, including PSLs that have not been previously evaluated by the USACE. Provide the Department with a copy of consultations or approvals from the USACE before initiating activities.

The Contractor may proceed with activities in PSLs that do not affect a USACE permit area if a self-determination has been made that the PSL is non-jurisdictional or if proper USACE clearances have been obtained in jurisdictional areas or have been previously evaluated by the USACE as part of the permit review of this project. The Contractor is solely responsible for documenting any determinations that their activities do not affect a USACE permit area. Maintain copies of their determinations for review by the Department or any regulatory agency.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

Document and coordinate with the USACE, if required, before hauling any excavation from or hauling any embankment to a USACE permit area by either 1 or 2 below:

**1. Restricted Use of Materials for the Previously Evaluated Permit Areas.**

Document both the Project Specific Locations (PSL) and their authorization. Maintain copies for review by the Department or any regulatory agency. When an area within the project limits has been evaluated by the USACE as part of the permit process for this project:

- a. Suitable excavation of required material in the areas shown on the plans and cross sections as specified in the Item, "Excavation" is used for permanent or temporary fill (under the Item, "Embankment") within a USACE permit area.
- b. Suitable embankment (under the Item, "Embankment") from within the USACE permit area is used as fill within a USACE evaluated area.
- c. Unsuitable excavation or excess excavation, "Waste" (under the Item, "Excavation"), that is disposed of at a location approved within a USACE evaluated area.

**2. Contractor Materials from Areas Other than Previously Evaluated Areas.**

Provide the Department with a copy of USACE coordination or approvals before initiating any activities for an area within the project limits that has not been evaluated by the USACE or for any off right of way locations used for the following, but not limited to, haul roads, equipment staging areas, borrow and disposal sites:

- a. The Item, "Embankment" used for temporary or permanent fill within a USACE permit area.
- b. Unsuitable excavation or excess excavation, "Waste" (under the Item, "Excavation"), that is disposed of outside a USACE evaluated area.

The total area disturbed for this project is 9 acres. The disturbed area in this project, the project locations in the Contract, and Contractor project specific locations (PSLs) within 1 mile of the project limits for the Contract, will further establish the authorization requirements for storm water discharges. The Department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans. The Contractor is to obtain required authorization from the TCEQ for Contractor PSLs for construction support activities on or off the ROW. When the total area disturbed in the Contract and PSLs within 1 mile of the project limits exceeds 5 acres, provide a copy of the Contractor NOI for PSLs on the ROW to the Engineer (to the appropriate MS4 operator when on an off-state system route) and to the local government that operates a separate storm drain system.

Maintain the roadway slope stability. Maintaining slope stability is subsidiary to the various bid items.

The nesting / breeding season for migratory birds is February 15 through September 30.

**County:** Fort Bend

**Control:** 0912-34-185

**Highway:** Park Road 72

Conduct any tree removal outside of the migratory bird nesting season. If this is not possible due to scheduling, then exercise caution to remove only those trees with no active nests. Do not destroy nests on structures or in trees within the project limits during the nesting / breeding season.

Take measures to prevent the building of nests on any structures or trees within the project limits throughout the duration of the construction if work / removal will be performed during the nesting / breeding season. This can be accomplished by application of bird repellent gel, netting by hand every 3 to 4 days, or any other non-threatening method approved by the Houston District Environmental Section. Obtain this approval well in advance of the planned use. Contact the Houston District Environmental Section at 713-802-5244. The cost of this work is subsidiary to the various bid items.

No significant traffic generator events have been identified.

**Item 8: Prosecution and Progress**

The Department will not adjust the number of days for the project and milestones, if any, due to differences in opinion regarding any assumptions made in the preparation of the schedule or for errors, omissions, or discrepancies found in the time determination schedule.

Working days will be computed and charged based on a standard workweek in accordance with Section 8.3.1.4

The maximum number of days the time charges on this contract may be suspended due to contractor mobilization, and material fabrication/accumulation or processing delays is 60 days. The Engineer and the Contractor may mutually agree, in writing, to decrease this maximum number of days.

**Item 105: Removing Treated and Untreated Base and Asphalt Pavement**

Removing curb on cement-treated and untreated base or on cement treatment being removed at the same time is subsidiary to this bid Item.

Obtain a secured site for the stockpile of the treated material to be salvaged from this project. Haul and stockpile the unused material as directed. This work is subsidiary to this bid Item.

Store the treated material salvaged from this project at the project sites designated by the Engineer.

**County:** Fort Bend

**Control:** 0912-34-185

**Highway:** Park Road 72

**Item 104: Removing Concrete**

**Item 105: Removing Treated and Untreated Base and Asphalt Pavement**

**Item 305: Salvaging, Hauling, and Stockpiling Reclaimable Asphalt Pavement**

Case 1 - ACP over asphalt treatment

Removing the Asphalt Concrete Pavement (ACP) and the asphalt treatment/asphalt stabilized base are paid for under the Item, "Salvaging, Hauling, and Stockpiling Reclaimable Asphalt Pavement."

Remove the ACP separately from the asphalt treatment/asphalt stabilized base. Make the removed depth as uniform as possible during each removal pass if the pavement depth being removed is composed of different asphalt layers. Unless otherwise approved, stockpile Reclaimable Asphalt Pavement (RAP) of differing types of quality separately by its intended use such as for the asphalt treatment, cement treatment, lime treatment, or asphalt concrete pavement. Break, crush, or mill the stockpiled materials so that 100 percent pass the 2-in. sieve.

**Item 110: Excavation**

If manipulating the excavated material requires moving the same material more than once to accomplish the desired results, the excavation is measured and paid for only once regardless of the manipulation required.

Transition the ditch grades and channel bottom widths at structure locations. Use only approved channel excavation in the embankment.

**Item 132: Embankment**

If salvaged base is used for the embankment material, break it into small pieces to achieve the required density and to facilitate placing in the embankment. Obtain approval of the material before placing in the embankment.

Furnish Type C material with a maximum Liquid Limit (LL) of 65, a minimum Plasticity Index (PI) of 5, and composed of suitable earth material such as loam, clay, or other materials that form a suitable embankment.

The embankment material used on the project which has a Liquid Limit exceeding 45 will be tested for Liquid Limits at the rate of one test per 20,000 cu. yd. or per total quantity less than 20,000 cu. yd., unless otherwise directed. Only use material that passes the above tests.

Furnish material with a maximum Liquid Limit (LL) of 65.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

**Item 134: Backfilling Pavement Edges**

Quantity by station includes both sides of the roadway.

The Contractor has the option of selecting the type of backfill material consisting of Reclaimable Asphalt Pavement (RAP), Flex Base, or Crushed Concrete provided that it meets the requirements listed below.

For Permeable Friction Courses (PFC), the backfill material chosen must meet the requirements of Department Test Method Tex-246-F.

If using salvaged asphalt concrete pavement, size it so that all the material, passes the 2-in. sieve. Use RAP that does not contain deleterious material such as clay or organic material.

Flex Base must meet the requirements of Item 247, Type A, Grade 1-2. Department Test Method Tex-117-E will not be required.

Crushed concrete must meet the requirements of Item 247, Grade 1-2. Department Test Methods Tex-116-E and Tex-117-E will not be required.

Place emulsified asphalt (SS-1, CSS-1, or CSS-1H) at an application rate of 0.25 gal/sq. yard.

**Item 161: Compost**

**Item 162: Sodding for Erosion Control**

**Item 164: Seeding for Erosion Control**

**Item 166: Fertilizer**

**Item 168: Vegetative Watering**

Refer to the "Fertilizer, Seed, Sod, Straw, Compost, and Water" plan sheet for material specifications, application rates, and for watering requirements.

**Item 204: Sprinkling**

Perform subsidiary sprinkling as required under various other items in accordance with the Item, "Sprinkling."

Sprinkling for dust control is subsidiary to the various bid items.

**Item 210: Rolling**

Use a medium pneumatic roller meeting the requirements of Item 210 as directed. This work is subsidiary to the various bid items. On every asphalt shot, use a minimum of 3 pneumatic rollers or as directed. Use approved rolling patterns. Successive asphalt shots will not be allowed until acceptable rolling has been accomplished on the preceding asphalt shot.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

**Item 292: Asphalt Treatment (Plant-Mixed)**

**Item 3076: Dense-Graded Hot Mix Asphalt**

Unless otherwise shown on the plans, RAP generated by this project will become the property of the Contractor for use in the current construction project or in future projects.

**Item 292: Asphalt Treatment (Plant-Mixed)**

If using the iron ore topsoil as the primary aggregate, meaning 80 percent or more by weight of the total mixture, the requirements for the water susceptibility test are waived.

Mixtures containing the iron ore topsoil are exempted from test methods TEX-217-F (Part I, separation of deleterious material and Part II, decantation test for coarse aggregate) and TEX-203-F (Sand Equivalent Test).

Assume responsibility for proportioning the materials entering the asphalt mixture, regardless of the type of plant used.

Furnish the mix designs for approval.

Compact the courses to a minimum density of 95 percent of the maximum density as determined using test method TEX-126-E.

**Item 502: Barricades, Signs, and Traffic Handling**

Use a traffic control plan for handling traffic through the various phases of construction. Follow the phasing sequence unless otherwise agreed upon by the Area Engineer and the Project Manager. Ensure this plan conforms to the latest "Texas Manual on Uniform Traffic Control Devices" and the latest Barricade and Construction (BC) Standard Sheets. The latest versions of Work Zone Standard Sheets WZ (BTS-1) and WZ (BTS-2) are the traffic control plan for the signal installations.

Submit changes to the traffic control plan to the Area Engineer. Provide a layout showing the construction phasing, signs, striping, and signalizations for changes to the original traffic control plan.

Furnish and maintain the barricades and warning signs, including the necessary temporary and portable traffic control devices, during the various phases of construction. Place and construct these barricades and warning signs in accordance with the latest "Texas Manual on Uniform Traffic Control Devices" for typical construction layouts.

Cover work zone signs when work related to the signs is not in progress, or when any hazard related to the signs no longer exists.

Keep the delineation devices, signs, and pavement markings clean. This work is subsidiary to the Item, "Barricades, Signs, and Traffic Handling."



**County:** Fort Bend

**Control:** 0912-34-185

**Highway:** Park Road 72

If a section is not complete before the end of the workday, pull back the base material to the existing pavement edge on a 6H: 1V slope. Edge drop-offs during the hours of darkness are not permitted.

Before detouring traffic onto the mainlane shoulders, remove dirt, debris, vegetation, and other deleterious material from the surface of the shoulders. Appropriately sign the detour in an approved manner. This work is subsidiary to the various bid items.

Coordinate and schedule the work with the appropriate Metro representative if requiring access to the High Occupancy Vehicle lanes.

Cover or remove the permanent signs and construction signs that are incorrect or that do not apply to the current situation for a particular phase.

Do not mount signs on drums or barricades, except those listed in the latest Barricades and Construction standard sheets.

Use traffic cones for daytime work only. Replace the cones with plastic drums during nighttime hours.

Place positive barriers to protect drop-off conditions greater than 2 ft. within the clear zone that remain overnight.

Use Uneven Lane Signs (CW 8-11) during resurfacing operations for elevation differences between adjacent lanes of greater than 1 in.

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

**Item 506: Temporary Erosion, Sedimentation and Environmental Controls**

The use of hay bales is not permitted as Storm Water Pollution Prevention Plan (SWP3) measures.

A Storm Water Pollution Prevention Plan (SWP3) is required. Since the disturbed area is more than 5 acres, a "Notice of Intent" (NOI) is also required.

Use appropriate measures to prevent, minimize, and control the spill of hazardous materials in the construction staging area. Remove and dispose of materials in compliance with State and Federal laws.

**County:** Fort Bend

**Control:** 0912-34-185

**Highway:** Park Road 72

Before starting construction, review with the Engineer the SWP3 used for temporary erosion control as outlined on the plans. Before construction, place the temporary erosion and sedimentation control features as shown on the SWP3.

Schedule the seeding or sodding work as soon as possible. The project schedule provides for a vegetation management plan.

After completing earthwork operations, restore and reseed the disturbed areas in accordance with the Department's specifications for permanent or temporary erosion control.

Implement temporary and permanent erosion control measures to comply with the National Pollution Discharge Elimination System (NPDES) general permit under the Clean Water Act.

Before starting grading operations and during the project duration, place the temporary or permanent erosion control measures to prevent sediment from leaving the right of way.

**Item 585: Ride Quality for Pavement Surfaces**

To eliminate the need for corrective action due to excessive deviations in the final surface layers, exercise caution to ensure satisfactory profile results in the intermediate paving layers (mixture).

Milling will not be allowed as a corrective action for excessive deviations in the final surface layer of hot-mix asphalt.

For asphalt mainlanes and direct connectors, use Surface Test Type B and Pay Adjustment Schedule 1. For ramps use Surface Test Type A.

**Item 644: Small Roadside Sign Assemblies**

Sign locations shown on the plans are approximate. Before placing them, obtain approval of and then stake the exact locations for these signs.

Use the Texas Universal Triangular Slip Base with the concrete foundation for small ground mounted signs, unless otherwise shown in the plans.

Remove existing street name signs from existing stop signs and re-install them above the new stop signs. Removing and re-installing existing street name signs is subsidiary to the Item, "Small Roadside Sign Assemblies."

When design details are not shown on the plans, provide signs and arrows conforming to the latest "Standard Highway Sign Designs for Texas" manual.

Use Type E Super High Specific Intensity (Fluorescent Prismatic) yellow green reflective sheeting background to fabricate school signs (S1-1, S3-1, S4-3, S5-1, W16-2, SW16-9p, and SW16-7pL(R)).



County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

Assume ownership of the removed existing signposts. Store removed sign panels at the Contractor's field office, to be picked up by the maintenance office. This work is subsidiary to this item.

Locations of the relocated signs are approximate. Before placing them, obtain approval of and then stake the exact locations for these signs.

Replace existing signs that become damaged during relocation at no expense to the Department.

**Item 662: Work Zone Pavement Markings**

**Item 666: Reflectorized Pavement Markings**

**Item 668: Prefabricated Pavement Markings**

**Item 6019: Longitudinal Prefabricated Pavement Markings (PPM) with Warranty**

**Item 6020: Multipolymer Pavement Markings (MPM) with Warranty**

**Item 6038: Multipolymer Pavement Markings (MPM)**

Use Type III glass beads for thermoplastic and multipolymer pavement markings.

Use a 0.100 in. (100 mil) thickness for thermoplastic pavement markings, measured to the top of the thermoplastic, not including the exposed glass beads.

Use a 0.022 in. (22 mil) thickness for multipolymer pavement markings, measured to the top of the multipolymer, not including the exposed glass beads.

For roadways with asphalt surfaces to be striped with work zone or permanent thermoplastic markings, the Contractor has the option to apply paint and beads markings for a maximum 30-day period until placing the thermoplastic markings, or until starting the succeeding phase of work on the striped area. Maintain the paint and beads markings, at no expense to the Department, until placing the thermoplastic markings or starting the succeeding phase of work on the striped area. The work zone markings, whether paint and beads or thermoplastic, are paid under the Item, "Work Zone Pavement Markings" and the markings are paid for only once for the given phase of construction.

If using paint and bead markings as described above, purchase the traffic paint from the open market.

If the Type II markings become dirty and require cleaning by washing, brushing, compressed air, or other approved methods before applying the Type I thermoplastic markings, this additional cleaning is subsidiary to the Item, "Reflectorized Pavement Markings."

Establish the alignment and layout for work zone striping and permanent striping.

Stripe all roadways before opening them to traffic.

Place pavement markings under these items in accordance with details shown on the plans, the latest "Texas Manual on Uniform Traffic Control Devices," or as directed.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

When design details are not shown on the plans, provide pavement markings for arrows, words, and symbols conforming to the latest "Standard Highway Sign Designs for Texas" manual.

**Item 672: Raised Pavement Markers**

If other operations are complete on the project and if the curing time period is not yet elapsed, the contract time will be suspended until the curing is done.

Before placing the raised pavement markers on concrete pavement, blast clean the surface using an abrasive-blasting medium. This work is subsidiary to the Item, "Raised Pavement Markers."

Provide epoxy adhesive that is machine-mixed or nozzle-mixed and dispensed. Equip the machine or nozzle with a mechanism to ensure positive mix measurement control.

**Item 677: Eliminating Existing Pavement Markings and Markers**

Remove existing pavement markings on concrete or asphalt surfaces by flail milling or as directed.

**Item 678: Pavement Surface Preparation for Markings**

Do not blast clean asphalt concrete pavement. Clean asphalt concrete pavement as required under the applicable specifications or as directed.

On new concrete pavement or on existing concrete pavement when placing a new stripe on a new location, remove the curing compounds and contamination from the pavement surface by flail milling or as directed. In addition, air-blast the surface with compressed air just before placing the new stripe.

On existing concrete pavement when placing a new stripe on an existing location, after removing the existing stripe under the Item, "Eliminating Existing Pavement Markings and Markers," air-blast the surface with compressed air just before placing the new stripe.

Do not clean concrete pavement by grinding.

**Item 730: Roadside Mowing**

**Item 734: Litter Removal**

**Item 735: Debris Removal**

Mow areas of existing vegetation, collect and dispose of litter, and sweep the roadway within the project limits according to the following chart for the duration of the project or as directed. This work is paid for under their respective bid items.

Roadside Mowing	Litter Removal	Debris Removal	Cleaning and Sweeping Highways
2 cycles	2 cycles	2 cycles	N/A

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

**Item 3076: Dense-Graded Hot Mix Asphalt**

Taper the asphalt concrete pavement at the beginning and ending points.

Use a maximum 6H:1V slope for the asphalt concrete pavement edge.

Where the 6H:1V ACP edge taper extends over onto the unsurfaced shoulders, blade off the loose existing shoulder material to provide a solid base for the outside taper edge. After placing the ACP overlay, blade this material back against the edge taper. This work is subsidiary to the various bid items.

The stockpile will be the point of sampling of coarse aggregate for test method TEX-217-F (Part II, decantation).

Place the asphalt concrete pavement in courses as shown on the typical sections.

Do not use petroleum-based solvents in the beds of hot mix asphalt delivery vehicles.

Dilution of tack coat is not allowed.

Do not use Surface Aggregate Classification (SAC) C for this project.

For determining the Asphalt Content, only ignition ovens will be allowed.

The tack coat rate shown on the "Basis of Estimate" is an average rate for calculating tack coat quantities. Vary the rate based on the pavement conditions and other factors such as manufacturer's recommendations and weather.

**Item 6185: Truck Mounted Attenuator (TMA) and Trailer Attenuator (TA)**

A shadow vehicle with Truck Mounted Attenuators (TMAs) or Trailer Attenuators (TAs) is required as shown on the appropriate Traffic Control Plan (TCP) sheets. TMAs/TAs must meet the requirements of the Compliant Work Zone Traffic Control Device List.

Level 3 Compliant TMAs/TAs are required for this project.

A total of one (1) shadow vehicle with a TMA/TA is required for the work with the exception of Pavement Marking Operations. The Contractor is responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMAs/TAs needed on the project.

A total of three (3) shadow vehicles with a TMA/TA are required for Pavement Marking Operations. The Contractor is responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMAs/TAs needed on the project.

County: Fort Bend

Control: 0912-34-185

Highway: Park Road 72

**Basis of Estimate**

Item	Description	Limit and Rate	Unit
134	Backfilling Pavement Edges <ul style="list-style-type: none"> <li>• Asphalt Emulsion</li> </ul>	0.25 Gal. / Sq. Yd.	STA
292	Asphalt Treatment (Plant-Mixed) <ul style="list-style-type: none"> <li>• Asphalt</li> <li>• Aggregate</li> </ul>	110 Lb. / Sq. Yd.-In. 5 % by weight 95 % by weight	TON
3076	Dense-Graded Hot Mix Asphalt <ul style="list-style-type: none"> <li>• Asphalt</li> <li>• Aggregate</li> </ul> Tack Coat <ul style="list-style-type: none"> <li>• Applied on new HMA</li> <li>• Applied on Existing HMA</li> <li>• Applied on Milled HMA</li> </ul>	110 Lb. / Sq. Yd.-In. 6 % by weight 94 % by weight  0.06 Gal. / Sq. Yd. 0.09 Gal. / Sq. Yd. 0.11 Gal. / Sq. Yd.	TON  GAL
	•		

\* If used in existing roadway base, rate will be determined on a case by case basis.



# Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0912-34-185

DISTRICT Houston  
HIGHWAY PR 72

COUNTY Fort Bend

CONTROL SECTION JOB				0912-34-185		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00098539			
COUNTY				Fort Bend			
HIGHWAY				PR 72			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	105-6014	REMOVING STAB BASE & ASPH PAV (7"-12")	SY	763.000		763.000	
	110-6001	EXCAVATION (ROADWAY)	CY	2,382.000		2,382.000	
	132-6006	EMBANKMENT (FINAL)(DENS CONT)(TY C)	CY	535.000		535.000	
	134-6004	BACKFILL (TY A OR B)	STA	240.000		240.000	
	292-6002	ASPHALT STAB BASE (GR 2)(PG 64)	TON	5,937.000		5,937.000	
	354-6041	PLANE ASPH CONC PAV (1.5")	SY	43,548.000		43,548.000	
	500-6001	MOBILIZATION	LS	1.000		1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	4.000		6.000	
	506-6038	TEMP SEDMT CONT FENCE (INSTALL)	LF	3,000.000		3,000.000	
	506-6039	TEMP SEDMT CONT FENCE (REMOVE)	LF	3,000.000		3,000.000	
	644-6001	IN SM RD SN SUP&AM TY10BWG(1)SA(P)	EA	4.000		4.000	
	644-6076	REMOVE SM RD SN SUP&AM	EA	4.000		4.000	
	666-6048	REFL PAV MRK TY I (W)24"(SLD)(100MIL)	LF	132.000		132.000	
	666-6303	RE PM W/RET REQ TY I (W)4"(SLD)(100MIL)	LF	1,300.000		1,300.000	
	666-6309	RE PM W/RET REQ TY I (W)6"(SLD)(100MIL)	LF	33,861.000		33,861.000	
	666-6321	RE PM W/RET REQ TY I (Y)6"(SLD)(100MIL)	LF	17,126.000		17,126.000	
	668-6027	PREFAB PAV MRK TY B (W)(WORD)	EA	4.000		4.000	
	668-6055	PRE PM TY B(ACC PRK)(BL&WH)(W/BORDR)LG	EA	4.000		4.000	
	672-6009	REFL PAV MRKR TY II-A-A	EA	858.000		858.000	
	678-6001	PAV SURF PREP FOR MRK (4")	LF	1,300.000		1,300.000	
	678-6002	PAV SURF PREP FOR MRK (6")	LF	50,987.000		50,987.000	
	678-6008	PAV SURF PREP FOR MRK (24")	LF	132.000		132.000	
	678-6016	PAV SURF PREP FOR MRK (WORD)	EA	4.000		4.000	
	678-6021	PAV SURF PREP FOR MRK (SYMBOL)	EA	4.000		4.000	
	730-6106	STRIP MOWING	CYC	2.000		2.000	
	734-6002	LITTER REMOVAL	CYC	2.000		2.000	
	735-6001	DEBRIS REMOVAL (CNTR MEDIANS/MAINLANES)	CYC	2.000		2.000	
	3076-6042	D-GR HMA TY-D SAC-B PG70-22	TON	4,188.000		4,188.000	
	3076-6066	TACK COAT	GAL	5,223.000		5,223.000	
	5057-6001	PRECAST CONCRETE WHEEL STOPS	EA	10.000		10.000	
	5057-6002	MOVE AND RESET PRECAST CONC WHEEL STOPS	EA	417.000		417.000	
	6001-6001	PORTABLE CHANGEABLE MESSAGE SIGN	DAY	75.000		75.000	
	6185-6002	TMA (STATIONARY)	DAY	75.000		75.000	
	6185-6005	TMA (MOBILE OPERATION)	DAY	20.000		20.000	
	08	CONTRACTOR FORCE ACCOUNT EROSION CONTROL MAINTENANCE (NON-PARTICIPATING)	LS	1.000		1.000	

DISTRICT	COUNTY	CCSJ	SHEET
Houston	Fort Bend	0912-34-185	7



# Estimate & Quantity Sheet

**CONTROLLING PROJECT ID** 0912-34-185

**DISTRICT** Houston

**COUNTY** Fort Bend

**HIGHWAY** PR 72

<b>CONTROL SECTION JOB</b>				<b>0912-34-185</b>		TOTAL EST.	TOTAL FINAL
<b>PROJECT ID</b>				<b>A00098539</b>			
<b>COUNTY</b>				<b>Fort Bend</b>			
<b>HIGHWAY</b>				<b>PR 72</b>			
<b>ALT</b>	<b>BID CODE</b>	<b>DESCRIPTION</b>	<b>UNIT</b>	EST.	FINAL		
	08	CONTRACTOR FORCE ACCOUNT LAW ENFORCEMENT (NON-PARTICIPATING)	LS	1.000		1.000	
		CONTRACTOR FORCE ACCOUNT SAFETY CONTINGENCY (NON-PARTICIPATING)	LS	1.000		1.000	

**SUMMARY OF ROADWAY QUANTITIES**

	0105-6014	0110-6001	0132-6006	0134-6004	0292-6002	0354-6041	0644-6076
	REMOVING STAB BASE & ASPH PAV (7"-12")	EXCAVATION (ROADWAY)	EMBANKMENT (FINAL) (DENS CONT) (TY C)	BACKFILL (TY A OR B)	ASPHALT STAB BASE (GR 2) (PG 64)	PLANE ASPH CONC PAV (1.5")	REMOVE SM RD SN SUP&AM
	SY	CY	CY	STA	TON	SY	EA
PARK ENTRANCE & EXIT	763	43		6	456		
PARK ROAD 72		1,069	535	145	4,408	9,616	
MAINTENANCE ROAD		85		8	1,073	1,950	
BURR OAK CAMPGROUND		456		31		12,632	
RED BUCKEYE CAMPGROUND		560		38		15,362	4
SHELTER AREA CAMPGROUND		169		12		3,989	
TOTAL	763	2,382	535	240	5,937	43,548	4

**SUMMARY OF ROADWAY QUANTITIES**

	3076-6042	3076-6066	5057-6001	5057-6002	6001-6001	6185-6002	6185-6005
	D-GR HMA TY-D SAC-B PG70-22	TACK COAT	PRECAST CONCRETE WHEEL STOPS	MOVE AND RESET PRECAST CONC WHEEL STOPS	PORTABLE CHANGEABLE MESSAGE SIGN	TMA (STATIONARY)	TMA (MOBILE OPERATION)
	TON	GAL	EA	EA	DAY	DAY	DAY
PARK ENTRANCE & EXIT	63	46					
PARK ROAD 72	1,323	1,443					
MAINTENANCE ROAD	161	215					
BURR OAK CAMPGROUND	1,043	1,390		139			
RED BUCKEYE CAMPGROUND	1,268	1,690		232			
SHELTER AREA CAMPGROUND	330	439		46			
TOTAL	4,188	5,223	10	417	75	75	20

**NOTE:**

- CONDITION OF WHEEL STOPS TO BE DETERMINED BY THE ENGINEER. DAMAGED WHEEL STOPS WILL BE REPLACED WITH NEW WHEEL STOPS. DAMAGED WHEEL STOPS WILL BECOME PROPERTY OF CONTRACTOR.
- EXISTING EDGE BACKFILL REMOVAL WILL BE PAID UNDER EXCAVATION QUANTITY.



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			8
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72

SUMMARY OF PAVEMENT MARKING QUANTITIES							
	0666-6048	0666-6303	0666-6309	0666-6321	0668-6027	0668-6055	0672-6009
	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)	RE PM W/RET REQ TY I (W) 4" (SLD) (100MIL)	RE PM W/RET REQ TY I (W) 6" (SLD) (100MIL)	RE PM W/RET REQ TY I (Y) 6" (SLD) (100MIL)	PREFAB PAV MRK TY B (W) (WORD)	PRE PM TY B (ACC PRK) (BL&WH) (W/BORDR) LG	REFL PAV MRKR TY II-A-A
	LF	LF	LF	LF	EA	EA	EA
PARK ENTRANCE & EXIT			572				
PARK ROAD 72			14,423				
MAINTENANCE ROAD			1,144	1,144			58
BURR OAK CAMPGROUND	20	140	6,576	6,156			308
RED BUCKEYE CAMPGROUND	100	1160	8,868	7,548	4	4	378
SHELTER AREA CAMPGROUND	12		2,278	2,278			114
TOTAL	132	1300	33,861	17,126	4	4	858

SUMMARY OF PAVEMENT MARKING QUANTITIES				SUMMARY OF SWPPP			
	0678-6001	0678-6002	0678-6008	0678-6016	0678-6021	0506-6038	0506-6039
	PAV SURF PREP FOR MRK (4")	PAV SURF PREP FOR MRK (6")	PAV SURF PREP FOR MRK (24")	PAV SURF PREP FOR MRK (WORD)	PAV SURF PREP FOR MRK (SYMBOL)	TEMP SEDMT CONT FENCE (INSTALL)	TEMP SEDMT CONT FENCE (REMOVE)
	LF	LF	LF	EA	EA	LF	LF
PARK ENTRANCE & EXIT		572				180	180
PARK ROAD 72		14,423				1,200	1,200
MAINTENANCE ROAD		2,288				240	240
BURR OAK CAMPGROUND	140	12,732	20			480	480
RED BUCKEYE CAMPGROUND	1160	16,416	100	4	4	660	660
SHELTER AREA CAMPGROUND		4,556	12			240	240
TOTAL	1300	50,987	132	4	4	3,000	3,000



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			9
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72



TRAFFIC CONTROL NARRATIVE

PARK ENTRANCE/EXIT - LANE AND SHOULDER BASE REPAIR

1. SET TRAFFIC CONTROL DEVICES
2. SHIFT TRAFFIC
3. REMOVE LANE AND SHOULDER ASPHALT PAVEMENT
4. REMOVE ASPHALT STABILIZED BASE
5. CONSTRUCT ASPHALT PAVEMENT
6. INSTALL PAVEMENT MARKING

PARK ROAD 72 - SHOULDER BASE REPAIR AND MILL/OVERLAY


1. SET TRAFFIC CONTROL DEVICES
2. SHIFT TRAFFIC
3. REMOVE SHOULDER BACKFILL MATERIAL
4. MILL 1.5" ASPHALT PAVEMENT
5. WIDEN SHOULDER ASPHALT STABILIZED BASE
6. CONSTRUCT ASPHALT PAVEMENT
7. INSTALL PAVEMENT MARKING

BURR OAK, RED BUCKEYE, AND SHELTER CAMPGROUNDS - MILL/OVERLAY

1. SET TRAFFIC CONTROL DEVICES
2. REMOVE SHOULDER BACKFILL MATERIAL
3. MILL 1.5" ASPHALT PAVEMENT
4. OVERLAY ASPHALT PAVEMENT
5. INSTALL PAVEMENT MARKING

MAINTENANCE ROAD - MILL/OVERLAY

1. SET TRAFFIC CONTROL DEVICES
2. REMOVE SHOULDER BACKFILL MATERIAL
3. MILL 1.5" ASPHALT PAVEMENT
4. OVERLAY ASPHALT PAVEMENT
5. INSTALL PAVEMENT MARKING



*Glenn Lazaro, P.E.*  
07/01/2023


**TRAFFIC CONTROL NARRATIVE**

SHEET 1 OF 1



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			11
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72





**TRAFFIC CONTROL  
TYPICAL SECTION**

PARK ROAD 72 - STA 136+11.13 TO STA 280+34.81  
 \* MATCH EXISTING SLOPE




*Glenn Lazaro, P.E.*  
 07/01/2023

**TRAFFIC CONTROL  
TYPICAL SECTION**

SHEET 1 OF 2




FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			12
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72



**TRAFFIC CONTROL  
TYPICAL SECTION**

PARK ROAD 72 - STA 136+11.13 TO STA 280+34.81  
 \* MATCH EXISTING SLOPE



*Glenn Lazaro, P.E.*  
 07/01/2023

**TRAFFIC CONTROL  
TYPICAL SECTION**

SHEET 1 OF 2



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			12
STATE	STATE DIST. NO.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

**BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:**

- The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
- The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
- The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
- Traffic control devices should be in place only while work is actually in progress or a definite need exists.
- The Engineer has the final decision on the location of all traffic control devices.
- Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

**WORKER SAFETY NOTES:**

- Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
- Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.


**COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES**

- Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
- Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).

<b>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT</b> <a href="http://www.txdot.gov">http://www.txdot.gov</a>
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS


DATE: 06/07/2023 11:03 AM  
 FILE: DOCUMENT NAME

SHEET 1 OF 12

 Texas Department of Transportation		Traffic Safety Division Standard
<b>BARRICADE AND CONSTRUCTION          GENERAL NOTES          AND REQUIREMENTS</b>		
<b>BC (1) - 21</b>		
FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT
	0912	34
		185
		PR 72
4-03 7-13		
9-07 8-14		
5-10 5-21		
	DIST	COUNTY
	HOU	FORT BEND
		SHEET NO.
		14


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

**TYPICAL LOCATION OF CROSSROAD SIGNS**



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
  - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
  - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
  - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
  - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
  - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

**T-INTERSECTION**



**CSJ LIMITS AT T-INTERSECTION**

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

**TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING<sup>1,5,6</sup>**

Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign Δ Spacing "x" Feet (Apprx.)
CW20 <sup>4</sup>	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25			50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"	55	500 <sup>2</sup>
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" x 48"	48" x 48"	60	600 <sup>2</sup>
			65	700 <sup>2</sup>
			70	800 <sup>2</sup>
			75	900 <sup>2</sup>
			80	1000 <sup>2</sup>
			*	* <sup>3</sup>


\* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

**GENERAL NOTES**


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

**WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS**




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS**



**SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS**



**NOTES**

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
- CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
- Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
- Contractor will install a regulatory speed limit sign at the end of the work zone.

**LEGEND**

—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12



**BARRICADE AND CONSTRUCTION PROJECT LIMIT**

**BC(2)-21**


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	HOU	FORT BEND	15	

DATE: 06/07/2023 11:03 AM  
 FILE: DOCUMENT NAME

# TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



## GUIDANCE FOR USE:

### LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

### SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

## GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:
 

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
  - Law enforcement.
  - Flagger stationed next to sign.
  - Portable changeable message sign (PCMS).
  - Low-power (drone) radar transmitter.
  - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME

SHEET 3 OF 12

		Traffic Safety Division Standard	
<h2>BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT</h2>			
<h3>BC (3) -21</h3>			
FILE:	bc-21.dgn	DW: TxDOT	CK: TxDOT
© TxDOT	November 2002	CONT	SECT
REVISIONS		0912 34	185 PR 72
9-07	8-14	DIST	COUNTY
7-13	5-21	HOU	FORT BEND
		SHEET NO. 16	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


**TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS**



\* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

\*\* When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

**ATTACHMENT FOR SIGN SUPPORTS**



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

**GENERAL NOTES FOR WORK ZONE SIGNS**

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

**DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)**

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
  - Long-term stationary - work that occupies a location more than 3 days.
  - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
  - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
  - Short, duration - work that occupies a location up to 1 hour.
  - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

**SIGN MOUNTING HEIGHT**

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

**SIZE OF SIGNS**

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

**SIGN SUBSTRATES**

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

**REFLECTIVE SHEETING**

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B<sub>FL</sub> or Type C<sub>FL</sub>, shall be used for rigid signs with orange backgrounds.

**SIGN LETTERS**

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

**REMOVING OR COVERING**

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

**SIGN SUPPORT WEIGHTS**


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

**FLAGS ON SIGNS**

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

**STOP/SLOW PADDLES**

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflectORIZED when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B <sub>FL</sub> OR C <sub>FL</sub> SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

**CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS**

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.





**BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES**

**BC (4) - 21**


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	HOU	FORT BEND	17	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.





### SKID MOUNTED WOOD SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



### GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



### SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

### WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

### OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

### GENERAL NOTES

- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
  - No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
  - When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.
- \* See BC(4) for definition of "Work Duration."
  - \*\* Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
  - See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



## BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	HOU	FORT BEND	18	

DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME



WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

# RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

## PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

## Phase 1: Condition Lists

### Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT
RIGHT X LANES CLOSED	RIGHT X LANES OPEN
CENTER LANE CLOSED	DAYTIME LANE CLOSURES
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE
EXIT CLOSED	RIGHT LN TO BE CLOSED
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI
XXXXXXXX BLVD CLOSED	

### Other Condition List

ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT *

\* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

## Phase 2: Possible Component Lists

### Action to Take/Effect on Travel List

MERGE RIGHT	FORM X LINES RIGHT
DETOUR NEXT X EXITS	USE XXXXX RD EXIT
USE EXIT XXX	USE EXIT I-XX NORTH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N
TRUCKS USE US XXX N	WATCH FOR TRUCKS
WATCH FOR TRUCKS	EXPECT DELAYS
EXPECT DELAYS	PREPARE TO STOP
REDUCE SPEED XXX FT	END SHOULDER USE
USE OTHER ROUTES	WATCH FOR WORKERS
STAY IN LANE *	

### Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXX TO XXXXXX
US XXX TO FM XXXX

### Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

### \*\* Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM-XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

\*\* See Application Guidelines Note 6.

## APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

## WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

## FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Canal	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High-Occupancy Vehicle	HOV	Tuesday	TUES
Highway	HWY	Time Minutes	TIME MIN
Hour(s)	HR, HRS	Upper Level	UPR LEVEL
Information	INFO	Vehicles (s)	VEH, VEHS
It Is	ITS	Warning	WARN
Junction	JCT	Wednesday	WED
Left	LFT	Weight Limit	WT LIMIT
Left Lane	LFT LN	West	W
Lane Closed	LN CLOSED	Westbound	(route) W
Lower Level	LWR LEVEL	Wet Pavement	WET PVMT
Maintenance	MAINT	Will Not	WONT

Roadway designation # IH-number, US-number, SH-number, FM-number



## BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)


BC (6) - 21

FILE: bc-21.dgn	DN: TxDOT	CR: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	HOU	FORT BEND	19	




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




**CONCRETE TRAFFIC BARRIER (CTB)**

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



**LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES**  
LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

**LOW PROFILE CONCRETE BARRIER (LPCB)**




**DELINEATION OF END TREATMENTS**

**END TREATMENTS FOR CTB'S USED IN WORK ZONES**  
End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

**BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS**

**WARNING LIGHTS**


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B<sub>FL</sub> or C<sub>FL</sub> Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.



Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.

**WARNING LIGHTS MOUNTED ON PLASTIC DRUMS**

- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.




Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

**WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS**

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

**ATTENTION**  
Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

**FLASHING ARROW BOARDS**

SHEET 7 OF 12

**TRUCK-MOUNTED ATTENUATORS**

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



**BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR**

**BC (7) -21**

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0912	34	185	PR 72				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	HOU	FORT BEND	20					

DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:03 AM  
 FILE: DOCUMENT NAME

**GENERAL NOTES**

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

**GENERAL DESIGN REQUIREMENTS**

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

**RETROREFLECTIVE SHEETING**

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


**BALLAST**

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




**DETECTABLE PEDESTRIAN BARRICADES**

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign  
(Maximum Sign Dimension)  
Chevron CW1-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer



12" x 24" Vertical Panel  
mount with diagonals sloping down towards travel way

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

**SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS**

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B<sub>FL</sub> or Type C<sub>FL</sub> Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (8) - 21**


FILE:	bc-21.dgn	DW:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0912	34	185	PR	72			
4-03	8-14	DIST	COUNTY	SHEET NO.					
9-07	5-21	HOU	FORT BEND	21					
7-13									

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



**FIXED**  
(Rigid or self-righting)


**DRIVEABLE**



**PORTABLE**


**VERTICAL PANELS (VPs)**

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




**OPPOSING TRAFFIC LANE DIVIDERS (OTLD)**

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

**CHEVRONS**



**LONGITUDINAL CHANNELIZING DEVICES (LCD)**

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

**WATER BALLASTED SYSTEMS USED AS BARRIERS**

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

**HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS**

**GENERAL NOTES**

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths * *			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

\* \* \* Taper lengths have been rounded off.  
L=Length of Taper (FT.) W=Width of Offset (FT.)  
S=Posted Speed (MPH)

**SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS**

SHEET 9 OF 12



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (9) - 21**

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	<b>0912</b>	<b>34</b>	<b>185</b>	<b>PR 72</b>
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	<b>HOU</b>	<b>FORT BEND</b>	<b>22</b>	


DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


**TYPE 3 BARRICADES**

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




**TYPICAL STRIPING DETAIL FOR BARRICADE RAIL**



Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.


**TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES**

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

**TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION**



PERSPECTIVE VIEW




PLAN VIEW

**CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS**

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.  
42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



**TRAFFIC CONTROL FOR MATERIAL STOCKPILES**



**BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES**

**BC (10) - 21**

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	HOU	FORT BEND	23	

DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME

## WORK ZONE PAVEMENT MARKINGS

### GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

### RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

### PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


### MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

### REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

## Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE  
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER  
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
  - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
  - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

### RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:  
 YELLOW - (two amber reflective surfaces with yellow body).  
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

**BC(11)-21**

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	<b>0912</b>	<b>34</b>	<b>185</b>	<b>PR 72</b>
2-98 9-07 5-21	DIST	COUNTY	SHEET NO.	
1-02 7-13	<b>HOU</b>	<b>FORT BEND</b>	<b>24</b>	
11-02 8-14				


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME

## PAVEMENT MARKING PATTERNS




REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




REFLECTORIZED PAVEMENT MARKINGS - PATTERN B

Pattern A is the TXDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN B

## CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

## EDGE & LANE LINES FOR DIVIDED HIGHWAY




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectORIZED pavement markings.




RAISED PAVEMENT MARKERS

## LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS


Prefabricated markings may be substituted for reflectORIZED pavement markings.





RAISED PAVEMENT MARKERS

## TWO-WAY LEFT TURN LANE


## STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS




### SOLID LINES



### BROKEN LINES




### AUXILIARY OR LANEDROP LINE



### REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



## BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC(12)-21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CR: TxDOT
©TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
1-97 9-07 5-21	DIST	COUNTY	SHEET NO.	
2-98 7-13	HOU	FORT BEND	25	
11-02 8-14				

Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:03 AM  
FILE: DOCUMENT NAME



**LEGEND**

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed * X	Formula L = WS <sup>2</sup> / 60	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

\* Conventional Roads Only  
\*\* Taper lengths have been rounded off.  
L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

**TYPICAL USAGE**

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

**GENERAL NOTES**

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
- Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or R1-2 "YIELD" sign is less than 150 feet.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.

**TCP (1-2a)**

- R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
- R1-2 "YIELD" sign with R1-2aP "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.

**TCP (1-2b)**

- Flaggers should use two-way radios or other methods of communication to control traffic.
- Length of work space should be based on the ability of flaggers to communicate.
- If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
- Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the Engineer.
- Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.


Texas Department of Transportation Traffic Operations Division Standard

**TRAFFIC CONTROL PLAN**  
**ONE-LANE TWO-WAY**  
**TRAFFIC CONTROL**


**TCP (1-2) - 18**

FILE: tcp1-2-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
4-90 4-98	DIST	COUNTY	SHEET NO.	
2-94 2-12	HOU	FORT BEND	26	
1-97 2-18				

DATE: 6/8/2023 11:01:38 AM  
 FILE: \\txdot.projectwiseonline.com:TXDOT3\Documents\12 - HOV\Design Projects\12-03-2023\12-03-2023.dgn  
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of units or the accuracy of the information contained herein.



**TCP (2-8a)**  
**ONE LANE TWO-WAY**  
**TRAFFIC CONTROL WITH YIELD SIGNS**  
 (Less Than 2000 ADT-See Note 5)



**TCP (2-8b)**  
**ONE LANE TWO-WAY**  
**TRAFFIC CONTROL WITH TRAFFIC SIGNAL**

**LEGEND**

	Type 3 Barricade		Channelizing Devices
	Sign		Traffic Flow
	Flag		Flagger
	Raised Pavement Markers Ty II-AA		Temporary or Portable Traffic Signal

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS <sup>2</sup> / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60	L = WS	600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75	L = WS	750'	825'	900'	75'	150'	900'	540'	820'

\* Conventional Roads Only  
 \*\* Taper lengths have been rounded off.  
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

**TYPICAL USAGE**

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

- GENERAL NOTES**
- Flags attached to signs where shown are REQUIRED.
  - When this TCP is used at a location which does not involve a bridge, a 48" x 48" CW20-4D "ONE LANE ROAD AHEAD" signs should be used in lieu of the CW5-3 "ONE LANE BRIDGE" signs. The CW13-1P Advisory Speed Plaque is required with either warning sign.
  - Raised pavement markers shall be placed 40 feet c-c on centerline between DO NOT PASS signs and stop or yield lines.
  - For intermediate term situations, when it is not feasible to remove and restore pavement markings, the channelization must be made dominant by using a very close spacing. This is especially important in locations of conflicting information, such as where traffic is directed over a double yellow centerline. In such locations a maximum channelizing device spacing of 20 feet is recommended. The 20 foot channelizing device spacing recommendation is intended for the area of conflicting information and not the entire work zone.
- TCP (2-8a)**
- Traffic control by CW3-2 "YIELD AHEAD" symbol signs for one lane two-way traffic control operations should be limited to work spaces less than 400 feet long and roadways with less than 2000 ADT. Otherwise, portable traffic signals should be used.
  - If power is available, a flashing beacon should be attached to the CW3-2 "YIELD AHEAD" symbol sign for emphasis.
  - The R1-2 "YIELD" and R1-2aP "TO ONCOMING TRAFFIC" signs and other regulatory signs shall be installed at 7 foot minimum mounting height.
- TCP (2-8b)**
- A list of approved Portable Traffic Signals can be found in the "Compliant Work Zone Traffic Control Devices" list.
  - Portable traffic signals should be located to provide adequate stopping sight distance for approaching motorist (See table above).

Texas Department of Transportation  
 Traffic Safety Division Standard

**TRAFFIC CONTROL PLAN**  
**LONG TERM ONE-LANE**  
**TWO-WAY CONTROL**


**TCP (2-8) -23**

FILE: tcp2-8-23.dgn	DN:	CK:	DW:	CK:
© TxDOT	APRIL 2023	CONT	SECT	JOB
12-85 4-98 2-18	0912	34	185	PR 72
8-95 3-03 4-23	DIST	COUNTY	SHEET NO.	
1-97 2-12	HOU	FORT BEND	27	




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:05 AM  
FILE: DOCUMENT NAME



TCP (3-1a)  
**UNDIVIDED MULTILANE ROADWAY**




**TRAIL/SHADOW VEHICLE A**  
with RIGHT Directional display Flashing Arrow Board

LEGEND			
*	Trail Vehicle	ARROW BOARD DISPLAY	
**	Shadow Vehicle		
***	Work Vehicle		RIGHT Directional
	Heavy Work Vehicle		LEFT Directional
	Truck Mounted Attenuator (TMA)		Double Arrow
	Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)


TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**GENERAL NOTES**


1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used the WORK vehicle must be equipped with an arrow board. The Engineer will determine if the LEAD VEHICLE and/or TRAIL VEHICLE are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE are required.
4. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
5. Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
6. Each vehicle shall have two-way radio communication capability.
7. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
8. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
9. "X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY" (CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
10. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the rearmost protection vehicle.




TCP (3-1b)  
**TWO-WAY ROADWAY WITH PAVED SHOULDERS**



TCP (3-1c)  
**TWO-WAY ROADWAY WITHOUT PAVED SHOULDERS**



**TRAIL/SHADOW VEHICLE B**  
with Flashing Arrow Board in CAUTION display



Texas Department of Transportation  
Traffic Operations Division Standard









**TRAFFIC CONTROL PLAN  
MOBILE OPERATIONS  
UNDIVIDED HIGHWAYS**

**TCP (3-1) - 13**

FILE: tcp3-1.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	HOU	FORT BEND	28	
1-97				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:06 AM  
 FILE: DOCUMENT NAME



LEGEND		
* Trail Vehicle	ARROW BOARD DISPLAY	
** Shadow Vehicle		
*** Work Vehicle		RIGHT Directional
		LEFT Directional
		Double Arrow
		CAUTION (Alternating Diamond or 4 Corner Flash)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

**GENERAL NOTES**

- TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used on two way roads the WORK vehicle must have an arrow board. For divided roadways, the arrow board on the WORK vehicle is optional based on the type of work being performed. The Engineer will determine if the LEAD vehicle and/or TRAIL vehicle are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating, or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE, ADVANCE WARNING and TRAIL VEHICLE are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
- Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
- X VEHICLE CONVOY (CW21-10cT) or WORK CONVOY (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" x 48" diamond shaped WORK CONVOY (CW21-10T) or X VEHICLE CONVOY (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The X VEHICLE CONVOY sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
- For divided highways with two or three lanes in one direction, the appropriate LEFT LANE CLOSED (CW20-5bTL), RIGHT LANE CLOSED (CW20-5bTR), or CENTER LANE CLOSED (CW20-5dT) sign should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board may be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
- A double arrow shall not be displayed on the arrow board on the Advance Warning Vehicle.
- For divided highways with three or four lanes in each direction, use TCP(3-2).
- Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
- The Advance Warning Vehicle may straddle the edgeline when Shoulder width makes it necessary.
- On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a DO NOT PASS (R4-1) sign should be placed on the back of the rearmost protection vehicle.


Texas Department of Transportation  
 Traffic Operations Division Standard

**TRAFFIC CONTROL PLAN**  
**MOBILE OPERATIONS**  
**RAISED PAVEMENT**  
**MARKER INSTALLATION/REMOVAL**  
**TCP (3-3) - 14**

FILE: tcp3-3.dgn	DN: TxDOT	CK: TxDOT	OW: TxDOT	CK: TxDOT
© TxDOT September 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 7-13	HOU	FORT BEND	29	
1-97 7-14				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:07 AM  
FILE: DOCUMENT NAME



SIGNS ARE SHOWN FOR ONE DIRECTION OF TRAVEL

\* When the optional larger WORKING FOR YOU GIVE US A BRAKE (G20-7T) 192" x 96" sign is required, the locations shall be noted elsewhere in the plans.

SUMMARY OF LARGE SIGNS

BACKGROUND COLOR	SIGN DESIGNATION	SIGN	SIGN DIMENSIONS	REFLECTIVE SHEETING	SQ FT	GALVANIZED STRUCTURAL STEEL		DRILLED SHAFT
						Size	(LF)	
						①	②	24" DIA. (LF)
Orange	G20-7T		96" X 48"	Type B <sub>FL</sub> or C <sub>FL</sub>	32	▲	▲	▲
Orange	G20-7T		192" X 96"	Type B <sub>FL</sub> or C <sub>FL</sub>	128	W8x18	16 17	12

▲ See Note 6 Below

**LEGEND**

	Sign
	Large Sign
	Traffic Flow

**DEPARTMENTAL MATERIAL SPECIFICATIONS**

PLYWOOD SIGN BLANKS	DMS-7100
ALUMINUM SIGN BLANKS	DMS-7110
SIGN FACE MATERIALS	DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B <sub>FL</sub> OR TYPE C <sub>FL</sub>
BLACK	LEGEND & BORDERS	NON-REFLECTIVE ACRYLIC FILM

**GENERAL NOTES**

- See BC and SMD sheets for additional sign support details.
- Sign locations shall be approved by the Engineer.
- For projects more than two miles in length, Give Us a BRAKE signs should be repeated halfway through the project. The Give Us a Brake (CW21-1T) may be used for this purpose.
- Work zone speed limits are sometimes used in conjunction with GIVE US A BRAKE signing. See BC(3) for location and spacing of construction speed zone signing when required.
- Give Us a Brake (CW21-1T) signs and supports shall be considered subsidiary to Item 502, "Barricades, Signs and Traffic Handling."
- The 96" X 48" Working For You Give Us A BRAKE (G20-7T) may use a 1/2" or 5/8" plywood substrate or 0.125" aluminum sheeting substrate and may be supported by two 4" x 6" wood posts with drilled holes for breakaway as per BC(5) and will be subsidiary to Item 502.
- The Working For You Give Us A BRAKE (G20-7T) 192" X 96" sign shall be paid for under the following specification items:  
Item 636 - Aluminum Signs  
Item 647 - Large Roadside Sign Supports and Assemblies.  
Item 416 - Drilled Shaft Foundations
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.

Texas Department of Transportation  
Traffic Operations Division Standard


**WORK ZONE  
"GIVE US A BRAKE"  
SIGNS**

**WZ (BRK) - 13**

FILE: wzbrk-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT August 1995	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
6-96 5-98 7-13	DIST	COUNTY	SHEET NO.	
8-96 3-03	HOU	FORT BEND	30	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

## WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS





### NOTES:

- Short term pavement markings may be prefabricated markings (stick down tape) or temporary flexible reflective roadway marker tabs unless otherwise specified elsewhere in plans.
- Short term pavement markings shall NOT be used to simulate edge lines.
- Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.
- Temporary flexible-reflective roadway marker tabs will require normal maintenance replacement when used on roadways with an ADT per lane of up to 7500 vehicles with no more than 10% truck mix. When roadways exceed these values, additional maintenance replacement of devices should be planned.
- No segment of roadway open to traffic shall remain without permanent pavement markings for a period greater than 14 calendar days. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
- For two lane, two-way roadways, DO NOT PASS signs shall be erected to mark the beginning of sections where passing is prohibited and PASS WITH CARE signs shall be erected to mark the beginning of sections where passing is permitted. Signs shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and may be used to indicate the limits of no-passing zones for up to 14 calendar days. Permanent pavement markings should then be placed.
- For low volume two lane, two-way roadways of 4000 ADT or less, no-passing lines may be omitted when approved by the Engineer. DO NOT PASS and PASS WITH CARE signs shall be erected (see note 6).
- For exit gores where a lane is being dropped place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are not allowed for this purpose.

### TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS (TABS)

- Temporary flexible-reflective roadway marker tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
- Tabs shall meet requirements of Departmental Material Specification DMS-8242.
- When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
- No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 3.

## WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS



If raised pavement markers are used to supplement REMOVABLE short term markings, the markers shall be applied to the top of the tape at the approximate mid length of the tape. This allows an easier removal of raised markers and tape.

### PREFABRICATED PAVEMENT MARKINGS

- Temporary Removable Prefabricated Pavement Markings shall meet the requirements of DMS-8241.
- Non-removable Prefabricated Pavement Markings shall meet the requirements of either DMS-8240 "Permanent Prefabricated Pavement Markings" or DMS-8243 "Temporary Construction-Grade Prefabricated Pavement Markings."

### RAISED PAVEMENT MARKERS

- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and DMS-4200.

### DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)

- DMSs referenced above can be found along with embedded links to their respective MPLs at the following website:

[http://www.txdot.gov/business/contractors\\_consultants/material\\_specifications/default.htm](http://www.txdot.gov/business/contractors_consultants/material_specifications/default.htm)



## WORK ZONE SHORT TERM PAVEMENT MARKINGS


### WZ(STPM)-23

FILE: wzsstpm-23.dgn	DWG: 0912	SECT: 34	JOB: 185	CK: PR 72
© TxDOT February 2023	REV. NO. 4-92	REV. DATE 7-13	DIST. COUNTY	SHEET NO.
	1-87	2-23	HOU FORT BEND	31
	3-03			

DATE: 06/07/2023 11:06 AM  
FILE: DOCUMENT NAME

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:07 AM  
 FILE: DOCUMENT NAME



**NOTES:**

1. Length of Safety Glare screen will be specified elsewhere in the plans.
2. The cumulative nominal length of the modular safety glare screen units shall equal the length of the individual sections of temporary concrete traffic barrier on which they are installed so the joint between barrier sections will not be spanned by any one safety glare screen unit.
3. Screen Panel/blades will be designed such that reflective sheeting conforming with Departmental Material Specification DMS-8300, Sign Face Materials, Type B or C Yellow, minimum size of 2 inches by 12 inches can be attached to the edge of the panel/blade. The sheeting shall be attached to one glare screen panel/blade per section of concrete barrier not to exceed a spacing of 30 feet. Barrier reflectors are not necessary when panel/blades are installed with reflective sheeting as described.
4. Payment for these devices will be under statewide Special Specification "Modular Glare Screens for Headlight Barrier."
5. This detail is only intended to show types of locations where Glare Screens would be appropriate. Required signing and other devices shall be as shown elsewhere in the plans.


**BARRIER DELINEATION WITH MODULAR GLARE SCREENS**

LEGEND	
	Type 3 Barricade
	Channelizing Devices
	Trailer Mounted Flashing Arrow Board
	Sign
	Safety glare screen

DEPARTMENTAL MATERIAL SPECIFICATIONS	
SIGN FACE MATERIALS	DMS-8300
DELINEATORS AND OBJECT MARKERS	DMS-8600
MODULAR GLARE SCREENS FOR HEADLIGHT BARRIER	DMS-8610

Only pre-qualified products shall be used. A copy of the Compliant Work Zone Traffic Control Devices List (CWZTCD) describes pre-qualified products and their sources and may be found at the following web address:

<http://www.txdot.gov/business/resources/producer-list.html>



**NOTES:**





1. When two-lane, two way traffic control must be maintained on one roadway of a normally divided highway, opposing traffic shall be separated with either temporary traffic barriers, channelizing devices, or a temporary raised island throughout the length of the two way operation. The above Typical Application is intended to show the appropriate application of channelizing devices when they are used for this purpose. This is not a traffic control plan. If this detail is to be used for other types of roads or applications, those locations should be stated elsewhere in the plans.
2. Space devices according to the Tangent Spacing shown on the Device Spacing table on BC(9) but not exceeding 100'.
3. Every fifth device should be an OTLD except when spaced closer to accommodate an intersection. An OTLD should be the first device on each side of intersecting streets or roads.
4. Locations where surface mount bases with adhesives or self-righting devices will be required in order to maintain them in their proper position should be noted elsewhere in the plans.
5. Channelizing devices are to be vertical panels, 42" cones or tubular markers that are at least 36" tall. Tubular markers used to separate traffic should have a rubber base weighing at least 30 pounds. Tubular markers that are 42" tall or more shall have four bands of reflective material as detailed for 42" cones on BC(10). Tubular markers less than 42" but at least 36" tall shall have three bands of 3" wide white reflective material spaced 2" apart. Reflective material shall meet DMS-8300, Type A.

**VERTICAL PANELS & OPPOSING TRAFFIC LANE DIVIDERS (OTLD) SEPARATING TWO-WAY TRAFFIC ON NORMALLY DIVIDED HIGHWAYS**

		Traffic Operations Division Standard	
<b>TRAFFIC CONTROL PLAN TYPICAL DETAILS</b>			
<b>WZ(TD) - 17</b>			
FILE:	wz1d-17.dgn	DN:	TxDOT
© TxDOT	February 1998	CK:	TxDOT
REVISIONS		OW:	TxDOT
4-98	2-17	CR:	TxDOT
3-03		CONT	SECT
7-13		0912	34
		JOB	185
		HIGHWAY	PR 72
		DIST	COUNTY
		HOU	FORT BEND
		SHEET NO.	32

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 06/07/2023 11:08 AM  
FILE: DOCUMENT NAME



DEPARTMENTAL MATERIAL SPECIFICATIONS	
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY (REMOVABLE) PREFABRICATED PAVEMENT MARKINGS	DMS-8241
SIGN FACE MATERIALS	DMS-8300

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B <sub>FL</sub> OR TYPE C <sub>FL</sub> SHEETING
BLACK	LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING

**GENERAL NOTES**

- If spalling or holes occur, ROUGH ROAD (CW8-8) signs should be placed in advance of the condition and be repeated every two miles where the condition persists.
- UNEVEN LANES (CW8-11) signs shall be installed in advance of the condition and repeated every mile. Signs installed along the uneven lane condition may be supplemented with the NEXT XX MILES (CW7-3aP) plaque or Advisory Speed (CW13-1P) plaque.
- NO CENTER LINE (CW8-12) signs and temporary pavement markings as per the WZ(STPM) standard shall be installed if yellow centerlines separating two way traffic are obscured or obliterated. Repeat NO CENTER LINE signs every two miles where the center line markings are not in place. The signs and markings shall remain in place until permanent pavement markings are installed.
- Signs shall be spaced at the distances recommended as per BC standards.
- Additional signs may be required as directed by the Engineer. Signs shall remain in place until final surface is applied. Signs shall be considered subsidiary to Item 502 "BARRICADES, SIGNS AND TRAFFIC HANDLING."
- Signs shall be fabricated and mounted on supports as shown on the BC standards and/or listed on the "Compliant Work Zone Traffic Control Devices" list.
- Short term markings shall not be used to simulate edge lines.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition.

TABLE 1		
Edge Condition	Edge Height (D)	* Warning Devices
①	Less than or equal to: 1/4" (maximum-planing) 1/2" (typical-overlay)	Sign: CW8-11
②	Less than or equal to 3"	Sign: CW8-11
③	Distance "D" may be a maximum of 3" if uneven lanes with edge condition 2 or 3 are open to traffic after work operations cease. Uneven lanes should not be open to traffic when "D" is greater than 3".	

**TRAFFIC CONTROL DURING PLANING, OVERLAY AND LEVELING OPERATIONS ARE SHOWN ELSEWHERE IN THE PLANS.**

MINIMUM WARNING SIGN SIZE	
Conventional roads	36" x 36"
Freeways/expressways, divided roadways	48" x 48"



**SIGNING FOR UNEVEN LANES**

**WZ (UL) - 13**

FILE: wzu1-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT	APRIL 1992	CONT	SECT	JOB
REVISIONS		0912	34	185
8-95	2-98	7-13	DIST	COUNTY
1-97	3-03	HOU	FORT BEND	SHEET NO. 33

<\* 1 DESCRIBE CHAIN PR72

Chain PR72 contains:

CUR PR721 CUR PR722 CUR PR723 PR101 CUR PR724 PR102 CUR PR725 CUR PR726 CUR PR-727 CUR PR728 CUR PR729 CUR PR7210 CUR PR7211 PR103 CUR PR7212 PR104 CUR PR7213- CUR PR7214 CUR PR7215 CUR PR7216 PR105 CUR PR7217 PR106 PR107 CUR PR7218 PR108- CUR PR7219 CUR PR7220 PR109 PR110 CUR PR7221 CUR PR7222 PR111 PR112

Beginning chain PR72 description

Curve Data
\*-----\*
Curve PR721
P.I. Station 136+24.36 N 13,697,941.2677 E 3,041,445.1714
Delta = 0° 46' 05.23" (RT)
Degree = 2° 54' 11.52"
Tangent = 13.2290
Length = 26.4577
Radius = 1,973.5381
External = 0.0443
Long Chord = 26.4575
Mid. Ord. = 0.0443
P.C. Station 136+11.13 N 13,697,943.9548 E 3,041,432.2181
P.T. Station 136+37.59 N 13,697,938.4072 E 3,041,458.0875
C.C. N 13,696,011.5574 E 3,041,031.3531
Back = S 78° 16' 49.92" E
Ahead = S 77° 30' 44.69" E
Chord Bear = S 77° 53' 47.31" E

Curve Data
\*-----\*
Curve PR722
P.I. Station 138+01.61 N 13,697,908.0335 E 3,041,619.2685
Delta = 33° 12' 38.41" (RT)
Degree = 10° 25' 02.69"
Tangent = 164.0179
Length = 318.7995
Radius = 550.0000
External = 23.9354
Long Chord = 314.3554
Mid. Ord. = 22.9372
P.C. Station 136+37.59 N 13,697,938.4072 E 3,041,458.0875
P.T. Station 139+56.39 N 13,697,794.3390 E 3,041,737.4862
C.C. N 13,697,397.9203 E 3,041,356.2353
Back = S 79° 19' 40.92" E
Ahead = S 46° 07' 02.51" E
Chord Bear = S 62° 43' 21.72" E

Course from PT PR722 to PC PR723 S 46° 07' 02.51" E Dist 179.6208

Curve Data
\*-----\*
Curve PR723
P.I. Station 143+17.01 N 13,697,544.3635 E 3,041,997.4068
Delta = 13° 45' 38.71" (LT)
Degree = 3° 49' 10.99"
Tangent = 180.9987
Length = 360.2557
Radius = 1,500.0000
External = 10.8807
Long Chord = 359.3905
Mid. Ord. = 10.8024
P.C. Station 141+36.01 N 13,697,669.8288 E 3,041,866.9499
P.T. Station 144+96.26 N 13,697,453.5309 E 3,042,153.9634
C.C. N 13,698,750.9706 E 3,042,906.7250
Back = S 46° 07' 02.51" E
Ahead = S 59° 52' 41.22" E
Chord Bear = S 52° 59' 51.87" E

Course from PT PR723 to PR101 S 59° 52' 41.22" E Dist 163.3548

Point PR101 N 13,697,371.5527 E 3,042,295.2587 Sta 146+59.62

Course from PR101 to PC PR724 S 61° 06' 19.08" E Dist 167.1948

Curve PR724
P.I. Station 150+32.69 N 13,697,191.2833 E 3,042,621.8876
Delta = 37° 52' 38.28" (RT)
Degree = 9° 32' 57.47"
Tangent = 205.8782
Length = 396.6501
Radius = 600.0000
External = 34.3389
Long Chord = 389.4666
Mid. Ord. = 32.4800
P.C. Station 148+26.81 N 13,697,290.7640 E 3,042,441.6393
P.T. Station 152+23.46 N 13,697,002.0931 E 3,042,703.0841
C.C. N 13,696,765.4584 E 3,042,151.7185
Back = S 61° 06' 19.08" E
Ahead = S 23° 13' 40.81" E
Chord Bear = S 42° 09' 59.95" E

Course from PT PR724 to PR102 S 23° 13' 40.81" E Dist 300.1326


Point PR102 N 13,696,726.2884 E 3,042,821.4537 Sta 155+23.60

Course from PR102 to PC PR725 S 24° 48' 44.99" E Dist 140.4053

Curve Data
\*-----\*
Curve PR725
P.I. Station 157+33.04 N 13,696,536.1763 E 3,042,909.3482
Delta = 5° 14' 07.59" (LT)
Degree = 3° 47' 38.94"
Tangent = 69.0416
Length = 137.9872
Radius = 1,510.1084
External = 1.5775
Long Chord = 137.9392
Mid. Ord. = 1.5758
P.C. Station 156+64.00 N 13,696,598.8445 E 3,042,880.3748
P.T. Station 158+01.99 N 13,696,476.4134 E 3,042,943.9190
C.C. N 13,697,232.5615 E 3,044,251.0790
Back = S 24° 48' 44.99" E
Ahead = S 30° 02' 52.58" E
Chord Bear = S 27° 25' 48.78" E

Curve Data
\*-----\*
Curve PR726
P.I. Station 159+28.12 N 13,696,367.0455 E 3,043,006.7572
Delta = 26° 39' 17.58" (LT)
Degree = 10° 45' 38.93"
Tangent = 126.1348
Length = 247.7032
Radius = 532.4484
External = 14.7365
Long Chord = 245.4755
Mid. Ord. = 14.3396
P.C. Station 158+01.99 N 13,696,476.4134 E 3,042,943.9190
P.T. Station 160+49.69 N 13,696,297.4909 E 3,043,111.9814
C.C. N 13,696,741.6702 E 3,043,405.5900
Back = S 29° 52' 47.53" E
Ahead = S 56° 32' 05.11" E
Chord Bear = S 43° 12' 26.32" E

Curve Data
\*-----\*
Curve PR727
P.I. Station 161+94.18 N 13,696,218.7463 E 3,043,233.1231
Delta = 42° 14' 35.53" (LT)
Degree = 15° 19' 07.68"
Tangent = 144.4854
Length = 275.7605
Radius = 374.0226
External = 26.9374
Long Chord = 269.5570
Mid. Ord. = 25.1277
P.C. Station 160+49.69 N 13,696,297.4909 E 3,043,111.9814
P.T. Station 163+25.45 N 13,696,241.8929 E 3,043,375.7424
C.C. N 13,696,611.0849 E 3,043,315.8238
Back = S 56° 58' 31.15" E
Ahead = N 80° 46' 53.32" E
Chord Bear = S 78° 05' 48.91" E



Glenn Lazaro, P.E.
07/01/2023



HORIZONTAL ALIGNMENT DATA SHEET

SHEET 1 OF 6

Table with project details: FED. RD. DIV. NO. 6, PROJECT NO., SHEET NO. 34, STATE TEXAS, DIST HOU, COUNTY FORT BEND, CONT 0912, SECT 34, JOB 185, HIGHWAY PR 72.



Curve Data

Curve PR728

```

P.I. Station      164+52.92  N   13,696,269.5944  E   3,043,500.1641
Delta            = 32° 37' 28.31" (LT)
Degree           = 13° 09' 16.11"
Tangent          = 127.4682
Length           = 248.0109
Radius           = 435.5611
External         = 18.2688
Long Chord       = 244.6740
Mid. Ord.        = 17.5334
P.C. Station     163+25.45  N   13,696,241.8929  E   3,043,375.7424
P.T. Station     165+73.46  N   13,696,360.0049  E   3,043,590.0200
C.C.             = N   13,696,667.0442  E   3,043,281.0858
Back             = N 77° 26' 53.77" E
Ahead            = N 44° 49' 25.46" E
Chord Bear       = N 61° 08' 09.61" E

```

Curve Data

Curve PR729

```

P.I. Station      166+49.73  N   13,696,410.1886  E   3,043,647.4512
Delta            = 15° 23' 50.49" (LT)
Degree           = 10° 09' 19.82"
Tangent          = 76.2675
Length           = 151.6159
Radius           = 564.1844
External         = 5.1317
Long Chord       = 151.1601
Mid. Ord.        = 5.0854
P.C. Station     165+73.46  N   13,696,360.0049  E   3,043,590.0200
P.T. Station     167+25.08  N   13,696,473.8196  E   3,043,689.4966
C.C.             = N   13,696,784.8484  E   3,043,218.7896
Back             = N 48° 51' 10.32" E
Ahead            = N 33° 27' 19.83" E
Chord Bear       = N 41° 09' 15.08" E

```

Course from PT PR729 to PC PR7210 N 31° 32' 26.39" E Dist 53.6872

Curve Data

Curve PR7210

```

P.I. Station      168+93.17  N   13,696,620.6341  E   3,043,771.2101
Delta            = 21° 58' 30.05" (RT)
Degree           = 9° 43' 24.11"
Tangent          = 114.4070
Length           = 226.0022
Radius           = 589.2589
External         = 11.0036
Long Chord       = 224.6195
Mid. Ord.        = 10.8018
P.C. Station     167+78.77  N   13,696,519.5755  E   3,043,717.5806
P.T. Station     170+04.77  N   13,696,694.2822  E   3,043,858.7596
C.C.             = N   13,696,243.3542  E   3,044,238.0878
Back             = N 27° 57' 13.94" E
Ahead            = N 49° 55' 44.00" E
Chord Bear       = N 38° 56' 28.97" E

```

Curve Data

Curve PR7211

```

P.I. Station      171+69.77  N   13,696,787.0536  E   3,043,995.2053
Delta            = 30° 14' 13.12" (RT)
Degree           = 9° 22' 53.93"
Tangent          = 164.9969
Length           = 322.2993
Radius           = 610.7220
External         = 21.8958
Long Chord       = 318.5722
Mid. Ord.        = 21.1380
P.C. Station     170+04.77  N   13,696,694.2822  E   3,043,858.7596
P.T. Station     173+27.07  N   13,696,798.4924  E   3,044,159.8052
C.C.             = N   13,696,189.2398  E   3,044,202.1449
Back             = N 55° 47' 15.63" E
Ahead            = N 86° 01' 28.75" E
Chord Bear       = N 70° 54' 22.19" E

```

Course from PT PR7211 to PR103 N 86° 36' 47.23" E Dist 144.3724

Point PR103 N 13,696,807.0216 E 3,044,303.9255 Sta 174+71.44

Course from PR103 to PC PR7212 N 87° 23' 54.81" E Dist 5,433.1886

Curve Data

Curve PR7212

```

P.I. Station      229+22.19  N   13,697,054.4210  E   3,049,749.0584
Delta            = 2° 00' 43.99" (RT)
Degree           = 5° 43' 46.48"
Tangent          = 17.5617
Length           = 35.1198
Radius           = 1,000.0000
External         = 0.1542
Long Chord       = 35.1180
Mid. Ord.        = 0.1542
P.C. Station     229+04.63  N   13,697,053.6239  E   3,049,731.5148
P.T. Station     229+39.75  N   13,697,054.6016  E   3,049,766.6192
C.C.             = N   13,696,054.6545  E   3,049,776.9029
Back             = N 87° 23' 54.81" E
Ahead            = N 89° 24' 38.79" E
Chord Bear       = N 88° 24' 16.80" E

```

Course from PT PR7212 to PR104 N 89° 24' 38.80" E Dist 282.4326

Point PR104 N 13,697,057.5060 E 3,050,049.0369 Sta 232+22.18

Course from PR104 to PC PR7213 N 89° 02' 16.03" E Dist 178.7129

Curve Data

Curve PR7213

```

P.I. Station      235+26.54  N   13,697,062.6171  E   3,050,353.3530
Delta            = 8° 58' 49.11" (LT)
Degree           = 3° 34' 51.55"
Tangent          = 125.6461
Length           = 250.7775
Radius           = 1,600.0000
External         = 4.9258
Long Chord       = 250.5209
Mid. Ord.        = 4.9107
P.C. Station     234+00.89  N   13,697,060.5072  E   3,050,227.7246
P.T. Station     236+51.67  N   13,697,084.3112  E   3,050,477.1121
C.C.             = N   13,698,660.2815  E   3,050,200.8558
Back             = N 89° 02' 16.03" E
Ahead            = N 80° 03' 26.92" E
Chord Bear       = N 84° 32' 51.47" E

```

Course from PT PR7213 to PC PR7214 N 79° 18' 33.28" E Dist 299.4964

Curve Data


Curve PR7214

```

P.I. Station      240+30.39  N   13,697,155.6948  E   3,050,849.0361
Delta            = 11° 18' 39.32" (LT)
Degree           = 7° 09' 43.10"
Tangent          = 79.2226
Length           = 157.9303
Radius           = 800.0000
External         = 3.9131
Long Chord       = 157.6739
Mid. Ord.        = 3.8940
P.C. Station     239+51.17  N   13,697,139.8702  E   3,050,771.4101
P.T. Station     241+09.10  N   13,697,186.4371  E   3,050,922.0507
C.C.             = N   13,697,923.7479  E   3,050,611.6110
Back             = N 78° 28' 39.84" E
Ahead            = N 67° 10' 00.52" E
Chord Bear       = N 72° 49' 20.18" E

```

Course from PT PR7214 to PC PR7215 N 67° 10' 00.52" E Dist 81.1711



HORIZONTAL ALIGNMENT DATA SHEET

SHEET 2 OF 6

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			35
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

Curve Data

\*-----\*

Curve PR7215  
P.I. Station = 242+68.05 N 13,697,248.1185 E 3,051,068.5474  
Delta = 17° 41' 03.96" (RT)  
Degree = 11° 27' 32.96"  
Tangent = 77.7814  
Length = 154.3258  
Radius = 500.0000  
External = 6.0138  
Long Chord = 153.7139  
Mid. Ord. = 5.9423  
P.C. Station = 241+90.27 N 13,697,217.9355 E 3,050,996.8610  
P.T. Station = 243+44.60 N 13,697,255.0988 E 3,051,146.0149  
C.C. = N 13,696,757.1162 E 3,051,190.8858  
Back = N 67° 10' 00.52" E  
Ahead = N 84° 51' 04.48" E  
Chord Bear = N 76° 00' 32.50" E

Course from PT PR7215 to PC PR7216 N 84° 51' 04.48" E Dist 31.7837

Curve Data

\*-----\*

Curve PR7216  
P.I. Station = 245+69.91 N 13,697,275.3190 E 3,051,370.4215  
Delta = 85° 19' 34.14" (LT)  
Degree = 27° 17' 01.34"  
Tangent = 193.5320  
Length = 312.7367  
Radius = 210.0000  
External = 75.5777  
Long Chord = 284.6281  
Mid. Ord. = 55.5762  
P.C. Station = 243+76.38 N 13,697,257.9511 E 3,051,177.6704  
P.T. Station = 246+89.12 N 13,697,468.8444 E 3,051,368.8174  
C.C. = N 13,697,467.1038 E 3,051,158.8246  
Back = N 84° 51' 04.48" E  
Ahead = N 0° 28' 29.66" W  
Chord Bear = N 42° 11' 17.41" E

Course from PT PR7216 to PR105 N 0° 28' 29.66" W Dist 64.8590

Point PR105 N 13,697,533.7012 E 3,051,368.2798 Sta 247+53.97

Course from PR105 to PC PR7217 N 1° 23' 48.98" E Dist 97.1412

Curve Data

\*-----\*

Curve PR7217  
P.I. Station = 249+27.36 N 13,697,707.0458 E 3,051,372.0017  
Delta = 29° 39' 36.04" (RT)  
Degree = 19° 53' 49.03"  
Tangent = 76.2443  
Length = 149.0681  
Radius = 287.9626  
External = 9.9227  
Long Chord = 147.4092  
Mid. Ord. = 9.5922  
P.C. Station = 248+51.12 N 13,697,630.8135 E 3,051,370.6480  
P.T. Station = 250+00.18 N 13,697,772.6201 E 3,051,410.9019  
C.C. = N 13,697,625.7006 E 3,051,658.5651  
Back = N 1° 01' 02.54" E  
Ahead = N 30° 40' 38.58" E  
Chord Bear = N 15° 50' 50.56" E

Course from PT PR7217 to PR106 N 33° 47' 30.26" E Dist 31.0824

Point PR106 N 13,697,798.4515 E 3,051,428.1891 Sta 250+31.27

Course from PR106 to PR107 N 34° 57' 07.71" E Dist 28.6612

Point PR107 N 13,697,821.9431 E 3,051,444.6089 Sta 250+59.93

Course from PR107 to PC PR7218 N 36° 23' 28.71" E Dist 52.1465

Curve Data

\*-----\*

Curve PR7218  
P.I. Station = 251+90.79 N 13,697,927.2872 E 3,051,522.2506  
Delta = 19° 50' 40.85" (LT)  
Degree = 12° 43' 56.62"  
Tangent = 78.7184  
Length = 155.8597  
Radius = 450.0000  
External = 6.8332  
Long Chord = 155.0819  
Mid. Ord. = 6.7310  
P.C. Station = 251+12.07 N 13,697,863.9202 E 3,051,475.5472  
P.T. Station = 252+67.93 N 13,698,002.7457 E 3,051,544.6692  
C.C. = N 13,698,130.9037 E 3,051,113.3045  
Back = N 36° 23' 28.71" E  
Ahead = N 16° 32' 47.86" E  
Chord Bear = N 26° 28' 08.28" E

Course from PT PR7218 to PR108 N 16° 32' 47.86" E Dist 85.1935

Point PR108 N 13,698,084.4112 E 3,051,568.9319 Sta 253+53.13

Course from PR108 to PC PR7219 N 17° 58' 35.39" E Dist 5.5426

Curve Data

\*-----\*

Curve PR7219  
P.I. Station = 255+75.20 N 13,698,295.6396 E 3,051,637.4684  
Delta = 11° 14' 31.30" (RT)  
Degree = 2° 36' 15.67"  
Tangent = 216.5265  
Length = 431.6629  
Radius = 2,200.0000  
External = 10.6297  
Long Chord = 430.9708  
Mid. Ord. = 10.5786  
P.C. Station = 253+58.67 N 13,698,089.6832 E 3,051,570.6425  
P.T. Station = 257+90.33 N 13,698,484.6163 E 3,051,743.1641  
C.C. = N 13,697,410.7041 E 3,053,663.2456  
Back = N 17° 58' 35.39" E  
Ahead = N 29° 13' 06.69" E  
Chord Bear = N 23° 35' 51.04" E

Course from PT PR7219 to PC PR7220 N 29° 13' 06.69" E Dist 270.5040

Curve Data

\*-----\*

Curve PR7220  
P.I. Station = 262+98.64 N 13,698,928.2485 E 3,051,991.2901  
Delta = 7° 46' 25.79" (LT)  
Degree = 1° 38' 13.28"  
Tangent = 237.8031  
Length = 474.8764  
Radius = 3,500.0000  
External = 8.0693  
Long Chord = 474.5122  
Mid. Ord. = 8.0508  
P.C. Station = 260+60.84 N 13,698,720.7025 E 3,051,875.2084  
P.T. Station = 265+35.71 N 13,699,149.5887 E 3,052,078.2316  
C.C. = N 13,700,429.1990 E 3,048,820.5334  
Back = N 29° 13' 06.69" E  
Ahead = N 21° 26' 40.90" E  
Chord Bear = N 25° 19' 53.79" E

Course from PT PR7220 to PR109 N 20° 50' 22.58" E Dist 369.1538

Point PR109 N 13,699,494.5925 E 3,052,209.5592 Sta 269+04.87

Course from PR109 to PR110 N 20° 00' 39.22" E Dist 522.4410

Point PR110 N 13,699,985.4924 E 3,052,388.3379 Sta 274+27.31

Course from PR110 to PC PR7221 N 18° 04' 37.49" E Dist 68.9910



HORIZONTAL ALIGNMENT DATA SHEET

SHEET 3 OF 6

FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
6				36
STATE	DIST	COUNTY		
TEXAS	HOU	FORT BEND		
CONT	SECT	JOB	HIGHWAY	
0912	34	185	PR 72	

PR 72

Curve Data

Curve PR7221

```

P.I. Station      275+72.46 N      13,700,123.4755 E      3,052,433.3766
Delta            = 37° 35' 32.94" (LT)
Degree           = 25° 36' 22.73"
Tangent         = 76.1565
Length          = 146.8094
Radius          = 223.7565
External        = 12.6051
Long Chord      = 144.1903
Mid. Ord.       = 11.9328
P.C. Station     274+96.30 N      13,700,051.0781 E      3,052,409.7455
P.T. Station     276+43.11 N      13,700,195.2570 E      3,052,407.9358
C.C.            = N      13,700,120.5089 E      3,052,197.0337
Back            = N 18° 04' 37.49" E
Ahead           = N 19° 30' 55.44" W
Chord Bear     = N 0° 43' 08.97" W

```

Curve Data

Curve PR7222

```

P.I. Station      277+43.14 N      13,700,287.4839 E      3,052,369.2001
Delta            = 51° 10' 18.35" (LT)
Degree           = 27° 25' 32.12"
Tangent         = 100.0313
Length          = 186.5840
Radius          = 208.9136
External        = 22.7136
Long Chord      = 180.4443
Mid. Ord.       = 20.4863
P.C. Station     276+43.11 N      13,700,195.2570 E      3,052,407.9358
P.T. Station     278+29.69 N      13,700,315.1329 E      3,052,273.0658
C.C.            = N      13,700,114.3582 E      3,052,215.3215
Back            = N 22° 46' 57.36" W
Ahead           = N 73° 57' 15.71" W
Chord Bear     = N 48° 22' 06.53" W

```

Course from PT PR7222 to PR111 N 73° 57' 15.71" W Dist 37.1901

Point PR111 N 13,700,325.4124 E 3,052,237.3245 Sta 278+66.88

Course from PR111 to PR112 N 83° 15' 46.01" W Dist 167.9258

Point PR112 N 13,700,345.1127 E 3,052,070.5583 Sta 280+34.81

Ending chain PR72 description

PR 72 ENTRANCE

<\* 1 DESCRIBE CHAIN PR\_ENT

Chain PR\_ENT contains:

PRENT100 CUR PR\_ENT1 CUR PR\_ENT2 CUR PR\_ENT3 CUR PR\_ENT4 PRENT101 PRENT102 CUR PR\_ENT5 CUR PR\_ENT6 CUR PR\_ENT7 CUR PR\_ENT8 CUR PR\_ENT9 CUR PR\_ENT10

Beginning chain PR\_ENT description

Point PRENT100 N 13,697,967.5396 E 3,038,043.1998 Sta 100+00.00

Course from PRENT100 to PC PR\_ENT1 S 85° 10' 09.06" E Dist 182.2173

Curve Data

Curve PR\_ENT1

```

P.I. Station      102+00.97 N      13,697,950.1005 E      3,038,243.4102
Delta            = 4° 17' 48.85" (RT)
Degree           = 11° 27' 32.96"
Tangent         = 18.7576
Length          = 37.4976
Radius          = 500.0000
External        = 0.3517
Long Chord      = 37.4888
Mid. Ord.       = 0.3515
P.C. Station     101+82.22 N      13,697,952.1944 E      3,038,224.7698
P.T. Station     102+19.71 N      13,697,946.6159 E      3,038,261.8412
C.C.            = N      13,697,455.3193 E      3,038,168.9558
Back            = S 83° 35' 26.97" E
Ahead           = S 79° 17' 38.12" E
Chord Bear     = S 81° 26' 32.55" E

```

Course from PT PR\_ENT1 to PC PR\_ENT2 S 79° 17' 38.12" E Dist 127.2521

Curve Data

Curve PR\_ENT2

```

P.I. Station      104+73.87 N      13,697,899.4010 E      3,038,511.5736
Delta            = 23° 53' 05.68" (LT)
Degree           = 9° 32' 57.47"
Tangent         = 126.9042
Length          = 250.1222
Radius          = 600.0000
External        = 13.2737
Long Chord      = 248.3150
Mid. Ord.       = 12.9864
P.C. Station     103+46.97 N      13,697,922.9761 E      3,038,386.8783
P.T. Station     105+97.09 N      13,697,928.3341 E      3,038,635.1355
C.C.            = N      13,698,512.5320 E      3,038,498.3408
Back            = S 79° 17' 38.12" E
Ahead           = N 76° 49' 16.20" E
Chord Bear     = N 88° 45' 49.04" E

```

Course from PT PR\_ENT2 to PC PR\_ENT3 N 76° 49' 16.20" E Dist 220.0171

Curve Data


Curve PR\_ENT3

```

P.I. Station      110+39.47 N      13,698,029.1922 E      3,039,065.8621
Delta            = 20° 59' 44.50" (RT)
Degree           = 4° 46' 28.73"
Tangent         = 222.3602
Length          = 439.7328
Radius          = 1,200.0000
External        = 20.4278
Long Chord      = 437.2766
Mid. Ord.       = 20.0859
P.C. Station     108+17.11 N      13,697,978.4961 E      3,038,849.3581
P.T. Station     112+56.84 N      13,697,998.9496 E      3,039,286.1561
C.C.            = N      13,696,810.1002 E      3,039,122.9475
Back            = N 76° 49' 16.20" E
Ahead           = S 82° 10' 59.30" E
Chord Bear     = N 87° 19' 08.45" E

```

Course from PT PR\_ENT3 to PC PR\_ENT4 S 82° 10' 59.30" E Dist 229.9071



Glenn Lazaro, P.E. 07/01/2023



HORIZONTAL ALIGNMENT DATA SHEET

SHEET 4 OF 6

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			37
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$ FILE: \$FILE\$

**PR 72 ENTRANCE**

Curve Data

```

*-----*
Curve PR_ENT4
P.I. Station      118+65.08  N   13,697,916.2243  E   3,039,888.7468
Delta            = 30° 14' 41.07" (LT)
Degree           = 4° 05' 33.20"
Tangent          = 378.3355
Length           = 739.0185
Radius           = 1,400.0000
External         = 50.2199
Long Chord       = 730.4681
Mid. Ord.        = 48.4808
P.C. Station     114+86.75  N   13,697,967.6806  E   3,039,513.9268
P.T. Station     122+25.76  N   13,698,060.5670  E   3,040,238.4651
C.C.             N   13,699,354.6716  E   3,039,704.3368
Back            = S 82° 10' 59.30" E
Ahead           = N 67° 34' 19.63" E
Chord Bear      = N 82° 41' 40.17" E
    
```

Course from PT PR\_ENT4 to PRENT101 N 67° 34' 19.63" E Dist 98.3699

Point PRENT101 N 13,698,098.0971 E 3,040,329.3944 Sta 123+24.13

Course from PRENT101 to PRENT102 N 66° 23' 45.70" E Dist 116.9891

Point PRENT102 N 13,698,144.9410 E 3,040,436.5957 Sta 124+41.12

Course from PRENT102 to PC PR\_ENT5 N 69° 31' 07.31" E Dist 50.5610

Curve Data  
\*-----\*

```

Curve PR_ENT5
P.I. Station      125+59.02  N   13,698,186.1926  E   3,040,547.0379
Delta            = 25° 18' 08.36" (RT)
Degree           = 19° 06' 00.46"
Tangent          = 67.3339
Length           = 132.4720
Radius           = 299.9759
External         = 7.4642
Long Chord       = 131.3982
Mid. Ord.        = 7.2829
P.C. Station     124+91.68  N   13,698,162.6324  E   3,040,483.9605
P.T. Station     126+24.16  N   13,698,180.5336  E   3,040,614.1336
C.C.             N   13,697,881.6190  E   3,040,588.9226
Back            = N 69° 31' 07.31" E
Ahead           = S 85° 10' 44.33" E
Chord Bear      = N 82° 10' 11.49" E
    
```

Course from PT PR\_ENT5 to PC PR\_ENT6 S 85° 10' 44.33" E Dist 34.1246

Curve Data  
\*-----\*

```

Curve PR_ENT6
P.I. Station      127+16.68  N   13,698,168.2091  E   3,040,705.7654
Delta            = 30° 01' 48.75" (RT)
Degree           = 26° 18' 59.61"
Tangent          = 58.3988
Length           = 114.1115
Radius           = 217.7176
External         = 7.6962
Long Chord       = 112.8098
Mid. Ord.        = 7.4334
P.C. Station     126+58.28  N   13,698,177.6657  E   3,040,648.1374
P.T. Station     127+72.39  N   13,698,131.1817  E   3,040,750.9250
C.C.             N   13,697,962.8215  E   3,040,612.8823
Back            = S 80° 40' 51.76" E
Ahead           = S 50° 39' 03.01" E
Chord Bear      = S 65° 39' 57.38" E
    
```

Course from PT PR\_ENT6 to PC PR\_ENT7 S 50° 39' 03.01" E Dist 24.1995

Curve Data

```

*-----*
Curve PR_ENT7
P.I. Station      128+32.20  N   13,698,093.2635  E   3,040,797.1710
Delta            = 15° 49' 04.59" (RT)
Degree           = 22° 21' 20.76"
Tangent          = 35.6042
Length           = 70.7555
Radius           = 256.2908
External         = 2.4613
Long Chord       = 70.5310
Mid. Ord.        = 2.4379
P.C. Station     127+96.59  N   13,698,115.8381  E   3,040,769.6384
P.T. Station     128+67.35  N   13,698,064.0388  E   3,040,817.5076
C.C.             N   13,697,917.6494  E   3,040,607.1386
Back            = S 50° 39' 03.01" E
Ahead           = S 34° 49' 58.42" E
Chord Bear      = S 42° 44' 30.72" E
    
```

Course from PT PR\_ENT7 to PC PR\_ENT8 S 33° 22' 06.23" E Dist 159.8636

Curve Data  
\*-----\*

```

Curve PR_ENT8
P.I. Station      131+22.10  N   13,697,851.2848  E   3,040,957.6247
Delta            = 50° 45' 42.76" (LT)
Degree           = 28° 38' 52.40"
Tangent          = 94.8855
Length           = 177.1924
Radius           = 200.0000
External         = 21.3668
Long Chord       = 171.4538
Mid. Ord.        = 19.3044
P.C. Station     130+27.21  N   13,697,930.5285  E   3,040,905.4358
P.T. Station     132+04.40  N   13,697,841.5812  E   3,041,052.0126
C.C.             N   13,698,040.5326  E   3,041,072.4660
Back            = S 33° 22' 06.23" E
Ahead           = S 84° 07' 48.99" E
Chord Bear      = S 58° 44' 57.61" E
    
```

Course from PT PR\_ENT8 to PC PR\_ENT9 S 84° 07' 48.99" E Dist 73.8333

Curve Data  
\*-----\*

```

Curve PR_ENT9
P.I. Station      133+55.45  N   13,697,826.1341  E   3,041,202.2673
Delta            = 42° 13' 11.28" (LT)
Degree           = 28° 38' 52.40"
Tangent          = 77.2133
Length           = 147.3749
Radius           = 200.0000
External         = 14.3872
Long Chord       = 144.0632
Mid. Ord.        = 13.4217
P.C. Station     132+78.24  N   13,697,834.0305  E   3,041,125.4588
P.T. Station     134+25.61  N   13,697,871.8998  E   3,041,264.4557
C.C.             N   13,698,032.9819  E   3,041,145.9122
Back            = S 84° 07' 48.99" E
Ahead           = N 53° 38' 59.73" E
Chord Bear      = N 74° 45' 35.37" E
    
```


Course from PT PR\_ENT9 to PC PR\_ENT10 N 53° 38' 59.73" E Dist 62.9873

Curve Data  
\*-----\*

```

Curve PR_ENT10
P.I. Station      135+53.00  N   13,697,946.7091  E   3,041,367.5651
Delta            = 43° 36' 20.42" (RT)
Degree           = 35° 35' 14.79"
Tangent          = 64.4046
Length           = 122.5311
Radius           = 161.0000
External         = 12.4040
Long Chord       = 119.5952
Mid. Ord.        = 11.5167
P.C. Station     134+88.60  N   13,697,909.2335  E   3,041,315.1864
P.T. Station     136+11.13  N   13,697,937.7202  E   3,041,431.3394
C.C.             N   13,697,778.2961  E   3,041,408.8688
Back            = N 54° 25' 02.02" E
Ahead           = S 81° 58' 37.56" E
Chord Bear      = N 76° 13' 12.23" E
    
```

=====  
Ending chain PR\_ENT description



*Glenn Lazaro, P.E.*  
07/01/2023



**HORIZONTAL  
ALIGNMENT  
DATA  
SHEET**

SHEET 5 OF 6

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			38
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

**PR 72 EXIT**

<\* 1 DESCRIBE CHAIN PR\_EXT

Chain PR\_EXT contains:  
PREXT100 CUR PR\_EXT1 CUR PR\_EXT2 PREXT101 PREXT102

Beginning chain PR\_EXT description

Point PREXT100 N 13,698,188.5460 E 3,040,614.7477 Sta 126+24.10

Course from PREXT100 to PC PR\_EXT1 S 85° 36' 59.85" E Dist 250.6437

Curve Data  
\*-----\*

Curve PR\_EXT1  
P.I. Station = 129+78.24 N 13,698,161.4793 E 3,040,967.8506  
Delta = 44° 33' 33.42" (RT)  
Degree = 22° 40' 55.83"  
Tangent = 103.4951  
Length = 196.4507  
Radius = 252.6027  
External = 20.3796  
Long Chord = 191.5372  
Mid. Ord. = 18.8582  
P.C. Station = 128+74.74 N 13,698,169.3894 E 3,040,864.6583  
P.T. Station = 130+71.19 N 13,698,083.4386 E 3,041,035.8277  
C.C. = N 13,697,917.5256 E 3,040,845.3520  
Back = S 85° 36' 59.85" E  
Ahead = S 41° 03' 26.43" E  
Chord Bear = S 63° 20' 13.14" E

Course from PT PR\_EXT1 to PC PR\_EXT2 S 41° 53' 28.47" E Dist 46.2304

Curve Data  
\*-----\*

Curve PR\_EXT2  
P.I. Station = 131+82.62 N 13,697,999.8498 E 3,041,109.5012  
Delta = 41° 16' 54.36" (LT)  
Degree = 33° 06' 18.29"  
Tangent = 65.1946  
Length = 124.6992  
Radius = 173.0725  
External = 11.8719  
Long Chord = 122.0194  
Mid. Ord. = 11.1098  
P.C. Station = 131+17.42 N 13,698,049.0240 E 3,041,066.6966  
P.T. Station = 132+42.12 N 13,697,991.1375 E 3,041,174.1111  
C.C. = N 13,698,162.6577 E 3,041,197.2395  
Back = S 41° 02' 18.85" E  
Ahead = S 82° 19' 13.22" E  
Chord Bear = S 61° 40' 46.04" E

Course from PT PR\_EXT2 to PREXT101 S 83° 30' 28.60" E Dist 161.3536

Point PREXT101 N 13,697,972.8940 E 3,041,334.4300 Sta 134+03.48

Course from PREXT101 to PREXT102 S 79° 39' 16.00" E Dist 101.3954

Point PREXT102 N 13,697,954.6850 E 3,041,434.1770 Sta 135+04.87

Ending chain PR\_EXT description

**MAINTENANCE ROAD**

<\* 2 DESCRIBE CHAIN MAINTA

Chain MAINTA contains:  
MAINTEN100 CUR MAINTA1 CUR MAINTA2 MAINTEN101 CUR MAINTA3

Beginning chain MAINTA description

Point MAINTEN100 N 13,697,755.8871 E 3,051,401.7113 Sta 10+00.00

Course from MAINTEN100 to PC MAINTA1 S 46° 13' 55.61" E Dist 63.3765

Curve Data  
\*-----\*

Curve MAINTA1  
P.I. Station = 11+27.08 N 13,697,664.4960 E 3,051,489.8660  
Delta = 46° 01' 28.39" (LT)  
Degree = 38° 12' 07.75"  
Tangent = 63.7009  
Length = 120.4763  
Radius = 149.9805  
External = 12.9672  
Long Chord = 117.2633  
Mid. Ord. = 11.9353  
P.C. Station = 10+63.38 N 13,697,712.0471 E 3,051,447.4785  
P.T. Station = 11+83.85 N 13,697,661.9826 E 3,051,553.5173  
C.C. = N 13,697,811.8463 E 3,051,559.4350  
Back = S 41° 42' 50.95" E  
Ahead = S 87° 44' 19.34" E  
Chord Bear = S 64° 43' 35.14" E

Course from PT MAINTA1 to PC MAINTA2 S 87° 44' 19.34" E Dist 110.6277

Curve Data  
\*-----\*

Curve MAINTA2  
P.I. Station = 13+66.58 N 13,697,658.5377 E 3,051,736.1510  
Delta = 20° 26' 15.93" (RT)  
Degree = 14° 19' 32.91"  
Tangent = 72.0981  
Length = 142.6639  
Radius = 399.9480  
External = 6.4466  
Long Chord = 141.9088  
Mid. Ord. = 6.3443  
P.C. Station = 12+94.48 N 13,697,657.6176 E 3,051,664.0588  
P.T. Station = 14+37.14 N 13,697,634.2261 E 3,051,804.0264  
C.C. = N 13,697,257.7021 E 3,051,669.1632  
Back = N 89° 16' 07.45" E  
Ahead = S 70° 17' 36.62" E  
Chord Bear = S 80° 30' 44.58" E

Course from PT MAINTA2 to MAINTEN101 S 73° 29' 18.92" E Dist 52.4568


Point MAINTEN101 N 13,697,619.3176 E 3,051,854.3201 Sta 14+89.60

Course from MAINTEN101 to PC MAINTA3 S 72° 35' 07.52" E Dist 125.9550


Curve Data  
\*-----\*

Curve MAINTA3  
P.I. Station = 16+81.90 N 13,697,563.9934 E 3,052,038.4603  
Delta = 18° 50' 12.83" (LT)  
Degree = 14° 19' 32.91"  
Tangent = 66.3433  
Length = 131.4893  
Radius = 399.9480  
External = 5.4652  
Long Chord = 130.8979  
Mid. Ord. = 5.3915  
P.C. Station = 16+15.56 N 13,697,581.6213 E 3,051,974.5018  
P.T. Station = 17+47.05 N 13,697,567.9601 E 3,052,104.6848  
C.C. = N 13,697,967.1926 E 3,052,080.7713  
Back = S 74° 35' 27.43" E  
Ahead = N 86° 34' 19.74" E  
Chord Bear = S 84° 00' 33.84" E

Ending chain MAINTA description



*Glenn Lazaro, P.E.*  
07/01/2023





**HORIZONTAL ALIGNMENT DATA SHEET**

SHEET 6 OF 6

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			39
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
FILE: \$FILE\$

DATE: \$DATE\$  
 \$FILEL\$



*Glenn Lazaro, P.E.*  
 07/01/2023







### PR 72 HORIZONTAL ALIGNMENT LAYOUT SHEET

C PR 72 STA 10+00.00  
 TO STA 168+00.00  
 SCALE: 1" = 200' HORZ


SHEET 1 OF 3

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			40
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
 \$FILEL\$



*Glenn Lazaro, P.E.*  
 07/01/2023






**PR 72  
 HORIZONTAL  
 ALIGNMENT  
 LAYOUT  
 SHEET**

☉ PR 72 STA 168+00.00  
 TO STA 240+00.00  
 SCALE: 1" = 200' HORZ

SHEET 2 OF 3

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			41
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72





Glenn Lazaro, P.E.  
07/01/2023



**PR 72  
HORIZONTAL  
ALIGNMENT  
LAYOUT  
SHEET**



☉ PR 72 STA 240+00.00  
TO STA 280+34.81  
SCALE: 1" = 200' HORZ

SHEET 3 OF 3


FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			42
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
\$FILEL\$

DATE: \$DATE\$  
 \$FILEL\$



*Glenn Lazaro, P.E.*  
 07/01/2023



**CAMPING AREA  
 HORIZONTAL  
 ALIGNMENT  
 LAYOUT  
 SHEET**









SCALE: 1" = 200' HORZ



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			43
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

**PROPOSED TYPICAL SECTION**

PARK ENTRANCE - STA 127+72.39 TO STA 131+00.00  
 PARK EXIT - STA 128+00.00 TO STA 131+17.42

**LEGEND**

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM



*Glenn Lazaro, P.E.*  
 09/31/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.











**PR 72  
 PLAN SHEET**



PR 72 BEGIN OF PROJECT TO STA 148+00  
 SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			44
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
 \$FILEL\$

LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM



*Glenn Lazaro, P.E.*  
07/31/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.











PR 72  
PLAN SHEET



CL PR 72 STA 148+00  
TO STA 172+00  
SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			45
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
\$FILEL\$

LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM



*Glenn Lazaro, P.E.*  
 7/31/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.



## PR 72 PLAN SHEET


CL PR 72 STA 172+00  
TO STA 208+00

SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			46
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72


DATE: \$DATE\$  
\$FILEL\$

DATE: \$DATE\$  
 \$FILEL\$



**LEGEND**

	DIRECTION OF TRAVEL
	LIMITS OF IMPROVEMENT
	RE PM W/RET REQ TY I (W) (6") (SLD)
	RE PM W/RET REQ TY I (Y) (6") (SLD)
	RE PM TY I (W) (24") (SLD)
	REFL PAV MRK TY II A-A
	SILT CONTROL FENCE
	ROCK FILTER DAM



*Glenn Lazaro, P.E.*  
 07/31/2023  
 The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.














**PR 72  
 PLAN SHEET**

CL PR 72 STA 208+00  
 TO STA 244+00  
 SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			47
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM



Glenn Lazaro, P.E.  
07/31/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.



PR 72  
PLAN SHEET









☉ PR 72 STA 244+00  
TO STA 268+00  
SCALE: 1" = 100' HORZ



FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			48
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
\$FILEL\$



LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM



*Glenn Lazaro, P.E.*  
07/31/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.




PR 72  
PLAN SHEET

C PR 72 STA 268+00  
TO END OF PROJECT  
SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			49
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
\$FILEL\$

DATE: \$DATE\$  
 \$FILEL\$



BURR OAK  
 CAMPGROUNDS

- LEGEND
- DIRECTION OF TRAVEL
  - LIMITS OF IMPROVEMENT
  - RE PM W/RET REQ TY I (W) (6") (SLD)
  - RE PM W/RET REQ TY I (Y) (6") (SLD)
  - RE PM TY I (W) (24") (SLD)
  - REFL PAV MRK TY II A-A
  - SILT CONTROL FENCE
  - ROCK FILTER DAM

NOTES:  
 1. SEE PR 72 MISCELLANEOUS  
 SHEETS FOR PAVEMENT MARKING LIMITS  
 AT CAMPING BAYS.

STATE OF TEXAS  
 ★  
 GLENN C. LAZARO  
 113746  
 LICENSED  
 PROFESSIONAL ENGINEER  
*Glenn Lazaro, P.E.*  
 09/31/2023











PR 72  
 PLAN SHEET


BURR OAKS  
 CAMPGROUNDS  
 SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			50
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM

NOTES:  
 1. SEE PR 72 MISCELLANEOUS DETAIL SHEETS FOR PAVEMENT MARKING LIMITS AT CAMPING BAYS.




DATE: \$DATE\$  
 \$FILEL\$



PR 72  
 PLAN SHEET









RED BUCKEYE CAMPGROUNDS  
 SCALE: 1" = 100' HORZ



*Glenn Lazaro, P.E.*  
 07/31/2023


FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			51
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

LEGEND


-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM

NOTES:

1. SEE PR 72 MISCELLANEOUS DETAIL SHEETS FOR PAVEMENT MARKING LIMITS AT CAMPING BAYS.



RED BUCKEYE CAMPGROUNDS



*Glenn Lazaro, P.E.*  
08/31/2023











PR 72  
PLAN SHEET

RED BUCKEYE CAMPGROUNDS  
SCALE: 1" = 100' HORZ

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			52
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
\$FILEL\$


LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM

NOTES:  
 1. SEE PR 72 MISCELLANEOUS DETAIL SHEETS FOR PAVEMENT MARKING LIMITS AT CAMPING BAYS.

SEE PR 72 MISCELLANEOUS DETAIL SHEET FOR CAMPING BAY DETAILS (TYP.)

SEE REDD BUCKEYE CAMPGROUNDS LAYOUT SHEET



SHELTER AREA

SEE PR 72 MISCELLANEOUS DETAIL SHEET FOR CAMPING BAY DETAILS (TYP.)



PR 72  
PLAN SHEET









SHELTER CAMPGROUNDS  
 SCALE: 1" = 100' HORZ



  
 Glenn Lazaro, P.E.  
 07/31/2023

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			53
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
 \$FILEL\$

LEGEND

-  DIRECTION OF TRAVEL
-  LIMITS OF IMPROVEMENT
-  RE PM W/RET REQ TY I (W) (6") (SLD)
-  RE PM W/RET REQ TY I (Y) (6") (SLD)
-  RE PM TY I (W) (24") (SLD)
-  REFL PAV MRK TY II A-A
-  SILT CONTROL FENCE
-  ROCK FILTER DAM



*Glenn Lazaro, P.E.*  
02/31/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.




PR 72  
PLAN SHEET

MAINTENANCE ROAD  
SCALE: 1" = 100' HORZ


FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			54
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DATE: \$DATE\$  
\$FILEL\$




**TYPICAL CAMPING BAY**

SHELTER AREA CAMPING - 14 LOC.  
 BURR OAK CAMPING - 31 LOC.  
 RED BUCKEYE CAMPING - 30 LOC.




**TYPICAL CAMPING BAY**

BURR OAK CAMPING - 5 LOC.  
 RED BUCKEYE CAMPING - 4 LOC.




**TYPICAL CAMPING BAY**

BURR OAK CAMPING - 5 LOC.




**TYPICAL CAMPING BAY**

BURR OAK CAMPING - 1 LOC.  
 RED BUCKEYE CAMPING - 1 LOC.



**SECTION B-B**  
 NTS



*Glenn Lazaro, P.E.*  
 07/01/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.




**PR 72  
 MISCELLANEOUS  
 DETAIL**


SCALE: N. T. S.

SHEET 1 OF 3

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			55
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72



PLANING DETAIL



*Glenn Lazaro, P.E.*  
07/01/2023

The seal appearing on this document was authorized by Glenn C. Lazaro, P.E. 113746. Alteration of a sealed document without proper notification to the responsible engineer is an offense under the Texas Engineering Practice Act.




PR 72  
MISCELLANEOUS  
DETAIL

SCALE: N. T. S.


SHEET 2 OF 3

FED. RD. DIV. NO. 6	PROJECT NO.		SHEET NO. 56
STATE TEXAS	DIST HOU	COUNTY FORT BEND	
CONT 0912	SECT 34	JOB 185	HIGHWAY PR 72







TYPICAL STRAIGHT-IN PARKING DETAIL



TYPICAL CROSSWALK DETAIL



TYPICAL ANGLED PARKING DETAIL



MISCELLANEOUS DETAILS

TYPICAL PAVEMENT MARKINGS IN CAMPING AREA  
(WHITE EDGE LINE WILL BREAK AT EACH CAMP SITE)





PR 72  
MISCELLANEOUS  
DETAIL

SCALE: N. T. S.

SHEET 3 OF 3

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			57
STATE	DIST	COUNTY	
TEXAS	HOU	FORT BEND	
CONT	SECT	JOB	HIGHWAY
0912	34	185	PR 72

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




PERPENDICULAR OR ANGLED ACCESSIBLE PARKING SPACE DIMENSIONS



R7-8T




R7-8P



R7-8aPT

ACCESSIBLE PARKING SIGNS




Detail A

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080
7.5 to 15	0.100
Greater than 15	0.125

DEPARTMENTAL MATERIAL SPECIFICATIONS	
ALUMINUM SIGN BLANKS	DMS-7110
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
SIGN FACE MATERIALS	DMS-8300

GENERAL NOTES:

- All paved accessible parking space limit lines shall be 4" solid white lines.
- Paved accessible parking spaces must include a white International Symbol of Accessibility applied conspicuously on the surface in a color that contrasts the pavement. A blue background with white border may supplement the symbol for additional contrast.
- The words "NO PARKING" must be applied on any access aisle adjacent to the parking space. The words must be white, applied:
  - in all capital letters.
  - centered within each access aisle adjacent to the parking space.
- RESERVED PARKING (R7-8T) sign including the International Symbol of Accessibility.
  - shall be REQUIRED for each accessible parking space.
  - shall NOT be placed between two accessible parking spaces.
  - shall NOT be placed in a location that restricts movement of wheelchairs within the adjacent sidewalk.
  - shall have a mounting height of 7 feet to the bottom of the sign.
- A sign identifying the consequences of parking illegally in a paved accessible parking space. Must:
  - at a minimum state "VIOLATORS SUBJECT TO FINE AND TOWING" (Plaque) (R7-8aPT).
  - be mounted on a pole, post, wall or freestanding board.
  - be no more than eight inches (8") below sign R7-8T a sign required by the Texas Accessibility Standards, 502.6.
  - be installed so that the bottom edge of the sign is no lower than 48 inches and no higher than 80 inches above the ground level.
- Signs identifying van parking spaces shall contain the designation "VAN ACCESSIBLE" (R7-8P) Signs shall be 60 inches minimum above the ground level measured to the bottom of the sign.
- Perpendicular or angled parking spaces shall be 8 feet wide minimum with an access aisle 8 feet minimum wide (van accessible). Two parking spaces are permitted to share a common access aisle.
- Access aisles shall be at street level, extend the full length of the parking space they serve, follow ADA surface requirements, and marked to discourage parking in the access aisle. Curb ramps shall connect the access aisle to the adjacent pedestrian access route. Curb ramps shall not be located within the access aisle.
- International Symbol of Accessibility Parking Space Marking and sign details can be found in The Standard Highway Sign Designs for Texas (SHSD) at the following website. <http://www.txdot.gov/>




Glenn Lazaro, P.E.  
07/01/2023

		Traffic Safety Division Standard	
<b>PAVEMENT MARKINGS AND SIGNING FOR ACCESSIBLE PARKING</b>			
<b>PM(AP) - 21 MOD</b>			
FILE: pm(ap)-21	DN: TxDOT	CK: TxDOT	DW: TxDOT
©TxDOT July 2021	CONT 0912	SECT 34	JOB 85
REVISIONS	HIGHWAY PR 72		SHEET NO. 58
DIST HOU	COUNTY FORT BEND		

DATE: FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 6/8/2023  
 FILE: \\txdot.projectwiseonline.com:TXDOT3\Documents\12 - HOU\Design Projects\091234185\4 - Design\Plan Set\13. Standards\1. Roadway\tehm11.dgn



\*\*\* SEE TYPICAL SECTION FOR ROADSIDE DETAILS


**CONDITION - 1**  
 THIN HMAC SURFACES OR HMAC OVERLAY  
 WITH THICKNESS OF 2.5" OR LESS



\*\* EXISTING ROADSIDE EMBANKMENT TO BE GRADED TO PRODUCE A SMOOTH LEVEL SURFACE FOR PLACEMENT OF TAPERED EDGE. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.


\*\*\* SEE TYPICAL SECTION FOR ROADSIDE DETAILS

**CONDITION - 2**  
 OVERLAY OF EXISTING PAVEMENT  
 HMAC THICKNESS 2.5" TO 5"



\*\*\* SEE TYPICAL SECTION FOR ROADSIDE DETAILS

**CONDITION - 3**  
 NEW OR RECONSTRUCTED PAVEMENT  
 HMAC THICKNESS 2.5" TO 5"



\*\*\* SEE TYPICAL SECTION FOR ROADSIDE DETAILS

**CONDITION - 4**  
 NEW OR RECONSTRUCTED PAVEMENT  
 HMAC THICKNESS 5" OR GREATER

**GENERAL NOTES**


1. UNLESS OTHERWISE SHOWN IN THE PLANS, A VERTICAL EDGE IS PERMISSIBLE FOR HMAC PLACED GREATER THAN 5" BELOW THE EDGE OF PAVEMENT AND FOR THICKNESS OF HMAC LESS THAN 2.5".
2. FOR FURTHER INFORMATION REGARDING THE ROADSIDE AND PAVEMENT DETAILS, SEE TYPICAL SECTIONS.
3. PAYMENT FOR TAPERED EDGE WILL BE IN ACCORDANCE WITH APPLICABLE ITEMS IN THE CONTRACT.
4. THE SLOPE OF THE TAPERED EDGE SHALL BE 1.75H:1V OR FLATTER.
5. THE TAPERED EDGE SHALL BE PRODUCED BY USE OF A SCREED ATTACHMENT CAPABLE OF PRODUCING A SMOOTH COMPACTED SURFACE. ADDITIONAL COMPACTING EFFORT BEHIND THE SCREED IS NOT REQUIRED.

(NOT TO SCALE)


					Design Division Standard	
<b>TAPERED EDGE DETAILS          HMAC PAVEMENT</b>						
<b>TE (HMAC) - 11</b>						
FILE: tehmac11.dgn	DN: TxDOT	CK: RL	DW: KB	CK:		
© TxDOT January 2011	CONT	SECT	JOB	HIGHWAY		
REVISIONS			0912 34	185	PR 72	
DIST		COUNTY		SHEET NO.		
HOU		FORT BEND		59		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 06/07/2023 10:46 AM  
FILE: DOCUMENT NAME




**EDGE LINE AND LANE LINES  
ONE-WAY ROADWAY  
WITH OR WITHOUT SHOULDERS**



**TYPICAL TWO-LANE, TWO-WAY PAVEMENT  
MARKINGS THROUGH INTERSECTIONS**




**CENTERLINE AND LANE LINES  
FOUR LANE TWO-WAY ROADWAY  
WITH OR WITHOUT SHOULDERS**




**DETAIL "A"**

9" min. - 10" typ.  
(18" max. for traveled way greater than 48' only)


\* 2" minimum for restripe projects when approved by the Engineer.  
\*\* 8" minimum for restripe projects when approved by the Engineer.



**TYPICAL MULTI-LANE, TWO-WAY PAVEMENT  
MARKINGS THROUGH INTERSECTIONS**




**TWO LANE TWO-WAY ROADWAY  
WITH OR WITHOUT SHOULDERS**



**DETAIL "B"**

\* 2" minimum for restripe projects when approved by the Engineer.



**YIELD LINES**

For posted speed on road being marked equal to or greater than 45 MPH.




For posted speed on road being marked equal to or less than 40 MPH.

**GENERAL NOTES**

- Edge line striping shall be as shown in the plans or as directed by the Engineer. The edge line should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement raveling or other conditions. Edge lines are not required in curb and gutter sections of roadways.
- The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the center of edge line to the center of edge line of a two lane roadway.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




NOTE: Traveled way is exclusive of shoulder widths. Refer to General Note 2 for additional details.

**GUIDE FOR PLACEMENT OF STOP LINES,  
EDGE LINE & CENTERLINE**  
Based on Traveled Way and Pavement Widths for Undivided Roadways

**NOTES**

- Where divided highways are separated by median widths at the median opening itself of 30 feet or more, median openings shall be signed as two separate intersections. Each median opening has two width measurements, with one measurement for each approach. The narrow median width will be the controlling width to determine if signs are required. Yield signs are the typical intersection control. Stop signs and stop bars are optional as determined by the Engineer.
- Install median striping (double yellow centerlines and stop lines/yield lines) when a 50' or greater median centerline can be placed. Stop lines shall only be used with stop signs. Yield lines shall only be used with yield signs.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.



**FOUR LANE DIVIDED ROADWAY CROSSOVERS**




**TYPICAL STANDARD  
PAVEMENT MARKINGS**

**PM(1) - 22**


FILE: pml-22.dgn	DN:	CK:	DW:	CK:
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
11-78 8-00 6-20	DIST	COUNTY	SHEET NO.	
8-95 3-03 12-22	HOU	FORT BEND	60	
5-00 2-12				

# REFLECTIVE RAISED PAVEMENT MARKERS FOR VEHICLE POSITIONING GUIDANCE


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



**CENTERLINE FOR ALL TWO LANE TWO-WAY ROADWAYS**




**CENTERLINE & LANE LINES  
FOR FOUR LANE TWO-WAY ROADWAYS**




**DETAIL "A"**

**DETAIL "B"**

**DETAIL "C"**





**CENTERLINE AND LANE LINES FOR TWO-WAY LEFT TURN LANE**



**LANE LINES FOR ONE-WAY ROADWAY (NON-FREEWAY FACILITIES)**


Raised pavement markers Type II-C-R shall have clear face toward normal traffic and red face toward wrong-way traffic.  
See Note 3.



**REFLECTORIZED PROFILE  
PATTERN DETAIL**

USING REFLECTIVE PROFILE PAVEMENT MARKINGS

6" EDGE LINE, 6" CENTERLINE  
OR 6" LANE LINE




**NOTES**


1. Edge lines should typically be 6" wide and the materials shall be specified in the plans.
2. Profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**Type I (Top View)**



**Type II (Top View)**



**SECTION A**

**RAISED PAVEMENT MARKERS**




**POSITION GUIDANCE USING  
RAISED MARKERS  
REFLECTORIZED PROFILE  
MARKINGS  
PM(2) - 22**

FILE: pm2-22.dgn	DN:	CK:	DW:	CK:
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
REVISIONS	0912	34	185	PR 72
4-77 8-00 6-20	DIST	COUNTY	SHEET NO.	
4-92 2-10 12-22	HOU	FORT BEND	61	
5-00 2-12				

DATE: 06/07/2023 10:48 AM  
FILE: DOCUMENT NAME

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




**HIGH-VISIBILITY LONGITUDINAL CROSSWALK AT CONTROLLED APPROACH**

**GENERAL NOTES**

1. Longitudinal crosswalk lines should not be placed in the wheel path of vehicles. Center the crosswalk lines on travel lanes, lane lines, and shoulder lines (if present).
2. A minimum 6" clear distance shall be provided to the curb face. If the last crosswalk line falls into this distance it must be omitted.
3. For divided roadways, adjustments in spacing of the crosswalk lines should be made in the median so that the crosswalk lines are maintained in their proper location across the travel portion of the roadway.
4. At skewed crosswalks, the crosswalk lines are to remain parallel to the lane lines.
5. Each crosswalk shall be a minimum of 6' wide.
6. The High-Visibility Longitudinal Crosswalk is the preferred crosswalk pattern on State Highways. Other crosswalk patterns as shown in the "Texas Manual on Uniform Traffic Control Devices" may be used. All crosswalk designs and dimension shall comply with the "Texas Manual on Uniform Traffic Control Devices."
7. Final placement of Stop Bar and Crosswalk shall be approved by the Engineer in the field.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



**UNSIGNALIZED MIDBLOCK HIGH-VISIBILITY LONGITUDINAL CROSSWALK**

**NOTES:**

1. Use stop bars with Stop Here For Pedestrians (R1-5b) signs at unsignalized midblock crosswalks.
2. Use stop bars with STOP HERE ON RED (R10-6 or R10-6a) signs at mid block crosswalks controlled by traffic signals or pedestrian hybrid beacons.

DATE: 06/07/2023 10:49 AM  
FILE: DOCUMENT NAME

<p><b>CROSSWALK PAVEMENT MARKINGS</b></p> <p><b>PM(4) - 22A</b></p>			
FILE: pm4-22a.dgn	DN:	CK:	DW:
© TxDOT December 2022	CONT	SECT	JOB
REVISIONS	0912	34	185
6-20	DIST	COUNTY	SHEET NO.
6-22	HOU	FORT BEND	62
12-22			

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

## SIGN SUPPORT DESCRIPTIVE CODES

(Descriptive Codes correspond to project estimate and quantities sheets)

SM RD SGN ASSM TY XXXXX(X)XX(X-XXXX)

### Post Type

FRP = Fiberglass Reinforced Plastic Pipe (see SMD(FRP))  
 TWT = Thin-Walled Tubing (see SMD(TWT))  
 10BWG = 10 BWG Tubing (see SMD(SLIP-1) to (SLIP-3))  
 S80 = Schedule 80 Pipe (see SMD(SLIP-1) to (SLIP-3))

### Number of Posts (1 or 2)


### Anchor Type

UA = Universal Anchor - Concreted (see SMD(FRP) and (TWT))  
 UB = Universal Anchor - Bolted down (see SMD(FRP) and (TWT))  
 WS = Wedge Anchor Steel - (see SMD(TWT))  
 WP = Wedge Anchor Plastic (see SMD(TWT))  
 SA = Slipbase - Concreted (see SMD(SLIP-1) to (SLIP-3))  
 SB = Slipbase - Bolted Down (see SMD(SLIP-1) to (SLIP-3))

### Sign Mounting Designation

P = Prefab. "Plain" (see SMD(SLIP-1) to (SLIP-3), (TWT), (FRP))  
 T = Prefab. "T" (see SMD(SLIP-1) to (SLIP-3), (TWT))  
 U = Prefab. "U" (see SMD(SLIP-1) to (SLIP-3))  
 IF REQUIRED  
 1EXT or 2EXT = Number of Extensions (see SMD(SLIP-1) to (SLIP-3), (TWT))  
 BM = Extruded Wind Beam (see SMD(SLIP-1) to (SLIP-3))  
 WC = 1.12 #/ft Wing Channel (see SMD(SLIP-1) to (SLIP-3))  
 EXAL = Extruded Aluminum Sign Panels (see SMD(SLIP-3))


## REQUIRED CLEARANCE FOR BREAKAWAY SUPPORT



To avoid vehicle undercarriage snagging, any substantial remains of a breakaway support, when it is broken away, should not project more than 4 inches above a 60-inch chord (i.e., typical space between wheel paths).


## SIGN LOCATION

### PAVED SHOULDERS



### LESS THAN 6 FT. WIDE


When the shoulder is 6 ft. or less in width, the sign must be placed at least 12 ft. from the edge of the travel lane.



### GREATER THAN 6 FT. WIDE


When the shoulder is greater than 6 ft in width, the sign must be placed at least 6 ft. from the edge of the shoulder.

### T-INTERSECTION




When this sign is needed at the end of a two-lane, two way roadway, the right edge of the sign should be in line with the centerline of the roadway. Place as close to ROW as practical.

No more than 2 sign posts should be located within a 7 ft. circle.




### BEHIND BARRIER




### BEHIND GUARDRAIL

\*\*Sign clearance based on distance required for proper guard rail or concrete barrier performance.



### BEHIND CONCRETE BARRIER



\* Signs shall be mounted using the following condition that results in the greatest sign elevation:


- (1) a minimum of 7 to a maximum of 7.5 feet above the edge of the travel lane or
- (2) a minimum of 7 to a maximum of 7.5 feet above the grade at the base of the support when sign is installed on the backslope.

The maximum values may be increased when directed by the Engineer.

See the Traffic Operations Division website for detailed drawings of sign clamps, Triangular Slipbase System components and Wedge Anchor System components.

The website address is:  
<http://www.txdot.gov/publications/traffic.htm>

## TYPICAL SIGN ATTACHMENT DETAIL




Bolts used to mount sign panels to the clamp are 5/16-18 UNC galvanized square head with nut, nylon washer, flat washer and lock washer. The bolt length is 1 inch for aluminum.

When two sign clamps are used to mount signs back-to-back, use a 5/16-18 UNC galvanized hex head per ASTM A307 with nut and helical-spring lock washer. The approximate bolt lengths for various post sizes and sign clamp types are given in the table at right. The bolt length may need to be adjusted depending upon field conditions.

Sign clamps may be either the specific size clamp or the universal clamp.


Pipe Diameter	Approximate Bolt Length	
	Specific Clamp	Universal Clamp
2" nominal	3"	3 or 3 1/2"
2 1/2" nominal	3 or 3 1/2"	3 1/2 or 4"
3" nominal	3 1/2 or 4"	4 1/2"

### SIGNS WITH PLAQUES




When a supplemental plaque or secondary sign is used, the 7 ft sign height is measured to the bottom of the supplemental plaque or secondary sign.

### CURB & GUTTER OR RAISED ISLAND



### RESTRICTED RIGHT-OF-WAY (When 6 ft min. is not possible.)



Right-of-way restrictions may be created by rocks, water, vegetation, forest, buildings, a narrow island, or other factors.

In situations where a lateral restriction prevents the minimum horizontal clearance from the edge of the travel lane, signs should be placed as far from the travel lane as practical.

\*\*\* Post may be shorter if protected by guardrail or if Engineer determines the post could not be hit due to extreme slope.

Texas Department of Transportation  
 Traffic Operations Division


## SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS GENERAL NOTES & DETAILS

SMD (GEN) - 08

© TxDOT July 2002	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
9-08	REVISIONS	CONTRACT	SECTION	JOB	HIGHWAY
		0912	34	185	PR 72
		DIST	COUNTY	SHEET NO.	
		HOU	FORT BEND	63	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

## TRIANGULAR SLIPBASE INSTALLATION GENERAL REQUIREMENTS



### NOTE

There are various devices approved for the Triangular Slipbase System. Please reference the Material Producer List for approved slip base systems. [http://www.txdot.gov/business/producer\\_list.htm](http://www.txdot.gov/business/producer_list.htm) The devices shall be installed per manufacturers' recommendations. Installation procedures shall be provided to the Engineer by Contractor.

### GENERAL NOTES:

- Slip base shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to approval of the TxDOT Traffic Standards Engineer.
- Material used as post with this system shall conform to the following specifications:
  - 10 BWG Tubing (2.875" outside diameter)
    - 0.134" nominal wall thickness
    - Seamless or electric-resistance welded steel tubing or pipe
    - Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008
    - Other steels may be used if they meet the following:
      - 55,000 PSI minimum yield strength
      - 70,000 PSI minimum tensile strength
      - 20% minimum elongation in 2"
    - Wall thickness (uncoated) shall be within the range of 0.122" to 0.138"
    - Outside diameter (uncoated) shall be within the range of 2.867" to 2.883"
    - Galvanization per ASTM A123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833.
  - Schedule 80 Pipe (2.875" outside diameter)
    - 0.276" nominal wall thickness
    - Steel tubing per ASTM A500 Gr C
    - Other seamless or electric-resistance welded steel tubing or pipe with equivalent outside diameter and wall thickness may be used if they meet the following:
      - 46,000 PSI minimum yield strength
      - 62,000 PSI minimum tensile strength
      - 21% minimum elongation in 2"
    - Wall thickness (uncoated) shall be within the range of 0.248" to 0.304"
    - Outside diameter (uncoated) shall be within the range of 2.855" to 2.895"
    - Galvanization per ASTM A123
- See the Traffic Operations Division website for detailed drawings of sign clamps and Texas Universal Triangular Slipbase System components. The website address is: <http://www.txdot.gov/publications/traffic.htm>
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.

### ASSEMBLY PROCEDURE


#### Foundation

- Prepare 12-inch diameter by 42-inch deep hole. If solid rock is encountered, the depth of the foundation may be reduced such that it is embedded a minimum of 18 inches into the solid rock.
- The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor-driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class A.
- Push the pipe end of the slip base stub into the center of the concrete. Rotate the stub back and forth while pushing it down into the concrete to assure good contact between the concrete and stub. Continue to work the stub into the concrete until it is between 2 to 4 inches above the ground.
- Plumb the stub. Allow a minimum of 4 days to set, unless otherwise directed by the Engineer.
- The triangular slipbase system is multidirectional and is designed to release when struck from any direction.

#### Support

- Cut support so that the bottom of the sign will be 7 to 7.5 feet above the edge of the travelway (i.e., edge of the closest lane) when slip plate is below the edge of pavement or 7 to 7.5 feet above slip plate when the slip plate is above the edge of the travelway. The cut shall be plumb and straight.
- Attach sign to support using connections shown. When multiple signs are installed on the same support, ensure the minimum clearance between each sign is maintained. See SMD(SLIP-2) for clearances based on sign types.

### CONCRETE ANCHOR



5/8" diameter Concrete Anchor - 8 places (embed a minimum of 5 1/2" and torque to min. of 50 ft-lbs). Anchor may be expansion or adhesive type.

SM RD SGN ASSM TY XXXXX(X)SB(X-XXXX)

Concrete anchor consists of 5/8" diameter stud bolt with UNC series bolt threads on the upper end. Heavy hex nut per ASTM A563, and hardened washer per ASTM F436. The stud bolt shall have a minimum yield and ultimate tensile strength of 50 and 75 KSI, respectively. Nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." Adhesive type anchors shall have stud bolts installed with Type III epoxy per DMS-6100, "Epoxyes and Adhesives." Adhesive anchors may be loaded after adequate epoxy cure time per the manufacturer's recommendations. Top of bolt shall extend at least flush with top of the nut when installed. The anchor, when installed in 4000 psi normal-weight concrete with a 5 1/2" minimum embedment, shall have a minimum allowable tension and shear of 3900 and 3100 psi, respectively.

**Texas Department of Transportation**  
Traffic Operations Division
















## SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

**SMD(SLIP-1)-08**

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
9-08	REVISIONS		CONT	SECT	JOB	HIGHWAY
			0912	34	185	PR 72
			DIST	COUNTY		SHEET NO.
		HOU	FORT BEND		64	



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



All dimensions are in english unless detailed otherwise.

Friction caps may be manufactured from hot rolled or cold rolled steel sheets. The minimum sheet metal thickness shall be 24 gauge for all cap sizes. The rim edges shall be reasonably straight and smooth. Caps shall be sized and formed in such a manner as to produce a drive-on friction fit and have no tendency to rock when seated on the pipe. The depth shall be sufficient to give positive protection against entrance of rainwater. They shall be free of sharp creases or indentations and show no evidence of metal fracture. Caps shall have an electrodeposited coating of zinc in accordance with the requirements of ASTM B633 Class FE/ZN 8.

GENERAL NOTES:

1. SIGN SUPPORT # OF POSTS MAX. SIGN AREA
 

10 BWG	1	16 SF
10 BWG	2	32 SF
Sch 80	1	32 SF
Sch 80	2	64 SF
2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
3. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
4. Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
10. Additional route markers may be added vertically, provided the total sign area does not exceed the maximum allowable amount per Note 1.
11. Additional sign clamp required on the "T-bracket" post for 24 inch height signs. Place the clamp 3 inches above bottom of sign when possible.
12. Post open ends shall be fitted with Friction Caps.
13. Sign blanks shall be the sizes and shapes shown on the plans.

REQUIRED SUPPORT		
SIGN DESCRIPTION	SUPPORT	
Regulatory	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)
Warning	48x60-inch signs	TY S80(1)XX(T)
	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)
	48x60-inch signs	TY S80(1)XX(T)
	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)
	48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)
Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)	






SIGN MOUNTING DETAILS  
SMALL ROADSIDE SIGNS  
TRIANGULAR SLIPBASE SYSTEM  
SMD(SLIP-2)-08

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CON: 0912	SECT: 34	JOB: 185	HIGHWAY: PR 72
		DIST: HOU	COUNTY: FORT BEND	SHEET NO.: 65	

DATE:  
FILE:



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:  
FILE:








**GENERAL NOTES:**

- | SIGN SUPPORT | # OF POSTS | MAX. SIGN AREA |
|--------------|------------|----------------|
| 10 BWG       | 1          | 16 SF          |
| 10 BWG       | 2          | 32 SF          |
| Sch 80       | 1          | 32 SF          |
| Sch 80       | 2          | 64 SF          |
- The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
- Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
- Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
- For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
- When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
- Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
- Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
- Sign blanks shall be the sizes and shapes shown on the plans.
- Additional sign clamp required on the "T-bracket" post for 24 inch high signs. Place the clamp 3 inches above bottom of sign when possible.
- Post open ends shall be fitted with Friction Caps.



**Typical Sign Mount**  
SM RD SGN ASSM TY S80(2)XX(IP-EXAL)  
\* Additional stiffener placed at approximate center of signs when sign width is greater than 10'.



Use Extruded Alum. Windbeam as stiffeners See SMD (2-1) for additional details  
See Detail E for clamp installation

		REQUIRED SUPPORT	
		SIGN DESCRIPTION	SUPPORT
Regulatory	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)	
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)	
	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)	
	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)	
Warning	48x60-inch signs	TY S80(1)XX(T)	
	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)	
	48x60-inch signs	TY S80(1)XX(T)	
	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)	
	48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)	
	Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)	

Texas Department of Transportation  
Traffic Operations Division

**SIGN MOUNTING DETAILS  
SMALL ROADSIDE SIGNS  
TRIANGULAR SLIPBASE SYSTEM  
SMD(SLIP-3)-08**

© TxDOT July 2002		DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		0912	34	185	PR 72
		DIST	COUNTY		SHEET NO.
		HOU	FORT BEND		66

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

**I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402**

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

1.  
2.  
 No Action Required     Required Action

Action No.

- Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000
- Comply with the SW3P and revise when necessary to control pollution or required by the Engineer.
- Post Construction Site Notice (CSN) with SW3P information on or near the site, accessible to the public and TCEQ, EPA or other inspectors.
- When Contractor project specific locations (PSL's) increase disturbed soil area to 5 acres or more, submit NOI to TCEQ and the Engineer.

**II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404**

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required  
 Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)  
 Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)  
 Individual 404 Permit Required  
 Other Nationwide Permit Required: NWP# \_\_\_\_\_

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

- 
- 
- 
- 

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

**Best Management Practices:**

<b>Erosion</b>	<b>Sedimentation</b>	<b>Post-Construction TSS</b>
<input type="checkbox"/> Temporary Vegetation	<input checked="" type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	<input type="checkbox"/> Grassy Swales

**III. CULTURAL RESOURCES**

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

- No Action Required     Required Action

Action No.

- 
- 
- 
- 

**IV. VEGETATION RESOURCES**

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

- No Action Required     Required Action

Action No.

- 
- 
- 
- 

**V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.**

- No Action Required     Required Action

Action No.

- 
- 
- 
- 

If any of the listed species are observed, cease work in the immediate area, do not disturb species or habitat and contact the Engineer immediately. The work may not remove active nests from bridges and other structures during nesting season of the birds associated with the nests. If caves or sinkholes are discovered, cease work in the immediate area, and contact the Engineer immediately.

**LIST OF ABBREVIATIONS**

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SW3P: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NWP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

**VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES**

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used. Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act. Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- \* Dead or distressed vegetation (not identified as normal)
- \* Trash piles, drums, canister, barrels, etc.
- \* Undesirable smells or odors
- \* Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

- Yes     No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

- Yes     No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

- No Action Required     Required Action

Action No.

- 
- 
- 

**VII. OTHER ENVIRONMENTAL ISSUES**

(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required     Required Action

Action No.

- 
- 
- 



*Glenn Lazaro, P.E.*  
07/01/2023

		<b>Design Division Standard</b>		
<b>ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS</b> <b>EPIC</b>				
FILE: epic.dgn	DN: TxDOT	CK: RG	DW: VP	CK: AR
©TxDOT: February 2015	CONT	SECT	JOB	HIGHWAY
12-12-2011 (DS) REVISIONS	0912	34	185	PR 72
05-07-14 ADDED NOTE SECTION IV.	DIST	COUNTY	SHEET NO.	
01-23-2015 SECTION I (CHANGED ITEM 1122 TO ITEM 506, ADDED GRASSY SWALES.	HOU	FORT BEND	67	

**STORMWATER POLLUTION PREVENTION PLAN (SWP3):**

This SWP3 has been developed in accordance with the TPDES Construction General Permit TXR150000 (CGP). The Texas Department of Transportation (TxDOT) ensures that project specifications include adequate best management practices (BMPs) for this project.

For all projects with any soil disturbing activities, TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office. If no field office is available, then this SWP3 shall be kept in the appropriate TxDOT Area Office.

This SWP3 is consistent with requirements specified in applicable stormwater plans and the projects environmental permits, issues, and commitments (EPICs). A copy of the CGP is included in Attachment 2.12 of the SWP3 binder.

**1.0 SITE/PROJECT DESCRIPTION**

**1.1 PROJECT CONTROL SECTION JOB (CSJ):**

0912-34-185

**1.2 PROJECT LIMITS:**

From: IN BRAZOS BEND STATE PARK

To: \_\_\_\_\_

**1.3 PROJECT COORDINATES:**

BEGIN: (Lat) 29.3717675, (Long) -95.6327938

END: (Lat) 29.3765203, (Long) -95.5960901

**1.4 TOTAL PROJECT AREA (Acres):** 9 AC

**1.5 TOTAL AREA TO BE DISTURBED (Acres):** 9 AC

**1.6 NATURE OF CONSTRUCTION ACTIVITY:**

MILL/OVERLAY  
PAVEMENT MARKING  
PAVEMENT RECONSTRUCTION/WIDENING

**1.7 MAJOR SOIL TYPES:**

Soil Type	Description

**1.8 PROJECT SPECIFIC LOCATIONS (PSLs):**

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

**1.9 CONSTRUCTION ACTIVITIES:**

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.5.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**1.10 POTENTIAL POLLUTANTS AND SOURCES:**

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**1.11 RECEIVING WATERS:**

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody
BRAZOS RIVER	

\* Add (\*) for impaired waterbodies with pollutant in ( ).

**1.12 ROLES AND RESPONSIBILITIES: TxDOT**


- Development of plans and specifications
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR**

- Day To Day Operational Control
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**1.14 LOCAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) OPERATOR COORDINATION:**

MS4 Entity



*Glenn Lazaro, P.E.*  
07/01/2023

**STORMWATER POLLUTION PREVENTION PLAN (SWP3)**

© 2023 Sheet 1 of 2

FED. RD. DIV. NO.	PROJECT NO.			SHEET NO.
6				68
STATE	STATE DIST.	COUNTY		
TEXAS	HOU	FORT BEND		
CONT.	SECT.	JOB	HIGHWAY NO.	
0912	34	185	PR 72	

**STORMWATER POLLUTION PREVENTION PLAN (SWP3):**

**2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE**

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

**2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:**

**T / P**

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**2.2 SEDIMENT CONTROL BMPs:**

**T / P**

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

Sediment control BMPs requiring design capacity calculations (See SWP3 Attachment 1.3.):

**T / P**

- Sediment Trap
  - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
  - 3,600 cubic feet of storage per acre drained
- Sedimentation Basin
  - Not required (<10 acres disturbed)
  - Required (>10 acres) and implemented.
    - Calculated volume runoff from 2-year, 24-hour storm for each acre of disturbed area
    - 3,600 cubic feet of storage per acre drained
  - Required (>10 acres), but not feasible due to:
    - Available area/Site geometry
    - Site slope/Drainage patterns
    - Site soils/Geotechnical factors
    - Public safety
    - Other: \_\_\_\_\_

**2.3 PERMANENT CONTROLS:**

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

**2.4 OFFSITE VEHICLE TRACKING CONTROLS:**

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**2.5 POLLUTION PREVENTION MEASURES:**

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_
- Other: \_\_\_\_\_

**2.6 VEGETATED BUFFER ZONES:**

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

**2.7 ALLOWABLE NON-STORMWATER DISCHARGES:**


- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

**2.8 INSPECTIONS:**

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3 .

**2.9 MAINTENANCE:**

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.5 of this SWP3.




**STORMWATER POLLUTION PREVENTION PLAN (SWP3)**

© 2023 Sheet 2 of 2

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6			69
STATE	STATE DIST.	COUNTY	
TEXAS	HOU	FORT BEND	
CONT.	SECT.	JOB	HIGHWAY NO.
0912	34	185	PR 72


*Glenn Lazaro, P.E.*  
07/01/2023

60872023  
 p:\as\txdot\projectwiseonline.com\TXDOT3\Documents\12 - HOU\Design Projects\091234185\4 - Design\Plan Set\13. Standards\3. SWPPP\ec116.dgn  
 DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



**TEMPORARY SEDIMENT CONTROL FENCE**

SCF



**HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL**

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

**SEDIMENT CONTROL FENCE USAGE GUIDELINES**

A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT<sup>2</sup>. Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.


**LEGEND**

Sediment Control Fence

SCF

**GENERAL NOTES**

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.




**VERTICAL TRACKING**

				Design Division Standard	
<b>TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE &amp; VERTICAL TRACKING</b> <b>EC(1) - 16</b>					
FILE: ec116	DN: TxDOT	CK: KM	DW: VP	DN/CK: LS	
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0912	34	185	PR 72	
	DIST	COUNTY	SHEET NO.		
	HOU	FORT BEND	70		


DATE: 6/8/2023  
 FILE: \\txdot\projectwise\online.com\TXDOT3\Documents\12 - HOU\Design Projects\091234185V4 - Design\Plan Set\13. Standards\3. SWPPP\ec216.dgn

DISCLAIMER:  
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




**FILTER DAM AT TOE OF SLOPE**

(RFD1)




**FILTER DAM AT SEDIMENT TRAP**

(RFD1) OR (RFD2)




**FILTER DAM AT CHANNEL SECTIONS**


(RFD1) OR (RFD2) OR (RFD3)




**PLAN VIEW**




**"V" SHAPE PLAN VIEW**



**SECTION B-B**



**PROFILE**



**SECTION C-C**

**ROCK FILTER DAM USAGE GUIDELINES**

Rock Filter Dams should be constructed downstream from disturbed areas to intercept sediment from overland runoff and/or concentrated flow. The dams should be sized to filter a maximum flow through rate of 60 GPM/FT<sup>2</sup> of cross sectional area. A 2 year storm frequency may be used to calculate the flow rate.


Type 1 (18" high with no wire mesh) (3" to 6" aggregate): Type 1 may be used at the toe of slopes, around inlets, in small ditches, and at dike or swale outlets. This type of dam is recommended to control erosion from a drainage area of 5 acres or less. Type 1 may not be used in concentrated high velocity flows (approximately 8 Ft/Sec or more) in which aggregate wash out may occur. Sandbags may be used at the embedded foundation (4" deep min.) for better filtering efficiency of low flows if called for on the plans or directed by the Engineer.

Type 2 (18" high with wire mesh) (3" to 6" aggregate): Type 2 may be used in ditches and at dike or swale outlets.

Type 3 (36" high with wire mesh) (4" to 8" aggregate): Type 3 may be used in stream flow and should be secured to the stream bed.


Type 4 (Sack gabions) (3" to 6" aggregate): Type 4 May be used in ditches and smaller channels to form an erosion control dam.

Type 5: Provide rock filter dams as shown on plans.



**TYPE 4 (SACK GABIONS)**

(RFD4)



**SECTION A-A**

**GENERAL NOTES**

1. If shown on the plans or directed by the Engineer, filter dams should be placed near the toe of slopes where erosion is anticipated, upstream and/or downstream at drainage structures, and in roadway ditches and channels to collect sediment.
2. Materials (aggregate, wire mesh, sandbags, etc.) shall be as indicated by the specification for "Rock Filter Dams for Erosion and Sedimentation Control".
3. The rock filter dam dimensions shall be as indicated on the SW3P plans.
4. Side slopes should be 2:1 or flatter. Dams within the safety zone shall have sideslopes of 6:1 or flatter.
5. Maintain a minimum of 1' between top of rock filter dam weir and top of embankment for filter dams at sediment traps.
6. Filter dams should be embedded a minimum of 4" into existing ground.
7. The sediment trap for ponding of sediment laden runoff shall be of the dimensions shown on the plans.
8. Rock filter dam types 2 & 3 shall be secured with 20 gauge galvanized woven wire mesh with 1" diameter hexagonal openings. The aggregate shall be placed on the mesh to the height & slopes specified. The mesh shall be folded at the upstream side over the aggregate and tightly secured to itself on the downstream side using wire ties or hog rings. For in stream use, the mesh should be secured or staked to the stream bed prior to aggregate placement.
9. Sack Gabions should be staked down with 3/4" dia. rebar stakes, and have a double-twisted hexagonal weave with a nominal mesh opening of 2 1/2" x 3 1/4".
10. Flow outlet should be onto a stabilized area (vegetation, rock, etc.).
11. The guidelines shown hereon are suggestions only and may be modified by the Engineer.

**PLAN SHEET LEGEND**

- Type 1 Rock Filter Dam (RFD1)
- Type 2 Rock Filter Dam (RFD2)
- Type 3 Rock Filter Dam (RFD3)
- Type 4 Rock Filter Dam (RFD4)

		<b>Design Division Standard</b>	
<b>TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES</b> <b>ROCK FILTER DAMS</b> <b>EC(2) - 16</b>			
FILE: ec216	DN: TxDOT	CK: KM	DW: VP
© TxDOT: JULY 2016	CONT: 0912	SECT: 34	JOB: 185
REVISIONS	DIST: HOU	COUNTY: FORT BEND	PR 72
			SHEET NO. 71