

# INDEX OF SHEETS

SHEET NO. DESCRIPTION

GENERAL	
1	Title Sheet
2 - 3	General Notes
4	E & Q Sheet -- Callahan
5	# RS-TCP-05
6	# TCP-AbiCableBarrier
#	TxDOT Standards

# STATE OF TEXAS DEPARTMENT OF TRANSPORTATION

## PLANS OF PROPOSED HIGHWAY ROUTINE MAINTENANCE CONTRACT


### TYPE OF WORK:

MOWING HIGHWAY RIGHT OF WAY

PROJECT NO. : RMC 6379 38 001

HIGHWAY : IH 20, ETC.

LIMITS OF WORK : Various locations in Callahan County



GRAPHICS FILE	MAINTENANCE PROJECT NO.	SHEET NO.		
Title-MNT.dgn	6379 38 001	1		
CHECKED	STATE	STATE DIST.	COUNTY	
	TEXAS	08	CALLAHAN	
CHECKED	CONT.	SECT.	JOB	HIGHWAY NO.
	6379	38	001	IH20, ETC.

#### FINAL PLANS:

Date Contractor Began Work:  
Date Work was Completed:  
Date Work Accepted:  
Final Contract Cost: \$

#### CERTIFICATION FOR FINAL PLANS:

Project was built according to the plans and specifications. These final plans reflect the work done and the quantities shown thereon and on the final estimate are final quantities.

Area Engineer

TEXAS DEPARTMENT OF TRANSPORTATION

SUBMITTED FOR LETTING:

DocuSigned by:

*Daniel P. Richardson, P.E.*

3/12/2021

E07CA1501A784BF

Daniel P. Richardson, P.E.  
Director of Operations

Date

DocuSigned by:

*Thomas G. Allbritton, P.E.*

3/12/2021

0E6E7E74C37D430

Thomas G. Allbritton, P.E.  
District Engineer

Date

LEVELS DISPLAYED
1
2
3
4
5
6
7
8
9
10
11
12
13
14

© by Texas Department of Transportation:  
2019 all rights reserved

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION  
NOVEMBER 1, 2014 AND SPECIAL SPECIFICATION ITEMS INCLUDED IN THE  
CONTRACT SHALL GOVERN ON THIS PROJECT.

**GENERAL NOTES**

**General**

- This is a CALLOUT CONTRACT. ITEM 730 and ITEM 734 will be performed on a CALLOUT BASIS at locations identified by each CALLOUT/WORK ORDER. Plan Quantity Measurement does not apply.
- This is a Non-Site-Specific Contract. The LOCATIONS (TRACTS) and QUANTITIES shown on the ESTIMATE/QUANTITY SHEET in the Plans are for Contractor's information only.
- TRACTS, QUANTITIES, FULL-WIDTH OR STRIP MOW and LITTER will be identified by each CALLOUT/WORK ORDER.
- Report to the PROJECT MANAGER/INSPECTOR prior to beginning work each day.

**Contract Prosecution**

Each contract awarded by the Department stands on its own and as such, is separate from other contracts. A contractor awarded multiple contracts, must be capable and sufficiently staffed to concurrently process any or all contracts at the same time.

**Item 2 Instructions to Bidders**

Contractor questions on this project are to be addressed to the following individual(s):

Paul Norman, P.E.: [Paul.Norman@txdot.gov](mailto:Paul.Norman@txdot.gov)  
 Chad Carter, P.E.: [Chad.W.Carter@txdot.gov](mailto:Chad.W.Carter@txdot.gov)  
 (Abilene Area Office)

Contractor questions will be accepted through email, phone, and in person by the above individuals.

All contractor questions will be reviewed by the Engineer. Once a response is developed, it will be posted to TxDOT's Public FTP at the following Address:

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting/Responses/>

All questions submitted that generate a response will be posted through this site. The site is organized by District, Project Type (Construction or Maintenance), Letting Date, CCSJ/Project Name.

**Item 7 Legal Relations and Responsibilities:**

No significant traffic generator events identified.

**Item 502 Barricades, Signs, and Traffic Handling**

Additional signs, barricades and traffic handling may be necessary to complete the work shown herein and will be provided by the contractor as required and will be considered subsidiary to the bid items.

**GENERAL NOTES**

Traffic control shall be in compliance with the "Texas Manual on Uniform Traffic Control Devices", the TCP standards included in the plans, and the "Compliant Work Zone Traffic Control Device" list.

**Item 730 Roadside Mowing**

Slopes will be mowed with no damage to the established vegetation.

Other construction and/or maintenance contracts may be underway on roadsides to be mowed in this contract. Mowing will not be required in these areas.

Spot Mowing may be designated by the Engineer to address safety concerns. The contractor will have 72 hours to begin mowing any designated area from the time of notification. Any Spot Mowing that is performed will also include Litter Removal. A one-time fee for a Callout Mobilization will be paid for Spot Mowing.

The Engineer will determine the sequence of tracts to be mowed. Refer to the Estimate and Quantity Sheet in the plans for width to be mowed on each tract.

For each cycle required, the Engineer shall send the contractor a work order containing the following information:

- Tract numbers and total number of acres to be mowed
- Working days allowed to complete the cycle
- Date when time charges for the cycle will begin

Working days allowed to complete a cycle of mowing and litter removal will be determined by dividing the total number of acres required for the cycle by the production rate of 115 acres each working day. A fraction of a day shall be rounded up to the nearest whole number. If the total number of working days is not used during the completion of the work required within one cycle, the working days will not be carried forward to any cycle period.

Perform hand trimming on guardrail in non-mow areas, outer separations on controlled access highways, restricted access areas and between main lanes and frontage roads located within 10 yards of the travel way or adjacent to paved shoulders. Hand trim 5 ft. behind guardrail or as directed by the Engineer.

Hand trim around all dead animal or other large debris that cannot be mowed over or moved in the same manner as any other fixed object. It is also acceptable to move the object to the right of way line prior to mowing.

**Definitions:**

Full Width Mow – Mow entire width of right of way.


Strip Mow – Mow 15 feet from edge of pavement or unpaved shoulder.

Always mow the entire width of medians and outer separations (areas between main lanes, ramps, and frontage road) except for non-mow areas.


CONT	SECT	JOB	HIGHWAY
6379	38	001	IH20, ETC.
DIST	COUNTY		SHEET NO.
ABL	CALLAHAN		02

**GENERAL NOTES**

Strip mow as shown below at intersections and curves for sight distance. Transition Length (Tr) will be no less than 200'.



MOWING FOR SIGHT DISTANCE  
 WITH TRANSITION FROM INTERSECTION  
 BACK TO STRIP MOWING



MOWING FOR SIGHT DISTANCE  
 TRANSITIONS AT DRIVEWAYS,  
 SIGNS, AND CURVES

**GENERAL NOTES**

**Item 734 Litter Removal**

Litter removal will be performed no more than 2 working days prior to the mowing cycle.

Pick up any litter remaining after mowing operation.

Only one cycle of litter removal will be paid per mowing cycle.

It is the intent of this item that TxDOT's right-of-way be mowed and litter-free after the contractor's mowing operation.

**Item 6185 Truck Mounted Attenuator (TMA) and Trailer Attenuator (TA)**

It is expected that when the contractor is mowing the narrow side of the cable median barrier that work will be continuous until completed.

Truck mounted attenuators shall be utilized in accordance with TCP-Abl Cable Barrier-Traffic Control Mobile Operations Adjacent to Cable Barrier when mowing the short side of cable median barrier right of way.

Provide to the Engineer a letter certifying that all truck-mounted attenuators (TMA) used on the project have proven to be crashworthy using the criteria outlined in the *National Cooperative Highway Research Program (NCHRP) Report 350*.

CONT	SECT	JOB	HIGHWAY
6379	38	001	IH20, ETC.
DIST	COUNTY		SHEET NO.
ABL	CALLAHAN		03

**CALLAHAN COUNTY 2021 MOWING LOCATION AND ITEM QUANTITY SUMMARY**

TRACT	HWY	LIMITS	ITEM 500-6033 MOBILIZATION (CALL OUT)			ITEM 730-6001 STRIP MOWING			ITEM 730-6002 FULL-WIDTH MOWING			ITEM 730-6003 SPOT MOWING			ITEM 734-6001 LITTER REMOVAL			ITEM 6185-6005 TMA MOBILE OPERATION		
			CYCLES	EACH	TOTAL EACH	CYCLES	ACRES	TOTAL ACRES	CYCLES	ACRES	TOTAL ACRES	CYCLES	ACRES	TOTAL ACRES	CYCLES	ACRES	TOTAL ACRES	DAYS for STRIP MOW	DAYS for FULL-WIDTH MOWS	TOTAL DAYS
1	BI 20-T	FROM FM 2047 TO IH 20 EAST			0			0	2	27	54			0			0			0
2	IH 20	FROM TAYLOR CO/L TO EASTLAND CO/L			0			0	3	862	2586			0	3	862	2586		6	6
3	FM 1864	FROM FM 880 TO EASTLAND CO/L			0	1	13	13	2	35	70			0			0			0
4	FM 3265	FROM FM 880 TO EASTLAND CO/L			0	1	18	18	2	44	88			0			0			0
5	FM 1079	FROM FM 880 TO 6 MILES WEST			0	1	3	3	2	5	10			0			0			0
*6	<sup>1</sup> FM 374	FROM SH 206 TO EASTLAND CO/L			0	1	8	8	2	8	16			0			0			0
7	FM 2707	FROM SH 36 TO COLEMAN CO/L			0	1	17	17	2	32	64			0			0			0
8	FM 2287	FROM FM 2707 TO SH 36			0	1	54	54	2	138	276			0			0			0
9	FM 880	FROM SHACKELFORD CO/L TO SH 206			0	1	128	128	2	277	554			0			0			0
10	FM 1178	FROM SH 36 TO FM 604			0	1	36	36	2	91	182			0			0			0
*11	<sup>2</sup> FM 604	FROM SHACKELFORD CO/L TO TAYLOR CO/L			0	1	117	117	2	286	572			0	3	34	102			0
12	FM 3217	FROM FM 604 TO CLYDE LAKE			0	1	14	14	2	37	74			0			0			0
13	FM 2700	FROM FM 18 TO FM 604			0	1	5	5	2	10	20			0	3	10	30			0
14	FM 2926	FROM FM 604 TO US 283			0	1	36	36	2	86	172			0			0			0
15	FM 603	FROM IH 20 TO SH 36			0	1	41	41	2	75	150			0	3	75	225			0
16	FM 2228	FROM IH 20 TO FM 880			0	1	51	51	2	129	258			0			0			0
17	FM 2047	FROM IH 20 TO 3.8 MILES NORTHWEST			0	1	14	14	2	37	74			0			0			0
18	FM 2945	FROM FM 880 TO EASTLAND CO/L			0	1	12	12	2	30	60			0			0			0
19	SPUR 880	FROM FM 880 TO SH 6			0	1	1	1	2	3	6			0			0			0
*20	<sup>3</sup> SH 206	FROM EASTLAND CO/L TO BROWN CO/L			0	1	24	24	2	97	194			0	3	97	291			0
21	SH 279	FROM SH 206 TO BROWN CO/L			0	1	8	8	2	20	40			0			0			0
22	US 283	FROM SHACKELFORD CO/L TO COLEMAN CO/L			0	1	110	110	2	356	712			0			0			0
23	SH 6	FROM SHACKELFORD CO/L TO EASTLAND CO/L			0	1	8	8	2	22	44			0			0			0
24	SH 36	FROM TAYLOR CO/L TO EASTLAND CO/L			0	1	125	125	2	262	524			0	3	262	786			0
25	FM 18	FROM TAYLOR CO/L TO UNION PACIFIC RR			0	1	44	44	2	91	182			0	3	91	273			0
26	FM 1707	FROM IH 20 TO FM 18			0	1	2	2	2	2	4			0			0			0
TBD	TBD	TBD	1	1	1						0	1	100	100	1	100	100			0
<b>TOTALS</b>					<b>1</b>			<b>889</b>			<b>6986</b>			<b>100</b>			<b>4393</b>			<b>6</b>

**\*Notes:**

1. Tract 6...FM 374 - Non-Mow area from SH 206 to Cross Plains East City Limit.
2. Tract 11...FM 604 - Litter-Removal area from IH 20 SFR to FM 3217.
3. Tract 20...SH 206 - Non-Mow area from FM 880 to Cross Plains South City Limit


FHWA DIVISION	PROJECT NO.		HIGHWAY NO.
6	SEE TITLE SHEET		IH20, ETC.
STATE	COUNTY		SHEET NO.
TEXAS	CALLAHAN		4
DISTRICT	CONTROL	SECTION	
ABL	6379	38	001

DISCLAIMER  
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

LEVELS DISPLAYED
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63


## EXAMPLES OF SIGN SUPPORTS

See the CWZTCD for the type of sign substrate that can be used for each approved sign support.



Flags as required by Engineer or as shown on plans


### SHORT TERM DURATION, DAYTIME USE ONLY PORTABLE SIGN SUPPORTS



The upright SHALL be made of hollow-profile plastic lumber (HPPL). Wood or metal shall NOT be used.  
1 Foot Mounting Height

Attachment to wooden supports will be by bolts and nuts or screws. Use TxDOT's or manufacturer's recommended procedures for attaching sign substrates to other types of sign supports.

**Nails will NOT be allowed.**




**SIGN IN ACCORDANCE WITH THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS**

**MOWERS AHEAD SIGNS ARE USED FOR MOWING OPERATIONS.**

**LITTER PICKUP AHEAD, ROAD WORK AHEAD AND WORKER AHEAD SIGNS ARE USED AS DIRECTED FOR OTHER MAINTENANCE OPERATIONS WHEN ALL WORK OCCURS OFF OF THE PAVED HIGHWAY SURFACE.**

### ROLL-UP SIGNS CONFORMING TO DMS-8310 AND THE CWZTCD ALLOWED


\*Letter dimensions and spacing for "CW21-SPECIAL" is the same as C20-1D



TYPICAL LOCATION OF SIGNS AT HIGHWAY CROSSING

WORK AREA IS A MAXIMUM OF 2.0 MILES UNLESS OTHERWISE DIRECTED. SIGNS MAY REMAIN IN PLACE ONLY DURING DAYLIGHT HOURS. SIGNS ARE TO BE PLACED 6' TO 12' OFF OF THE PAVED SURFACE UNLESS OTHERWISE DIRECTED. ROAD WORK AHEAD SIGNS SHOWN AS EXAMPLES, ONE OF THE FOUR TYPE SIGNS WILL BE USED AS DIRECTED.

\* SIGNS IN THE MEDIAN ARE REQUIRED WHEN WORK OCCURS IN MEDIAN



TRAFFIC CONTROL PLAN FOR WORK OFF OF THE PAVED SURFACE.

### GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- Nails shall NOT be used to attach signs to any support.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes. The additional signs requested by the Engineer/Inspector shall not be subsidiary.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD). The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so that the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for sign installations and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1".
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

### Duration of Work (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part VII)

- The Contractor is responsible for ensuring the sign support and substrate meets crashworthiness. For mowing operation all signs and supports are Short-term Duration for daytime work.
- The Contractor shall furnish the sign sizes shown on this sheet or as directed by the Engineer.

### SIGN SUBSTRATES

- The Contractor shall ensure that the sign substrate is allowed for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign faces.

### REFLECTIVE SHEETING

- Reflectorized signs shall be constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 or DMS-8310. The DMS specifications can be accessed from the following web address:  
[http://manuals.dot.state.tx.us/80/dynaweb/colmates/@Generic\\_\\_CollectionView;cs=default;ts=default](http://manuals.dot.state.tx.us/80/dynaweb/colmates/@Generic__CollectionView;cs=default;ts=default)
- White sheeting, meeting the requirements of DMS-8300 Type C (High Specific Intensity), shall be used for signs with white background and channelizing devices.
- Orange sheeting, meeting the requirements of DMS-8300 Type E (Fluorescent Prismatic), shall be used for signs with orange backgrounds.

### SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

### REMOVING OR COVERING

- Signs should be removed or completely covered when not mowing.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and supports shall be removed by the end of the day.

### SIGN SUPPORT WEIGHTS

- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry cohesionless sand is recommended.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects will not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact.
- Rubber (such as tire inner tubes) shall NOT be used for sandbags.
- Rubber ballasts (such as those used with cones or edgeline channelizers) shall NOT be used as sign support weights.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign supports.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

### CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

Any sign, sign support or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced or repaired as soon as possible by the Contractor at the Contractor's expense.

Only pre-qualified products shall be used. A copy of the "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources and may be obtained by contacting:

Standards Engineer  
 Traffic Operations Division - TE  
 Texas Department of Transportation  
 125 East 11th Street  
 Austin, Texas 78701-2483  
 Phone (512) 416-3120  
 Fax (512) 416-3299

Instructions to locate the "CWZTCD" on TxDOT website are:

Start at website - [www.dot.state.tx.us](http://www.dot.state.tx.us)  
 Click on "About TxDOT",  
 Click on "Organizational Chart",  
 Click on "Traffic Operations Box",  
 Click on "Compliant Work Zone Traffic Control Devices",  
 Click on "View PDF".  
 This site is printable.






## ROADSIDE TRAFFIC CONTROL PLAN

SHEET 1 OF 1		RS-TCP-05		NOT TO SCALE	
FILE#	RSTCP05.DGN	DN#	LJB	CR#	JG
REVISED#	September 17, 2004	STATE DISTRICT	08	FEDERAL REGION	N/A
REVISED#	FEBRUARY 2, 2005	COUNTY	CALLAHAN	FEDERAL AID PROJECT	N/A
REVISED#	Sign placement in TCP	CONTROL SECTION	6379 38	JOB	001
REVISED#		HIGHWAY			1H20, ETC.


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:  
FILE:



**LEFT LANE CLOSURE ADJACENT TO CABLE BARRIER**

Note: An engineer's seal is not required in accordance with 137.33.m of the Texas Engineering Act and Board Rules.



**STRIPING FOR TMA**

LEGEND			
*	Trail Vehicle	ARROW BOARD DISPLAY	
**	Shadow Vehicle		
***	Work Vehicle		RIGHT Directional
	Heavy Work Vehicle		LEFT Directional
	Truck Mounted Attenuator (TMA)		Double Arrow
	Traffic Flow		CAUTION (Alternating Diamond or 4 Corner Flash)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**GENERAL NOTES**

- ADVANCE WARNING and SHADOW vehicles shall be equipped with Type B or Type C flashing arrow boards as per the Barricade and Construction (BC) standards. Arrow boards on WORK vehicles will be optional based on the type of work being performed. The arrow boards shall be operated from inside the vehicle.
- A TRAIL VEHICLE is not required.
- The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
- The use of truck mounted attenuators (TMA) on the ADVANCE WARNING and SHADOW vehicles are required.
- Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DMS 8300, Type A.
- Each vehicle shall have two-way radio communication capability.
- When work convoys must change lanes, the ADVANCE WARNING VEHICLE should change lanes first to shadow the other convoy vehicles.
- Vehicle spacing between the ADVANCED WARNING VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the ADVANCE WARNING VEHICLE in time to slow down and/or change lanes as they approach the ADVANCED WARNING VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE may vary according to terrain, work activity and other factors.
- Standard 48" X 48" diamond shaped warning signs with the same message as those shown may be used where adequate mounting space exists.
- The signs shown should be used on the Advance Warning Vehicle. As an option, a portable changeable message sign (PCMS) or a truck mounted changeable message sign (TMCMS) with a minimum character height of 12", and displaying the same legend may be substituted for these signs. An appropriate directional arrow display, simulating the size and legibility of the flashing arrow board, must be used in the second phase of the PCMS/TMCMS message. When this is done, the arrow board will not be required on the Advance Warning Vehicle.
- Standard diamond shape versions of the CW20-5 series signs may be used as an option if the rectangular signs shown are not available.
- The Advance Warning Vehicle may straddle the edgeline when shoulder width makes it necessary.

		<b>Traffic Operations Division Standard</b>	
<b>TRAFFIC CONTROL PLAN MOBILE OPERATIONS ADJACENT TO CABLE BARRIER</b>			
<b>TCP-Ab1CableBarrier</b>			
FILE:TCP-Ab1CableBarrier.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT February 2017	CONT: 6379	SECT: 38	JOB: 001
REVISIONS			HWY: IH20, etc.
	DIST: 08	COUNTY: CALLAHAN	SHEET NO.: 6