

STATE OF TEXAS
DEPARTMENT OF TRANSPORTATION

PLANS OF PROPOSED
STATE HIGHWAY IMPROVEMENT
PROJECT NO. STP 2024(855)HES
PROJECT LIMITS: VARIOUS LOCATIONS
IN VAN ZANDT COUNTY

NET LENGTH OF PROJECT = 12,973 FT. = 2.457 MI.

| | | | |
|------|-----------|-----|-----------|
| CONT | SECT | JOB | HIGHWAY |
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | | SHEET NO. |
| TYL | VAN ZANDT | | 1 |

LOCATION 1 : FM 1255
FROM DFO 2.078 TO 2.376
SPEED LIMIT = 55 MPH
AADT (2022) = 1,471

LOCATION 2 : FM 1255
FROM DFO 18.519 TO 18.790
SPEED LIMIT = 60 MPH
AADT (2022) = 657

LOCATION 3 : FM 47
FROM DFO 13.290 TO 13.577
SPEED LIMIT = 45 MPH
AADT (2022) = 2,032

LOCATION 4 : FM 47
FROM DFO 22.381 TO 22.879
SPEED LIMIT = 60 MPH
AADT (2022) = 2,186

LOCATION 5 : FM 17
FROM DFO 20.769 TO 21.188
SPEED LIMIT = 60 MPH
AADT (2022) = 1,211

LOCATION 6 : FM 17
FROM DFO 28.545 TO 28.850
SPEED LIMIT = 60 MPH
AADT (2022) = 3,570

LOCATION 7 : FM 17
FROM DFO 33.727 TO 34.106
SPEED LIMIT = 60 MPH
AADT (2022) = 4,399

INDEX OF SHEETS

| SHEET NO. | DESCRIPTION |
|-----------|------------------------------|
| 1 | TITLE SHEET |
| 2 | SUPPLEMENTAL INDEX OF SHEETS |

FINAL PLANS

LETTING DATE: _____
DATE CONTRACTOR BEGAN WORK: _____
DATE WORK WAS COMPLETED & ACCEPTED: _____
FINAL CONTRACT COST: \$ _____
CONTRACTOR : _____
USED _____ OF _____ ALOTTED DAYS: _____



FINAL AS BUILT PLANS

THE CONSTRUCTION WAS PERFORMED UNDER MY SUPERVISION
IN ACCORDANCE WITH THE PLANS AND CONTRACT

DATE: _____

AREA ENGINEER

FOR THE CONSTRUCTION OF INSTALLING LED FLASHING CHEVRONS IN CURVES



VICINITY MAP
NOT TO SCALE

* REQUIRED SIGNS SHALL BE IN ACCORDANCE WITH BC (1) - 21 THRU BC (12) - 21 AND THE "TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES".

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL-AID CONSTRUCTION CONTRACTS (FORM FHWA 1273, OCTOBER 23, 2023)

© 2024 by Texas Department of Transportation all rights reserved

EXCEPTIONS: NONE
EQUATIONS: NONE
RAILROAD CROSSINGS: NONE

1/31/2024
RECOMMENDED FOR LETTING: _____
DocuSigned by: Janita Daniels-West, P.E.
DIRECTOR OF TRANSPORTATION OPERATIONS
1/31/2024
SUBMITTED FOR LETTING: _____
DocuSigned by: Rolando Mendez
DISTRICT DESIGN ENGINEER

1/31/2024
APPROVED FOR LETTING: _____
DocuSigned by: [Signature]
DISTRICT ENGINEER

DATE: 1/24/2024 12:58:47 PM
FILE: c:\pw\infatech\xin_zhang\dms34341\HSIP_TYL_PLAN_SET_01_TITLE.dgn

SUPPLEMENTAL INDEX OF SHEETS

GENERAL

| <u>SHEET NO.</u> | <u>DESCRIPTION</u> |
|------------------|-------------------------------|
| 1 | TITLE SHEET |
| 2 | SUPPLEMENTAL INDEX OF SHEETS |
| 3, 3A-3C | GENERAL NOTES |
| 4 | ESTIMATE AND QUANTITY SHEET |
| 5 | SUMMARY OF QUANTITIES |
| 6 - 9 | SUMMARY OF SMALL SIGNS (SOSS) |

TRAFFIC CONTROL PLAN

| <u>SHEET NO.</u> | <u>STANDARDS</u> |
|------------------|-------------------------|
| * 10 - 19 | BC(1)-21 THRU BC(12)-21 |

TRAFFIC ITEMS

| <u>SHEET NO.</u> | <u>DESCRIPTION</u> |
|------------------|---------------------------------------|
| 20 | CHEVRON LAYOUT - LOCATION 1 - FM 1255 |
| 21 | CHEVRON LAYOUT - LOCATION 2 - FM 1255 |
| 22 | CHEVRON LAYOUT - LOCATION 3 - FM 47 |
| 23 | CHEVRON LAYOUT - LOCATION 4 - FM 47 |
| 24 | CHEVRON LAYOUT - LOCATION 5 - FM 17 |
| 25 | CHEVRON LAYOUT - LOCATION 6 - FM 17 |
| 26 | CHEVRON LAYOUT - LOCATION 7 - FM 17 |
| 27 | PREPARING ROW DETAILS |


| <u>SHEET NO.</u> | <u>STANDARDS</u> |
|------------------|------------------------------------|
| * 28 - 30 | TSR(3)-13 THRU TSR(5)-13 |
| * 31 - 33 | D&OM(1)-20 THRU D&OM(3)-20 |
| * 34 | SMD(GEN)-08 |
| * 35 - 37 | SMD(SLIP-1)-08 THRU SMD(SLIP-3)-08 |

ENVIRONMENTAL ISSUES

| <u>SHEET NO.</u> | <u>DESCRIPTION</u> |
|------------------|--------------------|
| * 38 - 39 | SWP3 |
| * 40 | EPIC |

| <u>SHEET NO.</u> | <u>STANDARDS</u> |
|------------------|------------------|
| * 41 - 43 | EC(9)-16 |

* THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ON THIS SHEET HAVE BEEN ISSUED BY ME AND ARE APPLICABLE TO THIS PROJECT.



Z. Siddique

1/24/2024

| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |



SUPPLEMENTAL INDEX OF SHEETS

SHEET 1 OF 1

| CONT | SECT | JOB | HIGHWAY |
|------|-----------|-----------|---------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 2 | |

County: Van Zandt**Control:** 0910-12-141**Highway:** VA**GENERAL NOTES:****GENERAL.**

Contractor questions on this project are to be addressed to the following individuals:

Juanita Daniels-West, P.E. Juanita.Danielswest@txdot.gov

Steven Swindell, P.E. Steven.Swindell@txdot.gov

For Q&A on Proposals navigate to:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>

Use the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink for the project and click on the link in the window that pops up to view the Q&A.

All relevant project documentation including Contract Time Determinations and cross-sections will still be posted to the districts FTP website.

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting%20Responses/Tyler%20District/Construction%20Projects>

ITEM 5. CONTROL OF THE WORK

If utility lines need adjustments during construction operations, modify operations and continue the work in a manner that will allow others to make the utility adjustments. Additional working time may be allowed for delays caused by these utility adjustments.

Utility locations shown on the plans are approximate. Contact utilities in accordance with Article 5.6., "Cooperating With Utilities."

Prior to beginning driveway and intersection work, submit a detailed construction sequence to be approved by the Engineer. Driveway and intersection completion includes existing surface removal, structure removal, removal of debris from the project site, installing the new RCP and SETs, backfilling, grading ditches to drain, and installing the permanent driveway or intersection surface (or all-weather drive surface as allowed).

ITEM 6. CONTROL OF MATERIALS

To comply with the latest provisions of Build America, Buy America Act (BABA Act) of the Bipartisan Infrastructure Law, the Contractor must submit an original of the TxDOT

County: Van Zandt**Control:** 0910-12-141**Highway:** VA

Construction Material Buy America Certification Form for all items classified as construction materials. This form is not required for materials classified as a manufactured product.

Refer to the Buy America Material Classification Sheet for clarification on material categorization.

The Buy America Material Classification Sheet is located at the link below:

<https://www.txdot.gov/business/resources/materials/buy-america-material-classification-sheet.html>

ITEM 7. LEGAL RELATIONS AND RESPONSIBILITIES

Concrete truck drivers and concrete pump operators are required to wash out only in designated areas specifically constructed for eliminating run-off. Dispose of materials in accordance with federal, state, and local requirements.

Maintain positive drainage for permanent and temporary work for the duration of the project. The Contractor will be responsible for any items associated with the temporary or interim drainage and all related maintenance. This work will be subsidiary to various bid items.

The total disturbed area for this project is 0 acres. The disturbed area in this project and the Contractor Project Specific Locations (PSL's) within 1 mile of the project limits for the Contract will further establish the authorization requirements for storm water discharges. The Department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans. Obtain any required authorization from the TCEQ for any Contractor PSL for construction support activities on or off the ROW. When the total area disturbed for all projects in the Contract and PSLs within 1 mile of the project limits exceed 5 acres, before disturbance, provide a copy of the Contractor NOI for PSLs on the ROW and within 1 mile of the project limits to the Engineer and to any local government that operates a Municipal Separate Storm Sewer System (MSSS).

In accordance with Article 7.9, provide and maintain adequate, neat and sanitary toilet accommodations within the project limits for employees, including State employees.

No significant traffic generator events identified.

ITEM 8. PROSECUTION AND PROGRESS

Working days will be computed and charged in accordance with Section 8.3.1.1., "Five-Day Workweek."

Project Number:

Sheet 3A

County: Van Zandt

Control: 0910-12-141

Highway: VA

ITEM 9. MEASUREMENT & PAYMENT

In accordance with Article 9.1., "Measurement of Quantities," furnish the tare and maximum gross weights as well as the volume capacity of all vehicles, trucks, truck-tractors, trailers, semi-trailers, or combination of such vehicles used to deliver materials for this Contract. Also, furnish calculations supporting these weights and capacities. Provide all measurements required for pay a minimum of 2 days before the trucks are used.

ITEM 100. PREPARING RIGHT OF WAY

Perform work as necessary off the right of way on temporary or drainage easements and at those locations where improvements have been taken or partially taken by right of way acquisition. Review these locations with the Area Engineer. The cost of this work will be included in the unit price bid for this Item.

Burning will not be permitted within the right of way.

Do not use a forestry type mulcher for grinding. Tub grinders will be allowed.

Dispose of trees from the right of way within 24 hours of removal.

ITEM 104. REMOVING CONCRETE

Blasting will not be permitted on this project.

The stockpile site for salvageable material is located at 15500 FM 1255, Canton, TX 75103.

ITEM 421. HYDRAULIC CEMENT CONCRETE

Provide the Engineer with a mixture design report using Department-provided software in accordance with Section 421.4.1., "Classification of Concrete Mix Designs," of the standard specifications. Include in the report the producer's plant, all materials sources, and a unique identification number for the design.

Air is not required on concrete cast-in-place elements on this project. If the Contractor proposes the use of an existing concrete design containing air, the Engineer must approve the design in writing before placement. If used, air testing will be performed in accordance with the specifications.

Provide a calibrated machine capable of testing both 4 in. and 6 in. compressive cylinders. Provide the calibration certifications prior to setup and ensure calibrations do not expire during the project.

Project Number:

Sheet 3A

County: Van Zandt

Control: 0910-12-141

Highway: VA

ITEM 502. BARRICADES, SIGNS, AND TRAFFIC HANDLING

The traffic control plan for this Contract consists of: the installation and maintenance of warning signs and other traffic control devices shown on the plans; specification data, which may be included in the general notes; applicable provisions of the Texas Manual on Uniform Traffic Control Devices (TMUTCD); traffic control plan sheets included on the plans; standard BC sheets; Compliant Work Zone Traffic Control Device List, and Item 502 of the standard specifications.

Use ground-mounted sign mounts with two posts for all temporary work zone signs unless otherwise directed.

Inspect and correct deficiencies each day throughout the duration of the Contract. In accordance with Article 502.4., "Payment," no payment will be made for the month if the Contractor fails to provide or properly maintain signs and devices in compliance with Contract requirements. Temporary warning signs that are visible when conditions do not apply will be considered improper maintenance of signs.

Provide at least one employee on call nights and weekends (or any other time that work is not in progress) for maintenance of signs and traffic control devices. This employee must have an address and telephone number near the project, as approved. Notify the Engineer in writing of the name, address, and telephone number of this employee. The Engineer will furnish this information to local law enforcement officials.

In addition to providing a Contractor's Responsible Person and a phone number for emergency contact, have an employee available to respond on the project for emergencies and for taking corrective measures within 30 minutes.

Sign all roads intersecting the project in accordance with current BC standards.

Refer to the traffic control plan sheets for traffic handling through the work area. Contractor may vary the signing arrangement and spacing as necessary to fit field conditions; however, any proposed changes in the traffic control plan must be approved before implementation.

When the sequence of work is shown on the plans, the Contractor may submit an alternate proposal for approval. Submit in writing all proposed variations and revisions.

High-visibility safety apparel is required for workers in accordance with the General Notes on current BC standards.

Place and maintain signs, channelizing devices, and flaggers to direct and route traffic at any location and for any period of time as may be required or directed.

County: Van Zandt

Control: 0910-12-141

Highway: VA

When operations require a lane closure, provide cones, vertical panels, drums, signs, flaggers, and flashing arrow panels as necessary to route traffic around the closed lane as shown on the plans and as directed. Lane closures will be limited to one specific lane as directed.

Lane closures will not be allowed before 8:30 A.M. unless otherwise directed.

Unless otherwise approved, construction operations will not be allowed on Good Friday, Easter weekend, the Friday before Memorial Day thru Memorial Day, July 4th, the Friday before Labor Day thru Labor Day, the Wednesday before Thanksgiving Day thru Sunday, Christmas Eve, Christmas Day, New Year's Eve, New Year's Day, or on any other high traffic days or holidays as determined by the Engineer.

Erect R4-1 (Do Not Pass) and R4-2 (Pass With Care) signs to mark existing no-passing zones as directed. (These signs will not be required if these zones will not be eliminated during construction.)

Maintain existing roadside signs within this project's limits during this Contract. In order to accommodate the grading or other operations, temporarily relocate these signs in accordance with the TMUTCD as directed. Use ground-mounted sign mounts with two posts for all relocated signs unless otherwise directed. This work will not be paid for directly, but will be subsidiary to Item 502.

Provide truck-mounted attenuators (TMA) as shown on the appropriate traffic control plan sheets. Provide a letter certifying that all TMA used on this project meet NCHRP 350 or AASHTO Manual for Assessing Safety Hardware (MASH) requirements.

Regulate all construction activities and equipment to minimize inconvenience to the traveling public. At points where it is necessary for trucks to stop, load, or unload, provide warning signs and flaggers to protect the traveling public.

The pavement must be entirely open to traffic each night. Remove or clearly barricade all material stockpiles, equipment left overnight, or any obstruction within 30 ft. of a travelway as approved.

The Contractor Force Account "Safety Contingency" is intended to be used for work zone enhancements that could not be foreseen in the project planning and design stage for the purpose of improving the effectiveness of the Traffic Control Plan. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

Provide flaggers at county roads, commercial driveways, and other intersecting roadways deemed necessary by the Engineer to maintain control of the work zone during one-lane two-way

County: Van Zandt

Control: 0910-12-141

Highway: VA

operations. Provide communication radios to each flagger in the work zone and the pilot vehicle operator.

Provide a pilot vehicle.

Prior to beginning work, the Contractor and Engineer must agree on the allowable length of lane closure.

All work required by these general notes, except as provided for by Item 502, will not be paid for directly, but will be subsidiary to Item 502 unless otherwise shown on the plans.

ITEM 506. TEMPORARY EROSION, SEDIMENTATION, AND ENVIRONMENTAL CONTROLS

Remove dirt, silt, rocks, debris, and other foreign matter that accumulates in all structures due to project erosion and Contractor's operations. Keep stream channels open at all times. This work will not be paid for directly, but will be subsidiary to this Item.

The Storm Water Pollution Prevention Plan (SWP3) consists of temporary erosion control measures needed and provided for under this Item. The disturbed area is less than one acre and use of erosion control measures is not anticipated. If physical conditions encountered at the job site require necessary controls, BMP installation, maintenance, and removal will be paid as extra work on a force account basis per Articles 4.4 and 9.7

Provide the following Items for the SWP3 for this Contract as directed on a force account basis:

Temporary sediment control fence, seeding for erosion control, earthwork for erosion control, and vegetative watering.

ITEM 636. SIGNS

Install signs in accordance with the Department of Transportation's "Sign Crew Field Book," latest edition, or as directed.

All signs removed from the project are deemed salvageable and become the property of the Department. Stockpile salvageable material at the TxDOT Canton Maintenance Section located at 15500 FM 1255, Canton, TX 75103.

ITEM 644. SMALL ROADSIDE SIGN ASSEMBLIES

Sign types for which details are not shown on the plans must conform to "Standard Highway Sign Designs for Texas," latest edition.

Project Number:

Sheet 3C

County: Van Zandt

Control: 0910-12-141

Highway: VA

Before construction begins, locate all Texas Reference Marker (TRM) signs and Adopt-a-Highway signs using survey control methods for accuracy. Provide the survey data to the Engineer. If either type of sign is relocated during construction activities, survey the sign location and notify the Engineer before placement of the permanent sign.

Stake all sign locations for approval prior to placement.

ITEM 6185. TRUCK MOUNTED ATTENUATOR (TMA)

Shadow vehicles with truck mounted attenuator (TMA) are required on the traffic control plan and TCP standards for this project. The Contractor will be responsible for determining if one or more of these traffic control operations will be ongoing at the same time to determine the total number of TMAs needed for the project. Additional truck mounted attenuators (TMAs) may be required as deemed necessary by the Engineer.

The TMA/TA used for installation/removal of traffic control for a work area will be subsidiary to the TMA/TA used to perform the work.

ITEM 6350. DYNAMIC LED CURVE WARNING SYSTEM

Warning system must be serviceable for a minimum of 10 years. The need to replace one unit within the system will not require the replacement of the entire system. Updates to existing units necessary to replace a damaged or non-functioning unit must be provided without cost to the Department. If updates cannot be made to existing units, then those units must be replaced by the manufacturer without cost to the Department. This warranty must be provided before installation of any signs. Products which cannot be warrantied in this way are not approved for installation.

LEDs must be used to enhance conspicuity of the chevron symbol or legend and not the border. The LEDs must be arranged to create the appearance of a solid line of light. A product that uses approximately 110 LEDs to outline the chevron of a 24"x30" W1-8 should meet this requirement.



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0910-12-141

DISTRICT Tyler
HIGHWAY Various

COUNTY Van Zandt

| CONTROL SECTION JOB | | | | 0910-12-141 | | TOTAL EST. | TOTAL FINAL |
|---------------------|-----------|---|------|-------------|-------|------------|-------------|
| PROJECT ID | | | | A00177793 | | | |
| COUNTY | | | | Van Zandt | | | |
| HIGHWAY | | | | Various | | | |
| ALT | BID CODE | DESCRIPTION | UNIT | EST. | FINAL | | |
| | 100-6002 | PREPARING ROW | STA | 85.900 | | 85.900 | |
| | 500-6001 | MOBILIZATION | LS | 1.000 | | 1.000 | |
| | 502-6001 | BARRICADES, SIGNS AND TRAFFIC HANDLING | MO | 4.000 | | 4.000 | |
| | 644-6001 | IN SM RD SN SUP&AM TY10BWG(1)SA(P) | EA | 67.000 | | 67.000 | |
| | 644-6076 | REMOVE SM RD SN SUP&AM | EA | 31.000 | | 31.000 | |
| | 6185-6002 | TMA (STATIONARY) | DAY | 25.000 | | 25.000 | |
| | 6350-6001 | LEAD LED CHEVRON | EA | 16.000 | | 16.000 | |
| | 6350-6002 | LED CHEVRON | EA | 94.000 | | 94.000 | |
| | 18 | SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING) | LS | 1.000 | | 1.000 | |
| | | EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART) | LS | 1.000 | | 1.000 | |

| SMALL SIGN SUMMARY | | | | |
|---------------------------|---|--------------------------|------------------|-------------|
| LAYOUT SHEET & LOCATION | ITEM 644 | | ITEM 6350 | |
| | INSTALL SM RD SN SUP & AM TY 10BWG (1)SA(P) | REMOVE SM RD SN SUP & AM | LEAD LED CHEVRON | LED CHEVRON |
| | EA | EA | EA | EA |
| SHEET 1 OF 7 - LOCATION 1 | 8 | 6 | 2 | 10 |
| SHEET 2 OF 7 - LOCATION 2 | 8 | 2 | 2 | 10 |
| SHEET 3 OF 7 - LOCATION 3 | 6 | 4 | 2 | 10 |
| SHEET 4 OF 7 - LOCATION 4 | 15 | 9 | 4 | 22 |
| SHEET 5 OF 7 - LOCATION 5 | 13 | 2 | 2 | 20 |
| SHEET 6 OF 7 - LOCATION 6 | 9 | 2 | 2 | 12 |
| SHEET 7 OF 7 - LOCATION 7 | 8 | 6 | 2 | 10 |
| PROJECT TOTAL | 67 | 31 | 16 | 94 |

| PREPARING ROW SUMMARY | |
|---------------------------|---------------|
| LAYOUT SHEET & LOCATION | ITEM 100 |
| | PREPARING ROW |
| | STATION |
| SHEET 1 OF 7 - LOCATION 1 | 10.00 |
| SHEET 2 OF 7 - LOCATION 2 | 8.00 |
| SHEET 3 OF 7 - LOCATION 3 | 8.00 |
| SHEET 4 OF 7 - LOCATION 4 | 20.70 |
| SHEET 5 OF 7 - LOCATION 5 | 17.60 |
| SHEET 6 OF 7 - LOCATION 6 | 11.60 |
| SHEET 7 OF 7 - LOCATION 7 | 10.00 |
| PROJECT TOTAL | 85.90 |

NOTE: SEE PREPARING ROW DETAILS (SHEET 27) FOR ADDITIONAL INFORMATION.

| BASIS OF ESTIMATE | | | |
|-------------------|--|----------|------|
| ITEM | DESCRIPTION | QUANTITY | UNIT |
| 500 | MOBILIZATION | 1 | LS |
| 502 | BARRICADES, SIGNS AND TRAFFIC HANDLING | 4 | MO |

| TRUCK MOUNTED ATTENUATOR SUMMARY | | |
|----------------------------------|------------------|------------------|
| LAYOUT SHEET & LOCATION | NUMBER OF TRUCKS | ITEM 6185 |
| | | TMA (STATIONARY) |
| | EA | DAY |
| SHEET 1 OF 7 - LOCATION 1 | 1 | 3 |
| SHEET 2 OF 7 - LOCATION 2 | 1 | 3 |
| SHEET 3 OF 7 - LOCATION 3 | 1 | 3 |
| SHEET 4 OF 7 - LOCATION 4 | 1 | 5 |
| SHEET 5 OF 7 - LOCATION 5 | 1 | 4 |
| SHEET 6 OF 7 - LOCATION 6 | 1 | 4 |
| SHEET 7 OF 7 - LOCATION 7 | 1 | 3 |
| PROJECT TOTAL | 7 | 25 |

NOTE: ESTIMATED NUMBER OF TRUCKS IS FOR WORKING AT ONE LOCATION AT A TIME. ADDITIONAL TRUCKS WILL BE REQUIRED IF WORKING AT MULTIPLE LOCATIONS AT THE SAME TIME.

| | | | |
|--|-----------|----------|-----------|
| | | | |
| NO. | DATE | REVISION | APPROVED |
| © 2024 | | | |
| Engineers & Innovators, LLC TBPE REGISTRATION NO. F-18368 | | | |
| <h2>SUMMARY OF QUANTITIES</h2> | | | |
| SHEET 1 OF 1 | | | |
| CONT | SECT | JOB | HIGHWAY |
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | | SHEET NO. |
| TYL | VAN ZANDT | | 5 |

100% SUBMITTAL

SUMMARY OF SMALL SIGNS


| PLAN SHEET NO. | SIGN NO. | SIGN NOMENCLATURE | SIGN | DIMENSIONS | FLAT ALUMINUM (TYPE A) | EXAL ALUMINUM (TYPE G) | SM RD SGN ASSM TY XXXXX (X) XX (X- XXXX) | | | | BRIDGE MOUNT CLEARANCE SIGNS (See Note 2) |
|----------------|----------|-------------------|---|--------------------|------------------------|------------------------|---|--------|--|--|---|
| | | | | | | | POST TYPE | POSTS | ANCHOR TYPE | MOUNTING DESIGNATION | |
| | | | | | | | FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80 | 1 or 2 | UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic | PREFABRICATED P = "Plain" T = "T" U = "U" | |
| 1 | S1 | W1-2R | SYMBOL - HORIZ CURVE RIGHT | 36 x 36 | X | | 10BWG | 1 | SA | P | |
| | | W13-1P | 50 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | |
| | A1 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | A2 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | A3 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | A4 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| A5 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| A6 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| S2 | W1-2L | W13-1P | SYMBOL - HORIZ CURVE LEFT 50 MPH <ADVISORY SPEED PLAQUE> | 36 x 36 18 x 18 | X X | | 10BWG | 1 | SA | P | |
| 2 | S3 | W1-2R | SYMBOL - HORIZ CURVE RIGHT | 36 x 36 | X | | 10BWG | 1 | SA | P | |
| | | W13-1P | 45 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | |
| | B1 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | B2 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | B3 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | B4 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| B5 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| B6 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| S4 | W1-2L | W13-1P | SYMBOL - HORIZ CURVE LEFT 45 MPH <ADVISORY SPEED PLAQUE> | 36 x 36 18 x 18 | X X | | 10BWG | 1 | SA | P | |
| 3 | C1 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| | C2 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | |
| C3 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| C4 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |

| ALUMINUM SIGN BLANKS THICKNESS | |
|--------------------------------|-------------------|
| Square Feet | Minimum Thickness |
| Less than 7.5 | 0.080" |
| 7.5 to 15 | 0.100" |
| Greater than 15 | 0.125" |

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.
 PLOT DRIVER: TXDOT_PDF_BW_LEVELS.plt
 PENTABLE: PENTABLE_H\$IP_TYL.tbl
 DATE: 1/24/2024 12:59:48 PM
 FILE: c:\pw-infratech\xin.zhang\dms340301\TXDOT_TYL_SET_01_S055.dgn



NO. DATE REVISION APPROVED

Texas Department of Transportation

infraTECH
Engineers & Innovators, LLC
TBPE REGISTRATION NO. F-18368

SUMMARY OF SMALL SIGNS
SOSS

SHEET 1 OF 4

| | | | |
|------|-----------|-----------|---------|
| CONT | SECT | JOB | HIGHWAY |
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 6 | |

SUMMARY OF SMALL SIGNS

SM RD SGN ASSM TY XXXXX (X) XX (X- XXXX)

| PLAN SHEET NO. | SIGN NO. | SIGN NOMENCLATURE | SIGN | DIMENSIONS | FLAT ALUMINUM (TYPE A) | EXAL ALUMINUM (TYPE G) | SM RD SGN ASSM TY XXXXX (X) XX (X- XXXX) | | | | BRIDGE MOUNT CLEARANCE SIGNS (See Note 2) | |
|----------------|----------------|-------------------|--------------------------------|--------------------------------|------------------------|------------------------|---|--------|--|--|---|---|
| | | | | | | | POST TYPE | POSTS | ANCHOR TYPE | MOUNTING DESIGNATION | | |
| | | | | | | | FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80 | 1 or 2 | UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic | PREFABRICATED P = "Plain" T = "T" U = "U" | | 1EXT or 2EXT = # of Ext BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels |
| 3 | C5 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | C6 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | 4 | S5 | W1-4L W13-1P | SYMBOL - REVERSE CURVE LEFT | 36 x 36 | X | | 10BWG | 1 | SA | P | |
| | | | | 45 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | |
| D1 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| D2 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| D3 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| D4 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| D5 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| D6 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| D7 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| E1 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| E2 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| E3 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| E4 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| E5 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| E6 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| 5 | S7 | W1-2L W13-1P | SYMBOL - REVERSE CURVE LEFT | 36 x 36 | X | | 10BWG | 1 | SA | P | | |
| | | | 50 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | | |
| F1 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| F2 | W1-8R W1-8L | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |


| ALUMINUM SIGN BLANKS THICKNESS | |
|--------------------------------|-------------------|
| Square Feet | Minimum Thickness |
| Less than 7.5 | 0.080" |
| 7.5 to 15 | 0.100" |
| Greater than 15 | 0.125" |

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

- NOTE:**
- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
 - For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
 - For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

PLOT DRIVER: TXDOT_PDF_BW_LEVELS.plt; PENTABLE: PENTABLE_H\$IP_TYL.tbi
DATE: 1/24/2024 12:59:48 PM
FILE: c:\pw-infrotech\in_zhang\dms34030\TXDOT_TYL_SET_01_S055.dgn



| | | | |
|-------------------------------|------|-----------|-----------|
| SUMMARY OF SMALL SIGNS | | | |
| SOSS | | | |
| SHEET 2 OF 4 | | | |
| CONT | SECT | JOB | HIGHWAY |
| 0910 | 12 | 141 | VARIOUS |
| DIST | | COUNTY | SHEET NO. |
| TYL | | VAN ZANDT | 7 |

SUMMARY OF SMALL SIGNS

SM RD SGN ASSM TY XXXXX (X) XX (X- XXXX)

| PLAN SHEET NO. | SIGN NO. | SIGN NOMENCLATURE | SIGN | DIMENSIONS | FLAT ALUMINUM (TYPE A) | EXAL ALUMINUM (TYPE G) | SM RD SGN ASSM TY XXXXX (X) XX (X- XXXX) | | | | BRIDGE MOUNT CLEARANCE SIGNS (See Note 2) | |
|----------------|----------|--------------------------------|--------------------------------|------------|------------------------|------------------------|---|--------|--|-----------------------------------|---|-------------------------|
| | | | | | | | POST TYPE | POSTS | ANCHOR TYPE | MOUNTING DESIGNATION | | |
| | | | | | | | | | | PREFABRICATED | | 1EXT or 2EXT = # of Ext |
| | | | | | | | FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80 | 1 or 2 | UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic | P = "Plain" T = "T" U = "U" | BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels | TY = TYPE |
| | | | | | | | | | | | | TY N TY S |
| 5 | F3 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | F4 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | F5 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | F6 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | F7 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | F8 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| W1-8L | | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| F9 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| F10 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| F11 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| S8 | W1-2R | SYMBOL - HORIZ CURVE RIGHT | | 36 x 36 | X | | 10BWG | 1 | SA | P | | |
| | W13-1P | 50 MPH <ADVISORY SPEED PLAQUE> | | 18 x 18 | X | | | | | | | |
| 6 | S9 | W1-2R | SYMBOL - HORIZ CURVE RIGHT | 36 x 36 | X | | 10BWG | 1 | SA | P | | |
| | | W13-1P | 50 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | | |
| | G1 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | G2 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | G3 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | G4 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| G5 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| G6 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| G7 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | | |
| | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | | |
| S10 | W1-2L | SYMBOL - HORIZ CURVE LEFT | | 36 x 36 | X | | 10BWG | 1 | SA | P | | |
| | W13-1P | 50 MPH <ADVISORY SPEED PLAQUE> | | 18 x 18 | X | | | | | | | |

| ALUMINUM SIGN BLANKS THICKNESS | |
|--------------------------------|-------------------|
| Square Feet | Minimum Thickness |
| Less than 7.5 | 0.080" |
| 7.5 to 15 | 0.100" |
| Greater than 15 | 0.125" |

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.
<http://www.txdot.gov/>


NOTE:

- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
- For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
- For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


PLOT DRIVER: TXDOT_PDF_BW_LEVELS.plt
PENTABLE: PENTABLE_HSIP_TYL.tbi

DATE: 1/24/2024 12:59:49 PM
FILE: c:\pw-infrotech\xin.zhang\dms34030\TXDOT_TYL_SET_01_S055.dgn




1/24/2024

| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |



© 2024



Engineers & Innovators, LLC
TBPE REGISTRATION NO. F-18368

SUMMARY OF SMALL SIGNS

S055

SHEET 3 OF 4

| CONT | SECT | JOB | HIGHWAY |
|------|------|-----------|-----------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | | COUNTY | SHEET NO. |
| TYL | | VAN ZANDT | 8 |

100% SUBMITTAL

SUMMARY OF SMALL SIGNS

| PLAN SHEET NO. | SIGN NO. | SIGN NOMENCLATURE | SIGN | DIMENSIONS | FLAT ALUMINUM (TYPE A) | EXAL ALUMINUM (TYPE G) | SM RD SGN ASSM TY XXXXX (X) XX (X- XXXX) | | | | BRIDGE MOUNT CLEARANCE SIGNS (See Note 2) | |
|----------------|----------|-------------------|--------------------------------|------------|------------------------|------------------------|---|--------|--|-----------------------------------|--|-------------------------|
| | | | | | | | POST TYPE | POSTS | ANCHOR TYPE | MOUNTING DESIGNATION | | |
| | | | | | | | | | | PREFABRICATED | | 1EXT or 2EXT = # of Ext |
| | | | | | | | | | | | | |
| | | | | | | | FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80 | 1 or 2 | UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic | P = "Plain" T = "T" U = "U" | BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels | TY = TYPE |
| 7 | S11 | W1-2L | SYMBOL - HORIZ CURVE LEFT | 36 x 36 | X | | 10BWG | 1 | SA | P | | |
| | | W13-1P | 50 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | | |
| | H1 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | H2 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | H3 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | H4 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | H5 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | H6 | W1-8R | <CHEVRON RIGHT> | 24 x 30 | X | | 10BWG | 1 | SA | P | | |
| | | W1-8L | <CHEVRON LEFT> | 24 x 30 | X | | | | | | | |
| | S12 | W1-2R | SYMBOL - HORIZ CURVE RIGHT | 36 x 36 | X | | 10BWG | 1 | SA | P | | |
| | | W13-1P | 50 MPH <ADVISORY SPEED PLAQUE> | 18 x 18 | X | | | | | | | |

| ALUMINUM SIGN BLANKS THICKNESS | |
|--------------------------------|-------------------|
| Square Feet | Minimum Thickness |
| Less than 7.5 | 0.080" |
| 7.5 to 15 | 0.100" |
| Greater than 15 | 0.125" |

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.

<http://www.txdot.gov/>


NOTE:

- Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
- For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
- For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

PLOT DRIVER: TXDOT_PDF_BW_LEVELS.plt
PENTABLE: HSIP_TYL.tbl

DATE: 1/24/2024 12:59:49 PM
FILE: c:\pw-infratech\in.zhang\dms34030\TXDOT_TYL_SET_01_SOSS.dgn



| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |



SUMMARY OF SMALL SIGNS

SOSS

| CONT | SECT | JOB | HIGHWAY |
|---------------|------|-----|-----------|
| 0910 | 12 | 141 | VARIOUS |
| DIST COUNTY | | | SHEET NO. |
| TYL VAN ZANDT | | | 9 |

SHEET 4 OF 4

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:22:09 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\bc-21.dgn

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY NOTES:

1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

1. Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).

| |
|---|
| THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov |
| COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD) |
| DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) |
| MATERIAL PRODUCER LIST (MPL) |
| ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)" |
| STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD) |
| TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) |
| TRAFFIC ENGINEERING STANDARD SHEETS |

SHEET 1 OF 12




**BARRICADE AND CONSTRUCTION
GENERAL NOTES
AND REQUIREMENTS**

BC (1) -21

| | | | | | | | | | |
|-----------|---------------|------|-----------|-----|-----------|-----|-------|-----|-------|
| FILE: | bc-21.dgn | DN: | TxDOT | CK: | TxDOT | DW: | TxDOT | CK: | TxDOT |
| © TxDOT | November 2002 | CONT | SECT | JOB | HIGHWAY | | | | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS | | | | |
| 4-03 | 7-13 | DIST | COUNTY | | SHEET NO. | | | | |
| 9-07 | 8-14 | TYL | VAN ZANDT | | 10 | | | | |
| 5-10 | 5-21 | | | | | | | | |


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPICAL LOCATION OF CROSSROAD SIGNS



- ## May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
 - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
 - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
 - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
 - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
 - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

T-INTERSECTION



CSJ LIMITS AT T-INTERSECTION

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING^{1,5,6}

| Sign Number or Series | SIZE | | SPACING | |
|---------------------------------------|-------------------|--------------------|------------------|----------------------------------|
| | Conventional Road | Expressway/Freeway | Posted Speed MPH | Sign Δ Spacing "X" Feet (Apprx.) |
| CW20 ⁴ | 48" x 48" | 48" x 48" | 30 | 120 |
| CW21 | | | 35 | 160 |
| CW22 | | | 40 | 240 |
| CW23 | | | 45 | 320 |
| CW1, CW2, CW7, CW8, CW9, CW11, CW14 | 36" x 36" | 48" x 48" | 50 | 400 |
| CW3, CW4, CW5, CW6, CW8-3, CW10, CW12 | 48" x 48" | 48" x 48" | 60 | 600 ² |
| | | | 65 | 700 ² |
| | | | 70 | 800 ² |
| | | | 80 | 1000 ² |
| * | | | * | * ³ |


* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

Δ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS




When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS



SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS



NOTES

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "X" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
 - CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
 - Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
 - Contractor will install a regulatory speed limit sign at the end of the work zone.

| LEGEND | |
|--------|---|
| — | Type 3 Barricade |
| ○ ○ ○ | Channelizing Devices |
| ■ | Sign |
| X | See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements. |

SHEET 2 OF 12



BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC(2)-21


| | | | | |
|-----------------------|-----------|-----------|-----------|-----------|
| FILE: bc-21.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| © TxDOT November 2002 | CONT | SECT | JOB | HIGHWAY |
| REVISIONS | 0910 | 12 | 141 | VARIOUS |
| 9-07 8-14 | DIST | COUNTY | SHEET NO. | |
| 7-13 5-21 | TYL | VAN ZANDT | 11 | |

DATE: 1/12/2024 5:22:12 PM
FILE: c:\pw-inf\fratech\has.in.jinna\dms34488\bc-21.dgn

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:

| | |
|--------------------|----------------|
| 40 mph and greater | 0.2 to 2 miles |
| 35 mph and less | 0.2 to 1 mile |
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
 - Law enforcement.
 - Flagger stationed next to sign.
 - Portable changeable message sign (PCMS).
 - Low-power (drone) radar transmitter.
 - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE: 1/12/2024 5:22:15 PM
FILE: c:\pw-InfraTech\has.in.jinna\dms34488\bc-21.dgn

SHEET 3 OF 12

| | | | |
|---|---------------|-----------|-----------|
| | | | |
| <h2>BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT</h2> | | | |
| <h3>BC (3) -21</h3> | | | |
| FILE: | bc-21.dgn | DN: TxDOT | ck: TxDOT |
| © TxDOT | November 2002 | CONT | SECT |
| REVISIONS | | JOB | HIGHWAY |
| 9-07 | 8-14 | 0910 12 | 141 |
| 7-13 | 5-21 | DIST | COUNTY |
| | | TYL | VAN ZANDT |
| | | SHEET NO. | |
| | | 12 | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS



Attachment to wooden supports will be by bolts and nuts or screws. Use TxDOT's or manufacturer's recommended procedures for attaching sign substrates to other types of sign supports

Nails shall NOT be allowed.
Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.

Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - Long-term stationary - work that occupies a location more than 3 days.
 - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - Short, duration - work that occupies a location up to 1 hour.
 - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

STOP/SLOW PADDLES

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflectORIZED when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



| SHEETING REQUIREMENTS (WHEN USED AT NIGHT) | | |
|--|--------|--|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | RED | TYPE B OR C SHEETING |
| BACKGROUND | ORANGE | TYPE B _{FL} OR C _{FL} SHEETING |
| LEGEND & BORDER | WHITE | TYPE B OR C SHEETING |
| LEGEND & BORDER | BLACK | ACRYLIC NON-REFLECTIVE FILM |

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.



Texas Department of Transportation
Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC (4) -21


| | | | | |
|-----------------------|-----------|-----------|-----------|-----------|
| FILE: bc-21.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| © TxDOT November 2002 | CONT | SECT | JOB | HIGHWAY |
| REVISIONS | 0910 | 12 | 141 | VARIOUS |
| 9-07 8-14 | DIST | COUNTY | SHEET NO. | |
| 7-13 5-21 | TYL | VAN ZANDT | 13 | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act." No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.






SKID MOUNTED WOOD SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

GENERAL NOTES

- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final connection.
- No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
- When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.

- * See BC(4) for definition of "Work Duration."
- ** Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
- See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5)-21

| | | | | |
|-----------------------|-----------|-----------|-----------|-----------|
| FILE: bc-21.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| © TxDOT November 2002 | CONT | SECT | JOB | HIGHWAY |
| REVISIONS | 0910 | 12 | 141 | VARIOUS |
| 9-07 8-14 | DIST | COUNTY | SHEET NO. | |
| 7-13 5-21 | TYL | VAN ZANDT | 14 | |

DATE: 1/12/2024 5:22:20 PM
FILE: c:\pw-inf\fratech\has.in.jinna\dms34488\bc-21.dgn

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

| WORD OR PHRASE | ABBREVIATION | WORD OR PHRASE | ABBREVIATION |
|------------------------|--------------|----------------|--------------|
| Access Road | ACCS RD | Major | MAJ |
| Alternate | ALT | Miles | MI |
| Avenue | AVE | Miles Per Hour | MPH |
| Best Route | BEST RTE | Minor | MNR |
| Boulevard | BLVD | Monday | MON |
| Bridge | BRDG | Normal | NORM |
| Cannot | CANT | North | N |
| Center | CTR | Northbound | (route) N |
| Construction Ahead | CONST AHD | Parking | PKING |
| CROSSING | XING | Road | RD |
| Detour Route | DETOUR RTE | Right Lane | RT LN |
| Do Not | DONT | Saturday | SAT |
| East | E | Service Road | SERV RD |
| Eastbound | (route) E | Shoulder | SHLDR |
| Emergency | EMER | Slippery | SLIP |
| Emergency Vehicle | EMER VEH | South | S |
| Entrance, Enter | ENT | Southbound | (route) S |
| Express Lane | EXP LN | Speed | SPD |
| Expressway | EXPWY | Street | ST |
| XXXX Feet | XXXX FT | Sunday | SUN |
| Fog Ahead | FOG AHD | Telephone | PHONE |
| Freeway | FRWY, FWY | Temporary | TEMP |
| Freeway Blocked | FWY BLKD | Thursday | THURS |
| Friday | FRI | To Downtown | TO DWNTN |
| Hazardous Driving | HAZ DRIVING | Traffic | TRAF |
| Hazardous Material | HAZMAT | Travelers | TRVLR |
| High-Occupancy Vehicle | HOV | Tuesday | TUES |
| Highway | HWY | Time Minutes | TIME MIN |
| Hour(s) | HR, HRS | Upper Level | UPR LEVEL |
| Information | INFO | Vehicles (s) | VEH, VEHS |
| It Is | ITS | Warning | WARN |
| Junction | JCT | Wednesday | WED |
| Left | LFT | Weight Limit | WT LIMIT |
| Left Lane | LFT LN | West | W |
| Lane Closed | LN CLOSED | Westbound | (route) W |
| Lower Level | LWR LEVEL | Wet Pavement | WET PVMT |
| Maintenance | MAINT | Will Not | WONT |

Roadway designation # IH-number, US-number, SH-number, FM-number

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

| |
|-----------------------|
| FREEWAY CLOSED X MILE |
| ROAD CLOSED AT SH XXX |
| ROAD CLSD AT FM XXXX |
| RIGHT X LANES CLOSED |
| CENTER LANE CLOSED |
| NIGHT LANE CLOSURES |
| VARIOUS LANES CLOSED |
| EXIT CLOSED |
| MALL DRIVEWAY CLOSED |
| XXXXXXXX BLVD CLOSED |

Other Condition List

| |
|--------------------------|
| FRONTAGE ROAD CLOSED |
| SHOULDER CLOSED XXX FT |
| RIGHT LN CLOSED XXX FT |
| RIGHT X LANES OPEN |
| DAYTIME LANE CLOSURES |
| I-XX SOUTH EXIT CLOSED |
| EXIT XXX CLOSED X MILE |
| RIGHT LN TO BE CLOSED |
| X LANES CLOSED TUE - FRI |
| ROADWORK XXX FT |
| FLAGGER XXXX FT |
| RIGHT LN NARROWS XXXX FT |
| MERGING TRAFFIC XXXX FT |
| LOOSE GRAVEL XXXX FT |
| DETOUR X MILE |
| ROADWORK PAST SH XXXX |
| BUMP XXXX FT |
| TRAFFIC SIGNAL XXXX FT |
| ROAD REPAIRS XXXX FT |
| LANE NARROWS XXXX FT |
| TWO-WAY TRAFFIC XX MILE |
| CONST TRAFFIC XXX FT |
| UNEVEN LANES XXXX FT |
| ROUGH ROAD XXXX FT |
| ROADWORK NEXT FRI-SUN |
| US XXX EXIT X MILES |
| LANES SHIFT * |

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List

| |
|----------------------|
| MERGE RIGHT |
| DETOUR NEXT X EXITS |
| USE EXIT XXX |
| STAY ON US XXX SOUTH |
| TRUCKS USE US XXX N |
| WATCH FOR TRUCKS |
| EXPECT DELAYS |
| REDUCE SPEED XXX FT |
| USE OTHER ROUTES |
| STAY IN LANE * |

Location List

| |
|--------------------------|
| AT FM XXXX |
| BEFORE RAILROAD CROSSING |
| NEXT X MILES |
| PAST US XXX EXIT |
| XXXXXXXX TO XXXXXXX |
| US XXX TO FM XXXX |

Warning List

| |
|-----------------------|
| SPEED LIMIT XX MPH |
| MAXIMUM SPEED XX MPH |
| MINIMUM SPEED XX MPH |
| ADVISORY SPEED XX MPH |
| RIGHT LANE EXIT |
| USE CAUTION |
| DRIVE SAFELY |
| DRIVE WITH CARE |

** Advance Notice List

| |
|-----------------------|
| TUE-FRI XX AM-X PM |
| APR XX-XX X PM-X AM |
| BEGINS MONDAY |
| BEGINS MAY XX |
| MAY X-X XX PM - XX AM |
| NEXT FRI-SUN |
| XX AM TO XX PM |
| NEXT TUE AUG XX |
| TONIGHT XX PM-XX AM |

** See Application Guidelines Note 6.

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

SHEET 6 OF 12


| | | | |
|---|---------------|-----------|-----------|
| | | | |
| <h3>BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)</h3> | | | |
| <h2>BC (6) -21</h2> | | | |
| FILE: | bc-21.dgn | DN: | TxDOT |
| © TxDOT | November 2002 | CK: | TxDOT |
| REVISIONS | 0910 | DW: | TxDOT |
| 9-07 | 8-14 | CONT | SECT |
| 7-13 | 5-21 | 0910 | 12 |
| | | JOB | 141 |
| | | HIGHWAY | VARIOUS |
| | | DIST | COUNTY |
| | | TYL | VAN ZANDT |
| | | SHEET NO. | 15 |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:22:23 PM
 FILE: c:\pww-int\Franch\has.in.jinna\dms34488\bc-21.dgn


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.




CONCRETE TRAFFIC BARRIER (CTB)

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.



LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES
LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

LOW PROFILE CONCRETE BARRIER (LPCB)



DELINEATION OF END TREATMENTS

END TREATMENTS FOR CTB'S USED IN WORK ZONES
End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS

WARNING LIGHTS


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B_{FL} or C_{FL} Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.




Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

| REQUIREMENTS | | | |
|--------------|--------------|-------------------------------|-----------------------------|
| TYPE | MINIMUM SIZE | MINIMUM NUMBER OF PANEL LAMPS | MINIMUM VISIBILITY DISTANCE |
| B | 30 x 60 | 13 | 3/4 mile |
| C | 48 x 96 | 15 | 1 mile |

ATTENTION
Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

FLASHING ARROW BOARDS

SHEET 7 OF 12

TRUCK-MOUNTED ATTENUATORS

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR

BC (7) -21

| | | | | | | | | | |
|-----------|---------------|------|-----------|-----------|---------|-----|-------|-----|-------|
| FILE: | bc-21.dgn | DN: | TxDOT | CK: | TxDOT | DW: | TxDOT | CK: | TxDOT |
| © TxDOT | November 2002 | CONT | SECT | JOB | HIGHWAY | | | | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS | | | | |
| 9-07 | 8-14 | DIST | COUNTY | SHEET NO. | | | | | |
| 7-13 | 5-21 | TYL | VAN ZANDT | 16 | | | | | |

DATE: 1/12/2024 5:22:25 PM FILE: c:\pw-inf\fratech\has\in_jinna\dms34488\bc-21.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:22:29 PM
 FILE: c:\pw-InfraTech\has\in_jinna\dms34488\bc-21.dgn

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS




- Pre-qualified plastic drums shall meet the following requirements:
- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
 - The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
 - Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
 - Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
 - The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
 - The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
 - Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
 - Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
 - Drum body shall have a maximum unballasted weight of 11 lbs.
 - Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.



DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign (Maximum Sign Dimension)
 Chevron CW1-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer

12" x 24" Vertical Panel
 mount with diagonals sloping down towards travel way

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.




BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(8)-21


| | | | | | | | | | |
|-----------|---------------|------|-----------|-----------|---------|-----|-------|-----|-------|
| FILE: | bc-21.dgn | DN: | TxDOT | CK: | TxDOT | DW: | TxDOT | CK: | TxDOT |
| © TxDOT | November 2002 | CONT | SECT | JOB | HIGHWAY | | | | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS | | | | |
| 4-03 | 8-14 | DIST | COUNTY | SHEET NO. | | | | | |
| 9-07 | 5-21 | TYL | VAN ZANDT | 17 | | | | | |
| 7-13 | | | | | | | | | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



FIXED
(Rigid or self-righting)


DRIVEABLE



PORTABLE


VERTICAL PANELS (VPs)

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




OPPOSING TRAFFIC LANE DIVIDERS (OTLD)

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS



LONGITUDINAL CHANNELIZING DEVICES (LCD)

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

GENERAL NOTES

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

| Posted Speed | Formula | Minimum Desirable Taper Lengths * * * | | | Suggested Maximum Spacing of Channelizing Devices | |
|--------------|--------------------------|--|------------|------------|---|--------------|
| | | 10' Offset | 11' Offset | 12' Offset | On a Taper | On a Tangent |
| 30 | L = WS ² / 60 | 150' | 165' | 180' | 30' | 60' |
| 35 | | 205' | 225' | 245' | 35' | 70' |
| 40 | | 265' | 295' | 320' | 40' | 80' |
| 45 | L = WS | 450' | 495' | 540' | 45' | 90' |
| 50 | | 500' | 550' | 600' | 50' | 100' |
| 55 | | 550' | 605' | 660' | 55' | 110' |
| 60 | | 600' | 660' | 720' | 60' | 120' |
| 65 | | 650' | 715' | 780' | 65' | 130' |
| 70 | | 700' | 770' | 840' | 70' | 140' |
| 75 | | 750' | 825' | 900' | 75' | 150' |
| 80 | | 800' | 880' | 960' | 80' | 160' |

* * *Taper lengths have been rounded off.
L=Length of Taper (FT.) W=Width of Offset (FT.)
S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) -21

| | | | | | | | | | |
|-----------|---------------|------|-----------|-----|-----------|-----|-------|-----|-------|
| FILE: | bc-21.dgn | DN: | TxDOT | CK: | TxDOT | DW: | TxDOT | CK: | TxDOT |
| © TxDOT | November 2002 | CONT | SECT | JOB | HIGHWAY | | | | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS | | | | |
| 9-07 | 8-14 | DIST | COUNTY | | SHEET NO. | | | | |
| 7-13 | 5-21 | TYL | VAN ZANDT | | 18 | | | | |


DATE: 1/12/2024 5:22:31 PM
FILE: c:\pw-InfraTech\has.in.jinna\dms34488\bc-21.dgn

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPE 3 BARRICADES

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL




TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION



PERSPECTIVE VIEW




PLAN VIEW

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

| LEGEND | |
|--------|---|
| | Plastic drum |
| | Plastic drum with steady burn light or yellow warning reflector |
| | Steady burn warning light or yellow warning reflector |

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.
42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



TRAFFIC CONTROL FOR MATERIAL STOCKPILES



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(10)-21

| | | | | |
|----------------------|-----------|-----------|-----------|-----------|
| FILE: bc-21.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| ©TxDOT November 2002 | CONT | SECT | JOB | HIGHWAY |
| REVISIONS | 0910 | 12 | 141 | VARIOUS |
| 9-07 8-14 | DIST | COUNTY | SHEET NO. | |
| 7-13 5-21 | TYL | VAN ZANDT | 19 | |


DATE: 1/12/2024 5:22:34 PM
FILE: c:\pw-inf\fratech\has.in.jinna\dms34488\bc-21.dgn

- NOTES:**
1. CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
 2. VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
 3. REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
 4. PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
 5. LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
 6. ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
 7. STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
 8. ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
 9. REFER TO TxDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.



LEGEND

- PROP CURVE WARNING SIGN
- PROP FLASHING CHEVRON (BI-DIRECTIONAL)
- EXIST TRAFFIC SIGN
- EXIST CHEVRON SIGN TO BE REMOVED
- CHEVRON SEQUENCE/SIGN NUMBER
- PROP SIGN NUMBER



STATE OF TEXAS
 ZAHIDUL Q. SIDDIQUE
 98635
 LICENSED PROFESSIONAL ENGINEER
Z. Siddique
 1/24/2024

| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |

Texas Department of Transportation

infraTECH
 Engineers & Innovators, LLC
 TBPE REGISTRATION NO. F-18368


CHEVRON LAYOUT
LOCATION 1
FM 1255

SHEET 1 OF 7


| CONT | SECT | JOB | HIGHWAY |
|------|------|-----------|-----------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | | COUNTY | SHEET NO. |
| TYL | | VAN ZANDT | 20 |

DATE: 1/24/2024 1:01:29 PM
 FILE: c:\pw-infratech\lxin-zhang\dms34030\HSIP_TYL_PLAN_SET_01_SHEET_01.dgn
 PLOT DRIVER: TXDOT_PDF_BW_LEVELS.plt;cg
 PENTABLE: HSIP_TYL.tbl

- NOTES:**
1. CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
 2. VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
 3. REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
 4. PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
 5. LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
 6. ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
 7. STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
 8. ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
 9. REFER TO TxDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.



- LEGEND**
- ▶ PROP CURVE WARNING SIGN
 - ⚡ PROP FLASHING CHEVRON (BI-DIRECTIONAL)
 - Ⓢ EXIST TRAFFIC SIGN
 - Ⓜ EXIST CHEVRON SIGN TO BE REMOVED
 - XX CHEVRON SEQUENCE/SIGN NUMBER
 - Ⓧ PROP SIGN NUMBER



STATE OF TEXAS
ZAHIDUL Q. SIDDIQUE
98635
LICENSED PROFESSIONAL ENGINEER
Z. Siddique
1/24/2024

| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |

Texas Department of Transportation
© 2024
infratech
Engineers & Innovators, LLC
TBPE REGISTRATION NO. F-18368

CHEVRON LAYOUT
LOCATION 2
FM 1255

SHEET 2 OF 7



| CONT | SECT | JOB | HIGHWAY |
|------|-----------|-----------|---------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 21 | |

- NOTES:**
1. CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
 2. VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
 3. REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
 4. PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
 5. LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
 6. ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
 7. STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
 8. ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
 9. REFER TO TxDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.



LEGEND

- PROP CURVE WARNING SIGN
- ⊞ PROP FLASHING CHEVRON (BI-DIRECTIONAL)
- ⊕ EXIST TRAFFIC SIGN
- ⊞ EXIST CHEVRON SIGN TO BE REMOVED
- XX CHEVRON SEQUENCE/SIGN NUMBER
- ⊕ PROP SIGN NUMBER



1/24/2024

| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |




CHEVRON LAYOUT
 LOCATION 3
 FM 47

SHEET 3 OF 7

| CONT | SECT | JOB | HIGHWAY |
|------|-----------|-----------|---------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 22 | |





- NOTES:**
1. CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
 2. VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
 3. REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
 4. PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
 5. LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
 6. ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
 7. STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
 8. ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
 9. REFER TO TXDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.



LEGEND

- ▶ PROP CURVE WARNING SIGN
- ⚡ PROP FLASHING CHEVRON (BI-DIRECTIONAL)
- Ⓟ EXIST TRAFFIC SIGN
- Ⓢ EXIST CHEVRON SIGN TO BE REMOVED
- XX CHEVRON SEQUENCE/SIGN NUMBER
- Ⓧ PROP SIGN NUMBER



| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |

Texas Department of Transportation
 © 2024
infraTECH
 Engineers & Innovators, LLC
 TBPE REGISTRATION NO. F-18368

**CHEVRON LAYOUT
 LOCATION 4
 FM 47**

SHEET 4 OF 7


| CONT | SECT | JOB | HIGHWAY |
|------|-----------|-----------|---------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 23 | |

CK: DW: CK: DW:

- NOTES:**
1. CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
 2. VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
 3. REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
 4. PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
 5. LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
 6. ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
 7. STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
 8. ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
 9. REFER TO TxDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.



PLOT DRIVER: TXDOT_PDF_BW_LEVELS.plt;cg
PENTABLE: HSP_TYL.tbl

DATE: 1/24/2024 1:03:17 PM
FILE: c:\pw-infratech\lxin.zhang\dms34030\HSP_TYL_PLAN_SET_01_SHEET_05.dgn



LEGEND

- PROP CURVE WARNING SIGN
- ⚡ PROP FLASHING CHEVRON (BI-DIRECTIONAL)
- ⊙ EXIST TRAFFIC SIGN
- ⊙ EXIST CHEVRON SIGN TO BE REMOVED
- XX CHEVRON SEQUENCE/SIGN NUMBER
- ⊙ PROP SIGN NUMBER



1/24/2024


| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |



**CHEVRON LAYOUT
LOCATION 5
FM 17**


SHEET 5 OF 7

| CONT | SECT | JOB | HIGHWAY |
|------|------|-----------|-----------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | | COUNTY | SHEET NO. |
| TYL | | VAN ZANDT | 24 |



LEGEND

- PROP CURVE WARNING SIGN
- ⚡ PROP FLASHING CHEVRON (BI-DIRECTIONAL)
- Ⓢ EXIST TRAFFIC SIGN
- Ⓢ EXIST CHEVRON SIGN TO BE REMOVED
- XX CHEVRON SEQUENCE/SIGN NUMBER
- Ⓢ PROP SIGN NUMBER



- NOTES:**
- CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
 - VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
 - REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
 - PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
 - LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
 - ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
 - STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
 - ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
 - REFER TO TXDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.

| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |

infraTECH

 Engineers & Innovators, LLC

 TBPE REGISTRATION NO. F-18368

CHEVRON LAYOUT
LOCATION 6
FM 17

SHEET 6 OF 7

| CONT | SECT | JOB | HIGHWAY |
|------|-----------|-----------|---------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 25 | |



NOTES:

1. CENTERLINE, ROW, AND EDGE OF PAVEMENT (EOP) LINES ARE APPROXIMATE.
2. VERIFY ROW IN AREAS SHOWN OR AS DIRECTED BEFORE INSTALLATION OF SIGNS.
3. REFER TO SHEET NO 27 FOR TREE REMOVAL, CLEARING AND GRUBBING DETAILS.
4. PREPARE ROW ONE STATION BEFORE AND AFTER THE FIRST AND LAST PROPOSED LED SIGNS. REFER TO PREPARING ROW SUMMARY TABLE FOR INCLUDED STATIONS. OTHER STATIONS TO BE CLEARED ONLY AS DIRECTED.
5. LED ACTIVATION TIMING IS SEQUENTIAL, DIRECTIONAL, AND RADAR INITIATED. SEE SS 6350 FOR MORE INFORMATION.
6. ALL PROPOSED SIGN LOCATIONS ARE APPROXIMATE AND MAY BE ADJUSTED, AS APPROVED BY THE ENGINEER.
7. STAKE LOCATIONS OF PROPOSED AND RELOCATED SIGNS AND OBTAIN APPROVAL FROM THE ENGINEER PRIOR TO INSTALLATION.
8. ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.
9. REFER TO TXDOT STANDARDS FOR SIGN PLACEMENT AND OTHER DETAILS.



LEGEND

- PROP CURVE WARNING SIGN
- PROP FLASHING CHEVRON (BI-DIRECTIONAL)
- EXIST TRAFFIC SIGN
- EXIST CHEVRON SIGN TO BE REMOVED
- CHEVRON SEQUENCE/SIGN NUMBER
- PROP SIGN NUMBER



1/24/2024


| NO. | DATE | REVISION | APPROVED |
|-----|------|----------|----------|
| | | | |



CHEVRON LAYOUT
LOCATION 7
FM 17

SHEET 7 OF 7

| CONT | SECT | JOB | HIGHWAY |
|------|-----------|-----------|---------|
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 26 | |




PREPARING ROW DETAILS

NOTES:

- 1) PAYMENT WILL BE MADE AT THE UNIT BID PRICE FOR PREPARING RIGHT OF WAY BY THE STATION. STATION LIMITS WILL BE SHOWN ELSEWHERE IN THE PLANS. ALL TRIMMING APPLIES TO BOTH SIDES OF THE ROADWAY.
- 2) ALL TREE LIMBS EXTENDING INTO THE ROW SHALL BE REMOVED, UNLESS OTHERWISE SHOWN ON PLANS. VERTICAL CLEARING LIMITS ARE FROM NATURAL GROUND THROUGH TOP OF TREE OR AS DIRECTED.
- 3) CLEARING OPERATIONS SHALL BE PERFORMED IN ACCORDANCE TO ITEM 100, "PREPARING RIGHT OF ROW", EXCEPT THOSE SHOWN BY THESE DETAILS.
- 4) REMOVE OBSTRUCTIONS NOT DESIGNATED FOR PRESERVATION TO 2 FT BELOW NATURAL GROUND IN AREAS FOR EMBANKMENT.
- 5) REMOVE OBSTRUCTIONS TO 2 FT BELOW THE EXCAVATION LEVEL IN AREAS TO BE EXCAVATED.
- 6) WHERE STEEP SLOPES MAKE GRINDING OPERATIONS IMPRACTICAL, THE CONTRACTOR MAY CUT THE OBSTRUCTION AT GROUND LEVEL WITH WRITTEN APPROVAL FROM THE ENGINEER.
- 7) LOG STOCKPILES WITHIN TxDOT ROW ARE NOT ALLOWED.
- 8) NO MORE THAN 4" OF MULCH TO REMAIN.

RIGHT OF WAY WIDTH SUMMARY

| LAYOUT SHEET & LOCATION | APPROX. ROW WIDTH (FT) |
|---------------------------|------------------------|
| SHEET 1 OF 7 - LOCATION 1 | 80 |
| SHEET 2 OF 7 - LOCATION 2 | 90 |
| SHEET 3 OF 7 - LOCATION 3 | 90 |
| SHEET 4 OF 7 - LOCATION 4 | 90 |
| SHEET 5 OF 7 - LOCATION 5 | 80 |
| SHEET 6 OF 7 - LOCATION 6 | 80 |
| SHEET 7 OF 7 - LOCATION 7 | 80 |



| | | | |
|-----|------|----------|----------|
| NO. | DATE | REVISION | APPROVED |
| | | | |



PREPARING ROW DETAILS




| | | | |
|--------------|-----------|-----------|---------|
| SHEET 1 OF 1 | | | |
| CONT | SECT | JOB | HIGHWAY |
| 0910 | 12 | 141 | VARIOUS |
| DIST | COUNTY | SHEET NO. | |
| TYL | VAN ZANDT | 27 | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:28:16 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\tsr3-13 (3).dgn

REQUIREMENTS FOR INDEPENDENT MOUNTED ROUTE SIGNS



| SHEETING REQUIREMENTS | | |
|-----------------------|------------|-----------------------------|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | WHITE | TYPE A SHEETING |
| BACKGROUND | ALL OTHERS | TYPE B OR C SHEETING |
| LEGEND & BORDERS | WHITE | TYPE A SHEETING |
| LEGEND & BORDERS | BLACK | ACRYLIC NON-REFLECTIVE FILM |
| LEGEND & BORDERS | ALL OTHERS | TYPE B or C SHEETING |



TYPICAL EXAMPLES

REQUIREMENTS FOR BLUE, BROWN & GREEN D AND I SERIES GUIDE SIGNS

| SHEETING REQUIREMENTS | | |
|---------------------------|------------|----------------------|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | ALL | TYPE B OR C SHEETING |
| LEGEND & BORDERS | WHITE | TYPE D SHEETING |
| LEGEND, SYMBOLS & BORDERS | ALL OTHERS | TYPE B OR C SHEETING |



TYPICAL EXAMPLES

GENERAL NOTES

- Signs to be furnished shall be as detailed elsewhere in the plans and/or as shown on sign tabulation sheet. Standard sign designs and arrow dimensions can be found in the "Standard Highway Sign Designs for Texas" (SHSD).
- White legend shall use the Clearview Alphabet. The following Clearview fonts shall be used to replace the existing white Federal Highway Administration (FHWA) Standard Highway Alphabets, when not specified in the SHSD, or in the plans.

| | |
|------|--------|
| B | CV-1W |
| C | CV-2W |
| D | CV-3W |
| E | CV-4W |
| Emod | CV-5WR |
| F | CV-6W |

- Route sign legend (ie. IH, US, SH and FM shields) shall use the Federal Highway Administration (FHWA) Standard Highway Alphabets B, C, D, E, Emod or F).
- Lateral spacing between letters and numerals shall conform with the SHSD, and any approved changes thereto. Lateral spacing of legend shall provide a balanced appearance when spacing is not shown.
- Independent mounted route sign with white or colored legend and borders shall be applied by screening process with transparent color ink, transparent colored overlay film to white background sheeting or cut-out white sheeting to colored background sheeting, or combination thereof. White legend, symbols and borders on all other signs shall be cut-out white sheeting applied to colored background sheeting.
- Information regarding borders and radii for signs is found in the "Standard Highway Sign Designs for Texas". Dimensions shown and described for borders and corner radii on parent sign are nominal. Borders may vary in width as much as 1/2 inch. Corner radii above 3 inches may vary in width as much as 1 inch. Borders and corner radii within a parent sign must be of matching widths. The sign area outside the corner radius should be trimmed or rounded.
- Sign substrate shall be any material that meets the Departmental Material Specification requirements of DMS-7110 or approved alternative.
- Mounting details of roadside signs are shown in the "SMD series" Standard Plan Sheets.

DEPARTMENTAL MATERIAL SPECIFICATIONS

| | |
|----------------------|----------|
| ALUMINUM SIGN BLANKS | DMS-7110 |
| SIGN FACE MATERIALS | DMS-8300 |

ALUMINUM SIGN BLANKS THICKNESS

| Square Feet | Minimum Thickness |
|-----------------|-------------------|
| Less than 7.5 | 0.080 |
| 7.5 to 15 | 0.100 |
| Greater than 15 | 0.125 |

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.

<http://www.txdot.gov/>



TYPICAL SIGN REQUIREMENTS

TSR(3)-13


| | | | | | | | | | |
|-----------|--------------|------|-----------|-----------|---------|-----|-------|-----|-------|
| FILE: | tsr3-13.dgn | DN: | TxDOT | CK: | TxDOT | DW: | TxDOT | CK: | TxDOT |
| © TxDOT | October 2003 | CONT | SECT | JOB | HIGHWAY | | | | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS | | | | |
| 12-03 | 7-13 | DIST | COUNTY | SHEET NO. | | | | | |
| 9-08 | | TYL | VAN ZANDT | 28 | | | | | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:28:28 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\tsr4-13 (3).dgn

REQUIREMENTS FOR RED BACKGROUND REGULATORY SIGNS

(STOP, YIELD, DO NOT ENTER AND WRONG WAY SIGNS)



REQUIREMENTS FOR FOUR SPECIFIC SIGNS ONLY

| SHEETING REQUIREMENTS | | |
|-----------------------|-------|----------------------|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | RED | TYPE B OR C SHEETING |
| BACKGROUND | WHITE | TYPE B OR C SHEETING |
| LEGEND & BORDERS | WHITE | TYPE B OR C SHEETING |
| LEGEND | RED | TYPE B OR C SHEETING |

REQUIREMENTS FOR WHITE BACKGROUND REGULATORY SIGNS


(EXCLUDING STOP, YIELD, DO NOT ENTER AND WRONG WAY SIGNS)



TYPICAL EXAMPLES

| SHEETING REQUIREMENTS | | |
|-----------------------------|------------|-----------------------------|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | WHITE | TYPE A SHEETING |
| BACKGROUND | ALL OTHERS | TYPE B OR C SHEETING |
| LEGEND, BORDERS AND SYMBOLS | BLACK | ACRYLIC NON-REFLECTIVE FILM |
| LEGEND, BORDERS AND SYMBOLS | ALL OTHER | TYPE B OR C SHEETING |

REQUIREMENTS FOR WARNING SIGNS



TYPICAL EXAMPLES

| SHEETING REQUIREMENTS | | |
|-----------------------|--------------------|--|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | FLOURESCENT YELLOW | TYPE B _{FL} OR C _{FL} SHEETING |
| LEGEND & BORDERS | BLACK | ACRYLIC NON-REFLECTIVE FILM |
| LEGEND & SYMBOLS | ALL OTHER | TYPE B OR C SHEETING |

REQUIREMENTS FOR SCHOOL SIGNS



TYPICAL EXAMPLES

| SHEETING REQUIREMENTS | | |
|-----------------------------|--------------------------|--|
| USAGE | COLOR | SIGN FACE MATERIAL |
| BACKGROUND | WHITE | TYPE A SHEETING |
| BACKGROUND | FLOURESCENT YELLOW GREEN | TYPE B _{FL} OR C _{FL} SHEETING |
| LEGEND, BORDERS AND SYMBOLS | BLACK | ACRYLIC NON-REFLECTIVE FILM |
| SYMBOLS | RED | TYPE B OR C SHEETING |

GENERAL NOTES

- Signs to be furnished shall be as detailed elsewhere in the plans and/or as shown on sign tabulation sheet. Standard sign designs and arrow dimensions can be found in the "Standard Highway Sign Designs for Texas" (SHSD).
- Sign legend shall use the Federal Highway Administration (FHWA) Standard Highway Alphabets (B, C, D, E, Emod or F).
- Lateral spacing between letters and numerals shall conform with the SHSD, and any approved changes thereto. Lateral spacing of legend shall provide a balanced appearance when spacing is not shown.
- Black legend and borders shall be applied by screening process or cut-out acrylic non-reflective black film to background sheeting, or combination thereof.
- White legend and borders shall be applied by screening process with transparent colored ink, transparent colored overlay film to white background sheeting or cut-out white sheeting to colored background sheeting, or combination thereof.
- Colored legend shall be applied by screening process with transparent colored ink, transparent colored overlay film or colored sheeting to background sheeting, or combination thereof.
- Sign substrate shall be any material that meets the Departmental Material Specification requirements of DMS-7110 or approved alternative.
- Mounting details for roadside mounted signs are shown in the "SMD series" Standard Plan Sheets.

ALUMINUM SIGN BLANKS THICKNESS

| Square Feet | Minimum Thickness |
|-----------------|-------------------|
| Less than 7.5 | 0.080 |
| 7.5 to 15 | 0.100 |
| Greater than 15 | 0.125 |

DEPARTMENTAL MATERIAL SPECIFICATIONS

| | |
|----------------------|----------|
| ALUMINUM SIGN BLANKS | DMS-7110 |
| SIGN FACE MATERIALS | DMS-8300 |

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.

<http://www.txdot.gov/>



TYPICAL SIGN REQUIREMENTS

TSR (4) - 13


| | | | | | | | | | |
|-----------|--------------|------|-----------|-----------|---------|-----|-------|-----|-------|
| FILE: | tsr4-13.dgn | DN: | TxDOT | CK: | TxDOT | DW: | TxDOT | CK: | TxDOT |
| © TxDOT | October 2003 | CONT | SECT | JOB | HIGHWAY | | | | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS | | | | |
| 12-03 | 7-13 | DIST | COUNTY | SHEET NO. | | | | | |
| 9-08 | | TYL | VAN ZANDT | 29 | | | | | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:28:38 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\tsr5-13.dgn

ARROW DETAILS

for Large Ground-Mounted and Overhead Guide Signs




| TYPE | LETTER SIZE | USE |
|------|-------------------------|---------------------|
| A-1 | 10.67" U/L and 10" Caps | Single Lane Exits |
| A-2 | 13.33" U/L and 12" Caps | |
| A-3 | 16" & 20" U/L | |
| B-1 | 10.67" U/L and 10" Caps | Multiple Lane Exits |
| B-2 | 13.33" U/L and 12" Caps | |
| B-3 | 16" & 20" U/L | |

| CODE | USED ON SIGN NO. |
|------|------------------|
| E-3 | E5-1aT |
| E-4 | E5-1bT |

NOTE
 Arrow dimensions are shown in the "Standard Highway Sign Designs for Texas" manual.


The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

SIGN BLANK PUNCHING DETAILS FOR ATTACHMENTS WHEN SPECIFIED TO BE TYPE A ALUMINUM SIGNS (FOR MOUNTING TO GUIDE SIGN FACE)




INTERSTATE ROUTE MARKERS

| A | C | D | E |
|----|----|----|-------|
| 36 | 21 | 15 | 1 1/2 |
| 48 | 28 | 20 | 1 3/4 |




U.S. ROUTE MARKERS

| Sign Size | "Y" |
|-----------|-----|
| 24x24 | 2 |
| 30x24 | 3 |
| 36x36 | 3 |
| 45x36 | 4 |
| 48x48 | 4 |
| 60x48 | 5 |




STATE ROUTE MARKERS

| No. of Digits | W | X |
|---------------|----|---|
| 4 | 24 | 4 |
| 4 | 36 | 5 |
| 4 | 48 | 6 |
| 3 | 24 | 3 |
| 3 | 36 | 4 |
| 3 | 48 | 5 |




EXIT ONLY PANEL


MOUNTING DETAILS OF ATTACHMENTS TO GUIDE SIGN FACE ("EXIT ONLY" AND "LEFT EXIT" PANELS, ROUTE MARKERS AND OTHER ATTACHMENTS)



DIRECT APPLIED ATTACHMENT



SCREW ATTACHMENT




NUT/BOLT ATTACHMENT


- NOTE:**
- Sheeting for legend, symbols, and borders must be cut at panel joints.
 - Direct applied attachment signs will be subsidiary to "Aluminum Signs" or "Fiberglass Signs".

- NOTE:**
- Furnish Type A aluminum sign attachments only when specified in the plans. These signs will be paid for under "Aluminum Signs".

ARROW DETAILS for Destination Signs (Type D)



Standard arrow to be used with 6 inch letters.



Standard arrow to be used with 8 inch letters.



TYPICAL SIGN REQUIREMENTS

TSR (5) - 13

| | | | | |
|----------------------|-----------|-----------|-----------|-----------|
| FILE: tsr5-13.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| © TxDOT October 2003 | CONT | SECT | JOB | HIGHWAY |
| REVISIONS | 0910 | 12 | 141 | VARIOUS |
| 12-03 7-13 | DIST | COUNTY | SHEET NO. | |
| 9-08 | TYL | VAN ZANDT | 30 | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:28:50 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\dom1-20.dgn

| REFLECTOR UNIT SIZES FOR DELINEATORS AND OBJECT MARKERS | | | | | DELINEATORS | | | | D & OM DESCRIPTIVE CODES | | |
|---|---|-------------------------------|----------|-----------------|--|----------------------------------|--|---|--|--|----------------------------------|
| DEVICE | SIZE 1 | SIZE 2 | SIZE 3 | SIZE 4 | SINGLE | | DOUBLE | | INSTL DEL ASSM (D-XX)SZ X (XXXX)XXX (XX) | | |
| | | | | | | | | | | NUMBER OF REFLECTORS: S = Single, D = Double COLOR OF REFLECTORS: W = White, Y = Yellow, R = Red REFLECTOR UNIT SIZE: 1 or 2 TYPE OF POST OR DELINEATOR: WC = Wing Channel Post, YFLX = Yellow Flexible Post, WFLX = White Flexible Post, BRF = Barrier Reflector TYPE OF MOUNT: GND = Embedded (drivable or set in concrete), CTB = Concrete Barrier Mount, GF1 or GF2 = Guard Fence Attachment, SRF = Surface Mount | |
| SHEETING | Yellow, White or Red Type B or C reflective sheeting | | | | SHEETING | | Yellow, White or Red Type B or C Reflective Sheeting | | | | |
| NOTE | 1. Size 1 and 4 - Direct applied reflective sheeting for use on flexible post (flx). 2. Size 2 and 3 - For use on wing channel (wc) post only. Use approved metal, plastic or fiberglass backplate with 17/64" mounting holes. | | | | POST TYPE | WC | YFLX, WFLX | WC | YFLX, WFLX | DIRECTION: If Required, BI = Bi-Directional, BR = Bi-Directional with red on back | |
| | | | | | MOUNT TYPE | GND | GND, SRF | GND | GND, SRF | INSTL OM ASSM (OM-XX) (XXXX)XXX (XX) | |
| OBJECT MARKERS | | | | | | | | | | | |
| DEVICE | Type 1 (OM-1) | Type 2 (OM-2) | | | Type 3 (OM-3) | | | Type 4 (OM-4) | | NUMBER OF REFLECTORS OR DIRECTION: X = 3-Size 2 reflector unit (Type 2 only), Y = 1-Size 3 reflector unit (Type 2 only), Z = 3-Size 1 or 1-Size 4 reflector unit(s) (Type 2 only), L = Left Side (Type 3 Object Marker only), R = Right Side (Type 3 Object Marker only), C = Center (Type 3 Object Marker only) TYPE OF POST: WC = Wing Channel Post, WFLX = White Flexible Post, TWT = Thin Walled Tubing TYPE OF MOUNT: GND = Embedded (drivable), SRF = Surface Mount, WAS = Wedge Anchor Steel, WAP = Wedge Anchor Plastic DIRECTION: If Required, BI = Bi-Directional | |
| | | OM-1 | OM-2X | OM-2Y | OM-2Z | OM-3L | OM-3R | OM-3C | OM-4 | | |
| | | | | | | | | | | | |
| SHEETING | Yellow-Type B _{FL} or C _{FL} Sheeting | Yellow - Type B or C Sheeting | | | Alternating acrylic black and retroreflective yellow - Type B _{FL} or C _{FL} Sheeting | | | Red -Type B _{FL} or C _{FL} Sheeting | | | |
| POST TYPE | TWT | WC | WC | WFLX | TWT | | | TWT | | | |
| MOUNT TYPE | WAS, WAP | GND | GND | GND, SRF | WAS, WAP | | | WAS, WAP | | | |
| BARRIER REFLECTORS (BRF) | | | CHEVRONS | | | | ONE DIRECTION LARGE ARROW | | | | |
| DEVICE | GF1 | GF2 | CTB | | | | | | | | |
| | 1. Barrier reflectors shall meet the requirements of DMS 8600. 2. Approved Barrier Reflectors are listed on the "Barrier Reflectors" Material Producer List at: www.txdot.gov. | | | SIZE (W x L) | 18"x 24" (Conventional) | 24"x 30" (Conventional Oversize) | 30"x 36" (Expressway) | 36" x 48" (Freeway) | SIZE (W x L) | 48" x 24" (Conventional) | 60" x 30" (Expressway & Freeway) |
| | | | | MOUNTING HEIGHT | 4'-0" or 7'-0" | | 7'-0" Only | MOUNTING HEIGHT | 7'-0" | | |
| | | | | NOTE | 1. CHEVRON (W1-8) signs and ONE DIRECTION LARGE ARROW (W1-6) Signs shall be installed per Sign Mounting Details (SMD) Standard Sheets and paid under Item 644 (Small Roadside Sign Assemblies). 2. When there is a need to increase conspicuity, the Texas version of the ONE DIRECTION LARGE ARROW sign (W1-9T) may be used instead of the ONE DIRECTION LARGE ARROW (W1-6). | | | | | | |
| SHEETING | Yellow, White, Red | | | | | | | | | | |
| NOTE | 1. Reflective sheeting shall have a minimum dimension of 3 inches and minimum surface area of 9 square inches. | | | | | | | | | | |

| DEPARTMENTAL MATERIAL SPECIFICATIONS | |
|--|----------|
| FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES) | DMS-4400 |
| SIGN FACE MATERIALS | DMS-8300 |
| DELINEATORS, OBJECT MARKERS AND BARRIER REFLECTORS | DMS-8600 |

NOTE:
 Delineator and object marker substrates and sign substrates shall be 0.080" Aluminum sign blank to conform to ASTM B-209 Alloy 6061-T6 or approved alternative.

| | | | | | |
|---|-----------|-----------|-----------|-----------|--|
| | | | | | |
| DELINEATOR & OBJECT MARKER MATERIAL DESCRIPTION D & OM(1)-20 | | | | | |
| FILE: dom1-20.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT | |
| © TxDOT August 2004 | CONT | SECT | JOB | HIGHWAY | |
| REVISIONS | 0910 | 12 | 141 | VARIOUS | |
| 10-09 3-15 | DIST | COUNTY | SHEET NO. | | |
| 4-10 7-20 | TYL | VAN ZANDT | 31 | | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:29:00 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\dom2-20.dgn

POST TYPE AND SUPPORT FOUNDATION DETAILS








TYPE OF BARRIER MOUNTS

WING CHANNEL (WC)

FLEXIBLE POSTS (YFLX, WFLX)

WEDGE ANCHOR SYSTEMS

GUARD FENCE ATTACHMENT



NOTES

1. Embedded Wing Channel (WC) post option may be used for Type 2 Object Markers and Delineators only.
2. 1.12 lbs/ft steel per ASTM A 1011 SS Gr. 50, or ASTM A499.

EMBEDDED

SURFACE MOUNT

NOTES

1. See "Flexible Delineator and Object Marker Posts" Material Producer List for approved devices.
2. Install per manufacturer's recommendations.
3. Post length may vary to meet field conditions.
4. When using yellow delineators with flexible posts to separate opposing direction of travel, such as centerline or median use, the flexible posts shall be yellow.


STEEL

PLASTIC

NOTE

1. Install per manufacturer's recommendations.


CONCRETE TRAFFIC BARRIER (CTB)




GENERAL NOTES

1. Place delineators on a section of roadway at a consistent distance from the edge of pavement.
2. Where a restriction prevents consistent placement from the pavement edge, place the affected object markers in line with the innermost edge of the obstruction.
3. When Type 2 object markers and delineators are more than 8'-0" from the edge of the pavement, it may not be possible to maintain a height of approximately 4'-0". If this is the case, place the object marker or delineator as close to the desired height as possible.
4. Install all delineators, object markers and barrier reflectors in accordance with the manufacturer's recommendation.
5. Barrier reflectors should be installed a minimum of 18 inches above the edge of the pavement surface.
6. Diagonal stripes on Type 3 object markers shall slope down toward the intended travel lane.


TYPES 1,3, AND 4 OBJECT MARKERS AND CHEVRONS



CHEVRONS AND ONE DIRECTION LARGE ARROW SIGN



DELINEATORS AND TYPE 2 OBJECT MARKERS



Texas Department of Transportation
Traffic Safety Division Standard

DELINEATOR & OBJECT MARKER INSTALLATION

D & OM(2)-20

| | | | | |
|---------------------|-----------|-----------|-----------|-----------|
| FILE: dom2-20.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| © TxDOT August 2004 | CONT | SECT | JOB | HIGHWAY |
| REVISIONS | 0910 | 12 | 141 | VARIOUS |
| 10-09 3-15 | DIST | COUNTY | | SHEET NO. |
| 4-10 7-20 | TYL | VAN ZANDT | | 32 |

20B


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024 5:29:10 PM
 FILE: c:\pw-InfraTech\has.in.jinna\dms34488\dom3-20.dgn

MINIMUM WARNING DEVICES AT CURVES WITH ADVISORY SPEEDS

| Amount by which Advisory Speed is less than Posted Speed | Curve Advisory Speed | |
|--|--|---|
| | Turn (30 MPH or less) | Curve (35 MPH or more) |
| 5 MPH & 10 MPH | ● RPMs | ● RPMs |
| 15 MPH & 20 MPH | ● RPMs and One Direction Large Arrow sign | ● RPMs and Chevrons; or ● RPMs and One Direction Large Arrow sign where geometric conditions or roadside obstacles prevent the installation of chevrons. |
| 25 MPH & more | ● RPMs and Chevrons; or ● RPMs and One Direction Large Arrow sign where geometric conditions or roadside obstacles prevent the installation of chevrons | ● RPMs and Chevrons |


SUGGESTED SPACING FOR DELINEATORS ON HORIZONTAL CURVES



NOTE

ONE DIRECTION LARGE ARROW (W1-6) sign should be located at approximately and perpendicular to the extension of the centerline of the tangent section of approach lane.

SUGGESTED SPACING FOR CHEVRONS ON HORIZONTAL CURVES



NOTE

At least one chevron pair is installed beyond the point of tangent in tangent section.

DELINEATOR AND CHEVRON SPACING

| WHEN DEGREE OF CURVE OR RADIUS IS KNOWN | | | | |
|---|-----------------|------------------|-------------------------|--------------------------|
| Degree of Curve | FEET | | | |
| | Radius of Curve | Spacing in Curve | Spacing in Straightaway | Chevron Spacing in Curve |
| | | A | 2A | B |
| 1 | 5730 | 225 | 450 | — |
| 2 | 2865 | 160 | 320 | — |
| 3 | 1910 | 130 | 260 | 200 |
| 4 | 1433 | 110 | 220 | 160 |
| 5 | 1146 | 100 | 200 | 160 |
| 6 | 955 | 90 | 180 | 160 |
| 7 | 819 | 85 | 170 | 160 |
| 8 | 716 | 75 | 150 | 160 |
| 9 | 637 | 75 | 150 | 120 |
| 10 | 573 | 70 | 140 | 120 |
| 11 | 521 | 65 | 130 | 120 |
| 12 | 478 | 60 | 120 | 120 |
| 13 | 441 | 60 | 120 | 120 |
| 14 | 409 | 55 | 110 | 80 |
| 15 | 382 | 55 | 110 | 80 |
| 16 | 358 | 55 | 110 | 80 |
| 19 | 302 | 50 | 100 | 80 |
| 23 | 249 | 40 | 80 | 80 |
| 29 | 198 | 35 | 70 | 40 |
| 38 | 151 | 30 | 60 | 40 |
| 57 | 101 | 20 | 40 | 40 |

Curve delineator approach and departure spacing should include 3 delineators spaced at 2A. This spacing should be used during design preparation or when the degree of curve is known.

DELINEATOR AND CHEVRON SPACING

| WHEN DEGREE OF CURVE OR RADIUS IS NOT KNOWN | | | |
|---|------------------|-------------------------|--------------------------|
| Advisory Speed (MPH) | Spacing in Curve | Spacing in Straightaway | Chevron Spacing in Curve |
| | A | 2xA | B |
| 65 | 130 | 260 | 200 |
| 60 | 110 | 220 | 160 |
| 55 | 100 | 200 | 160 |
| 50 | 85 | 170 | 160 |
| 45 | 75 | 150 | 120 |
| 40 | 70 | 140 | 120 |
| 35 | 60 | 120 | 120 |
| 30 | 55 | 110 | 80 |
| 25 | 50 | 100 | 80 |
| 20 | 40 | 80 | 80 |
| 15 | 35 | 70 | 40 |

If the degree of curve is not known, delineator spacing may be determined based on the Advisory Speed of the curve. Use the delineator curve spacing for each Advisory Speed (MPH).

DELINEATOR AND OBJECT MARKER APPLICATION AND SPACING

| CONDITION | REQUIRED TREATMENT | MINIMUM SPACING |
|--|---|---|
| Frwy./Exp. Tangent | RPMs | See PM-series and FPM-series standard sheets |
| Frwy./Exp. Curve | Single delineators on right side | See delineator spacing table |
| Frwy/Exp. Ramp | Single delineators on at least one side of ramp (should be on outside of curves) (see Detail 3 on D&OM(4)) | 100 feet on ramp tangents Use delineator spacing table for ramp curves ("straightway spacing" does not apply to ramp curves) |
| Acceleration/Deceleration Lane | Double delineators (see Detail 3 on D&OM(4)) | 100 feet (See Detail 3 on D & OM (4)) |
| Truck Escape Ramp | Single red delineators on both sides | 50 feet |
| Bridge Rail (steel or concrete) and Metal Beam Guard Fence | Bi-Directional Delineators when undivided with one lane each direction Single Delineators when multiple lanes each direction | Equal spacing (100' max) but not less than 3 delineators |
| Concrete Traffic Barrier (CTB) or Steel Traffic Barrier | Barrier reflectors matching the color of the edge line | Equal spacing 100' max |
| Cable Barrier | Reflectors matching the color of the edge line | Every 5th cable barrier post (up to 100' max) |
| Guard Rail Terminus/Impact Head | Divided highway - Object marker on approach end Undivided 2-lane highways - Object marker on approach and departure end | Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM (5) and D & OM (6) |
| Bridges with no Approach Rail | Type 3 Object Marker (OM-3) at end of rail and 3 single delineators approaching rail | See D & OM(5) |
| Reduced Width Approaches to Bridge Rail | Type 2 and Type 3 Object Markers (OM-3) and 3 single delineators approaching bridge | Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM (5) |
| Culverts without MBGF | Type 2 Object Markers | See Detail 2 on D & OM(4) |
| Crossovers | Double yellow delineators and RPMs | See Detail 1 on D & OM (4) |
| Pavement Narrowing (lane merge) on Freeways/Expressway | Single delineators adjacent to affected lane for full length of transition | 100 feet |

NOTES

- Unless indicated otherwise, the delineator or barrier reflector color shall conform to the color of the pavement edge line on the side of the road where the delineators or barrier reflectors are placed.
- Barrier reflectors may be used to replace required delineators.
- Single red delineators may be mounted on the back side of delineator posts for wrong way driver applications

| LEGEND | |
|--------|---------------------------|
| | Bi-directional Delineator |
| | Delineator |
| | Sign |

Traffic Safety Division Standard

DELINEATOR & OBJECT MARKER PLACEMENT DETAILS

D & OM(3)-20

| | | | | | |
|---------------------|-----------|-----------|-----------|-----------|---------|
| FILE: dom3-20.dgn | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT | |
| © TxDOT August 2004 | CONT | SECT | JOB | HIGHWAY | |
| REVISIONS | | 0910 | 12 | 141 | VARIOUS |
| 3-15 8-15 | DIST | COUNTY | SHEET NO. | | |
| 8-15 7-20 | TYL | VAN ZANDT | 33 | | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

SIGN SUPPORT DESCRIPTIVE CODES

(Descriptive Codes correspond to project estimate and quantities sheets)

SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)

Post Type

FRP = Fiberglass Reinforced Plastic Pipe (see SMD (FRP))
 TWT = Thin-Walled Tubing (see SMD (TWT))
 10BWG = 10 BWG Tubing (see SMD (SLIP-1) to (SLIP-3))
 S80 = Schedule 80 Pipe (see SMD (SLIP-1) to (SLIP-3))

Number of Posts (1 or 2)


Anchor Type

UA = Universal Anchor - Concreted (see SMD (FRP) and (TWT))
 UB = Universal Anchor - Bolted down (see SMD (FRP) and (TWT))
 WS = Wedge Anchor Steel - (see SMD (TWT))
 WP = Wedge Anchor Plastic (see SMD (TWT))
 SA = Slipbase - Concreted (see SMD (SLIP-1) to (SLIP-3))
 SB = Slipbase - Bolted Down (see SMD (SLIP-1) to (SLIP-3))

Sign Mounting Designation

P = Prefab. "Plain" (see SMD (SLIP-1) to (SLIP-3), (TWT), (FRP))
 T = Prefab. "T" (see SMD (SLIP-1) to (SLIP-3), (TWT))
 U = Prefab. "U" (see SMD (SLIP-1) to (SLIP-3))
 IF REQUIRED
 1EXT or 2EXT = Number of Extensions (see SMD (SLIP-1) to (SLIP-3), (TWT))
 BM = Extruded Wind Beam (see SMD (SLIP-1) to (SLIP-3))
 WC = 1.12 #/ft Wing Channel (see SMD (SLIP-1) to (SLIP-3))
 EXAL = Extruded Aluminum Sign Panels (see SMD (SLIP-3))


REQUIRED CLEARANCE FOR BREAKAWAY SUPPORT



To avoid vehicle undercarriage snagging, any substantial remains of a breakaway support, when it is broken away, should not project more than 4 inches above a 60-inch chord (i.e., typical space between wheel paths).


SIGN LOCATION

PAVED SHOULDERS



LESS THAN 6 FT. WIDE


When the shoulder is 6 ft. or less in width, the sign must be placed at least 12 ft. from the edge of the travel lane.



GREATER THAN 6 FT. WIDE


When the shoulder is greater than 6 ft in width, the sign must be placed at least 6 ft. from the edge of the shoulder.

T-INTERSECTION




When this sign is needed at the end of a two-lane, two way roadway, the right edge of the sign should be in line with the centerline of the roadway. Place as close to ROW as practical.


No more than 2 sign posts should be located within a 7 ft. circle.



BEHIND BARRIER




BEHIND GUARDRAIL



BEHIND CONCRETE BARRIER

**Sign clearance based on distance required for proper guard rail or concrete barrier performance.



* Signs shall be mounted using the following condition that results in the greatest sign elevation:


- (1) a minimum of 7 to a maximum of 7.5 feet above the edge of the travel lane or
- (2) a minimum of 7 to a maximum of 7.5 feet above the grade at the base of the support when sign is installed on the backslope.

The maximum values may be increased when directed by the Engineer.

See the Traffic Operations Division website for detailed drawings of sign clamps, Triangular Slipbase System components and Wedge Anchor System components.

The website address is:
<http://www.txdot.gov/publications/traffic.htm>

TYPICAL SIGN ATTACHMENT DETAIL




Bolts used to mount sign panels to the clamp are 5/16-18 UNC galvanized square head with nut, nylon washer, flat washer and lock washer. The bolt length is 1 inch for aluminum.

When two sign clamps are used to mount signs back-to-back, use a 5/16-18 UNC galvanized hex head per ASTM A307 with nut and helical-spring lock washer. The approximate bolt lengths for various post sizes and the sign clamp types are given in the table at right. The bolt length may need to be adjusted depending upon field conditions.

Sign clamps may be either the specific size clamp or the universal clamp.


| Pipe Diameter | Approximate Bolt Length | |
|----------------|-------------------------|-----------------|
| | Specific Clamp | Universal Clamp |
| 2" nominal | 3" | 3 or 3 1/2" |
| 2 1/2" nominal | 3 or 3 1/2" | 3 1/2 or 4" |
| 3" nominal | 3 1/2 or 4" | 4 1/2" |

SIGNS WITH PLAQUES




When a supplemental plaque or secondary sign is used, the 7 ft sign height is measured to the bottom of the supplemental plaque or secondary sign.

CURB & GUTTER OR RAISED ISLAND



RESTRICTED RIGHT-OF-WAY (When 6 ft min. is not possible.)



Right-of-way restrictions may be created by rocks, water, vegetation, forest, buildings, a narrow island, or other factors.

In situations where a lateral restriction prevents the minimum horizontal clearance from the edge of the travel lane, signs should be placed as far from the travel lane as practical.

*** Post may be shorter if protected by guardrail or if Engineer determines the post could not be hit due to extreme slope.




SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS GENERAL NOTES & DETAILS

SMD (GEN) -08

| | | | | |
|-------------------|-----------|-----------|-----------|-----------|
| © TxDOT July 2002 | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| 9-08 | REVISIONS | CONT | SECT | JOB |
| | | 0910 | 12 | 141 |
| | | DIST | COUNTY | SHEET NO. |
| | | TYL | VAN ZANDT | 34 |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TRIANGULAR SLIPBASE INSTALLATION GENERAL REQUIREMENTS



NOTE

There are various devices approved for the Triangular Slipbase System. Please reference the Material Producer List for approved slip base systems. http://www.txdot.gov/business/producer_list.htm The devices shall be installed per manufacturers' recommendations. Installation procedures shall be provided to the Engineer by Contractor.

GENERAL NOTES:

- Slip base shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to approval of the TxDOT Traffic Standards Engineer.
- Material used as post with this system shall conform to the following specifications:
 - 10 BWG Tubing (2.875" outside diameter)
 - 0.134" nominal wall thickness
 - Seamless or electric-resistance welded steel tubing or pipe
 - Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008
 - Other steels may be used if they meet the following:
 - 55,000 PSI minimum yield strength
 - 70,000 PSI minimum tensile strength
 - 20% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.122" to 0.138"
 - Outside diameter (uncoated) shall be within the range of 2.867" to 2.883"
 - Galvanization per ASTM A123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833.
 - Schedule 80 Pipe (2.875" outside diameter)
 - 0.276" nominal wall thickness
 - Steel tubing per ASTM A500 Gr C
 - Other seamless or electric-resistance welded steel tubing or pipe with equivalent outside diameter and wall thickness may be used if they meet the following:
 - 46,000 PSI minimum yield strength
 - 62,000 PSI minimum tensile strength
 - 21% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.248" to 0.304"
 - Outside diameter (uncoated) shall be within the range of 2.855" to 2.895"
 - Galvanization per ASTM A123
- See the Traffic Operations Division website for detailed drawings of sign clamps and Texas Universal Triangular Slipbase System components. The website address is: <http://www.txdot.gov/publications/traffic.htm>
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.

ASSEMBLY PROCEDURE


Foundation

- Prepare 12-inch diameter by 42-inch deep hole. If solid rock is encountered, the depth of the foundation may be reduced such that it is embedded a minimum of 18 inches into the solid rock.
- The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor-driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class A.
- Push the pipe end of the slip base stub into the center of the concrete. Rotate the stub back and forth while pushing it down into the concrete to assure good contact between the concrete and stub. Continue to work the stub into the concrete until it is between 2 to 4 inches above the ground.
- Plumb the stub. Allow a minimum of 4 days to set, unless otherwise directed by the Engineer.
- The triangular slipbase system is multidirectional and is designed to release when struck from any direction.

Support

- Cut support so that the bottom of the sign will be 7 to 7.5 feet above the edge of the travelway (i.e., edge of the closest lane) when slip plate is below the edge of pavement or 7 to 7.5 feet above slip plate when the slip plate is above the edge of the travelway. The cut shall be plumb and straight.
- Attach sign to support using connections shown. When multiple signs are installed on the same support, ensure the minimum clearance between each sign is maintained. See SMD(SLIP-2) for clearances based on sign types.

CONCRETE ANCHOR



5/8" diameter Concrete Anchor - 8 places (embed a minimum of 5 1/2" and torque to min. of 50 ft-lbs). Anchor may be expansion or adhesive type.

SM RD SGN ASSM TY XXXX(X)SB(X-XXXX)

Concrete anchor consists of 5/8" diameter stud bolt with UNC series bolt threads on the upper end. Heavy hex nut per ASTM A563, and hardened washer per ASTM F436. The stud bolt shall have a minimum yield and ultimate tensile strength of 50 and 75 KSI, respectively. Nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." Adhesive type anchors shall have stud bolts installed with Type III epoxy per DMS-6100, "Epoxyes and Adhesives." Adhesive anchors may be loaded after adequate epoxy cure time per the manufacturer's recommendations. Top of bolt shall extend at least flush with top of the nut when installed. The anchor, when installed in 4000 psi normal-weight concrete with a 5 1/2" minimum embedment, shall have a minimum allowable tension and shear of 3900 and 3100 psi, respectively.

















SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

SMD(SLIP-1)-08

| | | | | | |
|-------------------|-----------|-----------|-----------|-----------|-----------|
| © TxDOT July 2002 | | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| 9-08 | REVISIONS | CONT | SECT | JOB | HIGHWAY |
| | | 0910 | 12 | 141 | VARIOUS |
| | | DIST | COUNTY | | SHEET NO. |
| | | TYL | VAN ZANDT | | 35 |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



GENERAL NOTES:

1. SIGN SUPPORT # OF POSTS MAX. SIGN AREA

| | | |
|--------|---|-------|
| 10 BWG | 1 | 16 SF |
| 10 BWG | 2 | 32 SF |
| Sch 80 | 1 | 32 SF |
| Sch 80 | 2 | 64 SF |
2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
3. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
4. Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
10. Additional route markers may be added vertically, provided the total sign area does not exceed the maximum allowable amount per Note 1.
11. Additional sign clamp required on the "T-bracket" post for 24 inch height signs. Place the clamp 3 inches above bottom of sign when possible.
12. Post open ends shall be fitted with Friction Caps.
13. Sign blanks shall be the sizes and shapes shown on the plans.

| REQUIRED SUPPORT | | |
|--------------------------------|--|---|
| SIGN DESCRIPTION | SUPPORT | |
| Regulatory | 48-inch STOP sign (R1-1) | TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM) |
| | 60-inch YIELD sign (R1-2) | TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM) |
| | 48x16-inch ONE-WAY sign (R6-1) | TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM) |
| | 36x48, 48x36, and 48x48-inch signs | TY 10BWG(1)XX(T) |
| Warning | 48x60-inch signs | TY S80(1)XX(T) |
| | 48x48-inch signs (diamond or square) | TY 10BWG(1)XX(T) |
| | 48x60-inch signs | TY S80(1)XX(T) |
| | 48-inch Advance School X-ing sign (S1-1) | TY 10BWG(1)XX(T) |
| | 48-inch School X-ing sign (S2-1) | TY 10BWG(1)XX(T) |
| Large Arrow sign (W1-6 & W1-7) | TY 10BWG(1)XX(T) | |

Friction caps may be manufactured from hot rolled or cold rolled steel sheets. The minimum sheet metal thickness shall be 24 gauge for all cap sizes. The rim edges shall be reasonably straight and smooth. Caps shall be sized and formed in such a manner as to produce a drive-on friction fit and have no tendency to rock when seated on the pipe. The depth shall be sufficient to give positive protection against entrance of rainwater. They shall be free of sharp creases or indentations and show no evidence of metal fracture. Caps shall have an electrodeposited coating of zinc in accordance with the requirements of ASTM B633 Class FE/ZN 8.

Texas Department of Transportation
Traffic Operations Division






SIGN MOUNTING DETAILS
SMALL ROADSIDE SIGNS
TRIANGULAR SLIPBASE SYSTEM
SMD(SLIP-2)-08

| | | | | | |
|-------------------|-----------|-----------|-----------|-----------|-----------|
| © TxDOT July 2002 | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT | |
| 9-08 | REVISIONS | CONT | SECT | JOB | HIGHWAY |
| | | 0910 | 12 | 141 | VARIOUS |
| | | DIST | COUNTY | | SHEET NO. |
| | | TYL | VAN ZANDT | | 36 |





DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:



* Additional stiffener placed at approximate center of signs when sign width is greater than 10'.



Use Extruded Alum. Windbeam as stiffeners See SMD (2-1) for additional details
See Detail E for clamp installation

GENERAL NOTES:

- | SIGN SUPPORT | # OF POSTS | MAX. SIGN AREA |
|--------------|------------|----------------|
| 10 BWG | 1 | 16 SF |
| 10 BWG | 2 | 32 SF |
| Sch 80 | 1 | 32 SF |
| Sch 80 | 2 | 64 SF |
- The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
- Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
- Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
- Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
- For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
- When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
- Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
- Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
- Sign blanks shall be the sizes and shapes shown on the plans.
- Additional sign clamp required on the "T-bracket" post for 24 inch high signs. Place the clamp 3 inches above bottom of sign when possible.
- Post open ends shall be fitted with Friction Caps.

| REQUIRED SUPPORT | | |
|------------------|--|---|
| | SIGN DESCRIPTION | SUPPORT |
| Regulatory | 48-inch STOP sign (R1-1) | TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM) |
| | 60-inch YIELD sign (R1-2) | TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM) |
| | 48x16-inch ONE-WAY sign (R6-1) | TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM) |
| | 36x48, 48x36, and 48x48-inch signs | TY 10BWG(1)XX(T) |
| | 48x60-inch signs | TY S80(1)XX(T) |
| Warning | 48x48-inch signs (diamond or square) | TY 10BWG(1)XX(T) |
| | 48x60-inch signs | TY S80(1)XX(T) |
| | 48-inch Advance School X-ing sign (S1-1) | TY 10BWG(1)XX(T) |
| | 48-inch School X-ing sign (S2-1) | TY 10BWG(1)XX(T) |
| | Large Arrow sign (W1-6 & W1-7) | TY 10BWG(1)XX(T) |

Texas Department of Transportation
Traffic Operations Division

SIGN MOUNTING DETAILS
SMALL ROADSIDE SIGNS
TRIANGULAR SLIPBASE SYSTEM
SMD (SLIP-3) -08

| | | | | | |
|-------------------|-----------|-----------|-----------|-----------|-----------|
| © TxDOT July 2002 | | DN: TxDOT | CK: TxDOT | DW: TxDOT | CK: TxDOT |
| 9-08 | REVISIONS | CONT | SECT | JOB | HIGHWAY |
| | | 0910 | 12 | 141 | VARIOUS |
| | | DIST | COUNTY | | SHEET NO. |
| | | TYL | VAN ZANDT | | 37 |

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with TxDOT policy for projects disturbing less than 1 acre of soil, and not part of a larger common plan of development.

This SWP3 is consistent with requirements specified in applicable stormwater plans, and the project's environmental permits, issues, and commitments (EPICs).

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

0910-12-141

1.2 PROJECT LIMITS: VARIOUS LOCATIONS

1. FM 1255 (DFO 2.078 - 2.376), 2. FM 1255 (DFO 18.519 - 18.790), 3. FM 47 (DFO 13.290 - 13.577), 4. FM 47 (DFO 22.381 - 22.879), 5. FM 17 (DFO 20.769 - 21.188), 6. FM 17 (DFO 28.545 - 28.85), 7. FM 17 (DFO 33.727 - 34.106).

1.3 PROJECT COORDINATES: VARIES

BEGIN: (Lat) _____, (Long) _____

END: (Lat) _____, (Long) _____

1.4 TOTAL PROJECT AREA (Acres): 25.7 ACRES

1.5 TOTAL AREA TO BE DISTURBED (Acres): < 1.0 ACRE

1.6 NATURE OF CONSTRUCTION ACTIVITY:

Installing LED Chevron and Advanced Warning Signs for various locations.

1.7 MAJOR SOIL TYPES:

| Soil Type | Description |
|-----------|-------------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

| Type | Sheet #s |
|------|----------|
| N/A | N/A |
| | |
| | |
| | |
| | |

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.3.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures

Other: Update if project scope changes to require soil disturbing activities. None planned at this time.

Other: _____

Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- _____

Other: Update if project scope changes to require soil disturbing activities. None planned at this time.

Other: _____

Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

| Tributaries | Classified Waterbody |
|-------------|----------------------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations

Other: _____


Other: _____

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs

Other: _____

Other: _____



Z Siddique

1/24/2024

**STORMWATER POLLUTION PREVENTION PLAN (SWP3)
(Less Than 1 Acre)**

© 2024 July 2023 Sheet 1 of 2

Texas Department of Transportation

| | | | | |
|-------------------|-------------|-----------|-------------|-----------|
| FED. RD. DIV. NO. | PROJECT NO. | | | SHEET NO. |
| | | | | 38 |
| STATE | STATE DIST. | COUNTY | | |
| TEXAS | TYL | VAN ZANDT | | |
| CONT. | SECT. | JOB | HIGHWAY NO. | |
| 0910 | 12 | 141 | VARIOUS | |

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: Update if project scope changes
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: Update if project scope changes
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

| Type | Stationing | |
|------|------------|----|
| | From | To |
| N/A | | |
| | | |
| | | |
| | | |
| | | |

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Daily street sweeping
- Other: N/A

Other: _____

Other: _____

Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: Update if project scope changes

Other: _____

Other: _____

Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

| Type | Stationing | |
|---|------------|----|
| | From | To |
| Preserve all existing vegetation, but clearing, grubbing trees within ROW | | |
| | | |
| | | |
| | | |
| | | |

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.


2.8 DEWATERING:

2.9 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.3 of this SWP3 .

2.10 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.3 of this SWP3.



1/24/2024

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (Less Than 1 Acre)

| | | | | |
|-------------------|-------------|-----------|-------------|-----------|
| FED. RD. DIV. NO. | PROJECT NO. | | | SHEET NO. |
| | | | | 39 |
| STATE | STATE DIST. | COUNTY | | |
| TEXAS | TYL | VAN ZANDT | | |
| CONT. | SECT. | JOB | HIGHWAY NO. | |
| 0910 | 12 | 141 | VARIOUS | |

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

- 1.
- 2. No Action Required Required Action

Action No.

- 1. Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000
- 2. Comply with the SW3P and revise when necessary to control pollution or required by the Engineer.
- 3. Post Construction Site Notice (CSN) with SW3P information on or near the site, accessible to the public and TCEQ, EPA or other inspectors.
- 4. When Contractor project specific locations (PSL's) increase disturbed soil area to 5 acres or more, submit NOI to TCEQ and the Engineer.

II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required
- Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
- Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
- Individual 404 Permit Required
- Other Nationwide Permit Required: NWP# _____

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

- 1.
- 2.
- 3.
- 4.

The elevation of the ordinary high water marks of any areas requiring work to be performed in the waters of the US requiring the use of a nationwide permit can be found on the Bridge Layouts.

Best Management Practices:

| | | |
|--|--|--|
| Erosion | Sedimentation | Post-Construction TSS |
| <input checked="" type="checkbox"/> Temporary Vegetation | <input checked="" type="checkbox"/> Silt Fence | <input checked="" type="checkbox"/> Vegetative Filter Strips |
| <input type="checkbox"/> Blankets/Matting | <input type="checkbox"/> Rock Berm | <input type="checkbox"/> Retention/Irrigation Systems |
| <input type="checkbox"/> Mulch | <input type="checkbox"/> Triangular Filter Dike | <input type="checkbox"/> Extended Detention Basin |
| <input type="checkbox"/> Sodding | <input type="checkbox"/> Sand Bag Berm | <input type="checkbox"/> Constructed Wetlands |
| <input type="checkbox"/> Interceptor Swale | <input type="checkbox"/> Straw Bale Dike | <input type="checkbox"/> Wet Basin |
| <input type="checkbox"/> Diversion Dike | <input type="checkbox"/> Brush Berms | <input type="checkbox"/> Erosion Control Compost |
| <input type="checkbox"/> Erosion Control Compost | <input type="checkbox"/> Erosion Control Compost | <input type="checkbox"/> Mulch Filter Berm and Socks |
| <input type="checkbox"/> Mulch Filter Berm and Socks | <input type="checkbox"/> Mulch Filter Berm and Socks | <input type="checkbox"/> Compost Filter Berm and Socks |
| <input type="checkbox"/> Compost Filter Berm and Socks | <input type="checkbox"/> Compost Filter Berm and Socks | <input type="checkbox"/> Vegetation Lined Ditches |
| | <input type="checkbox"/> Stone Outlet Sediment Traps | <input type="checkbox"/> Sand Filter Systems |
| | <input type="checkbox"/> Sediment Basins | <input type="checkbox"/> Grassy Swales |

III. CULTURAL RESOURCES

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

- No Action Required Required Action

Action No.

- 1.
- 2.
- 3.
- 4.

IV. VEGETATION RESOURCES

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

- No Action Required Required Action

Action No.

- 1. Contractor to adhere to specs listed above in IV.
- 2.
- 3.
- 4.

V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.

- No Action Required Required Action

Action No.

- 1. Adhere to the Migratory Bird Treaty Act.
- 2.
- 3.
- 4.

If any of the listed species are observed, cease work in the immediate area, do not disturb species or habitat and contact the Engineer immediately. The work may not remove active nests from bridges and other structures during nesting season of the birds associated with the nests. If caves or sinkholes are discovered, cease work in the immediate area, and contact the Engineer immediately.

LIST OF ABBREVIATIONS

| | |
|---|---|
| BMP: Best Management Practice | SPCC: Spill Prevention Control and Countermeasure |
| CGP: Construction General Permit | SW3P: Storm Water Pollution Prevention Plan |
| DSHS: Texas Department of State Health Services | PCN: Pre-Construction Notification |
| FHWA: Federal Highway Administration | PSL: Project Specific Location |
| MOA: Memorandum of Agreement | TCEQ: Texas Commission on Environmental Quality |
| MOU: Memorandum of Understanding | TPDES: Texas Pollutant Discharge Elimination System |
| MS4: Municipal Separate Stormwater Sewer System | TPWD: Texas Parks and Wildlife Department |
| MBTA: Migratory Bird Treaty Act | TxDOT: Texas Department of Transportation |
| NOT: Notice of Termination | T&E: Threatened and Endangered Species |
| NWP: Nationwide Permit | USACE: U.S. Army Corps of Engineers |
| NOI: Notice of Intent | USFWS: U.S. Fish and Wildlife Service |

VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used. Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act. Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- * Dead or distressed vegetation (not identified as normal)
- * Trash piles, drums, canister, barrels, etc.
- * Undesirable smells or odors
- * Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

- Yes No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

- Yes No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

- No Action Required Required Action

Action No.

- 1.
- 2.
- 3.


VII. OTHER ENVIRONMENTAL ISSUES

(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required Required Action


Action No.

- 1.
- 2.
- 3.


| | | | |
|---|-----------|-----------|---------------------------------|
|  | | © 2024 | Design Division Standard |
| ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS | | | |
| EPIC | | | |
| FILE: epic.dgn | DN: TxDOT | CK: RG | DW: VP |
| ©TxDOT: February 2015 | CONT | SECT | JOB |
| 12-12-2011 IDS REVISIONS | 0910 | 12 | 141 |
| 05-07-14 ADDED NOTE SECTION IV. | DIST | COUNTY | SHEET NO. |
| 01-23-2015 SECTION I CHANGED ITEM 1122 TO ITEM 506, ADDED GRASSY SWALES. | TYL | VAN ZANDT | 40 |

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. The use of this standard for the conversion of this standard to other formats or for incorrect results or damages resulting from its use, TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024
 FILE: c:\pww-int\fratech\has.in.jinna\dms34488\ec916.dgn




PLAN VIEW




SECTION A-A
EROSION CONTROL LOG DAM

CL-D




PLAN VIEW




SECTION B-B
EROSION CONTROL LOG AT BACK OF CURB

CL-BOC




PLAN VIEW




SECTION C-C
EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY

CL-ROW



DIAMETER MEASUREMENTS OF EROSION CONTROL LOGS SPECIFIED IN PLANS

- LEGEND**
- CL-D EROSION CONTROL LOG DAM
 - CL-BOC EROSION CONTROL LOG AT BACK OF CURB
 - CL-ROW EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY
 - CL-SST EROSION CONTROL LOGS ON SLOPES STAKE AND TRENCHING ANCHORING
 - CL-SSL EROSION CONTROL LOGS ON SLOPES STAKE AND LASHING ANCHORING
 - CL-DI EROSION CONTROL LOG AT DROP INLET
 - CL-CI EROSION CONTROL LOG AT CURB INLET
 - CL-GI EROSION CONTROL LOG AT CURB & GRATE INLET



REBAR STAKE DETAIL

SEDIMENT BASIN & TRAP USAGE GUIDELINES

An erosion control log sediment trap may be used to filter sediment out of runoff draining from an unstabilized area.

Log Traps: The drainage area for a sediment trap should not exceed 5 acres. The trap capacity should be 1800 CF/Acre (0.5" over the drainage area).

Control logs should be placed in the following locations:

1. Within drainage ditches spaced as needed or min. 500' on center
2. Immediately preceding ditch inlets or drain inlets
3. Just before the drainage enters a water course
4. Just before the drainage leaves the right of way
5. Just before the drainage leaves the construction limits where drainage flows away from the project.

The logs should be cleaned when the sediment has accumulated to a depth of 1/2 the log diameter.

Cleaning and removal of accumulated sediment deposits is incidental and will not be paid for separately.


- GENERAL NOTES:**
1. EROSION CONTROL LOGS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, OR AS DIRECTED BY THE ENGINEER.
 2. LENGTHS OF EROSION CONTROL LOGS SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND AS REQUIRED FOR THE PURPOSE INTENDED.
 3. UNLESS OTHERWISE DIRECTED, USE BIODEGRADABLE OR PHOTODEGRADABLE CONTAINMENT MESH ONLY WHERE LOG WILL REMAIN IN PLACE AS PART OF A VEGETATIVE SYSTEM. FOR TEMPORARY INSTALLATIONS, USE RECYCLABLE CONTAINMENT MESH.
 4. FILL LOGS WITH SUFFICIENT FILTER MATERIAL TO ACHIEVE THE MINIMUM COMPACTED DIAMETER SPECIFIED IN THE PLANS WITHOUT EXCESSIVE DEFORMATION.
 5. STAKES SHALL BE 2" X 2" WOOD OR #3 REBAR, 2'-4' LONG, EMBEDDED SUCH THAT 2" PROTRUDES ABOVE LOG, OR AS DIRECTED BY THE ENGINEER.
 6. DO NOT PLACE STAKES THROUGH CONTAINMENT MESH.
 7. COMPOST CRADLE MATERIAL IS INCIDENTAL & WILL NOT BE PAID FOR SEPARATELY.
 8. SANDBAGS USED AS ANCHORS SHALL BE PLACED ON TOP OF LOGS & SHALL BE OF SUFFICIENT SIZE TO HOLD LOGS IN PLACE.
 9. TURN THE ENDS OF EACH ROW OF LOGS UPSLOPE TO PREVENT RUNOFF FROM FLOWING AROUND THE LOG.
 10. FOR HEAVY RUNOFF EVENTS, ADDITIONAL UPSTREAM STAKES MAY BE NECESSARY TO KEEP LOG FROM FOLDING IN ON ITSELF.

SHEET 1 OF 3

| | | | |
|---|-----------|---------------------------------|-----------|
| | | Design Division Standard | |
| TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES | | | |
| EROSION CONTROL LOG | | | |
| EC (9) - 16 | | | |
| FILE: ec916 | DN: TxDOT | CK: KM | DW: LS/PT |
| © TxDOT: JULY 2016 | CONT | SECT | JOB |
| REVISIONS | 0910 | 12 | 141 |
| | DIST | COUNTY | SHEET NO. |
| | TYL | VAN ZANDT | 41 |


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024
 FILE: c:\pww-internet\has.in.jinna\dms34488\ec916.dgn



**EROSION CONTROL LOGS ON SLOPES
 STAKE AND TRENCHING ANCHORING**


CL-SST



END SECTION RAP DETAIL


| SLOPE | LOG DIAMETER | | | |
|----------------|--------------|-----|-----|-----|
| | 6" | 8" | 12" | 18" |
| 1:1 OR STEEPER | 5' | 10' | 15' | 20' |
| 2:1 | 10' | 20' | 30' | 40' |
| 3:1 | 15' | 30' | 45' | 60' |
| 4:1 OR FLATTER | 20' | 40' | 60' | 80' |

* ADJUSTMENTS CAN BE MADE FOR SOIL TYPE:
 SOFT, LOAMY SOILS-ADJUST ROWS CLOSER TOGETHER;
 HARD, ROCKY SOILS- ADJUST ROWS FARTHER APART




**EROSION CONTROL LOGS ON SLOPES
 STAKE AND LASHING ANCHORING**

CL-SSL




STAKE AND TRENCHING ANCHORING DETAIL

CL-SST



STAKE AND LASHING ANCHORING DETAIL

CL-SSL



STAKE NOTCH DETAIL

| LOG DIAMETER | DEPTH |
|--------------|-------|
| 6" | 2" |
| 8" | 3" |
| 12" | 4" |
| 18" | 5" |


TRENCH DEPTH TABLE

SHEET 2 OF 3

| | | | |
|---|-----------|---------------------------------|-----------|
| | | Design Division Standard | |
| TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16 | | | |
| FILE: ec116 | DN: TxDOT | CK: KM | DW: LS/PT |
| © TxDOT: JULY 2016 | CONT SECT | JOB | HIGHWAY |
| REVISIONS | 0910 12 | 141 | VARIOUS |
| | DIST | COUNTY | SHEET NO. |
| | TYL | VAN ZANDT | 42 |


DISCLAIMER:
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/12/2024
 FILE: c:\npw\infratech\has.in.j.inna\dms34488\ec916.dgn




EROSION CONTROL LOG AT DROP INLET

CL-DI



EROSION CONTROL LOG AT CURB INLET


CL-CI



EROSION CONTROL LOG AT CURB INLET



CL-CI

NOTE:
 EROSION CONTROL LOGS USED AT CURB INLETS SHOULD ONLY BE USED IF THEY WILL NOT IMPEDE TRAFFIC OR FLOOD THE ROADWAY OR WHEN THE STORM SEWER SYSTEM IS NOT FULLY FUNCTIONAL.



EROSION CONTROL LOG AT CURB & GRADE INLET

CL-GI



SHEET 3 OF 3

| | | | |
|---|-----------|---------------------------------|-----------|
| | | Design Division Standard | |
| TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16 | | | |
| FILE: ec916 | DN: TxDOT | CK: KM | DW: LS/PT |
| © TxDOT: JULY 2016 | CONT | SECT | JOB |
| REVISIONS | 0910 | 12 | 141 |
| | DIST | COUNTY | SHEET NO. |
| | TYL | VAN ZANDT | 43 |