SEE SHEET 2 FOR "INDEX OF SHEETS"

# STATE OF TEXAS TEXAS DEPARTMENT OF TRANSPORTATION


DIV.NO.		PROJECT NO.						
6		1						
STATE		STATE DIST.	COUNTY					
TEXAS		YKM	AUST	IN, ETC.				
CONT.		SECT.	JOB HIGH		WAY NO.			
				СП 24	ETC			

# PLANS OF PROPOSED STATE HIGHWAY IMPROVEMENT

SPECIALTY PAVEMENT MARKERS
STATE PROJECT NO. RMC 6467-09-001
COUNTY: AUSTIN, ETC.
LIMITS: SH 36, ETC.

CONTRACTOR:	
DATE OF LETTING:	
DATE WORK BEGAN:	
DATE WORK COMPLETED:	
DATE WORK ACCEPTED:	
FINAL CONTRACT COST: \$	

LIST OF APPROVED FIELD	CHANGES:
THIS IS TO CERTIFY THAT THE WORK WAS PERFORMED IN ACCOR PLANS, CONTRACT AND LISTED	RDANCE WITH THE
AREA ENGINEER	DATE





SUBMITTED FOR LETTING

5-24-24

DIRECTOR OF OPERATIONS

SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: SPECIAL LABOR PROVISIONS FOR STATE PROJECTS (000---008).

RAILROAD CROSSINGS: NO

TEXAS DEPARTMENT OF TRANSPORTATION
© 2024 BY TEXAS DEPARTMENT OF TRANSPORTATION
ALL RIGHTS RESERVED

SHEET
NO. DESCRIPTION

GENERAL

1 TITLE SHEET
2 INDEX OF SHEETS
3-4 GENERAL NOTES
5 ESTIMATE & QUANTITY SHEET
6-10 SPECIALITY PAVEMENT MARKINGS SUMMARY

TRAFFIC CONTROL

STANDARD SHEETS

11-22 BC(1-12)-21

TRAFFIC

TCP(2-2)-18

TCP(2-4)-18

TCP(2-6)-18 TCP(6-1)-12 TCP(6-2)-12

TCP(6-3)-12 WZ(RS)-22

23 24

25 26 27

28

30 PM(1)-22 31 PM(3)-22



THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ABOVE HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.

Karh C. March, P. E. May 31, 2024

# INDEX OF SHEETS

Texas Department of Transportation
© 2024 BY TEXAS DEPARTMENT OF TRANSPORTATION
ALL RIGHTS RESERVED

FED DIV	.RD. .NO.	PROJECT NO.								
(	ő	RMC 6467-09-001								
CONT.	SECT.	JOB	HIGHWAY NO.							
			SH 36, ETC.							
STATE	DIST.	COUNTY	SHEET NO.							
TEXAS	YKM	AUSTIN, ETC.	2							

Project Number: RMC 6467-09-001

County: AUSTIN, ETC.

Highway: SH 36, ETC.

**GENERAL NOTES:** 

**GENERAL:** 

Contractor questions on this project are to be addressed to the following individual(s):

Camille Marek <u>Camille\_Marek@txdot.gov</u>
Kelly Rother <u>Kelly.Rother@txdot.gov</u>

Questions may be submitted via the Letting Pre-Bid Q&A web page. This webpage can be accessed from the Notice to Contractors dashboard located at the following Address: https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors

All contractor questions will be reviewed by the Engineer. All questions and any corresponding responses that are generated will be posted through the same Letting Pre-Bid Q&A web page.

The Letting Pre-Bid Q&A web page for each project can be accessed by using the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink for the project you want to view the Q&A for and click on the link in the window that pops up.

Do not work on the roadway before sunrise or after sunset unless otherwise approved.

Leave all traffic lanes open to traffic at night, weekends and holidays unless otherwise approved. Do not cross the median except at existing crossovers.

# ITEM 7: LEGAL RELATIONS AND RESPONSIBILITIES

No significant traffic generator events identified.

# **ITEM 8: PROSECUTION AND PROGRESS**

Provide progress schedule as a Bar Chart.

**Project Number: RMC 6467-09-001** 

County: AUSTIN, ETC.

Highway: SH 36, ETC.

ITEM 502: BARRICADES, SIGNS, AND TRAFFIC HANDLING

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

Use WZ(RS)-22 in conjunction with TCP(2-2), TCP(2-4), and TCP(2-6). Use

TCP(2-2b) for one-lane, two-way traffic control.

When using TCP(2-2b), a pilot car is required to lead traffic through the work space with or without channelizing devices on the center line unless otherwise approved.

When using TCP(2-2b), channelizing devices may be omitted during base, subgrade and seal coat operations unless otherwise directed. Flaggers will be required at public intersections when channelizing devices are omitted.

When using TCP(2-2b), arrow boards, displaying the caution mode, may be used to enhance the flagger stations. If used, place the arrow board in advance of the flagger station a distance of ½X, the sign spacing distance shown on BC(2). Use arrow boards as shown on BC(7).

When using TCP(2-2b), the temporary 24" stop line and the CW16-2P plaques may be omitted.

When using TCP(2-2b), an additional "Road Work Ahead" and "Be Prepared To Stop" signs will be required on each end of the lane closure unless otherwise approved.

Provide suitable warning lights mounted high enough to be visible from all directions on all construction equipment, including pilot vehicles, and operate warning lights when the equipment is within the right of way. Equip other equipment such as trucks, trailers, autos, etc., with emergency flashers and use emergency flashers while within the work area.

Project limit traffic control devices will not be required for this project.

Sheet 3

P	roject Number: RMC 6467-09-001
C	ounty: AUSTIN, ETC.
Н	lighway: SH 36, ETC.

Project Number: RMC 6467-09-001

County: AUSTIN, ETC.

Highway: SH 36, ETC.

# ITEM 668: PREFABRICATED PAVEMENT MARKINGS

Pavement marking material may be placed on roadways at any time during the year, subject to temperature and moisture limitations specified.

# ITEM 6185: TRUCK MOUNTED ATTENUATOR (TMA) AND TRAILER ATTENUATOR (TA)

Shadow vehicle(s) with TMA are set up for stationary and/or mobile operations. The contractor will be responsible for determining if operations will be ongoing at the same time to determine the total number of TMAs needed for the project.

The TMA/TA used for installation/removal of traffic control for a work area will be subsidiary to the TMA/TA used to perform the work.

Sheet 4



# **Estimate & Quantity Sheet**

**CONTROLLING PROJECT ID** 6467-09-001

**DISTRICT** Yoakum SH0036

**COUNTY** Austin

		CONTROL SECTION	N JOB	6467-0	9-001		
		PROJI	ECT ID	A0020	9503		
		cc	DUNTY	Aus	tin	TOTAL EST.	TOTAL FINAL
		HIG	HWAY	SHOO	036		
ALT	BID CODE	DESCRIPTION	UNIT		FINAL		
	500-6001	MOBILIZATION	LS	1.000		1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	МО	6.000		6.000	
	668-6074	PREFAB PAV MRK TY C (W) (12") (SLD)	LF	3,393.000		3,393.000	
	668-6075	PREFAB PAV MRK TY C (W) (18") (SLD)	LF	236.000		236.000	
	668-6076	PREFAB PAV MRK TY C (W) (24") (SLD)	LF	2,248.000		2,248.000	
	668-6077	PREFAB PAV MRK TY C (W) (ARROW)	EA	89.000		89.000	
	668-6078	PREFAB PAV MRK TY C (W) (DBL ARROW)	EA	3.000		3.000	
	668-6085	PREFAB PAV MRK TY C (W) (WORD)	EA	42.000		42.000	
	668-6091	PREFAB PAV MRK TY C (W) (18")(YLD TRI)	EA	39.000		39.000	
	668-6092	PREFAB PAV MRK TY C (W) (36")(YLD TRI)	EA	29.000		29.000	
	668-6106	PREFAB PAV MRK TY C (Y) (12") (SLD)	LF	1,500.000		1,500.000	
	6185-6002	TMA (STATIONARY)	DAY	90.000		90.000	



DISTRICT	COUNTY	CCSJ	SHEET
Yoakum	Austin	6467-09-001	5

				668-6074	668-6075	668-6076		668-	-6077		668-6078		668-6085		668-6091	668-6092	668-6106
OCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12") (SLD)	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (18") (YLD TRI)		PREFAB PAV MRK TY ( (Y) (12") (SLD
					(= ,		"LEFT"	"RIGHT"	"STRAIGHT"	"DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
1	AUSTIN	SH 36	LOOP 350 INTERSECTION AT CVS PHARMACY			36											
2	AUSTIN	SH 36	TURNING LANE FOR LOOP 350					2				2					
			AUSTIN COUNTY TOTALS	0	0	36	0	2	0	0	0	2	0	0	0	0	0
					1							1				1	
				668-6074	668-6075	668-6076	DD554D		-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12") (SLD)	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)		PREFAB PAV MRK TY C (W) (36") (YLD TRI)	PREFAB PAV MRK TY ( (Y) (12") (SLD
				(SLD)	(SLD)	(SLD)	"LEFT"	"RIGHT"		"DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
3	CALHOUN	SH 238	AT SH 238	68		75											
4	CALHOUN	US 87	AT FM 1090			30											
5	CALHOUN	FM 1090	AT US 87 NORTH SIDE OF US 87			24											
6	CALHOUN	US 87	AT SEADRIFT STREET	168		123											
7	CALHOUN	US 87	AT WESTERLUND ROAD			12											
8	CALHOUN	US 87	AT FM 1090			40											
9	CALHOUN	SH 35	AT US 87														
10	CALHOUN	SH 35	AT FM 2433			73											
			CALHOUN COUNTY TOTALS	236	0	377	0	0	0	0	0	0	0	0	0	0	0
				668-6074	668-6075	668-6076		668-	-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (18") (YLD TRI)	PREFAB PAV MRK TY C	PREFAB PAV MRK TY ( (Y) (12") (SLD
				/	,,	, , , , , , , , , , , , , , , , , , , ,	"LEFT"	"RIGHT"	"STRAIGHT"	"DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
11	COLORADO	SH 71	SH 71 EASTBOUND FLYOVER AT IH 10														305
12	COLORADO	UA 90	EAGLE LAKE CITY LIMITS			122	17	15	2			8			5		
13	COLORADO	FM 2614	AT FM 950			30											
		,	COLORADO COUNTY TOTALS	0	0	152	17	15	2	0	0	8	0	0	5	0	305





FED. DIV.		PROJECT	ROJECT NO.						
6	i	RMC 6467-09-001							
CONT.	SECT.	JOB	HIGHWAY NO.						
			SH 36, ETC.						
STATE	DIST.	COUNTY	SHEET NO.						
TEXAS	YKM	AUSTIN, ETC.	6						

έ .:: <u></u>	1017: 5/3/3/
PATH: NFS-YKMHQ.dot.state.tx.us/U. FILE: SPECIALTY_SUMMARY.dgn	

	1	l		668-6074	668-6075	668-6076		668-	-6077	ı	668-6078		668-6085	ļ	668-6091	668-6092	668-6106
OCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12") (SLD)	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	C	PREFAB PAV MRK TY C (W) (DBL ARROW)	TY C	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C ) (W) (WORD)	(W) (18") (YLD	PREFAB PAV MRK TY C (W) (36") (YLD TRI)	PREFAB PAV MRK TY (Y) (12") (SLD
	[	I					"LEFT"	"RIGHT"	"STRAIGHT"	"DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
14	DE WITT	US 183	AT FM 237			12											
15	DE WITT	FM 237 W	AT US 183			12											
16	DE WITT	FM 237 E	AT US 183			12											
17	DE WITT	US 183	AT FM 2718					1				1					
18	DE WITT	FM 3157	AT FM 236			12									<u> </u>		
19	DE WITT	FM 238	AT FM 240			15											
20	DE WITT	FM 2816	AT FM 240			12											
21	DE WITT	FM 2816	AT US 87			15											
22	DE WITT	FM 3010	AT FM 682			15											
23	DE WITT	FM 1447	AT FM 682 S			10											
24	DE WITT	FM 1447	AT FM 682 N			11	T										
25	DE WITT	FM 966	AT SH 111			15									1		
26	DE WITT	FM 2656	AT FM 952			11											
27	DE WITT	FM 952	AT FM 2656			12									1		
28	DE WITT	US 87	AT BROADWAY ST.	350		76											
29	DE WITT	US 87	N AT MAIN ST	348		74									1		
30	DE WITT	US 87	AT W MORGAN ST	100		24											
31	DE WITT	US 87	AT E HEATON ST	56		12											
32	DE WITT	US 87	AT HEATON ST.			36	1								1		
33	DE WITT	US 87	AT FM 236	112		32											
34	DE WITT	US 87	AT ESPLANADE ST.	160		36											
35	DE WITT	US 87	AT HUNT ST	192		48											
36	DE WITT	US 87	AT PARK HEIGHTS	157		42											
37	DE WITT	US 87	AT FAIN MCDOUGAL DR	186		32	1				1				17		
38	DE WITT	US 87	AT PARK HEIGHTS	176		48											
39	DE WITT	US 87	AT REUSS BLVD.	170		38									[		
			DE WITT COUNTY TOTALS	2,007	0	662	2	1	0	0	1	1	0	0	17	0	0





			SHEET E OF S					
FED DIV	.RD. .NO.	PROJECT NO.						
(	5	RMC 6467-09-001						
CONT.	SECT.	JOB	HIGHWAY NO.					
			SH 36, ETC.					
STATE	DIST.	COUNTY	SHEET NO.					
TEXAS	YKM	AUSTIN, ETC.	7					

PATH: NFS-YKMHQ.dot.state.tx.us\DATA\\DATA\\YKM\GRO\

				668-6074	668-6075	668-6076		668	3-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12") (SLD)	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	TY C	PREFAB PAV MRK TY C (W) (WORD)	TY C	PREFAB PAV MRK TY C (W) (18") (YLD TRI)	PREFAB PAV MRK TY C (W) (36") (YLD TRI)	PREFAB PAV MRK TY C (Y) (12") (SLD)
							"LEFT"	"RIGHT"	"STRAIGHT	" "DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
40	FAYETTE	BS 71 E	AT WEST INTERCHANGE BETWEEN BS 71 E AND NORTH FRTG RD														588
41	FAYETTE	BS 71 E	AT WEST INTERCHANGE					2			2	2					
42	FAYETTE	BS 71 E	AT MCDONALDS														136
43	FAYETTE	BS 71 E	AT FM 609					2				2					
44	FAYETTE	BS 71 E	BETWEEN MAIN AND WASHINGTON														95
45	FAYETTE	BS 71 E	WEST OF MAIN STREET														28
46	FAYETTE	BS 71 E	AT US 77				2					2					
48	FAYETTE	IH 10	FLATONIA FM 609 OFF RAMP WB										1	1			
49	FAYETTE	IH 11	FLATONIA SH 95 OFF RAMP EB										1	1			
50	FAYETTE	SH 95	FLATONIA JCT IH 10					2				2					
51	FAYETTE	IH 10	FLATONIA JCT SH 95														348
52	FAYETTE	US 77	SCHULENBURG AT IH 10				6										
53	FAYETTE	US 77	SCHULENBURG AT US 90				3	2					2	2			
54	FAYETTE	US 77	SCHULENBURG AT JCT SL 222				1										
55	FAYETTE	FM 954	AT SH 159										1	1			
56	FAYETTE	FM 954	AT SH 237										1	1			
			FAYETTE COUNTY TOTALS	0	0	0	12	8	0	0	2	8	6	6	0	0	1195
				668-6074	668-6075	668-6076			3-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12") (SLD)	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	TY C	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)		PREFAB PAV MRK TY C (W) (36") (YLD TRI)	PREFAB PAV MRK TY C (Y) (12") (SLD)
							"LEFT"	"RIGHT"	"STRAIGHT	" "DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
57	GONZALES	US 183	AT SH 97	24													
			GONZALES COUNTY TOTALS	24	0	0	0	0	0	0	0	0	0	0	0	0	0





	.RD. .NO.	PROJECT NO.						
6	5	RMC 6467-09-001						
CONT.	SECT.	JOB	HIGHWAY NO.					
			SH 36, ETC.					
STATE	DIST.	COUNTY	SHEET NO.					
TEXAS	YKM	AUSTIN, ETC.	8					

VID. MESTERMING.GOUSIAIE.IX.UR	SPECIALTY_SUMMARY.d	
	Έ	į

				668-6074	668-6075	668-6076		668	-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	O. COUNTY HIGHWAY LOCATION		LOCATION	PREFAB	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (18") (YLD TRI)	PREFAB	PREFAB
							"LEFT"	"RIGHT"	"STRAIGHT"	"DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
58	JACKSON	US 59 SB FRTG RD	WHATABURGER TO SH 111 EB						3								
59	JACKSON	US 59 SB FRTG RD	WHATABURGER TO SH 111 WB						3								
60	JACKSON	US 59 SB FRTG RD	SH 111 TO NORTH EAST ST WB						1								
61	JACKSON	US 59 SB FRTG RD	SH 111 TO NORTH EAST ST EB						1								
62	JACKSON	US 59 SB FRTG RD	WHATABURGER WB YIELD			13											
63	JACKSON	US 59 SB FRTG RD	WHATABURGER EB YIELD			13											
64	JACKSON	US 59 NB FRTG RD	FM 822 AT EXIT RAMP WB YIELD			13											
65	JACKSON	US 59 NB FRTG RD	FM 822 AT EXIT RAMP EB YIELD			13											
66	JACKSON	US 59 NB FRTG RD	NB FRTG RD AT SL 521 INTERCHANGE			13											
The state of the s		1	JACKSON COUNTY TOTALS	0	0	65	0	0	8	0	0	0	0	0	0	0	0
						1											
				668-6074	668-6075	668-6076		668	-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12") (SLD)	PREFAB PAV MRK TY C (W) (18") (SLD)	PREFAB PAV MRK TY C (W) (24") (SLD)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (WORD)	PREFAB PAV MRK TY C (W) (18") (YLD TRI)	PREFAB PAV MRK TY C (W) (36") (YLD TRI)	
							"LEFT"	"RIGHT"	"STRAIGHT"	"DIAGONAL"	"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
				LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
67	LAVACA	FM 532	AT FM 1680			23											
68	LAVACA	FM 532	AT SH 95			17											
69	LAVACA	UA 90	SH 95	456		100											
70	LAVACA	UA 77	SH 95			92										14	
71	LAVACA	UA 77	AND UA 90 W			46									17		
72	LAVACA	US 77 N & S	HALLETTSVILLE LUMBER CO.			98	1					1					
73	LAVACA	US 77	UA 77			35	2	2				2					
74	LAVACA	UA 90	SCHOOL ZONE AT KELLEY ST		50												
75	LAVACA	UA 90	SCHOOL ZONE AT MARKET ST	100													
76	LAVACA	UA 90	SCHOOL ZONE AT RIDGE ST	100													
77	LAVACA	UA 90	SCHOOL ZONE AT MCLEON ST		50												
78	LAVACA	FM 530	AT UA 90			16											





			022 0. 5					
FED. DIV.	RD. NO.	PROJECT NO.						
6	i	RMC 6467-09-001						
CONT.	SECT.	JOB	HIGHWAY NO.					
			SH 36, ETC.					
STATE	DIST.	COUNTY	SHEET NO.					
TEXAS	YKM	AUSTIN, ETC.	9					

				668-6074	668-6075	668-6076		668	3-6077		668-6078		668-6085		668-6091	668-6092	668-6106
LOCATION NO.	. COUNTY	HIGHWAY	LOCATION	PREFAB	PREFAB PAV MRK TY C (W) (18")	PREFAB PAV MRK TY C (W) (24")	PREFAB PAV MRK TY C (W)	PREFAB PAV MRK TY C (W)	PREFAB PAV MRK TY C (W)	C	PREFAB PAV MRK TY C (W) (DBL	PREFAB PAV MRK TY C	PREFAB PAV MRK TY C	PREFAB PAV MRK TY C	PREFAB PAV MRK TY C (W) (18") (YLD	PREFAB PAV MRK TY C (W) (36") (YLD	PREFAB
				(SLD)	(SLD)	(SLD)	(ARRÓW)	(ARROW)	(ARRÓW)	(W) (ARROW)	ARROW)		(W) (WORD)		TRI)	TRI)	
							"LEFT"	"RIGHT"	"STRAIGHT		"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			
	+			LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
79	MATAGORDA	FM 2031	SH 60 TO END STATE MAINTENANCE			22									-	15	
80	MATAGORDA	FM 521	FM 1468 TO STP ENTRANCE			45											
			MATAGORDA COUNTY TOTALS	0	0	67	0	0	0	0	0	0	0	0	0	15	0
					T											T	
			-	PREFAB PAV MRK TY	PREFAB PAV MRK TY	PREFAB PAV MRK TY	PREFAB PAV MRK	PREFAB PAV MRK	PREFAB PAV MRK	PREFAB PAV MRK TY	668-6078 PREFAB PAV MRK TY C	PREFAB PAV MRK	PREFAB PAV MRK	PREFAB PAV MRK	668-6091 PREFAB PAV MRK TY C	PREFAB PAV MRK TY C	668-6106 PREFAB
LOCATION NO.	COUNTY	HIGHWAY	LOCATION	C (W) (12") (SLD)	(W) (18") (SLD)	C (W) (24") (SLD)	TY C (W) (ARROW)	TY C (W) (ARROW)	TY C (W) (ARROW)	C (W) (ARROW)	(W) (DBL ARROW)	TY C	TY C (W) (WORD)	TY C	(W) (18") (YLD		
I			ŀ	(SLD)	(JLD)	(JLD)	"LEFT"	"RIGHT"	"STRAIGHT		"RIGHT SIDE"	"ONLY"	"STOP"	"AHEAD"			+
			ŀ	LF	LF	LF	EA	EA	EA	EA	EA	EA	EA	EA	EA	EA	LF
81	VICTORIA	US 77	WB FRONTAGE US 87 TO WB ON RAMP TEXAN			+			3	3							
82	VICTORIA	FM 236	SCHOOL ZONE N AND S OF MISSION VALLEY ELEMENTARY		80												
83	VICTORIA	FM 444	STOP LINE AT FM 1686 INTERSECTION			14											
84	VICTORIA	US 87	FRTG RD BOTH STOP LINES AT FM 616 INTERSECTION PLACEDO			67											
85	VICTORIA	FM 616	SCHOOL ZONE W AND E OF BLOOMINGTON HIGH SCHOOL		56												
86	VICTORIA	BU 59	NEW NB LANE DROP AT TEAKWOOD DR 25' OF LAST SKIP LINE							1							
1		-	VICTORIA COUNTY TOTALS	0	136	81	0	0	3	4	0	0	0	0	0	0	0
		-					1	-					1				
				668-6074	668-6075	668-6076		668	3-6077		668-6078 668-6085				668-6091	668-6092	668-6106
LOCATION NO.	. COUNTY	HIGHWAY	LOCATION	PREFAB PAV MRK TY C (W) (12")	PREFAB PAV MRK TY C (W) (18")	PREFAB PAV MRK TY C (W) (24")	PREFAB PAV MRK TY C (W)	PREFAB PAV MRK TY C (W)	PREFAB PAV MRK TY C (W)	PREFAB PAV MRK TY C (W) (ARROW)	PREFAB PAV MRK TY C (W) (DBL ARROW)	PREFAB PAV MRK TY C	PREFAB PAV MRK TY C (W) (WORD)	TY C	(W) (18") (YLD	PREFAB PAV MRK TY C (W) (36") (YLD TRI)	
ı				(SLD)	(SLD)	(SLD)	(ARROW)	(ARROW)	(ARRÓW)						INI	1147	
I				LF	LF	LF	"LEFT" EA	"RIGHT" EA	"STRAIGHT" EA	" "DIAGONAL" EA	"RIGHT SIDE" EA	"ONLY"	"STOP" EA	"AHEAD" EA	EA	EA	LF
87	WHARTON	BU 59R	AT SH 60 S	LF	Lr	LF	1 1	1 1	EA	EA	EA	2 EA	EA	EA	EA	EA	LF
88	WHARTON	BU 59R	AT 511 00 3		+		-	1				1				<del>                                     </del>	+
89	WHARTON	SH 60	SH 60 NORTH AT BU 59R N		+	12						_				<del>                                     </del>	+
90	WHARTON	BU 59R	AT CANEY ST		+	56										<del> </del>	
91	WHARTON	BU 59R	AT BURLESON ST		+	50										<del>                                     </del>	+
92	WHARTON	BU 59R	AT BURLESON ST  AT MILAN ST		+	96	1					1				<del>                                     </del>	-
93	WHARTON	BU 59R	AT FM 1301	470	+	167	2	2	2			4				<del> </del>	+
33	WIARION		WHARTON COUNTY TOTALS		0	381	4	4	2	0	0	8	0	0	0	0	0
			WINITON COOKIT TOTALS	4,0		301	7	7			U	0	U	0			
			PROJECT TOTALS	3,393	236	2,248	38	32	15	4	3	30	6	6	39	29	1500
													_	_			

ITEM 6185	QUANTITY (DAY)
TMA (MOPBILE OPERATION)	90





			-					
	).RD. '.NO.	PROJECT NO.						
(	6	RMC 6467	-09-001					
CONT.	SECT.	JOB	HIGHWAY NO.					
			SH 36, ETC.					
STATE	DIST.	COUNTY	SHEET NO.					
TEXAS	YKM	AUSTIN, ETC.	10					

# ATE: 5/16/2024 10:53:19 AM ILE: \$FILE\$

# BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

- 1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- 2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
- 3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
- 4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- 5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- 6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- 7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- 8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- 9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- 10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
- 11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
- 12. The Engineer has the final decision on the location of all traffic control devices.
- 13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

# WORKER SAFETY NOTES:

- 1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
- 2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

# COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

- Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
- 2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).

# THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD) DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) MATERIAL PRODUCER LIST (MPL) ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)" STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD) TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12



BARRICADE AND CONSTRUCTION GENERAL NOTES

BC(1)-21

AND REQUIREMENTS

.E:	bc-21.dgn		DN: T	×D0T	ck: TxDOT	DW:	TxDO	ТС	k: TxDOT
TxDOT	November 2002		CONT	SECT	JOB			HIGH	VAY
-03	REVISIONS 7-13	RN	IC 064	67-	09-001		SH	36,	ETC.
-07	8-14		DIST		COUNTY	SHEET NO.			
-10	5-21	YKM	A	USTIN.	ET	c.		11	

ROAD

CLOSED R11-2

Type 3

devices


13

Barricade or

channelizing

CW13-1P

Channelizing Devices



- $\sharp$  May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D)sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
- 2. The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
- Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
- The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
- 5. Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
- When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS

ROAD

WORK

AHEAD

CW20-1D

### BEGIN T-INTERSECTION WORK ZONE ★ ★ G20-9TP ★ ★ R20-5T FINES DOUBL X R20-50TP BINEM BORKERS ARE PRESENT ROAD WORK ⟨⇒ NEXT X WILES X X G20-2bT WORK ZONE G20-1bTI $\Diamond$ INTERSECTED 1000' - 1500' - Hwy 1 Block - City 1000'-1500' - Hwy 1 Block - City ROADWAY $\Rightarrow$ ROAD WORK G20-1bTR NEXT X MILES => WORK ZONE G20-2bT \* \* Limit BEGIN G20-5T \* \* G20-9TP ZONE TRAFFI G20-6T \* \* R20-5T FINES DOUBLE \* R20-5aTP WHEN WORKERS ROAD WORK G20-2

# CSJ LIMITS AT T-INTERSECTION

- 1. The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- 2. If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME"(G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow(G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR)" signs shall be replaced by the detour signing called for in the plans.

# TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING 1,5,6

# SIZE

	Posted Speed	Sign∆ Spacing "X"
	MPH	Feet (Apprx.)
	30	120
	35	160
	40	240
	45	320
	50	400
	55	500²
	60	600²
	65	700 <sup>2</sup>
	70	800 <sup>2</sup>
	75	900 <sup>2</sup>
	80	1000 <sup>2</sup>
,	*	* 3

SPACING


Sign onventional Expressway/ Number Freeway or Series CW20' CW21 CW22 48" x 48" 48" × 48' CW23 CW25 CW1, CW2, CW7. CW8. 48" x 48' 36" x 36' CW9, CW11 CW14 CW3, CW4, CW5, CW6, 48" x 48" 48" × 48' CW8-3, CW10, CW12

\* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

 $\triangle$  Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

### GENERAL NOTES

- 1. Special or larger size signs may be used as necessary.
- 2. Distance between signs should be increased as required to have 1500 feet advance warning.
- 3. Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 4. 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- 5. Only diamond shaped warning sign sizes are indicated.
- 6. See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design



SPEED

LIMIT

-CSJ Limit

R2-1

BEGIN ROAD WORK NEXT X MILES

\* \*G20-5T

\* \*G20-6T

END

ROAD WORK

G20-2 \* \*

ROAD

WORK

∕₂ MILE

CW20-1E

★ ★G20-9TP

¥ ¥R20-5T

 $\times$   $\times$  R20-5aTP

ZONE

FINES

DOUBLE

SPEED R2-1

LIMIT

TRAFFIC

OBEY

SIGNS

STAY ALERT

G20-10

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS

The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "X" and shall be rounded to the nearest whole mile with the approval of the Engineer.

- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2b1 shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
- \*\* CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
- Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic
- the end of the work zone.

	LEGEND
I	Type 3 Barricade
000	Channelizing Devices
4	Sign
Х	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

# SHEET 2 OF 12



Traffic Safety

# BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC(2)-21


ILE:	bc-21.dgn	DN: TXDOT CK: TXDOT DW: TXDO		T c	k: TxDOT			
C) TxDOT	November 2002	CONT	SECT	JOB			WAY	
	REVISIONS F	MC 064	67-	09-001		SH	36,	ETC.
9-07	8-14	DIST	COUNTY				EET NO.	
7-13	5-21	YKM	Α	USTIN,	EΤ	C.		12

STATE LAW TALK OR TEXT LATER R20-3T  $\Diamond$  $\Rightarrow$ END | WORK ZONE G20-26T \* \*

Contractor will install a regulatory speed limit sign at

# TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.



# GUIDANCE FOR USE:

# LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- a) rough road or damaged pavement surface
- b) substantial alteration of roadway geometrics (diversions)
- c) construction detours
- d) grade
- e) width
- f) other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

# SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

# GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- 2. Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- 3. Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- 4. Frequency of work zone speed limit signs should be:

40 mph and greater 0.2 to 2 miles

35 mph and less 0.2 to 1 mile

- 5. Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- 7. Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
   A. Law enforcement.
  - B. Flagger stationed next to sign.
  - C. Portable changeable message sign (PCMS).
  - D. Low-power (drone) radar transmitter.
  - E. Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only.
   Work Zone Speed Limits should only be posted as approved for each project.
- 10. For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

SHEET 3 OF 12



Traffic Safety Division Standard


# BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC(3)-21

:	bc-21.dgn	DN: TXDOT		CK: TxDOT DW		Dw: TxDO		CK:	: TxDOT
TxDOT	November 2002	CONT	SECT	JOB		HIGHWAY			Y.
		VIC 064	67-	09-001		SH	36	,	ETC.
)-07 '-13	8-14 5-21	DIST	DIST COUNTY				SHEET NO.		
-13	3-21	YKM	AUSTIN, E			C.		1	3


97

# TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



\* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

\* X When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two SIDE ELEVATION above and two below the spice point. Splice must be located entirely behind

Attachment to wooden supports will be by bolts and nuts or screws. Use TxDOT's or manufacturer's recommended procedures for attaching sign substrates to other types of sign supports

Nails shall NOT be allowed. Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.


# STOP/SLOW PADDLES

the sign substrate, not near the base of the support. Splice insert lengths

should be at least 5 times nominal post size, centered on the splice and

of at least the same gauge material.

- 1. STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflectorized when used at night. 3. STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- 4. Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING RE	QUIREMEN	TS (WHEN USED AT NIGHT)
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B <sub>FL</sub> OR C <sub>FL</sub> SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

# CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

Wood

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CW7TCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

# GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question reaardina installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

# <u>DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)</u>

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
  - a. Long-term stationary work that occupies a location more than 3 days.
  - Intermediate-term stationary work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
  - Short-term stationary daytime work that occupies a location for more than 1 hour in a single daylight period.
  - Short, duration work that occupies a location up to 1 hour.
- Mobile work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

## SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plagues mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above
- the ground. Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

## SIZE OF SIGNS

The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

## SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

# REFLECTIVE SHEETING

- 1. All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300
- for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- 3. Orange sheeting, meeting the requirements of DMS-8300 Type  $B_{FL}$  or Type  $C_{FL}$ , shall be used for rigid signs with orange backgrounds.

# SIGN LETTERS

1. All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

# REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting. Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

# SIGN SUPPORT WEIGHTS

- 1. Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used. The sandbags will be tied shut to keep the sand from spilling and to maintain a
- constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular
- impact. Rubber (such as tire inner tubes) shall NOT be used. Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured
- with rubber bases may be used when shown on the CWZTCD list. Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

# FLAGS ON SIGNS

1. Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face. SHEET 4 OF 12




# BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC(4)-21

ILE:	bc-21.dgn	DN: T	×D0T	ck: TxDOT	DW:	TxDC	)T	ck: TxDO1
TxDOT	November 2002	CONT	SECT	JOB		HIGHWAY		
		MC 064	67-	09-001		SH	36	, ETC.
9-07 8-14 7-13 5-21	•	DIST		COUNTY			s	HEET NO.
	5-21	YKM	Α	USTIN,	ET.	c.		14







2"

SINGLE LEG BASE

weld starts here



Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



32'

# **WEDGE ANCHORS**

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

# OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

# GENERAL NOTES

- Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" lag screws must be used on every joint for final
- No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CW7TCD List.
- When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.
  - See BC(4) for definition of "Work Duration."
  - Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
  - ☐ See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

# SHEET 5 OF 12



Traffic Safety Division Standard

# BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

# BC(5)-21

7-13	5-21	YKM	Α	USTIN,	ETC	C.		15
9-07	8-14	DIST		COUNTY			SI	HEET NO.
		VIC 064	67-	09-001		SH	36,	, ETC.
© TxDOT	November 2002	CONT	SECT	JOB			HIGH	YAW
FILE:	bc-21.dgn	DN: T	kD0T	ck: TxDOT	DW:	TxD0	T	ck: TxDO

SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

\* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

5/1

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

# PORTABLE CHANGEABLE MESSAGE SIGNS

- 1. The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- 2. Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR." "AT." etc.
- 3. Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by
- 4. Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- 5. Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- 7. The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- 8. The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- 9. Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- 10. Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- 11. Do not use the word "Danger" in message.
- 12. Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- 13. Do not display messages that scroll horizontally or vertically across the face of the sign.
- 14. The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- 15. PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- 16. Each line of text should be centered on the message board rather than left or right justified.
- 17. If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	F	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER E	Slippery	SL IP
Emergency Vehicle		South	S
Entrance, Enter	ENT ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
	FOG AHD	Telephone	PHONE
Fog Ahead	FRWY, FWY	Temporary	TEMP
Freeway Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving		Traffic	TRAF
Hazardous Material		Travelers	TRVLRS
	HOV	Tuesday	TUES
High-Occupancy Vehicle	HUV	Time Minutes	TIME MIN
	HWY	Upper Level	UPR LEVEL
Highway Hour(s)	HR. HRS	Vehicles (s)	VEH, VEHS
Information	INFO	Warning	WARN
Intermetion It is	ITS	Wednesday	WED
Junction	JCT	Weight Limit	WT LIMIT
Left	LFT	West	W
		Westbound	(route) W
Left Lane	LFT LN	Wet Pavement	WET PVMT
Lane Closed	LN CLOSED	Will Not	WONT
Lower Level	LWR LEVEL	•	

Maintenance

designation # IH-number, US-number, SH-number, FM-number

MAINT

# RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

# Phase 1: Condition Lists

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED	ROADWORK XXX FT	ROAD REPAIRS XXXX FT
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT	FLAGGER XXXX FT	LANE NARROWS XXXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT	RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
RIGHT X LANES CLOSED	RIGHT X LANES OPEN	MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
CENTER LANE CLOSED	DAYTIME LANE CLOSURES	LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED	DETOUR X MILE	ROUGH ROAD XXXX FT
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE	ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
EXIT CLOSED	RIGHT LN TO BE CLOSED	BUMP XXXX FT	US XXX EXIT X MILES
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI	TRAFFIC SIGNAL XXXX FT	LANES SHIFT
XXXXXXX			

LANE

# Phase 2: Possible Component Lists

111036 1. CON	Idilion Lisi	3									
mp Closure List	Other Cond	dition List	Action to To	ake/Effect on Travel List	Location List	Warning List	* * Advance Notice List				
FRONTAGE ROAD CLOSED	ROADWORK XXX FT	ROAD REPAIRS XXXX FT	MERGE RIGHT	FORM X LINES RIGHT	AT FM XXXX	SPEED LIMIT XX MPH	TUE-FRI XX AM- X PM				
SHOULDER CLOSED XXX FT	FLAGGER XXXX FT	LANE NARROWS XXXX FT	DETOUR NEXT X EXITS	USE XXXXX RD EXIT	BEFORE RAILROAD CROSSING	MAXIMUM SPEED XX MPH	APR XX- XX X PM-X AM				
RIGHT LN CLOSED XXX FT	RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE	USE EXIT XXX	USE EXIT I-XX NORTH	NEXT X MILES	MINIMUM SPEED XX MPH	BEGINS MONDAY				
RIGHT X LANES OPEN	MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT	STAY ON US XXX SOUTH	USE I-XX E TO I-XX N	PAST US XXX EXIT	ADVISORY SPEED XX MPH	BEGINS MAY XX				
DAYTIME LANE CLOSURES	LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT	TRUCKS USE US XXX N	WATCH FOR TRUCKS	XXXXXXX TO XXXXXXX	RIGHT LANE EXIT	MAY X-X XX PM - XX AM				
I-XX SOUTH EXIT CLOSED	DETOUR X MILE	ROUGH ROAD XXXX FT	WATCH FOR TRUCKS	EXPECT DELAYS	US XXX TO FM XXXX	USE CAUTION	NEXT FRI-SUN				
EXIT XXX CLOSED X MILE	ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN	EXPECT DELAYS	PREPARE TO STOP		DRIVE SAFELY	XX AM TO XX PM				
RIGHT LN TO BE CLOSED	BUMP XXXX FT	US XXX EXIT X MILES	REDUCE SPEED XXX FT	END SHOULDER USE		DRIVE WITH CARE	NEXT TUE AUG XX				
X LANES CLOSED TUE - FRI	TRAFFIC SIGNAL XXXX FT	LANES SHIFT *	USE OTHER ROUTES	WATCH FOR WORKERS			TONIGHT XX PM- XX AM				
* LANES SHIFT in Phas	e 1 must be used wit	h STAY IN LANE in Pho	STAY IN LANE		* * Se	ee Application Guideli	nes Note 6.				

## APPLICATION GUIDELINES

- 1. Only 1 or 2 phases are to be used on a PCMS.
- 2. The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- 3. A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- 4. A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- 5. If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- 6. For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

# WORDING ALTERNATIVES

location phase is used.

- 1. The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- 2. Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- 3. EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- 4. Highway names and numbers replaced as appropriate.
- 5. ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- 6. AHEAD may be used instead of distances if necessary.
- 7. FI and MI. MILE and MILES interchanged as appropriate.
- 8. AT. BEFORE and PAST interchanged as needed. 9. Distances or AHEAD can be eliminated from the message if a

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC. THE FOUR DRUMS

SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.


## FULL MATRIX PCMS SIGNS

BLVD

CLOSED

- 1. When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- 2. When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above
- 3. When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- 4. A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

SHEET 6 OF 12



Traffic Safety


# BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)

BC(6)-21

ILE:	bc-21.dgn	DN: T	<dot< th=""><th colspan="2">CK: TXDOT DW</th><th colspan="2">DW: TxDC</th><th>ck: TxDOT</th></dot<>	CK: TXDOT DW		DW: TxDC		ck: TxDOT
C) TxDOT	November 2002	CONT	SECT	JOB			HWAY	
	REVISIONS RI	IC 064	67-	09-001		SH	36	, ETC.
9-07	8-14	DIST		COUNTY			SI	HEET NO.
7-13	5-21	YKM	AUSTIN, E			TC.		16


Ā 10:53:22

- 1. Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of pregualified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- 2. Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.



# CONCRETE TRAFFIC BARRIER (CTB)

- 3. Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- 4. Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- 5. When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- 6. Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- 7. Maximum spacing of Barrier Reflectors is forty (40) feet.
- 8. Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- 9. Attachment of Barrier Reflectors to CTB shall be per manufacturer's
- 10. Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer
- 11. Single slope barriers shall be delineated as shown on the above detail.




# LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES LPCB is approved for use in work

zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

Max. spacing of barrier reflectors is 20 feet. Attach the delineators as per manufacturer's recommendations.

# LOW PROFILE CONCRETE BARRIER (LPCB)




# DELINEATION OF END TREATMENTS

# END TREATMENTS FOR CTB'S USED IN WORK ZONES

End treatments used on CTB's in work zones shall meet the apppropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH), Refer to the CWZTCD List for approved end treatments and manufacturers.

# BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS

# Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.



Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

# WARNING LIGHTS

- 1. Warning lights shall meet the requirements of the TMUTCD.
- 2. Warning lights shall NOT be installed on barricades.
- 3. Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type  $B_{FL}$  or  $C_{FL}$  Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- 4. Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- 5. The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- 6. When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- 7. When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- 8. The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

# WARNING LIGHTS MOUNTED ON PLASTIC DRUMS

- 1. Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- 2. Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- 3. A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- 4. Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- 5. Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- 6. Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- 7. The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.


# WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- 1. A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- 2. The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed
- 3. The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- 4. Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- 5. Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- 6. The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- 7. When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- 8. The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- 9. The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- 1. The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.

  2. Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions
- or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- 4. The Flashing Arrow Board should be able to display the following symbols:



- 5. The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
   The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- 11. The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
  12. A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
  13. A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility,
- flash rate and dimming requirements on this sheet for the same size arrow.
- 14. Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

	REQUIREMENTS									
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE							
В	30 × 60	13	3/4 mile							
С	48 × 96	15	1 mile							

ATTENTION Flashing Arrow Boards shall be equipped with automatic dimmina devices.


WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

# FLASHING ARROW BOARDS

SHEET 7 OF 12

# TRUCK-MOUNTED ATTENUATORS

- 1. Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- 3. Refer to the CWZTCD for a list of approved TMAs.
- 4. TMAs are required on freeways unless otherwise noted in the plans. 5. A TMA should be used anytime that it can be positioned
- 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- 6. The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION ARROW PANEL. REFLECTORS. WARNING LIGHTS & ATTENUATOR

BC(7)-21

FILE:	bc-21.dgn		DN: T	<dot< td=""><td>ck: TxDOT</td><td>DW:</td><td>TxD0</td><td>T c</td><td>k: TxDO</td></dot<>	ck: TxDOT	DW:	TxD0	T c	k: TxDO
© TxD0T	November 2002		CONT	SECT	JOB			HIGH	VAY
9-07 7-13	REVISIONS	RI	IC 064	67-	09-001		SH	36,	ETC.
	8-14 5-21		DIST		COUNTY		SHEET NO.		
		YKM	Δ	UISTIN	FT	r		17	

# GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- 2. For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- 3. For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

## GENERAL DESIGN REQUIREMENTS

Pre-qualified plastic drums shall meet the following requirements:


- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- 4. Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- 5. The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- 6. The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- 7. Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- 8. Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- 9. Drum body shall have a maximum unballasted weight of 11 lbs.
- 10. Drum and base shall be marked with manufacturer's name and model number.


# RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials," Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.

## BALLAST

- 1. Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- 4. The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- 6. Ballast shall not be placed on top of drums.
- 7. Adhesives may be used to secure base of drums to pavement.





# DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- 4. Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign (Maximum Sign Dimension) Chevron CWI-8, Opposing Traffic Lane Divider, Driveway sign D70a, Keep Right R4 series or other signs as approved by Engineer

See Ballast



12" x 24"
Vertical Panel
mount with diagonals
sloping down towards
travel way

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- 2. Chevrons and other work zone signs with an orange background shall be manufactured with Type  $B_{FL}$  or Type  $C_{FL}$  Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- 4. Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- 7. Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12





Traffic Safety Division Standard

# BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(8)-21


FILE: bc-21.dgn	1	DN: T>	OOT	ck: TxDOT	DW:	TxDOT	ck: TxD0	TC
CTxDOT November 2002		CONT	SECT	JOB		н	SHWAY	
4-03 8-14	RM	IC 064	67-	09-001		SH 36	6, ETC	Ξ.
4-03 8-14 9-07 5-21		DIST		COUNTY		SHEET NO.		
7 17	Г	AKM	٨	IISTIN	FTC	•	1 2	П






- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- 2. VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- 3. VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- 4. VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base.
   See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.

# VERTICAL PANELS (VPs)



- 1. Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- 2. The OTLD may be used in combination with 42"
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- 4. The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type  $B_{FL}$  or Type  $C_{FL}$  conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.

# OPPOSING TRAFFIC LANE DIVIDERS (OTLD)



Fixed Base w/ Approved Adhesive (Driveable Base, or Flexible Support can be used)


36

- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- 3. Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- 4. To be effective, the chevron should be visible for at least 500 feet.
- 5. Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B<sub>FL</sub> or Type C<sub>FL</sub> conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

# **CHEVRONS**

# **GENERAL NOTES**

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- 3. Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- 4. The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- 6. Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- 7. The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.



# LONGITUDINAL CHANNELIZING DEVICES (LCD)

- 1. LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- 2. LCDs may be used instead of a line of cones or drums.
- 3. LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- 4. LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- 5. LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- 6. LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade roils as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

# WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- 4. Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

Posted Speed	Formula	D	esirab er Len *	le	Suggested Maximum Spacing of Channelizing Devices			
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	2	150′	1651	180′	30'	60′		
35	$L = \frac{WS^2}{60}$	2051	2251	2451	35′	70′		
40	60	265′	295′	320′	40′	80′		
45		450′	495′	540′	45′	90′		
50		5001	550′	6001	50′	100′		
55	L=WS	550′	6051	660′	55′	110′		
60	- 113	600'	660′	720′	60′	120′		
65		650′	715′	7801	65′	130′		
70		700′	770′	840'	70′	140'		
75		750′	8251	900′	75′	150′		
80		800′	880′	960′	80′	160′		

\*\*X\* Taper lengths have been rounded off, L=Length of Taper (FT.) W=Width of Offset (FT.) S=Posted Speed (MPH)

# SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



Traffic Safety Division Standard


# BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) -21


ILE:	bc-21.dgn	DN: T	×D0T	ck: TxDOT	DW:	TxDO	ТС	: TxDOT
C) TxDOT	November 2002	CONT	SECT	JOB			HIGHW	AY
		MC 064	67-	09-001		SH	36,	ETC.
9-07	8-14 5-21	DIST		COUNTY		SHEET NO.		
7-13		YKM	Α	USTIN.	FT	C.,		19

# DATE: 5/16/2024 10:53:19 AM

- TYPE 3 BARRICADES
- Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
- Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
- 3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
- 4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
- Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
- Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
- 7. Warning lights shall NOT be installed on barricades.
- 8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
- Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.




# TYPICAL STRIPING DETAIL FOR BARRICADE RAIL



Stiffener may be inside or outside of support, but no more than 2 stiffeners shall be allowed on one barricade.

# TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES



TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION

1. Where positive redirectional capability is provided, drums may be omitted. 2. Plastic construction fencing may be used with drums for safety as required in the plans. 3. Vertical Panels on flexible support may be substituted for drums when the Typical shoulder width is less than 4 feet. Plastic Drum 4. When the shoulder width is greater than 12 feet. steady-burn lights PERSPECTIVE VIEW may be omitted if drums are used. 5. Drums must extend the length These drums are not required of the culvert widening. on one-way roadway LEGEND Plastic drum Plastic drum with steady burn ligh of two drums s cross the work or yellow warning reflector Steady burn warning light or yellow warning reflector  $\Theta$ Increase number of plastic drums on the side of approaching traffic if the crown width makes it necessary. (minimum of 2 and maximum of 4 drums) PLAN VIEW

3"-4"

4" min. orange


2" min.

4" min. white


4" min. orange

4" min. white

Two-Piece cones




One-Piece cones



CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS

Tubular Marker



TRAFFIC CONTROL FOR MATERIAL STOCKPILES

28" Cones shall have a minimum weight of 9 1/2 lbs.

42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

- Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
- One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
- Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
- 4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
- 5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
- 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
- Cones or tubular markers used on each project should be of the same size and shape.





# BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

Traffic Safety Division Standard

# BC(10)-21

ILE:	bc-21.dgn	DN: T	<dot< th=""><th>ck: TxDOT</th><th>DW:</th><th>TxDC</th><th>)T (</th><th>k: TxDOT</th></dot<>	ck: TxDOT	DW:	TxDC	)T (	k: TxDOT
C) TxDOT	November 2002	CONT	SECT	JOB			HIGH	WAY
		VIC 064	67-	09-001		SH	36,	ETC.
9-07 8-14	•	DIST		COUNTY			SH	EET NO.
7-13	5-21	YKM	A	USTIN,	ET(	С.		20

# 10:53:

# WORK ZONE PAVEMENT MARKINGS

# **GENERAL**

- 1. The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- 2. Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- 3. Additional supplemental pavement marking details may be found in the plans or specifications.
- 4. Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- 5. When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- 6. When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing
- 7. All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

# RAISED PAVEMENT MARKERS

- 1. Raised pavement markers are to be placed according to the patterns
- 2. All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

## PREFABRICATED PAVEMENT MARKINGS

- 1. Removable prefabricated pavement markings shall meet the requirements
- 2. Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


## MAINTAINING WORK ZONE PAVEMENT MARKINGS

- 1. The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- 2. Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- 3. The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- 4. Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

## REMOVAL OF PAVEMENT MARKINGS

- 1. Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- 2. The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- 3. Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- 4. The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- 5. Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- 6. Blast cleaning may be used but will not be required unless specifically shown in the plans.
- 7. Over-painting of the markings SHALL NOT BE permitted.
- 8. Removal of raised pavement markers shall be as directed by the
- 9. Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS, " unless otherwise stated in the plans.
- 10. Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

# Temporary Flexible-Reflective Roadway Marker Tabs



STAPLES OR NAILS SHALL NOT BE USED TO SECURE TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER TABS TO THE PAVEMENT SURFACE

- 1. Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- 2. Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the
  - A. Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
  - B. Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- 3. Small design variances may be noted between tab manufacturers.
- 4. See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

# RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- 1. Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- 2. All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- 3. Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.
- Guidemarks shall be designated as: YELLOW - (two amber reflective surfaces with yellow body). WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIO	NS
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of preauglified reflective raised pavement markers. non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12




Traffic Safety


# BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS


BC(11)-21

FILE:	bc-21.dgn	DN: T	<dot< th=""><th>ck: TxDOT</th><th>DW:</th><th>TxDO</th><th>T C</th><th>k: TxDOT</th></dot<>	ck: TxDOT	DW:	TxDO	T C	k: TxDOT
© TxD0T	February 1998	CONT	SECT	JOB			HIGHW	/AΥ
2-00 0	REVISIONS RI -07 5-21	IC 064	67-	09-001		SH	36,	ETC.
-	13	DIST	COUNTY				SHEET NO.	
	14	YKM	ΑI	USTIN,	EΤ	c.		21

## PAVEMENT MARKING PATTERNS 10 to 12" Type II-A-A ₹> Yellow -Type Y buttons RAISED PAVEMENT MARKERS - PATTERN A REFLECTORIZED PAVEMENT MARKINGS - PATTERN A Type II-A-A <>> □وہ/ہ □ ہ ہ ہ اُ ہ ہ 4 to 8" Type Y Type II-A-Abuttons-REFLECTORIZED PAVEMENT MARKINGS - PATTERN B RAISED PAVEMENT MARKERS - PATTERN B Pattern A is the TXDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectorized pavement markings. CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE. TWO-WAY HIGHWAYS Type I-C Type W buttons--Type I-C or II-C-R Yellow Type I-A Type Y buttons | Type I-A | Type Y buttons ₹> Yellow White Type W buttons-└Type I-C or II-C-R REFLECTORIZED PAVEMENT MARKINGS RAISED PAVEMENT MARKERS Prefabricated markings may be substituted for reflectorized pavement markings. EDGE & LANE LINES FOR DIVIDED HIGHWAY Type I-C Type W buttons-0000 0000 White / Type II-A-A Type Y buttons ♦ $\langle \rangle$ Type W buttons-RAISED PAVEMENT MARKERS REFLECTORIZED PAVEMENT MARKINGS Prefabricated markings may be substituted for reflectorized pavement markings. LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS Type W buttons Type I-C-Type Y buttons-0 0 0 $\langle \rangle$ ₹> Type W buttons-└Type I-C REFLECTORIZED PAVEMENT MARKINGS RAISED PAVEMENT MARKERS Prefabricated markings may be substituted for reflectorized pavement markings. TWO-WAY LEFT TURN LANE







LEGEND											
	Type 3 Barricade		Channelizing Devices								
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)								
	Trailer Mounted Flashing Arrow Board	M	Portable Changeable Message Sign (PCMS)								
<b>þ</b>	Sign	♡	Traffic Flow								
$\Diamond$	Flag	ГO	Flagger								

									•
Speed	Formula	D	Minimum esirab er Leng **	le	Channelizing Devices		Minimum Sign Spacing "X"	Suggested Longitudinal Buffer Space	Stopping Sight Distance
×		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"B"	
30	2	150′	1651	180′	30′	60′	1201	90′	2001
35	L = WS <sup>2</sup>	2051	2251	245'	35′	70′	160′	120′	250′
40	80	265′	295′	3201	40'	80'	240'	155′	305′
45		450′	4951	540′	45′	90′	320′	195′	360′
50		5001	550′	600′	50'	100′	400′	240′	425′
55	L=WS	550′	605′	660′	55′	110′	500′	295′	495′
60	" " "	600′	660′	720′	60′	120′	600′	350′	570′
65		650′	715′	780′	65′	130′	700′	410′	645′
70		700′	770′	840′	70′	140′	8001	475′	730′
75		750′	8251	900'	75′	150'	900'	540'	820′

\* Conventional Roads Only

\*\* Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE LONG TERM TERM STATIONARY STATIONAR						
	1								

# GENERAL NOTES

- 1. Flags attached to signs where shown, are REQUIRED.
- 2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved
- 3. The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4 "ONE LANE ROAD XXX FT" sign, but proper sign spacing shall be maintained.
- Flaggers should use two-way radios or other methods of communication to control traffic.
- 5. Length of work space should be based on the ability of flaggers to communicate.
- 6. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- 7. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.

# TCP (2-2a)

- 8. The R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work space should be no longer than one half city block. In rural areas, roadways with less than 2000 ADT, work space should be no longer than 400 feet.
- 9. The R1-2aP "YIELD TO ONCOMING TRAFFIC" sign shall be placed on a support at a 7 foot minimum mounting height.

# TCP (2-2b)

- 10. Channelizing devices on the center line may be omitted when a pilot car is leading traffic and approved by the Engineer.
- 11.If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain stopping sight distance to the flagger and a queue of stopped vehicles.
- 12.Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situtations.




Traffic Operations Division Standard

TRAFFIC CONTROL PLAN ONE-LANE TWO-WAY TRAFFIC CONTROL

TCP (2-2) -18

FILE: tcp2-2-18.dgn	DN:		CK:	DW:		С	к:
© TxDOT December 1985	CONT	SECT	JOB			HIGHW	VAY
REVISIONS 8-95 3-03	RMC064	67-	09-001		SH	36,	ETC.
1-97 2-12	DIST		COUNTY	·	SHEET NO.		
4-98 2-18	YKM	Α	USTIN,	ET(	C.		23



	LEGEND										
~~~	Type 3 Barricade		Channelizing Devices								
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)								
<b>£</b>	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)								
-	Sign	♡	Traffic Flow								
$\Diamond$	Flag	Д	Flagger								

	$\wedge$	109				11099	-1	
Posted Speed *	Formulo	Tap	Desirable Taper Lengths X X			d Maximum ng of lizing ices On a Tangent	Minimum Sign Spacing "X" Distance	Suggested Longitudina। Buffer Space "B"
30		1 - 1 - 1	165	180'	Taper 30'	60'	120′	90'
35	L = WS	205	225′	245'	35′	70′	160'	120'
40	L = 60	2651	295′	3201	40′	80'	240'	155′
45		4501	4951	540'	45′	90′	320′	195′
50	1	5001	550′	6001	50′	100′	400'	240′
55	L=WS	550′	6051	660′	55′	110′	500'	295′
60	- " 3	600′	6601	720′	60′	120′	600'	350′
65		650′	715′	780′	65′	130′	700′	410′
70		700′	770′	840′	70′	140′	8001	475′
75		750′	8251	900′	75′	150′	900'	540′

- \* Conventional Roads Only
- \*\* Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY					
		<b>√</b>	<b>√</b>						

# GENERAL NOTES

- Flags attached to signs where shown, are REQUIRED.
   All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- 3. The downstream taper is optional. When used, it should be 100 feet minimum length per lane.
- 1. For short term applications, when post mounted signs are not used, the distance legend may be shown on the sign face rather than on a CW16-3aP supplemental plaque.
- 5. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- 5. Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.

# TCP (2-4a)

7. If this TCP is used for a left lane closure, CW20-5TL "LEFT LANE CLOSED" signs shall be used and channelizing devices shall be placed on the centerline to protect the work space from opposing traffic with the arrow board placed in the closed lane near the end of the merging taper.

# TCP (2-4b)

8. For shorter durations where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the speed in mph. This tighter devices spacing is intended for the area of conflicting markings, not the entire work zone.





Traffic Operations Division Standard

TRAFFIC CONTROL PLAN LANE CLOSURES ON MULTILANE CONVENTIONAL ROADS

TCP (2-4) -18

FILE: tcp2-4-18.dgn	DN:		CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB		HIGHWAY
8-95 3-03 REVISIONS	MC064	67-	09-001	SH	36, ETC.
1-97 2-12	DIST		COUNTY		SHEET NO.
4-98 2-18	YKM	A	USTIN,	ETC.	24





	LEGEND									
	Type 3 Barricade		Channelizing Devices							
□坤	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)							
<b>E</b>	Trailer Mounted Flashing Arrow Board	M	Portable Changeable Message Sign (PCMS)							
•	Sign	♡	Traffic Flow							
$\Diamond$	Flag	TO.	Flagger							
`										

Posted Speed	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x"	Suggested Longitudinal Buffer Space		
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"B"		
30	WS <sup>2</sup>	150′	1651	1801	30′	60′	1201	90′		
35	L = WS	2051	225′	245'	35′	70′	160′	120′		
40	80	265′	295′	3201	40′	80′	240'	155′		
45		4501	495′	540'	45′	90'	320′	195′		
50		5001	550′	6001	50′	100′	400′	240′		
55	L=WS	550′	6051	660′	55′	110'	500′	295′		
60	L 113	600′	660′	720′	60′	120'	600′	350′		
65		650′	715′	780′	65′	130′	700′	410′		
70		700′	770′	840′	70′	140′	800′	475′		
75		750′	8251	900′	75′	150′	900'	540′		

- \*\* Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY					
			1	1					

# GENERAL NOTES

- 1. Flags attached to signs where shown, are REQUIRED. 2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer
- Channelizing devices used to close lanes may be supplemented with the Chevron Alignment Sign placed on every other channelizing device. Chevrons may be attached to plastic drums as per BC Standards.
- Channelizing devices used along the work space or along tangent sections may be supplemented with vertical panels (VP) placed on everyother channelizing device. If night time conditions make it difficult to see at least two VPs, the VPs may be placed on each channelizing device.
- The placement of pavement markings may be omitted on Intermediate-term stationary work zones with the approval of the Engineer.
- Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. Shadow Vehicle with TMA and high intensity rotating, flashing, oscillating or strobe lights. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.


Texas Department of Transportation


TRAFFIC CONTROL PLAN LANE CLOSURES ON DIVIDED HIGHWAYS

Traffic Operations Division Standard

TCP(2-6)-18

RMC06467-09-001 SH 36, ETC 8-95 2-12 1-97 2-18 YKM AUSTIN, ETC.





	LEGEND									
~~~	Type 3 Barricade		Channelizing Devices							
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)							
	Trailer Mounted Flashing Arrow Board	M	Portable Changeable Message Sign (PCMS)							
-	Sign	♦	Traffic Flow							
$\Diamond$	Flag	ПО	Flagger							

Posted Speed	Formula	Minimum Desirable Taper Lengths "L" **			Suggested Maximum Spacing of Channelizing Devices		Suggested Longitudinal Buffer Space
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	"B"
45		450′	4951	540′	451	90′	1951
50		5001	550′	6001	50′	100'	240′
55	L=WS	550′	6051	660′	55′	110'	295′
60	- "3	600′	660′	720′	60′	120'	350′
65		650′	715′	780′	65′	130′	410′
70		700′	770′	840'	70′	140′	475′
75		750′	825′	9001	75′	150′	540′
80		8001	880′	9601	80′	160′	615′

\*\* Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY					
	1	1	1						

# **GENERAL NOTES**

- 1. All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
- 2. Drums or 42"cones are the typical channelizing devices. For Intermediate Term Stationary work, drums shall be used on tapers with drums or 42" cones used on tangent sections. Other channelizing devices may be used as directed by the Engineer.
- 3. All construction signs and barricades placed during any phase of work shall remain in place until removal is approved by the Engineer.
- 4. The Engineer may direct the Contractor to furnish additional signs and barricades as required to maintain traffic flow, detours and motorist safety during construction.
- 5. Static message boards or changeable message signs stating the date and duration of ramp or freeway lane closures shall be placed a minimum of seven (7) calendar days in advance of the actual closure.
- 6. Phase 2 of the PCMS message should include appropriate information formatted as shown on BC(6), such as "MERGE LEFT," recommended advisory speed, delay information, or other specific warnings.
- 7. Duplicate construction warning signs should be erected on the medians side of freeways where median width will permit and traffic volume justifies the signing.
- 8. The number of closed lanes may be increased provided the spacing of traffic control
- devices, taper lengths and tangent lengths meet the requirements of the TMUTCD. 9. Warning signs for intermediate term stationary work should be mounted at 7' to the bottom of the sign.
- 10. Warning signs shown shall be appropriately altered for left lane closures. When signs are mounted at 1' height for short term stationary or short duration work, sign versions shown in the SHSD for Texas with distances on the sign face rather than mounted on a plaque below the sign may be used.
- 11. When possible, PCMS units should be located in advance of the last available exit ramp prior to the lane closure to allow motorists an alternate route. They may also be relocated to improve advance warning in case of unanticipated queuing or congestion.
- 12.For Intermediate Term Stationary work at night, floodlights should be used to illuminate the work area and equipment crossings. Floodlights shall not produce a disabling glare condition for road users or workers.
- 13. The END ROAD WORK (G20-2) sign may be omitted when it conflicts with G20-2 signs already in place on the project.


A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.



# TRAFFIC CONTROL PLAN FREEWAY LANE CLOSURES

TCP(6-1)-12

FILE:	tcp6-1.dgn		DN: T>	OOT	ck: TxDOT	DW:	TxDO	TC	k: TxDOT
C TxD0T	February 1	998	CONT	SECT	JOB			HIGH	VAY
8-12	REVISIONS	RN	IC 064	67-	09-001		SH	36,	ETC.
8-12			DIST		COUNTY			SHI	EET NO.
			YKM	Α	USTIN,	ET(	С.		26



	LEGEND									
~~~	Type 3 Barricade	Channelizing Devices								
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)							
	Trailer Mounted Flashing Arrow Board	M	Portable Changeable Message Sign (PCMS)							
-	Sign	♡	Traffic Flow							
$\Diamond$	Flag	ПО	Flagger							

Posted Speed	Formula	Desirable S			Suggester Spacir Channe Dev	Suggested Longitudinal Buffer Space	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	"B"
45		450′	4951	540′	45′	90'	195′
50		5001	550′	600'	50′	100′	240′
55	L=WS	550′	605′	660′	55′	110′	295′
60	L-#3	600'	660′	720′	60′	120'	350′
65		650′	715′	780′	65′	130′	410′
70		700′	770′	840′	70′	140′	475′
75		750′	825′	900′	75′	150′	540′
80		800′	880′	960′	80'	160′	615'

\*\* Taper lengths have been rounded off.

L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE								
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY				
	1	✓	✓					

# GENERAL NOTES

- 1. All traffic control devices illustrated are REQUIRED. Devices denoted with the triangle symbol may be omitted when stated elsewhere in the plans.
- 2. ADDED LANE Symbol (CW4-3) sign may be omitted when sign
- between ramp and mainlane can be seen from both roadways.

  3. See "Advance Notice List" on BC(6) for recommended date
- and time formatting options for PCMS Phase 2 message.
  4. The END ROAD WORK (G20-2) sign may be omitted when it conflicts with G20-2 signs already in place on the project.

\*A shadow vehicle equipped with a Truck Mounted Attenuator is typically required. A shadow vehicle equipped with a TMA shall be used if it can be positioned 30' to 100' in advance of the area of crew exposure without adversely affecting the work performance.


Additional requirements for lane closures and advance signing shall be as shown on TCP (6-1) or as directed by the Engineer.



# TRAFFIC CONTROL PLAN WORK AREA NEAR RAMP


TCP (6-2) -12

C) TxDOT February 1994 CONT SECT JOB RMC 06467-09-001 SH 36, ETC 1-97 8-98 4-98 8-12 YKM AUSTIN, ETC.



RUMBLE STRIPS ON ONE-LANE

TWO-WAY APPLICATION



# **GENERAL NOTES**

- 1. Each Rumble Strip Array should consist of three rumble strips spaced center to center at the spacing shown in Table 2, placed transverse across the lane at locations shown.
- 2. The CW17-2T "RUMBLE STRIPS AHEAD" sign should be located after the CW20-1D "ROAD WORK AHEAD sign and spaced as shown. If traffic is observed to be queuing, or is expected to queue beyond the Rumble Strips, the CW17-2T sign and the first Rumble Strip Array may be located upstream of the CW20-1D sign as necessary to provide needed warning.
- 3. Temporary Rumble Strips will be considered subsidiary to Item 502, and shall be a product listed on the Compliant Work Zone Traffic Control
- 4. Remove Temporary Rumble Strips before removing the advanced warning signs.
- 5. Temporary Rumble Strips should not be used on horizontal curves, loose gravel, soft or bleeding asphalt, heavily rutted pavements or unpaved surfaces.
- 6. Temporary Rumble Strips shall be installed and maintained as per manufacturer's recommendations.
- 7. This standard sheet shall be used in conjunction with other appropriate TCP standard, TMUTCD typical application or project specific detail for the project.
- The one-lane two-way application may utilize a flagger, an Automated Flagger Assistance Device (AFAD) or a Portable Traffic Signal (PTS).
- 9. Replace defective Temporary Rumble Strips as directed by the Engineer.
- 10. Temporary Rumble Strips may be used on freeways or expressways based on engineering judgment and written direction from the Engineer.

	LEGEND									
	Type 3 Barricade		Channelizing Devices							
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)							
(E)	Trailer Mounted Flashing Arrow Panel	M	Portable Changeable Message Sign (PCMS)							
•	Sign	♦	Traffic Flow							
$\Diamond$	Flag	ПO	Flagger							

Speed	Formula	** Devices		Minimum Sign Spacing "x"	Suggested Longitudinal Buffer Space			
*		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent	Distance	"В"
30	ws <sup>2</sup>	150′	1651	180′	30′	60′	120'	90′
35	L = WS	2051	2251	2451	35′	701	160′	120′
40	80	265′	2951	3201	40′	80'	240'	155′
45		450′	495′	540'	45′	90′	320'	195′
50		500′	550′	600′	50′	100′	4001	240′
55	L=WS	550′	605′	660′	55′	110′	500′	295′
60	L - # 3	600'	660′	7201	60′	120′	600'	350′
65		6501	715′	7801	65′	130′	700′	410′
70		700′	770′	840′	70′	140′	800'	475′
75		750′	825′	900′	75′	150′	900′	540′

- \* Conventional Roads Only
- \*\* Taper lengths have been rounded off. L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed (MPH)

TYPICAL USAGE									
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY					
	✓	1							

- Signs are for illustrative purposes only. Signs required may vary depending on the TCP, TMUTCD Typical Application, or project specific details for the project.
- For posted speeds in excess of 65 MPH, it is recommended that spacing is increased as speed limits increase. Increasing space between rumble strips will improve effectiveness.

TABLE 2								
Speed	Approximate distance between strips in an array							
≤ 40 MPH	10′							
> 40 MPH & <u>&lt;</u> 55 MPH	15′							
= 60 MPH	20′							
<u>&gt;</u> 65 MPH	<b>*</b> 35′+							

Texas Department of Transportation


# TEMPORARY RUMBLE STRIPS

Traffic Safety Division Standard

WZ(RS) - 22

ILE:	wzrs22.dgn	DN: Tx	DOT	ck: TxDOT	DW:	TxDO	T	k: TxDOT
C) TxDOT	November 2012	CONT	SECT	JOB			HIGH	WAY
		MC064	67-	09-001		SH	36,	ETC.
2-14 4-16	1-22	DIST		COUNTY			SH	IEET NO.
4-16		YKM	Α	USTIN,	ΕT	C.		29





FOUR LANE DIVIDED ROADWAY CROSSOVERS

### **GENERAL NOTES**

 $\Diamond$ 

 $\triangleleft$ 

➪


♦

3. Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.

- 1. Edge line striping shall be as shown in the plans or as directed by the Engineer. The edge line should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement raveling or other conditions. Edge lines are not required in curb and gutter sections of roadways.
- 2. The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the center of edge line to the center of edge line of a two lane roadway.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



NOTE: Traveled way is exclusive of shoulder widths. Refer to General Note 2 for additional details.

# GUIDE FOR PLACEMENT OF STOP LINES. EDGE LINE & CENTERLINE

Based on Traveled Way and Pavement Widths for Undivided Roadways



# TYPICAL STANDARD PAVEMENT MARKINGS

Traffic Safety Division Standard

PM(1)-22

E: pm1-22.dgn	DN: CK:		CK:	DW:		CK:	
TxDOT December 2022	CONT	SECT	JOB		HIGHWAY		
REVISIONS R -78 8-00 6-20	MC064	67-	09-001		SH	36,	ETC.
-95 3-03 12-22	DIST		COUNTY			SH	EET NO.
-00 2-12	YKM	A	USTIN,	ETO	С.		30

Pavement

RIGHT LANE


Edge

10:53:28

NOTES

- 1. Lane reduction pavement markings are used where the number of through lanes is reduced because of narrowing of the roadway or because of a section of on-street parking in what would otherwise be a through lane. For Texas Super 2 Passing Lanes, see TS2(PL) standard sheets.
- 2. On divided highways, an additional RIGHT LANE ENDS (W9-1R) sign may be installed in the median aligned with the W9-1R sign on the right side of the highway.
- 3. Lane reduction arrows are required for speeds of 45 mph or greater. An optional third lane reduction arrow may be added based on engineering judgement. If used, the optional third lane reduction arrow should be centered between the first and last lane reduction arrows.
- 4. For lane reductions on Freeways and Expressways, signing shall conform to the TxDOT Freeway Signing Handbook.

ADVANCED WARNING SIGN DISTANCE (D)									
Posted Speed	D (ft)	L (f+)							
30 MPH	460	wc2							
35 MPH	565	$L = \frac{WS^2}{60}$							
40 MPH	670	00							
45 MPH	775								
50 MPH	885								
55 MPH	990								
60 MPH	1,100	L=WS							
65 MPH	1,200								
70 MPH	1,250								
75 MPH	1,350								



A two-way left-turn (TWLT) lane-use arrow pavement marking should be used at or just downstream from the beginning of a two-way left-turn lane within a corridor. Repeating the marking after each intersection or dedicated turn bay is not required unless stated elsewhere in the plans.


# TYPICAL TRANSITION FOR TWLTL AND DIVIDED HIGHWAY

# GENERAL NOTES


- 1. Lane use word and arrow markings shall be used where through lanes approaching an intersection become mandatory turn lanes. Lane use word and arrow markings should be used in auxiliary lanes of substantial length. Lane use arrow markings or word and arrow markings may be used in other lanes and turn bays for emphasis. Details for words and arrows are as shown in the Standard Highway Sign Designs for Texas.
- 2. When lane-use words and arrow markings are used, two sets of arrows should be used if the length of the bay is greater than 180 feet. When a single lane use arrow or word and arrow marking is used for a short turn lane, it should be located at or near the upstream end of the full-width turn lane.
- 3. Use raised pavement marker Type I-C with undivided highways, flush medians and two way left turn Use raised pavement marker Type II-C-R with divided highways and raised medians.
- 4. Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer. See Chapter 3 of the Roadway Design Manual for additional information on turning lanes or storage lengths.

MATERIAL SPECIFICATIONS								
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200							
EPOXY AND ADHESIVES	DMS-6100							
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130							
TRAFFIC PAINT	DMS-8200							
HOT APPLIED THERMOPLASTIC	DMS-8220							
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240							

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




# TYPICAL TWO-LANE ROADWAY INTERSECTION WITH LEFT TURN BAYS






# 'WO-WAY LEFT TURN LANES. RURAL LEFT TURN BAYS. AND LANE REDUCTION PAVEMENT MARKINGS PM(3) - 22

I	FILE: pm3-22.dgn	DN:		CK:	DW:		СК	:
I	© TxDOT December 2022	CONT	SECT	JOB			HIGHW	AY
I	REVISIONS RI 4-98 3-03 6-20	MC064	67-	09-001		SH	36,	ETC.
ı	5-00 2-10 12-22	DIST		COUNTY			SHE	ET NO.
1	8-00 2-12	YKM	Α	USTIN,	ETC	С.		31





TYPICAL TWLTL AT TWO-WAY CROSS STREET AND RIGHT TURN LANE DROP

6" Dotted White

D/2

8

Lane-Reduction

LANE REDUCTION

-8" Dotted White Lane Line

≤ 1 Mile (Auxiliary Lane)

Arrow

D/4

Lane Line

D/4

MERGE

Varies (See general Note 2:

텋

SEE DETAIL B

W9-2TL

Paved Shoulder

300' -500

(Optional)