

FED. RD. DIV. NO.	FEDERAL PROJECT NO.	SHEET NO.	
6	STP 2B24(237)VRUG	1	
STATE	STATE DIST.	COUNTY	
TEXAS	AMA	POTTER	
CONT.	SECT.	JOB	HIGHWAY NO.
0904	00	214	VARIOUS

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	INDEX OF SHEETS

**STATE OF TEXAS
DEPARTMENT OF TRANSPORTATION**

**PLANS OF PROPOSED
STATE HIGHWAY IMPROVEMENT
FEDERAL PROJECT: STP 2B24(237)VRUG
HIGHWAY - VARIOUS
POTTER COUNTY
CONTROL: 0904-00-214**

FINAL PLANS

FOR THE CONSTRUCTION OF IMPROVE TRAFFIC SIGNALS, INSTALL FLASHING YELLOW ARROW -
(45TH AVE AT VIRGINIA, ARTHUR ST. AT 10TH AVE, BELL ST. AT PLAINS AVE, GEORGIA ST. AT 58TH
AVE, GEORGIA ST AT WOLFLIN AVE & ROSS ST. AT 10TH AVE)

PROJECT LIMITS: VARIOUS
NET LENGTH = 0.001 FT. = 0.001 MILES

LETTING DATE: _____
DATE CONTRACTOR BEGAN WORK: _____
DATE WORK WAS COMPLETED & ACCEPTED: _____
FINAL CONTRACT COST: _____
CONTRACTOR : _____
AREA ENGINEER: _____ DATE: _____

- PROJECT LOCATIONS
- BELL AND PLAINS
 - ARTHUR AND SE 10TH
 - ROSS AND 10TH
 - GEORGIA AND WOLFLIN
 - VIRGINIA AND SW 45TH
 - GEORGIA AND SW 58TH



SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT: REQUIRED CONTRACT PROVISIONS FOR ALL FEDERAL-AID CONSTRUCTION CONTRACTS (FORM FHWA 1273, OCTOBER 23, 2023).

EXCEPTIONS:
NONE

RAILROADS:
NONE

EQUATIONS:
NONE



RECOMMENDED FOR LETTING: 2/29/2024 DATE:

DocuSigned by:
Brandon Billney
5A5732BEFD11410...
AREA ENGINEER

DATE:
3/1/2024

DocuSigned by:
Kit Black
9B5A6EA6AE8B46E...
DISTRICT DIRECTOR OF TRANSPORTATION
PLANNING AND DEVELOPMENT


APPROVED FOR LETTING: 3/1/2024 DATE:

DocuSigned by:
Blair Johnson
8B80E3AEB2BC43A...
DISTRICT ENGINEER

INDEX OF SHEETS

<u>SHEET NO.</u>	<u>DESCRIPTION</u>
	<u>GENERAL</u>
1	TITLE SHEET
2	INDEX OF SHEETS
3-3A	GENERAL NOTES
4	ESTIMATE & QUANTITY
5	SUMMARY OF QUANTITIES
	<u>TRAFFIC CONTROL PLAN</u>
6	TRAFFIC CONTROL PLAN
	<u>TRAFFIC CONTROL PLAN STANDARDS</u>
7-18	BC(1)-21 THRU BC(12)-21
19-22	TCP(1-1)-18 THRU TCP(1-4)-18
23	TCP(2-4)-18
24	TCP(2-5)-18
25	TCP(3-1)-13
26-27	WZ(BTS-1)-13 THRU WZ(BTS-2)-13
28	WZ(RS)-22
	<u>TRAFFIC ITEMS</u>
29	BELL AT PLAINS EXISTING SIGNAL LAYOUT
30	BELL AT PLAINS PROPOSED SIGNAL LAYOUT
31	BELL AT PLAINS PROPOSED SIGNAL WIRING
32	BELL AT PLAINS PROPOSED TRAFFIC SIGNAL DETAILS
33	BELL AT PLAINS SUMMARY OF QUANTITIES
34	ROSS AT 10TH EXISTING SIGNAL LAYOUT
35	ROSS AT 10TH PROPOSED SIGNAL LAYOUT
36	ROSS AT 10TH PROPOSED SIGNAL WIRING
37	ROSS AT 10TH PROPOSED TRAFFIC SIGNAL DETAILS
38	ROSS AT 10TH AVE SUMMARY OF QUANTITIES
39	ARTHUR AT 10TH EXISTING SIGNAL LAYOUT
40	ARTHUR AT 10TH PROPOSED SIGNAL LAYOUT
41	ARTHUR AT 10TH PROPOSED SIGNAL WIRING
42	ARTHUR AT 10TH PROPOSED TRAFFIC SIGNAL DETAILS
43	ARTHUR AT 10TH SUMMARY OF QUANTITIES
44	GEORGIA AT WOLFLIN EXISTING SIGNAL LAYOUT
45	GEORGIA AT WOLFLIN PROPOSED SIGNAL LAYOUT
46	GEORGIA AT WOLFLIN PROPOSED SIGNAL WIRING
47	GEORGIA AT WOLFLIN PROPOSED TRAFFIC SIGNAL DETAILS
48	GEORGIA AT WOLFLIN AVE SUMMARY OF QUANTITIES
49	GEORGIA AT 58TH EXISTING SIGNAL LAYOUT
50	GEORGIA AT 58TH PROPOSED SIGNAL LAYOUT
51	GEORGIA AT 58TH PROPOSED SIGNAL WIRING
52	GEORGIA AT 58TH PROPOSED TRAFFIC SIGNAL DETAILS
53	GEORGIA AT 58TH SUMMARY OF QUANTITIES
54	VIRGNIA AT 45TH EXISTING SIGNAL LAYOUT
55	VIRGNIA AT 45TH PROPOSED SIGNAL LAYOUT
56	VIRGNIA AT 45TH PROPOSED SIGNAL WIRING
57	VIRGNIA AT 45TH PROPOSED TRAFFIC SIGNAL DETAILS
58	VIRGNIA AT 45TH SUMMARY OF QUANTITIES
	<u>TRAFFIC STANDARD DETAILS</u>
59-60	TSR(3)-13 THRU TSR(4)-13
61	ED(1)-14
62-67	ED(3)-14 THRU ED(8)-14
68	ED(11)-14
69	TS-BP-20
	<u>ENVIRONMENTAL ISSUES</u>
70-71	(SW3P)
72	E.P. I.C.
	<u>ENVIRONMENTAL ISSUES STANDARDS</u>
73-75	EC(9)-16

THE STANDARD SHEETS SPECIFICALLY IDENTIFIED ABOVE HAVE BEEN SELECTED BY ME OR UNDER MY RESPONSIBLE SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.



Dawood Alani
2/9/2024

VARIOUS LOCATIONS

INDEX OF SHEETS

Texas Department of Transportation

SHEET 1 OF 1



DSN	EX	CONT	SECT	JOB	ISSUE
MP	DA	0904	00	214	VARIOUS
DRWN	EX	DEPT	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	2	

DATE: 2/9/2024
FILE: STMS

GENERAL NOTES

General

Contractor questions on this project are to be addressed to the following individual(s):

TO: Traffic Engineer	Bernardo.Ferrel@txdot.gov
CC: Transportation Specialist	Kevin.Wilcox@txdot.gov
Director of Construction	Wes.Kimmell@txdot.gov
Construction Manager	Darrell.Caldwell@txdot.gov

Contractor questions will be accepted through email, phone, or in person by the above individuals.

For Q&A's on Proposals navigate to:

<https://tableau.txdot.gov/views/ProjectInformationDashboard/NoticetoContractors>

Use the dashboard to navigate to the project you are interested in by scrolling or filtering the dashboard using the controls on the left. Hover over the blue hyperlink of the project you want to view the Q&A for and click on the link in the window that pops up.

All relevant project documentation including CTD will be posted to TxDOT District's FTP website.

<https://ftp.dot.state.tx.us/pub/txdot-info/Pre-Letting%20Responses/>

There are no "reference markers" within the project limits.

If Contractor damages any sprinkler heads, risers or water lines that are not to be relocated, he or she is required to replace or repair all damage at his or her own expense and to the Engineer's satisfaction.

Item 6 Control of Materials

To comply with the latest provisions of Build America, Buy America Act (BABA Act) of the Bipartisan Infrastructure Law, the contractor must submit an original of the TxDOT Construction Material Buy America Certification Form for all items classified as construction materials. This form is not required for materials classified as a manufactured product.

Refer to the Buy America Material Classification Sheet for clarification on material categorization.

The Buy America Material Classification Sheet is located at the below link.

<https://www.txdot.gov/business/resources/materials/buy-america-material-classification-sheet.html> for clarification on material categorization.

Item 7 Legal Relations and Responsibilities

No significant traffic generator events identified.

The total area disturbed for this project is approximately 0.015 acres. The disturbed area in this project, all project locations in the Contract, and the Contractor Project Specific Locations (PSLs), within 1 mile of the project limits, for the Contract will further establish the authorization requirements for storm water discharges. The Department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans. The Contractor is to obtain required authorization from the TCEQ for Contractor PSLs for construction support activities on or off the ROW. When the total area disturbed in the Contract and PSLs within 1 mile of the project limits exceeds 5 acres, provide a copy of the Contractor NOI for PSLs on the ROW to the Engineer and to the local government that operates a separate storm sewer system.

Item 8 Prosecution and Progress

The 90 days convenience delay special provision is intended to provide lead time to acquire required construction materials for traffic elements.

Item 502 Barricades, Signs, and Traffic Handling

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

Temporary rumble strips will be required as shown on WZ(RS)-22 regardless of loose gravel, and/or soft or bleeding asphalt. Adjust the traffic control setup such that rumble strips are not placed in areas of heavily rutted pavements, unpaved surfaces, or horizontal curves. Temporary rumble strips will not be allowed on interstate highway.

The Contractor is to have the option of using either plastic drums, vertical panels, grabber cones or a combination where drums are shown as channelizing devices, as approved by the Engineer. Plastic drums are to be used in all transition areas in accordance with BC(8)-21.

Notify the Engineer 24 hours prior to any lane closure.

Any work being done above travel lanes will require the lanes to be closed for traffic safety.

Item 506 Temporary Erosion, Sedimentation, and Environmental Controls

Erosion control devices are to be installed as needed in coordination with the work progress, or as directed by the Engineer.

Highway: VARIOUS

Control: 0904-00-214

Item 618 Conduit

The locations of conduit as shown are for diagrammatic purposed only and may be varied to meet local conditions, subject to approval. Backfill all open trenches before the end of the workday and do not leave any trench open overnight.

Item 620 Electrical Conductors

Provide breakaway electrical connectors for breakaway poles. Use Bussman HEBW, Littlefuse LEB, Ferraz-Shawmut FEB, or equal on ungrounded conductors. For grounded conductors, use Bussman HET, Littlefuse LET, Ferraz-Shawmut FEBN, or equal. These breakaway connectors have a white colored marking and a permanently installed solid neutral. See the latest RID (2) standard for additional details.

Item 624 Ground Boxes

Do not place ground boxes in driveways or wheelchair ramps. Alternate ground box locations will be as directed.

Item 680 Highway Traffic Signals

Furnish and install all required materials, incidentals and equipment necessary for a fully operational traffic signal. The proposed equipment is to be compatible with the existing traffic control systems in use by the local traffic signal operating and maintaining agency. Refer to TxDOT's Website for prequalified products list regarding cameras, vehicle LED traffic signal lamp unit, symbolic pedestrian signal head, symbolic pedestrian signal lamp, conduit, conductors, ground boxes and electric service. Check website periodically for current updates.

Furnish and install illumination fixtures mounted on Traffic Signal Pole luminaire arms. Use 250W equivalent LED luminaires.

Regulatory and street name signs shown to be mounted on the mast arms will be furnished and installed by the Contractor. All brackets and miscellaneous material will be furnished by the Contractor.

The Contractor will be responsible for adjustments in project construction which may be needed because of conflicts with utilities. In addition to calling Texas811 at all locations shown on the plans, contact the Amarillo District Headquarters signal shop at least 2 weeks in advance of work at the proposed locations. A representative from the signal shop will verify that no existing TxDOT electrical systems will interfere with the proposed work.

If overhead or underground power lines need to be de-energized, contact the electrical service provider to perform this work. Cost associated with de-energizing the power lines or other protective measures required will be at no expense to the Department. If working near power lines, comply with the appropriate sections of Texas state law and federal regulations relating to the type of work involved.

Once the integrity and /or function of an existing traffic signal(s) are altered by the Contractor, maintain and operate the existing traffic signal(s) until the traffic signal work is accepted by the department. Pursue the work at that location without delay or interruption to restore operation to its original or final operational design.

When work requires the removal of power from the controller and cabinet assembly, erect temporary stop signs. Remove the stop signs after the traffic signals are in operation.

The Contractor will not put signals in operation. Authorized TxDOT personnel must be onsite for controller start up.

Removing Traffic Signals - TxDOT will determine if signal components are designated for reuse. Other traffic signal materials salvaged from this project will become the property of the Contractor. Remove these salvaged materials from the project and dispose of in accordance with all applicable State and Local laws and regulations.

Item 682 Vehicle and Pedestrian Signal Heads

Cover new signal heads so that the faces cannot be seen from the time of installation until the signal are placed in operation. Trash bags, paper, etc. will not be acceptable for use in covering signal heads. Signal head covers will be made of burlap or other out-door fabric which will be weather resistant as approved by the Engineer.

Signal heads are to be installed level and plumb and aimed as directed.

Item 684 Traffic Signal Cables

For each traffic signal installation where signal cable is required, provide a minimum length of 5 feet for each conductor terminating in the controller.

Label all traffic signal cables, vehicle detector cables, and pedestrian signal cables terminating in the controller with marker ties and permanent markers.

Item 6083 Video Imaging and Radar Vehicle Detection System

Mount detector as shown in plans or as directed by the engineer. Adjust heights and locations of sensors to achieve the best possible detection. Provide a factory certified representative for testing and set up of the equipment at the time of signal flash and turn on. Furnish and install communication system (Edge Connect or equal as approved by the Engineer) to provide video communication back to the City of Amarillo.

Item 6185 Truck Mounted Attenuator (TMA) and Trailer Attenuator (TA)

In addition to the shadow vehicles with truck mounted attenuator (TMA) that are specified as being required on the traffic control plan for this project, provide 0 additional shadow vehicle(s) with TMA for TCP (1-1)-18, (1-2)-18, (1-3)-18, (1-4)-18, (2-4)-18, (2-5)-18, (3-1)-13 as detailed on the General Notes of this standard sheets.

Therefore, 2 total shadow vehicles with TMA will be required for this type of work. The Contractor will be responsible for determining if one or more of these operations will be ongoing at the same time to determine the total number of TMAs needed for the project.



Estimate & Quantity Sheet

CONTROLLING PROJECT ID 0904-00-214

DISTRICT Amarillo

COUNTY Potter

HIGHWAY Various

CONTROL SECTION JOB				0904-00-214		TOTAL EST.	TOTAL FINAL
PROJECT ID				A00176821			
COUNTY				Potter			
HIGHWAY				Various			
ALT	BID CODE	DESCRIPTION	UNIT	EST.	FINAL		
	500-6001	MOBILIZATION	LS	1.000		1.000	
	502-6001	BARRICADES, SIGNS AND TRAFFIC HANDLING	MO	4.000		4.000	
	620-6007	ELEC CONDR (NO.8) BARE	LF	2,770.000		2,770.000	
	620-6009	ELEC CONDR (NO.6) BARE	LF	385.000		385.000	
	620-6010	ELEC CONDR (NO.6) INSULATED	LF	770.000		770.000	
	680-6003	INSTALL HWY TRF SIG (SYSTEM)	EA	6.000		6.000	
	680-6004	REMOVING TRAFFIC SIGNALS	EA	6.000		6.000	
	682-6002	VEH SIG SEC (12")LED(GRN ARW)	EA	22.000		22.000	
	682-6004	VEH SIG SEC (12")LED(YEL ARW)	EA	44.000		44.000	
	682-6006	VEH SIG SEC (12")LED(RED ARW)	EA	22.000		22.000	
	682-6018	PED SIG SEC (LED)(COUNTDOWN)	EA	44.000		44.000	
	682-6055	BACKPLATE W/REF BRDR(4 SEC)(VENT)ALUM	EA	22.000		22.000	
	684-6031	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	LF	720.000		720.000	
	684-6033	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	LF	1,520.000		1,520.000	
	684-6046	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	LF	3,480.000		3,480.000	
	684-6080	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)	LF	480.000		480.000	
	688-6002	PED DETECT PUSH BUTTON (STANDARD)	EA	48.000		48.000	
	6083-6002	VID IMAGE AND RADAR DET PROCESSOR SYS	EA	6.000		6.000	
	6083-6003	VIDEO IMAGING AND RADAR DETECTOR	EA	24.000		24.000	
	6083-6004	VIDEO IMAGING AND RADAR SET-UP SYS	EA	6.000		6.000	
	6083-6005	VID IMAGE AND RADAR COM CABLE (COAX)	LF	5,090.000		5,090.000	
	6185-6002	TMA (STATIONARY)	DAY	51.000		51.000	
	18	SAFETY CONTINGENCY: CONTRACTOR FORCE ACCOUNT WORK (PARTICIPATING)	LS	1.000		1.000	
		EROSION CONTROL MAINTENANCE: CONTRACTOR FORCE ACCOUNT WORK (PART)	LS	1.000		1.000	

SUMMARY OF TRAFFIC SIGNAL QUANTITIES

ITEM	DESC CODE	DESCRIPTION	UNIT	BELL ST. AT PLAINS AVE QTY	ROSS ST. AT 10TH AVE QTY	ARTHUR ST. AT 10TH AVE QTY	GEORGIA ST. AT WOLFLIN AVE QTY	GEORGIA ST AT 58TH AVE QTY	45TH AVE AT VIRGINIA ST. QTY	PROJECT TOTAL
620	6007	ELEC CONTR (NO 8) BARE	LF	350	405	300	525	340	850	2770
620	6009	ELEC CONDR (NO 6) BARE	LF	85	55	125	30	45	45	385
620	6010	ELEC CONDR (NO 6) INSULATED	LF	170	110	250	60	90	90	770
680	6003	INSTALL HWY TRF SIG SYSTEM	EA	1	1	1	1	1	1	6
	*	TS-2 TYPE 2 CABINET (PROVIDED AND INSTALLED BY CONTRACTOR)	EA	1	1	1	1	1	1	6
	*	CABINET FOUNDATION (EXISTING TO BE REUSED)	EA	1	1	1	1	1	1	6
	*	CONTROLLER (EXISTING TO BE REUSED)	EA	1	1	1	1	1	1	6
	*	LEFT TURN YEILD ON FLASHING YELLOW ARROW SIGN R10-17 30"X30"	EA	4	4	4	2	4	4	22
	*	PEDESTRIAN SIGNS R10-3e	EA	8	8	8	8	8	8	48
680	6004	REMOVING TRAFFIC SIGNALS	EA	1	1	1	1	1	1	6
682	6002	VEH SIG SEC (12")LED(GRN ARW)	EA	4	4	4	2	4	4	22
682	6004	VEH SIG SEC (12")LED(YEL ARW)	EA	8	8	8	4	8	8	44
682	6006	VEH SIG SEC (12")LED(RED ARW)	EA	4	4	4	2	4	4	22
682	6018	PED SIG SEC (LED)(COUNTDOWN)	EA	8	8	8	4	8	8	44
682	6055	BACKPLATE W/REF BRDR(4 SEC)(VENT)ALUM	EA	4	4	4	2	4	4	22
684	6080	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)	LF	80	80	80	80	80	80	480
684	6031	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	LF	120	120	120	120	120	120	720
684	6033	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	LF	280	280	280	140	260	280	1520
684	6046	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	LF	545	405	425	525	730	850	3480
688	6002	PED DETECT PUSH BUTTON (STANDARD)	EA	8	8	8	8	8	8	48
6083	6002	VID IMAGE AND RADAR DET PROCESSOR SYS	EA	1	1	1	1	1	1	6
6083	6003	VIDEO IMAGING AND RADAR DETECTOR	EA	4	4	4	4	4	4	24
6083	6004	VIDEO IMAGING AND RADAR SET-UP SYS	EA	1	1	1	1	1	1	6
6083	6005	VID IMAGE AND RADAR COM CABLE (COAX)	LF	825	675	695	785	990	1120	5090

* SUBSIDIARY TO ITEM 680 6003, INSTALL HWY TRF SIG(SYSTEM) (FOR CONTRACTOR'S INFORMATION ONLY)

VARIOUS LOCATIONS


SUMMARY OF QUANTITIES

DATE: 04/25/2024
FILE: 090400




SHEET 1 OF 1


CONTRACT NO.	SECTION	SHEET NO.	TOTAL SHEETS	DATE	PROJECT NAME
MP DA 090400		214			VARIOUS
MP DA AMA		POTTER			5




AMARILLO




AMARILLO




AMARILLO






AMARILLO




AMARILLO



AMARILLO



VARIOUS LOCATIONS



- INTERSECTION
- ① BELL ST. AT PLAINS AVE
- ② ROSS ST. AT 10TH AVE
- ③ ARTHUR ST. AT 10TH AVE
- ④ GEORGIA ST. AT WOLFLIN AVE
- ⑤ GEORGIA ST. AT 58TH AVD
- ⑥ 45TH AVE AT VIRGINIA ST

DAW
02/14/2024
TRAFFIC CONTROL PLAN

SCALE: N. T. S.



SHEET 1 OF 1

DSK	EX	ENV	SEC	DOB	PROPERTY
MP	MP	0904	00	213	VARIOUS
OPN	CK	DET	COUNTY	SHEET NO.	
MP	MP	ANA	POTTER	6	

DATE: 02/14/2024
FILE: 021424

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

1. The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
11. Traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY NOTES:


1. Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
2. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES

1. Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
2. Work zone traffic control devices shall be compliant with the Manual for Assessing safety Hardware (MASH).


<p>THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT http://www.txdot.gov</p>
COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12

 Texas Department of Transportation		<i>Traffic Safety Division Standard</i>	
<p>BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS</p> <p>BC (1) - 21</p>			
FILE:	bc-21.dgn	DN:	TxDOT
© TxDOT	November 2002	CK:	TxDOT
		DW:	TxDOT
		CK:	TxDOT
		CONT	SECT
		0904	00
		JOB	HIGHWAY
		214	VARIOUS
		DIST	COUNTY
		AMA	POTTER
		SHEET NO.	7
		REVISIONS	
4-03	7-13		
9-07	8-14		
5-10	5-21		


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPICAL LOCATION OF CROSSROAD SIGNS



- # May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)
- The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
 - The Engineer may use the reduced size 36" x 36" ROAD WORK AHEAD (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "ROAD WORK NEXT X MILES" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
 - Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
 - The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
 - Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
 - When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

T-INTERSECTION



CSJ LIMITS AT T-INTERSECTION

- The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
- If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC(10) also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING^{1,5,6}


Sign Number or Series	SIZE		SPACING	
	Conventional Road	Expressway/Freeway	Posted Speed MPH	Sign* Spacing "x" Feet (Apprx.)
CW20 ⁴	48" x 48"	48" x 48"	30	120
CW21			35	160
CW22			40	240
CW23			45	320
CW25	36" x 36"	48" x 48"	50	400
CW1, CW2, CW7, CW8, CW9, CW11, CW14			55	500 ²
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12			60	600 ²
			65	700 ²
			70	800 ²
	75	900 ²		
	80	1000 ²		
	*	*	*	* ³

- * For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.
- * Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES


- Special or larger size signs may be used as necessary.
- Distance between signs should be increased as required to have 1500 feet advance warning.
- Distance between signs should be increased as required to have 1/2 mile or more advance warning.
- 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
- Only diamond shaped warning sign sizes are indicated.
- See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS



When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.


SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS



NOTES

- The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "x" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
- The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.
- CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.
- Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.
- Contractor will install a regulatory speed limit sign at the end of the work zone.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS



LEGEND

—	Type 3 Barricade
○ ○ ○	Channelizing Devices
■	Sign
x	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.

SHEET 2 OF 12

Texas Department of Transportation Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC (2) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904	00	214	VARIOUS
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	AMA	POTTER	8	

DATE: FILE:

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project. Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- rough road or damaged pavement surface
- substantial alteration of roadway geometrics (diversions)
- construction detours
- grade
- width
- other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).

GENERAL NOTES

- Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
- Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
- Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
- Frequency of work zone speed limit signs should be:

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
- Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
- Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
- Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
- Techniques that may help reduce traffic speeds include but are not limited to:
 - Law enforcement.
 - Flagger stationed next to sign.
 - Portable changeable message sign (PCMS).
 - Low-power (drone) radar transmitter.
 - Speed monitor trailers or signs.
- Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
- For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

SHEET 3 OF 12




BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT

BC (3) - 21

FILE:	bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS		0904	00	214	VARIOUS
9-07	8-14	DIST	COUNTY	SHEET NO.	
7-13	5-21	AMA	POTTER	9	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.

** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS



Nails shall NOT be allowed.
Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.

Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - Long-term stationary - work that occupies a location more than 3 days.
 - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - Short, duration - work that occupies a location up to 1 hour.
 - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be affixed to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS


- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

STOP/SLOW PADDLES

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflective when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6" to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.





BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC (4) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CR: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904 00		214	VARIOUS
9-07 8-14	DIST	COUNTY		SHEET NO.
7-13 5-21	AMA	POTTER		10

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.





SKID MOUNTED WOOD SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS



GROUND MOUNTED SIGN SUPPORTS

Refer to the CWZTCD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS

* LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS

WEDGE ANCHORS

Both steel and plastic Wedge Anchor Systems as shown on the SMD Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soils if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(1)).

OTHER DESIGNS

MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CWZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION.

GENERAL NOTES

1. Nails may be used in the assembly of wooden sign supports, but 3/8" bolts with nuts or 3/8" x 3 1/2" log screws must be used on every joint for final connection.
2. No more than 2 sign posts shall be placed within a 7 ft. circle, except for specific materials noted on the CWZTCD List.
3. When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered subsidiary to Item 502.

- * See BC(4) for definition of "Work Duration."
- ** Wood sign posts MUST be one piece. Splicing will NOT be allowed. Posts shall be painted white.
- ☐ See the CWZTCD for the type of sign substrate that can be used for each approved sign support.

SHEET 5 OF 12



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

BC(5) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0904	00	214	VARIOUS				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	AMA	POTTER	11					

DATE:
FILE:

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the T MUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act." No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT
RIGHT X LANES CLOSED	RIGHT X LANES OPEN
CENTER LANE CLOSED	DAYTIME LANE CLOSURES
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE
EXIT CLOSED	RIGHT LN TO BE CLOSED
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI
XXXXXXXX BLVD CLOSED	

Other Condition List

ROADWORK XXX FT	ROAD REPAIRS XXXX FT
FLAGGER XXXX FT	LANE NARROWS XXXX FT
RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
DETOUR X MILE	ROUGH ROAD XXXX FT
ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
BUMP XXXX FT	US XXX EXIT X MILES
TRAFFIC SIGNAL XXXX FT	LANES SHIFT *

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List

MERGE RIGHT	FORM X LINES RIGHT
DETOUR NEXT X EXITS	USE XXXXX RD EXIT
USE EXIT XXX	USE EXIT I-XX NORTH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N
TRUCKS USE US XXX N	WATCH FOR TRUCKS
WATCH FOR TRUCKS	EXPECT DELAYS
EXPECT DELAYS	PREPARE TO STOP
REDUCE SPEED XXX FT	END SHOULDER USE
USE OTHER ROUTES	WATCH FOR WORKERS
STAY IN LANE *	

Location List

AT FM XXXX
BEFORE RAILROAD CROSSING
NEXT X MILES
PAST US XXX EXIT
XXXXXXXX TO XXXXXXX
US XXX TO FM XXXX

Warning List

SPEED LIMIT XX MPH
MAXIMUM SPEED XX MPH
MINIMUM SPEED XX MPH
ADVISORY SPEED XX MPH
RIGHT LANE EXIT
USE CAUTION
DRIVE SAFELY
DRIVE WITH CARE

** Advance Notice List

TUE-FRI XX AM-X PM
APR XX-XX X PM-X AM
BEGINS MONDAY
BEGINS MAY XX
MAY X-X XX PM - XX AM
NEXT FRI-SUN
XX AM TO XX PM
NEXT TUE AUG XX
TONIGHT XX PM-XX AM

** See Application Guidelines Note 6.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Canal	CANT	North	N
Center	CTR	Northbound	(route) N
Construction Ahead	CONST AHD	Parking	PKING
CROSSING	XING	Road	RD
Detour Route	DETOUR RTE	Right Lane	RT LN
Do Not	DONT	Saturday	SAT
East	E	Service Road	SERV RD
Eastbound	(route) E	Shoulder	SHLDR
Emergency	EMER	Slippery	SLIP
Emergency Vehicle	EMER VEH	South	S
Entrance, Enter	ENT	Southbound	(route) S
Express Lane	EXP LN	Speed	SPD
Expressway	EXPWY	Street	ST
XXXX Feet	XXXX FT	Sunday	SUN
Fog Ahead	FOG AHD	Telephone	PHONE
Freeway	FRWY, FWY	Temporary	TEMP
Freeway Blocked	FWY BLKD	Thursday	THURS
Friday	FRI	To Downtown	TO DWNTN
Hazardous Driving	HAZ DRIVING	Traffic	TRAF
Hazardous Material	HAZMAT	Travelers	TRVLR
High Occupancy Vehicle	HOV	Tuesday	TUES
Hour(s)	HR, HRS	Time Minutes	TIME MIN
Information	INFO	Upper Level	UPR LEVEL
It Is	ITS	Vehicles (s)	VEH, VEHS
Junction	JCT	Warning	WARN
Left	LFT	Wednesday	WED
Left Lane	LFT LN	Weight Limit	WT LIMIT
Lane Closed	LN CLOSED	West	W
Lower Level	LWR LEVEL	Westbound	(route) W
Maintenance	MAINT	Wet Pavement	WET PVMT
		Will Not	WONT

Roadway designation = IH-number, US-number, SH-number, FM-number

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

SHEET 6 OF 12



BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)


BC (6) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904 00		214	VARIOUS
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	AMA	POTTER	12	

DATE: FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- Barrier Reflectors shall be pre-qualified, and conform to the color and reflectivity requirements of DMS-8600. A list of prequalified Barrier Reflectors can be found at the Material Producer List web address shown on BC(1).
- Color of Barrier Reflectors shall be as specified in the TMUTCD. The cost of the reflectors shall be considered subsidiary to Item 512.



CONCRETE TRAFFIC BARRIER (CTB)

- Where traffic is on one side of the CTB, two (2) Barrier Reflectors shall be mounted in approximately the midsection of each section of CTB. An alternate mounting location is uniformly spaced at one end of each CTB. This will allow for attachment of a barrier grapple without damaging the reflector. The Barrier Reflector mounted on the side of the CTB shall be located directly below the reflector mounted on top of the barrier, as shown in the detail above.
- Where CTB separates two-way traffic, three barrier reflectors shall be mounted on each section of CTB. The reflector unit on top shall have two yellow reflective faces (Bi-Directional) while the reflectors on each side of the barrier shall have one yellow reflective face, as shown in the detail above.
- When CTB separates traffic traveling in the same direction, no barrier reflectors will be required on top of the CTB.
- Barrier Reflector units shall be yellow or white in color to match the edgeline being supplemented.
- Maximum spacing of Barrier Reflectors is forty (40) feet.
- Pavement markers or temporary flexible-reflective roadway marker tabs shall NOT be used as CTB delineation.
- Attachment of Barrier Reflectors to CTB shall be per manufacturer's recommendations.
- Missing or damaged Barrier Reflectors shall be replaced as directed by the Engineer.
- Single slope barriers shall be delineated as shown on the above detail.




LOW PROFILE CONCRETE BARRIER (LPCB) USED IN WORK ZONES

LPCB is approved for use in work zone locations, where the posted speed is 45mph, or less. See Roadway Standard Sheet LPCB.

Max. spacing of barrier reflectors is 20 feet. Attach the delineators as per manufacturer's recommendations.

LOW PROFILE CONCRETE BARRIER (LPCB)



DELINEATION OF END TREATMENTS

END TREATMENTS FOR CTB'S USED IN WORK ZONES

End treatments used on CTB's in work zones shall meet the appropriate crashworthy standards as defined in the Manual for Assessing Safety Hardware (MASH). Refer to the CWZTCD List for approved end treatments and manufacturers.

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS

WARNING LIGHTS


- Warning lights shall meet the requirements of the TMUTCD.
- Warning lights shall NOT be installed on barricades.
- Type A-Low Intensity Flashing Warning Lights are commonly used with drums. They are intended to warn of or mark a potentially hazardous area. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "FL". The Type A Warning Lights shall not be used with signs manufactured with Type B_{PL} or C_{FL} Sheeting meeting the requirements of Departmental Material Specification DMS-8300.
- Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to supplement other traffic control devices. Their use shall be as indicated on this sheet and/or other sheets of the plans by the designation "SB".
- The Engineer/Inspector or the plans shall specify the location and type of warning lights to be installed on the traffic control devices.
- When required by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purchase Specifications for Flashing and Steady-Burn Warning Lights.
- When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
- The location of warning lights and warning reflectors on drums shall be as shown elsewhere in the plans.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS


- Type A flashing warning lights are intended to warn drivers that they are approaching or are in a potentially hazardous area.
- Type A random flashing warning lights are not intended for delineation and shall not be used in a series.
- A series of sequential flashing warning lights placed on channelizing devices to form a merging taper may be used for delineation. If used, the successive flashing of the sequential warning lights should occur from the beginning of the taper to the end of the merging taper in order to identify the desired vehicle path. The rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
- Type C and D steady-burn warning lights are intended to be used in a series to delineate the edge of the travel lane on detours, on lane changes, on lane closures, and on other similar conditions.
- Type A, Type C and Type D warning lights shall be installed at locations as detailed on other sheets in the plans.
- Warning lights shall not be installed on a drum that has a sign, chevron or vertical panel.
- The maximum spacing for warning lights on drums should be identical to the channelizing device spacing.

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

- A warning reflector or approved substitute may be mounted on a plastic drum as a substitute for a Type C, steady burn warning light at the discretion of the Contractor unless otherwise noted in the plans.
- The warning reflector shall be yellow in color and shall be manufactured using a sign substrate approved for use with plastic drums listed on the CWZTCD.
- The warning reflector shall have a minimum retroreflective surface area (one-side) of 30 square inches.
- Round reflectors shall be fully reflectorized, including the area where attached to the drum.
- Square substrates must have a minimum of 30 square inches of reflectorized sheeting. They do not have to be reflectorized where it attaches to the drum.
- The side of the warning reflector facing approaching traffic shall have sheeting meeting the color and retroreflectivity requirements for DMS 8300-Type B or Type C.
- When used near two-way traffic, both sides of the warning reflector shall be reflectorized.
- The warning reflector should be mounted on the side of the handle nearest approaching traffic.
- The maximum spacing for warning reflectors should be identical to the channelizing device spacing requirements.



Type C Warning Light or approved substitute mounted on a drum adjacent to the travel way.




Warning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

DATE:
FILE:

Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.

- The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
- Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or work on shoulders unless the "CAUTION" display (see detail below) is used.
- The Engineer/Inspector shall choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
- The Flashing Arrow Board should be able to display the following symbols:



- The "CAUTION" display consists of four corner lamps flashing simultaneously, or the Alternating Diamond Caution mode as shown.
- The straight line caution display is NOT ALLOWED.
- The Flashing Arrow Board shall be capable of minimum 50 percent dimming from rated lamp voltage. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
- Minimum lamp "on time" shall be approximately 50 percent for the flashing arrow and equal intervals of 25 percent for each sequential phase of the flashing chevron.
- The sequential arrow display is NOT ALLOWED.
- The flashing arrow display is the TxDOT standard; however, the sequential chevron display may be used during daylight operations.
- The Flashing Arrow Board shall be mounted on a vehicle, trailer or other suitable support.
- A Flashing Arrow Board SHALL NOT BE USED to laterally shift traffic.
- A full matrix PCMS may be used to simulate a Flashing Arrow Board provided it meets visibility, flash rate and dimming requirements on this sheet for the same size arrow.
- Minimum mounting height of trailer mounted Arrow Boards should be 7 feet from roadway to bottom of panel.

REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

ATTENTION
Flashing Arrow Boards shall be equipped with automatic dimming devices.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.

FLASHING ARROW BOARDS

SHEET 7 OF 12

TRUCK-MOUNTED ATTENUATORS

- Truck-mounted attenuators (TMA) used on TxDOT facilities must meet the requirements outlined in the Manual for Assessing Safety Hardware (MASH).
- Refer to the CWZTCD for the requirements of Level 2 or Level 3 TMAs.
- Refer to the CWZTCD for a list of approved TMAs.
- TMAs are required on freeways unless otherwise noted in the plans.
- A TMA should be used anytime that it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the work performance.
- The only reason a TMA should not be required is when a work area is spread down the roadway and the work crew is an extended distance from the TMA.



BARRICADE AND CONSTRUCTION ARROW PANEL, REFLECTORS, WARNING LIGHTS & ATTENUATOR

BC (7) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0904	00	214	VARIOUS				
9-07	8-14	DIST	COUNTY	SHEET NO.					
7-13	5-21	AMA	POTTER	13					

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflectorized space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign
(Maximum Sign Dimension)
Chevron CW1-8, Opposing Traffic Lane
Divider, Driveway sign D70a, Keep Right
R4 series or other signs as approved
by Engineer



12" x 24"
Vertical Panel
mount with diagonals
sloping down towards
travel way

Plywood, Aluminum or Metal sign
substrates shall NOT be used on
plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12




BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(8)-21


FILE:	bc-21.dgn	DN:	TxDOT	CR:	TxDOT	OW:	TxDOT	CK:	TxDOT
© TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0904	00	214	VARIOUS				
4-03	8-14	DIST	COUNTY	SHEET NO.					
9-07	5-21	AMA	POTTER	14					
7-13									

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



FIXED
(Rigid or self-righting)


DRIVEABLE



PORTABLE


VERTICAL PANELS (VPs)

- Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
- VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
- VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
- VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
- Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
- Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.




OPPOSING TRAFFIC LANE DIVIDERS (OTLD)

- Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
- The OTLD may be used in combination with 42" cones or VPs.
- Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
- The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.



- The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
- Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
- Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
- To be effective, the chevron should be visible for at least 500 feet.
- Chevrons shall be orange with a black nonreflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
- For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS



LONGITUDINAL CHANNELIZING DEVICES (LCD)

- LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
- LCDs may be used instead of a line of cones or drums.
- LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
- LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
- LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

- Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
- Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
- Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
- Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
- When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

GENERAL NOTES

- Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
- Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
- Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
- Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
- The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.

Posted Speed	Formula	Minimum Desirable Taper Lengths * *			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	L = WS ² / 60	150'	165'	180'	30'	60'
35		205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45	L = WS	450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

* * *Taper lengths have been rounded off.
L=Length of Taper (FT.) W=Width of Offset (FT.)
S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (9) - 21


FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904	00	214	VARIOUS
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	AMA	POTTER	15	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


TYPE 3 BARRICADES

1. Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
3. Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
4. Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
5. Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
7. Warning lights shall NOT be installed on barricades.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
9. Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL




TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.



PERSPECTIVE VIEW


The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic. Barricade striping should slant downward in the direction of detour.




PLAN VIEW

1. Signs should be mounted on independent supports at a 7 foot mounting height in center of roadway. The signs should be a minimum of 10 feet behind Type 3 Barricades.
2. Advance signing shall be as specified elsewhere in the plans.

TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION



PERSPECTIVE VIEW




PLAN VIEW

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS

1. Where positive redirection capability is provided, drums may be omitted.
2. Plastic construction fencing may be used with drums for safety as required in the plans.
3. Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
4. When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
5. Drums must extend the length of the culvert widening.

LEGEND	
	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector




Two-Piece cones

One-Piece cones

Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.
42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

1. Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
3. Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
4. Cones or tubular markers shall have white or white and orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
7. Cones or tubular markers used on each project should be of the same size and shape.



TRAFFIC CONTROL FOR MATERIAL STOCKPILES

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (10) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904	00	214	VARIOUS
9-07 8-14	DIST	COUNTY	SHEET NO.	
7-13 5-21	AMA	POTTER	16	

WORK ZONE PAVEMENT MARKINGS

GENERAL

- The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
- Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- Additional supplemental pavement marking details may be found in the plans or specifications.
- Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
- When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
- When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
- All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

- Raised pavement markers are to be placed according to the patterns on BC(12).
- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

- Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
- Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

- The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
- Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
- The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
- Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

- Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
- The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
- Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
- The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
- Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
- Blast cleaning may be used but will not be required unless specifically shown in the plans.
- Over-painting of the markings SHALL NOT BE permitted.
- Removal of raised pavement markers shall be as directed by the Engineer.
- Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
- Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



**STAPLES OR NAILS SHALL NOT BE USED TO SECURE
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER
TABS TO THE PAVEMENT SURFACE**

- Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
- Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
- Small design variances may be noted between tab manufacturers.
- See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

- Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
- All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
- Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:
 YELLOW - (two amber reflective surfaces with yellow body).
 WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

SHEET 11 OF 12







BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

BC(11)-21



FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS		0904 00	214	VARIOUS
2-98 9-07 5-21	DIST	COUNTY	SHEET NO.	
1-02 7-13	AMA	POTTER	17	
11-02 8-14				

PAVEMENT MARKING PATTERNS





Pattern A is the TxDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectorized pavement markings.

CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS





Prefabricated markings may be substituted for reflectorized pavement markings.

EDGE & LANE LINES FOR DIVIDED HIGHWAY



Prefabricated markings may be substituted for reflectorized pavement markings.


LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS






Prefabricated markings may be substituted for reflectorized pavement markings.

TWO-WAY LEFT TURN LANE


STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS



SOLID LINES




BROKEN LINES



REMOVABLE MARKINGS WITH RAISED PAVEMENT MARKERS

If raised pavement markers are used to supplement REMOVABLE markings, the markers shall be applied to the top of the tape at the approximate mid length of tape used for broken lines or at 20 foot spacing for solid lines. This allows an easier removal of raised pavement markers and tape.



SHEET 12 OF 12



BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC (12) - 21


Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904	00	214	VARIOUS
1-97 9-07 5-21	DIST	COUNTY	SHEET NO.	
2-98 7-13	AMA	POTTER	18	
11-02 8-14				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




TCP (1-1a)

WORK SPACE NEAR SHOULDER
Conventional Roads



TCP (1-1b)

WORK SPACE ON SHOULDER
Conventional Roads



TCP (1-1c)

WORK VEHICLES ON SHOULDER
Conventional Roads

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
** Taper lengths have been rounded off.
L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES**
- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - Inactive work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
 - See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
 - CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.

TRAFFIC CONTROL PLAN
CONVENTIONAL ROAD
SHOULDER WORK



TCP (1-1) - 18

FILE: tcp1-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CON:	SECT:	JOB:	HIGHWAY:
REVISIONS	0904	00	214	VARIOUS
2-94 4-98	DIST:	COUNTY:	SHEET NO.:	
8-95 2-12	AMA	POTTER	19	
1-97 2-18				

DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

GENERAL NOTES

- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
 - Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or R1-2 "YIELD" sign is less than 1500 feet.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
- TCP (1-2a)**
- R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
 - R1-2 "YIELD" sign with R1-2aP "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.
- TCP (1-2b)**
- Flaggers should use two-way radios or other methods of communication to control traffic.
 - Length of work space should be based on the ability of flaggers to communicate.
 - If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
 - Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the Engineer.
 - Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

Texas Department of Transportation
 Traffic Operations Division Standard


TRAFFIC CONTROL PLAN
ONE-LANE TWO-WAY
TRAFFIC CONTROL

TCP (1-2) - 18


FILE: tcp1-2-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	090400	214	VARIOUS	
4-90 4-98	DIST	COUNTY	SHEET NO.	
2-94 2-12	AMA	POTTER	20	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



BE PREPARED TO STOP
CW3-4 48" X 48"▲
CW20-7 48" X 48"▲
For either TCP(1-3a) or TCP(1-3b)
USE ONLY WHEN FLAGGERS CONTROL TRAFFIC
(See Notes 2 & 3)



LEGEND

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
** Taper lengths have been rounded off.
L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES**
- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - Flagger control should NOT be used unless roadway conditions or heavy traffic volume require additional emphasis to safely control traffic. Additional flaggers may be positioned in advance of traffic queues to alert traffic to reduce speed.
 - DO NOT PASS, PASS WITH CARE and construction regulatory speed zone signs may be installed downstream of the ROAD WORK AHEAD signs.
 - When the work zone is made up of several work spaces, channelizing devices should be placed laterally across the closed lane to re-emphasize closure. Laterally placed channelizing devices should be repeated every 500 to 1000 feet in urban areas and every 1/4 to 1/2 mile in rural areas.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
 - Where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20', or 15' if posted speed are 35 mph or slower, and for tangent sections, at 1/2S where S is the speed in mph. This tighter device spacing is intended for the area of conflicting markings not the entire work zone.



Texas Department of Transportation
Traffic Operations Division Standard

TRAFFIC CONTROL PLAN
TRAFFIC SHIFTS ON
TWO LANE ROADS
TCP (1-3) - 18

FILE: tcp1-3-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	090400	214	VARIOUS	
2-94 4-98	DIST	COUNTY	SHEET NO.	
8-95 2-12	AMA	POTTER	21	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	$L = WS$	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
** Taper lengths have been rounded off.
L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

- GENERAL NOTES**
- Flags attached to signs where shown are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - The CW20-1D "ROAD WORK AHEAD" sign may be repeated if the visibility of the work zone is less than 1500 feet.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.

TCP (1-4g)

6. If this TCP is used for a left lane closure, CW20-5TL "LEFT LANE CLOSED" signs shall be used and channelizing devices shall be placed on the centerline where needed to protect the work space from opposing traffic with the arrow panel placed in the closed lane near the end of the merging taper.

TCP (1-4b)

7. Where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2S where S is the speed in mph. This tighter device spacing is intended for the areas of conflicting markings, not the entire work zone.

Texas Department of Transportation
Traffic Operations Division Standard


TRAFFIC CONTROL PLAN
LANE CLOSURES ON MULTILANE CONVENTIONAL ROADS

TCP (1-4) - 18


FILE: tcp1-4-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CON:	SECT:	JOB:	HIGHWAY:
REVISIONS	090400	214	VARIOUS	
2-94 4-98	DIST:	COUNTY:	SHEET NO.:	
8-95 2-12	AMA	POTTER	22	
1-97 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



TCP (2-4a)
ONE LANE CLOSED



TCP (2-4b)
TWO LANES CLOSED

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
		✓	✓	

GENERAL NOTES

- Flags attached to signs where shown, are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The downstream taper is optional. When used, it should be 100 feet minimum length per lane.
- For short term applications, when post mounted signs are not used, the distance legend may be shown on the sign face rather than on a CW16-3aP supplemental plaque.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.

TCP (2-4a)

- If this TCP is used for a left lane closure, CW20-5TL "LEFT LANE CLOSED" signs shall be used and channelizing devices shall be placed on the centerline to protect the work space from opposing traffic with the arrow board placed in the closed lane near the end of the merging taper.

TCP (2-4b)

- For shorter durations where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the speed in mph. This tighter devices spacing is intended for the area of conflicting markings, not the entire work zone.




**TRAFFIC CONTROL PLAN
LANE CLOSURES ON MULTILANE
CONVENTIONAL ROADS**


TCP (2-4) - 18

FILE: tcp2-4-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS	090400	214	VARIOUS	
8-95 3-03	DIST	COUNTY	SHEET NO.	
1-97 2-12	AMA	POTTER	23	
4-98 2-18				

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



TCP (2-5a)
ONE LANE CLOSED



TCP (2-5b)
TWO LANES CLOSED

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
** Taper lengths have been rounded off.
L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

- GENERAL NOTES**
- Flags attached to signs where shown, are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned in each closed lane, on the shoulder or off the paved surface, next to those shown in order to protect a wider work space.
 - The downstream taper is optional. When used, it should be 100 feet approximately per lane, with channelizing devices spaced at 20 feet.
- TCP (2-5a)**
- If this TCP is used for a left lane closure, CW20-5TL "LEFT LANE CLOSED" signs shall be used and channelizing devices shall be placed on the centerline to protect the work space from opposing traffic, with the arrow board placed in the closed lane near the end of the merging taper.
- TCP (2-5b)**
- Conflicting pavement markings shall be removed for long-term projects.

Traffic Operations Division Standard


TRAFFIC CONTROL PLAN
LONG TERM LANE CLOSURES
MULTILANE CONVENTIONAL RDS.

TCP (2-5) - 18


FILE: tcp2-5-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
8-95 2-12 REVISIONS	090400	214	VARIOUS	
1-97 3-03	DIST	COUNTY	SHEET NO.	
4-98 2-18	AMA	POTTER	24	

1165

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



TCP (3-1a)
UNDIVIDED MULTILANE ROADWAY




TRAIL/SHADOW VEHICLE A
with RIGHT Directional display Flashing Arrow Board

LEGEND		
*	Trail Vehicle	ARROW BOARD DISPLAY
**	Shadow Vehicle	
***	Work Vehicle	RIGHT Directional
☐	Heavy Work Vehicle	LEFT Directional
☐	Truck Mounted Attenuator (TMA)	Double Arrow
↔	Traffic Flow	CAUTION (Alternating Diamond or 4 Corner Flash)


TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
✓				

GENERAL NOTES


1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used the WORK vehicle must be equipped with an arrow board. The Engineer will determine if the LEAD VEHICLE and/or TRAIL VEHICLE are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE are required.
4. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
5. Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
6. Each vehicle shall have two-way radio communication capability.
7. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
8. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
9. "X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY" (CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.
10. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the rearmost protection vehicle.




TCP (3-1b)
TWO-WAY ROADWAY WITH PAVED SHOULDERS



TCP (3-1c)
TWO-WAY ROADWAY WITHOUT PAVED SHOULDERS



TRAIL/SHADOW VEHICLE B
with Flashing Arrow Board in CAUTION display




STRIPING FOR TMA

TRAFFIC CONTROL PLAN
MOBILE OPERATIONS
UNDIVIDED HIGHWAYS


TCP (3-1) - 13

FILE:	tcp3-1.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	December 1985	CONT	SECT	JOB	HIGHWAY				
REVISIONS		0904	00	214	VARIOUS				
2-94	4-98	DIST	COUNTY	SHEET NO.					
8-95	7-13	AMA	POTTER	25					
1-97									


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



NEAR SIDE LANE CLOSURE
SHORT DURATION OR SHORT TERM STATIONARY



FAR SIDE RIGHT LANE CLOSURE
SHORT DURATION OR SHORT TERM STATIONARY




FAR SIDE LEFT LANE CLOSURE
SHORT DURATION OR SHORT TERM STATIONARY

LEGEND			
	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger


Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

WORKERS IN BUCKET TRUCKS SHALL NOT WORK ABOVE OPEN LANES OF TRAFFIC.



OPERATIONS IN THE INTERSECTION
SHORT DURATION



GENERAL NOTES

- The minimum size channelizing device is the 28" cone. 42" Two-piece cones, drums, vertical panels or barricades will be required when the device must be left unattended at night.
- Obstructions or hazards at the work area shall be clearly marked and delineated at all times.
- Flaggers and Flagger Symbol (CW20-7) signs may be required according to field conditions.
- Vehicles parked in roadway shall be equipped with at least two high intensity rotating, flashing, oscillating or strobe type lights.
- High level warning devices (flag trees) may be used at corners of the vehicle.
- When work operations are performed on existing signals, the signals may be placed in flashing red mode when approved by the engineer. If existing signals do not have power, All-Way Stop (R1-1 and R1-3P) signs may be implemented when approved by the engineer.
- For Short-Term Stationary work the buffer space "B" from the above table should be used if field conditions permit. For Short Duration (less than 1 hour) any buffer space provided will enhance the safety of the setup.
- The arrow board at this location may be omitted for Short Duration work if the work vehicle has an arrow board in operation. As an option, the arrow board may be placed at the end of the taper in the closed lane if space is not available at the beginning of the taper.
- Signs and devices for the NEAR SIDE LANE CLOSURE may be altered for a left lane closure by using a LEFT LANE CLOSED (CW20-5TL) and adding channelizing devices on the centerline to protect the work space from opposing traffic.

SHEET 1 OF 2



TRAFFIC SIGNAL WORK TYPICAL DETAILS


WZ(BTS-1)-13

FILE: wzbts-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT April 1992	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904	00	214	VARIOUS
2-98 10-99 7-13	DIST	COUNTY	SHEET NO.	
4-98 3-03	AMA	POTTER	26	

DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



TYPICAL ADVANCE SIGNAL PROJECT SIGNING
FOR LONG TERM and INTERMEDIATE-TERM STATIONARY WORK OPERATIONS

- NOTES**
1. Project signing as shown shall be in place whenever signal contract work is in progress.
 2. For closely adjoining projects, advance signing may not be required in advance of each intersection, but only in advance of the intersections at the project limits. Actual locations will be as directed by the Engineer.
 3. Advance signs shall be removed when signal construction operations are no longer under way, as directed by the Engineer.
 4. Warning sign spacing shown is typical for both directions.
 5. See the Table on sheet 1 of 2 for Typical warning sign spacing.

GENERAL NOTES FOR WORK ZONE SIGNS

1. Signs shall be installed and maintained in a straight and plumb condition.
2. Wooden sign posts shall be painted white.
3. Barricades shall NOT be used as sign supports.
4. Nails shall NOT be used to attach signs to any support.
5. All signs shall be installed in accordance with the plans or as directed by the Engineer.
6. The Contractor shall furnish the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD).
7. The Contractor shall furnish sign supports and substrates listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD), installed as per the manufacturer's recommendations.
8. Temporary signs that have damaged or cracked substrates and/or damaged or marred reflective sheeting shall be replaced as directed by the Engineer.
9. Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1".
10. Damaged wood posts shall be replaced. Splicing wood posts will not be allowed.

DURATION OF WORK

1. Work zone durations are defined in Part 6, Section 60.02 of the Texas Manual on Uniform Traffic Control Devices (TMUTCD).

SIGN MOUNTING HEIGHT

1. Sign height of Long-term/Intermediate-term warning signs shall be as shown on Figure 6F-1 of the TMUTCD.
2. Sign height of Short-term/Short Duration warning signs shall be as shown on Figure 6F-2 of the TMUTCD.
3. Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

REMOVING OR COVERING

1. When sign messages may be confusing or do not apply, the signs shall be removed or completely covered, unless otherwise approved by the Engineer.
2. When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night without damaging the sign sheeting. Burlap, or heavy materials such as plywood or aluminum shall not be used to cover signs.
3. Duct tape or other adhesive material shall NOT be affixed to a sign face.
4. Signs and anchor stubs shall be removed and holes back filled upon completion of the work.

REFLECTIVE SHEETING

1. All signs shall be retroreflective and constructed of sheeting meeting the requirements of the DMS and color usage table shown on this sheet.

SIGN SUPPORT WEIGHTS


1. Weights used to keep signs from turning over should be sandbags filled with dry, cohesionless material.
2. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
3. Rock, concrete, iron, steel or other solid objects will not be permitted for use as sign support weights.
4. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
5. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber, such as tire inner tubes, shall not be used.
6. Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
7. Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
8. Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

LEGEND	
	Sign
	Channelizing Devices
	Type 3 Barricade


DEPARTMENTAL MATERIAL SPECIFICATIONS	
SIGN FACE MATERIALS	DMS-8300
FLEXIBLE ROLL-UP REFLECTIVE SIGNS	DMS-8310

COLOR	USAGE	SHEETING MATERIAL
ORANGE	BACKGROUND	TYPE B _{FL} OR TYPE C _{FL} SHEETING
WHITE	BACKGROUND	TYPE A SHEETING
BLACK	LEGEND & BORDERS	ACRYLIC NON-REFLECTIVE SHEETING


Only pre-qualified products shall be used. A copy of the "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources and may be found at the following web address:
http://www.txdot.gov/txdot_library/publications/construction.htm



SIDEWALK DIVERSION



SIDEWALK DETOUR



CROSSWALK CLOSURES

PEDESTRIAN CONTROL

1. Holes, trenches or other hazards shall be adequately protected by covering, delineating or surrounding the hazard with orange plastic pedestrian fencing or longitudinal channelizing devices, or as directed by the Engineer.
2. "CROSSWALK CLOSURES" as detailed above will require the Engineer's approval prior to installation.
3. R9 series signs shown may be placed on supports detailed on the BC standards or CWZTCD list, or when fabricated from approved lightweight plastic substrates, they may be mounted on top of a plastic drum at or near the location shown.
4. For speeds less than 45 mph longitudinal channelizing devices may be used instead of traffic barriers when approved by the Engineer. Attenuation of blunt ends and installation of water filled devices shall be as per BC(9) and manufacturer's recommendations.
5. Location of devices are for general guidance. Actual device spacing and location must be field adjusted to meet actual conditions.
6. Where pedestrians with visual disabilities normally use the closed sidewalk Detectable Pedestrian Barricades should be used instead of the Type 3 Barricades shown.
7. The width of existing sidewalk should be maintained if practical.
8. Pavement markings for mid-block crosswalks shall be paid for under the appropriate bid items.
9. When crosswalks or other pedestrian facilities are closed or relocated, temporary facilities shall be detectable and shall include accessibility features consistent with the features present in the existing pedestrian facility.

SHEET 2 OF 2

		Traffic Operations Division Standard	
<h2>TRAFFIC SIGNAL WORK BARRICADES AND SIGNS</h2>			
<h3>WZ (BTS-2) - 13</h3>			
FILE:	wzBts-13.dgn	DN:	TxDOT
© TxDOT	April 1992	CK:	TxDOT
REVISIONS	0904 00	DW:	TxDOT
2-98	10-99	CON:	214
4-98	3-03	JOB:	VARIOUS
		DIST:	COUNTY
		AMA:	POTTER
		SHEET NO.:	27

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

Warning sign and rumble strip sequence in opposite direction is same as below.


Rumble Strip Array (See note 1)

Rumble Strip Array (See note 1)


The second Rumble Strip Array is required when the ADT thresholds in Table 1 indicate the need for 2 Arrays.

DATE: FILE:

Flagger to Flagger (Length of Work Area)	ADT	# of Rumble Strip Arrays
1/8 Mile	< 4,500	1
	≥ 4,500	2
1/4 Mile	< 3,500	1
	≥ 3,500	2
1/2 Mile	< 2,600	1
	≥ 2,600	2
1 Mile	< 1,600	1
	≥ 1,600	2
> 1 Mile	N/A	2



RUMBLE STRIPS ON ONE-LANE TWO-WAY APPLICATION



RUMBLE STRIPS FOR LANE CLOSURE ON CONVENTIONAL ROADWAY

GENERAL NOTES

- Each Rumble Strip Array should consist of three rumble strips spaced center to center at the spacing shown in Table 2, placed transverse across the lane at locations shown.
- The CW17-2T "RUMBLE STRIPS AHEAD" sign should be located after the CW20-1D "ROAD WORK AHEAD" sign and spaced as shown. If traffic is observed to be queuing, or is expected to queue beyond the Rumble Strips, the CW17-2T sign and the first Rumble Strip Array may be located upstream of the CW20-1D sign as necessary to provide needed warning.
- Temporary Rumble Strips will be considered subsidiary to Item 502, and shall be a product listed on the Compliant Work Zone Traffic Control Devices.
- Remove Temporary Rumble Strips before removing the advanced warning signs.
- Temporary Rumble Strips should not be used on horizontal curves, loose gravel, soft or bleeding asphalt, heavily rutted pavements or unpaved surfaces.
- Temporary Rumble Strips shall be installed and maintained as per manufacturer's recommendations.
- This standard sheet shall be used in conjunction with other appropriate TCP standard, TMUTCD typical application or project specific detail for the project.
- The one-lane two-way application may utilize a flagger, an Automated Flagger Assistance Device (AFAD) or a Portable Traffic Signal (PTS).
- Replace defective Temporary Rumble Strips as directed by the Engineer.
- Temporary Rumble Strips may be used on freeways or expressways based on engineering judgment and written direction from the Engineer.

Speed	Approximate distance between strips in an array
≤ 40 MPH	10'
> 40 MPH & ≤ 55 MPH	15'
= 60 MPH	20'
≥ 65 MPH	* 35'+

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Panel		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths * #			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	L = WS ² / 60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L = WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only
 ** Taper lengths have been rounded off.
 L=Length of Taper (FT) W=Width of Offset (FT)
 S=Posted Speed (MPH)

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

◆ Signs are for illustrative purposes only. Signs required may vary depending on the TCP, TMUTCD Typical Application, or project specific details for the project.

* For posted speeds in excess of 65 MPH, it is recommended that spacing is increased as speed limits increase. Increasing space between rumble strips will improve effectiveness.


Texas Department of Transportation Traffic Safety Division Standard

TEMPORARY RUMBLE STRIPS


WZ (RS) - 22

FILE: wzrs22.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2012	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904 00	214	VARIOUS	
2-14 1-22	DIST	COUNTY	SHEET NO.	
4-16	AMA	POTTER	28	



TRAFFIC SIGNAL HEADS



PEDESTRIAN SIGNS



LEGEND:



[Signature]
2/9/2024

BELL AT PLAINS
EXISTING
SIGNAL
LAYOUT

NOTES:

THE SALVAGEABLE MATERIALS REMOVED (CONTROLLER CABINET AND CONTENTS, SHALL BE DELIVERED TO THE CITY OF AMARILLO SIGNAL YARD IN AMARILLO (800 SE 23RD AVE) AT TIME OF REMOVAL.

THE CONTRACTOR WILL ACCEPT OWNERSHIP OF ALL OTHER MATERIALS (SIGNAL HEADS, CABLES, PUSHBUTTONS, SIGNS, ETC.) AND SHALL DISPOSE OF PROPERLY.

TRAFFIC SIGNAL REMOVAL NOTES

LIST ITEMS TO BE REMOVED:(SUBSIDIARY TO ITEM 680 6004 REMOVING TRAFFIC SIGNALS)

1. REMOVE 5 SECTION SIGNAL HEADS AND BACKPLATES, SIGNAL HEADS 4,8,12,16
2. REMOVE PEDESTRIAN SIGNALS AND PUSHBUTTONS AND SIGNS
3. REMOVE TRAFFIC SIGNAL CONTROL CABINET (FOUNDATION TO BE RE-USED)
4. REMOVE (4) SIGNS S5-PROTECTED LEFT ON GREEN ARROW
5. REMOVE SIGNAL CONDUCTORS FROM CABINET TO POLE
6. REMOVE SIGNAL CONDUCTORS IN POLES FOR 4 SECTION HEADS, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS

SCALE: 1" = 40'

SHEET 1 OF 1



Texas Department of Transportation

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	MP	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	MP	AMA	POTTER	29	

DATE: 2/9/24
FILE: 214-29

PROPOSED SIGNAL HEAD



4,8,12,16

PROPOSED SIGNAL HEADS AND SIGNS



PSH1-PSH8



R10-3e (R)



R10-3e (L)



R10-XR



R10-XL

PB1 - PB8

PROPOSED MAST ARM MOUNTED SIGN


S5



R10-17T
30X30

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- CONDUIT RUN
- SIGNAL HEAD
- ELECTRICAL SERVICE
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- ITERIS DETECTOR
- SIGNAL POLE



TRAFFIC SIGNAL INSTALLATION NOTES:

1. REPLACE SIGNAL (5 SECTION HEAD) TO (4 SECTION HEAD) FOR LEFT TURNS.
2. INSTALL VIDEO IMAGING AND RADAR DETECTORS, SYSTEM, AND CABLING.
3. REPLACE ALL PEDESTRIAN STANDARDS, SIGNS AND SIGNAL HEADS.
4. REPLACE CONTROL CABINET TO (TS-TY 2) (REUSE EXISTING CABINET CONTROLLER AND FOUNDATION)
5. ALL SIGNAL EQUIPMENT PROVIDED BY CONTRACTORS SHALL BE COMPATIBLE WITH CITY OF AMARILLO'S SIEMENS-TACTICS CENTRAL SOFTWARE AND ITERIS VANTAGE VECTOR DETECTOR.
6. REPLACE ALL SIGNAL CONDUCTORS FROM CABINET TO SIGNALPOLE
7. REPLACE SIGNAL CONDUCTORS IN POLE FOR 4 SECTION HEAD, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS.
8. ALL CONDUITS WILL REMAIN IN PLACE
9. EXISTING SERVICE POLE AND METER TO REMAI IN PLACE



[Signature]
2/19/2024

BELL AT PLAINS
PROPOSED
SIGNAL
LAYOUT

SCALE: 1" = 40'



Texas Department of Transportation

SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	30	

SUMMARY OF CABLES INSIDE POLES & MAST ARMS					
POLE NO.	ATTACHMENT	ITEM 0684 TRAFFIC SIGNAL CABLE 6080	ITEM 0684 TRAFFIC SIGNAL CABLE 6031	ITEM 0684 TRAFFIC SIGNAL CABLE 6033	ITEM 6083 - VIDEO IMAGING RAD. VEH DETECT. 6005
		(TY C) (14 AWG) (2 CONDR)	(TY A) (14 AWG) (5 CONDR)	(TY A) (14 AWG) (7 CONDR)	COMMUNICATION CABLE (COAXIAL)
		LF	LF	LF	LF
SP-A					
	SIGNAL 4			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB1	10			
	PB8	10			
	PSH-1		15		
	PSH-8		15		
SP-B					
	SIGNAL 8			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB6	10			
	PB8	10			
	PSH-6		15		
	PSH-8		15		
SP-C					
	SIGNAL 12			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB4	10			
	PB6	10			
	PSH-4		15		
	PSH-6		15		
SP-D					
	SIGNAL 16			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB1	10			
	PB4	10			
	PSH-1		15		
	PSH-4		15		
	TOTAL:	80	120	280	280

RUN NO.	LENGTH	EXISTING CONDUIT		ITEM 0620 -		ITEM 0684 -		ITEM 0620 -		ITEM 0620 -		ITEM 6083 - VIDEO IMAGING RAD VEH DETECT.	
				6010		6046		6007		6009		6005	
				ELEC CONDR (NO 6) INSULATED		TRF SIG CBL (TY A)(14 AWG)(20 CONDR)		ELEC CONDR (NO. 8) BARE		ELEC CONDR (NO. 6) BARE		COMMUNICATION CABLE (COAXIAL)	
EA	LF	EA	LF	EA	LF	EA	LF	EA	LF	EA	LF	EA	LF
1	15	1	15			4	60	1	15			4	60
2	50	1	50			4	200	1	50			4	200
3	15	1	15			1	15	1	15			1	15
4	105	1	105			1	105	1	105			1	105
5	15	1	15			1	15	1	15			1	15
6	10	1	10			2	20	1	20			2	20
7	15	1	15			1	15	1	15			1	15
8	80	1	80			1	80	1	80			1	80
9	15	1	15			1	15	1	15			1	15
10	70	1	70	2	140					1	70		
11	15	1	15	2	30					1	15		
12	105	1	105			1	20	1	20			1	20
TOTAL:	510		510		170		545		350		85		545



[Signature]
2/9/2024

**BELL AT PLAINS
PROPOSED SIGNAL
WIRING**




Texas Department of Transportation


SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	31	

PHASING DIAGRAM



PHASING DIAGRAM



1,3,5,7 ARE PROTECTED/PERMISSIVE FLASHING YELLOW

CONSTRUCTION NOTE:
 1. A REPRESENTATIVE FROM THE CITY OF AMARILLO MUST BE PRESENT TO VERIFY THE REWIRING OF THE NEW CABINET TO THE FIELD WIRES AND TO CONFIGURE THE CONTROLLER PROGRAMMING PRIOR TO REACTIVATION OF THE SIGNAL



Dawood Alani
 2/9/2021



BELL AT PLAINS
 PROPOSED TRAFFIC
 SIGNAL DETAILS

SCALE: N.T.S



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	32	


ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
BELL AT PLAINS			
TOTAL	350	85	170

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
BELL AT PLAINS					
TOTAL	1	1	4	8	1


** SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN) LED (GRN ARW)	VEH SIG SEC (12 IN) LED (YEL ARW)	VEH SIG SEC (12 IN) LED (RED ARW)	PED SIG SEC (LED)(COUNT DOWN)	BACK PLATE W/REF BRDR (4 SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
BELL AT PLAINS									
TOTAL	4	8	4	8	4	120	280	545	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET-UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
BELL AT PLAINS					
TOTAL	8	1	4	1	825



Dawood Alani
2/9/2024



BELL AT PLAINS

SUMMARY OF QUANTITIES




DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	33	

STIMES

DATE: 02/09/2024
FILE: 090400

TRAFFIC SIGNAL HEADS



1,2,4,5,6,8
9,11,12,13

7,14

3,10

PEDESTRIAN SIGNS



R10-XR





R10-XL



PSH1-PSH8

PB1 - PB4

LEGEND:



[Signature]
2/19/2024

ROSS AT 10TH
EXISTING
SIGNAL
LAYOUT

NOTES:

THE SALVAGEABLE MATERIALS REMOVED (CONTROLLER CABINET AND CONTENTS, SHALL BE DELIVERED TO THE CITY OF AMARILLO SIGNAL YARD IN AMARILLO (800 SE 23RD AVE) AT TIME OF REMOVAL.

THE CONTRACTOR WILL ACCEPT OWNERSHIP OF ALL OTHER MATERIALS (SIGNAL HEADS, CABLES, PUSHBUTTONS, SIGNS, ETC.) AND SHALL DISPOSE OF PROPERLY.

TRAFFIC SIGNAL REMOVAL NOTES

LIST ITEMS TO BE REMOVED:(SUBSIDIARY TO ITEM 680 6004 REMOVING TRAFFIC SIGNALS)

1. REMOVE 5 SECTION SIGNAL HEADS AND BACKPLATES, SIGNAL HEADS 4,8,12,16
2. REMOVE PEDESTRIAN SIGNALS AND PUSHBUTTONS AND SIGNS
3. REMOVE TRAFFIC SIGNAL CONTROL CABINET (FOUNDATION TO BE RE-USED)
4. REMOVE (4) SIGNS S5-PROTECTED LEFT ON GREEN ARROW
5. REMOVE SIGNAL CONDUCTORS FROM CABINET TO POLE
6. REMOVE SIGNAL CONDUCTORS IN POLES FOR 4 SECTION HEADS, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS

SCALE: 1" = 40'



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	MP	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	MP	AMA	POTTER	34	

STIMES

DATE: 02/19/2024
FILE: 214-00-34

PROPOSED SIGNAL HEAD



3,7,10,14

PROPOSED PEDESTRIAN SIGNAL HEADS AND SIGNS



PSH1-PSH8



R10-3e (R)



R10-3e (L)



R10-XR



R10-XL

PB1 - PB8

PROPOSED MAST ARM MOUNTED SIGN




S5

LEFT TURN
YIELD
ON FLASHING
YELLOW
ARROW

R10-17T
30X30


LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- CONDUIT RUN
- SIGNAL HEAD
- ELECTRICAL SERVICE
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- ITERIS DETECTOR
- SIGNAL POLE



TRAFFIC SIGNAL INSTALLATION NOTES:

1. REPLACE SIGNAL (5 SECTION HEAD) TO (4 SECTION HEAD) FOR LEFT TURNS.
2. INSTALL VIDEO IMAGING AND RADAR DETECTORS. SYSTEM, AND CABLING.
3. REPLACE ALL PEDESTRIAN STANDARDS, SIGNS AND SIGNAL HEADS.
4. REPLACE CONTROL CABINET TO (TS-TY 2) (REUSE EXISTING CABINET CONTROLLER AND FOUNDATION)
5. ALL SIGNAL EQUIPMENT PROVIDED BY CONTRACTORS SHALL BE COMPATIBLE WITH CITY OF AMARILLO'S SIEMENS-TACTICS CENTRAL SOFTWARE AND ITERIS VANTAGE VECTOR DETECTOR.
6. REPLACE ALL SIGNAL CONDUCTORS FROM CABINET TO SIGNALPOLE
7. REPLACE SIGNAL CONDUCTORS IN POLE FOR 4 SECTION HEAD, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS.
8. ALL CONDUITS WILL REMAIN IN PLACE
9. EXISTING SERVICE POLE AND METER TO REMAI IN PLACE



[Signature]
2/19/2024

ROSS AT 10TH
PROPOSED
SIGNAL
LAYOUT

SCALE: 1" = 40'




Texas Department of Transportation

SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	35	

SUMMARY OF CABLES INSIDE POLES & MAST ARMS					
POLE NO.	ATTACHMENT	ITEM 0684	ITEM 0684	ITEM 0684	ITEM 6083 - VIDEO
		TRAFFIC SIGNAL CABLE 6080	TRAFFIC SIGNAL CABLE 6031	TRAFFIC SIGNAL CABLE 6033	IMAGING RAD. VEH DETECT. 6005
		(TY C) (14 AWG) (2 CONDR)	(TY A) (14 AWG) (5 CONDR)	(TY A) (14 AWG) (7 CONDR)	COMMUNICATION CABLE (COAXIAL)
		LF	LF	LF	LF
SP-A					
	SIGNAL 3			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB2	10			
	PB8	10			
	PSH-2		15		
	PSH-8		15		
SP-B					
	SIGNAL 7			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB6	10			
	PB8	10			
	PSH-6		15		
	PSH-8		15		
SP-C					
	SIGNAL 10			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB4	10			
	PB6	10			
	PSH-4		15		
	PSH-6		15		
SP-D					
	SIGNAL 14			70	
	VIDEO IMAGING AND RADAR DETECTOR				60
	PB2	10			
	PB4	10			
	PSH-2		15		
	PSH-4		15		
	TOTAL:	80	120	280	270

RUN NO.	LENGTH	EXISTING CONDUIT		ITEM 0620 -	ITEM 0684 -	ITEM 0620 -	ITEM 0620 -	ITEM 6083 - VIDEO IMAGING RAD VEH DETECT.			
				6010	6046	6007	6009	6005			
		ELEC CONDR (NO 6) INSULATED	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	EA	LF	EA	LF		
1	25	1	25	2	50			1	25		
2	30	1	30	2	60			1	30		
3	20	1	20			1	20	1	20		1 20
4	75	1	75			2	150	1	75		2 150
5	20	1	20			1	20	1	20		1 20
6	85	1	85			1	85	1	85		1 85
7	20	1	20			1	20	1	20		1 20
8	85	1	85			1	85	1	85		1 85
9	25	1	25			1	25	1	25		1 25
TOTAL:	385		385		110		405		330		55 405



Dawood Alani
2/9/2024

**ROSS AT 10TH
PROPOSED SIGNAL
WIRING**




Texas Department of Transportation


SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	36	

PHASING DIAGRAM




PHASING DIAGRAM



1,3,5,7 ARE PROTECTED/PERMISSIVE FLASHING YELLOW

CONSTRUCTION NOTE:
 1. A REPRESENTATIVE FROM THE CITY OF AMARILLO MUST BE PRESENT TO VERIFY THE REWIRING OF THE NEW CABINET TO THE FIELD WIRES AND TO CONFIGURE THE CONTROLLER PROGRAMMING PRIOR TO REACTIVATION OF THE SIGNAL



[Signature]
 2/9/2024



ROSS AT 10TH
 PROPOSED TRAFFIC
 SIGNAL DETAILS

SCALE: N.T.S

Texas Department of Transportation
 SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	37	

ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
ROSS AT 10TH			
TOTAL	405	55	110

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
ROSS AT 10TH					
TOTAL	1	1	4	8	1

** SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN)LED (GRN ARW)	VEH SIG SEC (12 IN)LED (YEL ARW)	VEH SIG SEC (12 IN)LED (RED ARW)	PED SIG SEC (LED)COUNT DOWN)	BACK PLATE W/REF BRDR (4 SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
ROSS AT 10TH									
TOTAL	4	8	4	8	4	120	280	405	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET-UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
ROSS AT 10TH					
TOTAL	8	1	4	1	675



Dawood Alani
2/19/2024


ROSS AT 10TH

SUMMARY OF QUANTITIES



DSR	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DSR	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	38	

TRAFFIC SIGNAL HEADS



1,2,3,5,6,8,9,11,12,13



3,7,10,14

PEDESTRIAN SIGNS



R10-XR



R10-XL



PB1 - PB4



PSH1-PSH8

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- SIGNAL HEAD
- POWER SOURCE
- LOOP DETECTOR
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- SIGNAL POLE



[Signature]
2/9/2024

ARTHUR AT 10TH
EXISTING
SIGNAL
LAYOUT

SCALE: 1" = 40'

NOTES:
THE SALVAGEABLE MATERIALS REMOVED (CONTROLLER CABINET AND CONTENTS, SHALL BE DELIVERED TO THE CITY OF AMARILLO SIGNAL YARD IN AMARILLO (800 SE 23RD AVE) AT TIME OF REMOVAL.

THE CONTRACTOR WILL ACCEPT OWNERSHIP OF ALL OTHER MATERIALS (SIGNAL HEADS, CABLES, PUSHBUTTONS, SIGNS, ETC.) AND SHALL DISPOSE OF PROPERLY.

- TRAFFIC SIGNAL REMOVAL NOTES
LIST ITEMS TO BE REMOVED: (SUBSIDIARY TO ITEM 680 6004 REMOVING TRAFFIC SIGNALS)
1. REMOVE 5 SECTION SIGNAL HEADS AND BACKPLATES, SIGNAL HEADS 4,8,12,16
 2. REMOVE PEDESTRIAN SIGNALS AND PUSHBUTTONS AND SIGNS
 3. REMOVE TRAFFIC SIGNAL CONTROL CABINET (FOUNDATION TO BE RE-USED)
 4. REMOVE (4) SIGNS S5-PROTECTED LEFT ON GREEN ARROW
 5. REMOVE SIGNAL CONDUCTORS FROM CABINET TO POLE
 6. REMOVE SIGNAL CONDUCTORS IN POLES FOR 4 SECTION HEADS, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS

DATE: 2/9/2024
FILE: ST15



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	MP	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	MP	AMA	POTTER	39	

PROPOSED SIGNAL HEAD



3,7,10,14

PROPOSED SIGNAL HEADS AND SIGNS



PSH1-PSH8



R10-3e (R)



R10-3e (L)



R10-XR



R10-XL

PB1 - PB8


PROPOSED MAST ARM MOUNTED SIGN



R10-17T
30X30

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- CONDUIT RUN
- SIGNAL HEAD
- ELECTRICAL SERVICE
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- ITERIS DETECTOR
- SIGNAL POLE



- TRAFFIC SIGNAL INSTALLATION NOTES:
1. REPLACE SIGNAL (5 SECTION HEAD) TO (4 SECTION HEAD) FOR LEFT TURNS.
 2. INSTALL VIDEO IMAGING AND RADAR DETECTORS. SYSTEM, AND CABLING.
 3. REPLACE ALL PEDESTRIAN STANDARDS, SIGNS AND SIGNAL HEADS.
 4. REPLACE CONTROL CABINET TO (TS-TY 2) (REUSE EXISTING CABINET CONTROLLER AND FOUNDATION)
 5. ALL SIGNAL EQUIPMENT PROVIDED BY CONTRACTORS SHALL BE COMPATIBLE WITH CITY OF AMARILLO'S SIEMENS-TACTICS CENTRAL SOFTWARE AND ITERIS VANTAGE VECTOR DETECTOR.
 6. REPLACE ALL SIGNAL CONDUCTORS FROM CABINET TO SIGNALPOLE
 7. REPLACE SIGNAL CONDUCTORS IN POLE FOR 4 SECTION HEAD, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS.
 8. ALL CONDUITS WILL REMAIN IN PLACE
 9. EXISTING SERVICE POLE AND METER TO REMAI IN PLACE



Dawood Alani
2/9/2024

ARTHUR AT 10TH
PROPOSED
SIGNAL
LAYOUT

SCALE: 1" = 40'



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	40	

SUMMARY OF CABLES INSIDE POLES & MAST ARMS					
POLE NO.	ATTACHMENT	ITEM 0684	ITEM 0684	ITEM 0684	ITEM 6083 - VIDEO
		TRAFFIC SIGNAL CABLE 6080	TRAFFIC SIGNAL CABLE 6031	TRAFFIC SIGNAL CABLE 6033	IMAGING RAD. VEH DETECT. 6005
		(TY C) (14 AWG) (2 CONDR)	(TY A) (14 AWG) (5 CONDR)	(TY A) (14 AWG) (7 CONDR)	COMMUNICATION CABLE (COAXIAL)
		LF	LF	LF	LF
SP-A					
	SIGNAL 3			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB2	10			
	PB8	10			
	PSH-2		15		
	PSH-8		15		
SP-B					
	SIGNAL 7			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB6	10			
	PB8	10			
	PSH-6		15		
	PSH-8		15		
SP-C					
	SIGNAL 10			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB4	10			
	PB6	10			
	PSH-4		15		
	PSH-6		15		
SP-D					
	SIGNAL 14			70	
	VIDEO IMAGING AND RADAR DETECTOR				60
	PB2	10			
	PB4	10			
	PSH-2		15		
	PSH-4		15		
	TOTAL:	80	120	280	270

RUN NO.	LENGTH	EXISTING CONDUIT		ITEM 0620 -		ITEM 0684 -		ITEM 0620 -		ITEM 0620 -		ITEM 6083 - VIDEO IMAGING RAD VEH DETECT.	
				6010		6046		6007		6009		6005	
		ELEC CONDR (NO 6) INSULATED		TRF SIG CBL (TY A)(14 AWG)(20 CONDR)		ELEC CONDR (NO. 8) BARE		ELEC CONDR (NO. 6) BARE		COMMUNICATION CABLE (COAXIAL)			
		EA	LF	EA	LF	EA	LF	EA	LF	EA	LF	EA	LF
1	10	1	10	2	20					1	10		
2	100	1	100	2	200					1	100		
3	10	1	10			1	10	1	10			1	10
4	80	1	80			2	160	1	80			2	160
5	10	1	10			1	10	1	10			1	10
6	75	1	75			1	75	1	75			1	75
7	10	1	10			1	10	1	10			1	10
8	85	1	85			1	85	1	85			1	85
9	15	1	15			1	15	1	15			1	15
10	15	1	15	2	30	4	60	1	15	1	15	4	60
TOTAL:	410		410		250		425		300		125		425



Dawood Alani
2/9/2021

**ARTHUR AT 10TH
PROPOSED SIGNAL
WIRING**




Texas Department of Transportation


SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	41	

PHASING DIAGRAM



PHASING DIAGRAM



1,3,5,7 ARE PROTECTED/PERMISSIVE FLASHING YELLOW



Dawood Alani
2/9/2024



ARTHUR AT 10TH
PROPOSED TRAFFIC
SIGNAL DETAILS

SCALE: N.T.S



SHEET 1 OF 1

CONSTRUCTION NOTE:
1. A REPRESENTATIVE FROM THE CITY OF AMARILLO MUST BE PRESENT TO VERIFY THE REWIRING OF THE NEW CABINET TO THE FIELD WIRES AND TO CONFIGURE THE CONTROLLER PROGRAMMING PRIOR TO REACTIVATION OF THE SIGNAL

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	42	

ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
ARTHUR AT 10TH			
TOTAL	300	125	250

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
ARTHUR AT 10TH					
TOTAL	1	1	4	8	1


** SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN) LED (GRN ARW)	VEH SIG SEC (12 IN) LED (YEL ARW)	VEH SIG SEC (12 IN) LED (RED ARW)	PED SIG SEC (LED)(COUNT DOWN)	BACK PLATE W/REF BRDR (4 SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
ARTHUR AT 10TH									
TOTAL	4	8	4	8	4	120	280	425	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET-UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
ARTHUR AT 10TH					
TOTAL	8	1	4	1	695



Dawood Alani
2/9/2024



ARTHUR AT 10TH

SUMMARY OF QUANTITIES





DSN	CK	CONT	SECT	JOB	HEWKEY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	43	

STIMES

DATE: 02/09/2024
FILE: 0904

TRAFFIC SIGNAL HEADS



1,2,3,5,6,7,9,10,
11,13,14,15

4,12

8,16

PEDESTRIAN SIGNS



R10-XR




R10-XL




PSH1-PSH8

PB1 - PB4

LEGEND:



MAST ARM & POLE
CONTROLLER CABINET
PULL BOX
CONDUIT
SIGNAL HEAD
POWER SOURCE
LOOP DETECTOR
PEDESTRIAN SIGNAL HEAD
PEDESTRIAN PUSH BUTTON
SIGNAL POLE



NOTES:

THE SALVAGEABLE MATERIALS REMOVED (CONTROLLER CABINET AND CONTENTS, SHALL BE DELIVERED TO THE CITY OF AMARILLO SIGNAL YARD IN AMARILLO (800 SE 23RD AVE) AT TIME OF REMOVAL.

THE CONTRACTOR WILL ACCEPT OWNERSHIP OF ALL OTHER MATERIALS (SIGNAL HEADS, CABLES, PUSHBUTTONS, SIGNS, ETC.) AND SHALL DISPOSE OF PROPERLY.

TRAFFIC SIGNAL REMOVAL NOTES

LIST ITEMS TO BE REMOVED: (SUBSIDIARY TO ITEM 680 6004 REMOVING TRAFFIC SIGNALS)

1. REMOVE 5 SECTION SIGNAL HEADS AND BACKPLATES, SIGNAL HEADS 4,8,12,16
2. REMOVE PEDESTRIAN SIGNALS AND PUSHBUTTONS AND SIGNS
3. REMOVE TRAFFIC SIGNAL CONTROL CABINET (FOUNDATION TO BE RE-USED)
4. REMOVE (4) SIGNS S5-PROTECTED LEFT ON GREEN ARROW
5. REMOVE SIGNAL CONDUCTORS FROM CABINET TO POLE
6. REMOVE SIGNAL CONDUCTORS IN POLES FOR 4 SECTION HEADS, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS



Dawood Alani
2/9/2024

GEORGIA AT WOLFLIN
EXISTING
SIGNAL
LAYOUT

SCALE: 1" = 40'



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	44	



DATE: 2/9/2024
FILE: S1E1

PROPOSED SIGNAL HEAD



8, 16

PROPOSED SIGNAL HEADS AND SIGNS



PSH1-PSH8



R10-3e (R)



R10-XR



R10-3e (L)



R10-XL

PB1 - PB8


PROPOSED MAST ARM MOUNTED SIGN



R10-17T
30X30

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- CONDUIT RUN
- SIGNAL HEAD
- ELECTRICAL SERVICE
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- ITERIS DETECTOR
- SIGNAL POLE



TRAFFIC SIGNAL INSTALLATION NOTES:

1. REPLACE SIGNAL (5 SECTION HEAD) TO (4 SECTION HEAD) FOR LEFT TURNS.
2. INSTALL VIDEO IMAGING AND RADAR DETECTORS, SYSTEM, AND CABLING.
3. REPLACE ALL PEDESTRIAN STANDARDS, SIGNS AND SIGNAL HEADS.
4. REPLACE CONTROL CABINET TO (TS-TY 2) (REUSE EXISTING CABINET CONTROLLER AND FOUNDATION)
5. ALL SIGNAL EQUIPMENT PROVIDED BY CONTRACTORS SHALL BE COMPATIBLE WITH CITY OF AMARILLO'S SIEMENS-TACTICS CENTRAL SOFTWARE AND ITERIS VANTAGE VECTOR DETECTOR.
6. REPLACE ALL SIGNAL CONDUCTORS FROM CABINET TO SIGNAL POLE
7. REPLACE SIGNAL CONDUCTORS IN POLE FOR 4 SECTION HEAD, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS.
8. ALL CONDUITS WILL REMAIN IN PLACE
9. EXISTING SERVICE POLE AND METER TO REMAI IN PLACE



Signature
2/9/2020



GEORGIA AT WOLFLIN
PROPOSED
SIGNAL
LAYOUT


SCALE: 1" = 40'




SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	45	


PHASING DIAGRAM



PHASING DIAGRAM



1,3,5,7 ARE PROTECTED/PERMISSIVE FLASHING YELLOW



[Signature]
2/19/2022



GEORGIA AT WOLFLIN
PROPOSED TRAFFIC
SIGNAL DETAILS

SCALE: N.T.S




SHEET 1 OF 1


CONSTRUCTION NOTE:
1. A REPRESENTATIVE FROM THE CITY OF AMARILLO MUST BE PRESENT TO VERIFY THE REWIRING OF THE NEW CABINET TO THE FIELD WIRES AND TO CONFIGURE THE CONTROLLER PROGRAMMING PRIOR TO REACTIVATION OF THE SIGNAL

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	47	


PHASING DIAGRAM



PHASING DIAGRAM



1,3,5,7 ARE PROTECTED/PERMISSIVE FLASHING YELLOW



[Handwritten Signature]
2/19/2022

GEORGIA AT WOLFLIN
PROPOSED TRAFFIC
SIGNAL DETAILS

SCALE: N.T.S



SHEET 1 OF 1



CONSTRUCTION NOTE:
1. A REPRESENTATIVE FROM THE CITY OF AMARILLO MUST BE PRESENT TO VERIFY THE REWIRING OF THE NEW CABINET TO THE FIELD WIRES AND TO CONFIGURE THE CONTROLLER PROGRAMMING PRIOR TO REACTIVATION OF THE SIGNAL

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	47	

ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
GEORGIA AT WOLFLIN			
TOTAL	525	30	60

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
GEORGIA AT WOLFLIN					
TOTAL	1	1	2	8	1


**SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN)LED (GRN ARW)	VEH SIG SEC (12 IN)LED (YEL ARW)	VEH SIG SEC (12 IN)LED (RED ARW)	PED SIG SEC (LED)(COUNT DOWN)	BACK PLATE W/REF BRDR (4 SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
GEORGIA AT WOLFLIN									
TOTAL	2	4	2	4	2	120	260	525	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET- UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
GEORGIA AT WOLFLIN					
TOTAL	8	1	4	1	785



Dawood Alani
2/19/2021




GEORGIA AT WOLFLIN

SUMMARY OF
QUANTITIES



BSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
BSN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	48	

TRAFFIC SIGNAL HEADS




1,2,3,5,6,8,9,11,12,13



3,7,10,14

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- SIGNAL HEAD
- POWER SOURCE
- LOOP DETECTOR
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- SIGNAL POLE



NOTES:

THE SALVAGEABLE MATERIALS REMOVED (CONTROLLER CABINET AND CONTENTS, SHALL BE DELIVERED TO THE CITY OF AMARILLO SIGNAL YARD IN AMARILLO (800 SE 23RD AVE) AT TIME OF REMOVAL.

THE CONTRACTOR WILL ACCEPT OWNERSHIP OF ALL OTHER MATERIALS (SIGNAL HEADS, CABLES, PUSHBUTTONS, SIGNS, ETC.) AND SHALL DISPOSE OF PROPERLY.

TRAFFIC SIGNAL REMOVAL NOTES

- LIST ITEMS TO BE REMOVED:(SUBSIDIARY TO ITEM 680 6004 REMOVING TRAFFIC SIGNALS)
1. REMOVE 5 SECTION SIGNAL HEADS AND BACKPLATES, SIGNAL HEADS 4,8,12,16
 2. REMOVE PEDESTRIAN SIGNALS AND PUSHBUTTONS AND SIGNS
 3. REMOVE TRAFFIC SIGNAL CONTROL CABINET (FOUNDATION TO BE RE-USED)
 4. REMOVE (4) SIGNS S5-PROTECTED LEFT ON GREEN ARROW
 5. REMOVE SIGNAL CONDUCTORS FROM CABINET TO POLE
 6. REMOVE SIGNAL CONDUCTORS IN POLES FOR 4 SECTION HEADS, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS



Dawood Alani
2/9/2024



GEORGIA AT 58TH
EXISTING
SIGNAL
LAYOUT

SCALE: 1" = 40'



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	49	

STAGES

DATE: 02/09/2024
FILE: 214-00-001

PROPOSED SIGNAL HEAD



3,7,10,14

PROPOSED SIGNAL HEADS AND SIGNS



PSH1-PSH8



R10-3e (R)



R10-3e (L)



R10-XR



R10-XL

PB1 - PB8


PROPOSED MAST ARM MOUNTED SIGN

S5




R10-17T
30X30

LEGEND:



MAST ARM & POLE
CONTROLLER CABINET
PULL BOX
CONDUIT
CONDUIT RUN
SIGNAL HEAD
ELECTRICAL SERVICE
PEDESTRIAN SIGNAL HEAD
PEDESTRIAN PUSH BUTTON
ITERIS DETECTOR
SIGNAL POLE



TRAFFIC SIGNAL INSTALLATION NOTES:

1. REPLACE SIGNAL (5 SECTION HEAD) TO (4 SECTION HEAD) FOR LEFT TURNS.
2. INSTALL VIDEO IMAGING AND RADAR DETECTORS, SYSTEM, AND CABLING.
3. REPLACE ALL PEDESTRIAN STANDARDS, SIGNS AND SIGNAL HEADS.
4. REPLACE CONTROL CABINET TO (TS-TY 2) (REUSE EXISTING CABINET CONTROLLER AND FOUNDATION)
5. ALL SIGNAL EQUIPMENT PROVIDED BY CONTRACTORS SHALL BE COMPATIBLE WITH CITY OF AMARILLO'S SIEMENS-TACTICS CENTRAL SOFTWARE AND ITERIS VANTAGE VECTOR DETECTOR.
6. REPLACE ALL SIGNAL CONDUCTORS FROM CABINET TO SIGNALPOLE
7. REPLACE SIGNAL CONDUCTORS IN POLE FOR 4 SECTION HEAD, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS.
8. ALL CONDUITS WILL REMAIN IN PLACE
9. EXISTING SERVICE POLE AND METER TO REMAI IN PLACE



Dawood Alani
2/19/2024

AMARILLO
TRAFFIC ENGINEERING

GEORGIA AT 58TH
PROPOSED
SIGNAL
LAYOUT

SCALE: 1" = 40'



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	50	

SUMMARY OF CABLES INSIDE POLES & MAST ARMS					
POLE NO.	ATTACHMENT	ITEM 0684 TRAFFIC SIGNAL CABLE 6080	ITEM 0684 TRAFFIC SIGNAL CABLE 6031	ITEM 0684 TRAFFIC SIGNAL CABLE 6033	ITEM 6083 - VIDEO IMAGING RAD. VEH DETECT. 6005
		(TY C) (14 AWG) (2 CONDR)	(TY A) (14 AWG) (5 CONDR)	(TY A) (14 AWG) (7 CONDR)	COMMUNICATION CABLE (COAXIAL)
		LF	LF	LF	LF
SP-A	SIGNAL 3			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB2	10			
	PB8	10			
	PSH-2		15		
	PSH-8		15		
SP-B	SIGNAL 7			60	
	VIDEO IMAGING AND RADAR DETECTOR				60
	PB6	10			
	PB8	10			
	PSH-6		15		
	PSH-8		15		
SP-C	SIGNAL 10			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB4	10			
	PB6	10			
	PSH-4		15		
	PSH-6		15		
SP-D	SIGNAL 14			60	
	VIDEO IMAGING AND RADAR DETECTOR				60
	PB2	10			
	PB4	10			
	PSH-2		15		
	PSH-4		15		
	TOTAL:	80	120	260	260

RUN NO.	LENGTH	EXISTING CONDUIT		ITEM 0620 -		ITEM 0684 -		ITEM 0620 -		ITEM 0620 -		ITEM 6083 - VIDEO IMAGING RAD VEH DETECT.	
				6010		6046		6007		6009		6005	
		ELEC CONDR (NO 6) INSULATED	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	EA	LF	EA	LF	EA	LF	EA	LF
1	20	1	20	2	40	4	80	1	20	1	20	4	80
2	25	1	25	2	50					1	25		
3	35	1	35			4	140	1	35			4	140
4	15	1	15			1	15	1	15			1	15
5	75	1	75			3	225	1	75			3	225
6	15	1	15			1	15	1	15			1	15
7	75	1	75			2	150	1	75			2	150
8	15	1	15			1	15	1	15			1	15
9	70	1	70			1	70	1	70			1	70
10	20	1	20			1	20	1	20			1	20
TOTAL:	365		365		90		730		340		45		730



Dawood Alani
2/9/2011



**GEORGIA AT 58TH
PROPOSED SIGNAL
WIRING**



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	51	


ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
GEORGIA AT 58TH			
TOTAL	340	45	90

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
GEORGIA AT 58TH					
TOTAL	1	1	4	8	1


**SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN)LED (GRN ARW)	VEH SIG SEC (12 IN)LED (YEL ARW)	VEH SIG SEC (12 IN)LED (RED ARW)	PED SIG SEC (LED)COUNT DOWN)	BACK PLATE W/REF BRDR (4" SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
GEORGIA AT 58TH									
TOTAL	4	8	4	8	4	120	260	730	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET- UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
GEORGIA AT 58TH					
TOTAL	8	1	4	1	990



Dawood Alani
2/9/2024



GEORGIA AT 58TH

SUMMARY OF
QUANTITIES



DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	53	


ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
GEORGIA AT 58TH			
TOTAL	340	45	90

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
GEORGIA AT 58TH					
TOTAL	1	1	4	8	1


**SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN)LED (GRN ARW)	VEH SIG SEC (12 IN)LED (YEL ARW)	VEH SIG SEC (12 IN)LED (RED ARW)	PED SIG SEC (LED)COUNT DOWN)	BACK PLATE W/REF BRDR (4 SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
GEORGIA AT 58TH									
TOTAL	4	8	4	8	4	120	260	730	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET- UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
GEORGIA AT 58TH					
TOTAL	8	1	4	1	990



Dawood Alani
2/9/2024





GEORGIA AT 58TH

SUMMARY OF QUANTITIES



DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	53	

TRAFFIC SIGNAL HEADS



PEDESTRIAN SIGNS




PB1 - PB4



PSH1-PSH8

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- SIGNAL HEAD
- POWER SOURCE
- LOOP DETECTOR
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- SIGNAL POLE



NOTES:

THE SALVAGEABLE MATERIALS REMOVED (CONTROLLER CABINET AND CONTENTS, SHALL BE DELIVERED TO THE CITY OF AMARILLO SIGNAL YARD IN AMARILLO (800 SE 23RD AVE) AT TIME OF REMOVAL.

THE CONTRACTOR WILL ACCEPT OWNERSHIP OF ALL OTHER MATERIALS (SIGNAL HEADS, CABLES, PUSHBUTTONS, SIGNS, ETC.) AND SHALL DISPOSE OF PROPERLY.

TRAFFIC SIGNAL REMOVAL NOTES

- LIST ITEMS TO BE REMOVED: (SUBSIDIARY TO ITEM 680 6004 REMOVING TRAFFIC SIGNALS)
1. REMOVE 5 SECTION SIGNAL HEADS AND BACKPLATES, SIGNAL HEADS 4,8,12,16
 2. REMOVE PEDESTRIAN SIGNALS AND PUSHBUTTONS AND SIGNS
 3. REMOVE TRAFFIC SIGNAL CONTROL CABINET (FOUNDATION TO BE RE-USED)
 4. REMOVE (4) SIGNS S5-PROTECTED LEFT ON GREEN ARROW
 5. REMOVE SIGNAL CONDUCTORS FROM CABINET TO POLE
 6. REMOVE SIGNAL CONDUCTORS IN POLES FOR 4 SECTION HEADS, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS



Dawood Alani
2/19/2024



VIRGINIA AT 45TH
EXISTING
SIGNAL
LAYOUT

SCALE: 1" = 40'



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	MP	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	MP	AMA	POTTER	54	

STIMES

DATE: 2/19/2024
FILE: STIMES

PROPOSED SIGNAL HEAD



3,7,10,14

PROPOSED SIGNAL HEADS AND SIGNS



PSH1-PSH8



R10-3e (R)



R10-3e (L)



R10-XR



R10-XL

PB1 - PB8

PROPOSED MAST ARM MOUNTED SIGN


S5



R10-17T
30X30

LEGEND:

- MAST ARM & POLE
- CONTROLLER CABINET
- PULL BOX
- CONDUIT
- CONDUIT RUN
- SIGNAL HEAD
- ELECTRICAL SERVICE
- PEDESTRIAN SIGNAL HEAD
- PEDESTRIAN PUSH BUTTON
- ITERIS DETECTOR
- SIGNAL POLE



TRAFFIC SIGNAL INSTALLATION NOTES:

1. REPLACE SIGNAL (5 SECTION HEAD) TO (4 SECTION HEAD) FOR LEFT TURNS.
2. INSTALL VIDEO IMAGING AND RADAR DETECTORS. SYSTEM, AND CABLING.
3. REPLACE ALL PEDESTRIAN STANDARDS, SIGNS AND SIGNAL HEADS.
4. REPLACE CONTROL CABINET TO (TS-TY 2) (REUSE EXISTING CABINET CONTROLLER AND FOUNDATION)
5. ALL SIGNAL EQUIPMENT PROVIDED BY CONTRACTORS SHALL BE COMPATIBLE WITH CITY OF AMARILLO'S SIEMENS-TACTICS CENTRAL SOFTWARE AND ITERIS VANTAGE VECTOR DETECTOR.
6. REPLACE ALL SIGNAL CONDUCTORS FROM CABINET TO SIGNALPOLE
7. REPLACE SIGNAL CONDUCTORS IN POLE FOR 4 SECTION HEAD, PEDESTRIAN HEADS AND PEDESTRIAN PUSH BUTTONS.
8. ALL CONDUITS WILL REMAIN IN PLACE
9. EXISTING SERVICE POLE AND METER TO REMAI IN PLACE



Dawood Alani
2/9/2024



VIRGINIA AT 45TH
PROPOSED
SIGNAL
LAYOUT

SCALE: 1" = 40'

Texas Department of Transportation

SHEET 1 OF 1


DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	55	

SUMMARY OF CABLES INSIDE POLES & MAST ARMS					
POLE NO.	ATTACHMENT	ITEM 0684	ITEM 0684	ITEM 0684	ITEM 6083 - VIDEO
		TRAFFIC SIGNAL CABLE 6080	TRAFFIC SIGNAL CABLE 6031	TRAFFIC SIGNAL CABLE 6033	IMAGING RAD VEH DETECT. 6005
		(TY C) (14 AWG) (2 CONDR)	(TY A) (14 AWG) (5 CONDR)	(TY A) (14 AWG) (7 CONDR)	COMMUNICATION CABLE (COAXIAL)
		LF	LF	LF	LF
SP-A	SIGNAL 3			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB2	10			
	PB8	10			
	PSH-2		15		
	PSH-8		15		
SP-B	SIGNAL 7			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB6	10			
	PB8	10			
	PSH-6		15		
	PSH-8		15		
SP-C	SIGNAL 10			70	
	VIDEO IMAGING AND RADAR DETECTOR				70
	PB4	10			
	PB6	10			
	PSH-4		15		
	PSH-6		15		
SP-D	SIGNAL 14			70	
	VIDEO IMAGING AND RADAR DETECTOR				60
	PB2				
	PB4				
	PSH-2		15		
	PSH-4		15		
SP-E	SIGNAL				
	VIDEO IMAGING AND RADAR DETECTOR				
	PB2	10			
	PB4	10			
	PSH-2		15		
	PSH-4		15		
	TOTAL:	80	120	280	270

RUN NO.	LENGTH	EXISTING CONDUIT		ITEM 0620 - 6010		ITEM 0684 - 6046		ITEM 0620 - 6007		ITEM 0620 - 6009		ITEM 6083 - VIDEO IMAGING RAD VEH DETECT. 6005	
		EA	LF	ELEC CONDR (NO 6) INSULATED		TRF SIG CBL (TY A)(14 AWG)(20 CONDR)		ELEC CONDR (NO. 8) BARE		ELEC CONDR (NO. 6) BARE		COMMUNICATION CABLE (COAXIAL)	
				EA	LF	EA	LF	EA	LF	EA	LF	EA	LF
1	30	1	30	2	60					1	30		
2	15	1	15	2	30	4	60	4	60	1	15	4	60
3	20	1	70			4	280	4	280			4	280
4	20	1	20			1	20	1	20			1	20
5	20	1	20			1	20	1	20			1	20
6	55	1	55			1	55	1	55			1	55
7	75	1	75			2	150	2	150			2	150
8	20	1	20			1	20	1	20			1	20
9	75	1	75			1	75	1	75			1	75
10	30	1	30			1	30	1	30			1	30
11	30	1	30			4	120	4	120			4	120
12	20	1	20			1	20	1	20			1	20
TOTAL:	410		410		90		850		850		45		850




(Handwritten signature)
2/19/2014




**VIRGINIA AT 45TH
PROPOSED SIGNAL
WIRING**

Texas Department of Transportation					
SHEET 1 OF 1					
DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY		SHEET NO.
MP	DA	AMA	POTTER		56

PHASING DIAGRAM



PHASING DIAGRAM



1,3,5,7 ARE PROTECTED/PERMISSIVE FLASHING YELLOW

CONSTRUCTION NOTE:
 1. A REPRESENTATIVE FROM THE CITY OF AMARILLO MUST BE PRESENT TO VERIFY THE REWIRING OF THE NEW CABINET TO THE FIELD WIRES AND TO CONFIGURE THE CONTROLLER PROGRAMMING PRIOR TO REACTIVATION OF THE SIGNAL



Dawood Alani
 2/19/2024



VIRGINIA AT 45TH
 PROPOSED TRAFFIC
 SIGNAL DETAILS

SCALE: N.T.S



SHEET 1 OF 1

DSN	CK	CONT	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DRWN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	57	


ITEM CODE	0620-6007	0620-6009	0620-6010
DESCRIPTION	ELEC CONDR (NO. 8) BARE	ELEC CONDR (NO. 6) BARE	ELEC CONDR (NO. 6) INSULATED
	LF	LF	LF
VIRGINIA AT 45TH			
TOTAL	850	45	90

ITEM CODE	0680-6003	**	**	**	0680-6004
DESCRIPTION	INSTALL HWY TRF SIG (SYSTEM)	TRAFFIC SIGNAL CABINET (TS2-TYP2)	LEFT TURN YIELD ON FLASHING YELLOW ARW SIGN	R10-3E PED PB SIGN	REMOVING TRAFFIC SIGNALS
	EA	EA	EA	EA	EA
VIRGINIA AT 45TH					
TOTAL	1	1	4	8	1

** SUBSIDIARY TO BID ITEM 680 6003

ITEM CODE	0682-6002	0682-6004	0682-6006	0682-6018	0682-6055	0684-6031	0684-6033	0684-6046	0684-6080
DESCRIPTION	VEH SIG SEC (12 IN) LED (GRN ARW)	VEH SIG SEC (12 IN) LED (YEL ARW)	VEH SIG SEC (12 IN) LED (RED ARW)	PED SIG SEC (LED)(COUNT DOWN)	BACK PLATE W/REF BRDR (4 SEC) (VEN)ALUM	TRF SIG CBL (TY A)(14 AWG)(5 CONDR)	TRF SIG CBL (TY A)(14 AWG)(7 CONDR)	TRF SIG CBL (TY A)(14 AWG)(20 CONDR)	TRF SIG CBL (TY C)(14 AWG)(2 CONDR)
	EA	EA	EA	EA	EA	LF	LF	LF	LF
VIRGINIA AT 45TH									
TOTAL	4	8	4	8	4	120	280	850	80

ITEM CODE	0688-6002	6083-6002	6083-6003	6083-6004	6083-6005
DESCRIPTION	PED DETECT PUSH BUTTON (STANDARD)	VID IMAGE AND RADAR DET PROCESSOR SYS	VIDEO IMAGING AND RADAR DETECTOR	VIDEO IMAGING AND RADAR SET- UP SYS	VIDEO IMAGE AND RADAR COM CABLE (COAX)
	EA	EA	EA	EA	LF
VIRGINIA AT 45TH					
TOTAL	8	1	4	1	1120



Dawood Alani
2/19/2024



VIRGINIA AT 45TH

**SUMMARY OF
QUANTITIES**



DSN	CK	CONF	SECT	JOB	HIGHWAY
MP	DA	0904	00	214	VARIOUS
DSN	CK	DIST	COUNTY	SHEET NO.	
MP	DA	AMA	POTTER	58	

STIMES



DATE: 2/19/2024
FILE: 5815

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

REQUIREMENTS FOR INDEPENDENT MOUNTED ROUTE SIGNS




SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	WHITE	TYPE A SHEETING
BACKGROUND	ALL OTHERS	TYPE B OR C SHEETING
LEGEND & BORDERS	WHITE	TYPE A SHEETING
LEGEND & BORDERS	BLACK	ACRYLIC NON-REFLECTIVE FILM
LEGEND & BORDERS	ALL OTHERS	TYPE B or C SHEETING



TYPICAL EXAMPLES

REQUIREMENTS FOR BLUE, BROWN & GREEN D AND I SERIES GUIDE SIGNS

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	ALL	TYPE B OR C SHEETING
LEGEND & BORDERS	WHITE	TYPE D SHEETING
LEGEND, SYMBOLS & BORDERS	ALL OTHERS	TYPE B OR C SHEETING



TYPICAL EXAMPLES

GENERAL NOTES

- Signs to be furnished shall be as detailed elsewhere in the plans and/or as shown on sign tabulation sheet. Standard sign designs and arrow dimensions can be found in the "Standard Highway Sign Designs for Texas" (SHSD).
- White legend shall use the Clearview Alphabet. The following Clearview fonts shall be used to replace the existing white Federal Highway Administration (FHWA) Standard Highway Alphabets, when not specified in the SHSD, or in the plans.

B	CV-1W
C	CV-2W
D	CV-3W
E	CV-4W
Emod	CV-5WR
F	CV-6W

- Route sign legend (ie. IH, US, SH and FM shields) shall use the Federal Highway Administration (FHWA) Standard Highway Alphabets B, C, D, E, Emod or F).
- Lateral spacing between letters and numerals shall conform with the SHSD, and any approved changes thereto. Lateral spacing of legend shall provide a balanced appearance when spacing is not shown.
- Independent mounted route sign with white or colored legend and borders shall be applied by screening process with transparent color ink, transparent colored overlay film to white background sheeting or cut-out white sheeting to colored background sheeting, or combination thereof. White legend, symbols and borders on all other signs shall be cut-out white sheeting applied to colored background sheeting.
- Information regarding borders and radii for signs is found in the "Standard Highway Sign Designs for Texas". Dimensions shown and described for borders and corner radii on parent sign are nominal. Borders may vary in width as much as 1/2 inch. Corner radii above 3 inches may vary in width as much as 1 inch. Borders and corner radii within a parent sign must be of matching widths. The sign area outside the corner radius should be trimmed or rounded.
- Sign substrate shall be any material that meets the Departmental Material Specification requirements of DMS-7110 or approved alternative.
- Mounting details of roadside signs are shown in the "SMD series" Standard Plan Sheets.

DEPARTMENTAL MATERIAL SPECIFICATIONS	
ALUMINUM SIGN BLANKS	DMS-7110
SIGN FACE MATERIALS	DMS-8300

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080
7.5 to 15	0.100
Greater than 15	0.125

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.

<http://www.txdot.gov/>


Texas Department of Transportation		<i>Traffic Operations Division Standard</i>
<h1 style="margin: 0;">TYPICAL SIGN REQUIREMENTS</h1> <h2 style="margin: 0;">TSR(3) - 13</h2>		
FILE: tsr3-13.dgn	DN: TxDOT	CK: TxDOT
© TxDOT October 2003	CONT SECT	JOB HIGHWAY
REVISIONS	0904 00	214 VARIOUS
12-03 7-13	DIST COUNTY	SHEET NO.
9-08	AMA POTTER	59

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

REQUIREMENTS FOR RED BACKGROUND REGULATORY SIGNS

(STOP, YIELD, DO NOT ENTER AND WRONG WAY SIGNS)



REQUIREMENTS FOR FOUR SPECIFIC SIGNS ONLY

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	WHITE	TYPE B OR C SHEETING
LEGEND & BORDERS	WHITE	TYPE B OR C SHEETING
LEGEND	RED	TYPE B OR C SHEETING

REQUIREMENTS FOR WHITE BACKGROUND REGULATORY SIGNS


(EXCLUDING STOP, YIELD, DO NOT ENTER AND WRONG WAY SIGNS)



TYPICAL EXAMPLES

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	WHITE	TYPE A SHEETING
BACKGROUND	ALL OTHERS	TYPE B OR C SHEETING
LEGEND, BORDERS AND SYMBOLS	BLACK	ACRYLIC NON-REFLECTIVE FILM
LEGEND, BORDERS AND SYMBOLS	ALL OTHER	TYPE B OR C SHEETING

REQUIREMENTS FOR WARNING SIGNS



TYPICAL EXAMPLES

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	FLOURESCENT YELLOW	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDERS	BLACK	ACRYLIC NON-REFLECTIVE FILM
LEGEND & SYMBOLS	ALL OTHER	TYPE B OR C SHEETING

REQUIREMENTS FOR SCHOOL SIGNS



TYPICAL EXAMPLES

SHEETING REQUIREMENTS		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	WHITE	TYPE A SHEETING
BACKGROUND	FLOURESCENT YELLOW GREEN	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND, BORDERS AND SYMBOLS	BLACK	ACRYLIC NON-REFLECTIVE FILM
SYMBOLS	RED	TYPE B OR C SHEETING

GENERAL NOTES

- Signs to be furnished shall be as detailed elsewhere in the plans and/or as shown on sign tabulation sheet. Standard sign designs and arrow dimensions can be found in the "Standard Highway Sign Designs for Texas" (SHSD).
- Sign legend shall use the Federal Highway Administration (FHWA) Standard Highway Alphabets (B, C, D, E, Emod or F).
- Lateral spacing between letters and numerals shall conform with the SHSD, and any approved changes thereto. Lateral spacing of legend shall provide a balanced appearance when spacing is not shown.
- Black legend and borders shall be applied by screening process or cut-out acrylic non-reflective black film to background sheeting, or combination thereof.
- White legend and borders shall be applied by screening process with transparent colored ink, transparent colored overlay film to white background sheeting or cut-out white sheeting to colored background sheeting, or combination thereof.
- Colored legend shall be applied by screening process with transparent colored ink, transparent colored overlay film or colored sheeting to background sheeting, or combination thereof.
- Sign substrate shall be any material that meets the Departmental Material Specification requirements of DMS-7110 or approved alternative.
- Mounting details for roadside mounted signs are shown in the "SMD series" Standard Plan Sheets.

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080
7.5 to 15	0.100
Greater than 15	0.125

DEPARTMENTAL MATERIAL SPECIFICATIONS	
ALUMINUM SIGN BLANKS	DMS-7110
SIGN FACE MATERIALS	DMS-8300

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website:
<http://www.txdot.gov/>

		<i>Traffic Operations Division Standard</i>	
<h2>TYPICAL SIGN REQUIREMENTS</h2>			
<h3>TSR(4) - 13</h3>			
FILE: tsr4-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT October 2003	CONT: 0904	SECT: 00	JOB: 214
REVISIONS			HIGHWAY: VARIOUS
12-03 7-13			DIST: COUNTY
9-08			SHEET NO. 60
	AMA	POTTER	

GENERAL NOTES FOR ALL ELECTRICAL WORK

1. The location of all conduits, junction boxes, ground boxes, and electrical services is diagrammatic and may be shifted to accommodate field conditions.
2. Provide new and unused materials. Ensure that all materials and installations comply with the applicable articles of the National Electrical Code (NEC), TxDOT standards and specifications, National Electrical Manufacturers Association (NEMA), and are listed by Underwriters Laboratories (UL) or a Nationally Recognized Testing Lab (NRTL). NRTLs such as Canadian Standard Association (CSA), Intertek Testing Services NA Inc., or FM Approvals LLC can be considered equivalent to UL. Where reference is made to NEMA listed devices, International Electrotechnical Commission (IEC) listed devices will not be considered an acceptable equal to a NEMA listed device. Acceptable devices may have both a NEMA and IEC listing. Faulty fabrication or poor workmanship in any material, equipment, or installation is justification for rejection. Replace or reinstall rejected material or equipment at no additional cost to the Department.
3. Miscellaneous nuts, bolts and hardware, except for high strength bolts, may be stainless steel when plans specify galvanized, provided the bolt size is 1/2 in. or less in diameter.
4. Provide the following test equipment as required by the Engineer to confirm compliance with the contract and the NEC: voltmeter, ammeter, megohm meter (1000 volt DC), ground resistance tester, torque wrenches, and torque screwdrivers. Ensure all equipment has been properly calibrated within the last year. Provide calibration certification to the Engineer upon request. Operate test equipment during inspection as requested by the Engineer.
5. Install grounding as shown on the plans and in accordance with the NEC. Ensure all metallic conduits; metal poles; luminaires; and metal enclosures are bonded to the equipment grounding conductor. Provide stranded bare copper or green insulated grounding conductors. Ground rods, connectors, and bonding jumpers are subsidiary to the various bid items.
6. When required by the Engineer, notify the Department in writing of materials from the Material Producers List (MPL) intended for use on each project. Prequalified materials are listed on the MPL on TxDOT's website under "Roadway Illumination and Electrical Supplies." No substitutions will be allowed for materials on this list.

CONDUIT

A. MATERIALS

1. Provide conduit, junction boxes, fittings, and hardware as per TxDOT Departmental Material Specification (DMS) 11030 "Conduit" and Item 618 "Conduit" of TxDOT's "Standard Specifications For Construction And Maintenance Of Highways, Streets, And Bridges," latest edition. Provide conduits listed under Item 618 on the MPL under "Roadway Illumination and Electrical Supplies." Provide conduit types according to the descriptive code or as shown on the plans. Do not substitute other types of conduits for those shown. Provide liquidtight flexible metal conduit (LFMC) when flexible conduit is called for on galvanized steel rigid metallic conduit (RMC) systems. Provide liquidtight flexible nonmetallic conduit (LFNC) when flexible conduit is called for on polyvinyl chloride (PVC) systems.
2. Provide galvanized steel RMC for all exposed conduits, unless otherwise shown on the plans. Properly bond all metal conduits.
3. Unless otherwise shown on the plans, provide junction boxes with a minimum size as shown in the following table, which applies to the greatest number of conductors entering the box through one conduit with no more than four conduits per box. When a mixture of conductor sizes is present, count the conductors as if all are of the larger size. For situations not applicable to the table, size junction boxes in accordance with NEC.

AWG	3 CONDUCTORS	5 CONDUCTORS	7 CONDUCTORS
#1	10" x 10" x 4"	12" x 12" x 4"	16" x 16" x 4"
#2	8" x 8" x 4"	10" x 10" x 4"	12" x 12" x 4"
#4	8" x 8" x 4"	10" x 10" x 4"	10" x 10" x 4"
#6	8" x 8" x 4"	8" x 8" x 4"	10" x 10" x 4"
#8	8" x 8" x 4"	8" x 8" x 4"	8" x 8" x 4"

4. Junction boxes with an internal volume of less than 100 cu. in. and supported by entering raceways must have threaded entries or hubs identified for the intended purpose and supported by connection of two or more rigid metal conduits. Secure conduit within 3 ft. of the enclosure or within 18 in. of the enclosure if all conduit entries are on the same side. Mechanically secure all junction boxes with an internal volume greater than 100 cu. inches.
5. Provide hot dipped galvanized cast iron or sand cast aluminum outlet boxes for junction boxes containing only 10 AWG or 12 AWG conductors. Do not use die cast aluminum boxes. Size outlet boxes according to the NEC.
6. Do not use intermediate metal conduit (IMC) or electrical metallic tubing (EMT) unless specifically required by the plan sheets. When EMT is called for, provide junction boxes made from galvanized steel sheeting, listed and approved for outdoor use, unless otherwise noted on the plans. Size all galvanized steel junction boxes in accordance with the NEC. Provide junction boxes for IMC conduit systems that meet the same requirements for junction boxes used with RMC systems.
7. Provide PVC junction boxes intended for outdoor use on PVC conduit systems, unless otherwise noted on the plans.


8. Provide PVC elbows in PVC conduit systems, unless otherwise shown on the plans. Use only a flat, high tensile strength polyester fiber pull tape for pulling conductors through the PVC conduit system. When galvanized steel RMC elbows are specifically called for in the plans and any portion of the RMC elbow is buried less than 18 in., ground the RMC elbow by means of a grounding bushing on a rigid metal extension. Grounding of the rigid metal elbow is not required if the entire RMC elbow is encased in a minimum of 2 in. of concrete. PVC extensions are allowed on these concrete encased rigid metal elbows. RMC or PVC elbows are subsidiary to various bid items.
9. When required, provide High-Density Polyethylene (HDPE) conduit with factory installed internal conductors according to Item 622 "Duct Cable." At the Contractor's request and with approval by the Engineer, substitute HDPE conduit with no conductors for bored schedule 40 or schedule 80 PVC conduit bid under Item 618. Ensure bored HDPE substituted for PVC is schedule 40 and of the same size PVC called for in the plans. Ensure the substituted HDPE meets the requirements of Item 622, except that the conduit is supplied without factory-installed conductors. Make the transition of the HDPE conduit to PVC (or RMC elbow when required) at the bore pit. Provide conduit of the size and schedule as shown on the plans. Do not extend substituted conduit into ground boxes or foundations. Provide PVC or galvanized steel RMC elbows as called for at all ground boxes and foundations.
10. Use two-hole straps when supporting 2 in. and larger conduits. On electrical service poles, properly sized stainless steel or hot dipped galvanized one-hole standoff straps are allowed on the service riser conduit.

B. CONSTRUCTION METHODS

1. Provide and install expansion joint conduit fittings on all structure-mounted conduits at the structure's expansion joints to allow for movement of the conduit. In addition, provide and install expansion joint fittings on all continuous runs of galvanized steel RMC conduit externally exposed on structures such as bridges at maximum intervals of 150 ft. When requested by the project Engineer, supply manufacturer's specification sheet for expansion joint conduit fittings. Repair or replace expansion joint fittings that do not allow for movement at no additional cost to the Department. Provide the method of determining the amount of expansion to the Engineer upon request. Do not use LFMC or LFNC as a substitute for the required expansion conduit fittings.
2. Space all conduit supports at maximum intervals of 5 ft. Install conduit spacers when attaching metal conduit to surface of concrete structures. See "Conduit Mounting Options" on ED(2). Install conduit support within 3 ft. of all enclosures and conduit terminations.
3. Do not attach conduit supports directly to pre-stressed concrete beams except as shown specifically in the plans or as approved by the Engineer.
4. Unless otherwise shown on the plans, jack or bore conduit placed beneath existing roadways, driveways, sidewalks, or after the base or surfacing operation has begun. Backfill and compact the bore pits below the conduit per Item 476 "Jacking, Boring, or Tunneling Pipe or Box" prior to installing conduit or duct cable to prevent bending of the connections.
5. When placing conduit in the sub-grade of new roadways, backfill all trenches with excavated material unless otherwise noted on the plans. When placing conduit in the sub-base of new roadways, backfill all trenches with cement-stabilized base as per requirements of Items 110 "Excavation", 400 "Excavation and Backfill for Structures", 401 "Flowable Backfill", 402 "Trench Excavation Protection", and 403 "Temporary Special Shoring."
6. Provide and place warning tape approximately 10 in. above all trenched conduit as per Item 618.
7. During construction, temporarily cap or plug open ends of all conduit and raceways immediately after installation to prevent entry of dirt, debris and animals. Temporary caps constructed of durable duct tape are allowed. Tightly fix the tape to the conduit opening. Clean out the conduit and prove it clear in accordance with Item 618 prior to installing any conductors.
8. Ensure conduit entry into the top of any enclosure is waterproof by installing conduit sealing hubs or using boxes with threaded bosses. This includes surface mounted safety switches, meter cans, service enclosures, auxiliary enclosures and junction boxes. Grounding bushings on water tight sealing hubs are not required.
9. Fit the ends of all PVC conduit terminations with bushings or bell end fittings. Provide and install a grounding type bushing on all metal conduit terminations.
10. Install a bonding jumper from each grounding bushing to the nearest ground rod, grounding lug, or equipment grounding conductor. Ensure all bonding jumpers are the same size as the equipment grounding conductor. Bonding of conduit used as a casing under roadways for duct cable is not required, if the duct extends the full length through the casing.
11. At all electrical services, install a 6 AWG solid copper grounding electrode conductor.
12. Place conduits entering ground boxes so that the conduit openings are between 3 in. and 6 in. from the bottom of the box. See the ground box detail on sheet ED(4).
13. Seal ends of all conduits with duct seal, expandable foam, or by other methods approved by the Engineer. Seal conduit immediately after completion of conductor installation and pull tests. Do not use duct tape as a permanent conduit sealant. Do not use silicone caulk as a conduit sealant.
14. File smooth the cut ends of all mounting strut and conduit. Before installing, paint the field cut ends of all mounting strut and RMC (threaded or non-threaded) with zinc rich paint (94% or more zinc content) to alleviate overspray. Use zinc rich paint to touch up galvanized material as allowed under Item 445 "Galvanizing." Do not paint non-galvanized material with a zinc rich paint as an alternative for materials required to be galvanized.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

				Traffic Operations Division Standard	
<h2>ELECTRICAL DETAILS CONDUITS & NOTES</h2>					
<h3>ED(1) - 14</h3>					
FILE:	ed1-14.dgn	DN:	CK:	DW:	CK:
© TxDOT	October 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS		0904 00	214	VARIOUS	
		DIST	COUNTY	SHEET NO.	
		AMA	POTTER	61	

ELECTRICAL CONDUCTORS

A. MATERIAL INFORMATION

1. Provide Type XHHW insulated conductors in accordance with Departmental Material Specification (DMS) 11040 "Conductors" and Item 620 "Electrical Conductors." Provide conductors as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies" Item 620. Color code insulated conductors in conformance with the NEC. Identify grounded (neutral) conductors with white insulation. Identify grounding conductors (ground wires) with green insulation or bare conductors. Identify ungrounded (hot) conductors with any color insulation except green, white, or gray. Keep color scheme consistent throughout the wiring system. Identify conductors 6 American Wire Gauge (AWG) and smaller by continuous color jacket. Identify electrical conductors 4 AWG and larger by continuous color jacket or by colored tape. When identifying conductors with colored tape, mark at least 6 in. of the conductor's insulation with half laps of tape.

2. Provide a solid copper 6 AWG grounding electrode conductor to bond the electrical service equipment to the concrete encased grounding electrode or the ground rod at the service location. Connect the grounding electrode conductor to the ground rod with a UL listed connector in accordance with DMS 11040. Connect the grounding electrode conductor to the concrete encased grounding electrode as shown in the plans.

3. Where two or more circuits are present in one conduit or enclosure, permanently identify the conductors of each branch circuit by attaching a non-metallic tag around both circuit conductors at each accessible location. Provide tags with two straps, large enough to indicate circuit number, letter, or other identification as shown in the plans. Print circuit identification on the tag with a permanent marker.

4. Use listed compression or screw type pressure connectors, terminal blocks, or split bolt connectors for splicing as specified in DMS 11040. Use hot melt adhesive tape to fill the gap and seal the ends of heat shrink tubing. Provide UL listed gel-filled insulating splice covers. Splicing materials, insulating materials, breakaway disconnects, splice covers, and fuse holders are subsidiary to various bid items.

B. CONSTRUCTION METHODS

1. Use only a flat, high tensile strength polyester fiber pull tape for pulling conductors through the conduit system. After installing conductors in conduit, perform conductor pull test. If a conductor cannot be freely pulled, make any needed alterations or repairs at no additional cost to the department. Perform insulation resistance tests in accordance with Item 620. Coordinate with the Engineer to witness the tests.

2. Leave 2 ft. minimum, 3 ft. maximum length for each conductor up to the splice in ground boxes. Leave 3 ft. minimum, 4 ft. maximum length of conductor in ground boxes when pulled through with no splice. Leave 1 ft. minimum, 1.5 ft. maximum length of conductor at enclosures, weatherheads and pole bases.

3. Make splices only in junction boxes, ground boxes, pole bases, or electrical enclosures and use only listed compression or screw type pressure connectors, terminal blocks, or split bolt connectors. Insulate splices with heavy wall heat shrink tubing or gel-filled insulating splice covers to provide a watertight seal. Overlap conductor insulation with heat shrink tubing a minimum of 2 in. past both sides of the splice. Where heat shrink tubing may not shrink sufficiently to provide a watertight seal around the individual conductors, prior to heating the tubing, increase the diameter of the conductor insulation using hot melt adhesive tape to provide a watertight seal between the individual conductors and the heat shrink tubing. Ensure the tape extends past the heat shrink tubing. Use hot melt adhesive tape to fill the gap and seal the ends of heat shrink tubing. Heat shrink tubing that appears to have been burned, or overheated, is considered defective and must be replaced.

4. Size and install gel-filled insulating splice covers according to manufacturer's specifications when used in place of heat shrink tubing.

5. Wire nuts with factory applied waterproof sealant may be used for 8 AWG or smaller conductors in above ground junction boxes, but not in pole bases or ground boxes. Install wire nuts in an upright position to prevent the accumulation of water.

6. Support conductors in illumination poles with a J-hook at the top of the pole.

7. When terminating conductors, remove the insulation and jacketing material without nicking the individual strands of the conductor. Conductors with nicked individual conductor strands or removed strands will be considered damaged.

8. Replace conductors and cables that are damaged beyond repair or that fail an insulation resistance test at no additional cost to the department.

9. Do not repair damaged conductors with duct tape, electrical tape, or wire nuts. Use only approved splicing methods.

10. Do not terminate more than one conductor under a single connector, unless the connector is rated for multiple conductors. Do not exceed the pressure connector's listing for maximum number and size of conductors allowed.

11. Install breakaway connectors on conductors bid under Item 620 whenever those conductors pass through a breakaway support device. Follow manufacturer's instructions when terminating conductors to breakaway connectors. Properly torque threaded connections. Proper terminations are critical to the safe operation of breakaway devices. Trim waterproofing boots on breakaway connectors to fit snugly around the conductor to ensure waterproof connection. Only one conductor may enter a single opening in a boot. Provide waterproof boots with the correct number of openings. Leave unused openings factory sealed. Use prequalified breakaway connectors as shown on the MPL.

12. Provide and install a separate stranded equipment grounding conductor (EGC) in all conduits that contain circuit wiring of 50 volts or more. Unless shown elsewhere, size the EGC to be the same size as the largest current carrying conductor contained in the conduit. Ensure all EGCs are bonded together at every accessible location. For traffic signal installations, provide a minimum size 8 AWG EGC. The EGC is paid for under Item 620.

C. TEMPORARY WIRING

1. Install temporary conductors and electrical equipment in accordance with the NEC article "Temporary Installations" and Department standard sheets.

2. Provide a ground fault circuit interrupter (GFCI) for power outlets for portable electrical equipment, power tools, ice machines, ice storage bins and refrigerators located outdoors at grade. GFCI may be any one of the following: molded cord and plug set, receptacle, or circuit breaker type.

3. Use listed wire nuts with factory applied sealant for temporary wiring where approved.

4. Enclose conductor splices within a listed enclosure or ground box, or ensure the splices are more than 10 ft. above grade vertically and more than 5 ft. horizontally from any metal structure. Where installing temporary conductors in areas subject to vehicle traffic or mobile construction equipment, ensure the vertical clearance to ground is at least 18 ft. when measured at the lowest point. Ground messenger wires that support power conductors in conformance with the NEC.

5. Protect and when necessary repair any existing electrical conduits uncovered during the construction process in a timely manner and in conformance with the NEC.

GROUND RODS & GROUNDING ELECTRODES

A. MATERIAL INFORMATION

1. Provide and install a grounding electrode at electrical services. Provide ground rods according to DMS 11040 and the plans. Larger diameter or longer length rods may be called for in some specific locations, see the individual plans sheets. Concrete encased grounding electrodes may be called for in specific locations including electrical service, see individual plan sheets.

B. CONSTRUCTION METHODS

1. Furnish auxiliary ground rods for lightning protection and install in soil, concrete, or both, as called for in the plans. For ground rods installed in concrete, ensure the connection of the conductor to the ground rod is readily accessible for inspection or repairs. For ground rods installed in soil, ensure that the upper end is between 2 to 4 in. below finished grade.

2. Do not place ground rods in the same drilled hole as a timber pole.


3. Install ground rods so the imprinted part number is at the upper end of the rod.

4. Remove all non-conductive coatings such as concrete splatter from the rod at the clamp location.


5. Route all conductors as short and straight as possible for connection to lightning protection ground rods. When a bend is required, ensure a minimum radius bend of four inches for these conductors.

6. Unless otherwise called for in the plans, protect grounding electrode conductors with non-metallic conduit. When protecting grounding electrode conductors with metal conduit, provide and install a grounding type bushing and properly sized bonding jumper on each end of the metal conduit.


7. Written authorization is required before installing a ground rod in a horizontal trench for rocky soil or a solid rock bottom.



**SPLICE OPTION 1
Compression Type**



**SPLICE OPTION 2
Split Bolt Type**



**SPLICE OPTION 3
Listed Screw Type**


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

 Texas Department of Transportation		Traffic Operations Division Standard	
<h2>ELECTRICAL DETAILS CONDUCTORS</h2>			
<h3>ED(3) - 14</h3>			
FILE: ed3-14.dgn	DW: TxDOT	CK: TxDOT	DR: TxDOT
© TxDOT October 2014	CON: 0904	SECT: 00	JOB: 214
REVISIONS	AMA	COUNTY: POTTER	HIGHWAY: VARIOUS
			SHEET NO.: 62

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:




APRON FOR GROUND BOX

- (1) Uniformly space ends of conduits within the ground box. Position ends of conduits so that ground box walls do not interfere with the installation of grounding bushings or bell end fittings.
- (2) Maintain sufficient space between conduits to allow for proper installation of bushing.
- (3) Place aggregate under the box, not in the box. Aggregate should not encroach on the interior volume of the box.
- (4) Install a grounding bushing on the upper end of all RMC terminating in a ground box. Ground RMC elbows when any part of the elbow is less than 18 in. below the bottom of the ground box. Install a PVC bushing or bell end fitting on the upper end of all PVC conduits terminating in a ground box.

GROUND BOX DIMENSIONS	
TYPE	OUTSIDE DIMENSIONS (INCHES) (Width x Length X Depth)
A	12 X 23 X 11
B	12 X 23 X 22
C	16 X 29 X 11
D	16 X 29 X 22
E	12 X 23 X 17

GROUND BOX COVER DIMENSIONS								
TYPE	DIMENSIONS (INCHES)							
	H	I	J	K	L	M	N	P
A, B & E	23 1/4	23	13 3/4	13 1/2	9 7/8	5 1/8	1 3/8	2
C & D	30 1/2	30 1/4	17 1/2	17 1/4	13 1/4	6 3/4	1 3/8	2



GROUND BOX COVER

GROUND BOXES

A. MATERIALS

1. Provide polymer concrete ground boxes measuring 16x30x24 in. (WxLxD) or smaller in accordance with Departmental Material Specification (DMS) 11070 "Ground Boxes" and Item 624 "Ground Boxes."
2. Provide Type A, B, C, D, and E ground boxes as shown in the plans, and as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies," Item 624.
3. Ensure ground box cover is correctly labeled in accordance with DMS 11070.
4. Provide larger ground boxes in accordance with Item 624 and as shown in the plans.

B. CONSTRUCTION METHODS

1. Remove all gravel and dirt from conduit. Cap all conduits prior to placing aggregate and setting ground box. Provide Grade 3 or 4 coarse aggregate as shown on Table 2 of Item 302 "Aggregates for Surface Treatments." Ensure aggregate bed is in place and at least 9 inches deep, prior to setting the ground box. Install ground box on top of aggregate.
2. Cast ground box aprons in place. Reinforcing steel may be field bent. Ensure the depth of concrete for the apron extends from finished grade to the top of the aggregate bed under the box. Ground box aprons, including concrete and reinforcing steel, are subsidiary to ground boxes when called for by descriptive code.
3. Keep bolt holes in the box clear of dirt. Bolt covers down when not working in ground boxes.
4. Install all conduits and elis in a neat and workmanlike manner. Uniformly space conduits so grounding bushings and bell end fittings can easily be installed.
5. Temporarily seal all conduits in the ground box until conductors are installed.
6. Permanently seal conduits immediately after the completion of conductor installation and pull tests. Permanently seal the ends of all conduits with duct seal, expandable foam, or other method as approved. Do not use duct tape as a permanent conduit sealant. Do not use silicone caulk as a sealant.
7. When a ground rod is present in a ground box, bond all equipment grounding conductors together and to the ground rod with listed connectors.
8. When a type B or D ground box is stacked to meet volume requirements, it is allowable to cut an appropriately sized hole for conduit entry in the side wall at least 18 inches below grade.
9. If an existing ground box in the contract has a metal cover, bond the cover to the equipment grounding conductor with a 3 ft. long stranded bonding jumper the same size as the grounding conductor. The bonding jumper is subsidiary to various bid items. Verify existing ground boxes with metal covers are shown on the plans, with notes fully describing the work required.
10. If other ground boxes with metal covers are within the project limits but are not part of the contract, the Engineer may direct the Contractor to bond the metal covers, identifying the specific boxes in writing. This work will be paid for separately.
11. Bond metal ground box covers to the grounding conductor with a tank ground type lug.

				Traffic Operations Division Standard	
<h2>ELECTRICAL DETAILS</h2> <h3>GROUND BOXES</h3>					
<h3>ED(4) - 14</h3>					
FILE:	ed4-14.dgn	DW:	TxDOT	CK:	TxDOT
© TxDOT	October 2014	CONT:	0904	SECT:	00
REVISIONS		JOB:	214	HIGHWAY:	VARIOUS
		DIST:	AMA	COUNTY:	POTTER
				SHEET NO.:	63

ELECTRICAL SERVICES NOTES

1. Provide new materials. Ensure installation and materials comply with the applicable provisions of the National Electrical Code (NEC) and National Electrical Manufacturers Association (NEMA) standards. Ensure material is Underwriters Laboratories (UL) listed. Provide and install electrical service conduits, conductors, disconnects, contactors, circuit breaker panels, and branch circuit breakers as shown on the Electrical Service Data chart in the plans. Faulty fabrication or poor workmanship in material, equipment, or installation is justification for rejection. Where manufacturers provide warranties and guarantees as a customary trade practice, furnish these to the State.
2. Provide electrical services in accordance with Electrical Details standard sheets, Departmental Material Specification (DMS) 11080 "Electrical Services," DMS 11081 "Electrical Services-Type A," DMS 11082 "Electrical Services-Type C," DMS 11083 "Electrical Services-Type D," DMS 11084 "Electrical Services-Type T," DMS 11085 "Electrical Services-Pedestal (PS)," and Item 628 "Electrical Services" of the Standard Specifications. Provide electrical service types A, C, and D, as listed on the Material Producers List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies," Item 628. Provide other service types as detailed on the plans.
3. Provide all work, materials, services, and any incidentals needed to install a complete electrical service as specified in the plans.
4. Coordinate with the Engineer and the utility provider for metering and compliance with utility requirements. Primary line extensions, connection charges, meter charges, and other charges by the utility company to provide power to the location are paid for in accordance with Item 628. Get approval for the costs associated with these charges prior to engaging the utility company to do the work. Consult with the utility provider to determine costs and requirements, and coordinate the work as approved.
5. The enclosure manufacturer will provide Master Lock Type 2 with brass tumblers keyed #2195 for all custom electrical enclosures. Installing Contractor is to provide Master Lock #2195 Type 2 with brass tumblers for "off the shelf" enclosures. Master Lock #2195 keys and locks become property of the State. Unless otherwise approved, do not energize electrical service equipment until locks are installed.
6. Enclosures with external disconnects that de-energize all equipment inside the enclosure do not need a dead front trim. Protect incoming line terminations from incidental contact as required by the NEC.
7. When galvanized is specified for nuts, screws, bolts or miscellaneous hardware, stainless steel may be used.
8. Provide wiring and electrical components rated for 75°C. Provide red, black, and white colored XHHW service entrance conductors of minimum size 6 American Wire Gauge (AWG). Identify size 6 AWG conductors by continuous color jacket. Identify electrical conductors sized 4 AWG and larger by continuous color jacket or by colored tape. Mark at least 6 inches of the conductor's insulation with half laps of colored tape, when identifying conductors. Ensure each service entrance conductor exits through a separately bushed non-metallic opening in the weatherhead. The lengths of the conductors outside the weatherhead are to be 12 inches minimum, 18 inches maximum, or as required by utility.
9. All electrical service conduit and conductors attached to the electrical service including the riser or the elbow below ground are subsidiary to the electrical service. For an underground utility feed, all service conduit and conductors after the elbow, including service conduit and conductors for the utility pole riser when furnished by the Contractor, will be paid for separately.
10. Provide rigid metal conduit (RMC) for all conduits on service, except for the 1/2 in. PVC conduit containing the electrical service grounding electrode conductor. Size the service entrance conduit as shown in the plans. Ensure conduit for branch circuit entry to enclosure is the same size as that shown on the layout sheets for branch circuit conduit. Extend all rigid metal conduits a minimum of 6 inches underground and then couple to the type and schedule of the conduit shown on the layout for that particular branch circuit. Install a grounding bushing on the RMC where it terminates in the service enclosure.
11. Use of liquidtight flexible metal conduit (LFMC) is allowed between the meter and service enclosure when they are mounted 90 to 180 degrees to each other. Size the LFMC the same size as service entrance conduit. LFMC must not exceed 3 feet in length. Strap LFMC within 1 foot of each end. LFMC less than 12 inches in length need not be strapped. Each end of LFMC must have a grounding bushing or be terminated with a grounding fitting. The LFMC must contain a grounded (neutral) conductor. Ensure any bend in LFMC never exceeds 180 degrees. A pull test is required on all installed conductors, with at least six inches of free conductor movement demonstrated to the satisfaction of the Engineer.
12. Ensure all mounting hardware and installation details of services conform to utility company specifications.
13. For all electrical service enclosures listed under Item 628 on the MPL, the UL 508 enclosure manufacturers will prepare and submit a schematic drawing unique to each service. Before shipment to the job site, place the applicable laminated schematic drawings and the laminated plan sheet showing the electrical service data chart used to build the enclosure in the enclosure's data pocket. The installing contractor will copy and laminate the actual project plan sheets detailing all equipment and branch circuits supplied by that service. The laminated plan sheets are to be placed in the service enclosure's document pocket. Reduce 11 in. x 17 in. plan sheets to 8 1/2 in. x 11 in. before laminating. If the installation differs from the plan sheets, the installing contractor is to redline plan sheets before laminating.
14. When providing an "Off The Shelf" Type D or Type T service, provide laminated plan sheets detailing equipment and branch circuits supplied by that service. Reduce 11 in. x 17 in. plan sheets to 8 1/2 in. x 11 in. before laminating. Deliver these drawings before completion of the work to the Engineer, instead of placing in enclosure that has no door pocket.
15. Do not install conduit in the back wall of a service enclosure where it would penetrate the equipment mounting panel inside the enclosure. Provide grounding bushings on all metal conduits, and terminate bonding jumpers to grounding bus. Grounding bushings are not required when the end of the metal conduit is fitted with a conduit sealing hub or threaded boss, such as a meter base hub.

SERVICE ASSEMBLY ENCLOSURE

1. Provide threaded hub for all conduit entries into the top of enclosure.
2. Type galvanized steel (GS) enclosures may be used for Type C panelboards and for Type D and T services that do not use an enclosure mounted photocell or lighting contactor. Provide GS enclosures in accordance with DMS 11080, 11082, 11083, and 11084.
3. Provide aluminum (AL) and stainless steel (SS) enclosures for Types A, C, and D in accordance with DMS 11080, 11081, 11082, 11083, and 11084. Do not paint stainless steel.
4. Provide pedestal service (PS) enclosures in accordance with ED(9) and DMS 11080 and 11085. Do not provide GS pedestal services. If GS is shown in the PS descriptive code, provide an AL enclosure.

MAIN DISCONNECT & BRANCH CIRCUIT BREAKERS

1. Field drill flange-mounted remote operator handle if needed, to ensure handle is lockable in both the "On" and "Off" positions.
2. When the utility company provides a transformer larger than 50 KVA, verify that the available fault current is less than the circuit breaker's ampere interrupting capacity (AIC) rating and provide documentation from the electric utility provider to the Engineer.

PHOTOELECTRIC CONTROL



1. Provide photocell as listed on the MPL. Move, adjust, or shield the photocell from stray or ambient night time light to ensure proper operation. Mount photocell facing north when practical. Mount top of pole photocells as shown on Top Mounted Photocell Detail.

* ELECTRICAL SERVICE DATA												
Elec. Service ID	Plan Sheet Number	Electrical Service Description	Service Conduit #xSize	Service Conductors No./Size	Safety Switch Amps	Main Ckt. Bkr. Pole/Amps	Two-Pole Contractor Amps	Panelbd/ Loadcenter Amp Rating	Branch Circuit ID	Branch Ckt. Bkr. Pole/Amps	Branch Circuit Amps	KVA Load
ADAMS AT 3RD	30	ELC SRV TY D 120/240 060(NS)SS(N)SP(O)	1 1/4"	3/#6	N/A	2P/60	N/A	100	2	30	30	3.6
GEORGIA AT 26TH	35	ELC SRV TY D 120/240 060(NS)SS(E)TS(O)	1 1/4"	3/#6	N/A	2P/60	N/A	100	2	30	30	3.6
WESTERN AT 34TH	40	ELC SRV TY D 120/240 060(NS)SS(E)TS(O)	1 1/4"	3/#6	N/A	2P/60	N/A	100	2	30	30	3.6

* Example only, not for construction. All new electrical services must have electrical service data chart specific to that service as shown in the plans.
 ** Verify service conduit size with utility. Size may change due to utility meter requirements. Ensure conduit size meets the National Electrical Code.

EXPLANATION OF ELECTRICAL SERVICE DESCRIPTIVE CODE

ELEC SERV TY X XXX/XXX XXX (XX) XX (X) XX (X)



TOP MOUNTED PHOTOCELL

Install conduit strap maximum 3 feet from box. 5 foot maximum spacing between straps supporting conduit.

Texas Department of Transportation Traffic Operations Division Standard

ELECTRICAL DETAILS SERVICE NOTES & DATA


ED(5) - 14

FILE: ed5-14.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT October 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904 00	214	VARIOUS	
DIST	COUNTY	SHEET NO.		
AMA	POTTER	64		

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




**SCHEMATIC TYPE A
THREE WIRE**

Red insulation or color code 6" length of Line 1 or Line 2 conductors' insulation with red tape where conductor exits the weatherhead.


White insulation or color code 6" length of neutral conductors' insulation with white tape where conductor exits the weatherhead.

8 Two Photocell viewing windows not shown but required when photocell is listed as enclosure mounted. Windows not required when photocell is listed as pole top mounted.



**SCHEMATIC TYPE C
THREE WIRE**


WIRING LEGEND	
————	Power Wiring
-----	Control Wiring
—N—	Neutral Conductor
—G—	Equipment grounding conductor-always required



**SCHEMATIC TYPE D - CUSTOM
120/240 VOLTS - THREE WIRE**

Red insulation or color code 6" length of Line 1 or Line 2 conductors' insulation with red tape where conductor exits the weatherhead.

White insulation or color code 6" length of neutral conductors' insulation with white tape where conductor exits the weatherhead.



**SCHEMATIC TYPE T
120/240 VOLTS - THREE WIRE**
Galvanized steel-"Buy Off The Shelf" only. When required install photocell top of the pole or on luminaire only, no lighting contractor will be installed.

SCHEMATIC LEGEND	
1	Safety Switch (when required)
2	Meter (when required-verify with electric utility provider)
3	Service Assembly Enclosure
4	Main Disconnect Breaker (See Electrical Service Data)
5	Circuit Breaker, 15 Amp (Control Circuit)
6	Auxiliary Enclosure
7	Control Station ("H-O-A" Switch)
8	Photo Electric Control (enclosure-mounted shown)
9	Lighting Contactor
10	Power Distribution Terminal Blocks
11	Neutral Bus
12	Branch Circuit Breaker (See Electrical Service Data)
13	Separate Circuit Breaker Panelboard
14	Load Center
15	Ground Bus

				Traffic Operations Division Standard	
ELECTRICAL DETAILS SERVICE ENCLOSURE AND NOTES					
ED(6) - 14					
FILE:	ed6-14.dgn	DN:	TxDOT	CK:	TxDOT
© TxDOT	October 2014	CON:	SECT	JOB	HIGHWAY
REVISIONS		0904	00	214	VARIOUS
DIST:	AMA	COUNTY:	POTTER	SHEET NO.:	65

DATE:
FILE:


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

SUPPORT TYPE STEEL POLE (SP) AND STEEL FRAME (SF)

1. Provide steel pole and steel frame supports as per TxDOT Departmental Material Specification (DMS) 11080 "Electrical Services." Mount all equipment and conduit on 12 gauge galvanized steel or stainless steel channel strut, 1 1/2 in. or 1 3/8 in. wide by 1 in. up to 3 3/4 in. deep Unistrut, Kindorf, B-line or equal. Bolt or weld all channel and hardware to vertical members as approved. Do not stack channel. File smooth and paint field cut ends of all channel with zinc-rich paint before installing.
2. Provide poles for overhead service with an eyebolt or similar fitting for attachment of the service drop to the pole in conformance with the electric utility provider's specifications.
3. Provide and install galvanized 3/4 in. x 18 in. x 4 in. (dia. x length x hook length) anchor bolts for underground service supports. Provide and install galvanized 3/4 in. x 56 in. x 4 in. anchor bolts for overhead service supports. Ensure anchor bolts have 3 in. of thread, with 3 1/4 in. to 3 1/2 in. of the exposed anchor bolt projecting above finished foundation. Provide and install leveling nuts for all anchor bolts.
4. Bond one of the anchor bolts to the rebar cage with 6 AWG bare stranded copper conductor. Use listed mechanical connectors rated for embedment in concrete. See Inset B.
5. Furnish and install rigid metallic ellis in all steel pole and steel frame foundations for all conduits entering the service from underground.
6. Use class C concrete for foundations. Ensure reinforcing steel is Grade 60 with 3" of unobstructed concrete cover.
7. Drill and tap steel poles and frames for 1/2 in. X 13 UNC tank ground fitting. For steel pole service supports, provide and install tank ground fitting 4 in. to 6 in. below electrical service enclosure. Provide properly sized hole through the bottom of the enclosure for the service grounding electrode conductor. Ensure electrical service grounding electrode conductor is as short and straight as possible from the enclosure to the tank ground fitting. For steel frame service supports, provide and install tank ground fitting on steel frame post. Install service grounding electrode conductor in a non-metallic conduit or tubing from the enclosure to the steel frame post. Connect electrical service grounding electrode conductor to the tank ground fitting. See steel frame and steel pole details and Inset A for more information. Size service entrance conduit and branch circuit conduit as shown in the plans. For underground conduit runs from the electrical service, extend RMC from the service enclosure to an RMC elbow, and then connect the schedule type and size of conduit shown in the plans. Provide and install grounding bushings where RMC terminates in the enclosure. Grounding bushings are not required when RMC is fitted into a sealing hub or threaded boss.
8. If Steel pole or frame is painted, bond each separate painted piece with a bonding jumper attached to a tapped hole.
9. Provide 1/4" - 20 machine screws for bonding. Do not use sheet metal screws. Remove all non-conductive material at contact points. Terminate bonding jumpers with listed devices. Install minimum size 6 AWG stranded copper bonding jumpers. Make up all threaded bonding connections wrench tight.
10. Avoid contact of the service drop and service entrance conductors with the metal pole to prevent abrasion of the insulated conductors.
11. Shop drawings are not required for service support structure unless specifically stated elsewhere or directed by the Engineer.


White insulation or color code 6" of neutral conductor's insulation with white tape where conductor exits weatherhead.

Red insulation or color code 6" length of Line 1 or Line 2 conductor's insulation with red tape where conductor exits the weatherhead. Conductor slack length, 12" min., 18" max.




WITH SAFETY SWITCH WITHOUT SAFETY SWITCH
SERVICE SUPPORT TYPE SP (O) - OVERHEAD SERVICE


Drill, tap, and thread 1/2" X 13 UNC. Install tank ground fitting, connect electrical service grounding electrode conductor. See Note 7.




FRONT VIEW INSET A INSET B




WITH SAFETY SWITCH HOOKED ANCHOR DETAIL
SERVICE SUPPORT TYPE SP (U) - UNDERGROUND SERVICE



POLE TOP PLATE




BASE PLATE DETAIL




BOTTOM OF POLE

SERVICE SUPPORT TYPE SF & SP



TOP VIEW
SERVICE SUPPORT TY SF (O) & SF (U)



WITH SAFETY SWITCH FRONT VIEW WITHOUT SAFETY SWITCH
SERVICE SUPPORT TYPE SF (U) - UNDERGROUND SERVICE


		Traffic Operations Division Standard	
ELECTRICAL DETAILS SERVICE SUPPORT TYPES SF & SP ED(7)-14			
FILE: ed7-14.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT October 2014	CON: 0904	SECT: 00	JOB: 214
REVISIONS	DIST: AMA	COUNTY: POTTER	SHEET NO.: 66

DATE: DATE TIME
 FILE: DOCUMENT NAME

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TRAFFIC SIGNAL NOTES

1. Do not pass luminaire conductors through the signal controller cabinet.
2. Include an equipment grounding conductor in all conduits throughout the electrical system. Bond all exposed metal parts to the grounding conductor.
3. Provide roadway luminaires, when required, in accordance with the material and construction sections of Item 610, "Roadway Illumination Assemblies," except for performance testing of luminaires. Test installed roadway luminaires for proper operation as a part of the associated traffic signal system test.
4. If internally illuminated street name signs are approved for use, ground the fixture to the pole with a 12 AWG green XHHW conductor.
5. Bond anchor bolts to rebar cage in two locations using #3 bars or 6 AWG stranded copper conductors. Use listed mechanical connectors rated for embedment in concrete. See TxDOT standard TS-FD for further details.
6. Drill and tap signal poles for 1/2 in. X 13 UNC tank ground fitting. Provide and install tank ground fitting 4 in. to 6 in. directly below electrical service enclosure. Provide properly sized hole through the bottom of the enclosure for the service grounding electrode conductor. Connect the electrical service grounding electrode conductor to the tank ground fitting. Ensure electrical service grounding electrode conductor is as short and straight as possible from the enclosure to the tank ground fitting. See Inset A detail for further information. Size service entrance conduit and branch circuit conduit as shown in the plans.
7. Mount electrical service enclosure and meter to signal pole with stainless steel bands. Ensure bands are a minimum width of 3/4 in. Secure enclosures to bands using two-bolt brackets. Install brackets near top and bottom of each enclosure. Install properly sized stainless steel washers on each bolt in the enclosure. Band or drill and tap properly sized stand-off straps to signal pole for attaching conduit.
8. Conduct pull tests and insulation resistance tests on all illumination and power conductors as required in Item 620 "Electrical Conductors" and ED(3). To prevent electronics damage, do not conduct insulation resistance tests on traffic signal cables after termination.
9. Lock all enclosures and bolt down all ground box covers before applying power to the signal installation.
10. Terminate conduits entering the top of enclosures with a conduit-sealing hub or threaded boss such as meter hub. Install a grounding bushing on all metal conduits not connected to conduit-sealing hub or threaded boss. Bond the grounding bushing to the ground bus with a bonding jumper. Seal all conduits entering enclosures with duct seal or expanding foam. Do not use silicone to seal conduit ends.
11. For all conduits, ensure the burial depth is a minimum of 18". Ensure the minimum burial depth for conduit placed under a roadway is 24".




SIGNAL POLE WITH SERVICE

Type I electrical service mounted on signal pole shown as an example. See electrical details, layout sheets, and electrical service data chart for additional details.

SIGNAL CONTROLLER FRONT VIEW

SIGNAL POLE



SIGNAL CONTROLLER SIDE VIEW

See TS-CF standard for conduit and grounding requirements. See layout sheets for ground box locations and any additional conduits that are required.

**ELECTRICAL DETAILS
 TYPICAL TRAFFIC SIGNAL
 SYSTEM DETAILS**
ED(8) - 14


FILE: ed8-14.dgn	DW: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT October 2014	CONT	SECT	JOB	HIGHWAY
REVISIONS	0904	00	214	VARIOUS
DIST	COUNTY	SHEET NO.		
AMA	POTTER	67		

DATE: FILE:

DUCT CABLE & HDPE CONDUIT NOTES


1. Provide duct cable in accordance with Departmental Material Specification (DMS) 11060 "Duct Cable" and Item 622 "Duct Cable." Provide duct cable as listed on the Material Producer List (MPL) on the Department web site under "Roadway Illumination and Electrical Supplies" Item 622.
2. Provide High-Density Polyethylene (HDPE) conduit in accordance with DMS 11060 and Item 618, "Conduit." Provide HDPE as listed on the MPL on the Department web site under "Roadway Illumination and Electrical Supplies," Item 618.
3. Supply duct cable with a minimum 2 in. diameter, unless otherwise shown in the plans. Provide duct cable and HDPE conduit as shown by descriptive code or on the plans. Bend duct cable and HDPE conduit as recommended by the manufacturer, with a minimum bending radius of 26 in. for 2 in. duct. Follow manufacturers' recommendations when handling duct cable and HDPE conduit reels and during installation of duct cable and HDPE conduit.
4. Do not splice conductors within duct cable or HDPE conduit. Couple duct cable and HDPE entering a ground box or foundation to a PVC elbow. When galvanized steel RMC elbows are called for in the plans and any portion of the RMC elbow is buried less than 18" from possible contact, ground the RMC elbow.
5. Furnish and install duct cable with factory installed conductors, sized as shown in the plans and as required by the National Electrical Code (NEC). The NEC contains specific requirements for duct cable in Article, "Nonmetallic Underground Conduit with Conductors: Type NUCC."
6. When conduit casing is called for in the plans, extend duct cable or HDPE conduit through the conduit casing in one continuous length without connection to the casing.
7. Seal the ends of duct cable or HDPE conduit with duct seal, expandable foam, or other approved method after completing the pull tests required by Item 622.
8. Provide minimum cover of 24 in. under roadways, 18 in. in other locations, or as shown on the plans.
9. Furnish and install listed fittings to couple duct cable or HDPE conduit to other types of conduit. Duct cable and HDPE conduit may be field-threaded and spliced with PVC or RMC threaded couplings; connected with listed tie-wrap fittings; connected using listed coupling made of HDPE with stainless steel external banding clamps and locking rings; connected with approved electrofusion conduit couplings; or connected using an approved chemical fusion method using an epoxy or adhesive specifically designed for HDPE couplings and connectors all installed in accordance with their manufacturer's instructions. Do not use PVC glue on HDPE. Do not use water pipe fittings, or connect conduit with heat shrink tubing.

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




DUCT CABLE/HDPE AT GROUND BOX


When the upper end of an RMC EII does not enter the ground box, it may be extended with a SCH-40 PVC conduit nipple and bell end, provided there is a minimum of 18" of cover over all parts of the elbow. If not, a rigid extension and ground bushing is required.




DUCT CABLE / HDPE AT FOUNDATION



DUCT CABLE/HDPE TO PVC



DUCT CABLE/HDPE TO RMC




BORE PIT DETAIL

Texas Department of Transportation				Traffic Operations Division Standard	
ELECTRICAL DETAILS DUCT CABLE/ HDPE CONDUIT					
ED(11)-14					
FILE: ed11-14.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
© TxDOT October 2014	CONT	SECT	JOB	HIGHWAY	
REVISIONS	0904	00	214	VARIOUS	
	DIST	COUNTY		SHEET NO.	
	AMA	POTTER		68	


DATE:
FILE:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.


DATE:
FILE:




THREE-SECTION HEAD
HORIZONTAL OR VERTICAL




FOUR-SECTION HEAD
HORIZONTAL OR VERTICAL



FIVE-SECTION HEAD
HORIZONTAL OR VERTICAL



FIVE-SECTION HEAD
CLUSTER



PEDESTRIAN HYBRID
BEACON

GENERAL NOTES:

1. Backplates are optional for traffic signals and pedestrian hybrid beacons. When backplates are used, a 2-inch wide fluorescent yellow AASHTO Type B_{FL} or C_{FL} retroreflective border conforming to TxDOT DMS-8300 is required. Place on all approaches when used.
2. Signal head and backplate compatibility must be verified by the contractor prior to installation.
3. When using backplates on signal heads, venting is preferred to reduce cyclic vibration stress.
4. When a vented backplate is used, the retroreflective border must not be placed over the louvers.
5. This standard sheet applies to all signal heads with backplates, including but not limited to:
 - Pole mounted
 - Overhead mounted
 - Span wire mounted
 - Mast arm mounted
 - Vertical signal heads
 - Horizontal signal heads
 - Clustered signal heads
 - Pedestrian hybrid beacons

		Traffic Safety Division Standard	
TRAFFIC SIGNAL HEAD WITH BACKPLATE TS-BP-20			
FILE: ts-bp-20.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT June 2020	CONT: 0904	SECT: 00	JOB: 214
REVISIONS	DIST: AMA		COUNTY: POTTER
			SHEET NO.: 69

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with TxDOT policy for projects disturbing less than 1 acre of soil, and not part of a larger common plan of development.

For projects with less than one acre of soil disturbing activity and that have Environmental, Permits, Issues, and Commitments (EPICs) dependent on stormwater controls and water quality measures TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office, Area Office, or electronically.

This SWP3 is consistent with requirements specified in applicable stormwater plans, and the project's environmental permits, issues, and commitments (EPICs).

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

1.2 PROJECT LIMITS:

From: VARIOUS INTERSECTIONS IN AMARILLO: BELL ST AT PLAINS, ARTHUR ST AT 10TH, ROSS ST AT 10TH, GEORGIA ST AT WOLFLIN, To: VIRGINIA AT 45TH, GEORGIA ST AT 58TH

1.3 PROJECT COORDINATES:

BEGIN: (Lat) _____, (Long) _____
 END: (Lat) _____, (Long) _____

1.4 TOTAL PROJECT AREA (Acres): _____

1.5 TOTAL AREA TO BE DISTURBED (Acres): _____

1.6 NATURE OF CONSTRUCTION ACTIVITY:

INSTALL FLASHING YELLOW ARROWS, REWIRE TRAFFIC SIGNAL, REPLACE CONTROLLER CABINET, REPLACE PEDESTRIAN PUSHBUTTONS AND SIGNAL HEADS.

1.7 MAJOR SOIL TYPES:

Soil Type	Description

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

All off-ROW PSLs required by the Contractor are the Contractor's responsibility. The Contractor shall secure all permits required by local, state, federal laws for off-ROW PSLs. The contractor shall provide diagrams, areas of disturbance, acreage, and BMPs for all off-ROW PSLs within one mile of the project.

1.9 CONSTRUCTION ACTIVITIES:

(Use the following list as a starting point when developing the Construction Activity Schedule and Ceasing Record in Attachment 2.3.)

- Mobilization
- Install sediment and erosion controls
- Blade existing topsoil into windrows, prep ROW, clear and grub
- Remove existing pavement
- Grading operations, excavation, and embankment
- Excavate and prepare subgrade for proposed pavement widening
- Remove existing culverts, safety end treatments (SETs)
- Remove existing metal beam guard fence (MBGF), bridge rail
- Install proposed pavement per plans
- Install culverts, culvert extensions, SETs
- Install mow strip, MBGF, bridge rail
- Place flex base
- Rework slopes, grade ditches
- Blade windrowed material back across slopes
- Revegetation of unpaved areas
- Achieve site stabilization and remove sediment and erosion control measures

Other: _____

 Other: _____

 Other: _____

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Discharges from concrete washout activities, runoff from concrete cutting activities, and other concrete related activities
- Other: _____
- Other: _____
- Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody


* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES: TxDOT

- Development of plans and specifications
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Other: Less than 1 acre of disturbed area including PSLs within 1 mile needs no posting on the project.
- Other: Binder needs to be maintained and inspection completed by TxDOT weekly.

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Other: Less than 1 acre of disturbed area including PSLs within 1 mile needs no posting on the project.
- Other: Binder needs to be maintained and inspection completed by TxDOT weekly.



[Signature]
 02/14/2024

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (Less Than 1 Acre)

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6	(SEE PROJECT TITLE SHEET)		70
STATE	STATE DIST.	COUNTY	
TEXAS	AMA	POTTER	
CONT.	SECT.	JOB	HIGHWAY NO.
0904	00	214	VARIOUS

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

2.0 BEST MANAGEMENT PRACTICES (BMPs) AND CONTROLS, INSPECTION, AND MAINTENANCE

The Contractor shall be the responsible party for implementing the BMPs described herein and for complying with the SWP3 for control of erosion and sedimentation during day-to-day operations. The Contractor shall implement changes to this SWP3 approved by TxDOT within the times specified in this SWP3 or the CGP.

2.1 EROSION CONTROL AND SOIL STABILIZATION BMPs:

T / P

- Protection of Existing Vegetation
- Vegetated Buffer Zones
- Soil Retention Blankets
- Geotextiles
- Mulching/ Hydromulching
- Soil Surface Treatments
- Temporary Seeding
- Permanent Planting, Sodding or Seeding
- Biodegradable Erosion Control Logs
- Rock Filter Dams/ Rock Check Dams
- Vertical Tracking
- Interceptor Swale
- Riprap
- Diversion Dike
- Temporary Pipe Slope Drain
- Embankment for Erosion Control
- Paved Flumes
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.2 SEDIMENT CONTROL BMPs:

T / P

- Biodegradable Erosion Control Logs
- Dewatering Controls
- Inlet Protection
- Rock Filter Dams/ Rock Check Dams
- Sandbag Berms
- Sediment Control Fence
- Stabilized Construction Exit
- Floating Turbidity Barrier
- Vegetated Buffer Zones
- Vegetated Filter Strips
- Other: _____
- Other: _____
- Other: _____
- Other: _____

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.3 PERMANENT CONTROLS:

(Coordinate post-construction BMPs with appropriate TxDOT maintenance sections.)

BMPs To Be Left In Place Post Construction:

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.4 OFFSITE VEHICLE TRACKING CONTROLS:

- Excess dirt/mud on road removed daily
- Haul roads dampened for dust control
- Loaded haul trucks to be covered with tarpaulin
- Stabilized construction exit
- Daily street sweeping
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.5 POLLUTION PREVENTION MEASURES:

- Chemical Management
- Concrete and Materials Waste Management
- Debris and Trash Management
- Dust Control
- Sanitary Facilities
- Other: _____
- Other: _____
- Other: _____
- Other: _____

2.6 VEGETATED BUFFER ZONES:

Natural vegetated buffers shall be maintained as feasible to protect adjacent surface waters. If vegetated natural buffer zones are not feasible due to site geometry, the appropriate additional sediment control measures have been incorporated into this SWP3.

Type	Stationing	
	From	To

Refer to the Environmental Layout Sheets/ SWP3 Layout Sheets located in Attachment 1.2 of this SWP3

2.7 ALLOWABLE NON-STORMWATER DISCHARGES:

- Fire hydrant flushings
- Irrigation drainage
- Pavement washwater (where spills or leaks have not occurred, and detergents are not used)
- Potable water sources
- Springs
- Uncontaminated groundwater
- Water used to wash vehicles or control dust
- Other allowable non-stormwater discharges as allowed by TPDES GP TXR150000.

2.8 DEWATERING:


Dewatering discharges of accumulated stormwater, groundwater, and surface water including discharges from dewatering of trenches, excavations, foundations, vaults, and other points of accumulation are prohibited unless managed by appropriate controls to prevent and minimize the offsite discharge of sediment and other pollutants.

2.9 INSPECTIONS:

All disturbed areas and erosion and sediment control devices shall be inspected at least once every seven (7) days. Inspections shall be performed by TxDOT as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.3 of this SWP3 .

2.10 MAINTENANCE:

Control measures shall be properly installed according to specifications. If it is determined that a BMP or control measure is not operating effectively, maintenance must be accomplished as soon as possible and before the next anticipated rain event, but in no case later than 7 calendar days after being able to access the site. Maintenance shall be performed by the Contractor as indicated on the Field Inspection and Maintenance Report Form 2118 and retained in Attachment 2.3 of this SWP3.



Dawood Alani
07/14/2024

STORMWATER POLLUTION PREVENTION PLAN (SWP3) (Less Than 1 Acre)

FED. RD. DIV. NO.	PROJECT NO.		SHEET NO.
6	(SEE PROJECT TITLE SHEET)		71
STATE	STATE DIST.	COUNTY	
TEXAS	AMA	POTTER/RANDALL	
CONT.	SECT.	JOB	HIGHWAY NO.
0904	00	214	VARIOUS

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATES: SITES
 FILES: FILES

I. STORMWATER POLLUTION PREVENTION-CLEAN WATER ACT SECTION 402

TPDES TXR 150000: Stormwater Discharge Permit or Construction General Permit required for projects with 1 or more acres disturbed soil. Projects with any disturbed soil must protect for erosion and sedimentation in accordance with Item 506.

List MS4 Operator(s) that may receive discharges from this project. They may need to be notified prior to construction activities.

City of Amarillo

2. No Action Required **Required Action**

Action No.

1. Comply with Construction General Permit and implement project SWP3's.
2. Less than one acre of disturbed area including any PSLs within 1 mile of the project needs no construction site notice posting on the project. Binder needs to be maintained and inspection completed by TxDOT weekly.
3. Prevent stormwater pollution by controlling erosion and sedimentation in accordance with TPDES Permit TXR 150000.
4. Comply with the City of Amarillo MS4 Permit.

II. WORK IN OR NEAR STREAMS, WATERBODIES AND WETLANDS CLEAN WATER ACT SECTIONS 401 AND 404

USACE Permit required for filling, dredging, excavating or other work in any water bodies, rivers, creeks, streams, wetlands or wet areas.

The Contractor must adhere to all of the terms and conditions associated with the following permit(s):

- No Permit Required**
- Nationwide Permit 14 - PCN not Required (less than 1/10th acre waters or wetlands affected)
- Nationwide Permit 14 - PCN Required (1/10 to <1/2 acre, 1/3 in tidal waters)
- Individual 404 Permit Required
- Other Nationwide Permit Required: NWP# _____

Required Actions: List waters of the US permit applies to, location in project and check Best Management Practices planned to control erosion, sedimentation and post-project TSS.

- 1.
- 2.
- 3.
- 4.

Best Management Practices:

Erosion	Sedimentation	Post-Construction TSS
<input type="checkbox"/> Temporary Vegetation	<input type="checkbox"/> Silt Fence	<input type="checkbox"/> Vegetative Filter Strips
<input type="checkbox"/> Blankets/Matting	<input type="checkbox"/> Rock Berm	<input type="checkbox"/> Retention/Irrigation Systems
<input type="checkbox"/> Mulch	<input type="checkbox"/> Triangular Filter Dike	<input type="checkbox"/> Extended Detention Basin
<input type="checkbox"/> Sodding	<input type="checkbox"/> Sand Bag Berm	<input type="checkbox"/> Constructed Wetlands
<input type="checkbox"/> Interceptor Swale	<input type="checkbox"/> Straw Bale Dike	<input type="checkbox"/> Wet Basin
<input type="checkbox"/> Diversion Dike	<input type="checkbox"/> Brush Berms	<input type="checkbox"/> Erosion Control Compost
<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Erosion Control Compost	<input type="checkbox"/> Mulch Filter Berm and Socks
<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Mulch Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks
<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Compost Filter Berm and Socks	<input type="checkbox"/> Vegetation Lined Ditches
	<input type="checkbox"/> Stone Outlet Sediment Traps	<input type="checkbox"/> Sand Filter Systems
	<input type="checkbox"/> Sediment Basins	<input type="checkbox"/> Grassy Swales

III. CULTURAL RESOURCES

Refer to TxDOT Standard Specifications in the event historical issues or archeological artifacts are found during construction. Upon discovery of archeological artifacts (bones, burnt rock, flint, pottery, etc.) cease work in the immediate area and contact the Engineer immediately.

- No Action Required **Required Action**

Action No.

1. In the event that unanticipated archeological deposits are encountered during construction, work in the immediate area will cease and TxDOT archeological staff will be contacted to initiate post-review discovery procedures.

IV. VEGETATION RESOURCES

Preserve native vegetation to the extent practical. Contractor must adhere to Construction Specification Requirements Specs 162, 164, 192, 193, 506, 730, 751, 752 in order to comply with requirements for invasive species, beneficial landscaping, and tree/brush removal commitments.

- No Action Required **Required Action**

Action No.

1. Comply with Executive Order 13112 on Invasive Species and the intent of the Executive Order Memorandum on Beneficial Landscapes for re-vegetating the project area. The proposed seed mixture (both grasses and forbs) would be in accordance with Item 164, Seeding for Erosion Control in TxDOT's Standard Specifications for the construction of Highways, Streets, and Bridges.

V. FEDERAL LISTED, PROPOSED THREATENED, ENDANGERED SPECIES, CRITICAL HABITAT, STATE LISTED SPECIES, CANDIDATE SPECIES AND MIGRATORY BIRDS.

- No Action Required **Required Action**

Action No.

1. If any species on the Potter County T&E Lists is sighted in the project area during construction, stop construction and notify the Area Engineer.
2. Bird BMP's: a) Do not disturb, destroy, or remove active nests, including ground nesting birds, during the nesting season; b) avoid the removal of unoccupied, inactive nests, as practicable; c) do not collect, capture, relocate, or transport birds, eggs, young, or active nests without a permit.
3. The Migratory Bird Treaty Act of 1918 states that it is unlawful to kill, capture, collect, possess, buy, sell, trade, or transport any migratory bird, nest, young, feather, egg in part or in whole, without a Federal permit issued in accordance within the Act's policies and regulations. In the event that migratory birds are encountered on-site during project construction, adverse impacts on protected birds, active nests, eggs, and/or young would be avoided.

If any of the listed species are observed, cease work in the immediate area, do not disturb species or habitat and contact the Engineer immediately. The work may not remove active nests from bridges and other structures during nesting season of the birds associated with the nests. If caves or sinkholes are discovered, cease work in the immediate area, and contact the Engineer immediately.

LIST OF ABBREVIATIONS

BMP: Best Management Practice	SPCC: Spill Prevention Control and Countermeasure
CGP: Construction General Permit	SW3P: Storm Water Pollution Prevention Plan
DSHS: Texas Department of State Health Services	PCN: Pre-Construction Notification
FHWA: Federal Highway Administration	PSL: Project Specific Location
MOA: Memorandum of Agreement	TCEQ: Texas Commission on Environmental Quality
MOU: Memorandum of Understanding	TPDES: Texas Pollutant Discharge Elimination System
MS4: Municipal Separate Stormwater Sewer System	TPWD: Texas Parks and Wildlife Department
MBTA: Migratory Bird Treaty Act	TxDOT: Texas Department of Transportation
NOT: Notice of Termination	T&E: Threatened and Endangered Species
NMP: Nationwide Permit	USACE: U.S. Army Corps of Engineers
NOI: Notice of Intent	USFWS: U.S. Fish and Wildlife Service

VI. HAZARDOUS MATERIALS OR CONTAMINATION ISSUES

General (applies to all projects):

Comply with the Hazard Communication Act (the Act) for personnel who will be working with hazardous materials by conducting safety meetings prior to beginning construction and making workers aware of potential hazards in the workplace. Ensure that all workers are provided with personal protective equipment appropriate for any hazardous materials used. Obtain and keep on-site Material Safety Data Sheets (MSDS) for all hazardous products used on the project, which may include, but are not limited to the following categories: Paints, acids, solvents, asphalt products, chemical additives, fuels and concrete curing compounds or additives. Provide protected storage, off bare ground and covered, for products which may be hazardous. Maintain product labelling as required by the Act. Maintain an adequate supply of on-site spill response materials, as indicated in the MSDS. In the event of a spill, take actions to mitigate the spill as indicated in the MSDS, in accordance with safe work practices, and contact the District Spill Coordinator immediately. The Contractor shall be responsible for the proper containment and cleanup of all product spills.

Contact the Engineer if any of the following are detected:

- * Dead or distressed vegetation (not identified as normal)
- * Trash piles, drums, canister, barrels, etc.
- * Undesirable smells or odors
- * Evidence of leaching or seepage of substances

Does the project involve any bridge class structure rehabilitation or replacements (bridge class structures not including box culverts)?

- Yes No

If "No", then no further action is required.

If "Yes", then TxDOT is responsible for completing asbestos assessment/inspection.

Are the results of the asbestos inspection positive (is asbestos present)?

- Yes No

If "Yes", then TxDOT must retain a DSHS licensed asbestos consultant to assist with the notification, develop abatement/mitigation procedures, and perform management activities as necessary. The notification form to DSHS must be postmarked at least 15 working days prior to scheduled demolition.

If "No", then TxDOT is still required to notify DSHS 15 working days prior to any scheduled demolition.

In either case, the Contractor is responsible for providing the date(s) for abatement activities and/or demolition with careful coordination between the Engineer and asbestos consultant in order to minimize construction delays and subsequent claims.

Any other evidence indicating possible hazardous materials or contamination discovered on site. Hazardous Materials or Contamination Issues Specific to this Project:

- No Action Required** Required Action


Action No.

VII. OTHER ENVIRONMENTAL ISSUES


(includes regional issues such as Edwards Aquifer District, etc.)

- No Action Required Required Action


Action No.

		Design Division Standard	
ENVIRONMENTAL PERMITS, ISSUES AND COMMITMENTS			
E.P.I.C.			
FILE: epic.dgn	REVISED: February 2015	CONT: 0904	SECT: 00
JOB: 214	HIGHWAY: VARIOUS	DIST: AMA	COUNTY: POTTER
		SHEET NO. 72	


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




PLAN VIEW



PLAN VIEW




PLAN VIEW



SECTION A-A

EROSION CONTROL LOG DAM


CL-D



SECTION B-B

EROSION CONTROL LOG AT BACK OF CURB


CL-BOC



SECTION C-C


EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY

CL-ROW



DIAMETER MEASUREMENTS OF EROSION CONTROL LOGS SPECIFIED IN PLANS

- LEGEND**
- CL-D EROSION CONTROL LOG DAM
 - CL-BOC EROSION CONTROL LOG AT BACK OF CURB
 - CL-ROW EROSION CONTROL LOG AT EDGE OF RIGHT-OF-WAY
 - CL-SST EROSION CONTROL LOGS ON SLOPES STAKE AND TRENCHING ANCHORING
 - CL-SSL EROSION CONTROL LOGS ON SLOPES STAKE AND LASHING ANCHORING
 - CL-DI EROSION CONTROL LOG AT DROP INLET
 - CL-CI EROSION CONTROL LOG AT CURB INLET
 - CL-GI EROSION CONTROL LOG AT CURB & GRATE INLET



REBAR STAKE DETAIL

SEDIMENT BASIN & TRAP USAGE GUIDELINES

An erosion control log sediment trap may be used to filter sediment out of runoff draining from an unstabilized area.

Log Traps: The drainage area for a sediment trap should not exceed 5 acres. The trap capacity should be 1800 CF/Acre (0.5" over the drainage area).

Control logs should be placed in the following locations:

1. Within drainage ditches spaced as needed or min. 500' on center
2. Immediately preceding ditch inlets or drain inlets
3. Just before the drainage enters a water course
4. Just before the drainage leaves the right of way
5. Just before the drainage leaves the construction limits where drainage flows away from the project.

The logs should be cleaned when the sediment has accumulated to a depth of 1/2 the log diameter.

Cleaning and removal of accumulated sediment deposits is incidental and will not be paid for separately.

GENERAL NOTES:

1. EROSION CONTROL LOGS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, OR AS DIRECTED BY THE ENGINEER.
2. LENGTHS OF EROSION CONTROL LOGS SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND AS REQUIRED FOR THE PURPOSE INTENDED.
3. UNLESS OTHERWISE DIRECTED, USE BIODEGRADABLE OR PHOTODEGRADABLE CONTAINMENT MESH ONLY WHERE LOG WILL REMAIN IN PLACE AS PART OF A VEGETATIVE SYSTEM. FOR TEMPORARY INSTALLATIONS, USE RECYCLABLE CONTAINMENT MESH.
4. FILL LOGS WITH SUFFICIENT FILTER MATERIAL TO ACHIEVE THE MINIMUM COMPACTED DIAMETER SPECIFIED IN THE PLANS WITHOUT EXCESSIVE DEFORMATION.
5. STAKES SHALL BE 2" X 2" WOOD OR #3 REBAR, 2'-4' LONG, EMBEDDED SUCH THAT 2" PROTRUDES ABOVE LOG, OR AS DIRECTED BY THE ENGINEER.
6. DO NOT PLACE STAKES THROUGH CONTAINMENT MESH.
7. COMPOST CRADLE MATERIAL IS INCIDENTAL & WILL NOT BE PAID FOR SEPARATELY.
8. SANDBAGS USED AS ANCHORS SHALL BE PLACED ON TOP OF LOGS & SHALL BE OF SUFFICIENT SIZE TO HOLD LOGS IN PLACE.
9. TURN THE ENDS OF EACH ROW OF LOGS UPSLOPE TO PREVENT RUNOFF FROM FLOWING AROUND THE LOG.
10. FOR HEAVY RUNOFF EVENTS, ADDITIONAL UPSTREAM STAKES MAY BE NECESSARY TO KEEP LOG FROM FOLDING IN ON ITSELF.


SHEET 1 OF 3

		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC(9) - 16			
FILE: ec916	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CONT	SECT	JOB
REVISIONS	0904	00	214
	DIST	COUNTY	SHEET NO.
	AMA	POTTER	73

DATE: 3/15/16
FILE: 5/15/16


DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
 FILE:
 SHEETS:
 FILES:



**EROSION CONTROL LOGS ON SLOPES
STAKE AND TRENCHING ANCHORING**


CL-SST



END SECTION RAP DETAIL


EROSION CONTROL LOG SPACING TABLE				
SLOPE	LOG DIAMETER			
	6"	8"	12"	18"
1:1 OR STEEPER	5'	10'	15'	20'
2:1	10'	20'	30'	40'
3:1	15'	30'	45'	60'
4:1 OR FLATTER	20'	40'	60'	80'

* ADJUSTMENTS CAN BE MADE FOR SOIL TYPE:
SOFT, LOAMY SOILS-ADJUST ROWS CLOSER TOGETHER;
HARD, ROCKY SOILS- ADJUST ROWS FARTHER APART




**EROSION CONTROL LOGS ON SLOPES
STAKE AND LASHING ANCHORING**

CL-SSL




STAKE AND TRENCHING ANCHORING DETAIL

CL-SST




NOTE: COMPACT EXCAVATED SOIL TO PREVENT UNDERCUTTING.




STAKE AND LASHING ANCHORING DETAIL

CL-SSL



TRENCH DEPTH TABLE	
LOG DIAMETER	DEPTH
6"	2"
8"	3"
12"	4"
18"	5"




STAKE NOTCH DETAIL

SHEET 2 OF 3


		Design Division Standard	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16			
FILE: ec116	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CONT SECT	JOB	HIGHWAY
REVISIONS	0904 00	214	VARIOUS
	DIST	COUNTY	SHEET NO.
	AMA	POTTER	74

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.




EROSION CONTROL LOG AT DROP INLET

CL-DI



EROSION CONTROL LOG AT CURB INLET


CL-CI



EROSION CONTROL LOG AT CURB INLET


CL-CI

NOTE:
EROSION CONTROL LOGS USED AT CURB INLETS SHOULD ONLY BE USED IF THEY WILL NOT IMPEDE TRAFFIC OR FLOOD THE ROADWAY OR WHEN THE STORM SEWER SYSTEM IS NOT FULLY FUNCTIONAL.



EROSION CONTROL LOG AT CURB & GRADE INLET

CL-GI



SANDBAG DETAIL

SHEET 3 OF 3

		<i>Design Division Standard</i>	
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES EROSION CONTROL LOG EC (9) - 16			
FILE: ec916	DN: TxDOT	CK: KM	DW: LS/PT
© TxDOT: JULY 2016	CONT SECT	JOB	HIGHWAY
REVISIONS	0904 04	214	VARIOUS
DIST	COUNTY	SHEET NO.	
AMA	POTTER	75	

DATE: 5/15/16
FILE: 5/15/16